



FCC RADIO TEST REPORT

FCC ID : A4RG020D
Equipment : Smartphone
Model name : G020D
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA 94043, USA
Standard : FCC Part 15 Subpart E §15.407

The product was completed on Dec. 21, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	5
1.3 Modification of EUT	6
1.4 Testing Location	7
1.5 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 Test Result	12
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	12
3.2 Maximum Conducted Output Power Measurement	15
3.3 Power Spectral Density Measurement	16
3.4 Unwanted Emissions Measurement.....	19
3.5 AC Conducted Emission Measurement.....	25
3.6 Automatically Discontinue Transmission	27
3.7 Antenna Requirements.....	29
4 List of Measuring Equipment.....	30
5 Uncertainty of Evaluation.....	32
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR891147-01F	01	Initial issue of report	Dec. 26, 2018
FR891147-01F	02	Add test data.	Jan. 23, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403 (i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407 (a)	Maximum Conducted Output Power	Pass	-
3.3	15.407 (a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	Under limit 4.23 dB at 35.130 MHz
3.5	15.207	AC Conducted Emission	Pass	Under limit 12.48 dB at 0.168 MHz
3.6	15.407 (c)	Automatically Discontinue Transmission	Pass	-
3.7	15.203 & 15.407 (a)	Antenna Requirement	Pass	-

Reviewed by: Wii Chang

Report Producer: Natasha Hsieh

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Model Name	G020D
Sample 1	The device with 1st battery
Sample 2	The device with 2nd battery
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/NFC/GNSS WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	<5745 MHz ~ 5825 MHz> <Ant. 1> 802.11a : 17.43 dBm / 0.0553 W 802.11n HT20 : 17.37 dBm / 0.0546 W 802.11n HT40 : 17.46 dBm / 0.0557 W 802.11ac VHT20: 17.36 dBm / 0.0545 W 802.11ac VHT40: 17.42 dBm / 0.0552 W 802.11ac VHT80: 16.56 dBm / 0.0453 W <Ant. 2> 802.11a : 17.49 dBm / 0.0561 W 802.11n HT20 : 17.49 dBm / 0.0561 W 802.11n HT40 : 17.44 dBm / 0.0555 W 802.11ac VHT20: 17.48 dBm / 0.0560 W 802.11ac VHT40: 17.38 dBm / 0.0547 W 802.11ac VHT80: 17.04 dBm / 0.0506 W MIMO <Ant. 1 + 2> 802.11a : 20.45 dBm / 0.1109 W 802.11n HT20 : 20.45 dBm / 0.1109 W 802.11n HT40 : 20.47 dBm / 0.1114 W 802.11ac VHT20: 20.44 dBm / 0.1107 W 802.11ac VHT40: 20.41 dBm / 0.1099 W 802.11ac VHT80: 19.92 dBm / 0.0982 W

Standards-related Product Specification			
99% Occupied Bandwidth	MIMO<Ant. 1> 802.11a : 16.75 MHz 802.11n HT20 : 17.95 MHz 802.11n HT40 : 36.70 MHz 802.11ac VHT80 : 76.44 MHz		
	MIMO<Ant. 2> 802.11a : 16.80 MHz 802.11n HT20 : 17.90 MHz 802.11n HT40 : 36.60 MHz 802.11ac VHT80 : 76.68 MHz		
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)		
Antenna Type / Gain	<Ant. 1> : PIFA Antenna with gain -3.00 dBi <Ant. 2> : PIFA Antenna with gain -2.20 dBi		
Antenna Function Description		Ant. 1	Ant. 2
	802.11 a/n/ac	V	V
	802.11 n/ac MIMO	V	V

Remark: MIMO Ant. 1+2 is a calculated result from sum of the power MIMO Ant. 1 and MIMO Ant. 2.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH12-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X Plane for Sample 1 with Adapter 1 and Sample 1 with Adapter 2, and Z Plane for Sample 2 with Adapter 2) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

MIMO Mode


Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN (5GHz) Link + GPS Rx + Earphone + USB Type C Cable 2 (Charging form Adapter 1) + Battery<10% for Sample 1
Remark: For Radiated Test Cases, the tests were performed with USB Type C Cable 1.	


Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emissions Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony	SBH20	PY7-RD0010	N/A	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
5.	Notebook	DELL	P20G	FCC DoC/ Contains FCC ID: QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.




Minimum 6dB Bandwidth




Date: 15.NOV.2018 11:03:39

Maximum 26dB Bandwidth



Date: 15.NOV.2018 14:27:42



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW $\geq$ 1 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{\text{ANT}})$ dB.



With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{\text{ANT}})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{\text{ANT}})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{\text{ANT}}^{\text{th}}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.



3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz


- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.




2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C and D.

3.4.7 Duty Cycle

Please refer to Appendix E.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

EUT is verified this characteristic during the function check of normal sample associated with an access point:

- A. Information start: make EUT supply information to the access point.
- B. Information stop: stop supplying information to the access point.


While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

- C. Information start: make EUT supply information to the access point again.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



5745MHz



Note : The control / signalling information during the period B is precluded.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

Directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain;

The EUT supports CDD mode.

For power, the directional gain G_{ANT} is set equal to the antenna having the highest gain, i.e., F)2)f)i).

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG for Power	DG for PSD	Power Limit Reduction	PSD Limit Reduction
	Ant. 1 (dBi)	Ant. 2 (dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	-3.00	-2.20	-2.20	0.42	0.00	0.00

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1132003	N/A	Aug. 16, 2018	Oct. 04, 2018~ Dec. 21, 2018	Aug. 15, 2019	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 16, 2018	Oct. 04, 2018~ Dec. 21, 2018	Aug. 15, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jun. 14, 2018	Oct. 04, 2018~ Dec. 21, 2018	Jun. 13, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	100895	9kHz~30GHz	Apr. 20, 2018	Oct. 04, 2018~ Dec. 21, 2018	Apr. 19, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Oct. 04, 2018~ Dec. 21, 2018	Feb. 28, 2019	Conducted (TH05-HY)
Hygrometer	Testo	DTM-303A	TP157075	N/A	Mar. 06, 2018	Oct. 04, 2018~ Dec. 21, 2018	Mar. 05, 2019	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY84209521	1GHz~26GHz	Dec. 01, 2017	Oct. 04, 2018~ Nov. 29, 2018	Nov. 30, 2018	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY84209521	1GHz~26GHz	Nov. 30, 2018	Nov. 30, 2018~ Dec. 21, 2018	Nov. 29, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 04, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Dec. 04, 2018	Nov. 11, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Dec. 04, 2018	Nov. 13, 2019	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Dec. 04, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Test Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Dec. 04, 2018	N/A	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Dec. 04, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 06, 2018	Dec. 04, 2018	Mar. 05, 2019	Conduction (CO05-HY)
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	Mar. 29, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 28, 2019	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 13, 2018	Nov. 30, 2018~ Dec. 17, 2018	Oct. 12, 2019	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 19, 2018	Nov. 30, 2018~ Dec. 17, 2018	Oct. 18, 2019	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	May 08, 2018	Nov. 30, 2018~ Dec. 17, 2018	May 07, 2019	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 25, 2017	Nov. 30, 2018~ Dec. 17, 2018	Dec. 24, 2018	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 15, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 14, 2019	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 26, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 25, 2019	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 15, 2018	Nov. 30, 2018~ Dec. 17, 2018	Jan. 14, 2019	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Apr. 17, 2018	Nov. 30, 2018~ Dec. 17, 2018	Apr. 16, 2019	Radiation (03CH12-HY)
Preamplifier	MITEQ	TTA1840-35-HG	1864481	18GHz ~ 40GHz	Aug. 24, 2018	Nov. 30, 2018~ Dec. 17, 2018	Aug. 23, 2019	Radiation (03CH12-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECEPEL	DTM-303B	TP161243	N/A	May 12, 2018	Nov. 30, 2018~ Dec. 17, 2018	May 11, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30M-18G	Mar. 14, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 13, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Oct. 16, 2018	Nov. 30, 2018~ Dec. 17, 2018	Oct. 15, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Oct. 16, 2018	Nov. 30, 2018~ Dec. 17, 2018	Oct. 15, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-1 2SS	SN2	1.2GHz Low Pass	Mar. 21, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 20, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN2	3GHz High Pass	Mar. 21, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 20, 2019	Radiation (03CH12-HY)
Filter	Woken	WHKX8-5272. 5-6750-18000 -40ST	SN2	6.75G Highpass	Mar. 21, 2018	Nov. 30, 2018~ Dec. 17, 2018	Mar. 20, 2019	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Nov. 30, 2018~ Dec. 17, 2018	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Nov. 30, 2018~ Dec. 17, 2018	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Nov. 30, 2018~ Dec. 17, 2018	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Nov. 30, 2018~ Dec. 17, 2018	N/A	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.20
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.10
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.70
---	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Kai Liao	Temperature:	21~25	°C
Test Date:	2018/10/4 ~2018/11/15	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	2	149	5745	16.75	16.75	24.80	25.20	15.10	15.35	0.5	Pass
11a	6Mbps	2	157	5785	16.75	16.70	24.90	25.15	15.15	15.15	0.5	Pass
11a	6Mbps	2	165	5825	16.70	16.80	25.10	25.20	15.10	15.10	0.5	Pass
HT20	MCS0	2	149	5745	17.90	17.90	25.60	25.80	15.10	15.45	0.5	Pass
HT20	MCS0	2	157	5785	17.90	17.90	25.75	25.55	15.95	15.95	0.5	Pass
HT20	MCS0	2	165	5825	17.95	17.90	25.95	26.00	15.15	15.70	0.5	Pass
HT40	MCS0	2	151	5755	36.70	36.60	41.76	41.85	35.10	35.19	0.5	Pass
HT40	MCS0	2	159	5795	36.70	36.60	41.76	41.94	35.37	35.19	0.5	Pass
VHT80	MCS0	2	155	5775	76.44	76.68	82.88	83.20	75.20	75.20	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.08	0.08	17.08	17.49		30.00	30.00	-3.00	-2.20	Pass
11a	6Mbps	1	157	5785	0.08	0.08	17.43	17.19		30.00	30.00	-3.00	-2.20	Pass
11a	6Mbps	1	165	5825	0.08	0.08	17.42	17.17		30.00	30.00	-3.00	-2.20	Pass
HT20	MCS0	1	149	5745	0.09	0.09	17.03	17.49		30.00	30.00	-3.00	-2.20	Pass
HT20	MCS0	1	157	5785	0.09	0.09	17.37	17.06		30.00	30.00	-3.00	-2.20	Pass
HT20	MCS0	1	165	5825	0.09	0.09	17.36	16.97		30.00	30.00	-3.00	-2.20	Pass
HT40	MCS0	1	151	5755	0.18	0.18	17.17	17.44		30.00	30.00	-3.00	-2.20	Pass
HT40	MCS0	1	159	5795	0.18	0.18	17.46	16.65		30.00	30.00	-3.00	-2.20	Pass
VHT20	MCS0	1	149	5745	0.09	0.09	16.98	17.48		30.00	30.00	-3.00	-2.20	Pass
VHT20	MCS0	1	157	5785	0.09	0.09	17.36	16.69		30.00	30.00	-3.00	-2.20	Pass
VHT20	MCS0	1	165	5825	0.09	0.09	17.35	16.74		30.00	30.00	-3.00	-2.20	Pass
VHT40	MCS0	1	151	5755	0.18	0.18	17.14	17.38		30.00	30.00	-3.00	-2.20	Pass
VHT40	MCS0	1	159	5795	0.18	0.18	17.42	16.61		30.00	30.00	-3.00	-2.20	Pass
VHT80	MCS0	1	155	5775	0.33	0.33	16.56	17.04		30.00	30.00	-3.00	-2.20	Pass
11a	6Mbps	2	149	5745	0.08	0.08	17.37	17.50	20.45	30.00		-2.20		Pass
11a	6Mbps	2	157	5785	0.08	0.08	17.49	17.29	20.41	30.00		-2.20		Pass
11a	6Mbps	2	165	5825	0.08	0.08	17.48	17.24	20.38	30.00		-2.20		Pass
HT20	MCS0	2	149	5745	0.09	0.09	17.37	17.50	20.45	30.00		-2.20		Pass
HT20	MCS0	2	157	5785	0.09	0.09	17.49	17.16	20.34	30.00		-2.20		Pass
HT20	MCS0	2	165	5825	0.09	0.09	17.44	16.99	20.23	30.00		-2.20		Pass
HT40	MCS0	2	151	5755	0.18	0.18	17.42	17.49	20.47	30.00		-2.20		Pass
HT40	MCS0	2	159	5795	0.18	0.18	17.48	16.98	20.25	30.00		-2.20		Pass
VHT20	MCS0	2	149	5745	0.09	0.09	17.36	17.50	20.44	30.00		-2.20		Pass
VHT20	MCS0	2	157	5785	0.09	0.09	17.49	17.12	20.32	30.00		-2.20		Pass
VHT20	MCS0	2	165	5825	0.09	0.09	17.43	16.97	20.22	30.00		-2.20		Pass
VHT40	MCS0	2	151	5755	0.16	0.16	17.32	17.47	20.41	30.00		-2.20		Pass
VHT40	MCS0	2	159	5795	0.16	0.16	17.50	16.90	20.22	30.00		-2.20		Pass
VHT80	MCS0	2	155	5775	0.33	0.33	16.67	17.13	19.92	30.00		-2.20		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	2	149	5745	0.08	0.08	2.22	3.82	4.26	7.27	30.00	0.42	Pass			
11a	6Mbps	2	157	5785	0.08	0.08	2.22	4.27	3.82	7.28	30.00	0.42	Pass			
11a	6Mbps	2	165	5825	0.08	0.08	2.22	4.33	3.78	7.34	30.00	0.42	Pass			
HT20	MCS0	2	149	5745	0.09	0.09	2.22	3.52	3.81	6.82	30.00	0.42	Pass			
HT20	MCS0	2	157	5785	0.09	0.09	2.22	3.95	3.37	6.96	30.00	0.42	Pass			
HT20	MCS0	2	165	5825	0.09	0.09	2.22	3.82	3.37	6.83	30.00	0.42	Pass			
HT40	MCS0	2	151	5755	0.18	0.18	2.22	0.84	1.10	4.11	30.00	0.42	Pass			
HT40	MCS0	2	159	5795	0.18	0.18	2.22	0.80	0.43	3.81	30.00	0.42	Pass			
VHT80	MCS0	2	155	5775	0.33	0.33	2.22	-2.42	-1.77	1.24	30.00	0.42	Pass			

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Rick Lin	Temperature :	23~25°C
		Relative Humidity :	55~58%

EUT Information

Report NO : 891147-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.168000	---	37.84	55.06	17.22	L1	OFF	19.5
0.168000	52.58	---	65.06	12.48	L1	OFF	19.5
0.174750	---	32.56	54.73	22.17	L1	OFF	19.5
0.174750	45.39	---	64.73	19.34	L1	OFF	19.5
0.179250	---	31.67	54.52	22.85	L1	OFF	19.5
0.179250	44.53	---	64.52	19.99	L1	OFF	19.5
0.183750	---	29.66	54.31	24.65	L1	OFF	19.5
0.183750	41.77	---	64.31	22.54	L1	OFF	19.5
0.188250	---	29.38	54.11	24.73	L1	OFF	19.5
0.188250	40.38	---	64.11	23.73	L1	OFF	19.5
0.258000	---	27.86	51.50	23.64	L1	OFF	19.5
0.258000	37.80	---	61.50	23.70	L1	OFF	19.5
0.264750	---	26.56	51.28	24.72	L1	OFF	19.5
0.264750	35.95	---	61.28	25.33	L1	OFF	19.5
0.271500	---	26.90	51.07	24.17	L1	OFF	19.5
0.271500	36.96	---	61.07	24.11	L1	OFF	19.5
0.357000	---	25.18	48.80	23.62	L1	OFF	19.5
0.357000	34.07	---	58.80	24.73	L1	OFF	19.5
0.435750	---	24.58	47.14	22.56	L1	OFF	19.5
0.435750	30.69	---	57.14	26.45	L1	OFF	19.5
0.514500	---	22.87	46.00	23.13	L1	OFF	19.5

0.514500	25.31	---	56.00	30.69	L1	OFF	19.5
0.636000	---	27.55	46.00	18.45	L1	OFF	19.6
0.636000	38.32	---	56.00	17.68	L1	OFF	19.6
0.696750	---	27.46	46.00	18.54	L1	OFF	19.6
0.696750	37.95	---	56.00	18.05	L1	OFF	19.6

EUT Information

Report NO : 891147-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	34.05	55.88	21.83	N	OFF	19.5
0.152250	51.10	---	65.88	14.78	N	OFF	19.5
0.156750	---	31.62	55.63	24.01	N	OFF	19.5
0.156750	49.72	---	65.63	15.91	N	OFF	19.5
0.161250	---	30.49	55.40	24.91	N	OFF	19.5
0.161250	48.39	---	65.40	17.01	N	OFF	19.5
0.217500	---	34.76	52.91	18.15	N	OFF	19.5
0.217500	47.83	---	62.91	15.08	N	OFF	19.5
0.233250	---	29.41	52.33	22.92	N	OFF	19.5
0.233250	38.56	---	62.33	23.77	N	OFF	19.5
0.289500	---	30.21	50.54	20.33	N	OFF	19.5
0.289500	42.60	---	60.54	17.94	N	OFF	19.5
0.363750	---	27.34	48.64	21.30	N	OFF	19.5
0.363750	37.87	---	58.64	20.77	N	OFF	19.5
0.552750	---	25.61	46.00	20.39	N	OFF	19.5
0.552750	37.10	---	56.00	18.90	N	OFF	19.5
0.575250	---	32.33	46.00	13.67	N	OFF	19.5
0.575250	41.07	---	56.00	14.93	N	OFF	19.5
0.651750	---	26.42	46.00	19.58	N	OFF	19.6
0.651750	36.83	---	56.00	19.17	N	OFF	19.6



Appendix C. Radiated Spurious Emission

Test Engineer :	Jack Cheng, Lance Chiang, and Peter Liao	Temperature :	22~24°C
		Relative Humidity :	52~60%

<For Sample 1>

<Adapter 1>

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5650	54.13	-14.07	68.2	43.19	31.7	10.46	31.22	115	114	P	H
		5700	56.94	-48.26	105.2	45.69	32	10.5	31.25	115	114	P	H
		5719.8	70.02	-40.72	110.74	58.72	32.04	10.52	31.26	115	114	P	H
		5724.6	77.71	-43.58	121.29	66.4	32.05	10.52	31.26	115	114	P	H
	*	5745	114.65	-	-	103.29	32.09	10.54	31.27	115	114	P	H
	*	5745	102.67	-	-	91.31	32.09	10.54	31.27	115	114	A	H
													H
													H
		5624.6	53.71	-14.49	68.2	42.73	31.75	10.44	31.21	290	71	P	V
		5697.8	55.81	-47.77	103.58	44.57	31.99	10.5	31.25	290	71	P	V
		5719.6	65.74	-44.95	110.69	54.44	32.04	10.52	31.26	290	71	P	V
		5724.6	74.36	-46.93	121.29	63.05	32.05	10.52	31.26	290	71	P	V
	*	5745	112.11	-	-	100.75	32.09	10.54	31.27	290	71	P	V
	*	5745	99.82	-	-	88.46	32.09	10.54	31.27	290	71	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5624.8	53.51	-14.69	68.2	42.53	31.75	10.44	31.21	100	115	P	H
		5698.6	53.46	-50.71	104.17	42.22	31.99	10.5	31.25	100	115	P	H
		5717.4	54.31	-55.76	110.07	43.03	32.03	10.51	31.26	100	115	P	H
		5724.6	54.02	-67.27	121.29	42.71	32.05	10.52	31.26	100	115	P	H
	*	5785	111.17	-	-	99.72	32.17	10.57	31.29	100	115	P	H
	*	5785	98.47	-	-	87.02	32.17	10.57	31.29	100	115	A	H
		5851.8	53.7	-64.4	118.1	42.1	32.3	10.62	31.32	100	115	P	H
		5865	54.34	-53.66	108	42.71	32.33	10.63	31.33	100	115	P	H
		5899.6	53.45	-33.51	86.96	41.74	32.4	10.65	31.34	100	115	P	H
		5944.6	54.22	-13.98	68.2	42.32	32.58	10.69	31.37	100	115	P	H
													H
													H
		5605.2	53.47	-14.73	68.2	42.47	31.79	10.42	31.21	334	70	P	V
		5687.6	53.8	-42.25	96.05	42.63	31.93	10.49	31.25	334	70	P	V
		5716.8	54.57	-55.34	109.91	43.29	32.03	10.51	31.26	334	70	P	V
		5721.8	54.69	-60.21	114.9	43.39	32.04	10.52	31.26	334	70	P	V
	*	5785	112.05	-	-	100.6	32.17	10.57	31.29	334	70	P	V
	*	5785	99.47	-	-	88.02	32.17	10.57	31.29	334	70	A	V
		5851.6	53.8	-64.75	118.55	42.2	32.3	10.62	31.32	334	70	P	V
		5858.6	53.93	-55.86	109.79	42.32	32.32	10.62	31.33	334	70	P	V
		5913	54.07	-22.98	77.05	42.31	32.45	10.66	31.35	334	70	P	V
		5927	54.23	-13.97	68.2	42.39	32.51	10.68	31.35	334	70	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz	*	5825	113.47	-	-	101.93	32.25	10.6	31.31	115	115	P	H
	*	5825	102.66	-	-	91.12	32.25	10.6	31.31	115	115	A	H
		5851.8	58.99	-59.11	118.1	47.39	32.3	10.62	31.32	115	115	P	H
		5857.6	56.55	-53.52	110.07	44.93	32.32	10.62	31.32	115	115	P	H
		5889.8	54.8	-39.42	94.22	43.11	32.38	10.65	31.34	115	115	P	H
		5944.8	53.49	-14.71	68.2	41.59	32.58	10.69	31.37	115	115	P	H
													H
													H
	*	5825	111.49	-	-	99.95	32.25	10.6	31.31	344	74	P	V
	*	5825	100.81	-	-	89.27	32.25	10.6	31.31	344	74	A	V
		5852.4	57.59	-59.14	116.73	45.99	32.3	10.62	31.32	344	74	P	V
		5872.4	55.01	-50.92	105.93	43.37	32.34	10.63	31.33	344	74	P	V
		5880.4	54.44	-46.75	101.19	42.77	32.36	10.64	31.33	344	74	P	V
		5949	54.16	-14.04	68.2	42.24	32.6	10.69	31.37	344	74	P	V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	48.85	-25.15	74	54.18	39.78	16.49	61.6	100	0	P	H
		17235	48.11	-20.09	68.2	42.41	40.7	20.78	55.78	100	0	P	H
													H
													H
		11490	52.93	-21.07	74	58.26	39.78	16.49	61.6	100	271	P	V
		11490	40.12	-13.88	54	45.45	39.78	16.49	61.6	100	271	A	V
		17235	47.76	-20.44	68.2	42.06	40.7	20.78	55.78	100	0	P	V
													V
802.11a CH 157 5785MHz		11570	46.43	-27.57	74	51.97	39.66	16.55	61.75	100	0	P	H
		17355	49.73	-18.47	68.2	42.97	41.4	20.88	55.52	100	0	P	H
													H
													H
		11570	47.54	-26.46	74	53.08	39.66	16.55	61.75	100	0	P	V
		17355	48.91	-19.29	68.2	42.15	41.4	20.88	55.52	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11650	46.6	-27.4	74	52.56	39.35	16.62	61.93	100	0	P	H
		17475	49.55	-18.65	68.2	41.67	42.17	20.97	55.26	100	0	P	H
													H
													H
		11650	47.08	-26.92	74	53.04	39.35	16.62	61.93	100	0	P	V
		17475	49.23	-18.97	68.2	41.35	42.17	20.97	55.26	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5608.8	54.01	-14.19	68.2	43.01	31.78	10.43	31.21	119	113	P	H
		5698	56.16	-47.57	103.73	44.92	31.99	10.5	31.25	119	113	P	H
		5720	70.55	-40.25	110.8	59.25	32.04	10.52	31.26	119	113	P	H
		5723	78.5	-39.14	117.64	67.19	32.05	10.52	31.26	119	113	P	H
	*	5745	115.63	-	-	104.27	32.09	10.54	31.27	119	113	P	H
	*	5745	104.17	-	-	92.81	32.09	10.54	31.27	119	113	A	H
													H
													H
		5626.8	53.79	-14.41	68.2	42.81	31.75	10.44	31.21	307	71	P	V
		5697.2	54.59	-48.55	103.14	43.36	31.98	10.5	31.25	307	71	P	V
		5720	65.9	-44.9	110.8	54.6	32.04	10.52	31.26	307	71	P	V
		5724.8	76.49	-45.25	121.74	65.18	32.05	10.52	31.26	307	71	P	V
	*	5745	113.4	-	-	102.04	32.09	10.54	31.27	307	71	P	V
	*	5745	102.03	-	-	90.67	32.09	10.54	31.27	307	71	A	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5642.6	53.93	-14.27	68.2	42.99	31.71	10.45	31.22	115	115	P	H
		5699.2	54.34	-50.27	104.61	43.09	32	10.5	31.25	115	115	P	H
		5716.6	54.92	-54.93	109.85	43.64	32.03	10.51	31.26	115	115	P	H
		5724.4	54.82	-66.01	120.83	43.51	32.05	10.52	31.26	115	115	P	H
	*	5785	112.8	-	-	101.35	32.17	10.57	31.29	115	115	P	H
	*	5785	101.71	-	-	90.26	32.17	10.57	31.29	115	115	A	H
		5851	54.15	-65.77	119.92	42.55	32.3	10.62	31.32	115	115	P	H
		5869.4	54.2	-52.57	106.77	42.56	32.34	10.63	31.33	115	115	P	H
		5898	53.75	-34.39	88.14	42.04	32.4	10.65	31.34	115	115	P	H
		5937.8	54.16	-14.04	68.2	42.3	32.55	10.68	31.37	115	115	P	H
													H
													H
		5601	53.17	-15.03	68.2	42.15	31.8	10.42	31.2	334	70	P	V
		5696.8	54.16	-48.68	102.84	42.93	31.98	10.5	31.25	334	70	P	V
		5717.2	53.96	-56.06	110.02	42.68	32.03	10.51	31.26	334	70	P	V
		5722.2	53.28	-62.54	115.82	41.98	32.04	10.52	31.26	334	70	P	V
	*	5785	110.83	-	-	99.38	32.17	10.57	31.29	334	70	P	V
	*	5785	99.77	-	-	88.32	32.17	10.57	31.29	334	70	A	V
		5851	53.06	-66.86	119.92	41.46	32.3	10.62	31.32	334	70	P	V
		5874.6	54.2	-51.11	105.31	42.54	32.35	10.64	31.33	334	70	P	V
		5880.2	54.29	-47.05	101.34	42.62	32.36	10.64	31.33	334	70	P	V
		5932.6	53.92	-14.28	68.2	42.06	32.53	10.68	31.35	334	70	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	113.54	-	-	102	32.25	10.6	31.31	100	116	P	H
	*	5825	102.65	-	-	91.11	32.25	10.6	31.31	100	116	A	H
		5850.2	59.3	-62.44	121.74	47.7	32.3	10.62	31.32	100	116	P	H
		5867.8	56.73	-50.48	107.21	45.09	32.34	10.63	31.33	100	116	P	H
		5884.4	54.55	-43.67	98.22	42.88	32.37	10.64	31.34	100	116	P	H
		5947	53.82	-14.38	68.2	41.91	32.59	10.69	31.37	100	116	P	H
													H
													H
	*	5825	111.64	-	-	100.1	32.25	10.6	31.31	326	70	P	V
	*	5825	100.6	-	-	89.06	32.25	10.6	31.31	326	70	A	V
		5850	58.15	-64.05	122.2	46.55	32.3	10.62	31.32	326	70	P	V
		5864.6	54.94	-53.17	108.11	43.31	32.33	10.63	31.33	326	70	P	V
		5890.2	54.91	-39.01	93.92	43.22	32.38	10.65	31.34	326	70	P	V
		5932	53.83	-14.37	68.2	41.97	32.53	10.68	31.35	326	70	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	54.78	-19.22	74	60.11	39.78	16.49	61.6	113	230	P	H
		11490	39.2	-14.8	54	44.53	39.78	16.49	61.6	113	230	A	H
		17235	47.92	-20.28	68.2	42.22	40.7	20.78	55.78	100	0	P	H
													H
		11490	55.56	-18.44	74	60.89	39.78	16.49	61.6	100	271	P	V
		11490	39.78	-14.22	54	45.11	39.78	16.49	61.6	100	271	A	V
		17235	47.28	-20.92	68.2	41.58	40.7	20.78	55.78	100	0	P	V
													V
802.11n HT20 CH 157 5785MHz		11570	53.01	-20.99	74	58.55	39.66	16.55	61.75	119	230	P	H
		11570	38.27	-15.73	54	43.81	39.66	16.55	61.75	119	230	A	H
		17355	48.36	-19.84	68.2	41.6	41.4	20.88	55.52	100	0	P	H
													H
		11570	53.49	-20.51	74	59.03	39.66	16.55	61.75	100	272	P	V
		11570	38.84	-15.16	54	44.38	39.66	16.55	61.75	100	272	A	V
		17355	47.02	-21.18	68.2	40.26	41.4	20.88	55.52	100	0	P	V
													V
802.11n HT20 CH 165 5825MHz		11650	52.06	-21.94	74	58.02	39.35	16.62	61.93	115	238	P	H
		11650	37.85	-16.15	54	43.81	39.35	16.62	61.93	115	238	A	H
		17475	51.1	-17.1	68.2	43.22	42.17	20.97	55.26	100	0	P	H
													H
		11650	52.6	-21.4	74	58.56	39.35	16.62	61.93	100	270	P	V
		11650	38.15	-15.85	54	44.11	39.35	16.62	61.93	100	270	A	V
		17475	48.7	-19.5	68.2	40.82	42.17	20.97	55.26	100	0	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5649.4	54.32	-13.88	68.2	43.38	31.7	10.46	31.22	124	111	P	H
		5699	65.19	-39.27	104.46	53.95	31.99	10.5	31.25	124	111	P	H
		5712.6	79	-29.73	108.73	67.72	32.03	10.51	31.26	124	111	P	H
		5723.8	78.52	-40.94	119.46	67.21	32.05	10.52	31.26	124	111	P	H
	*	5755	112.31	-	-	100.93	32.11	10.54	31.27	124	111	P	H
	*	5755	101.39	-	-	90.01	32.11	10.54	31.27	124	111	A	H
		5853.6	55.34	-58.65	113.99	43.73	32.31	10.62	31.32	124	111	P	H
		5857.2	54.76	-55.42	110.18	43.15	32.31	10.62	31.32	124	111	P	H
		5902.8	54.05	-30.54	84.59	42.32	32.41	10.66	31.34	124	111	P	H
		5929.2	54.31	-13.89	68.2	42.46	32.52	10.68	31.35	124	111	P	H
													H
													H
		5636.8	53.86	-14.34	68.2	42.9	31.73	10.45	31.22	321	71	P	V
		5699	62.76	-41.7	104.46	51.52	31.99	10.5	31.25	321	71	P	V
		5716.4	77.33	-32.46	109.79	66.05	32.03	10.51	31.26	321	71	P	V
		5724.2	75.94	-44.44	120.38	64.63	32.05	10.52	31.26	321	71	P	V
	*	5755	110.76	-	-	99.38	32.11	10.54	31.27	321	71	P	V
	*	5755	99.59	-	-	88.21	32.11	10.54	31.27	321	71	A	V
		5855	54.34	-56.46	110.8	42.73	32.31	10.62	31.32	321	71	P	V
		5860.8	54.76	-54.41	109.17	43.14	32.32	10.63	31.33	321	71	P	V
		5906	54.61	-27.61	82.22	42.87	32.42	10.66	31.34	321	71	P	V
		5925.8	53.97	-14.23	68.2	42.15	32.5	10.67	31.35	321	71	P	V
													V
													V



WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5631	53.47	-14.73	68.2	42.51	31.74	10.44	31.22	123	112	P	H
		5697	55.06	-47.93	102.99	43.83	31.98	10.5	31.25	123	112	P	H
		5715.4	56.87	-52.64	109.51	45.59	32.03	10.51	31.26	123	112	P	H
		5723.8	57.17	-62.29	119.46	45.86	32.05	10.52	31.26	123	112	P	H
	*	5795	111.53	-	-	100.05	32.19	10.58	31.29	123	112	P	H
	*	5795	100.47	-	-	88.99	32.19	10.58	31.29	123	112	A	H
		5852.8	56.96	-58.86	115.82	45.35	32.31	10.62	31.32	123	112	P	H
		5856	56.15	-54.37	110.52	44.54	32.31	10.62	31.32	123	112	P	H
		5876.6	55.57	-48.44	104.01	43.91	32.35	10.64	31.33	123	112	P	H
		5930.2	55.99	-12.21	68.2	44.14	32.52	10.68	31.35	123	112	P	H
													H
													H
		5631.6	53.17	-15.03	68.2	42.2	31.74	10.45	31.22	317	71	P	V
		5679.8	54.37	-35.92	90.29	43.26	31.88	10.48	31.25	317	71	P	V
		5710.8	55.48	-52.75	108.23	44.21	32.02	10.51	31.26	317	71	P	V
		5725	55.78	-66.42	122.2	44.47	32.05	10.52	31.26	317	71	P	V
	*	5795	109.85	-	-	98.37	32.19	10.58	31.29	317	71	P	V
	*	5795	98.67	-	-	87.19	32.19	10.58	31.29	317	71	A	V
		5852.6	55.42	-60.85	116.27	43.81	32.31	10.62	31.32	317	71	P	V
		5858.4	55.36	-54.49	109.85	43.75	32.32	10.62	31.33	317	71	P	V
		5878.8	54.74	-47.64	102.38	43.07	32.36	10.64	31.33	317	71	P	V
		5926.4	54.55	-13.65	68.2	42.72	32.51	10.67	31.35	317	71	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	46.03	-27.97	74	51.37	39.78	16.5	61.62	100	0	P	H
		17265	48.22	-19.98	68.2	42.33	40.8	20.81	55.72	100	0	P	H
													H
													H
		11510	46.49	-27.51	74	51.83	39.78	16.5	61.62	100	0	P	V
		17265	48.48	-19.72	68.2	42.59	40.8	20.81	55.72	100	0	P	V
													V
													V
802.11n HT40 CH 159 5795MHz		11590	46.26	-27.74	74	51.87	39.62	16.57	61.8	100	0	P	H
		17385	48.66	-19.54	68.2	41.54	41.67	20.9	55.45	100	0	P	H
													H
													H
		11590	46.42	-27.58	74	52.03	39.62	16.57	61.8	100	0	P	V
		17385	48.3	-19.9	68.2	41.18	41.67	20.9	55.45	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		5647	55.82	-12.38	68.2	44.87	31.71	10.46	31.22	122	114	P	H
		5686.2	72.03	-22.99	95.02	60.87	31.92	10.49	31.25	122	114	P	H
		5704	76.76	-29.56	106.32	65.5	32.01	10.5	31.25	122	114	P	H
		5724.6	78.07	-43.22	121.29	66.76	32.05	10.52	31.26	122	114	P	H
	*	5775	108.37	-	-	96.94	32.15	10.56	31.28	122	114	P	H
	*	5775	97.21	-	-	85.78	32.15	10.56	31.28	122	114	A	H
		5851.6	68.07	-50.48	118.55	56.47	32.3	10.62	31.32	122	114	P	H
		5860.6	69.45	-39.78	109.23	57.83	32.32	10.63	31.33	122	114	P	H
		5884.4	61.94	-36.28	98.22	50.27	32.37	10.64	31.34	122	114	P	H
		5925.8	53.89	-14.31	68.2	42.07	32.5	10.67	31.35	122	114	P	H
													H
													H
		5640.4	54.98	-13.22	68.2	44.03	31.72	10.45	31.22	310	72	P	V
		5685.6	68.14	-26.44	94.58	56.99	31.91	10.49	31.25	310	72	P	V
		5706.8	71.83	-35.28	107.11	60.57	32.01	10.51	31.26	310	72	P	V
		5724.6	73.85	-47.44	121.29	62.54	32.05	10.52	31.26	310	72	P	V
	*	5775	105.52	-	-	94.09	32.15	10.56	31.28	310	72	P	V
	*	5775	94.42	-	-	82.99	32.15	10.56	31.28	310	72	A	V
		5850.4	64.71	-56.58	121.29	53.11	32.3	10.62	31.32	310	72	P	V
		5869.2	64.79	-42.03	106.82	53.15	32.34	10.63	31.33	310	72	P	V
		5884.2	58.87	-39.5	98.37	47.2	32.37	10.64	31.34	310	72	P	V
		5934.6	54.15	-14.05	68.2	42.3	32.54	10.68	31.37	310	72	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11ac VHT80 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 155 5775MHz		11550	46.38	-27.62	74	51.85	39.7	16.54	61.71	100	0	P	H
		17325	49.31	-18.89	68.2	42.92	41.12	20.85	55.58	100	0	P	H
													H
													H
		11550	46.15	-27.85	74	51.62	39.7	16.54	61.71	100	0	P	V
		17325	48.8	-19.4	68.2	42.41	41.12	20.85	55.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

[illegible]



<Adapter 2>

Band 4 - 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5628.4	52.94	-15.26	68.2	41.98	31.74	10.44	31.22	121	114	P	H
		5694.4	55.36	-45.71	101.07	44.14	31.97	10.5	31.25	121	114	P	H
		5716.8	56.04	-53.87	109.91	44.76	32.03	10.51	31.26	121	114	P	H
		5725	56.18	-66.02	122.2	44.87	32.05	10.52	31.26	121	114	P	H
	*	5795	111.01	-	-	99.53	32.19	10.58	31.29	121	114	P	H
	*	5795	100.8	-	-	89.32	32.19	10.58	31.29	121	114	A	H
		5854.6	56.44	-55.27	111.71	44.83	32.31	10.62	31.32	121	114	P	H
		5856.4	55.73	-54.68	110.41	44.12	32.31	10.62	31.32	121	114	P	H
		5877	54.89	-48.82	103.71	43.23	32.35	10.64	31.33	121	114	P	H
		5927.4	54.02	-14.18	68.2	42.18	32.51	10.68	31.35	121	114	P	H
													H
													H
		5602.4	52.49	-15.71	68.2	41.47	31.8	10.42	31.2	295	61	P	V
		5684.4	53.37	-40.32	93.69	42.22	31.91	10.49	31.25	295	61	P	V
		5717.2	54.34	-55.68	110.02	43.06	32.03	10.51	31.26	295	61	P	V
		5720.8	53.67	-58.95	112.62	42.37	32.04	10.52	31.26	295	61	P	V
	*	5795	108.01	-	-	96.53	32.19	10.58	31.29	295	61	P	V
	*	5795	97.12	-	-	85.64	32.19	10.58	31.29	295	61	A	V
		5853.8	53.38	-60.16	113.54	41.77	32.31	10.62	31.32	295	61	P	V
		5856.2	54.29	-56.17	110.46	42.68	32.31	10.62	31.32	295	61	P	V
		5912.8	53.52	-23.68	77.2	41.76	32.45	10.66	31.35	295	61	P	V
		5933.8	53.21	-14.99	68.2	41.34	32.54	10.68	31.35	295	61	P	V
													V
													V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												

**Band 4 5725~5850MHz****WIFI 802.11n HT40 (Harmonic @ 3m)**

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		11590	46.47	-27.53	74	52.08	39.62	16.57	61.8	100	0	P	H
		17385	49.18	-19.02	68.2	42.06	41.67	20.9	55.45	100	0	P	H
													H
													H
		11590	46.36	-27.64	74	51.97	39.62	16.57	61.8	100	0	P	V
		17385	48.83	-19.37	68.2	41.71	41.67	20.9	55.45	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		61.59	22.8	-17.2	40	40.38	11.77	1.11	30.46	-	-	P	H
		108.84	24.29	-19.21	43.5	36.57	16.68	1.46	30.42	-	-	P	H
		155.55	25.67	-17.83	43.5	37.52	16.68	1.84	30.37	-	-	P	H
		799.8	33.25	-12.75	46	30.61	27.96	3.97	29.29	-	-	P	H
		887.3	34.18	-11.82	46	30.16	28.97	4.21	29.16	-	-	P	H
		949.6	36.17	-9.83	46	30.18	30.56	4.43	29	100	0	P	H
													H
													H
													H
													H
													H
													H
		30	31.46	-8.54	40	36.37	24.57	0.7	30.18	-	-	P	V
		118.56	25.74	-17.76	43.5	37.46	17.17	1.52	30.41	-	-	P	V
		159.6	29.02	-14.48	43.5	41.03	16.46	1.89	30.36	-	-	P	V
		659.1	30.68	-15.32	46	30.45	26.18	3.61	29.56	-	-	P	V
		788.6	33.03	-12.97	46	30.46	27.96	3.93	29.32	-	-	P	V
		904.1	38.22	-7.78	46	34.08	29	4.27	29.13	100	0	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<For Sample 2>

<Adapter 1>

Band 4 - 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 159 5795MHz		5637.4	52.98	-15.22	68.2	42.02	31.73	10.45	31.22	100	117	P	H
		5698.6	54.81	-49.36	104.17	43.57	31.99	10.5	31.25	100	117	P	H
		5714.2	58.01	-51.17	109.18	46.73	32.03	10.51	31.26	100	117	P	H
		5723.6	58.65	-60.36	119.01	47.34	32.05	10.52	31.26	100	117	P	H
	*	5795	110.7	-	-	99.22	32.19	10.58	31.29	100	117	P	H
	*	5795	99.73	-	-	88.25	32.19	10.58	31.29	100	117	A	H
		5854.2	56.08	-56.54	112.62	44.47	32.31	10.62	31.32	100	117	P	H
		5855	55.92	-54.88	110.8	44.31	32.31	10.62	31.32	100	117	P	H
		5879.2	54.07	-48.01	102.08	42.4	32.36	10.64	31.33	100	117	P	H
		5938	54.39	-13.81	68.2	42.53	32.55	10.68	31.37	100	117	P	H
													H
		5605.8	52.77	-15.43	68.2	41.77	31.79	10.42	31.21	105	91	P	V
		5691.8	54.3	-44.85	99.15	43.11	31.95	10.49	31.25	105	91	P	V
		5718.8	57.14	-53.32	110.46	45.84	32.04	10.52	31.26	105	91	P	V
		5724	59.34	-60.58	119.92	48.03	32.05	10.52	31.26	105	91	P	V
	*	5795	111.1	-	-	99.62	32.19	10.58	31.29	105	91	P	V
	*	5795	100.66	-	-	89.18	32.19	10.58	31.29	105	91	A	V
		5850	56.36	-65.84	122.2	44.76	32.3	10.62	31.32	105	91	P	V
		5873.6	56.29	-49.3	105.59	44.63	32.35	10.64	31.33	105	91	P	V
		5891	54.92	-38.41	93.33	43.23	32.38	10.65	31.34	105	91	P	V
		5930.6	53.51	-14.69	68.2	41.66	32.52	10.68	31.35	105	91	P	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		11590	46.36	-27.64	74	51.97	39.62	16.57	61.8	100	0	P	H
		17385	47.86	-20.34	68.2	40.74	41.67	20.9	55.45	100	0	P	H
													H
													H
		11590	45.22	-28.78	74	50.83	39.62	16.57	61.8	100	0	P	V
		17385	47.46	-20.74	68.2	40.34	41.67	20.9	55.45	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		35.67	28.17	-11.83	40	36.23	21.43	0.78	30.27	-	-	P	H
		64.56	25.23	-14.77	40	42.8	11.75	1.14	30.46	-	-	P	H
		166.08	27.93	-15.57	43.5	40.52	15.85	1.92	30.36	-	-	P	H
		807.5	32.08	-13.92	46	29.71	27.66	3.99	29.28	-	-	P	H
		904.1	37.34	-8.66	46	33.2	29	4.27	29.13	100	0	P	H
		955.2	36.35	-9.65	46	30.12	30.77	4.44	28.98	-	-	P	H
													H
													H
													H
													H
													H
													H
		35.13	35.77	-4.23	40	43.29	21.97	0.77	30.26	100	0	P	V
		64.83	23.5	-16.5	40	41.07	11.75	1.14	30.46	-	-	P	V
		166.35	28.23	-15.27	43.5	40.91	15.76	1.92	30.36	-	-	P	V
		842.5	32.81	-13.19	46	29.39	28.58	4.07	29.23	-	-	P	V
		885.9	37.8	-8.2	46	33.78	28.97	4.21	29.16	-	-	P	V
		904.8	38.18	-7.82	46	34.01	29.03	4.27	29.13	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
 = 55.45 (dBμV/m)
2. Over Limit(dB)
 = Level(dBμV/m) – Limit Line(dBμV/m)
 = 55.45(dBμV/m) – 74(dBμV/m)
 = -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
 = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
 = 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
 = 43.54 (dBμV/m)
2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)
 = 43.54(dBμV/m) – 54(dBμV/m)
 = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Jack Cheng, Lance Chiang, and Peter Liao	Temperature :	22~24°C
		Relative Humidity :	52~60%

Note symbol



-L	Low channel location
-R	High channel location





<For Sample 1>

<Adapter 1>




Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site Condition : 03CH12-HV : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site Condition : 03CH12-HV : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(157)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto
	 Site : 03CH12-HY Condition : PEAK_BE(157)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site Condition : 03CH12-HV : PEAK_BE(157)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	 Site Condition : 03CH12-HV : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto
	 Site Condition : 03CH12-HV : PEAK_BE(157)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto



Band 4 5725~5850MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-4Y Condition : PEAK(FUND) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Fundamental
Peak	Site : 03CH12-HY Condition : PEAK_BE(16)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	Site : 03CH12-HY Condition : PEAK_BE(16)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto




Band 4 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto
	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL RBW:3000.000KHz VBW:3000.000KHz SWT:Auto	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	Site Condition : 03CH12-HY : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site Condition : 03CH12-HY : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	Site Condition : 03CH12-HY : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank

Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto
Peak	 Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Vertical	Fundamental
Peak	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
	 Site : 03CH12-4Y Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak







WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

Band 4 5725~5850MHz
WIFI 802.11n HT20 (Harmonic @ 3m)



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-4Y Condition : PEAK(UMI) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-4Y Condition : PEAK(UMI) 3m HORN_9120D_1328 VERTICAL Detector : Peak





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak



Band 4 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

Band 4 5725~5850MHz
WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ac VHT80 CH155 5775MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-4Y Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

Emission below 1GHz
5GHz WIFI 802.11n HT40 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT40 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 VERTICAL Detector : Peak






<Adapter 2>



Band 4 - 5725~5850MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Site : 03CH12-HY Condition : PEAK(UNIT1) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	Site : 03CH12-HY Condition : PEAK_BE(B4)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	 Site Condition : 03CH12-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	 Site Condition : 03CH12-HY : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto
Peak	 Site Condition : 03CH12-HY : PEAK_BE(B4)_16-24 3m HORN_91200_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto	Left blank

Band 4 - 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

Emission below 1GHz
5GHz WIFI 802.11n HT40 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT40 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 VERTICAL Detector : Peak









<For Sample 2>

<Adapter 1>



Band 4 - 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Fundamental
Peak	 Site Condition : 03CH12-HY : PEAK_BE(BA)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto	 Site Condition : 03CH12-HY : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto
Peak	 Site Condition : 03CH12-HY : PEAK_BE(BA)_16-24 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto	Left blank

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Vertical	Fundamental
Peak	 Site Condition : 03CH12-14V : PEAK_BE(16)_16-24 3m HORN_91200_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	 Site Condition : 03CH12-14V : PEAK(UNIT) 3m HORN_91200_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto
	 Site Condition : 03CH12-14V : PEAK_BE(16)_16-24 3m HORN_91200_1328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto	Left blank

Band 4 - 5725~5850MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1+2	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : PEAK(UNIT) 3m HORN_9120D_1328 VERTICAL Detector : Peak

Emission below 1GHz
5GHz WIFI 802.11n HT40 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT40 LF	
1+2	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 HORIZONTAL Detector : Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 VERTICAL Detector : Peak


Appendix E. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
1	802.11a	98.07	-	-	10Hz	0.08
2	802.11a	98.07	-	-	10Hz	0.08
1+2	802.11a for Ant. 1	98.07	-	-	10Hz	0.08
1+2	802.11a for Ant. 2	98.07	-	-	10Hz	0.08
1	5GHz 802.11n HT20	97.93	1890	0.53	1kHz	0.09
2	5GHz 802.11n HT20	97.93	1890	0.53	1kHz	0.09
1+2	5GHz 802.11n HT20 for Ant. 1	97.93	1890	0.53	1kHz	0.09
1+2	5GHz 802.11n HT20 for Ant. 2	97.93	1890	0.53	1kHz	0.09
1	5GHz 802.11n HT40	95.85	925	1.08	3kHz	0.18
2	5GHz 802.11n HT40	95.85	925	1.08	3kHz	0.18
1+2	5GHz 802.11n HT40 for Ant. 1	95.85	925	1.08	3kHz	0.18
1+2	5GHz 802.11n HT40 for Ant. 2	95.85	925	1.08	3kHz	0.18
1	5GHz 802.11ac VHT20	97.94	1900	0.53	1kHz	0.09
2	5GHz 802.11ac VHT20	97.94	1900	0.53	1kHz	0.09
1+2	5GHz 802.11ac VHT20 for Ant. 1	97.94	1900	0.53	1kHz	0.09
1+2	5GHz 802.11ac VHT20 for Ant. 2	97.94	1900	0.53	1kHz	0.09
1	5GHz 802.11ac VHT40	95.90	935	1.07	3kHz	0.18
2	5GHz 802.11ac VHT40	95.90	935	1.07	3kHz	0.18
1+2	5GHz 802.11ac VHT40 for Ant. 1	96.39	935	1.07	3kHz	0.16
1+2	5GHz 802.11ac VHT40 for Ant. 2	96.39	935	1.07	3kHz	0.16
1	5GHz 802.11ac VHT80	92.68	456	2.19	3kHz	0.33
2	5GHz 802.11ac VHT80	92.68	456	2.19	3kHz	0.33
1+2	5GHz 802.11ac VHT80 for Ant. 1	92.68	456	2.19	3kHz	0.33
1+2	5GHz 802.11ac VHT80 for Ant. 2	92.68	456	2.19	3kHz	0.33




<Ant. 1>


802.11a



802.11n HT20




802.11n HT40




Date: 5.OCT.2018 01:08:47

802.11ac VHT20




Date: 5.OCT.2018 01:19:33

802.11ac VHT40




802.11ac VHT80




<Ant. 2>

802.11a




Date: 5.OCT.2018 01:01:01

802.11n HT20




Date: 5.OCT.2018 01:07:55


802.11n HT40




802.11ac VHT20



802.11ac VHT40




802.11ac VHT80






MIMO <Ant. 1>


802.11a




802.11n HT20




802.11n HT40



802.11ac VHT20




802.11ac VHT40



Date: 5.OCT.2018 01:25:49

802.11ac VHT80




Date: 5.OCT.2018 01:28:43




MIMO <Ant. 2>


802.11a



802.11n HT20




802.11n HT40




Date: 5.OCT.2018 01:16:06

802.11ac VHT20




Date: 5.OCT.2018 01:17:45

802.11ac VHT40



802.11ac VHT80



————THE END————