FCC RADIO TEST REPORT

FCC ID	:	**A4RG020J**
Equipment	:	**Phone**
Model Name	:	**G020J**
Applicant	:	**Google LLC** **1600 Amphitheatre Parkway,** **Mountain View, California, 94043 USA**
Standard	:	**FCC 47 CFR Part 2, 90(R)**

The product was received on Nov. 07, 2018 and testing was started from Apr. 07, 2019 and completed on Jun. 20, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA-603-E and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsai

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 5
1.3 Modification of EUT 5
1.4 Testing Site 6
1.5 Applied Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Support Unit used in test configuration and system 8
2.4 Measurement Results Explanation Example 8
2.5 Frequency List of Low/Middle/High Channels 9
3 Conducted Test Items **10**
3.1 Measuring Instruments 10
3.2 Conducted Output Power Measurement and ERP 11
3.3 Peak-to-Average Ratio 12
3.4 Occupied Bandwidth 13
3.5 Conducted Band Edge 14
3.6 Mask 15
3.7 Conducted Spurious Emission 16
3.8 Frequency Stability 17
4 Radiated Test Items **18**
4.1 Measuring Instruments 18
4.2 Radiated Spurious Emission 19
5 List of Measuring Equipment **20**
6 Uncertainty of Evaluation **22**
Appendix A. Test Results of Conducted Test
Appendix B. Test Results of ERP and Radiated Test

History of this test report

Report No.	Version	Description	Issued Date
FG8N0620-05E	01	Initial issue of report	Jun. 28, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Reporting only	-
	§90.542 (a)(7)	Effective Radiated Power	Pass	-
3.3	-	Peak-to-Average Ratio	Reporting only	-
3.4	§2.1049	Occupied Bandwidth	Reporting only	-
3.5	§2.1053 §90.543 (e)(2)	Conducted Band Edge Measurement	Pass	-
3.6	§2.1051 §90.210 (n)	Emission Mask	Pass	-
3.7	§2.1053 §90.543 (e)(3)	Conducted Spurious Emission	Pass	-
3.8	§2.1055 §90.539 (e)	Frequency Stability Temperature & Voltage	Pass	-
4.2	§2.1053 §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission	Pass	Under limit 10.46 dB at 1592.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Elise Chang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	G020J
FCC ID	A4RG020J
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC/GNSS/WPC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE 60 GHz Low Power Transmitter
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
No.	S/N
#1	92UBA06699
#2	958BA00AJH

1.2 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	790.5 ~ 795.5 MHz
Rx Frequency	760.5 ~ 765.5 MHz
Bandwidth	5MHz / 10MHz
Maximum Output Power to Antenna	24.70 dBm
Antenna Type / Gain	**<Ant. 0_C>** LTE Band 14 : ILA Antenna type with gain 0.7 dBi **<Ant. 1>** LTE Band 14 : ILA Antenna type with gain -5.4 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH05-HY
Test Engineer	George Chen
Temperature	22-25℃
Relative Humidity	52-55%

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY
Test Engineer	Jack Cheng, Lance Chiang, Chuan Chu
Temperature	22-26℃
Relative Humidity	54-60%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW0007

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ANSI C63.26-2015
- 47 CFR Part 2, Part 90(R)
- ANSI / TIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z with Accessory (Earphone or Adapter).

<Adapter Mode>

LTE Band 14
Z plane for Ant. 0_C
Y plane for Ant. 1

Conducted Test Cases	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	14	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	14	-	-		v	-	-	v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	14	-	-	v	v	-	-	v	v	v			v	v	v	v
Conducted Band Edge	14	-	-	v	v	-	-	v	v	v	v		v	v		v
Mask	14	-	-	v	v	-	-	v	v	v	v		v	v	v	v
Conducted Spurious Emission	14	-	-	v	v	-	-	v	v	v	v			v	v	v
Frequency Stability	14	-	-		v	-	-	v	v	v			v		v	
E.R.P	14	-	-	v	v	-	-	v	v	v	v	v		v	v	v
Radiated Spurious Emission	14	Worst Case												v	v	v
Remark	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. **3.** The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. **4.** All the radiated test cases were performed with Adapter 1.															

2.2 Connection Diagram of Test System

<For Adapter Mode>



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.5 + 10 = 14.5 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 14 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Mask, and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power Measurement and ERP

3.2.1 Description of the Conducted Output Power Measurement and ERP Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

90.543(e)

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.
   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.6 Mask

3.6.1 Description of Mask Measurement

Transmitters designed must meet the emission mask comply with the emission mask provisions of FCC Part 90.210(n).

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.0.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The power of the modulated signal was measured on a spectrum analyzer using an RMS and 10 second sweep time in order to maximize the level.
3. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7 Conducted Spurious Emission

3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.7.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.8 Frequency Stability

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.8.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.1.1 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



4.1.2 Test Result of Radiated Test

Please refer to Appendix B.

4.2 Radiated Spurious Emission

4.2.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.2.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI / TIA-603-E Section 2.2.12.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Base Station (Measure)	Anritsu	MT8821C	6201664755	GSM / GPRS /WCDMA / LTE FDD/TDD with 44) /LTE-3CC DLCA,2CC ULCA	Mar. 03, 2019	Apr. 07, 2019~ Jun. 06, 2019	Mar. 02, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 13, 2018	Apr. 07, 2019~ Jun. 06, 2019	Nov. 12, 2019	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-40℃~90℃	Aug. 29, 2018	Apr. 07, 2019~ Jun. 06, 2019	Aug. 28, 2019	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 02, 2018	Apr. 07, 2019~ Jun. 06, 2019	Oct. 01, 2019	Conducted (TH05-HY)
Coupler	Warison	20dB 25W SM A Directional Coupler	#A	1-18GHz	Jan. 14, 2019	Apr. 07, 2019~ Jun. 06, 2019	Jan. 13, 2020	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	May 28, 2019~ Jun. 20, 2019	Jan. 06, 2020	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00802N 1D01N-06	47020&06	30MHz to 1GHz	Oct. 13, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 12, 2019	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1212	1GHz ~ 18GHz	Oct. 19, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 18, 2019	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120D	9120D-1326	1GHz ~ 18GHz	Oct. 30, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 29, 2019	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA917058 4	18GHz ~ 40GHz	Dec. 05, 2018	May 28, 2019~ Jun. 20, 2019	Dec. 04, 2019	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 25, 2019	May 28, 2019~ Jun. 20, 2019	Mar. 24, 2020	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5Ghz	May. 28, 2018	May 28, 2019~ Jun. 20, 2019	May. 26, 2020	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-303	17100018000 55007	1GHz~18GHz	Apr. 01, 2019	May 28, 2019~ Jun. 20, 2019	Mar. 31, 2020	Radiation (03CH12-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 06, 2018	May 28, 2019~ Jun. 20, 2019	Dec. 05, 2019	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 26, 2018	May 28, 2019~ Jun. 20, 2019	Dec. 25, 2019	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Dec. 19, 2018	May 28, 2019~ Jun. 20, 2019	Dec. 18, 2019	Radiation (03CH12-HY)
Hygrometer	TECPEL	DTM-303B	TP161243	N/A	May. 11, 2019	May 28, 2019~ Jun. 20, 2019	May. 10, 2020	Radiation (03CH12-HY)
Signal Generator	Rohde & Schwarz	SMB100A	175727	100kHz~40GHz	Dec. 23, 2018	May 28, 2019~ Jun. 20, 2019	Dec. 23, 2019	Radiation (03CH12-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Filter	Wainwright	WLK4-1000-1530-6000-40SS	SN11	1 GHz Lowpass	Sep. 16, 2018	May 28, 2019~ Jun. 20, 2019	Sep. 15, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-1080-1200-1500-60SS	SN2	1.2G High Pass	Sep. 16, 2018	May 28, 2019~ Jun. 20, 2019	Sep. 15, 2019	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN2	3GHz High Pass	Mar. 20, 2019	May 28, 2019~ Jun. 20, 2019	Mar. 19, 2020	Radiation (03CH12-HY)
Notch Filter	EWT	EWT-14-0041	D1	DCS 1800	Nov. 01, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 31, 2019	Radiation (03CH12-HY)
Notch Filter	Wainwright	WRCT698/798-10/40 8SSK	SN1	AWS Band	Nov. 01, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 31, 2019	Radiation (03CH12-HY)
Notch Filter	Wainwright	WRCG824/849-40/8SS	SN35	CDMA 850	Nov. 07, 2018	May 28, 2019~ Jun. 20, 2019	Nov. 06, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30M-18G	Mar. 13, 2019	May 28, 2019~ Jun. 20, 2019	Mar. 12, 2020	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M~40GHz	Oct. 16, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 15, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M~40GHz	Oct. 16, 2018	May 28, 2019~ Jun. 20, 2019	Oct. 15, 2019	Radiation (03CH12-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 28, 2019~ Jun. 20, 2019	N/A	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	May 28, 2019~ Jun. 20, 2019	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	May 28, 2019~ Jun. 20, 2019	N/A	Radiation (03CH12-HY)
Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	May 28, 2019~ Jun. 20, 2019	N/A	Radiation (03CH12-HY)

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.05

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.44

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.95

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 14 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	-	24.70	-
10	1	25			24.43	
10	1	49			24.29	
10	25	0			23.57	
10	25	12			23.55	
10	25	25			23.47	
10	50	0			23.52	
10	1	0	16-QAM		23.79	
10	1	25			23.73	
10	1	49			23.56	
10	25	0			22.61	
10	25	12			22.57	
10	25	25			22.49	
10	50	0			22.55	
10	1	0	64-QAM		22.77	
10	1	25			22.67	
10	1	49			22.52	
10	25	0			21.61	
10	25	12			21.59	
10	25	25			21.50	
10	50	0			21.56	
5	1	0	QPSK	24.36	24.35	24.33
5	1	12		24.47	24.46	24.40
5	1	24		24.48	24.43	24.40
5	12	0		23.56	23.52	23.49
5	12	7		23.65	23.52	23.53
5	12	13		23.62	23.57	23.55
5	25	0		23.60	23.51	23.43
5	1	0	16-QAM	23.68	23.64	23.61
5	1	12		23.78	23.75	23.69
5	1	24		23.76	23.68	23.66
5	12	0		22.61	22.54	22.50
5	12	7		22.66	22.54	22.57
5	12	13		22.63	22.60	22.51
5	25	0		22.63	22.55	22.45
5	1	0	64-QAM	22.61	22.66	22.56
5	1	12		22.70	22.71	22.62
5	1	24		22.73	22.67	22.60
5	12	0		21.64	21.58	21.52
5	12	7		21.72	21.60	21.57
5	12	13		21.70	21.64	21.55
5	25	0		21.63	21.56	21.45

LTE Band 14

Peak-to-Average Ratio

Mode	LTE Band 14 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.62	4.96	4.17	5.88	
Highest CH	-	-	-	-	
Mode	LTE Band 14 / 10MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	-	-	-	-	PASS
Middle CH	4.35	5.80	-	-	
Highest CH	-	-	-	-	

LTE Band 14 / 10MHz / QPSK

Middle Channel/ 1RB



Middle Channel / Full RB



LTE Band 14 / 10MHz / 16QAM

Middle Channel/ 1RB



Middle Channel / Full RB



LTE Band 14 / 10MHz / 64QAM

Middle Channel/ 1RB



Middle Channel / Full RB



26dB Bandwidth

Mode	LTE Band 14 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.89	4.93	-	-	-	-	-	-
Middle CH	-	-	-	-	4.95	4.85	9.93	9.77	-	-	-	-
Highest CH	-	-	-	-	4.93	4.96	-	-	-	-	-	-
Mode	LTE Band 14 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.91	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.91	-	9.79	-	-	-	-	-
Highest CH	-	-	-	-	4.95	-	-	-	-	-	-	-

LTE Band 14

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 14	
Middle Channel / 10MHz / QPSK	**Middle Channel / 10MHz / 16QAM**
	

LTE Band 14

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



Occupied Bandwidth

Mode	LTE Band 14 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.5	4.5	-	-	-	-	-	-
Middle CH	-	-	-	-	4.49	4.48	9.03	9.03	-	-	-	-
Highest CH	-	-	-	-	4.49	4.48	-	-	-	-	-	-
Mode	LTE Band 14 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.50	-	-	-	-	-	-	-
Middle CH	-	-	-	-	4.49	-	8.97	-	-	-	-	-
Highest CH	-	-	-	-	4.50	-	-	-	-	-	-	-

LTE Band 14

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 14	
Middle Channel / 10MHz / QPSK	**Middle Channel / 10MHz / 16QAM**
	

LTE Band 14

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



Conducted Band Edge

LTE Band 14 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.00549 MHz	-50.38 dBm	-15.38 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.30270 MHz	-61.75 dBm	-48.75 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-21.22 dBm	-8.22 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.36813 MHz	20.51 dBm	-9.49 dB
799.000 MHz	805.000 MHz	6.250 kHz	802.17383 MHz	-61.59 dBm	-26.59 dB

Date: 12.APR.2019 19:39:25

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	762.60989 MHz	-50.42 dBm	-15.42 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.84216 MHz	-61.55 dBm	-48.55 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.86364 MHz	-50.35 dBm	-37.35 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.67582 MHz	20.59 dBm	-9.41 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.83616 MHz	-40.18 dBm	-5.18 dB

Date: 12.APR.2019 19:50:17

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	761.23626 MHz	-50.40 dBm	-15.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.43556 MHz	-61.58 dBm	-48.58 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-29.02 dBm	-16.02 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.17033 MHz	6.10 dBm	-23.90 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.50649 MHz	-53.35 dBm	-18.35 dB

Date: 12.APR.2019 19:34:25

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	767.08242 MHz	-50.39 dBm	-15.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.00400 MHz	-61.52 dBm	-48.52 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.82468 MHz	-43.44 dBm	-30.44 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.67582 MHz	6.27 dBm	-23.73 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.11089 MHz	-46.52 dBm	-11.52 dB

Date: 12.APR.2019 19:45:16

LTE Band 14 / 5MHz / 16QAM

Lowest Band Edge /1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	767.30220 MHz	-50.43 dBm	-15.43 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.57942 MHz	-61.66 dBm	-48.66 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-20.44 dBm	-7.44 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.31319 MHz	19.66 dBm	-10.34 dB
799.000 MHz	805.000 MHz	6.250 kHz	802.98302 MHz	-61.65 dBm	-26.65 dB

Date: 12.APR.2019 19:37:45

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	762.22527 MHz	-50.40 dBm	-15.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.07692 MHz	-61.49 dBm	-48.49 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.68182 MHz	-50.36 dBm	-37.36 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.62088 MHz	19.74 dBm	-10.26 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.81818 MHz	-45.68 dBm	-10.68 dB

Date: 12.APR.2019 19:48:36

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	762.47802 MHz	-50.35 dBm	-15.35 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.62537 MHz	-61.48 dBm	-48.48 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-30.41 dBm	-17.41 dB
788.000 MHz	799.000 MHz	100.000 kHz	791.46703 MHz	5.16 dBm	-24.84 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.38661 MHz	-54.62 dBm	-19.62 dB

Date: 12.APR.2019 19:36:05

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	768.64286 MHz	-50.38 dBm	-15.38 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.01499 MHz	-61.47 dBm	-48.47 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.88961 MHz	-43.39 dBm	-30.39 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.95055 MHz	5.15 dBm	-24.85 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.15285 MHz	-46.54 dBm	-11.54 dB

Date: 12.APR.2019 19:46:56

LTE Band 14 / 5MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.40110 MHz	-50.40 dBm	-15.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.46354 MHz	-61.74 dBm	-48.74 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-21.41 dBm	-8.41 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.32418 MHz	19.73 dBm	-10.27 dB
799.000 MHz	805.000 MHz	6.250 kHz	800.74126 MHz	-61.52 dBm	-26.52 dB

Date: 12.APR.2019 19:55:20

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	763.98352 MHz	-50.38 dBm	-15.38 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.26773 MHz	-61.52 dBm	-48.52 dB
775.000 MHz	788.000 MHz	100.000 kHz	782.51299 MHz	-50.36 dBm	-37.36 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.63187 MHz	19.75 dBm	-10.25 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.81818 MHz	-44.28 dBm	-9.28 dB

Date: 12.APR.2019 20:00:46

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	763.48901 MHz	-50.42 dBm	-15.42 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.34066 MHz	-61.61 dBm	-48.61 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-30.58 dBm	-17.58 dB
788.000 MHz	799.000 MHz	100.000 kHz	790.22527 MHz	5.22 dBm	-24.78 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.17682 MHz	-54.85 dBm	-19.85 dB

Date: 12.APR.2019 19:53:40

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.50000 MHz	-50.42 dBm	-15.42 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.69530 MHz	-61.60 dBm	-48.60 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.87662 MHz	-43.25 dBm	-30.25 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.66484 MHz	5.25 dBm	-24.75 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.48851 MHz	-46.35 dBm	-11.35 dB

Date: 12.APR.2019 19:59:06

LTE Band 14 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	765.99451 MHz	-50.34 dBm	-15.34 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.74725 MHz	-61.50 dBm	-48.50 dB
775.000 MHz	788.000 MHz	100.000 kHz	784.21429 MHz	-32.91 dBm	-19.91 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.58791 MHz	20.65 dBm	-9.35 dB
799.000 MHz	805.000 MHz	6.250 kHz	802.68931 MHz	-61.32 dBm	-26.32 dB

Date: 12.APR.2019 20:08:52

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.08242 MHz	-50.40 dBm	-15.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	770.01598 MHz	-61.50 dBm	-48.50 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-47.89 dBm	-34.89 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.40110 MHz	20.48 dBm	-9.52 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.83217 MHz	-40.52 dBm	-5.52 dB

Date: 12.APR.2019 20:10:32

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	766.12637 MHz	-50.40 dBm	-15.40 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.46354 MHz	-61.71 dBm	-48.71 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-31.82 dBm	-18.82 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.56593 MHz	3.27 dBm	-26.73 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.00899 MHz	-48.00 dBm	-13.00 dB

Date: 12.APR.2019 20:03:52

LTE Band 14 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	760.51099 MHz	-50.39 dBm	-15.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	773.04296 MHz	-61.65 dBm	-48.65 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-32.58 dBm	-19.58 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.55495 MHz	19.86 dBm	-10.14 dB
799.000 MHz	805.000 MHz	6.250 kHz	803.67233 MHz	-61.47 dBm	-26.47 dB

Date: 12.APR.2019 20:07:12

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	759.10440 MHz	-50.36 dBm	-15.36 dB
769.000 MHz	775.000 MHz	6.250 kHz	771.12488 MHz	-61.66 dBm	-48.66 dB
775.000 MHz	788.000 MHz	100.000 kHz	786.96753 MHz	-49.93 dBm	-36.93 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.39011 MHz	19.61 dBm	-10.39 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.85015 MHz	-44.94 dBm	-9.94 dB

Date: 12.APR.2019 20:12:12

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	762.86264 MHz	-50.42 dBm	-15.42 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.27572 MHz	-61.41 dBm	-48.41 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.93 dBm	-20.93 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.44505 MHz	2.41 dBm	-27.59 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.02098 MHz	-48.91 dBm	-13.91 dB

Date: 12.APR.2019 20:05:32

LTE Band 14 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	764.59890 MHz	-50.36 dBm	-15.36 dB
769.000 MHz	775.000 MHz	6.250 kHz	769.59041 MHz	-61.64 dBm	-48.64 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.93 dBm	-20.93 dB
788.000 MHz	799.000 MHz	100.000 kHz	788.57692 MHz	19.79 dBm	-10.21 dB
799.000 MHz	805.000 MHz	6.250 kHz	800.06394 MHz	-61.47 dBm	-26.47 dB

Date: 12.APR.2019 20:17:15

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	764.11538 MHz	-50.39 dBm	-15.39 dB
769.000 MHz	775.000 MHz	6.250 kHz	772.62338 MHz	-61.22 dBm	-48.22 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-50.08 dBm	-37.08 dB
788.000 MHz	799.000 MHz	100.000 kHz	797.41209 MHz	19.65 dBm	-10.35 dB
799.000 MHz	805.000 MHz	6.250 kHz	801.82018 MHz	-44.52 dBm	-9.52 dB

Date: 12.APR.2019 20:18:55

Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
758.000 MHz	769.000 MHz	100.000 kHz	764.63187 MHz	-50.38 dBm	-15.38 dB
769.000 MHz	775.000 MHz	6.250 kHz	774.67932 MHz	-61.50 dBm	-48.50 dB
775.000 MHz	788.000 MHz	100.000 kHz	787.99351 MHz	-33.96 dBm	-20.96 dB
788.000 MHz	799.000 MHz	100.000 kHz	793.32418 MHz	2.31 dBm	-27.69 dB
799.000 MHz	805.000 MHz	6.250 kHz	799.23077 MHz	-49.44 dBm	-14.44 dB

Date: 12.APR.2019 20:15:34

Conducted Spurious Emission

LTE Band 14 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	236.10295 MHz	-59.58 dBm	-46.58 dB
805.000 MHz	1.000 GHz	100.000 kHz	998.68441 MHz	-58.25 dBm	-45.25 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-47.22 dBm	-34.22 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.54980 GHz	-43.46 dBm	-30.46 dB

Date: 12.APR.2019 19:40:05

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	234.28386 MHz	-59.51 dBm	-46.51 dB
805.000 MHz	1.000 GHz	100.000 kHz	977.05022 MHz	-58.42 dBm	-45.42 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-47.35 dBm	-34.35 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.85076 GHz	-43.51 dBm	-30.51 dB

Date: 12.APR.2019 19:40:45

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	737.80810 MHz	-59.66 dBm	-46.66 dB
805.000 MHz	1.000 GHz	100.000 kHz	998.78186 MHz	-58.13 dBm	-45.13 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-46.99 dBm	-33.99 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.54780 GHz	-43.37 dBm	-30.37 dB

Date: 12.APR.2019 19:42:04

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	757.45427 MHz	-59.49 dBm	-46.49 dB
805.000 MHz	1.000 GHz	100.000 kHz	976.85532 MHz	-58.26 dBm	-45.26 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-47.77 dBm	-34.77 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.54430 GHz	-43.51 dBm	-30.51 dB

Date: 12.APR.2019 19:41:25

LTE Band 14 / 5MHz

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	703.97301 MHz	-59.37 dBm	-46.37 dB
805.000 MHz	1.000 GHz	100.000 kHz	982.02024 MHz	-58.21 dBm	-45.21 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-47.10 dBm	-34.10 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.55979 GHz	-43.44 dBm	-30.44 dB

Date: 12.APR.2019 19:50:56

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	735.98901 MHz	-59.49 dBm	-46.49 dB
805.000 MHz	1.000 GHz	100.000 kHz	997.90480 MHz	-58.31 dBm	-45.31 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-47.81 dBm	-34.81 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.55729 GHz	-43.50 dBm	-30.50 dB

Date: 12.APR.2019 19:51:36

LTE Band 14 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	736.71664 MHz	-59.55 dBm	-46.55 dB
805.000 MHz	1.000 GHz	100.000 kHz	947.03523 MHz	-58.28 dBm	-45.28 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57761 GHz	-46.68 dBm	-33.68 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.55479 GHz	-43.49 dBm	-30.49 dB

Date: 12.APR.2019 20:13:31

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	755.63518 MHz	-59.28 dBm	-46.28 dB
805.000 MHz	1.000 GHz	100.000 kHz	990.59595 MHz	-58.17 dBm	-45.17 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-47.75 dBm	-34.75 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.54730 GHz	-43.35 dBm	-30.35 dB

Date: 12.APR.2019 20:12:52

LTE Band 14 / 5MHz

Lowest Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	745.08446 MHz	-59.44 dBm	-46.44 dB
805.000 MHz	1.000 GHz	100.000 kHz	977.63493 MHz	-58.31 dBm	-45.31 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.57711 GHz	-46.97 dBm	-33.97 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.54980 GHz	-43.31 dBm	-30.31 dB

Date: 12.APR.2019 19:55:59

Middle Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	736.35282 MHz	-59.44 dBm	-46.44 dB
805.000 MHz	1.000 GHz	100.000 kHz	977.92729 MHz	-58.30 dBm	-45.30 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58210 GHz	-47.63 dBm	-34.63 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.84527 GHz	-43.37 dBm	-30.37 dB

Date: 12.APR.2019 19:56:39

Highest Channel / 64QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	758.000 MHz	100.000 kHz	736.71664 MHz	-59.42 dBm	-46.42 dB
805.000 MHz	1.000 GHz	100.000 kHz	998.58696 MHz	-58.12 dBm	-45.12 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.58710 GHz	-48.03 dBm	-35.03 dB
3.000 GHz	8.000 GHz	1.000 MHz	7.48980 GHz	-43.48 dBm	-30.48 dB

Date: 12.APR.2019 20:01:25