FCC RADIO TEST REPORT

FCC ID	:	**A4RG1XJ6**
Equipment	:	**Wireless Device**
Model Name	:	**G1XJ6**
Applicant	:	**Google LLC** **1600 Amphitheatre Parkway,** **Mountain View, CA, 94043 USA**
Standard	:	**FCC Part 15 Subpart E §15.407**

The product was received on Jan. 20, 2026 and testing was performed from Jan. 29, 2026 to Mar. 13, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 5
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency and Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 EUT Operation Test Setup 9
2.5 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB & 26dB & 99% Occupied Bandwidth Measurement 11
3.2 Maximum Conducted Output Power Measurement 13
3.3 Power Spectral Density Measurement 15
3.4 Unwanted Emissions Measurement 18
3.5 AC Conducted Emission Measurement 22
3.6 Antenna Requirements 24
4 List of Measuring Equipment **25**
5 Measurement Uncertainty **27**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Data
Appendix D. Duty Cycle Plots
Appendix E. Spot Check Evaluation on G1XJ6
Appendix F. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR5O3008E	01	Initial issue of report	Apr. 01, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	-
3.5	15.207	AC Conducted Emission	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. ECR inquiry for data referencing from A4RG0F3Y has been approved by FCC. The ECR inquiry and the associated document are submitted in the confidential exhibit.
2. A4RG1XJ6 is different from FCC ID: A4RG0F3Y (Reference model), in the following:
   i. The only difference between A4RG0F3Y and A4RG1XJ6 are the LTE and NTN function, which is depopulated by hardware.
3. All the test results are referenced from A4RG0F3Y (Sporton Test Report FR5O3007E), and spot check results to justify data referencing is presented in the Appendix E.
4. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
5. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Shiori Chen

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Bluetooth-LE, Bluetooth-LE ASK, Bluetooth-LE GFSK, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, UWB, 60GHz and GNSS. **Antenna Type** WLAN: PIFA Antenna

EUT Information List	
S/N	**Performed Test Item**
58011WRDQL10KA	RF Conducted Measurement
5C251WRDQL13PF	Radiated Spurious Emission
5C261WRDQL13RY	Conducted Emission

Antenna information		
5150 MHz ~ 5850 MHz	Peak Gain (dBi)	-0.1

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- FCC Part 15 Subpart E
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z plane with Adapter as worst plane.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42#	5210		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5250-5350 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58#	5290		

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5470-5725 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106#	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122#	5610	128	5640

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	138#	5690	144	5720
	142*	5710		

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "#" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

This device support 26/52/106/242/484/996-tone RU.

The PSD of partial RU is reduced to be smaller than full RU according to TCB workshop interim guidance Oct. 2022.

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The 242-tone RU is covered by 20MHz channel, 484-tone RU is covered by 40MHz channel and 996-tone RU is covered by 80MHz channel.

The power for 802.11ac VHT20/40 mode is smaller than 802.11n mode, so all other conducted and radiated test is covered by 802.11n mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11a	**6 Mbps**
802.11n HT20	**MCS0**
802.11n HT40	**MCS0**
802.11ac VHT20 (Covered by HT20)	**MCS0**
802.11ac VHT40 (Covered by HT40)	**MCS0**
802.11ac VHT80	**MCS0**
802.11ax HE20	**MCS0**
802.11ax HE40	**MCS0**
802.11ax HE80	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1: WLAN (5GHz_11a Ch36) Tx + USB Cable (Charging from Adapter)

Remark:
1. The detailed Radiated test modes are shown in Appendix C.
2. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

The RF test items, utility “adb version 1.0.41” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB & 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The 6 dB bandwidth shall be at least 500kHz for 5725-5850MHz.

There is no restriction limits for 26dB and 99% Occupied bandwidth.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules **v02r01**, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
8. Measure and record the results in the test report.
9. For 6dB Bandwidth Measurement
   (1) The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
   (2) Section C) Emission bandwidth for the band 5.725-5.85 GHz
   (3) Set RBW = 100 kHz.
   (4) Set the VBW ≥ 3 x RBW.
   (5) Detector = Peak.
   (6) Trace mode = max hold
   (7) Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
   (8) Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the 5.15–5.25 GHz bands:

■ For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For the 5.25–5.725 GHz bands:

■ The maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

For the band 5.725–5.85 GHz bands:

■ The maximum conducted output power over the frequency band of operation shall not exceed 1 W.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the 5.15–5.25 GHz bands:

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band. For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1.0 MHz band.

For the 5.25–5.725 GHz bands:

The maximum power spectral density shall not exceed 11 dBm in any 1.0 MHz band.

For the 5.725–5.85 GHz bands:

The maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

For Straddle Channel, according to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, if the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

For the band 5.15-5.725 GHz

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW ≥ 3 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

For the band 5.725–5.85 GHz

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 500kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of –27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.
For transmitters operating in the 5.725-5.85 GHz band:
15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.
   (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.(3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LOOP Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Feb. 03, 2026~ Mar. 05, 2026	Dec. 10, 2026	Radiation (03CH21-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63303 & 001	30MHz~1GHz	Nov. 26, 2025	Feb. 03, 2026~ Mar. 05, 2026	Nov. 25, 2026	Radiation (03CH21-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C03A18 EN	1GHz~18GHz	Aug. 07, 2025	Feb. 03, 2026~ Mar. 05, 2026	Aug. 06, 2026	Radiation (03CH21-HY)
SHF-EHF Horn Antenna	SCHWARZBEC K	BBHA 9170	1223	18GHz~40GHz	Jul. 02, 2025	Feb. 03, 2026~ Mar. 05, 2026	Jul. 01, 2026	Radiation (03CH21-HY)
Amplifier	SONOMA	310N	421580	30MHz~1GHz	Jul. 13, 2025	Feb. 03, 2026~ Mar. 05, 2026	Jul. 12, 2026	Radiation (03CH21-HY)
Amplifier	EMEC	EM01G18GA	060876	1GHz~18GHz	Sep. 26, 2025	Feb. 03, 2026~ Mar. 05, 2026	Sep. 25, 2026	Radiation (03CH21-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Aug. 26, 2025	Feb. 03, 2026~ Mar. 05, 2026	Aug. 25, 2026	Radiation (03CH21-HY)
EXA Signal Analyzer	Keysight	N9010B	MY6217035 8	10Hz~44GHz	Sep. 09, 2025	Feb. 03, 2026~ Mar. 05, 2026	Sep. 08, 2026	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Feb. 03, 2026~ Mar. 03, 2026	Mar. 04, 2026	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 04, 2026	Mar. 04, 2026~ Mar. 05, 2026	Mar. 03, 2027	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804397/2,80 4612/2,8039 54/2	30MHz~40GHz	Aug. 11, 2025	Feb. 03, 2026~ Mar. 05, 2026	Aug. 10, 2026	Radiation (03CH21-HY)
RF Cable	EMCI	EMC101Y-KM-KM-1000	240906	30MHz~40GHz	Oct. 21, 2025	Feb. 03, 2026~ Mar. 05, 2026	Oct. 20, 2026	Radiation (03CH21-HY)
Hygrometer	TECPEL	DTM-303A	TP211568	N/A	Oct. 21, 2025	Feb. 03, 2026~ Mar. 05, 2026	Oct. 20, 2026	Radiation (03CH21-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Feb. 03, 2026~ Mar. 05, 2026	N/A	Radiation (03CH21-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Feb. 03, 2026~ Mar. 05, 2026	N/A	Radiation (03CH21-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Feb. 03, 2026~ Mar. 05, 2026	N/A	Radiation (03CH21-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Feb. 03, 2026~ Mar. 05, 2026	N/A	Radiation (03CH21-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Jan. 29, 2026~ Mar. 11, 2026	Nov. 03, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SN O37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Jan. 29, 2026~ Mar. 11, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101467	10HZ~44GHZ	Dec. 16, 2025	Jan. 29, 2026~ Mar. 11, 2026	Dec. 15, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900067 (BOX7)	N/A	Jul. 02, 2025	Jan. 29, 2026~ Mar. 11, 2026	Jul. 01, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24051 3	N/A	Conducted Other Test Item	N/A	Jan. 29, 2026~ Mar. 11, 2026	N/A	Conducted (TH05-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 13, 2026	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 13, 2026	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Mar. 13, 2026	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 2, 2026	Mar. 13, 2026	Mar. 1, 2027	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Mar. 13, 2026	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	Mar. 13, 2026	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 21, 2025	Mar. 13, 2026	Oct. 20, 2026	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.4 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.8 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.3 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2026/1/29~2026/3/11	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

U-NII-1 single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)			Note
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	18.65	-	31.02	-	-		22.71	-	-	
11a	6Mbps	1	44	5220	19.24	-	35.66	-	-		22.84	-		
11a	6Mbps	1	48	5240	19.68	-	38.03	-	-		22.94	-		
HT20	MCS0	1	36	5180	19.44	-	35.49	-	-		22.89	-		
HT20	MCS0	1	44	5220	20.09	-	44.14	-	-		23.01	-		
HT20	MCS0	1	48	5240	19.77	-	45.12	-	-		22.96	-		
HT40	MCS0	1	38	5190	37.49	-	75.31	-	-		23.01	-		
HT40	MCS0	1	46	5230	37.76	-	80.94	-	-		23.01	-		
VHT80	MCS0	1	42	5210	76.08	-	87.55	-	-		23.01	-		

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	17.30	-	-	24.00	-	-0.10	-	-	Pass
11a	6Mbps	1	44	5220	17.60	-		24.00	-	-0.10	-		Pass
11a	6Mbps	1	48	5240	17.60	-		24.00	-	-0.10	-		Pass
HT20	MCS0	1	36	5180	17.30	-		24.00	-	-0.10	-		Pass
HT20	MCS0	1	44	5220	17.60	-		24.00	-	-0.10	-		Pass
HT20	MCS0	1	48	5240	17.90	-		24.00	-	-0.10	-		Pass
HT40	MCS0	1	38	5190	15.10	-		24.00	-	-0.10	-		Pass
HT40	MCS0	1	46	5230	16.90	-		24.00	-	-0.10	-		Pass
VHT20	MCS0	1	36	5180	17.20	-		24.00	-	-0.10	-		Pass
VHT20	MCS0	1	44	5220	17.50	-		24.00	-	-0.10	-		Pass
VHT20	MCS0	1	48	5240	17.80	-		24.00	-	-0.10	-		Pass
VHT40	MCS0	1	38	5190	15.00	-		24.00	-	-0.10	-		Pass
VHT40	MCS0	1	46	5230	16.80	-		24.00	-	-0.10	-		Pass
VHT80	MCS0	1	42	5210	14.40	-		24.00	-	-0.10	-		Pass

TEST RESULTS DATA
Power Spectral Density

FCC U-NII-1 single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	36	5180	0.43	-	5.15	-		11.00	-	-0.10	-		Pass
11a	6Mbps	1	44	5220	0.43	-	5.55	-		11.00	-	-0.10	-		Pass
11a	6Mbps	1	48	5240	0.43	-	5.47	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	36	5180	0.46	-	4.93	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	44	5220	0.46	-	5.35	-	-	11.00	-	-0.10	-	-	Pass
HT20	MCS0	1	48	5240	0.46	-	5.57	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	38	5190	0.48	-	0.11	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	46	5230	0.48	-	1.59	-		11.00	-	-0.10	-		Pass
VHT80	MCS0	1	42	5210	0.52	-	-3.09	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2A single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	52	5260	19.89	-	38.51	-	23.98	-	29.99	-	23.98	-	-
11a	6Mbps	1	60	5300	20.35	-	39.89	-	23.98	-	30.00	-	23.98	-	
11a	6Mbps	1	64	5320	19.02	-	35.47	-	23.79	-	29.79	-	23.98	-	
HT20	MCS0	1	52	5260	20.98	-	43.62	-	23.98	-	30.00	-	23.98	-	
HT20	MCS0	1	60	5300	21.13	-	45.10	-	23.98	-	30.00	-	23.98	-	
HT20	MCS0	1	64	5320	19.62	-	41.13	-	23.93	-	29.93	-	23.98	-	
HT40	MCS0	1	54	5270	37.52	-	77.34	-	23.98	-	30.00	-	23.98	-	
HT40	MCS0	1	62	5310	37.07	-	66.14	-	23.98	-	30.00	-	23.98	-	
VHT80	MCS0	1	58	5290	76.11	-	83.49	-	23.98	-	30.00	-	23.98	-	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	52	5260	17.80	-	-	23.98	-	-0.10	-	30	Pass
11a	6Mbps	1	60	5300	17.70	-		23.98	-	-0.10	-	30	Pass
11a	6Mbps	1	64	5320	17.50	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	52	5260	17.70	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	60	5300	17.80	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	64	5320	17.20	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	54	5270	16.90	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	62	5310	14.40	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	52	5260	17.60	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	60	5300	17.70	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	64	5320	17.10	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	54	5270	16.80	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	62	5310	14.30	-		23.98	-	-0.10	-	30	Pass
VHT80	MCS0	1	58	5290	14.10	-		23.98	-	-0.10	-	30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2A single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	52	5260	0.43	-	5.77	-		11.00	-	-0.10	-		Pass
11a	6Mbps	1	60	5300	0.43	-	5.70	-		11.00	-	-0.10	-		Pass
11a	6Mbps	1	64	5320	0.43	-	5.49	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	52	5260	0.46	-	5.37	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	60	5300	0.46	-	5.40	-	-	11.00	-	-0.10	-	-	Pass
HT20	MCS0	1	64	5320	0.46	-	5.02	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	54	5270	0.48	-	1.48	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	62	5310	0.48	-	-0.62	-		11.00	-	-0.10	-		Pass
VHT80	MCS0	1	58	5290	0.52	-	-3.32	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2C single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
11a	6Mbps	1	100	5500	21.77	-	40.12	-	23.98	-	30.00	-	23.98	-	----	----
11a	6Mbps	1	120	5600	23.41	-	43.37	-	23.98	-	30.00	-	23.98	-	----	----
11a	6Mbps	1	140	5700	18.30	-	29.85	-	23.63	-	29.63	-	23.98	-	----	----
HT20	MCS0	1	100	5500	22.43	-	44.06	-	23.98	-	30.00	-	23.98	-	----	----
HT20	MCS0	1	120	5600	25.42	-	47.35	-	23.98	-	30.00	-	23.98	-	----	----
HT20	MCS0	1	140	5700	19.12	-	38.01	-	23.81	-	29.81	-	23.98	-	----	----
HT40	MCS0	1	102	5510	37.90	-	82.77	-	23.98	-	30.00	-	23.98	-	----	----
HT40	MCS0	1	118	5590	38.75	-	88.83	-	23.98	-	30.00	-	23.98	-	----	----
HT40	MCS0	1	134	5670	38.30	-	86.66	-	23.98	-	30.00	-	23.98	-	----	----
VHT80	MCS0	1	106	5530	76.54	-	139.49	-	23.98	-	30.00	-	23.98	-	----	----
VHT80	MCS0	1	122	5610	76.59	-	159.52	-	23.98	-	30.00	-	23.98	-	----	----

U-NII-2C straddle channel single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
11a	6Mbps	1	144	5720	15.58	-	26.14	-	23.98	-	30.00	-	23.98	-	3.21	-
HT20	MCS0	1	144	5720	17.46	-	28.76	-	23.98	-	30.00	-	23.98	-	3.91	-
HT40	MCS0	1	142	5710	33.98	-	57.54	-	23.98	-	30.00	-	23.98	-	3.36	-
VHT80	MCS0	1	138	5690	73.26	-	108.31	-	23.98	-	30.00	-	23.98	-	3.096	-

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	100	5500	17.90	-	-	23.98	-	-0.10	-	30	Pass
11a	6Mbps	1	120	5600	17.70	-		23.98	-	-0.10	-	30	Pass
11a	6Mbps	1	140	5700	15.80	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	100	5500	17.70	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	120	5600	17.70	-		23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	140	5700	15.90	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	102	5510	16.80	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	118	5590	17.10	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	134	5670	16.90	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	100	5500	17.60	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	120	5600	17.60	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	140	5700	15.80	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	102	5510	16.70	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	118	5590	17.00	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	134	5670	16.80	-		23.98	-	-0.10	-	30	Pass
VHT80	MCS0	1	106	5530	16.20	-		23.98	-	-0.10	-	30	Pass
VHT80	MCS0	1	122	5610	16.10	-		23.98	-	-0.10	-	30	Pass

FCC U-NII-2C straddle channel single antenna													
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	144	5720	17.70	-	-	23.98	-	-0.10	-	30	Pass
HT20	MCS0	1	144	5720	17.90	-		23.98	-	-0.10	-	30	Pass
HT40	MCS0	1	142	5710	17.20	-		23.98	-	-0.10	-	30	Pass
VHT20	MCS0	1	144	5720	17.80	-		23.98	-	-0.10	-	30	Pass
VHT40	MCS0	1	142	5710	17.10	-		23.98	-	-0.10	-	30	Pass
VHT80	MCS0	1	138	5690	16.30	-		23.98	-	-0.10	-	30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2C single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	100	5500	0.43	-	5.73	-	-	11.00	-	-0.10	-	-	Pass
11a	6Mbps	1	120	5600	0.43	-	5.72	-		11.00	-	-0.10	-		Pass
11a	6Mbps	1	140	5700	0.43	-	4.08	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	100	5500	0.46	-	5.41	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	120	5600	0.46	-	5.35	-		11.00	-	-0.10	-		Pass
HT20	MCS0	1	140	5700	0.46	-	3.70	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	102	5510	0.48	-	2.07	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	118	5590	0.48	-	2.25	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	134	5670	0.48	-	2.19	-		11.00	-	-0.10	-		Pass
VHT80	MCS0	1	106	5530	0.52	-	-1.50	-		11.00	-	-0.10	-		Pass
VHT80	MCS0	1	122	5610	0.52	-	-1.55	-		11.00	-	-0.10	-		Pass

U-NII-2C straddle channel single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	144	5720	0.43	-	5.62	-	-	11.00	-	-0.10	-	-	Pass
HT20	MCS0	1	144	5720	0.46	-	5.55	-		11.00	-	-0.10	-		Pass
HT40	MCS0	1	142	5710	0.48	-	2.05	-		11.00	-	-0.10	-		Pass
VHT80	MCS0	1	138	5690	0.52	-	-1.21	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-1 single antenna															
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)			Note
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	19.54	-	35.56	-	-		22.91	-	-	-
HE20	MCS0	1	44	5220	Full	19.67	-	39.11	-	-		22.94	-		
HE20	MCS0	1	48	5240	Full	19.74	-	40.79	-	-		22.95	-		
HE40	MCS0	1	38	5190	Full	37.90	-	41.97	-	-		23.01	-		
HE40	MCS0	1	46	5230	Full	38.03	-	53.68	-	-		23.01	-		
HE80	MCS0	1	42	5210	Full	77.43	-	83.36	-	-		23.01	-		

TEST RESULTS DATA
Average Power Table

FCC U-NII-1 single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)			Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	16.60	-	-	24.00	-	-0.10	-	-	Pass
HE20	MCS0	1	36	5180	26/0	7.50	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	36	5180	52/37	10.20	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	36	5180	106/53	13.20	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	Full	17.30	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	26/4	8.40	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	52/38	11.00	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	106/53	14.00	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	Full	17.30	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	26/8	7.70	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	52/40	10.50	-		24.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	106/54	13.60	-		24.00	-	-0.10	-		Pass
HE40	MCS0	1	38	5190	Full	14.20	-		24.00	-	-0.10	-		Pass
HE40	MCS0	1	46	5230	Full	16.60	-		24.00	-	-0.10	-		Pass
HE80	MCS0	1	42	5210	Full	14.50	-		24.00	-	-0.10	-		Pass

TEST RESULTS DATA
Power Spectral Density

FCC U-NII-1 single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	36	5180	Full	0.58	-	4.55	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	36	5180	26/0	0.77	-	4.18	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	36	5180	52/37	0.78	-	4.20	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	36	5180	106/53	0.85	-	4.23	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	Full	0.58	-	5.11	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	26/4	0.77	-	4.83	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	52/38	0.78	-	4.97	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	44	5220	106/53	0.85	-	4.88	-	-	11.00	-	-0.10	-	-	Pass
HE20	MCS0	1	48	5240	Full	0.58	-	5.06	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	26/8	0.77	-	4.64	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	52/40	0.78	-	4.61	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	48	5240	106/54	0.85	-	4.76	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	38	5190	Full	0.59	-	-1.17	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	46	5230	Full	0.59	-	1.39	-		11.00	-	-0.10	-		Pass
HE80	MCS0	1	42	5210	Full	0.62	-	-2.94	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2A single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26 dB Bandwidth (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		Note
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	1	52	5260	Full	19.68	-	41.58	-	23.94	-	29.94	-	23.98	-	
HE20	MCS0	1	60	5300	Full	19.67	-	41.30	-	23.94	-	29.94	-	23.98	-	
HE20	MCS0	1	64	5320	Full	19.80	-	38.99	-	23.97	-	29.97	-	23.98	-	
HE40	MCS0	1	54	5270	Full	37.97	-	52.45	-	23.98	-	30.00	-	23.98	-	
HE40	MCS0	1	62	5310	Full	37.91	-	42.51	-	23.98	-	30.00	-	23.98	-	
HE80	MCS0	1	58	5290	Full	77.48	-	82.88	-	23.98	-	30.00	-	23.98	-	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2A single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	52	5260	Full	17.20	-	-	23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	52	5260	26/0	8.20	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	52	5260	52/37	10.70	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	52	5260	106/53	14.10	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	60	5300	Full	17.10	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	60	5300	26/4	8.80	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	60	5300	52/38	10.80	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	60	5300	106/53	13.80	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	64	5320	Full	17.20	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	64	5320	26/8	7.60	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	64	5320	52/40	11.10	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	64	5320	106/54	13.90	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	54	5270	Full	16.40	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	62	5310	Full	14.50	-		23.98	-	-0.10	-	30	Pass
HE80	MCS0	1	58	5290	Full	14.20	-		23.98	-	-0.10	-	30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2A single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	52	5260	Full	0.58	-	5.13	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	52	5260	26/0	0.77	-	4.92	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	52	5260	52/37	0.78	-	4.81	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	52	5260	106/53	0.85	-	5.02	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	60	5300	Full	0.58	-	4.93	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	60	5300	26/4	0.77	-	4.71	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	60	5300	52/38	0.78	-	4.60	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	60	5300	106/53	0.85	-	4.75	-	-	11.00	-	-0.10	-	-	Pass
HE20	MCS0	1	64	5320	Full	0.58	-	5.19	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	64	5320	26/8	0.77	-	4.82	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	64	5320	52/40	0.78	-	5.18	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	64	5320	106/54	0.85	-	4.85	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	54	5270	Full	0.59	-	1.10	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	62	5310	Full	0.59	-	-0.84	-		11.00	-	-0.10	-		Pass
HE80	MCS0	1	58	5290	Full	0.62	-	-3.39	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
26dB and 99% OBW

U-NII-2C single antenna																	
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
HE20	MCS0	1	100	5500	Full	19.84	-	41.62	-	23.98	-	29.98	-	23.98	-	----	----
HE20	MCS0	1	120	5600	Full	20.18	-	45.65	-	23.98	-	30.00	-	23.98	-	----	----
HE20	MCS0	1	140	5700	Full	19.36	-	29.98	-	23.87	-	29.87	-	23.98	-	----	----
HE40	MCS0	1	102	5510	Full	38.18	-	69.78	-	23.98	-	30.00	-	23.98	-	----	----
HE40	MCS0	1	118	5590	Full	38.22	-	66.98	-	23.98	-	30.00	-	23.98	-	----	----
HE40	MCS0	1	134	5670	Full	38.30	-	68.96	-	23.98	-	30.00	-	23.98	-	----	----
HE80	MCS0	1	106	5530	Full	77.78	-	134.21	-	23.98	-	30.00	-	23.98	-	----	----
HE80	MCS0	1	122	5610	Full	77.79	-	153.82	-	23.98	-	30.00	-	23.98	-	----	----

U-NII-2C straddle channel single antenna																	
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	99% Bandwidth In U-NII 2C (MHz)		26 dB Bandwidth In U-NII 2C (MHz)		IC 99% Bandwidth Power Limit (dBm)		IC 99% Bandwidth EIRP Limit (dBm)		FCC 26dB Bandwidth Power Limit (dBm)		6 dB Bandwidth for Straddle Channel (MHz)	
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1
HE20	MCS0	1	144	5720	Full	15.00	-	26.80	-	23.98	-	30.00	-	23.98	-	4.5	-
HE40	MCS0	1	142	5710	Full	34.10	-	44.42	-	23.98	-	30.00	-	23.98	-	3.9	-
HE80	MCS0	1	138	5690	Full	73.88	-	100.98	-	23.98	-	30.00	-	23.98	-	3.592	-
6dB Bandwidth Limit ≧ 500kHz																Pass	

TEST RESULTS DATA
Average Power Table

FCC U-NII-2C single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	100	5500	Full	17.40	-	-	23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	100	5500	26/0	8.40	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	100	5500	52/37	11.40	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	100	5500	106/53	14.20	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	120	5600	Full	17.20	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	120	5600	26/4	8.80	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	120	5600	52/38	10.80	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	120	5600	106/53	13.90	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	140	5700	Full	14.30	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	140	5700	26/8	5.00	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	140	5700	52/40	7.60	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	140	5700	106/54	10.40	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	102	5510	Full	16.70	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	118	5590	Full	16.40	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	134	5670	Full	16.60	-		23.98	-	-0.10	-	30	Pass
HE80	MCS0	1	106	5530	Full	16.30	-		23.98	-	-0.10	-	30	Pass
HE80	MCS0	1	122	5610	Full	16.20	-		23.98	-	-0.10	-	30	Pass

FCC U-NII-2C straddle channel single antenna														
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		EIRP Power Limit (dBm)	Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	144	5720	Full	17.40	-	-	23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	144	5720	26/8	8.10	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	144	5720	52/40	10.50	-		23.98	-	-0.10	-	30	Pass
HE20	MCS0	1	144	5720	106/54	14.10	-		23.98	-	-0.10	-	30	Pass
HE40	MCS0	1	142	5710	Full	16.70	-		23.98	-	-0.10	-	30	Pass
HE80	MCS0	1	138	5690	Full	16.40	-		23.98	-	-0.10	-	30	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-2C single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	100	5500	Full	0.58	-	5.41	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	100	5500	26/0	0.77	-	5.18	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	100	5500	52/37	0.78	-	5.34	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	100	5500	106/53	0.85	-	5.05	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	120	5600	Full	0.58	-	4.89	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	120	5600	26/4	0.77	-	4.82	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	120	5600	52/38	0.78	-	4.83	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	120	5600	106/53	0.85	-	4.85	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	140	5700	Full	0.58	-	1.86	-	-	11.00	-	-0.10	-	-	Pass
HE20	MCS0	1	140	5700	26/8	0.77	-	1.62	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	140	5700	52/40	0.78	-	1.77	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	140	5700	106/54	0.85	-	1.59	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	102	5510	Full	0.59	-	1.42	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	118	5590	Full	0.59	-	0.94	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	134	5670	Full	0.59	-	1.35	-		11.00	-	-0.10	-		Pass
HE80	MCS0	1	106	5530	Full	0.62	-	-1.50	-		11.00	-	-0.10	-		Pass
HE80	MCS0	1	122	5610	Full	0.62	-	-1.67	-		11.00	-	-0.10	-		Pass

U-NII-2C straddle channel single antenna																
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density (dBm/MHz)			Average PSD Limit (dBm/MHz)		DG (dBi)			Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	144	5720	Full	0.58	-	5.12	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	144	5720	26/8	0.77	-	5.06	-		11.00	-	-0.10	-		Pass
HE20	MCS0	1	144	5720	52/40	0.78	-	4.68	-	-	11.00	-	-0.10	-	-	Pass
HE20	MCS0	1	144	5720	106/54	0.85	-	4.98	-		11.00	-	-0.10	-		Pass
HE40	MCS0	1	142	5710	Full	0.59	-	1.22	-		11.00	-	-0.10	-		Pass
HE80	MCS0	1	138	5690	Full	0.62	-	-1.26	-		11.00	-	-0.10	-		Pass

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
11a	6Mbps	1	149	5745	22.26	-	41.88	-	16.55	-	0.5	Pass
11a	6Mbps	1	157	5785	22.12	-	41.23	-	16.48	-	0.5	Pass
11a	6Mbps	1	165	5825	21.12	-	38.85	-	16.52	-	0.5	Pass
HT20	MCS0	1	149	5745	23.45	-	46.35	-	17.98	-	0.5	Pass
HT20	MCS0	1	157	5785	23.66	-	45.84	-	18.00	-	0.5	Pass
HT20	MCS0	1	165	5825	22.50	-	44.21	-	18.02	-	0.5	Pass
HT40	MCS0	1	151	5755	38.17	-	84.27	-	36.49	-	0.5	Pass
HT40	MCS0	1	159	5795	38.28	-	92.10	-	36.50	-	0.5	Pass
VHT80	MCS0	1	155	5775	76.43	-	154.66	-	76.00	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	149	5745	17.80	-		30.00	-	-0.10	-	Pass
11a	6Mbps	1	157	5785	17.90	-		30.00	-	-0.10	-	Pass
11a	6Mbps	1	165	5825	17.70	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	149	5745	17.80	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	157	5785	17.90	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	165	5825	17.70	-		30.00	-	-0.10	-	Pass
HT40	MCS0	1	151	5755	17.20	-		30.00	-	-0.10	-	Pass
HT40	MCS0	1	159	5795	16.90	-		30.00	-	-0.10	-	Pass
VHT20	MCS0	1	149	5745	17.70	-		30.00	-	-0.10	-	Pass
VHT20	MCS0	1	157	5785	17.80	-		30.00	-	-0.10	-	Pass
VHT20	MCS0	1	165	5825	17.60	-		30.00	-	-0.10	-	Pass
VHT40	MCS0	1	151	5755	17.10	-		30.00	-	-0.10	-	Pass
VHT40	MCS0	1	159	5795	16.80	-		30.00	-	-0.10	-	Pass
VHT80	MCS0	1	155	5775	16.20	-		30.00	-	-0.10	-	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
11a	6Mbps	1	149	5745	0.43		3.00	-		30.00	-	-0.10	-	Pass
11a	6Mbps	1	157	5785	0.43		2.62	-		30.00	-	-0.10	-	Pass
11a	6Mbps	1	165	5825	0.43		2.66	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	149	5745	0.46		2.41	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	157	5785	0.46		2.43	-		30.00	-	-0.10	-	Pass
HT20	MCS0	1	165	5825	0.46		2.11	-		30.00	-	-0.10	-	Pass
HT40	MCS0	1	151	5755	0.48		-0.94	-		30.00	-	-0.10	-	Pass
HT40	MCS0	1	159	5795	0.48		-1.28	-		30.00	-	-0.10	-	Pass
VHT80	MCS0	1	155	5775	0.52		-4.73	-		30.00	-	-0.10	-	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 0	Ant 1	Ant 0	Ant 1	Ant 0	Ant 1		
HE20	MCS0	1	149	5745	Full	19.90	-	42.71	-	19.14	-	0.5	Pass
HE20	MCS0	1	157	5785	Full	19.94	-	44.51	-	19.13	-	0.5	Pass
HE20	MCS0	1	165	5825	Full	19.77	-	40.84	-	19.12	-	0.5	Pass
HE40	MCS0	1	151	5755	Full	38.17	-	71.57	-	37.63	-	0.5	Pass
HE40	MCS0	1	159	5795	Full	38.21	-	76.90	-	37.91	-	0.5	Pass
HE80	MCS0	1	155	5775	Full	77.67	-	131.39	-	76.99	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	1	149	5745	Full	17.20	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	26/0	7.90	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	52/37	11.00	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	106/53	13.50	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	Full	17.30	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	26/4	8.40	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	52/38	10.80	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	106/53	13.80	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	Full	17.10	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	26/8	7.70	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	52/40	10.50	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	106/54	13.40	-		30.00	-	-0.10	-	Pass
HE40	MCS0	1	151	5755	Full	16.70	-		30.00	-	-0.10	-	Pass
HE40	MCS0	1	159	5795	Full	16.60	-		30.00	-	-0.10	-	Pass
HE80	MCS0	1	155	5775	Full	16.30	-		30.00	-	-0.10	-	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 0	Ant 1	Ant 0	Ant 1	SUM	Ant 0	Ant 1	Ant 0	Ant 1	
HE20	MCS0	1	149	5745	Full	0.58	-	1.86	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	26/0	0.77	-	1.51	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	52/37	0.78	-	1.83	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	149	5745	106/53	0.85	-	1.69	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	Full	0.58	-	2.04	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	26/4	0.77	-	2.00	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	52/38	0.78	-	1.70	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	157	5785	106/53	0.85	-	1.89	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	Full	0.58	-	1.60	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	26/8	0.77	-	1.39	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	52/40	0.78	-	1.55	-		30.00	-	-0.10	-	Pass
HE20	MCS0	1	165	5825	106/54	0.85	-	1.26	-		30.00	-	-0.10	-	Pass
HE40	MCS0	1	151	5755	Full	0.59	-	-1.51	-		30.00	-	-0.10	-	Pass
HE40	MCS0	1	159	5795	Full	0.59	-	-1.83	-		30.00	-	-0.10	-	Pass
HE80	MCS0	1	155	5775	Full	0.62	-	-4.38	-		30.00	-	-0.10	-	Pass

Note: PSD Sum = Max PSD(Ant. 1, Ant. 2) + 10 log (n)

<Band 1-3>

Test Result of 26dB & 99% Occupied Bandwidth

SISO <Ant. 0>

<802.11a>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11n HT20>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11n HT40>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ac VHT80>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE20>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE40>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11ax HE80>

26dB Bandwidth	99% Occupied Bandwidth
	

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Test Result of Power Spectral Density

<802.11a>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11n HT20>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11n HT40>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11ac VHT80>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11ax HE20>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11ax HE40>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<802.11ax HE80>

Maximum Power Density Plot Trace 1 (Ant 0)	Maximum Power Density Plot Trace 2 (Ant 1)
	

<Band 4>

Test Result of 6dB and 26dB and 99% Occupied Bandwidth

SISO <Ant. 0>

<802.11a>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11n HT20>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11n HT40>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ac VHT80>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE20>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE40>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

<802.11ax HE80>

6dB Bandwidth	26dB Bandwidth
	
99% Occupied Bandwidth	**N/A**
	

Test Result of Power Spectral Density

<802.11a>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	**Ant. 1**
	

<802.11n HT20>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	**Ant. 1**
	

<802.11n HT40>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	**Ant. 1**
	

<802.11ac VHT80>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	**Ant. 1**
	

<802.11ax HE20>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	Ant. 1
	

<802.11ax HE40>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	Ant. 1
	

<802.11ax HE80>

Maximum Power Density Plot (dBm/500kHz)	
Ant. 0	**Ant. 1**
	

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	**Temperature :**	17.2~23.6℃
		Relative Humidity :	46.7~49.9%

EUT Information

Report NO :	5O3008
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	24.31	55.88	31.57	L1	ON	20.0
0.152250	43.10	---	65.88	22.78	L1	ON	20.0
0.163500	---	20.10	55.28	35.18	L1	ON	20.0
0.163500	37.38	---	65.28	27.90	L1	ON	20.0
0.197250	---	18.64	53.73	35.09	L1	ON	20.0
0.197250	32.23	---	63.73	31.50	L1	ON	20.0
0.683250	---	15.42	46.00	30.58	L1	ON	20.0
0.683250	18.05	---	56.00	37.95	L1	ON	20.0
2.960250	---	16.88	46.00	29.12	L1	ON	20.1
2.960250	19.30	---	56.00	36.70	L1	ON	20.1
21.720750	---	19.26	50.00	30.74	L1	ON	20.9
21.720750	22.93	---	60.00	37.07	L1	ON	20.9

EUT Information

Report NO :	5O3008
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	23.61	55.88	32.27	N	ON	20.0
0.152250	41.66	---	65.88	24.22	N	ON	20.0
0.170250	---	19.14	54.95	35.81	N	ON	20.0
0.170250	37.78	---	64.95	27.17	N	ON	20.0
0.199500	---	17.82	53.63	35.81	N	ON	20.0
0.199500	30.56	---	63.63	33.07	N	ON	20.0
0.685500	---	14.71	46.00	31.29	N	ON	20.0
0.685500	16.98	---	56.00	39.02	N	ON	20.0
2.978250	---	16.42	46.00	29.58	N	ON	20.1
2.978250	18.92	---	56.00	37.08	N	ON	20.1
21.770250	---	19.48	50.00	30.52	N	ON	20.9
21.770250	24.30	---	60.00	35.70	N	ON	20.9

Appendix C. Radiated Spurious Emission Test Data

Test Engineer:	Jack Cheng, Ray Lung	**Temperature:**	21.1 ~ 25.7°C
		Relative Humidity:	55.8 ~ 63.2%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1-1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	U-NII-1	5.15-5.25	0	802.11a	36	5180	6Mbps	-	-
Mode 2	U-NII-1	5.15-5.25	0	802.11a	44	5220	6Mbps	-	-
Mode 3	U-NII-1	5.15-5.25	0	802.11a	48	5240	6Mbps	-	-
Mode 4	U-NII-1	5.15-5.25	0	802.11n HT20	36	5180	MCS0	-	-
Mode 5	U-NII-1	5.15-5.25	0	802.11n HT20	44	5220	MCS0	-	-
Mode 6	U-NII-1	5.15-5.25	0	802.11n HT20	48	5240	MCS0	-	-
Mode 7	U-NII-1	5.15-5.25	0	802.11n HT40	38	5190	MCS0	-	-
Mode 8	U-NII-1	5.15-5.25	0	802.11n HT40	46	5230	MCS0	-	-
Mode 9	U-NII-1	5.15-5.25	0	802.11ac VHT80	42	5210	MCS0	-	-
Mode 10	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	Full	-
Mode 11	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	26/0	-
Mode 12	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	52/37	-
Mode 13	U-NII-1	5.15-5.25	0	802.11ax HE20	36	5180	MCS0	106/53	-
Mode 14	U-NII-1	5.15-5.25	0	802.11ax HE20	44	5220	MCS0	Full	-
Mode 15	U-NII-1	5.15-5.25	0	802.11ax HE20	48	5240	MCS0	Full	-
Mode 16	U-NII-1	5.15-5.25	0	802.11ax HE40	38	5190	MCS0	Full	-
Mode 17	U-NII-1	5.15-5.25	0	802.11ax HE40	46	5230	MCS0	Full	-

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 18	U-NII-1	5.15-5.25	0	802.11ax HE80	42	5210	MCS0	Full	-
Mode 19	U-NII-2A	5.25-5.35	0	802.11a	52	5260	6Mbps	-	-
Mode 20	U-NII-2A	5.25-5.35	0	802.11a	60	5300	6Mbps	-	-
Mode 21	U-NII-2A	5.25-5.35	0	802.11a	64	5320	6Mbps	-	-
Mode 22	U-NII-2A	5.25-5.35	0	802.11n HT20	52	5260	MCS0	-	-
Mode 23	U-NII-2A	5.25-5.35	0	802.11n HT20	60	5300	MCS0	-	-
Mode 24	U-NII-2A	5.25-5.35	0	802.11n HT20	64	5320	MCS0	-	-
Mode 25	U-NII-2A	5.25-5.35	0	802.11n HT40	54	5270	MCS0	-	-
Mode 26	U-NII-2A	5.25-5.35	0	802.11n HT40	62	5310	MCS0	-	-
Mode 27	U-NII-2A	5.25-5.35	0	802.11ac VHT80	58	5290	MCS0	-	-
Mode 28	U-NII-2A	5.25-5.35	0	802.11ax HE20	52	5260	MCS0	Full	-
Mode 29	U-NII-2A	5.25-5.35	0	802.11ax HE20	60	5300	MCS0	Full	-
Mode 30	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	Full	-
Mode 31	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	26/8	-
Mode 32	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	2/40	-
Mode 33	U-NII-2A	5.25-5.35	0	802.11ax HE20	64	5320	MCS0	106/54	-
Mode 34	U-NII-2A	5.25-5.35	0	802.11ax HE40	54	5270	MCS0	Full	-
Mode 35	U-NII-2A	5.25-5.35	0	802.11ax HE40	62	5310	MCS0	Full	-
Mode 36	U-NII-2A	5.25-5.35	0	802.11ax HE80	58	5290	MCS0	Full	-
Mode 37	U-NII-2C	5.47-5.725	0	802.11a	100	5500	6Mbps	-	-
Mode 38	U-NII-2C	5.47-5.725	0	802.11a	120	5600	6Mbps	-	-
Mode 39	U-NII-2C	5.47-5.725	0	802.11a	140	5700	6Mbps	-	-
Mode 40	U-NII-2C	5.47-5.725	0	802.11a	144	5720	6Mbps	-	-
Mode 41	U-NII-2C	5.47-5.725	0	802.11n HT20	100	5500	MCS0	-	-
Mode 42	U-NII-2C	5.47-5.725	0	802.11n HT20	120	5600	MCS0	-	-
Mode 43	U-NII-2C	5.47-5.725	0	802.11n HT20	140	5700	MCS0	-	-
Mode 44	U-NII-2C	5.47-5.725	0	802.11n HT20	144	5720	MCS0	-	-

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 45	U-NII-2C	5.47-5.725	0	802.11n HT40	102	5510	MCS0	-	-
Mode 46	U-NII-2C	5.47-5.725	0	802.11n HT40	118	5590	MCS0	-	-
Mode 47	U-NII-2C	5.47-5.725	0	802.11n HT40	134	5670	MCS0	-	-
Mode 48	U-NII-2C	5.47-5.725	0	802.11n HT40	142	5710	MCS0	-	-
Mode 49	U-NII-2C	5.47-5.725	0	802.11ac VHT80	106	5530	MCS0	-	-
Mode 50	U-NII-2C	5.47-5.725	0	802.11ac VHT80	138	5690	MCS0	-	-
Mode 51	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	Full	-
Mode 52	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	26/0	-
Mode 53	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	52/37	-
Mode 54	U-NII-2C	5.47-5.725	0	802.11ax HE20	100	5500	MCS0	106/53	-
Mode 55	U-NII-2C	5.47-5.725	0	802.11ax HE20	120	5600	MCS0	Full	-
Mode 56	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	Full	-
Mode 57	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	26/8	-
Mode 58	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	52/40	-
Mode 59	U-NII-2C	5.47-5.725	0	802.11ax HE20	140	5700	MCS0	106/54	-
Mode 60	U-NII-2C	5.47-5.725	0	802.11ax HE20	144	5720	MCS0	Full	-
Mode 61	U-NII-2C	5.47-5.725	0	802.11ax HE40	102	5510	MCS0	Full	-
Mode 62	U-NII-2C	5.47-5.725	0	802.11ax HE40	118	5590	MCS0	Full	-
Mode 63	U-NII-2C	5.47-5.725	0	802.11ax HE40	134	5670	MCS0	Full	-
Mode 64	U-NII-2C	5.47-5.725	0	802.11ax HE40	142	5710	MCS0	Full	-
Mode 65	U-NII-2C	5.47-5.725	0	802.11ax HE80	106	5530	MCS0	Full	-
Mode 66	U-NII-2C	5.47-5.725	0	802.11ax HE80	138	5690	MCS0	Full	-
Mode 67	U-NII-2C	5.47-5.725	0	802.11ac VHT80	122	5610	MCS0	-	-
Mode 68	U-NII-2C	5.47-5.725	0	802.11ax HE80	122	5610	MCS0	Full	-
Mode 69	U-NII-2C	5.47-5.725	0	SHF (Above 18GHz)					-
Mode 70	U-NII-2C	5.47-5.725	0	LF (Below 1GHz)					-

C1-2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	802.11a	36	5149.94	51.88	54.00	-2.12	V	Avg.	Pass	-	Band Edge
	802.11a	36	15540.00	44.88	54.00	-9.12	H	Avg.	Pass	-	Harmonic
2	802.11a	44	5149.60	42.57	54.00	-11.43	V	Avg.	Pass	-	Band Edge
	802.11a	44	15660.00	44.75	54.00	-9.25	V	Avg.	Pass	-	Harmonic
3	802.11a	48	5138.48	41.68	54.00	-12.32	V	Avg.	Pass	-	Band Edge
	802.11a	48	15720.00	44.85	54.00	-9.15	H	Avg.	Pass	-	Harmonic
4	802.11n HT20	36	5148.68	50.74	54.00	-3.26	V	Avg.	Pass	-	Band Edge
	802.11n HT20	36	15540.00	45.63	54.00	-8.37	H	Avg.	Pass	-	Harmonic
5	802.11n HT20	44	5149.38	42.10	54.00	-11.90	V	Avg.	Pass	-	Band Edge
	802.11n HT20	44	15660.00	45.17	54.00	-8.83	H	Avg.	Pass	-	Harmonic
6	802.11n HT20	48	5145.68	41.86	54.00	-12.14	V	Avg.	Pass	-	Band Edge
	802.11n HT20	48	15720.00	44.79	54.00	-9.21	H	Avg.	Pass	-	Harmonic
7	802.11n HT40	38	5149.34	51.34	54.00	-2.66	V	Avg.	Pass	-	Band Edge
8	802.11n HT40	46	5146.74	42.69	54.00	-11.31	V	Avg.	Pass	-	Band Edge
9	802.11ac VHT80	42	5149.94	51.05	54.00	-2.95	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	42	15630.00	44.70	54.00	-9.30	V	Avg.	Pass	-	Harmonic
10	802.11ax HE20	36	5149.94	50.34	54.00	-3.66	V	Avg.	Pass	Full	Band Edge
	802.11ax HE20	36	15540.00	44.73	54.00	-9.27	V	Avg.	Pass	Full	Harmonic
11	802.11ax HE20	36	5138.42	50.72	54.00	-3.28	H	Avg.	Pass	26/0	Band Edge
12	802.11ax HE20	36	5140.04	51.71	54.00	-2.29	V	Avg.	Pass	52/37	Band Edge
13	802.11ax HE20	36	5149.58	43.70	54.00	-10.30	V	Avg.	Pass	106/53	Band Edge
14	802.11ax HE20	44	5146.96	42.20	54.00	-11.80	V	Avg.	Pass	Full	Band Edge
14	802.11ax HE20	44	15660.00	44.53	54.00	-9.47	V	Avg.	Pass	Full	Harmonic
15	802.11ax HE20	48	5016.08	41.96	54.00	-12.04	V	Avg.	Pass	Full	Band Edge
15	802.11ax HE20	48	15720.00	44.66	54.00	-9.34	H	Avg.	Pass	Full	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
16	802.11ax HE40	38	5148.58	52.43	54.00	-1.57	V	Avg.	Pass	Full	Band Edge
	802.11ax HE40	38	10380.00	49.69	68.20	-18.51	V	Peak	Pass	Full	Harmonic
17	802.11ax HE40	46	5149.96	43.05	54.00	-10.95	V	Avg.	Pass	Full	Band Edge
	802.11ax HE40	46	15690.00	44.21	54.00	-9.79	V	Avg.	Pass	Full	Harmonic
18	802.11ax HE80	42	5145.95	51.28	54.00	-2.72	V	Avg.	Pass	Full	Band Edge
	802.11ax HE80	42	15630.00	44.74	54.00	-9.26	V	Avg.	Pass	Full	Harmonic
19	802.11a	52	5051.74	41.71	54.00	-12.29	V	Avg.	Pass	-	Band Edge
	802.11a	52	15780.00	44.46	54.00	-9.54	V	Avg.	Pass	-	Harmonic
20	802.11a	60	5351.20	45.42	54.00	-8.58	V	Avg.	Pass	-	Band Edge
20	802.11a	60	15900.00	44.60	54.00	-9.40	V	Avg.	Pass	-	Harmonic
21	802.11a	64	5350.38	51.84	54.00	-2.16	V	Avg.	Pass	-	Band Edge
21	802.11a	64	15960.00	44.77	54.00	-9.23	H	Avg.	Pass	-	Harmonic
22	802.11n HT20	52	5030.42	41.75	54.00	-12.25	H	Avg.	Pass	-	Band Edge
23	802.11n HT20	52	15780.00	44.34	54.00	-9.66	V	Avg.	Pass	-	Harmonic
23	802.11n HT20	60	5350.08	45.69	54.00	-8.31	V	Avg.	Pass	-	Band Edge
23	802.11n HT20	60	15900.00	45.58	54.00	-8.42	V	Avg.	Pass	-	Harmonic
24	802.11n HT20	64	5350.38	48.41	54.00	-5.59	V	Avg.	Pass	-	Band Edge
24	802.11n HT20	64	15960.00	44.68	54.00	-9.32	H	Avg.	Pass	-	Harmonic
25	802.11n HT40	54	5351.51	42.34	54.00	-11.66	V	Avg.	Pass	-	Band Edge
26	802.11n HT40	62	5350.20	52.08	54.00	-1.92	V	Avg.	Pass	-	Band Edge
27	802.11ac VHT80	58	5351.20	50.50	54.00	-3.50	V	Avg.	Pass	-	Band Edge
27	802.11ac VHT80	58	15870.00	44.33	54.00	-9.67	V	Avg.	Pass	-	Harmonic
28	802.11ax HE20	52	5024.44	41.70	54.00	-12.30	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	52	15780.00	44.37	54.00	-9.63	V	Avg.	Pass	Full	Harmonic
29	802.11ax HE20	60	5350.08	43.23	54.00	-10.77	V	Avg.	Pass	Full	Band Edge
	802.11ax HE20	60	15900.00	44.63	54.00	-9.37	V	Avg.	Pass	Full	Harmonic
30	802.11ax HE20	64	5350.66	49.95	54.00	-4.05	V	Avg.	Pass	Full	Band Edge
	802.11ax HE20	64	15960.00	44.74	54.00	-9.26	H	Avg.	Pass	Full	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
31	802.11ax HE20	64	5362.28	72.24	74.00	-1.76	V	Peak	Pass	26/8	Band Edge
32	802.11ax HE20	64	5355.98	50.32	54.00	-3.68	V	Avg.	Pass	52/40	Band Edge
33	802.11ax HE20	64	5350.66	49.56	54.00	-4.44	V	Avg.	Pass	106/54	Band Edge
34	802.11ax HE40	54	5351.32	42.10	54.00	-11.90	V	Avg.	Pass	Full	Band Edge
	802.11ax HE40	54	15810.00	43.95	54.00	-10.05	H	Avg.	Pass	Full	Harmonic
35	802.11ax HE40	62	5350.05	51.08	54.00	-2.92	V	Avg.	Pass	Full	Band Edge
	802.11ax HE40	62	15930.00	44.16	54.00	-9.84	H	Avg.	Pass	Full	Harmonic
36	802.11ax HE80	58	5350.01	50.84	54.00	-3.16	V	Avg.	Pass	Full	Band Edge
	802.11ax HE80	58	15870.00	44.35	54.00	-9.65	V	Avg.	Pass	Full	Harmonic
37	802.11a	100	5469.25	61.69	68.20	-6.51	V	Peak	Pass	-	Band Edge
	802.11a	100	11000.00	40.85	54.00	-13.15	V	Avg.	Pass	-	Harmonic
38	802.11a	120	5449.50	39.46	54.00	-14.54	V	Avg.	Pass	-	Band Edge
	802.11a	120	11200.00	41.13	54.00	-12.87	H	Avg.	Pass	-	Harmonic
39	802.11a	140	5727.82	65.66	68.20	-2.54	V	Peak	Pass	-	Band Edge
	802.11a	140	11400.00	41.66	54.00	-12.34	V	Avg.	Pass	-	Harmonic
40	802.11a	144	5459.20	39.48	54.00	-14.52	V	Avg.	Pass	-	Band Edge
40	802.11a	144	11440.00	41.76	54.00	-12.24	H	Avg.	Pass	-	Harmonic
41	802.11n HT20	100	5466.10	61.59	68.20	-6.61	V	Peak	Pass	-	Band Edge
41	802.11n HT20	100	16500.00	55.39	68.20	-12.81	H	Peak	Pass	-	Harmonic
42	802.11n HT20	120	5447.00	39.58	54.00	-14.42	V	Avg.	Pass	-	Band Edge
42	802.11n HT20	120	11200.00	41.04	54.00	-12.96	V	Avg.	Pass	-	Harmonic
43	802.11n HT20	140	5725.03	66.67	68.20	-1.53	H	Peak	Pass	-	Band Edge
43	802.11n HT20	140	11400.00	41.57	54.00	-12.43	H	Avg.	Pass	-	Harmonic
44	802.11n HT20	144	5451.01	39.47	54.00	-14.53	V	Avg.	Pass	-	Band Edge
44	802.11n HT20	144	11440.00	41.80	54.00	-12.20	H	Avg.	Pass	-	Harmonic
44	802.11n HT20	144	5451.01	39.47	54.00	-14.53	V	Avg.	Pass	-	Band Edge
45	802.11n HT40	102	5469.20	66.18	68.20	-2.02	V	Peak	Pass	-	Band Edge

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
46	802.11n HT40	118	5458.24	39.75	54.00	-14.25	V	Avg.	Pass	-	Band Edge
47	802.11n HT40	134	5725.20	66.42	68.20	-1.78	V	Peak	Pass	-	Band Edge
48	802.11n HT40	142	5457.25	39.27	54.00	-14.73	V	Avg.	Pass	-	Band Edge
49	802.11ac VHT80	106	5459.08	51.21	54.00	-2.79	V	Avg.	Pass	-	Band Edge
	802.11ac VHT80	106	11060.00	40.87	54.00	-13.13	H	Avg.	Pass	-	Harmonic
50	802.11ac VHT80	138	5861.20	54.90	68.20	-13.30	V	Peak	Pass	-	Band Edge
	802.11ac VHT80	138	11380.00	41.30	54.00	-12.70	H	Avg.	Pass	-	Harmonic
51	802.11ax HE20	100	5467.75	57.81	68.20	-10.39	V	Peak	Pass	Full	Band Edge
51	802.11ax HE20	100	11000.00	40.89	54.00	-13.11	H	Avg.	Pass	Full	Harmonic
52	802.11ax HE20	100	5457.10	51.53	54.00	-2.47	V	Avg.	Pass	26/0	Band Edge
53	802.11ax HE20	100	5465.50	66.91	68.20	-1.29	H	Peak	Pass	52/37	Band Edge
54	802.11ax HE20	100	5470.00	56.34	68.20	-11.86	V	Peak	Pass	106/53	Band Edge
55	802.11ax HE20	120	5458.75	39.54	54.00	-14.46	V	Avg.	Pass	Full	Band Edge
55	802.11ax HE20	120	11200.00	41.18	54.00	-12.82	V	Avg.	Pass	Full	Harmonic
56	802.11ax HE20	140	5725.03	63.93	68.20	-4.27	V	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	140	11400.00	41.53	54.00	-12.47	H	Avg.	Pass	Full RU	Harmonic
57	802.11ax HE20	140	5726.65	64.46	68.20	-3.74	V	Peak	Pass	26/8	Band Edge
58	802.11ax HE20	140	5726.46	65.22	68.20	-2.98	V	Peak	Pass	52/40	Band Edge
59	802.11ax HE20	140	5729.12	65.72	68.20	-2.48	H	Peak	Pass	106/54	Band Edge
60	802.11ax HE20	144	5435.41	39.50	54.00	-14.50	H	Avg.	Pass	Full	Band Edge
	802.11ax HE20	144	11440.00	41.83	54.00	-12.17	V	Avg.	Pass	Full	Harmonic
61	802.11ax HE40	102	5469.52	65.54	68.20	-2.66	V	Peak	Pass	Full	Band Edge
	802.11ax HE40	102	11020.00	40.69	54.00	-13.31	V	Avg.	Pass	Full	Harmonic
62	802.11ax HE40	118	5456.56	39.91	54.00	-14.09	V	Avg.	Pass	Full	Band Edge
62	802.11ax HE40	118	11180.00	40.87	54.00	-13.13	H	Avg.	Pass	Full	Harmonic
63	802.11ax HE40	134	5727.10	62.74	68.20	-5.46	V	Peak	Pass	Full	Band Edge
63	802.11ax HE40	134	11340.00	41.06	54.00	-12.94	H	Avg.	Pass	Full	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
64	802.11ax HE40	142	5454.13	39.48	54.00	-14.52	H	Avg.	Pass	Full	Band Edge
	802.11ax HE40	142	11420.00	41.27	54.00	-12.73	V	Avg.	Pass	Full	Harmonic
65	802.11ax HE80	106	5459.80	52.42	54.00	-1.58	V	Avg.	Pass	Full	Band Edge
	802.11ax HE80	106	11060.00	40.77	54.00	-13.23	V	Avg.	Pass	Full	Harmonic
66	802.11ax HE80	138	5862.70	55.95	68.20	-12.25	V	Peak	Pass	Full	Band Edge
	802.11ax HE80	138	11380.00	41.12	54.00	-12.88	V	Avg.	Pass	Full	Harmonic
67	802.11ac VHT80	122	5732.45	55.67	68.20	-12.53	H	Peak	Pass	-	Band Edge
	802.11ac VHT80	122	11220.00	40.32	54.00	-13.68	V	Avg.	Pass	-	Harmonic
68	802.11ax HE80	122	5726.25	57.19	68.20	-11.01	H	Peak	Pass	Full	Band Edge
	802.11ax HE80	122	11220.00	40.66	54.00	-13.34	H	Avg.	Pass	Full	Harmonic
69	SHF		5862.70	55.95	68.20	-12.25	V	Peak	Pass	Full	Band Edge
70	LF		11380.00	41.12	54.00	-12.88	V	Avg.	Pass	Full	Harmonic

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.58 60.02 74.00 -13.98 48.25 32.50 12.59 34.28 0.96 100 204 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 102.47 ------ ------ 90.72 32.50 12.62 34.32 0.95 100 204 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 47.89 54.00 -6.11 36.12 32.50 12.59 34.28 0.96 100 204 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 95.36 ------ ------ 83.61 32.50 12.62 34.32 0.95 100 204 Average

Mode	1	
	Band Edge	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5148.14 63.75 74.00 -10.25 51.97 32.50 12.59 34.27 0.96 338 221 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5180.00 105.50 ------ ------ 93.75 32.50 12.62 34.32 0.95 338 221 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5149.94 51.88 54.00 -2.12 40.11 32.50 12.59 34.28 0.96 338 221 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5180.00 98.06 ------ ------ 86.31 32.50 12.61 34.31 0.95 338 221 Average

Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 48.93 68.20 -19.27 31.54 37.36 17.96 39.70 1.77 -- -- Peak 2 15540.00 54.38 74.00 -19.62 34.88 40.80 22.47 45.92 2.15 -- -- Peak 3 15540.00 44.88 54.00 -9.12 25.38 40.80 22.47 45.92 2.15 -- -- Average	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.59 68.20 -18.61 32.20 37.36 17.96 39.70 1.77 -- -- Peak 2 15540.00 53.98 74.00 -20.02 34.48 40.80 22.47 45.92 2.15 -- -- Peak 3 15540.00 44.85 54.00 -9.15 25.35 40.80 22.47 45.92 2.15 -- -- Average

Mode	1	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL

Mode	2	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5110.22 51.36 74.00 -22.64 39.56 32.50 12.56 34.22 0.96 109 216 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 104.05 ------ ------ 92.36 32.45 12.66 34.38 0.96 109 216 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5147.40 41.96 54.00 -12.04 30.18 32.50 12.59 34.27 0.96 109 216 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 96.41 ------ ------ 84.72 32.45 12.66 34.38 0.96 109 216 Average

Mode	2	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5449.68 48.93 74.00 -25.07 37.30 32.40 12.91 34.71 1.03 109 216 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.04 39.36 54.00 -14.64 27.72 32.42 12.92 34.72 1.02 109 216 Average	Blank

Mode	2	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5039.38 52.26 74.00 -21.74 40.18 32.72 12.51 34.12 0.97 378 220 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 104.63 ------ ------ 92.92 32.48 12.64 34.37 0.96 378 220 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.60 42.57 54.00 -11.43 30.80 32.50 12.59 34.28 0.96 378 220 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 97.51 ------ ------ 85.80 32.48 12.64 34.37 0.96 378 220 Average

Mode	2	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5370.48 49.07 74.00 -24.93 37.53 32.26 12.83 34.59 1.04 378 220 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5438.64 39.36 54.00 -14.64 27.77 32.35 12.90 34.69 1.03 378 220 Average	Blank

Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 50.22 68.20 -17.98 33.03 37.20 18.03 39.83 1.79 -- -- Peak 2 15660.00 55.30 74.00 -18.70 35.68 40.96 22.57 46.06 2.15 -- -- Peak 3 15660.00 44.73 54.00 -9.27 25.11 40.96 22.57 46.06 2.15 -- -- Average	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 49.48 68.20 -18.72 32.29 37.20 18.03 39.83 1.79 -- -- Peak 2 15660.00 55.55 74.00 -18.45 35.93 40.96 22.57 46.06 2.15 -- -- Peak 3 15660.00 44.75 54.00 -9.25 25.13 40.96 22.57 46.06 2.15 -- -- Average

Mode	2	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL

Mode	3	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5072.96 51.94 74.00 -22.06 40.00 32.61 12.53 34.17 0.97 101 215 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5240.00 103.99 ------ ------ 92.32 32.43 12.67 34.40 0.97 101 215 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5035.28 41.57 54.00 -12.43 29.47 32.73 12.51 34.11 0.97 101 215 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5240.00 96.93 ------ ------ 85.26 32.43 12.67 34.40 0.97 101 215 Average

Mode	3	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5452.96 49.38 74.00 -24.62 37.74 32.41 12.91 34.71 1.03 101 215 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5458.46 39.52 54.00 -14.48 27.88 32.42 12.92 34.72 1.02 101 215 Average	Blank

Mode	3	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5010.08 50.94 74.00 -23.06 38.76 32.78 12.49 34.07 0.98 330 208 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5240.00 106.84 ------ ------ 95.18 32.42 12.68 34.41 0.97 330 208 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5138.48 41.68 54.00 -12.32 29.90 32.50 12.58 34.26 0.96 330 208 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto 1 5240.00 99.23 ------ ------ 87.57 32.42 12.68 34.41 0.97 330 208 Average

Mode	3	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5452.74 48.43 74.00 -25.57 36.79 32.41 12.91 34.71 1.03 330 208 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.750kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5352.86 39.59 54.00 -14.41 28.03 32.29 12.81 34.57 1.03 330 208 Average	Blank

Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10480.00 49.01 68.20 -19.19 31.77 37.26 18.07 39.89 1.80 -- -- Peak 2 15720.00 54.46 74.00 -19.54 35.03 40.80 22.62 46.13 2.14 -- -- Peak 3 15720.00 44.85 54.00 -9.15 25.42 40.80 22.62 46.13 2.14 -- -- Average	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10480.00 49.77 68.20 -18.43 32.53 37.26 18.07 39.89 1.80 -- -- Peak 2 15720.00 54.16 74.00 -19.84 34.73 40.80 22.62 46.13 2.14 -- -- Peak 3 15720.00 44.82 54.00 -9.18 25.39 40.80 22.62 46.13 2.14 -- -- Average

Mode	3	
	Harmonic	
	U-NII-1_5.15-5.25_802.11a_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.94 61.51 74.00 -12.49 49.74 32.50 12.59 34.28 0.96 100 205 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 103.40 ------ ------ 91.66 32.50 12.62 34.33 0.95 100 205 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5148.68 49.24 54.00 -4.76 37.46 32.50 12.59 34.27 0.96 100 205 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5180.00 96.04 ------ ------ 84.29 32.50 12.62 34.32 0.95 100 205 Average

Mode	4	
	Band Edge	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_5180MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5142.38 60.02 74.00 -13.98 48.24 32.50 12.59 34.27 0.96 399 214 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5180.00 106.40 ------ ------ 94.66 32.50 12.62 34.33 0.95 399 214 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5148.68 50.74 54.00 -3.26 38.96 32.50 12.59 34.27 0.96 399 214 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5180.00 99.38 ------ ------ 87.63 32.50 12.62 34.32 0.95 399 214 Average

Mode	4	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 50.17 68.20 -18.03 32.78 37.36 17.96 39.70 1.77 -- -- Peak 2 15540.00 55.95 74.00 -18.05 36.45 40.80 22.47 45.92 2.15 -- -- Peak 3 15540.00 45.63 54.00 -8.37 26.13 40.80 22.47 45.92 2.15 -- -- Average	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10360.00 49.51 68.20 -18.69 32.12 37.36 17.96 39.70 1.77 -- -- Peak 2 15540.00 54.10 74.00 -19.90 34.60 40.80 22.47 45.92 2.15 -- -- Peak 3 15540.00 44.21 54.00 -9.79 24.71 40.80 22.47 45.92 2.15 -- -- Average

Mode	4	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH36_5180MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL

Mode	5	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5041.80 51.23 74.00 -22.77 39.15 32.72 12.51 34.12 0.97 100 216 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5220.00 104.49 ------ ------ 92.80 32.45 12.66 34.38 0.96 100 216 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5148.50 41.89 54.00 -12.11 30.11 32.50 12.59 34.27 0.96 100 216 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5220.00 97.29 ------ ------ 85.60 32.45 12.66 34.38 0.96 100 216 Average

Mode	5	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5400.72 49.29 74.00 -24.71 37.81 32.20 12.86 34.64 1.06 100 216 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5452.08 39.38 54.00 -14.62 27.75 32.40 12.91 34.71 1.03 100 216 Average	Blank

Mode	5	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5028.60 51.10 74.00 -22.90 38.98 32.74 12.50 34.10 0.98 314 213 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 106.23 ------ ------ 94.53 32.46 12.65 34.37 0.96 314 213 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5149.38 42.10 54.00 -11.90 30.33 32.50 12.59 34.28 0.96 314 213 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5220.00 99.82 ------ ------ 88.13 32.45 12.66 34.38 0.96 314 213 Average

Mode	5	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5377.20 49.17 74.00 -24.83 37.64 32.25 12.83 34.60 1.05 314 213 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5459.52 39.53 54.00 -14.47 27.89 32.42 12.92 34.72 1.02 314 213 Average	Blank

Mode	5	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 50.57 68.20 -17.63 33.38 37.20 18.03 39.83 1.79 -- -- Peak 2 15660.00 55.22 74.00 -18.78 35.60 40.96 22.57 46.06 2.15 -- -- Peak 3 15660.00 45.17 54.00 -8.83 25.55 40.96 22.57 46.06 2.15 -- -- Average	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 VERTICAL Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 10440.00 50.10 68.20 -18.10 32.91 37.20 18.03 39.83 1.79 -- -- Peak 2 15660.00 54.48 74.00 -19.52 34.86 40.96 22.57 46.06 2.15 -- -- Peak 3 15660.00 44.39 54.00 -9.61 24.77 40.96 22.57 46.06 2.15 -- -- Average

Mode	5	
	Harmonic	
	U-NII-1_5.15-5.25_802.11n HT20_CH44_5220MHz	
ANT	0	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 VERTICAL

Mode	6	
	Band Edge - L	
	U-NII-1_5.15-5.25_802.11n HT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5143.76 51.28 74.00 -22.72 39.50 32.50 12.59 34.27 0.96 113 210 Peak	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto 1 5240.00 104.75 ------ ------ 93.09 32.42 12.68 34.41 0.97 113 210 Peak
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5148.80 41.82 54.00 -12.18 30.04 32.50 12.59 34.27 0.96 113 210 Average	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto 1 5240.00 97.09 ------ ------ 85.42 32.43 12.67 34.40 0.97 113 210 Average

Mode	6	
	Band Edge - R	
	U-NII-1_5.15-5.25_802.11n HT20_CH48_5240MHz	
ANT	0	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH21-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5356.38 48.72 74.00 -25.28 37.15 32.29 12.81 34.57 1.04 113 210 Peak	Blank
Avg	 Site : 03CH21-HY Condition: AVG_BE_54 3m DRH18-E_LE2C03A18EN_250807 HORIZONTAL : RBW:1000.000kHz VBW:0.820kHz SWT:Auto Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 5439.10 39.53 54.00 -14.47 27.93 32.36 12.90 34.69 1.03 113 210 Average	Blank