



FCC RADIO TEST REPORT

BLUETOOTH EDR

FCC ID : A4RGE1GQ
Equipment : Phone
Model Name : GE1GQ
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on May 12, 2025 and testing was performed from May 21, 2025 to Aug. 05, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	6
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result.....	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Power Spectral Density Measurement	13
3.4 Conducted Band Edges and Spurious Emission Measurement	14
3.5 Radiated Band Edges and Spurious Emission Measurement	15
3.6 AC Conducted Emission Measurement.....	19
3.7 Antenna Requirements.....	21
4 List of Measuring Equipment	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR550731J	01	Initial issue of report	Sep. 16, 2025
FR550731J	02	Revise cover page, section 2.2, section 3.5.5, Appendix D and Appendix E. This report is an updated version, replacing the report issued on Sep. 16, 2025.	Oct. 06, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Steve Chen

Report Producer: Hannah Yang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, Wi-Fi 6GHz 802.11a/ax, NFC, WPC Rx, and GNSS.		
Antenna Type Bluetooth: <Ant. 4>: IFA Antenna <Ant. 3>: IFA Antenna		
EUT Information List		
S/N	Performed Test Item	
54181JEA300022	RF Conducted Measurement	
56141JEA302762 56141JEA302828	Radiated Spurious Emission	
56141JEA302747	Conducted Emission	
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant.3: 0.5 Ant.4: -3.2

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH16-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find Z Plane with Adapter for <Ant. 3>, Y Plane with Adapter for <Ant. 4> as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.


The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases		
Test Item	Data Rate / Modulation	
Conducted Test Cases	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz
AC Conducted Emission	Mode 1: WLAN(2.4G) Link + BT Link + MPEG4	
Remark:		
1. For Radiated Test Cases, the tests were performed with USB Cable 1.		
2. During the preliminary test, both charging modes (Adapter mode and WPT RX mode) were verified. It is determined that the adaptor mode is the worst case for official test.		
3. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.		
4. The detailed Radiated test modes are shown in Appendix C.		

2.3 Connection Diagram of Test System



Conduction Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	-	-	-	-	-	-
A1	BT Earphone	Bluetooth	X	-	-	-	-	-	-
A2	AP router	WiFi	X	-	-	-	-	-	-
No.	Power Source	Connection Type	1	-	-	-	-	-	-
B1	AC : 120V/60Hz	AC Power Cable	X	-	-	-	-	-	-



Radiation Test Setup									
No.	Power Source	Connection Type	Test Mode						
			TX						
B1	AC : 110V/60Hz	AC Power Cable	X						

2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Bluetooth Earphone	Google	G1007/G1008	A4RG1007/ A4RG1008	N/A	N/A
3.	Adapter	Google	GW8L7	N/A	N/A	N/A



2.5 EUT Operation Test Setup

The RF test items, utility "BT_DUT_Control_GUI" for DTS was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




3.5.3 Test Procedures


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9kHz~30MHz	Aug. 29, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Aug. 28, 2025	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA9170	1224	18GHz~40GHz	Oct. 25, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Oct. 24, 2025	Radiation (03CH16-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241055	10Hz~44GHz	Jul. 19, 2024	Jul. 09, 2025 ~ Jul. 17, 2025	Jul. 18, 2025	Radiation (03CH16-HY)
Spectrum Analyzer	Keysight	N9010B	MY60240520	10Hz~44GHz	Dec. 09, 2024	Jul. 17, 2025 ~ Aug. 05, 2025	Dec. 08, 2025	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Nov. 22, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Nov. 21, 2025	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N-06	47020 & 06	30MHz to 1GHz	Oct. 05, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Oct. 04, 2025	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Mar. 27, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Mar. 26, 2026	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1GHz	Jun. 30, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Jun. 29, 2026	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY57280120	1GHz~26.5GHz	Jan. 12, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Jan. 11, 2026	Radiation (03CH16-HY)
Preamplifier	EMEC	EM1G18G	060812	1GHz~18GHz	Dec. 24, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Dec. 23, 2025	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 26, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	May 25, 2026	Radiation (03CH16-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN17	1.53GHz Low Pass Filter	Jan. 14, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Jan. 13, 2026	Radiation (03CH16-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60ST	SN3	3GHz High Pass Filter	Jun. 26, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Jun. 25, 2026	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	801606/2	9KHz ~ 40GHz	Apr. 23, 2025	Jul. 09, 2025 ~ Aug. 05, 2025	Apr. 22, 2026	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102/SUCOFLEX 104	EC-A5-300-5757,805935/4,802434/4	30MHz~18GHz	Aug. 07, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Aug. 06, 2025	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804012/2	18-40GHz	Dec. 31, 2024	Jul. 09, 2025 ~ Aug. 05, 2025	Dec. 30, 2025	Radiation (03CH16-HY)
Software	Audix	E3 230621 V9	RK-002393	N/A	N/A	Jul. 09, 2025 ~ Aug. 05, 2025	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Jul. 09, 2025 ~ Aug. 05, 2025	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 09, 2025 ~ Aug. 05, 2025	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 09, 2025 ~ Aug. 05, 2025	N/A	Radiation (03CH16-HY)
Hygrometer	TECEPIL	DTM-303A	TP201996	N/A	Nov. 01, 2024	May 21, 2025 ~ Jun. 24, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	May 21, 2025 ~ Jun. 24, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2024	May 21, 2025 ~ Jun. 24, 2025	Aug. 22, 2025	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	May 21, 2025 ~ Jun. 24, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	May 21, 2025 ~ Jun. 24, 2025	N/A	Conducted (TH05-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 04, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 10, 2024	Jul. 04, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Oct. 14, 2024	Jul. 04, 2025	Oct. 13, 2025	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 14, 2024	Jul. 04, 2025	Nov. 13, 2025	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Jul. 04, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 30, 2024	Jul. 04, 2025	Jul. 29, 2025	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	9KHz - 30MHz	Oct. 15, 2024	Jul. 04, 2025	Oct. 14, 2025	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Willy Chang	Temperature:	21~25	°C
Test Date:	2025/5/21~2025/6/24	Relative Humidity:	51~54	%

<Ant. 3>

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BT	2Mbps	1	00	2402	1.196	1.075	0.50	Pass
BT	2Mbps	1	39	2441	1.196	1.075	0.50	Pass
BT	2Mbps	1	78	2480	1.195	1.074	0.50	Pass
BT	3Mbps	1	00	2402	1.173	1.066	0.50	Pass
BT	3Mbps	1	39	2441	1.173	1.062	0.50	Pass
BT	3Mbps	1	78	2480	1.172	1.066	0.50	Pass

TEST RESULTS DATA Average Power Table										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BT	2Mbps	1	00	2402	17.44	30.00	0.50	17.94	36.00	Pass
BT	2Mbps	1	39	2441	17.08	30.00	0.50	17.58	36.00	Pass
BT	2Mbps	1	78	2480	17.76	30.00	0.50	18.26	36.00	Pass
BT	3Mbps	1	00	2402	17.22	30.00	0.50	17.72	36.00	Pass
BT	3Mbps	1	39	2441	17.05	30.00	0.50	17.55	36.00	Pass
BT	3Mbps	1	78	2480	17.75	30.00	0.50	18.25	36.00	Pass

TEST RESULTS DATA Peak Power Density									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BT	2Mbps	1	00	2402	16.21	2.47	0.50	8.00	Pass
BT	2Mbps	1	39	2441	16.76	3.11	0.50	8.00	Pass
BT	2Mbps	1	78	2480	16.93	3.30	0.50	8.00	Pass
BT	3Mbps	1	00	2402	16.36	2.80	0.50	8.00	Pass
BT	3Mbps	1	39	2441	16.96	3.44	0.50	8.00	Pass
BT	3Mbps	1	78	2480	17.22	3.62	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant.4>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BT	2Mbps	1	00	2402	1.195	1.075	0.50	Pass
BT	2Mbps	1	39	2441	1.196	1.076	0.50	Pass
BT	2Mbps	1	78	2480	1.195	1.074	0.50	Pass
BT	3Mbps	1	00	2402	1.173	1.065	0.50	Pass
BT	3Mbps	1	39	2441	1.173	1.067	0.50	Pass
BT	3Mbps	1	78	2480	1.172	1.064	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BT	2Mbps	1	00	2402	17.54	30.00	-3.20	14.34	36.00	Pass
BT	2Mbps	1	39	2441	16.68	30.00	-3.20	13.48	36.00	Pass
BT	2Mbps	1	78	2480	17.28	30.00	-3.20	14.08	36.00	Pass
BT	3Mbps	1	00	2402	17.59	30.00	-3.20	14.39	36.00	Pass
BT	3Mbps	1	39	2441	16.79	30.00	-3.20	13.59	36.00	Pass
BT	3Mbps	1	78	2480	17.36	30.00	-3.20	14.16	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BT	2Mbps	1	00	2402	16.80	3.15	-3.20	8.00	Pass
BT	2Mbps	1	39	2441	16.15	2.31	-3.20	8.00	Pass
BT	2Mbps	1	78	2480	16.97	3.21	-3.20	8.00	Pass
BT	3Mbps	1	00	2402	16.97	3.52	-3.20	8.00	Pass
BT	3Mbps	1	39	2441	16.32	2.61	-3.20	8.00	Pass
BT	3Mbps	1	78	2480	17.11	3.57	-3.20	8.00	Pass




Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.



<Ant.3>

6dB Bandwidth


<2Mbps>

6 dB Bandwidth Plot on Channel 00**6 dB Bandwidth Plot on Channel 39****6 dB Bandwidth Plot on Channel 78**




<3Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 39






6 dB Bandwidth Plot on Channel 78



**99% Occupied Bandwidth**

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00**99% Occupied Plot Bandwidth on Channel 39****99% Occupied Bandwidth Plot on Channel 78**

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



99% Occupied Plot Bandwidth on Channel 39






99% Occupied Bandwidth Plot on Channel 78



**Power Spectral Density (dBm/3kHz)**


<2Mbps>

Power Density (dBm/3kHz) Plot Channel 00**Power Density (dBm/3kHz) Plot Channel 39****Power Density (dBm/3kHz) Plot Channel 78**




<3Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 39




Power Density (dBm/3kHz) Plot Channel 78






Band Edge and Spurious Emission






<2Mbps> Channel 39

100kHz PSD reference Level Plot




Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2Mbps> Channel 78


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<3Mbps> Channel 00


100kHz PSD reference Level Plot




Low Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<3Mbps> Channel 39

100kHz PSD reference Level Plot




Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<3Mbps> Channel 78


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot








<Ant.4>

6dB Bandwidth


<2Mbps>

6 dB Bandwidth Plot on Channel 00**6 dB Bandwidth Plot on Channel 39****6 dB Bandwidth Plot on Channel 78**




<3Mbps>


6 dB Bandwidth Plot on Channel 00



6 dB Bandwidth Plot on Channel 39






6 dB Bandwidth Plot on Channel 78



**99% Occupied Bandwidth**

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00**99% Occupied Plot Bandwidth on Channel 39****99% Occupied Bandwidth Plot on Channel 78**

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



99% Occupied Plot Bandwidth on Channel 39



99% Occupied Bandwidth Plot on Channel 78







Power Spectral Density (dBm/3kHz)

<2Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 39




Power Density (dBm/3kHz) Plot Channel 78






<3Mbps>


Power Density (dBm/3kHz) Plot Channel 00



Power Density (dBm/3kHz) Plot Channel 39




Power Density (dBm/3kHz) Plot Channel 78






Band Edge and Spurious Emission






<2Mbps> Channel 39

100kHz PSD reference Level Plot




Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<2Mbps> Channel 78


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<3Mbps> Channel 00


100kHz PSD reference Level Plot




Low Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






<3Mbps> Channel 39

100kHz PSD reference Level Plot





Middle Channel Plot

Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot








Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	Temperature :	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO : 550731
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	38.27	55.40	17.13	L1	OFF	19.8
0.161250	55.24	---	65.40	10.16	L1	OFF	19.8
0.172500	---	37.39	54.84	17.45	L1	OFF	19.8
0.172500	53.42	---	64.84	11.42	L1	OFF	19.8
0.244500	---	27.86	51.94	24.08	L1	OFF	19.8
0.244500	37.07	---	61.94	24.87	L1	OFF	19.8
0.253500	---	27.85	51.64	23.79	L1	OFF	19.8
0.253500	36.16	---	61.64	25.48	L1	OFF	19.8
0.336750	---	23.89	49.28	25.39	L1	OFF	19.8
0.336750	25.82	---	59.28	33.46	L1	OFF	19.8
3.738750	---	25.02	46.00	20.98	L1	OFF	20.0
3.738750	26.05	---	56.00	29.95	L1	OFF	20.0
23.707500	---	28.72	50.00	21.28	L1	OFF	21.0
23.707500	31.43	---	60.00	28.57	L1	OFF	21.0

EUT Information

Report NO : 550731
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150540	---	31.58	55.97	24.39	N	OFF	19.8
0.150540	47.63	---	65.97	18.34	N	OFF	19.8
0.159000	---	36.53	55.52	18.99	N	OFF	19.8
0.159000	53.20	---	65.52	12.32	N	OFF	19.8
0.179250	---	33.22	54.52	21.30	N	OFF	19.8
0.179250	49.53	---	64.52	14.99	N	OFF	19.8
0.233250	---	24.90	52.33	27.43	N	OFF	19.8
0.233250	31.54	---	62.33	30.79	N	OFF	19.8
0.246750	---	26.72	51.87	25.15	N	OFF	19.8
0.246750	35.33	---	61.87	26.54	N	OFF	19.8
3.219000	---	25.26	46.00	20.74	N	OFF	20.0
3.219000	26.90	---	56.00	29.10	N	OFF	20.0
23.262000	---	30.84	50.00	19.16	N	OFF	20.9
23.262000	34.20	---	60.00	25.80	N	OFF	20.9



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Jerry Lan, Gary Guo and Steven Wu	Temperature :	20~26°C
		Relative Humidity :	40~65%

Note symbol

-L	Low channel location
-R	High channel location

C1-1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 7	2400-2483.5	3	Bluetooth BR_GFSK	00	2402	3Mbps	-	-
Mode 8	2400-2483.5	3	Bluetooth BR_GFSK	39	2441	3Mbps	-	-
Mode 9	2400-2483.5	3	Bluetooth BR_GFSK	78	2480	3Mbps	-	-
Mode 27	2400-2483.5	3	Bluetooth BR_GFSK	39	2441	3Mbps	-	LF
Mode 28	2400-2483.5	3	Bluetooth BR_GFSK	39	2441	3Mbps	-	SHF

**C1-2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
7	Bluetooth BR_GFSK	00	2388.29	47.64	54.00	-6.36	V	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	00	4804.00	40.32	74.00	-33.68	H	Peak	Pass	-	Harmonic
8	Bluetooth BR_GFSK	39	2493.52	48.01	54.00	-5.99	H	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	39	7323.00	45.21	74.00	-28.79	V	Peak	Pass	-	Harmonic
9	Bluetooth BR_GFSK	78	2483.52	47.54	54.00	-6.46	H	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	78	4960.00	38.82	54.00	-15.18	V	Avg.	Pass	-	Harmonic
27	LF	39	198.78	34.49	43.50	-9.01	H	Peak	Pass	-	LF
28	SHF	39	24912.00	39.09	74.00	-34.91	H	Peak	Pass	-	SHF



Mode	7																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																			
ANT	3																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.76</td><td>58.57</td><td>74.00</td><td>-15.43</td><td>43.85</td><td>27.50</td><td>7.71</td><td>30.41</td><td>9.92</td><td>316</td><td>22</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.76	58.57	74.00	-15.43	43.85	27.50	7.71	30.41	9.92	316	22	Peak	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>112.65</td><td>-----</td><td>-----</td><td>97.00</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>316</td><td>22</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	112.65	-----	-----	97.00	27.60	7.73	30.40	9.92	316	22	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2389.76	58.57	74.00	-15.43	43.85	27.50	7.71	30.41	9.92	316	22	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	112.65	-----	-----	97.00	27.60	7.73	30.40	9.92	316	22	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.76</td><td>47.50</td><td>54.00</td><td>-6.50</td><td>32.78</td><td>27.50</td><td>7.71</td><td>30.41</td><td>9.92</td><td>316</td><td>22</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.76	47.50	54.00	-6.50	32.78	27.50	7.71	30.41	9.92	316	22	Average	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>109.83</td><td>-----</td><td>-----</td><td>94.98</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>316</td><td>22</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	109.83	-----	-----	94.98	27.60	7.73	30.40	9.92	316	22	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2389.76	47.50	54.00	-6.50	32.78	27.50	7.71	30.41	9.92	316	22	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	109.83	-----	-----	94.98	27.60	7.73	30.40	9.92	316	22	Average																																																																																								



Mode	7																																																																																								
	Band Edge																																																																																								
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																								
ANT	3																																																																																								
Pol.	Vertical						Fundamental																																																																																		
Peak	Level (dBuV/m) Date: 2025-07-16 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2335.58</td><td>58.30</td><td>74.00</td><td>-15.70</td><td>43.95</td><td>27.26</td><td>7.62</td><td>30.45</td><td>9.92</td><td>247</td><td>94</td><td>Peak</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2335.58	58.30	74.00	-15.70	43.95	27.26	7.62	30.45	9.92	247	94	Peak	Level (dBuV/m) Date: 2025-07-16 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>115.27</td><td>-----</td><td>-----</td><td>100.42</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>247</td><td>94</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	115.27	-----	-----	100.42	27.60	7.73	30.40	9.92	247	94	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2335.58	58.30	74.00	-15.70	43.95	27.26	7.62	30.45	9.92	247	94	Peak																																																																													
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2402.00	115.27	-----	-----	100.42	27.60	7.73	30.40	9.92	247	94	Peak																																																																													
Avg	Level (dBuV/m) Date: 2025-07-16 Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2388.29</td><td>47.64</td><td>54.00</td><td>-6.36</td><td>32.95</td><td>27.47</td><td>7.71</td><td>30.41</td><td>9.92</td><td>247</td><td>94</td><td>Average</td></tr></tbody></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2388.29	47.64	54.00	-6.36	32.95	27.47	7.71	30.41	9.92	247	94	Average	Level (dBuV/m) Date: 2025-07-16 Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>112.56</td><td>-----</td><td>-----</td><td>97.71</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>247</td><td>94</td><td>Average</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2402.00	112.56	-----	-----	97.71	27.60	7.73	30.40	9.92	247	94	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2388.29	47.64	54.00	-6.36	32.95	27.47	7.71	30.41	9.92	247	94	Average																																																																													
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																														
1	2402.00	112.56	-----	-----	97.71	27.60	7.73	30.40	9.92	247	94	Average																																																																													







Mode	7																																																																																																					
	Harmonic																																																																																																					
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																					
ANT	3																																																																																																					
Pol.	Horizontal						Vertical																																																																																															
Peak Avg	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>40.32</td><td>74.00</td><td>-33.68</td><td>62.72</td><td>32.56</td><td>11.04</td><td>66.39</td><td>0.39</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4804.00	40.32	74.00	-33.68	62.72	32.56	11.04	66.39	0.39	--	--	Peak	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4804.00</td><td>40.20</td><td>74.00</td><td>-33.80</td><td>62.60</td><td>32.56</td><td>11.04</td><td>66.39</td><td>0.39</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4804.00	40.20	74.00	-33.80	62.60	32.56	11.04	66.39	0.39	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	4804.00	40.32	74.00	-33.68	62.72	32.56	11.04	66.39	0.39	--	--	Peak																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																											
1	4804.00	40.20	74.00	-33.80	62.60	32.56	11.04	66.39	0.39	--	--	Peak																																																																																										



Mode	7	
	Harmonic	
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL
	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL







Mode	8																																																																																																
	Band Edge - L																																																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																
ANT	3																																																																																																
Pol.	Horizontal						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2362.66</td><td>57.95</td><td>74.00</td><td>-16.05</td><td>43.49</td><td>27.30</td><td>7.67</td><td>30.43</td><td>9.92</td><td>276</td><td>26 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2362.66	57.95	74.00	-16.05	43.49	27.30	7.67	30.43	9.92	276	26 Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>112.50</td><td>-----</td><td>-----</td><td>97.43</td><td>27.72</td><td>7.80</td><td>30.37</td><td>9.92</td><td>276</td><td>26 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	112.50	-----	-----	97.43	27.72	7.80	30.37	9.92	276	26 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2362.66	57.95	74.00	-16.05	43.49	27.30	7.67	30.43	9.92	276	26 Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2441.00	112.50	-----	-----	97.43	27.72	7.80	30.37	9.92	276	26 Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2387.29</td><td>47.40</td><td>54.00</td><td>-6.60</td><td>32.73</td><td>27.45</td><td>7.71</td><td>30.41</td><td>9.92</td><td>276</td><td>26 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.29	47.40	54.00	-6.60	32.73	27.45	7.71	30.41	9.92	276	26 Average	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>109.52</td><td>-----</td><td>-----</td><td>94.48</td><td>27.70</td><td>7.79</td><td>30.37</td><td>9.92</td><td>276</td><td>26 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	109.52	-----	-----	94.48	27.70	7.79	30.37	9.92	276	26 Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2387.29	47.40	54.00	-6.60	32.73	27.45	7.71	30.41	9.92	276	26 Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2441.00	109.52	-----	-----	94.48	27.70	7.79	30.37	9.92	276	26 Average																																																																																						



Mode	8																																														
	Band Edge - R																																														
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																														
ANT	3																																														
Pol.	Horizontal						Fundamental																																								
Peak	Level (dBuV/m) Date: 2025-07-16 PEAK_BE_74 1 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2496.40</td><td>59.08</td><td>74.00</td><td>-14.92</td><td>43.61</td><td>28.00</td><td>7.88</td><td>30.33</td><td>9.92</td><td>276</td><td>26</td><td>Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2496.40	59.08	74.00	-14.92	43.61	28.00	7.88	30.33	9.92	276	26	Peak	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1 2496.40	59.08	74.00	-14.92	43.61	28.00	7.88	30.33	9.92	276	26	Peak																																				
Avg	Level (dBuV/m) Date: 2025-07-16 AVG_BE_54 1 Frequency (MHz) Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 2493.52</td><td>48.01</td><td>54.00</td><td>-5.99</td><td>32.55</td><td>28.00</td><td>7.87</td><td>30.33</td><td>9.92</td><td>276</td><td>26</td><td>Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2493.52	48.01	54.00	-5.99	32.55	28.00	7.87	30.33	9.92	276	26	Average	Blank				
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																					
1 2493.52	48.01	54.00	-5.99	32.55	28.00	7.87	30.33	9.92	276	26	Average																																				



Mode	8																																																																																																
	Band Edge - L																																																																																																
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																
ANT	3																																																																																																
Pol.	Vertical						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2376.94</td><td>57.69</td><td>74.00</td><td>-16.31</td><td>43.20</td><td>27.30</td><td>7.69</td><td>30.42</td><td>9.92</td><td>273</td><td>91 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2376.94	57.69	74.00	-16.31	43.20	27.30	7.69	30.42	9.92	273	91 Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>116.77</td><td>-----</td><td>-----</td><td>101.70</td><td>27.72</td><td>7.80</td><td>30.37</td><td>9.92</td><td>273</td><td>91 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	116.77	-----	-----	101.70	27.72	7.80	30.37	9.92	273	91 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2376.94	57.69	74.00	-16.31	43.20	27.30	7.69	30.42	9.92	273	91 Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2441.00	116.77	-----	-----	101.70	27.72	7.80	30.37	9.92	273	91 Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.78</td><td>47.23</td><td>54.00</td><td>-6.77</td><td>32.51</td><td>27.50</td><td>7.71</td><td>30.41</td><td>9.92</td><td>273</td><td>91 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.78	47.23	54.00	-6.77	32.51	27.50	7.71	30.41	9.92	273	91 Average	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2441.00</td><td>113.48</td><td>-----</td><td>-----</td><td>98.41</td><td>27.72</td><td>7.80</td><td>30.37</td><td>9.92</td><td>273</td><td>91 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2441.00	113.48	-----	-----	98.41	27.72	7.80	30.37	9.92	273	91 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2389.78	47.23	54.00	-6.77	32.51	27.50	7.71	30.41	9.92	273	91 Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																									
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor		Remark																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2441.00	113.48	-----	-----	98.41	27.72	7.80	30.37	9.92	273	91 Average																																																																																						



Mode	8																																																		
	Band Edge - R																																																		
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																		
ANT	3																																																		
Pol.	Vertical						Fundamental																																												
Peak	Level (dBuV/m) Date: 2025-07-16 PEAK_BE_74 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2495.86</td><td>59.18</td><td>74.00</td><td>-14.82</td><td>43.71</td><td>28.00</td><td>7.88</td><td>30.33</td><td>9.92</td><td>273</td><td>91</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2495.86	59.18	74.00	-14.82	43.71	28.00	7.88	30.33	9.92	273	91	Peak	Blank					
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																								
1	2495.86	59.18	74.00	-14.82	43.71	28.00	7.88	30.33	9.92	273	91	Peak																																							
Avg	Level (dBuV/m) Date: 2025-07-16 AVG_BE_54 Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2498.58</td><td>47.96</td><td>54.00</td><td>-6.04</td><td>32.51</td><td>28.00</td><td>7.87</td><td>30.34</td><td>9.92</td><td>273</td><td>91</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2498.58	47.96	54.00	-6.04	32.51	28.00	7.87	30.34	9.92	273	91	Average	Blank					
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																							
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																								
1	2498.58	47.96	54.00	-6.04	32.51	28.00	7.87	30.34	9.92	273	91	Average																																							



Mode	8																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5 Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																								
ANT	3																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2025-07-17 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 300060009000120001500018000 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4882.00</td><td>40.47</td><td>74.00</td><td>-33.53</td><td>62.40</td><td>32.93</td><td>11.05</td><td>66.32</td><td>0.41</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7323.00</td><td>44.68</td><td>74.00</td><td>-29.32</td><td>59.89</td><td>36.90</td><td>13.31</td><td>65.76</td><td>0.34</td><td>--</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	40.47	74.00	-33.53	62.40	32.93	11.05	66.32	0.41	--	Peak	2	7323.00	44.68	74.00	-29.32	59.89	36.90	13.31	65.76	0.34	--	Peak	Level (dBuV/m) Date: 2025-07-17 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 300060009000120001500018000 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4882.00</td><td>41.92</td><td>74.00</td><td>-32.08</td><td>63.94</td><td>32.86</td><td>11.05</td><td>66.33</td><td>0.40</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7323.00</td><td>45.21</td><td>74.00</td><td>-28.79</td><td>60.20</td><td>37.20</td><td>13.27</td><td>65.75</td><td>0.29</td><td>--</td><td>Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4882.00	41.92	74.00	-32.08	63.94	32.86	11.05	66.33	0.40	--	Peak	2	7323.00	45.21	74.00	-28.79	60.20	37.20	13.27	65.75	0.29	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4882.00	40.47	74.00	-33.53	62.40	32.93	11.05	66.32	0.41	--	Peak																																																																																																														
2	7323.00	44.68	74.00	-29.32	59.89	36.90	13.31	65.76	0.34	--	Peak																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4882.00	41.92	74.00	-32.08	63.94	32.86	11.05	66.33	0.40	--	Peak																																																																																																														
2	7323.00	45.21	74.00	-28.79	60.20	37.20	13.27	65.75	0.29	--	Peak																																																																																																														







Mode	8	
	Harmonic	
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL
	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL



Mode	9																																																																																			
	Band Edge																																																																																			
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																			
ANT	3																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.90</td><td>59.39</td><td>74.00</td><td>-14.61</td><td>44.01</td><td>27.94</td><td>7.86</td><td>30.34</td><td>9.92</td><td>356</td><td>84 Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.90	59.39	74.00	-14.61	44.01	27.94	7.86	30.34	9.92	356	84 Peak	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>110.65</td><td>-----</td><td>-----</td><td>95.32</td><td>27.90</td><td>7.85</td><td>30.34</td><td>9.92</td><td>356</td><td>84 Peak</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	110.65	-----	-----	95.32	27.90	7.85	30.34	9.92	356	84 Peak
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1	2483.90	59.39	74.00	-14.61	44.01	27.94	7.86	30.34	9.92	356	84 Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1	2480.00	110.65	-----	-----	95.32	27.90	7.85	30.34	9.92	356	84 Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.52</td><td>47.54</td><td>54.00</td><td>-6.46</td><td>32.16</td><td>27.94</td><td>7.86</td><td>30.34</td><td>9.92</td><td>356</td><td>84 Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.52	47.54	54.00	-6.46	32.16	27.94	7.86	30.34	9.92	356	84 Average	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>107.64</td><td>-----</td><td>-----</td><td>92.31</td><td>27.90</td><td>7.85</td><td>30.34</td><td>9.92</td><td>356</td><td>84 Average</td></tr></table>						Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	107.64	-----	-----	92.31	27.90	7.85	30.34	9.92	356	84 Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1	2483.52	47.54	54.00	-6.46	32.16	27.94	7.86	30.34	9.92	356	84 Average																																																																									
Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1	2480.00	107.64	-----	-----	92.31	27.90	7.85	30.34	9.92	356	84 Average																																																																									







Mode	9																																																																																									
	Band Edge																																																																																									
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																									
ANT	3																																																																																									
Pol.	Vertical						Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2025-07-18  Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2490.56</td><td>58.79</td><td>74.00</td><td>-15.21</td><td>43.34</td><td>28.00</td><td>7.87</td><td>30.34</td><td>9.92</td><td>400</td><td>117</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2490.56	58.79	74.00	-15.21	43.34	28.00	7.87	30.34	9.92	400	117	Peak	Level (dBuV/m) Date: 2025-07-18  Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>109.11</td><td>-----</td><td>-----</td><td>93.78</td><td>27.90</td><td>7.85</td><td>30.34</td><td>9.92</td><td>400</td><td>117</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	109.11	-----	-----	93.78	27.90	7.85	30.34	9.92	400	117	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2490.56	58.79	74.00	-15.21	43.34	28.00	7.87	30.34	9.92	400	117	Peak																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2480.00	109.11	-----	-----	93.78	27.90	7.85	30.34	9.92	400	117	Peak																																																																														
Avg	Level (dBuV/m) Date: 2025-07-18  Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2483.74</td><td>47.46</td><td>54.00</td><td>-6.54</td><td>32.08</td><td>27.94</td><td>7.86</td><td>30.34</td><td>9.92</td><td>400</td><td>117</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2483.74	47.46	54.00	-6.54	32.08	27.94	7.86	30.34	9.92	400	117	Average	Level (dBuV/m) Date: 2025-07-18  Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2480.00</td><td>106.05</td><td>-----</td><td>-----</td><td>90.72</td><td>27.90</td><td>7.85</td><td>30.34</td><td>9.92</td><td>400</td><td>117</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	2480.00	106.05	-----	-----	90.72	27.90	7.85	30.34	9.92	400	117	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2483.74	47.46	54.00	-6.54	32.08	27.94	7.86	30.34	9.92	400	117	Average																																																																														
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																															
1	2480.00	106.05	-----	-----	90.72	27.90	7.85	30.34	9.92	400	117	Average																																																																														



Mode	9																																																																																																																									
	Harmonic																																																																																																																									
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																									
ANT	3																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2025-07-19 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_250327 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 4960.00</td><td>45.60</td><td>74.00</td><td>-28.40</td><td>67.18</td><td>33.22</td><td>11.06</td><td>66.27</td><td>0.41</td><td>100 299 Peak</td></tr><tr><td>2 4960.00</td><td>36.89</td><td>54.00</td><td>-17.11</td><td>58.47</td><td>33.22</td><td>11.06</td><td>66.27</td><td>0.41</td><td>100 299 Average</td></tr><tr><td>3 7440.00</td><td>44.56</td><td>74.00</td><td>-29.44</td><td>60.07</td><td>36.50</td><td>13.39</td><td>65.77</td><td>0.37</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 4960.00	45.60	74.00	-28.40	67.18	33.22	11.06	66.27	0.41	100 299 Peak	2 4960.00	36.89	54.00	-17.11	58.47	33.22	11.06	66.27	0.41	100 299 Average	3 7440.00	44.56	74.00	-29.44	60.07	36.50	13.39	65.77	0.37	-- -- Peak	Level (dBuV/m) Date: 2025-07-19 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_250327 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 4960.00</td><td>46.63</td><td>74.00</td><td>-27.37</td><td>68.21</td><td>33.22</td><td>11.06</td><td>66.27</td><td>0.41</td><td>100 182 Peak</td></tr><tr><td>2 4960.00</td><td>38.82</td><td>54.00</td><td>-15.18</td><td>60.40</td><td>33.22</td><td>11.06</td><td>66.27</td><td>0.41</td><td>100 182 Average</td></tr><tr><td>3 7440.00</td><td>45.08</td><td>74.00</td><td>-28.92</td><td>60.58</td><td>36.52</td><td>13.38</td><td>65.77</td><td>0.37</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark	MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 4960.00	46.63	74.00	-27.37	68.21	33.22	11.06	66.27	0.41	100 182 Peak	2 4960.00	38.82	54.00	-15.18	60.40	33.22	11.06	66.27	0.41	100 182 Average	3 7440.00	45.08	74.00	-28.92	60.58	36.52	13.38	65.77	0.37	-- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																	
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																	
1 4960.00	45.60	74.00	-28.40	67.18	33.22	11.06	66.27	0.41	100 299 Peak																																																																																																																	
2 4960.00	36.89	54.00	-17.11	58.47	33.22	11.06	66.27	0.41	100 299 Average																																																																																																																	
3 7440.00	44.56	74.00	-29.44	60.07	36.50	13.39	65.77	0.37	-- -- Peak																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																	
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																	
1 4960.00	46.63	74.00	-27.37	68.21	33.22	11.06	66.27	0.41	100 182 Peak																																																																																																																	
2 4960.00	38.82	54.00	-15.18	60.40	33.22	11.06	66.27	0.41	100 182 Average																																																																																																																	
3 7440.00	45.08	74.00	-28.92	60.58	36.52	13.38	65.77	0.37	-- -- Peak																																																																																																																	



Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-07-19  Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-19  Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL
	Level (dBuV/m) Date: 2025-07-19  Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-19  Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL



Mode	27																																																																																																																																																																																					
	LF																																																																																																																																																																																					
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																																																																					
ANT	3																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
QPI Peak	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06_241005 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>37.76</td><td>24.03</td><td>40.00</td><td>-15.97</td><td>34.38</td><td>20.09</td><td>0.95</td><td>32.25</td><td>0.06 -- -- Peak</td></tr><tr><td>2</td><td>198.78</td><td>34.49</td><td>43.50</td><td>-9.01</td><td>49.24</td><td>15.15</td><td>2.19</td><td>32.16</td><td>0.07 -- -- Peak</td></tr><tr><td>3</td><td>216.24</td><td>31.17</td><td>46.00</td><td>-14.83</td><td>45.81</td><td>15.19</td><td>2.28</td><td>32.18</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>294.81</td><td>28.26</td><td>46.00</td><td>-17.74</td><td>38.54</td><td>19.21</td><td>2.66</td><td>32.22</td><td>0.07 -- -- Peak</td></tr><tr><td>5</td><td>729.37</td><td>29.97</td><td>46.00</td><td>-16.03</td><td>30.13</td><td>27.86</td><td>4.20</td><td>32.36</td><td>0.14 -- -- Peak</td></tr><tr><td>6</td><td>950.53</td><td>33.36</td><td>46.00</td><td>-12.64</td><td>28.46</td><td>30.99</td><td>4.81</td><td>31.16</td><td>0.26 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	37.76	24.03	40.00	-15.97	34.38	20.09	0.95	32.25	0.06 -- -- Peak	2	198.78	34.49	43.50	-9.01	49.24	15.15	2.19	32.16	0.07 -- -- Peak	3	216.24	31.17	46.00	-14.83	45.81	15.19	2.28	32.18	0.07 -- -- Peak	4	294.81	28.26	46.00	-17.74	38.54	19.21	2.66	32.22	0.07 -- -- Peak	5	729.37	29.97	46.00	-16.03	30.13	27.86	4.20	32.36	0.14 -- -- Peak	6	950.53	33.36	46.00	-12.64	28.46	30.99	4.81	31.16	0.26 -- -- Peak	Level (dBuV/m) Date: 2025-07-18 Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06_241005 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>39.70</td><td>27.72</td><td>40.00</td><td>-12.28</td><td>39.15</td><td>19.79</td><td>0.97</td><td>32.25</td><td>0.06 100 360 QP</td></tr><tr><td>2</td><td>177.44</td><td>33.63</td><td>43.50</td><td>-9.87</td><td>48.24</td><td>15.42</td><td>2.07</td><td>32.18</td><td>0.08 -- -- Peak</td></tr><tr><td>3</td><td>266.68</td><td>23.84</td><td>46.00</td><td>-22.16</td><td>33.87</td><td>19.59</td><td>2.53</td><td>32.22</td><td>0.07 -- -- Peak</td></tr><tr><td>4</td><td>415.09</td><td>25.34</td><td>46.00</td><td>-20.66</td><td>31.94</td><td>22.32</td><td>3.20</td><td>32.23</td><td>0.11 -- -- Peak</td></tr><tr><td>5</td><td>757.50</td><td>30.62</td><td>46.00</td><td>-15.38</td><td>30.13</td><td>28.37</td><td>4.28</td><td>32.31</td><td>0.15 -- -- Peak</td></tr><tr><td>6</td><td>940.83</td><td>33.25</td><td>46.00</td><td>-12.75</td><td>28.69</td><td>30.80</td><td>4.78</td><td>31.26</td><td>0.24 -- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	39.70	27.72	40.00	-12.28	39.15	19.79	0.97	32.25	0.06 100 360 QP	2	177.44	33.63	43.50	-9.87	48.24	15.42	2.07	32.18	0.08 -- -- Peak	3	266.68	23.84	46.00	-22.16	33.87	19.59	2.53	32.22	0.07 -- -- Peak	4	415.09	25.34	46.00	-20.66	31.94	22.32	3.20	32.23	0.11 -- -- Peak	5	757.50	30.62	46.00	-15.38	30.13	28.37	4.28	32.31	0.15 -- -- Peak	6	940.83	33.25	46.00	-12.75	28.69	30.80	4.78	31.26	0.24 -- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																													
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	37.76	24.03	40.00	-15.97	34.38	20.09	0.95	32.25	0.06 -- -- Peak																																																																																																																																																																													
2	198.78	34.49	43.50	-9.01	49.24	15.15	2.19	32.16	0.07 -- -- Peak																																																																																																																																																																													
3	216.24	31.17	46.00	-14.83	45.81	15.19	2.28	32.18	0.07 -- -- Peak																																																																																																																																																																													
4	294.81	28.26	46.00	-17.74	38.54	19.21	2.66	32.22	0.07 -- -- Peak																																																																																																																																																																													
5	729.37	29.97	46.00	-16.03	30.13	27.86	4.20	32.36	0.14 -- -- Peak																																																																																																																																																																													
6	950.53	33.36	46.00	-12.64	28.46	30.99	4.81	31.16	0.26 -- -- Peak																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	39.70	27.72	40.00	-12.28	39.15	19.79	0.97	32.25	0.06 100 360 QP																																																																																																																																																																													
2	177.44	33.63	43.50	-9.87	48.24	15.42	2.07	32.18	0.08 -- -- Peak																																																																																																																																																																													
3	266.68	23.84	46.00	-22.16	33.87	19.59	2.53	32.22	0.07 -- -- Peak																																																																																																																																																																													
4	415.09	25.34	46.00	-20.66	31.94	22.32	3.20	32.23	0.11 -- -- Peak																																																																																																																																																																													
5	757.50	30.62	46.00	-15.38	30.13	28.37	4.28	32.31	0.15 -- -- Peak																																																																																																																																																																													
6	940.83	33.25	46.00	-12.75	28.69	30.80	4.78	31.26	0.24 -- -- Peak																																																																																																																																																																													



Mode	28																																																																																							
	SHF																																																																																							
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																							
ANT	3																																																																																							
Pol.	Horizontal	Vertical																																																																																						
Peak	Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 1m SHF_00994_250109 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24912.00</td><td>39.09</td><td>74.00</td><td>-34.91</td><td>55.94</td><td>39.68</td><td>6.31</td><td>53.30</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	24912.00	39.09	74.00	-34.91	55.94	39.68	6.31	53.30	-9.54	--	-- Peak	Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 1m SHF_00994_250109 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24976.00</td><td>38.83</td><td>74.00</td><td>-35.17</td><td>55.00</td><td>39.55</td><td>6.32</td><td>53.30</td><td>-9.54</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	24976.00	38.83	74.00	-35.17	55.00	39.55	6.32	53.30	-9.54	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	24912.00	39.09	74.00	-34.91	55.94	39.68	6.31	53.30	-9.54	--	-- Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	24976.00	38.83	74.00	-35.17	55.00	39.55	6.32	53.30	-9.54	--	-- Peak																																																																													

**C2-1. Radiated Spurious Emission Test Modes**

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 10	2400-2483.5	4	Bluetooth BR_GFSK	00	2402	3Mbps	-	-
Mode 11	2400-2483.5	4	Bluetooth BR_GFSK	39	2441	3Mbps	-	-
Mode 12	2400-2483.5	4	Bluetooth BR_GFSK	78	2480	3Mbps	-	-
Mode 33	2400-2483.5	4	Bluetooth BR_GFSK	78	2480	3Mbps	-	LF
Mode 34	2400-2483.5	4	Bluetooth BR_GFSK	78	2480	3Mbps	-	SHF





**C2-2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
10	Bluetooth BR_GFSK	00	2387.56	46.95	54.00	-7.05	H	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	00	4804.00	35.99	54.00	-18.01	H	Avg.	Pass	-	Harmonic
11	Bluetooth BR_GFSK	39	2498.80	47.74	54.00	-6.26	H	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	39	4882.00	40.82	54.00	-13.18	H	Avg.	Pass	-	Harmonic
12	Bluetooth BR_GFSK	78	2483.56	48.24	54.00	-5.76	H	Avg.	Pass	-	Band Edge
	Bluetooth BR_GFSK	78	4960.00	39.04	54.00	-14.96	V	Avg.	Pass	-	Harmonic
33	LF	78	205.57	33.65	43.50	-9.85	H	Peak	Pass	-	LF
34	SHF	78	25680.00	39.35	74.00	-34.65	H	Peak	Pass	-	SHF



Mode	10																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																			
ANT	4																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2383.23</td><td>57.80</td><td>74.00</td><td>-16.20</td><td>43.24</td><td>27.36</td><td>7.70</td><td>30.42</td><td>9.92</td><td>154</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2383.23	57.80	74.00	-16.20	43.24	27.36	7.70	30.42	9.92	154	360	Peak	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>108.37</td><td>-----</td><td>-----</td><td>93.52</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>154</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	108.37	-----	-----	93.52	27.60	7.73	30.40	9.92	154	360	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2383.23	57.80	74.00	-16.20	43.24	27.36	7.70	30.42	9.92	154	360	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	108.37	-----	-----	93.52	27.60	7.73	30.40	9.92	154	360	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2387.56</td><td>46.95</td><td>54.00</td><td>-7.05</td><td>32.28</td><td>27.45</td><td>7.71</td><td>30.41</td><td>9.92</td><td>154</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2387.56	46.95	54.00	-7.05	32.28	27.45	7.71	30.41	9.92	154	360	Average	Level (dBuV/m) Date: 2025-07-16 Frequency (MHz) Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 HORIZONTAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>105.65</td><td>-----</td><td>-----</td><td>90.80</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>154</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	105.65	-----	-----	90.80	27.60	7.73	30.40	9.92	154	360	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2387.56	46.95	54.00	-7.05	32.28	27.45	7.71	30.41	9.92	154	360	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2402.00	105.65	-----	-----	90.80	27.60	7.73	30.40	9.92	154	360	Average																																																																																								



Mode	10																																																																																											
	Band Edge																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																											
ANT	4																																																																																											
Pol.	Vertical												Fundamental																																																																															
Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2381.67</td><td>57.55</td><td>74.00</td><td>-16.45</td><td>43.02</td><td>27.33</td><td>7.70</td><td>30.42</td><td>9.92</td><td>270</td><td>104</td><td>Peak</td></tr></tbody></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	2381.67	57.55	74.00	-16.45	43.02	27.33	7.70	30.42	9.92	270	104	Peak	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>105.99</td><td>-----</td><td>-----</td><td>91.14</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>270</td><td>104</td><td>Peak</td></tr></tbody></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	2402.00	105.99	-----	-----	91.14	27.60	7.73	30.40	9.92	270	104	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																
1	2381.67	57.55	74.00	-16.45	43.02	27.33	7.70	30.42	9.92	270	104	Peak																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																
1	2402.00	105.99	-----	-----	91.14	27.60	7.73	30.40	9.92	270	104	Peak																																																																																
Avg	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_BE_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2385.16</td><td>46.58</td><td>54.00</td><td>-7.42</td><td>31.97</td><td>27.40</td><td>7.70</td><td>30.41</td><td>9.92</td><td>270</td><td>104</td><td>Average</td></tr></tbody></table>														Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	2385.16	46.58	54.00	-7.42	31.97	27.40	7.70	30.41	9.92	270	104	Average	Level (dBuV/m) Date: 2025-07-16  Site : 03CH16-HY Condition: AVG_54 3m 91200-1522_250327 VERTICAL : RBW:1000.000kHz VBW:0.360kHz SMT:Auto <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2402.00</td><td>103.29</td><td>-----</td><td>-----</td><td>88.44</td><td>27.60</td><td>7.73</td><td>30.40</td><td>9.92</td><td>270</td><td>104</td><td>Average</td></tr></tbody></table>		Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	2402.00	103.29	-----	-----	88.44	27.60	7.73	30.40	9.92	270	104	Average
	Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																
1	2385.16	46.58	54.00	-7.42	31.97	27.40	7.70	30.41	9.92	270	104	Average																																																																																
	Freq	Level	Limit	Line Margin	Read Level	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																
1	2402.00	103.29	-----	-----	88.44	27.60	7.73	30.40	9.92	270	104	Average																																																																																



Mode	10																																																																																																																													
	Harmonic																																																																																																																													
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																							
Peak Avg	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_250327 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>43.65</td><td>74.00</td><td>-30.35</td><td>66.10</td><td>32.52</td><td>11.04</td><td>66.40</td><td>0.39</td><td>200</td><td>319</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>35.99</td><td>54.00</td><td>-18.01</td><td>58.44</td><td>32.52</td><td>11.04</td><td>66.40</td><td>0.39</td><td>200</td><td>319</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	43.65	74.00	-30.35	66.10	32.52	11.04	66.40	0.39	200	319	Peak	2	4804.00	35.99	54.00	-18.01	58.44	32.52	11.04	66.40	0.39	200	319	Average	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_250327 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>41.46</td><td>74.00</td><td>-32.54</td><td>63.91</td><td>32.52</td><td>11.04</td><td>66.40</td><td>0.39</td><td>200</td><td>32</td><td>Peak</td></tr><tr><td>2</td><td>4804.00</td><td>31.30</td><td>54.00</td><td>-22.70</td><td>53.75</td><td>32.52</td><td>11.04</td><td>66.40</td><td>0.39</td><td>200</td><td>32</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4804.00	41.46	74.00	-32.54	63.91	32.52	11.04	66.40	0.39	200	32	Peak	2	4804.00	31.30	54.00	-22.70	53.75	32.52	11.04	66.40	0.39	200	32	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4804.00	43.65	74.00	-30.35	66.10	32.52	11.04	66.40	0.39	200	319	Peak																																																																																																																		
2	4804.00	35.99	54.00	-18.01	58.44	32.52	11.04	66.40	0.39	200	319	Average																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	4804.00	41.46	74.00	-32.54	63.91	32.52	11.04	66.40	0.39	200	32	Peak																																																																																																																		
2	4804.00	31.30	54.00	-22.70	53.75	32.52	11.04	66.40	0.39	200	32	Average																																																																																																																		



Mode	10	
	Harmonic	
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL
	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 HORIZONTAL	Level (dBuV/m) Date: 2025-07-17 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_250327 VERTICAL