



The following test report with report number FR5N0803-01M is an addendum to the RF spot check test report for FCC ID: A4RG4HCD variant model G4HCD. It contains test data from FCC ID: A4RGBC0H reference model GBC0H that is referenced in the variant model G4HCD RF spot check report.




FCC CO-LOCATION RADIO TEST REPORT

FCC ID : A4RGBC0H
Equipment : Phone
Model Name : GBC0H
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Nov. 26, 2025 and testing was performed from Nov. 28, 2025 to Feb. 26, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Connection Diagram of Test System.....	8
2.3 EUT Operation Test Setup	8
3 Test Result	9
3.1 Unwanted Emissions Measurement.....	9
3.2 Antenna Requirements.....	15
4 List of Measuring Equipment.....	16
5 Measurement Uncertainty	18
Appendix A. Radiated Spurious Emission Test Data	
Appendix B. Duty Cycle Plots	
Appendix C. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR5N0803-01M	01	Initial issue of report	Apr. 21, 2026
FR5N0803-01M	02	Revised Page 9 This report is an updated version, replacing the report issued on Apr. 21, 2026.	Apr. 29, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(d) 15.407(b)	Unwanted Emissions	Pass	-
3.2	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Shannon Huang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx.
Antenna Type WLAN: <Ant. 3>: IFA Antenna <Ant. 4>: IFA Antenna

EUT Information List	
S/N	Performed Test Item
61041FDDV0000U 61041FDDV0000M	Radiated Spurious Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant. 3: 0.8 Ant. 4: -1.4
5150 MHz ~ 5250 MHz	Peak Gain (dBi)	Ant. 3: -2.9 Ant. 4: -4.2
5925 MHz ~ 6425 MHz	Peak Gain (dBi)	<6G_Ant3 + 6G_Ant4> Correlated: -0.28 Uncorrelated: -3.22

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. 03CH15-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures.

2.1 Carrier Frequency and Channel

2400-2483.5 MHz			
Bluetooth – LE 1Mbps		802.11g	
Channel	Channel	Channel	Freq. (MHz)
39	2480	06	2437


5150-5250 MHz			
802.11a		802.11be EHT20	
Channel	Channel	Channel	Freq. (MHz)
36	5180	36	5180

5925-6425 MHz			
802.11a		-	
Channel	Freq. (MHz)	-	-
01	5955	-	-

<Co-Location>

Modulation	Data Rate	Worst Plane
2.4GHz 802.11g for MIMO <Ant. 3+4> + 5GHz 802.11a for MIMO <Ant. 3+4>	6 Mbps + 6 Mbps	X Plane with Adapter
2.4GHz 802.11g for MIMO <Ant. 3+4> + 6GHz 802.11a for MIMO <Ant. 3+4>	6 Mbps + 6 Mbps	Z Plane with Adapter
Bluetooth-LE_GFSK for MIMO < Ant. 3+4> + 5GHz 802.11be EHT20 for MIMO < Ant. 3+4>	1 Mbps + MCS0	Z Plane with Adapter

2.2 Connection Diagram of Test System



Radiation Tx Test Setup								
No.	Power Source	Connection Type	Test Mode					
			1~4	-	-	-	-	-
B1	AC : 120V/60Hz	AC Power Cable	X	-	-	-	-	-

2.3 EUT Operation Test Setup

The RF test items, utility “CMD” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.1.1 Limit of Unwanted Emissions

<For 2402 MHz ~ 2480 MHz>

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

<For 5150 MHz ~ 5250 MHz>

For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

<For 5925 MHz ~ 6425 MHz>

For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an e.i.r.p. of -27 dBm/MHz.

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27 (RMS)	68.2
- 7 (Peak)	88.2

According 987594 D02 U-NII 6GHz EMC Measurement v01 section G:

Unwanted emissions outside of restricted bands are measured with a RMS detector.

In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit

Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(2) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.1.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.1.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



3.1.6 Duty Cycle

Please refer to Appendix B.

3.1.7 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix A.



3.2 Antenna Requirements

3.2.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.2.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

(3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9kHz~30MHz	May 06, 2025	Nov. 28, 2025~ Feb. 26, 2026	May 05, 2026	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	37059 & 01	30MHz~1GHz	Mar. 01, 2025	Nov. 28, 2025~ Feb. 26, 2026	Feb. 28, 2026	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-02294	1GHz~18GHz	Jun. 06, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jun. 05, 2026	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1225	18GHz~40GHz	Jul. 02, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jul. 01, 2026	Radiation (03CH15-HY)
Amplifier	EMEC	EM1G18G	060837	1GHz~18GHz	Feb. 13, 2025	Nov. 28, 2025~ Feb. 09, 2026	Feb. 12, 2026	Radiation (03CH15-HY)
Amplifier	EMEC	EM1G18G	060837	1GHz~18GHz	Feb. 10, 2026	Feb. 10, 2026~ Feb. 26, 2026	Feb. 09, 2027	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 14, 2025	Nov. 28, 2025~ Feb. 10, 2026	Feb. 13, 2026	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 11, 2026	Feb. 11, 2026~ Feb. 26, 2026	Feb. 10, 2027	Radiation (03CH15-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 26, 2025	Nov. 28, 2025~ Feb. 26, 2026	May 25, 2026	Radiation (03CH15-HY)
Preamplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 24, 2024	Nov. 28, 2025~ Dec. 17, 2025	Dec. 23, 2025	Radiation (03CH15-HY)
Preamplifier	SONOMA	310N	363440	9kHz~1GHz	Dec. 18, 2025	Dec. 18, 2025~ Feb. 26, 2026	Dec. 17, 2026	Radiation (03CH15-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20Hz~8.4GHz	Apr. 21, 2025	Nov. 28, 2025~ Feb. 26, 2026	Apr. 20, 2026	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44Gz	Jul. 15, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jul. 14, 2026	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY519228/2, 803950/2,508 407/2E	30MHz~40GHz	Sep. 24, 2025	Nov. 28, 2025~ Feb. 26, 2026	Sep. 23, 2026	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40G	Dec. 31, 2024	Nov. 28, 2025~ Dec. 17, 2025	Dec. 30, 2025	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804011/2,804 012/2	18-40G	Dec. 18, 2025	Dec. 18, 2025~ Feb. 26, 2026	Dec. 17, 2026	Radiation (03CH15-HY)
Hygrometer	TECPEL	DTM-302	SN2	N/A	Aug. 26, 2025	Nov. 28, 2025~ Feb. 26, 2026	Aug. 25, 2026	Radiation (03CH15-HY)
Filter	Wainwright	WHKX12- 2700-3000- 18000-60ST	SN4	3GHz High Pass Filter	Jun. 03, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jun. 02, 2026	Radiation (03CH15-HY)
Filter	wright	WLJ4-1000- 1530-6000- 40ST	SN4	1.53GHz Low Pass Filter	Jun. 03, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jun. 02, 2026	Radiation (03CH15-HY)
Filter	wright	WHKX8- 5872.5-6750- 18000-40ST	SN6	6.75GHz High Pass Filter	Jun. 03, 2025	Nov. 28, 2025~ Feb. 26, 2026	Jun. 02, 2026	Radiation (03CH15-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Nov. 28, 2025~ Feb. 26, 2026	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Nov. 28, 2025~ Feb. 26, 2026	N/A	Radiation (03CH15-HY)
Software	Audix	E3_V9_23062 1	RK-002394	N/A	N/A	Nov. 28, 2025~ Feb. 26, 2026	N/A	Radiation (03CH15-HY)

5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
--	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.30 dB
--	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50 dB
--	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.90 dB
--	---------



Appendix A. Radiated Spurious Emission

Test Engineer :	Leo Li, Karl Hou, and Lucifer Jiang	Temperature :	19.0 ~ 23.0°C
		Relative Humidity :	60.0 ~ 64.5%

Note symbol

-L	Low channel location
-R	High channel location

A1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5 + 5150-5250	MIMO+MIMO	802.11g + 802.11a	CH06 CH36	2437MHz 5180MHz	6Mbps 6Mbps	-	Harmonic
Mode 2	2400-2483.5 + 5925-6425	MIMO+MIMO	802.11g + 802.11a	CH06 CH01	2437MHz 5955MHz	6Mbps 6Mbps	-	Harmonic
Mode 3	2400-2483.5 + 5150-5250	MIMO+MIMO	Bluetooth-LE_GFSK + 802.11be EHT20	CH39 CH36	2480MHz 5180MHz	1Mbps MCS0	Full RU	Harmonic
Mode 4	2400-2483.5 + 5150-5250	MIMO+MIMO	Bluetooth-LE_GFSK + 802.11be EHT20	CH39 CH36	2480MHz 5180MHz	1Mbps MCS0	Full RU	LF







A2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	802.11g + 802.11a	6 + 36	4874.00	41.16	54.00	-12.84	V	Avg.	Pass	-	Harmonic
2	802.11g + 802.11a	6 + 1	4874.00	41.06	54.00	-12.94	V	Avg.	Pass	-	Harmonic
3	Bluetooth-LE_GFSK + 802.11be EHT20	39 + 36	7440.00	49.09	54.00	-4.91	H	Avg.	Pass	Full RU	Harmonic
4	Bluetooth-LE_GFSK + 802.11be EHT20	39 + 36	745.86	36.82	46.00	-9.18	V	Peak	Pass	Full RU	LF



Mode	1																																																																																																																																																																	
	Co-location Harmonic																																																																																																																																																																	
	2400-2483.5MHz_802.11g_CH06_2437MHz 5150-5250MHz_802.11a_CH36_5180MHz																																																																																																																																																																	
ANT	MIMO+MIMO																																																																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																																																																
1G ~18G Peak Avg	Level (dBuV/m) Date: 2026-02-13 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4874.00</td><td>53.53</td><td>74.00</td><td>-20.47</td><td>44.82</td><td>32.70</td><td>12.35</td><td>36.87</td><td>0.53</td><td>-- Peak</td></tr><tr><td>2 4874.00</td><td>41.00</td><td>54.00</td><td>-13.00</td><td>32.29</td><td>32.70</td><td>12.35</td><td>36.87</td><td>0.53</td><td>-- Average</td></tr><tr><td>3 7311.00</td><td>45.54</td><td>74.00</td><td>-28.46</td><td>51.83</td><td>36.86</td><td>15.26</td><td>59.54</td><td>1.13</td><td>-- Peak</td></tr><tr><td>4 10360.00</td><td>45.86</td><td>68.20</td><td>-22.34</td><td>47.30</td><td>38.60</td><td>18.24</td><td>58.84</td><td>0.56</td><td>-- Peak</td></tr><tr><td>5 15540.00</td><td>46.75</td><td>74.00</td><td>-27.25</td><td>43.66</td><td>38.20</td><td>22.67</td><td>58.43</td><td>0.65</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4874.00	53.53	74.00	-20.47	44.82	32.70	12.35	36.87	0.53	-- Peak	2 4874.00	41.00	54.00	-13.00	32.29	32.70	12.35	36.87	0.53	-- Average	3 7311.00	45.54	74.00	-28.46	51.83	36.86	15.26	59.54	1.13	-- Peak	4 10360.00	45.86	68.20	-22.34	47.30	38.60	18.24	58.84	0.56	-- Peak	5 15540.00	46.75	74.00	-27.25	43.66	38.20	22.67	58.43	0.65	-- Peak	Level (dBuV/m) Date: 2026-02-13 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4874.00</td><td>53.73</td><td>74.00</td><td>-20.27</td><td>45.02</td><td>32.70</td><td>12.35</td><td>36.87</td><td>0.53</td><td>-- Peak</td></tr><tr><td>2 4874.00</td><td>41.16</td><td>54.00</td><td>-12.84</td><td>32.45</td><td>32.70</td><td>12.35</td><td>36.87</td><td>0.53</td><td>-- Average</td></tr><tr><td>3 7311.00</td><td>47.14</td><td>74.00</td><td>-26.86</td><td>53.43</td><td>36.86</td><td>15.26</td><td>59.54</td><td>1.13</td><td>-- Peak</td></tr><tr><td>4 10360.00</td><td>45.28</td><td>68.20</td><td>-22.92</td><td>46.72</td><td>38.60</td><td>18.24</td><td>58.84</td><td>0.56</td><td>-- Peak</td></tr><tr><td>5 15540.00</td><td>46.87</td><td>74.00</td><td>-27.13</td><td>43.78</td><td>38.20</td><td>22.67</td><td>58.43</td><td>0.65</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4874.00	53.73	74.00	-20.27	45.02	32.70	12.35	36.87	0.53	-- Peak	2 4874.00	41.16	54.00	-12.84	32.45	32.70	12.35	36.87	0.53	-- Average	3 7311.00	47.14	74.00	-26.86	53.43	36.86	15.26	59.54	1.13	-- Peak	4 10360.00	45.28	68.20	-22.92	46.72	38.60	18.24	58.84	0.56	-- Peak	5 15540.00	46.87	74.00	-27.13	43.78	38.20	22.67	58.43	0.65	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 4874.00	53.53	74.00	-20.47	44.82	32.70	12.35	36.87	0.53	-- Peak																																																																																																																																																									
2 4874.00	41.00	54.00	-13.00	32.29	32.70	12.35	36.87	0.53	-- Average																																																																																																																																																									
3 7311.00	45.54	74.00	-28.46	51.83	36.86	15.26	59.54	1.13	-- Peak																																																																																																																																																									
4 10360.00	45.86	68.20	-22.34	47.30	38.60	18.24	58.84	0.56	-- Peak																																																																																																																																																									
5 15540.00	46.75	74.00	-27.25	43.66	38.20	22.67	58.43	0.65	-- Peak																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 4874.00	53.73	74.00	-20.27	45.02	32.70	12.35	36.87	0.53	-- Peak																																																																																																																																																									
2 4874.00	41.16	54.00	-12.84	32.45	32.70	12.35	36.87	0.53	-- Average																																																																																																																																																									
3 7311.00	47.14	74.00	-26.86	53.43	36.86	15.26	59.54	1.13	-- Peak																																																																																																																																																									
4 10360.00	45.28	68.20	-22.92	46.72	38.60	18.24	58.84	0.56	-- Peak																																																																																																																																																									
5 15540.00	46.87	74.00	-27.13	43.78	38.20	22.67	58.43	0.65	-- Peak																																																																																																																																																									
18G ~40G Peak	Level (dBuV/m) Date: 2026-02-14 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1223_250702 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 24871.88</td><td>33.19</td><td>68.20</td><td>-35.01</td><td>56.43</td><td>39.60</td><td>0.00</td><td>53.30</td><td>-9.54</td><td>-- PEAK</td></tr><tr><td>2 39605.14</td><td>38.28</td><td>74.00</td><td>-35.72</td><td>58.92</td><td>45.25</td><td>0.00</td><td>56.35</td><td>-9.54</td><td>-- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 24871.88	33.19	68.20	-35.01	56.43	39.60	0.00	53.30	-9.54	-- PEAK	2 39605.14	38.28	74.00	-35.72	58.92	45.25	0.00	56.35	-9.54	-- PEAK	Level (dBuV/m) Date: 2026-02-14 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1223_250702 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 23253.04</td><td>33.09</td><td>68.20</td><td>-35.11</td><td>57.83</td><td>39.20</td><td>0.00</td><td>54.40</td><td>-9.54</td><td>-- PEAK</td></tr><tr><td>2 39576.59</td><td>38.84</td><td>74.00</td><td>-35.16</td><td>59.47</td><td>45.30</td><td>0.00</td><td>56.39</td><td>-9.54</td><td>-- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 23253.04	33.09	68.20	-35.11	57.83	39.20	0.00	54.40	-9.54	-- PEAK	2 39576.59	38.84	74.00	-35.16	59.47	45.30	0.00	56.39	-9.54	-- PEAK																																																												
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 24871.88	33.19	68.20	-35.01	56.43	39.60	0.00	53.30	-9.54	-- PEAK																																																																																																																																																									
2 39605.14	38.28	74.00	-35.72	58.92	45.25	0.00	56.35	-9.54	-- PEAK																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 23253.04	33.09	68.20	-35.11	57.83	39.20	0.00	54.40	-9.54	-- PEAK																																																																																																																																																									
2 39576.59	38.84	74.00	-35.16	59.47	45.30	0.00	56.39	-9.54	-- PEAK																																																																																																																																																									



Mode	1	
	Co-location Harmonic	
	2400-2483.5MHz_802.11g_CH06_2437MHz 5150-5250MHz_802.11a_CH36_5180MHz	
ANT	MIMO+MIMO	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL



2

Mode

Co-location Harmonic

2400-2483.5MHz_802.11g_CH06_2437MHz

5925-6425MHz_802.11a_CH01_5955MHz


ANT

MIMO+MIMO

Pol.


Horizontal

Vertical

1G
~18G
Peak
Avg


Site : 03CH15-HY
Condition: PEAK(UNII) 3m 91200-02294_250606 HORIZONTAL

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg	
1	4874.00	52.31	74.00	-21.69	43.60	32.70	12.35	36.87	0.53	--	--	--	Peak
2	4874.00	41.06	54.00	-12.96	32.33	32.70	12.35	36.87	0.53	--	--	--	Average
3	7311.00	45.23	74.00	-28.77	51.52	36.06	15.26	59.54	1.13	--	--	--	Peak
4	11910.00	47.18	74.00	-26.82	45.59	39.02	19.72	57.75	0.60	--	--	--	Peak
5	17865.00	52.70	74.00	-21.30	45.72	40.05	24.30	58.95	0.78	--	--	--	Peak
6	17865.00	36.72	54.00	-17.28	29.74	40.05	24.30	58.95	0.78	--	--	--	Average




Site : 03CH15-HY
Condition: PEAK(UNII) 3m 91200-02294_250606 VERTICAL

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg	
1	4874.00	52.30	74.00	-21.61	43.68	32.70	12.35	36.87	0.53	--	--	--	Peak
2	4874.00	41.06	54.00	-12.94	32.35	32.70	12.35	36.87	0.53	--	--	--	Average
3	7311.00	45.20	74.00	-28.80	51.49	36.06	15.26	59.54	1.13	--	--	--	Peak
4	11910.00	47.03	74.00	-26.97	45.46	39.01	19.71	57.75	0.60	--	--	--	Peak
5	17865.00	52.12	74.00	-21.88	45.10	40.08	24.30	58.94	0.78	--	--	--	Peak
6	17865.00	36.90	54.00	-17.10	29.92	40.05	24.30	58.95	0.78	--	--	--	Average

18G
~40G
Peak

Site : 03CH15-HY
Condition: PEAK(UNII) 1m SHF_1223_250702 HORIZONTAL





	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg	
1	24988.07	33.14	68.20	-35.06	56.46	39.52	0.00	53.30	-9.54	--	--	--	PEAK
2	39495.96	37.26	74.00	-36.74	58.23	45.07	0.00	56.50	-9.54	--	--	--	PEAK



Site : 03CH15-HY
Condition: PEAK(UNII) 1m SHF_1223_250702 VERTICAL

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	dB	dB	cm	deg	
1	24169.71	31.93	68.20	-36.27	56.05	39.12	0.00	53.70	-9.54	--	--	--	PEAK
2	39514.54	37.44	74.00	-36.56	58.37	45.09	0.00	56.48	-9.54	--	--	--	PEAK



Mode	2	
	Co-location Harmonic	
	2400-2483.5MHz_802.11g_CH06_2437MHz 5925-6425MHz_802.11a_CH01_5955MHz	
ANT	MIMO+MIMO	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24  Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL



Mode	3																																																																																																																																																																																					
	Co-location Harmonic																																																																																																																																																																																					
	2400-2483.5MHz_Bluetooth-LE_GFSK_CH39_2480MHz 5150-5250MHz_802.11be EHT20_CH36_5180MHz																																																																																																																																																																																					
ANT	MIMO+MIMO																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
1G ~18G Peak Avg	Level (dBuV/m) Date: 2026-02-13 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4968.00</td><td>52.01</td><td>74.00</td><td>-21.99</td><td>42.90</td><td>33.04</td><td>12.44</td><td>36.89</td><td>0.52</td><td>-- -- Peak</td></tr><tr><td>2 4968.00</td><td>42.18</td><td>54.00</td><td>-11.82</td><td>33.07</td><td>33.04</td><td>12.44</td><td>36.89</td><td>0.52</td><td>-- -- Average</td></tr><tr><td>3 7440.00</td><td>54.03</td><td>74.00</td><td>-19.97</td><td>60.96</td><td>36.32</td><td>15.40</td><td>59.69</td><td>1.04</td><td>300 319 Peak</td></tr><tr><td>4 7440.00</td><td>49.09</td><td>54.00</td><td>-4.91</td><td>56.02</td><td>36.32</td><td>15.40</td><td>59.69</td><td>1.04</td><td>300 319 Average</td></tr><tr><td>5 10368.00</td><td>46.07</td><td>68.20</td><td>-22.13</td><td>47.51</td><td>38.60</td><td>18.24</td><td>58.84</td><td>0.56</td><td>-- -- Peak</td></tr><tr><td>6 15540.00</td><td>47.69</td><td>74.00</td><td>-26.31</td><td>44.60</td><td>38.20</td><td>22.67</td><td>58.43</td><td>0.65</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4968.00	52.01	74.00	-21.99	42.90	33.04	12.44	36.89	0.52	-- -- Peak	2 4968.00	42.18	54.00	-11.82	33.07	33.04	12.44	36.89	0.52	-- -- Average	3 7440.00	54.03	74.00	-19.97	60.96	36.32	15.40	59.69	1.04	300 319 Peak	4 7440.00	49.09	54.00	-4.91	56.02	36.32	15.40	59.69	1.04	300 319 Average	5 10368.00	46.07	68.20	-22.13	47.51	38.60	18.24	58.84	0.56	-- -- Peak	6 15540.00	47.69	74.00	-26.31	44.60	38.20	22.67	58.43	0.65	-- -- Peak	Level (dBuV/m) Date: 2026-02-13 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 4968.00</td><td>53.52</td><td>74.00</td><td>-20.48</td><td>44.41</td><td>33.04</td><td>12.44</td><td>36.89</td><td>0.52</td><td>-- -- Peak</td></tr><tr><td>2 4968.00</td><td>42.23</td><td>54.00</td><td>-11.77</td><td>33.12</td><td>33.04</td><td>12.44</td><td>36.89</td><td>0.52</td><td>-- -- Average</td></tr><tr><td>3 7440.00</td><td>52.14</td><td>74.00</td><td>-21.86</td><td>59.10</td><td>36.30</td><td>15.40</td><td>59.70</td><td>1.04</td><td>205 316 Peak</td></tr><tr><td>4 7440.00</td><td>46.95</td><td>54.00</td><td>-7.05</td><td>53.88</td><td>36.32</td><td>15.40</td><td>59.69</td><td>1.04</td><td>205 316 Average</td></tr><tr><td>5 10368.00</td><td>46.48</td><td>68.20</td><td>-21.72</td><td>47.92</td><td>38.60</td><td>18.24</td><td>58.84</td><td>0.56</td><td>-- -- Peak</td></tr><tr><td>6 15540.00</td><td>47.83</td><td>74.00</td><td>-26.17</td><td>44.74</td><td>38.20</td><td>22.67</td><td>58.43</td><td>0.65</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 4968.00	53.52	74.00	-20.48	44.41	33.04	12.44	36.89	0.52	-- -- Peak	2 4968.00	42.23	54.00	-11.77	33.12	33.04	12.44	36.89	0.52	-- -- Average	3 7440.00	52.14	74.00	-21.86	59.10	36.30	15.40	59.70	1.04	205 316 Peak	4 7440.00	46.95	54.00	-7.05	53.88	36.32	15.40	59.69	1.04	205 316 Average	5 10368.00	46.48	68.20	-21.72	47.92	38.60	18.24	58.84	0.56	-- -- Peak	6 15540.00	47.83	74.00	-26.17	44.74	38.20	22.67	58.43	0.65	-- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 4968.00	52.01	74.00	-21.99	42.90	33.04	12.44	36.89	0.52	-- -- Peak																																																																																																																																																																													
2 4968.00	42.18	54.00	-11.82	33.07	33.04	12.44	36.89	0.52	-- -- Average																																																																																																																																																																													
3 7440.00	54.03	74.00	-19.97	60.96	36.32	15.40	59.69	1.04	300 319 Peak																																																																																																																																																																													
4 7440.00	49.09	54.00	-4.91	56.02	36.32	15.40	59.69	1.04	300 319 Average																																																																																																																																																																													
5 10368.00	46.07	68.20	-22.13	47.51	38.60	18.24	58.84	0.56	-- -- Peak																																																																																																																																																																													
6 15540.00	47.69	74.00	-26.31	44.60	38.20	22.67	58.43	0.65	-- -- Peak																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 4968.00	53.52	74.00	-20.48	44.41	33.04	12.44	36.89	0.52	-- -- Peak																																																																																																																																																																													
2 4968.00	42.23	54.00	-11.77	33.12	33.04	12.44	36.89	0.52	-- -- Average																																																																																																																																																																													
3 7440.00	52.14	74.00	-21.86	59.10	36.30	15.40	59.70	1.04	205 316 Peak																																																																																																																																																																													
4 7440.00	46.95	54.00	-7.05	53.88	36.32	15.40	59.69	1.04	205 316 Average																																																																																																																																																																													
5 10368.00	46.48	68.20	-21.72	47.92	38.60	18.24	58.84	0.56	-- -- Peak																																																																																																																																																																													
6 15540.00	47.83	74.00	-26.17	44.74	38.20	22.67	58.43	0.65	-- -- Peak																																																																																																																																																																													
18G ~40G Peak	Level (dBuV/m) Date: 2026-02-14 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1223_250702 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 24863.28</td><td>32.96</td><td>68.20</td><td>-35.24</td><td>56.20</td><td>39.60</td><td>0.00</td><td>53.30</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 38761.16</td><td>36.28</td><td>74.00</td><td>-37.72</td><td>59.06</td><td>43.76</td><td>0.00</td><td>57.00</td><td>-9.54</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 24863.28	32.96	68.20	-35.24	56.20	39.60	0.00	53.30	-9.54	-- -- PEAK	2 38761.16	36.28	74.00	-37.72	59.06	43.76	0.00	57.00	-9.54	-- -- PEAK	Level (dBuV/m) Date: 2026-02-14 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1223_250702 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 24905.59</td><td>32.78</td><td>68.20</td><td>-35.42</td><td>56.02</td><td>39.60</td><td>0.00</td><td>53.30</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 39643.61</td><td>37.30</td><td>74.00</td><td>-36.70</td><td>58.28</td><td>44.86</td><td>0.00</td><td>56.30</td><td>-9.54</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 24905.59	32.78	68.20	-35.42	56.02	39.60	0.00	53.30	-9.54	-- -- PEAK	2 39643.61	37.30	74.00	-36.70	58.28	44.86	0.00	56.30	-9.54	-- -- PEAK																																																																																
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 24863.28	32.96	68.20	-35.24	56.20	39.60	0.00	53.30	-9.54	-- -- PEAK																																																																																																																																																																													
2 38761.16	36.28	74.00	-37.72	59.06	43.76	0.00	57.00	-9.54	-- -- PEAK																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 24905.59	32.78	68.20	-35.42	56.02	39.60	0.00	53.30	-9.54	-- -- PEAK																																																																																																																																																																													
2 39643.61	37.30	74.00	-36.70	58.28	44.86	0.00	56.30	-9.54	-- -- PEAK																																																																																																																																																																													



Mode	3	
	Co-location Harmonic	
	2400-2483.5MHz_Bluetooth-LE_GFSK_CH39_2480MHz 5150-5250MHz_802.11be EHT20_CH36_5180MHz	
ANT	MIMO+MIMO	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-02-24 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-02-24 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-02-24 Site : 03CH15-HY Condition: AVG(UNII)_6E 3m 91280-92294_250606 VERTICAL





Mode	4																																																																																																																																																																																																																																													
	Co-location LF																																																																																																																																																																																																																																													
	2400-2483.5MHz_Bluetooth-LE_GFSK_CH39_2480MHz 5150-5250MHz_802.11be EHT20_CH36_5180MHz																																																																																																																																																																																																																																													
ANT	MIMO+MIMO																																																																																																																																																																																																																																													
Pol.	Horizontal							Vertical																																																																																																																																																																																																																																						
QPI Peak	Level (dBuV/m) Date: 2026-02-14 30224.418.612.806.1000 Frequency (MHz) Site : 03CH15-HY Condition: QP 3m Bilog_41912 & 05_250301 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>87.23</td><td>26.96</td><td>40.00</td><td>-13.04</td><td>43.16</td><td>14.47</td><td>1.64</td><td>32.39</td><td>0.08</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>179.38</td><td>31.38</td><td>43.50</td><td>-12.12</td><td>45.97</td><td>15.20</td><td>2.38</td><td>32.40</td><td>0.23</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>224.97</td><td>24.94</td><td>46.00</td><td>-21.06</td><td>38.84</td><td>15.73</td><td>2.62</td><td>32.34</td><td>0.09</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>418.97</td><td>26.65</td><td>46.00</td><td>-19.35</td><td>32.92</td><td>22.37</td><td>3.58</td><td>32.34</td><td>0.12</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>745.86</td><td>34.79</td><td>46.00</td><td>-11.21</td><td>33.71</td><td>28.38</td><td>4.79</td><td>32.26</td><td>0.17</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>955.38</td><td>33.34</td><td>46.00</td><td>-12.66</td><td>27.54</td><td>31.05</td><td>5.40</td><td>31.00</td><td>0.35</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg		1	87.23	26.96	40.00	-13.04	43.16	14.47	1.64	32.39	0.08	--	--	--	Peak	2	179.38	31.38	43.50	-12.12	45.97	15.20	2.38	32.40	0.23	--	--	--	Peak	3	224.97	24.94	46.00	-21.06	38.84	15.73	2.62	32.34	0.09	--	--	--	Peak	4	418.97	26.65	46.00	-19.35	32.92	22.37	3.58	32.34	0.12	--	--	--	Peak	5	745.86	34.79	46.00	-11.21	33.71	28.38	4.79	32.26	0.17	--	--	--	Peak	6	955.38	33.34	46.00	-12.66	27.54	31.05	5.40	31.00	0.35	--	--	--	Peak	Level (dBuV/m) Date: 2026-02-14 30224.418.612.806.1000 Frequency (MHz) Site : 03CH15-HY Condition: QP 3m Bilog_41912 & 05_250301 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>30.97</td><td>30.36</td><td>40.00</td><td>-9.64</td><td>37.93</td><td>23.86</td><td>0.90</td><td>32.43</td><td>0.10</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>202.66</td><td>28.62</td><td>43.50</td><td>-14.88</td><td>43.22</td><td>15.13</td><td>2.50</td><td>32.32</td><td>0.09</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>221.09</td><td>26.67</td><td>46.00</td><td>-19.33</td><td>40.93</td><td>15.39</td><td>2.60</td><td>32.34</td><td>0.09</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>489.78</td><td>25.51</td><td>46.00</td><td>-20.49</td><td>29.95</td><td>23.88</td><td>3.88</td><td>32.30</td><td>0.10</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>745.86</td><td>36.82</td><td>46.00</td><td>-9.18</td><td>35.74</td><td>28.38</td><td>4.79</td><td>32.26</td><td>0.17</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>930.16</td><td>33.14</td><td>46.00</td><td>-12.86</td><td>28.77</td><td>29.99</td><td>5.31</td><td>31.22</td><td>0.29</td><td>--</td><td>--</td><td>--</td><td>Peak</td></tr></table>								Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg		1	30.97	30.36	40.00	-9.64	37.93	23.86	0.90	32.43	0.10	--	--	--	Peak	2	202.66	28.62	43.50	-14.88	43.22	15.13	2.50	32.32	0.09	--	--	--	Peak	3	221.09	26.67	46.00	-19.33	40.93	15.39	2.60	32.34	0.09	--	--	--	Peak	4	489.78	25.51	46.00	-20.49	29.95	23.88	3.88	32.30	0.10	--	--	--	Peak	5	745.86	36.82	46.00	-9.18	35.74	28.38	4.79	32.26	0.17	--	--	--	Peak	6	930.16	33.14	46.00	-12.86	28.77	29.99	5.31	31.22	0.29	--	--	--	Peak
		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																
		MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																	
1	87.23	26.96	40.00	-13.04	43.16	14.47	1.64	32.39	0.08	--	--	--	Peak																																																																																																																																																																																																																																	
2	179.38	31.38	43.50	-12.12	45.97	15.20	2.38	32.40	0.23	--	--	--	Peak																																																																																																																																																																																																																																	
3	224.97	24.94	46.00	-21.06	38.84	15.73	2.62	32.34	0.09	--	--	--	Peak																																																																																																																																																																																																																																	
4	418.97	26.65	46.00	-19.35	32.92	22.37	3.58	32.34	0.12	--	--	--	Peak																																																																																																																																																																																																																																	
5	745.86	34.79	46.00	-11.21	33.71	28.38	4.79	32.26	0.17	--	--	--	Peak																																																																																																																																																																																																																																	
6	955.38	33.34	46.00	-12.66	27.54	31.05	5.40	31.00	0.35	--	--	--	Peak																																																																																																																																																																																																																																	
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																		
1	30.97	30.36	40.00	-9.64	37.93	23.86	0.90	32.43	0.10	--	--	--	Peak																																																																																																																																																																																																																																	
2	202.66	28.62	43.50	-14.88	43.22	15.13	2.50	32.32	0.09	--	--	--	Peak																																																																																																																																																																																																																																	
3	221.09	26.67	46.00	-19.33	40.93	15.39	2.60	32.34	0.09	--	--	--	Peak																																																																																																																																																																																																																																	
4	489.78	25.51	46.00	-20.49	29.95	23.88	3.88	32.30	0.10	--	--	--	Peak																																																																																																																																																																																																																																	
5	745.86	36.82	46.00	-9.18	35.74	28.38	4.79	32.26	0.17	--	--	--	Peak																																																																																																																																																																																																																																	
6	930.16	33.14	46.00	-12.86	28.77	29.99	5.31	31.22	0.29	--	--	--	Peak																																																																																																																																																																																																																																	

Appendix B. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
3+4	Bluetooth - LE for 1Mbps	60.32	380	2.63	2.7kHz
3+4	802.11g	99.27	-	-	10Hz
3+4	802.11a	99.51	-	-	10Hz
3+4	802.11be EHT20 Full RU	99.31	-	-	10Hz

MIMO <Ant. 3+4>



—THE END—