



FCC RADIO TEST REPORT

FCC ID : A4RG7SWN
Equipment : Phone
Model Name : G7SWN
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)

The product was received on Jan. 19, 2026 and testing was performed from Jan. 19, 2026 to Mar. 01, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode.....	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration	8
2.4 Measurement Results Explanation Example	8
2.5 Frequency List of Low/Middle/High Channels.....	9
3 Conducted Test Result	10
3.1 Measuring Instruments.....	10
3.2 Conducted Output Power and ERP/EIRP	11
3.3 Peak-to-Average Ratio	12
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	13
3.5 Conducted Band Edge	14
3.6 Conducted Spurious Emission	15
3.7 Frequency Stability.....	16
4 Radiated Test Items	17
4.1 Measuring Instruments.....	17
4.2 Test Setup	17
4.3 Test Result of Radiated Test.....	18
4.4 Field Strength of Spurious Radiation Measurement	19
5 List of Measuring Equipment.....	20
6 Measurement Uncertainty	22
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FG5N0815-01A	01	Initial issue of report	Apr. 28, 2026
FG5N0815-01A	02	Updated section 1.1 and appendix A typo	May 14, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
	§22.913 (a)(5)	Effective Radiated Power (GSM850) (WCDMA Band V)		
	§24.232 (c)	Equivalent Isotropic Radiated Power (GSM1900) (WCDMA Band II)		
	§27.50 (d)(4)	Equivalent Isotropic Radiated Power (WCDMA Band IV)		
3.3	§24.232 (d)	Peak-to-Average Ratio	Pass	-
3.4	§2.1049 §22.917 (b) §24.238 (b) §27.53 (g)	Occupied Bandwidth (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.5	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Band Edge Measurement (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.6	§2.1051 §22.917 (a) §24.238 (a) §27.53 (g)	Conducted Emission (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-
3.7	§2.1055 §22.355 §24.235 §27.54	Frequency Stability Temperature & Voltage	Pass	-
4.4	§2.1053 §22.917 (a) §24.238 (a) §27.53 (h)	Field Strength of Spurious Radiation (GSM850) (WCDMA Band V) (GSM1900) (WCDMA Band II) (WCDMA Band IV)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Shannon Huang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx.
Antenna Type WWAN: <Ant. 0>: ILA Antenna <Ant. 1>: ILA Antenna <Ant. 2>: IFA Antenna

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

Antenna information					
Band	Ant0	Ant1	Ant2	Main Ant. #	Sub Ant. #
GSM 850	-4.8	-6.3	-	0	1
GSM 1900	-0.2	-	-0.3	2	0
WCDMA B5	-4.8	-6.3	-	0	1
WCDMA B2	-0.2	-	-0.3	2	0
WCDMA B4	-0.8	-	-0.1	2	0

Remark:

1. For Test Items, Main Ant. means Tx0 and Sub Ant. means Tx1.
2. After preliminary scan, the main antenna Ant 0 for Low band and main antenna Ant 2 for Mid/high band are selected as the worst mode to be reported for conducted test.

EUT Information List	
S/N	Performed Test Item
5C251FDKX00035	Conducted Measurement ERP/EIRP
61061FDKX00036	Radiated Spurious Emission

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH21-HY
Test Engineer	Eric Wu	Jack Cheng, Ray Lung
Temperature (°C)	21.4 ~23.4	20.1~23.5
Relative Humidity (%)	55.1~57.1	52.5~63.6

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190 and TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and worst plane as below.

Plane	Main Antenna	Sub Antenna
GSM850 WCDMA Band V	Z with adapter	Y with adapter
GSM1900 WCDMA Band II	X with adapter	Z with adapter
WCDMA Band IV	X with adapter	X standalone

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II


All modes, data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM850	■ GPRS Class 8 Link ■ EDGE Class 8 Link	■ GPRS Class 8 Link ■ EDGE Class 8 Link
GSM1900	■ GPRS Class 8 Link ■ EDGE Class 8 Link	■ GPRS Class 8 Link ■ EDGE Class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System

<EUT with Adapter>



2.3 Support Unit used in test configuration

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
3.	AC Adapter	N/A	GW8L7	N/A	N/A	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10 dB attenuator.

Example:

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


3 Conducted Test Result

3.1 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.1.1 Test Setup


3.1.2 Conducted Output Power



3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.1.4 Frequency Stability



3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

3.2 Conducted Output Power and ERP/EIRP

3.2.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.2.2 Test Procedures

1. The transmitter output port is connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select the lowest, middle, and the highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.3 Peak-to-Average Ratio

3.3.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.3.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.2.6

1. The EUT is connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
5. Record the maximum PAPR level associated with a probability of 0.1%.

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT is connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(This is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT is connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT is connected to the spectrum analyzer by an RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers are measured.
4. The RF fundamental frequency shall be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT is connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT is connected to the spectrum analyzer by an RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency is measured.
4. The conducted spurious emission for the whole frequency range is taken.
5. The RF fundamental frequency shall be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.7 Frequency Stability

3.7.1 Description of Frequency Stability Measurement

22.355

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

24.235 & 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.7.2 Test Procedures for Temperature Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT is set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature is decreased to -30°C and the EUT is stabilized before testing. Power is applied and the maximum change in frequency is recorded within one minute.
3. With power OFF, the temperature is raised in 10°C steps up to 50°C . The EUT is stabilized at each step for at least half an hour. Power is applied and the maximum frequency change is recorded within one minute.

3.7.3 Test Procedures for Voltage Variation

The testing follows FCC KDB 971168 D01 v03r01 Section 9.0.

1. The EUT is placed in a temperature chamber at $20 \pm 5^{\circ}\text{C}$ and connected with the system simulator.
2. The power supply voltage to the EUT is varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency is measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


Please refer to the measuring equipment list in this test report.

4.2 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI C63.26-2015 section 5.5.4 Radiated measurement using the field strength method.

1. The EUT is placed on a rotatable wooden table 0.8 meters for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz above the ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the antenna tower.
3. The table is rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1 MHz, VBW = 3 MHz, taking record of maximum spurious emission.
6. To convert spectrum reading E(dBuV/m) to EIRP(dBm)
$$\text{EIRP(dBm)} = \text{Level (dBuV/m)} + 20\log(d) - 104.77,$$
where d is the distance at which field strength limit is specified in the rules
7. Field Strength Level (dBm) = Spectrum Reading (dBm) + Antenna Factor + Cable Loss + Read Level - Preamp Factor.
8. ERP (dBm) = EIRP (dBm) - 2.15
9. The RF fundamental frequency shall be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LOOP Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 06, 2025	Feb. 27, 2026~ Mar. 01, 2026	Mar. 05, 2026	Radiation (03CH21-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63303 & 001	30MHz~1GHz	Nov. 26, 2025	Feb. 27, 2026~ Mar. 01, 2026	Nov. 25, 2026	Radiation (03CH21-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C03A18E N	1GHz~18GHz	Aug. 07, 2025	Feb. 27, 2026~ Mar. 01, 2026	Aug. 06, 2026	Radiation (03CH21-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1223	18GHz~40GHz	Jul. 02, 2025	Feb. 27, 2026~ Mar. 01, 2026	Jul. 01, 2026	Radiation (03CH21-HY)
Amplifier	SONOMA	310N	421580	30MHz~1GHz	Jul. 13, 2025	Feb. 27, 2026~ Mar. 01, 2026	Jul. 12, 2026	Radiation (03CH21-HY)
Amplifier	EMEC	EM01G18GA	060876	1GHz~18GHz	Sep. 26, 2025	Feb. 27, 2026~ Mar. 01, 2026	Sep. 25, 2026	Radiation (03CH21-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Aug. 26, 2025	Feb. 27, 2026~ Mar. 01, 2026	Aug. 25, 2026	Radiation (03CH21-HY)
EXA Signal Analyzer	Keysight	N9010B	MY62170358	10Hz~44GHz	Sep. 09, 2025	Feb. 27, 2026~ Mar. 01, 2026	Sep. 08, 2026	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Feb. 27, 2026~ Mar. 01, 2026	Mar. 04, 2026	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804397/2,80 4612/2,8039 54/2	30MHz~40GHz	Aug. 11, 2025	Feb. 27, 2026~ Mar. 01, 2026	Aug. 10, 2026	Radiation (03CH21-HY)
RF Cable	EMCI	EMC101Y-KM- KM-1000	240906	30MHz~40GHz	Oct. 21, 2025	Feb. 27, 2026~ Mar. 01, 2026	Oct. 20, 2026	Radiation (03CH21-HY)
Hygrometer	TECPEL	DTM-303A	TP211568	N/A	Oct. 21, 2025	Feb. 27, 2026~ Mar. 01, 2026	Oct. 20, 2026	Radiation (03CH21-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Feb. 27, 2026~ Mar. 01, 2026	N/A	Radiation (03CH21-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Feb. 27, 2026~ Mar. 01, 2026	N/A	Radiation (03CH21-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Feb. 27, 2026~ Mar. 01, 2026	N/A	Radiation (03CH21-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Feb. 27, 2026~ Mar. 01, 2026	N/A	Radiation (03CH21-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 30, 2025	Jan. 19, 2026~ Feb. 10, 2026	Sep. 29, 2026	Conducted (TH05-HY)
Universal Digital Radio COMM. Tester	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Aug. 14, 2025	Jan. 19, 2026~ Feb. 10, 2026	Aug. 13, 2026	Conducted (TH05-HY)
DC Power Supply	GW Instek	GPE-2323	GEU871221	0V~64V ; 0A~6A	Apr. 14, 2025	Jan. 19, 2026~ Feb. 10, 2026	Apr. 13, 2026	Conducted (TH05-HY)
Temperature & Humidity Cabinet Chamber	ESPEC	SU-241	92003713	-30°C ~95°C	May. 12, 2025	Jan. 19, 2026~ Feb. 10, 2026	May. 11, 2026	Conducted (TH05-HY)
Hygrometer	TECPEL	DTM-303B	TP200886	N/A	Mar. 03, 2025	Jan. 19, 2026~ Feb. 10, 2026	Mar. 02, 2026	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 30, 2025	Jan. 19, 2026~ Feb. 10, 2026	Sep. 29, 2026	Conducted (TH05-HY)

6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.4 dB
--	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 6 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (6 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.8 dB
--	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.3 dB
--	--------

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power and ERP/EIRP)

ANT 0

GSM850 Maximum Average Power [dBm] (GT - LC = -4.8 dB)					
Channel	128	189	251	ERP (dBm)	ERP (W)
Frequency	824.2	836.4	848.8		
GSM 1 Tx slot	32.81	32.88	32.81	25.94	0.3926
GPRS 1 Tx slot	32.82	32.89	32.82		
GPRS 2 Tx slots	31.93	32.04	32.02		
GPRS 3 Tx slots	30.88	30.96	30.98		
GPRS 4 Tx slots	29.68	29.83	29.80		
EDGE 1 Tx slot	26.19	26.26	26.34	19.39	0.0869
EDGE 2 Tx slots	25.22	25.26	25.27		
EDGE 3 Tx slots	24.13	24.13	24.25		
EDGE 4 Tx slots	23.00	23.11	23.18		
Limit	ERP < 7W			Result	Pass

GSM1900 Maximum Average Power [dBm] (GT - LC = -0.2 dB)					
Channel	512	661	810	EIRP (dBm)	EIRP (W)
Frequency	1850.2	1880	1909.8		
GSM 1 Tx slot	29.77	29.82	30.00	29.82	0.9594
GPRS 1 Tx slot	29.78	29.84	30.02		
GPRS 2 Tx slots	28.53	28.61	28.79		
GPRS 3 Tx slots	27.97	28.05	28.21		
GPRS 4 Tx slots	26.84	26.95	27.04		
EDGE 1 Tx slot	25.15	25.15	25.12	24.95	0.3126
EDGE 2 Tx slots	24.33	24.13	24.16		
EDGE 3 Tx slots	23.24	23.15	23.11		
EDGE 4 Tx slots	22.30	22.28	22.23		
Limit	EIRP < 2W			Result	Pass

WCDMA Band V Maximum Average Power [dBm] (GT - LC = -4.8 dB)					
Channel	4132	4182	4233	ERP (dBm)	ERP (W)
Frequency	826.4	836.4	846.6		
AMR 12.2Kbps	24.35	24.42	24.30	17.50	0.0562
RMC 12.2Kbps	24.40	24.45	24.35		
HSDPA Subtest-1	23.42	23.45	23.39		
HSDPA Subtest-2	23.41	23.44	23.42		
HSDPA Subtest-3	22.94	22.98	22.96		
HSDPA Subtest-4	22.95	22.97	22.89		
HSUPA Subtest-1	21.38	21.43	21.37		
HSUPA Subtest-2	21.42	21.47	21.42		
HSUPA Subtest-3	22.40	22.47	22.41		
HSUPA Subtest-4	20.90	20.91	20.90		
HSUPA Subtest-5	22.40	22.40	22.40		
Limit	ERP < 7W			Result	Pass

ANT 0

WCDMA Band II Maximum Average Power [dBm] (GT - LC = -0.2 dB)					
Channel	9262	9400	9538	EIRP (dBm)	EIRP (W)
Frequency	1852.4	1880	1907.6		
AMR 12.2Kbps	24.08	24.10	23.88	23.91	0.2460
RMC 12.2Kbps	24.10	24.11	23.90		
HSDPA Subtest-1	23.11	23.11	22.88		
HSDPA Subtest-2	23.09	23.14	22.87		
HSDPA Subtest-3	22.67	22.67	22.43		
HSDPA Subtest-4	22.68	22.65	22.41		
HSUPA Subtest-1	21.00	21.10	20.90		
HSUPA Subtest-2	21.00	21.09	20.88		
HSUPA Subtest-3	22.04	22.14	21.97		
HSUPA Subtest-4	20.55	20.69	20.44		
HSUPA Subtest-5	22.10	22.00	21.90		
Limit	EIRP < 2W			Result	Pass

WCDMA Band IV Maximum Average Power [dBm] (GT - LC = -0.8 dB)					
Channel	1312	1413	1513	EIRP (dBm)	EIRP (W)
Frequency	1712.4	1732.6	1752.6		
AMR 12.2Kbps	24.20	24.22	24.18	23.46	0.2218
RMC 12.2Kbps	24.23	24.26	24.20		
HSDPA Subtest-1	23.29	23.27	23.19		
HSDPA Subtest-2	23.33	23.26	23.22		
HSDPA Subtest-3	22.82	22.81	22.75		
HSDPA Subtest-4	22.82	22.75	22.67		
HSUPA Subtest-1	21.24	21.27	21.19		
HSUPA Subtest-2	21.26	21.24	21.18		
HSUPA Subtest-3	22.28	22.27	22.19		
HSUPA Subtest-4	20.80	20.79	20.68		
HSUPA Subtest-5	22.30	22.30	22.20		
Limit	EIRP < 1W			Result	Pass

ANT 1

GSM850 Maximum Average Power [dBm] (GT - LC = -6.3 dB)					
Channel	128	189	251	ERP (dBm)	ERP (W)
Frequency	824.2	836.4	848.8		
GSM 1 Tx slot	33.03	33.02	32.92	24.60	0.2884
GPRS 1 Tx slot	33.04	33.05	32.93		
GPRS 2 Tx slots	31.98	31.99	31.98		
GPRS 3 Tx slots	30.98	30.99	31.00		
GPRS 4 Tx slots	29.97	29.99	29.94		
EDGE 1 Tx slot	25.90	25.86	25.69	17.45	0.0556
EDGE 2 Tx slots	24.77	24.77	24.61		
EDGE 3 Tx slots	23.62	23.67	23.45		
EDGE 4 Tx slots	22.60	22.55	22.34		
Limit	ERP < 7W			Result	Pass

WCDMA Band V Maximum Average Power [dBm] (GT - LC = -6.3 dB)					
Channel	4132	4182	4233	ERP (dBm)	ERP (W)
Frequency	826.4	836.4	846.6		
AMR 12.2Kbps	24.40	24.45	24.40	16.02	0.0400
RMC 12.2Kbps	24.41	24.47	24.42		
HSDPA Subtest-1	23.44	23.51	23.45		
HSDPA Subtest-2	23.42	23.50	23.47		
HSDPA Subtest-3	22.96	23.03	23.00		
HSDPA Subtest-4	22.93	22.99	22.98		
HSUPA Subtest-1	21.88	21.46	21.37		
HSUPA Subtest-2	21.37	21.49	21.44		
HSUPA Subtest-3	22.45	22.50	22.42		
HSUPA Subtest-4	20.92	20.98	20.89		
HSUPA Subtest-5	22.40	22.40	22.40		
Limit	ERP < 7W			Result	Pass

ANT 2

GSM1900 Maximum Average Power [dBm] (GT - LC = -0.3 dB)					
Channel	512	661	810	EIRP (dBm)	EIRP (W)
Frequency	1850.2	1880	1909.8		
GSM 1 Tx slot	29.44	29.45	29.45	29.17	0.8260
GPRS 1 Tx slot	29.45	29.47	29.46		
GPRS 2 Tx slots	28.44	28.40	28.37		
GPRS 3 Tx slots	27.98	27.91	27.86		
GPRS 4 Tx slots	27.00	26.92	26.84		
EDGE 1 Tx slot	25.37	25.19	25.26	25.07	0.3214
EDGE 2 Tx slots	24.49	24.36	24.39		
EDGE 3 Tx slots	23.57	23.43	23.44		
EDGE 4 Tx slots	22.77	22.64	22.59		
Limit	EIRP < 2W			Result	Pass

WCDMA Band II Maximum Average Power [dBm] (GT - LC = -0.3 dB)					
Channel	9262	9400	9538	EIRP (dBm)	EIRP (W)
Frequency	1852.4	1880	1907.6		
AMR 12.2Kbps	23.91	24.02	23.74	23.74	0.2366
RMC 12.2Kbps	23.97	24.04	23.82		
HSDPA Subtest-1	22.93	23.03	22.82		
HSDPA Subtest-2	22.93	23.03	22.80		
HSDPA Subtest-3	22.49	22.57	22.37		
HSDPA Subtest-4	22.42	22.54	22.38		
HSUPA Subtest-1	20.97	21.00	20.80		
HSUPA Subtest-2	20.97	21.02	20.82		
HSUPA Subtest-3	21.98	22.03	21.82		
HSUPA Subtest-4	20.47	20.52	20.30		
HSUPA Subtest-5	22.00	22.00	21.80		
Limit	EIRP < 2W			Result	Pass

WCDMA Band IV Maximum Average Power [dBm] (GT - LC = -0.1 dB)					
Channel	1312	1413	1513	EIRP (dBm)	EIRP (W)
Frequency	1712.4	1732.6	1752.6		
AMR 12.2Kbps	24.25	24.25	24.12	24.17	0.2612
RMC 12.2Kbps	24.26	24.27	24.14		
HSDPA Subtest-1	23.28	23.27	23.18		
HSDPA Subtest-2	23.34	23.23	23.21		
HSDPA Subtest-3	22.87	22.81	22.74		
HSDPA Subtest-4	22.77	22.77	22.72		
HSUPA Subtest-1	21.28	21.26	21.17		
HSUPA Subtest-2	21.30	21.30	21.18		
HSUPA Subtest-3	22.30	22.32	22.20		
HSUPA Subtest-4	20.78	20.85	20.74		
HSUPA Subtest-5	22.30	22.30	22.20		
Limit	EIRP < 1W			Result	Pass















A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.24	3.20	PASS
Middle CH	0.24	3.20	
Highest CH	0.24	3.16	

Mode	GSM1900		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.20	3.44	PASS
Middle CH	0.24	3.44	
Highest CH	0.20	3.24	


GSM850 (GPRS class 8)		GSM850 (EDGE class 8)	
Lowest Channel		Lowest Channel	
 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 824.2 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 32.01 dBm Peak 32.22 dBm Crest 0.21 dB 10 % 0.20 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB Date: 28.JAN.2026 13:59:50		 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 824.2 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.15 dBm Peak 29.47 dBm Crest 3.31 dB 10 % 2.60 dB 1 % 3.08 dB .1 % 3.20 dB .01 % 3.28 dB Date: 28.JAN.2026 14:43:07	
Middle Channel		Middle Channel	
 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 836.4 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.93 dBm Peak 32.15 dBm Crest 0.22 dB 10 % 0.16 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB Date: 28.JAN.2026 14:00:21		 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 836.4 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.00 dBm Peak 29.25 dBm Crest 3.26 dB 10 % 2.56 dB 1 % 3.12 dB .1 % 3.20 dB .01 % 3.28 dB Date: 28.JAN.2026 14:43:30	
Highest Channel		Highest Channel	
 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 849.8 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 31.94 dBm Peak 32.15 dBm Crest 0.21 dB 10 % 0.20 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB Date: 28.JAN.2026 14:00:53		 Ref 35 dBm Att 30 dB AQT 3.125 ms Center 849.8 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 26.23 dBm Peak 29.47 dBm Crest 3.23 dB 10 % 2.52 dB 1 % 2.96 dB .1 % 3.16 dB .01 % 3.24 dB Date: 28.JAN.2026 14:43:53	

GSM1900 (GPRS class 8)		GSM1900 (EDGE class 8)	
Lowest Channel		Lowest Channel	
 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.78 dBm Peak 30.03 dBm Crest 0.25 dB 10 % 0.20 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.24 dB Date: 28.JAN.2026 15:05:22		 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.33 dBm Peak 28.83 dBm Crest 3.50 dB 10 % 2.64 dB 1 % 3.28 dB .1 % 3.44 dB .01 % 3.48 dB Date: 28.JAN.2026 15:24:41	
Middle Channel		Middle Channel	
 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.85 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.75 dBm Peak 30.03 dBm Crest 0.28 dB 10 % 0.20 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB Date: 28.JAN.2026 15:05:52		 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.85 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.23 dBm Peak 28.76 dBm Crest 3.53 dB 10 % 2.68 dB 1 % 3.28 dB .1 % 3.44 dB .01 % 3.52 dB Date: 28.JAN.2026 15:25:05	
Highest Channel		Highest Channel	
 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 29.77 dBm Peak 30.03 dBm Crest 0.26 dB 10 % 0.20 dB 1 % 0.20 dB .1 % 0.20 dB .01 % 0.28 dB Date: 28.JAN.2026 15:06:19		 Ref 35 dBm *Att 30 dB AGT 3.125 ms Offset 17.0 dB Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 25.37 dBm Peak 28.69 dBm Crest 3.32 dB 10 % 2.56 dB 1 % 3.08 dB .1 % 3.24 dB .01 % 3.32 dB Date: 28.JAN.2026 15:25:27	

26dB Bandwidth

Mode	GSM850 : 26dB BW(MHz)	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.310	0.309
Middle CH	0.317	0.312
Highest CH	0.317	0.312


Mode	GSM1900 : 26dB BW(MHz)	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.316	0.321
Middle CH	0.321	0.315
Highest CH	0.320	0.314




Occupied Bandwidth

Mode	GSM850 : 99%OBW(MHz)	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.246	0.250
Middle CH	0.245	0.243
Highest CH	0.249	0.248


Mode	GSM1900 : 99%OBW(MHz)	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.243	0.247
Middle CH	0.248	0.249
Highest CH	0.243	0.249








Conducted Band Edge






GSM850 (EDGE class 8)

Lowest Band Edge



Date: 28.JAN.2026 14:36:13

Highest Band Edge




Date: 28.JAN.2026 14:37:55




GSM1900 (GPRS class 8)

Lowest Band Edge



Date: 28.JAN.2026 14:58:59

Highest Band Edge




Date: 28.JAN.2026 15:00:41




GSM1900 (EDGE class 8)

Lowest Band Edge







Date: 28.JAN.2026 15:18:15


Highest Band Edge




Date: 28.JAN.2026 15:19:56

Conducted Spurious Emission

GSM850 (GPRS class 8)		GSM850 (EDGE class 8)																																																																																					
Lowest Channel		Lowest Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PwrAve</th><th>Limit</th></tr><tr><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>819.802500 M</td><td>-28.10</td><td>-15.10</td></tr><tr><td>855.000 M</td><td>1.000 G</td><td>1.00 M</td><td>911.006254 M</td><td>-43.03</td><td>-30.03</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.472000 G</td><td>-40.02</td><td>-27.02</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.119000 G</td><td>-38.94</td><td>-25.94</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.130000 G</td><td>-36.15</td><td>-23.15</td></tr></table> Date: 28.JAN.2026 13:56:54		Start	Stop	RBW	Freq	PwrAve	Limit	[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	819.802500 M	-28.10	-15.10	855.000 M	1.000 G	1.00 M	911.006254 M	-43.03	-30.03	1.000 G	3.000 G	1.00 M	2.472000 G	-40.02	-27.02	3.000 G	7.000 G	1.00 M	3.119000 G	-38.94	-25.94	7.000 G	9.000 G	1.00 M	8.130000 G	-36.15	-23.15	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PwrAve</th><th>Limit</th></tr><tr><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>819.802500 M</td><td>-32.87</td><td>-19.87</td></tr><tr><td>855.000 M</td><td>1.000 G</td><td>1.00 M</td><td>901.400003 M</td><td>-41.82</td><td>-28.82</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.390000 G</td><td>-41.06</td><td>-28.06</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.083000 G</td><td>-38.69</td><td>-25.69</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.888500 G</td><td>-36.39</td><td>-23.39</td></tr></table> Date: 28.JAN.2026 14:39:30		Start	Stop	RBW	Freq	PwrAve	Limit	[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	819.802500 M	-32.87	-19.87	855.000 M	1.000 G	1.00 M	901.400003 M	-41.82	-28.82	1.000 G	3.000 G	1.00 M	2.390000 G	-41.06	-28.06	3.000 G	7.000 G	1.00 M	3.083000 G	-38.69	-25.69	7.000 G	9.000 G	1.00 M	7.888500 G	-36.39	-23.39
Start	Stop	RBW	Freq	PwrAve	Limit																																																																																		
[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	819.802500 M	-28.10	-15.10																																																																																		
855.000 M	1.000 G	1.00 M	911.006254 M	-43.03	-30.03																																																																																		
1.000 G	3.000 G	1.00 M	2.472000 G	-40.02	-27.02																																																																																		
3.000 G	7.000 G	1.00 M	3.119000 G	-38.94	-25.94																																																																																		
7.000 G	9.000 G	1.00 M	8.130000 G	-36.15	-23.15																																																																																		
Start	Stop	RBW	Freq	PwrAve	Limit																																																																																		
[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	819.802500 M	-32.87	-19.87																																																																																		
855.000 M	1.000 G	1.00 M	901.400003 M	-41.82	-28.82																																																																																		
1.000 G	3.000 G	1.00 M	2.390000 G	-41.06	-28.06																																																																																		
3.000 G	7.000 G	1.00 M	3.083000 G	-38.69	-25.69																																																																																		
7.000 G	9.000 G	1.00 M	7.888500 G	-36.39	-23.39																																																																																		
Middle Channel		Middle Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PwrAve</th><th>Limit</th></tr><tr><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>788.202500 M</td><td>-43.98</td><td>-30.98</td></tr><tr><td>855.000 M</td><td>1.000 G</td><td>1.00 M</td><td>930.001255 M</td><td>-42.62</td><td>-29.62</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.673000 G</td><td>-27.95</td><td>-14.95</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>5.187000 G</td><td>-38.83</td><td>-25.83</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.883000 G</td><td>-36.12</td><td>-23.12</td></tr></table> Date: 28.JAN.2026 13:57:58		Start	Stop	RBW	Freq	PwrAve	Limit	[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	788.202500 M	-43.98	-30.98	855.000 M	1.000 G	1.00 M	930.001255 M	-42.62	-29.62	1.000 G	3.000 G	1.00 M	1.673000 G	-27.95	-14.95	3.000 G	7.000 G	1.00 M	5.187000 G	-38.83	-25.83	7.000 G	9.000 G	1.00 M	7.883000 G	-36.12	-23.12	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PwrAve</th><th>Limit</th></tr><tr><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[MHz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>776.392500 M</td><td>-43.68</td><td>-30.68</td></tr><tr><td>855.000 M</td><td>1.000 G</td><td>1.00 M</td><td>897.489760 M</td><td>-42.43</td><td>-29.43</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.978000 G</td><td>-41.28</td><td>-28.28</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.773000 G</td><td>-38.75</td><td>-25.75</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.138500 G</td><td>-36.27</td><td>-23.27</td></tr></table> Date: 28.JAN.2026 14:40:33		Start	Stop	RBW	Freq	PwrAve	Limit	[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	776.392500 M	-43.68	-30.68	855.000 M	1.000 G	1.00 M	897.489760 M	-42.43	-29.43	1.000 G	3.000 G	1.00 M	2.978000 G	-41.28	-28.28	3.000 G	7.000 G	1.00 M	3.773000 G	-38.75	-25.75	7.000 G	9.000 G	1.00 M	8.138500 G	-36.27	-23.27
Start	Stop	RBW	Freq	PwrAve	Limit																																																																																		
[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	788.202500 M	-43.98	-30.98																																																																																		
855.000 M	1.000 G	1.00 M	930.001255 M	-42.62	-29.62																																																																																		
1.000 G	3.000 G	1.00 M	1.673000 G	-27.95	-14.95																																																																																		
3.000 G	7.000 G	1.00 M	5.187000 G	-38.83	-25.83																																																																																		
7.000 G	9.000 G	1.00 M	7.883000 G	-36.12	-23.12																																																																																		
Start	Stop	RBW	Freq	PwrAve	Limit																																																																																		
[MHz]	[MHz]	[MHz]	[MHz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	776.392500 M	-43.68	-30.68																																																																																		
855.000 M	1.000 G	1.00 M	897.489760 M	-42.43	-29.43																																																																																		
1.000 G	3.000 G	1.00 M	2.978000 G	-41.28	-28.28																																																																																		
3.000 G	7.000 G	1.00 M	3.773000 G	-38.75	-25.75																																																																																		
7.000 G	9.000 G	1.00 M	8.138500 G	-36.27	-23.27																																																																																		
Highest Channel		Highest Channel																																																																																					




Date: 28.JAN.2026 13:58:58



Date: 28.JAN.2026 14:41:31

GSM1900 (GPRS class 8)


Lowest Channel



Date: 28.JAN.2026 15:02:10


GSM1900 (EDGE class 8)

Lowest Channel




Date: 28.JAN.2026 15:21:52

Middle Channel




Date: 28.JAN.2026 15:03:14

Middle Channel




Date: 28.JAN.2026 15:22:48

Highest Channel



Date: 28.JAN.2026 15:04:09

Highest Channel



Date: 28.JAN.2026 15:23:40

**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0084	0.0072	PASS
40	Normal Voltage	0.0024	0.0012	
30	Normal Voltage	0.0048	0.0048	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0012	0.0036	
0	Normal Voltage	0.0120	0.0072	
-10	Normal Voltage	0.0514	0.0586	
-20	Normal Voltage	0.0036	0.0132	
-30	Normal Voltage	0.0155	0.0072	
20	Maximum Voltage	0.0430	0.0371	
20	Normal Voltage	0.0407	0.0383	
20	Minimum Voltage	0.0442	0.0323	

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (Hz)		Result
50	Normal Voltage	7	6	PASS
40	Normal Voltage	-2	1	
30	Normal Voltage	-4	4	
20(Ref.)	Normal Voltage	0	0	
10	Normal Voltage	1	3	
0	Normal Voltage	10	6	
-10	Normal Voltage	43	49	
-20	Normal Voltage	3	-11	
-30	Normal Voltage	13	-6	
20	Maximum Voltage	36	31	
20	Normal Voltage	34	32	
20	Minimum Voltage	37	27	



Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0011	0.0032	PASS
40	Normal Voltage	0.0016	0.0027	
30	Normal Voltage	0.0027	0.0048	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0032	0.0043	
0	Normal Voltage	0.0149	0.0133	
-10	Normal Voltage	0.0378	0.0415	
-20	Normal Voltage	0.0457	0.0447	
-30	Normal Voltage	0.0032	0.0021	
20	Maximum Voltage	0.0154	0.0138	
20	Normal Voltage	0.0314	0.0277	
20	Minimum Voltage	0.0319	0.0287	

Note:

1. Normal Voltage = 3.9V. ; Minimum Voltage = 3.6 V. ; Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.









A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.48	3.36	3.00	PASS
Middle CH	3.44	3.36	3.08	
Highest CH	3.40	3.20	3.04	




WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)																
Lowest Channel	Lowest Channel																
 Ref 30 dBm RSW 10 MHz Offset 15.0 dB Att 30 dB AGT 3.125 ms Center 826.4 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.32 dBm Peak 28.27 dBm Crest 3.95 dB <table><tr><td>10 %</td><td>1.84 dB</td></tr><tr><td>1 %</td><td>2.88 dB</td></tr><tr><td>.1 %</td><td>3.48 dB</td></tr><tr><td>.01 %</td><td>3.76 dB</td></tr></table> Date: 29.DEC.2025 16:34:26	10 %	1.84 dB	1 %	2.88 dB	.1 %	3.48 dB	.01 %	3.76 dB	 Ref 30 dBm RSW 10 MHz Offset 17.0 dB Att 30 dB AGT 3.125 ms Center 1.8324 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 23.98 dBm Peak 27.85 dBm Crest 3.87 dB <table><tr><td>10 %</td><td>1.84 dB</td></tr><tr><td>1 %</td><td>2.80 dB</td></tr><tr><td>.1 %</td><td>3.36 dB</td></tr><tr><td>.01 %</td><td>3.64 dB</td></tr></table> Date: 30.DEC.2025 11:55:59	10 %	1.84 dB	1 %	2.80 dB	.1 %	3.36 dB	.01 %	3.64 dB
10 %	1.84 dB																
1 %	2.88 dB																
.1 %	3.48 dB																
.01 %	3.76 dB																
10 %	1.84 dB																
1 %	2.80 dB																
.1 %	3.36 dB																
.01 %	3.64 dB																
Middle Channel	Middle Channel																
 Ref 30 dBm RSW 10 MHz Offset 15.0 dB Att 30 dB AGT 3.125 ms Center 826.4 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.30 dBm Peak 28.20 dBm Crest 3.90 dB <table><tr><td>10 %</td><td>1.84 dB</td></tr><tr><td>1 %</td><td>2.88 dB</td></tr><tr><td>.1 %</td><td>3.44 dB</td></tr><tr><td>.01 %</td><td>3.72 dB</td></tr></table> Date: 29.DEC.2025 16:34:48	10 %	1.84 dB	1 %	2.88 dB	.1 %	3.44 dB	.01 %	3.72 dB	 Ref 30 dBm RSW 10 MHz Offset 17.0 dB Att 30 dB AGT 3.125 ms Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.08 dBm Peak 27.85 dBm Crest 3.77 dB <table><tr><td>10 %</td><td>1.80 dB</td></tr><tr><td>1 %</td><td>2.80 dB</td></tr><tr><td>.1 %</td><td>3.36 dB</td></tr><tr><td>.01 %</td><td>3.60 dB</td></tr></table> Date: 30.DEC.2025 11:56:20	10 %	1.80 dB	1 %	2.80 dB	.1 %	3.36 dB	.01 %	3.60 dB
10 %	1.84 dB																
1 %	2.88 dB																
.1 %	3.44 dB																
.01 %	3.72 dB																
10 %	1.80 dB																
1 %	2.80 dB																
.1 %	3.36 dB																
.01 %	3.60 dB																
Highest Channel	Highest Channel																
 Ref 30 dBm RSW 10 MHz Offset 15.0 dB Att 30 dB AGT 3.125 ms Center 846.6 MHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 24.31 dBm Peak 28.13 dBm Crest 3.82 dB <table><tr><td>10 %</td><td>1.80 dB</td></tr><tr><td>1 %</td><td>2.84 dB</td></tr><tr><td>.1 %</td><td>3.40 dB</td></tr><tr><td>.01 %</td><td>3.64 dB</td></tr></table> Date: 29.DEC.2025 16:35:10	10 %	1.80 dB	1 %	2.84 dB	.1 %	3.40 dB	.01 %	3.64 dB	 Ref 30 dBm RSW 10 MHz Offset 17.0 dB Att 30 dB AGT 3.125 ms Center 1.9076 GHz 2 dB/ Mean Pwr + 20 dB Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 23.98 dBm Peak 27.57 dBm Crest 3.59 dB <table><tr><td>10 %</td><td>1.72 dB</td></tr><tr><td>1 %</td><td>2.68 dB</td></tr><tr><td>.1 %</td><td>3.20 dB</td></tr><tr><td>.01 %</td><td>3.44 dB</td></tr></table> Date: 30.DEC.2025 11:56:43	10 %	1.72 dB	1 %	2.68 dB	.1 %	3.20 dB	.01 %	3.44 dB
10 %	1.80 dB																
1 %	2.84 dB																
.1 %	3.40 dB																
.01 %	3.64 dB																
10 %	1.72 dB																
1 %	2.68 dB																
.1 %	3.20 dB																
.01 %	3.44 dB																




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 30.DEC.2025 14:39:49

Middle Channel



Date: 30.DEC.2025 14:40:11


Highest Channel



Date: 30.DEC.2025 14:40:32


**26dB Bandwidth**

Mode	WCDMA Band V 26dB BW(MHz)	WCDMA Band II 26dB BW(MHz)	WCDMA Band IV 26dB BW(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.68	4.69	4.71
Middle CH	4.69	4.69	4.70
Highest CH	4.68	4.70	4.69



**Occupied Bandwidth**


Mode	WCDMA Band V 99%OBW(MHz)	WCDMA Band II 99%OBW(MHz)	WCDMA Band IV 99%OBW(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.15	4.15	4.15
Middle CH	4.15	4.16	4.15
Highest CH	4.14	4.15	4.15






WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 30.DEC.2025 14:19:27

Middle Channel



Date: 30.DEC.2025 14:20:16

Highest Channel




Date: 30.DEC.2025 14:21:03



Conducted Band Edge


WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Date: 29.DEC.2025 16:25:17

Highest Band Edge




Date: 29.DEC.2025 16:29:10




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge

Highest Band Edge



Date: 30.DEC.2025 09:15:51




Date: 30.DEC.2025 09:19:05




WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge



Date: 30.DEC.2025 14:25:08

Highest Band Edge




Date: 30.DEC.2025 14:32:28

Conducted Spurious Emission

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	Lowest Channel
</	




Highest Channel



Date: 29.DEC.2025 16:32:51

Highest Channel




Date: 30.DEC.2025 11:53:29




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel




Date: 30.DEC.2025 14:36:40

Middle Channel



Date: 30.DEC.2025 14:37:38

Highest Channel



Date: 30.DEC.2025 14:38:39

Frequency Stability

Test Conditions		WCDMA Band V (RMC 12.2Kbps) / Middle Channel			
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Deviation (Hz)	Within Authorized Frequency Block(Hz)	Result
50	Normal Voltage	0.0024	-2	Yes	PASS
40	Normal Voltage	0.0036	-3	Yes	
30	Normal Voltage	0.0048	-4	Yes	
20(Ref.)	Normal Voltage	0.0000	0	Yes	
10	Normal Voltage	0.0120	10	Yes	
0	Normal Voltage	0.0143	12	Yes	
-10	Normal Voltage	0.0215	18	Yes	
-20	Normal Voltage	0.0239	20	Yes	
-30	Normal Voltage	0.0263	22	Yes	
20	Maximum Voltage	0.0060	5	Yes	
20	Normal Voltage	0.0024	2	Yes	
20	Minimum Voltage	0.0048	4	Yes	

Note:

1. Normal Voltage = 3.9 V. ; Minimum Voltage = 3.6 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.
3. The frequency variation is sufficient to ensure that the occupied bandwidth of all operation channels stay within the operating frequency block or frequency block group.

Test Conditions		WCDMA Band II (RMC 12.2Kbps) / Middle Channel			
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Deviation (Hz)	Within Authorized Frequency Block(Hz)	Result
50	Normal Voltage	0.0043	8	Yes	PASS
40	Normal Voltage	0.0037	7	Yes	
30	Normal Voltage	0.0005	1	Yes	
20(Ref.)	Normal Voltage	0.0000	0	Yes	
10	Normal Voltage	0.0005	-1	Yes	
0	Normal Voltage	0.0021	4	Yes	
-10	Normal Voltage	0.0027	5	Yes	
-20	Normal Voltage	0.0048	9	Yes	
-30	Normal Voltage	0.0016	3	Yes	
20	Maximum Voltage	0.0011	2	Yes	
20	Normal Voltage	0.0011	-2	Yes	
20	Minimum Voltage	0.0032	6	Yes	

Note:

1. Normal Voltage = 3.9 V. ; Minimum Voltage = 3.6 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.
3. The frequency variation is sufficient to ensure that the occupied bandwidth of all operation channels stay within the operating frequency block or frequency block group.

Test Conditions		WCDMA Band IV (RMC 12.2Kbps) / Middle Channel			
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Deviation (Hz)	Within Authorized Frequency Block(Hz)	Result
50	Normal Voltage	0.0063	11	Yes	PASS
40	Normal Voltage	0.0052	9	Yes	
30	Normal Voltage	0.0012	2	Yes	
20(Ref.)	Normal Voltage	0.0000	0	Yes	
10	Normal Voltage	0.0006	1	Yes	
0	Normal Voltage	0.0035	6	Yes	
-10	Normal Voltage	0.0046	8	Yes	
-20	Normal Voltage	0.0029	5	Yes	
-30	Normal Voltage	0.0058	10	Yes	
20	Maximum Voltage	0.0023	4	Yes	
20	Normal Voltage	0.0040	7	Yes	
20	Minimum Voltage	0.0017	3	Yes	

Note:

1. Normal Voltage = 3.9 V. ; Minimum Voltage = 3.6 V. ; Maximum Voltage = 4.4 V.
2. The frequency fundamental emissions stay within the authorized frequency block.
3. The frequency variation is sufficient to ensure that the occupied bandwidth of all operation channels stay within the operating frequency block or frequency block group.



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Fred Tseng, Ray Lung, and Sky Chang	Temperature :	21.1 ~ 25.7°C
		Relative Humidity :	55.8 ~ 63.2%

B1. Summary of each worse mode

Mode	Band	Part	Ch	Freq (MHz)	Level (dBm)	Det	Ant Factor (dB)	AmplCbl (dB)	Filter (dB)	EIRPCF (dB)	Reading (dBuV)	Limit (dBm)	Margin (dB)	Pol	Ant
1	GSM 850	Part 22H	M	2509	-41.56	RMS	26.80	-24.17	0.90	-95.23	50.14	-13.00	-28.56	H	0
2	GSM 850	Part 22H	M	3346	-63.56	RMS	28.19	-23.87	1.06	-95.23	26.29	-13.00	-50.56	H	1
3	WCDMA B5	Part 22H	L	2479	-62.13	RMS	26.60	-24.21	0.91	-95.23	29.80	-13.00	-49.13	V	0
4	WCDMA B5	Part 22H	M	3346	-63.84	RMS	28.19	-23.87	1.06	-95.23	26.01	-13.00	-50.84	V	1
1	GPRS 1900	Part 24E	M	5640	-37.83	RMS	33.06	-21.84	1.54	-95.23	44.64	-13.00	-24.83	V	2
2	GPRS 1900	Part 24E	M	7520	-54.68	RMS	36.66	-21.17	1.55	-95.23	23.51	-13.00	-41.68	V	0
3	WCDMA B2	Part 24E	M	7520	-54.94	RMS	36.66	-21.17	1.55	-95.23	23.25	-13.00	-41.94	H	2
4	WCDMA B2	Part 24E	M	7520	-54.43	RMS	36.66	-21.17	1.55	-95.23	23.76	-13.00	-41.43	H	0
1	WCDMA B4	Part 27L	L	5137	-52.33	RMS	32.50	-21.67	2.09	-95.23	29.98	-13.00	-39.33	H	2
2	WCDMA B4	Part 27L	M	6930	-56.47	RMS	36.06	-21.58	1.44	-95.23	22.84	-13.00	-43.47	V	0




Ant. 0

Part 22H Mode 1

GSM 850 Ch128

L




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: GPRS 850 Ch128

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	1						
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-55.16	RMS	24.67	-25.13	1.08	-95.23	39.45	-13.00	-42.16	Horizontal
2	2479.00	-42.40	RMS	26.60	-24.21	0.91	-95.23	49.53	-13.00	-29.40	Horizontal
3	3306.00	-63.87	RMS	28.11	-23.84	1.06	-95.23	26.03	-13.00	-50.87	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: GPRS 850 Ch128

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	1						
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-56.78	RMS	24.67	-25.13	1.08	-95.23	37.83	-13.00	-43.78	Vertical
2	2479.00	-44.47	RMS	26.60	-24.21	0.91	-95.23	47.46	-13.00	-31.47	Vertical
3	3306.00	-64.39	RMS	28.11	-23.84	1.06	-95.23	25.51	-13.00	-51.39	Vertical




Ant. 0

Part 22H Mode 1

GSM 850 Ch189

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: GPRS 850 Ch189

	Freq	Level	Detector	Ant	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm		Factor	1	dB		dB	dBuV		
1	1673.00	-52.05	RMS	24.66	-25.11	1.08	-95.23	42.55	-13.00	-39.05	Horizontal
2	2509.00	-41.56	RMS	26.80	-24.17	0.90	-95.23	50.14	-13.00	-28.56	Horizontal
3	3346.00	-63.97	RMS	28.19	-23.87	1.06	-95.23	25.88	-13.00	-50.97	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: GPRS 850 Ch189

	Freq		Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
	Level			Factor	l			g			
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1673.00	-49.82	RMS	24.66	-25.11	1.08	-95.23	44.78	-13.00	-36.82	Vertical
2	2509.00	-42.92	RMS	26.80	-24.17	0.90	-95.23	48.78	-13.00	-29.92	Vertical
3	3346.00	-63.94	RMS	28.19	-23.87	1.06	-95.23	25.91	-13.00	-50.94	Vertical




Ant. 0

Part 22H Mode 1

GSM 850 Ch251

H




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: EDGE 850 Ch251

	Freq Level		Detector	Ant Amp\Cb		Filter	EIRPCF		Readin	Limit	Margin		Pol
	MHz	dBm		Factor	1		dB	dB		dBuV	dBm	dB	
1	1693.00	-55.30	RMS	24.80	-25.10	1.08	-95.23	39.15	-13.00	-42.30	Horizontal		
2	2540.00	-43.69	RMS	27.00	-24.13	0.90	-95.23	47.77	-13.00	-30.69	Horizontal		
3	3386.00	-63.88	RMS	28.27	-23.90	1.06	-95.23	25.92	-13.00	-50.88	Horizontal		



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: EDGE 850 Ch251

	Freq Level		Detector	Ant Amp\Cb		Filter	EIRPCF		Readin	Limit	Margin		Pol
	MHz	dBm		Factor	1		dB	dB		dBuV	dBm	dB	
1	1693.00	-57.02	RMS	24.80	-25.10	1.08	-95.23	37.43	-13.00	-44.02	Vertical		
2	2540.00	-44.95	RMS	27.00	-24.13	0.90	-95.23	46.51	-13.00	-31.95	Vertical		
3	3386.00	-63.91	RMS	28.27	-23.90	1.06	-95.23	25.89	-13.00	-50.91	Vertical		




Ant. 0

Part 22H Mode 3

WCDMA B5 Ch4132

L




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B5 Ch4132

	Freq	Level	Detector	Ant Factor	Amp\Cb 1	Filter	EIRPCF	Reading	Limit	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-67.87	RMS	24.67	-25.13	1.08	-95.23	26.74	-13.00	-54.87	Horizontal
2	2479.00	-65.28	RMS	26.60	-24.21	0.91	-95.23	26.65	-13.00	-52.28	Horizontal
3	3306.00	-64.41	RMS	28.11	-23.84	1.06	-95.23	25.49	-13.00	-51.41	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B5 Ch4132

	Freq	Level	Detector	Ant Factor	Amp\Cb 1	Filter	EIRPCF	Readin g	Limit dBm	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1653.00	-67.74	RMS	24.67	-25.13	1.08	-95.23	26.87	-13.00	-54.74	Vertical
2	2479.00	-62.13	RMS	26.60	-24.21	0.91	-95.23	29.80	-13.00	-49.13	Vertical
3	3306.00	-64.43	RMS	28.11	-23.84	1.06	-95.23	25.47	-13.00	-51.43	Vertical




Ant. 0

Part 22H Mode 3

WCDMA B5 Ch4182

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B5 Ch4182

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	1							
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1673.00	-66.01	RMS		24.66	-25.11	1.08	-95.23	28.59	-13.00	-53.01	Horizontal
2	2509.00	-65.38	RMS		26.80	-24.17	0.90	-95.23	26.32	-13.00	-52.38	Horizontal
3	3346.00	-63.97	RMS		28.19	-23.87	1.06	-95.23	25.88	-13.00	-50.97	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B5 Ch4182

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	1							
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB	
1	1673.00	-66.63	RMS		24.66	-25.11	1.08	-95.23	27.97	-13.00	-53.63	Vertical
2	2509.00	-64.73	RMS		26.80	-24.17	0.90	-95.23	26.97	-13.00	-51.73	Vertical
3	3346.00	-64.23	RMS		28.19	-23.87	1.06	-95.23	25.62	-13.00	-51.23	Vertical




Ant. 0

Part 22H Mode 3

WCDMA B5 Ch4233

H




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B5 Ch4233

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit	Margin Pol	
	MHz	dBm		Factor	1					
1	1693.00	-67.87	RMS	24.80	-25.10	1.08	-95.23	26.58	-13.00	-54.87 Horizontal
2	2540.00	-65.42	RMS	27.00	-24.13	0.90	-95.23	26.04	-13.00	-52.42 Horizontal
3	3386.00	-63.78	RMS	28.27	-23.90	1.06	-95.23	26.02	-13.00	-50.78 Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B5 Ch4233

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit	Margin Pol	
	MHz	dBm		Factor	1					
1	1693.00	-67.60	RMS	24.80	-25.10	1.08	-95.23	26.85	-13.00	-54.60 Vertical
2	2540.00	-65.46	RMS	27.00	-24.13	0.90	-95.23	26.00	-13.00	-52.46 Vertical
3	3386.00	-64.09	RMS	28.27	-23.90	1.06	-95.23	25.71	-13.00	-51.09 Vertical




Ant. 1

Part 22H Mode 2

GSM 850 Ch189

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: GPRS 850 Ch189

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	1						
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB
1	1673.00	-66.61	RMS		24.66	-25.11	1.08	-95.23	27.99	-13.00	-53.61 Horizontal
2	2509.00	-65.15	RMS		26.80	-24.17	0.90	-95.23	26.55	-13.00	-52.15 Horizontal
3	3346.00	-63.56	RMS		28.19	-23.87	1.06	-95.23	26.29	-13.00	-50.56 Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: GPRS 850 Ch189

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	1						
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB
1	1673.00	-65.57	RMS		24.66	-25.11	1.08	-95.23	29.03	-13.00	-52.57 Vertical
2	2509.00	-64.11	RMS		26.80	-24.17	0.90	-95.23	27.59	-13.00	-51.11 Vertical
3	3346.00	-63.88	RMS		28.19	-23.87	1.06	-95.23	25.97	-13.00	-50.88 Vertical




Ant. 1

Part 22H Mode 4

WCDMA B5 Ch4182

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B5 Ch4182

	Freq Level		Detector	Ant Amp\Cb		Filter	EIRPCF		Readin	Limit	Margin Pol	
	MHz	dBm		Factor	1		dB	dB	dBuV	dBm		
1	1673.00	-67.18	RMS	24.66	-25.11	1.08	-95.23	-95.23	27.42	-13.00	-54.18	Horizontal
2	2509.00	-65.06	RMS	26.80	-24.17	0.90	-95.23	-95.23	26.64	-13.00	-52.06	Horizontal
3	3346.00	-64.03	RMS	28.19	-23.87	1.06	-95.23	-95.23	25.82	-13.00	-51.03	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B5 Ch4182

	Freq Level		Detector	Ant Amp\Cb		Filter	EIRPCF		Readin	Limit	Margin Pol	
	MHz	dBm		Factor	1		dB	dB	dBuV	dBm		
1	1673.00	-67.50	RMS	24.66	-25.11	1.08	-95.23	-95.23	27.10	-13.00	-54.50	Vertical
2	2509.00	-65.43	RMS	26.80	-24.17	0.90	-95.23	-95.23	26.27	-13.00	-52.43	Vertical
3	3346.00	-63.84	RMS	28.19	-23.87	1.06	-95.23	-95.23	26.01	-13.00	-50.84	Vertical




Ant. 2

Part 24E Mode 1

GPRS 1900 Ch512

L




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: GPRS 1900 Ch512

	Freq Level		Detector	Ant Amp\Cb Filter		Factor	Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		dB/m	dB		dB	dB			dBuV	dBm	dB	
1	3700.00	-57.43	RMS	29.60	-23.75	1.68	-95.23	30.27	-13.00	-44.43	Horizontal			
2	5551.00	-43.66	RMS	32.70	-21.83	1.54	-95.23	39.16	-13.00	-30.66	Horizontal			
3	7401.00	-55.11	RMS	36.90	-21.26	1.44	-95.23	23.04	-13.00	-42.11	Horizontal			



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: GPRS 1900 Ch512

	Freq Level		Detector	Ant Amp\Cb Filter		Factor	Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		dB/m	dB		dB	dB			dBuV	dBm	dB	
1	3700.00	-53.71	RMS	29.60	-23.75	1.68	-95.23	33.99	-13.00	-40.71	Vertical			
2	5551.00	-42.74	RMS	32.70	-21.83	1.54	-95.23	40.08	-13.00	-29.74	Vertical			
3	7401.00	-55.04	RMS	36.90	-21.26	1.44	-95.23	23.11	-13.00	-42.04	Vertical			




Ant. 2

Part 24E Mode 1

GPRS 1900 Ch661

M




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: GPRS 1900 Ch661

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Reading	Limit	Margin		Pol
				Factor	1							
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB	
1	3760.00	-59.13	RMS		30.04	-23.62	1.67	-95.23	28.01	-13.00	-46.13	Horizontal
2	5640.00	-38.69	RMS		33.06	-21.84	1.54	-95.23	43.78	-13.00	-25.69	Horizontal
3	7520.00	-54.62	RMS		36.66	-21.17	1.55	-95.23	23.57	-13.00	-41.62	Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: GPRS 1900 Ch661

	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Reading	Limit	Margin		Pol
				Factor	1							
	MHz	dBm			dB/m	dB	dB	dB	dBuV	dBm	dB	
1	3760.00	-53.94	RMS		30.04	-23.62	1.67	-95.23	33.20	-13.00	-40.94	Vertical
2	5640.00	-37.83	RMS		33.06	-21.84	1.54	-95.23	44.64	-13.00	-24.83	Vertical
3	7520.00	-54.81	RMS		36.66	-21.17	1.55	-95.23	23.38	-13.00	-41.81	Vertical
4	9405.00	-52.55	RMS		36.90	-21.96	1.54	-95.23	26.20	-13.00	-39.55	Vertical




Ant. 2

Part 24E Mode 1

GPRS 1900 Ch810

H




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: GPRS 1900 Ch810

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3825.00	-57.64	RMS	30.40	-23.53	1.69	-95.23	29.03	-13.00	-44.64 Horizontal
2	5729.00	-41.15	RMS	33.57	-21.84	1.59	-95.23	40.76	-13.00	-28.15 Horizontal
3	7639.00	-55.04	RMS	36.60	-21.26	1.61	-95.23	23.24	-13.00	-42.04 Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: GPRS 1900 Ch810

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3820.00	-57.59	RMS	30.36	-23.53	1.69	-95.23	29.12	-13.00	-44.59 Vertical
2	5729.00	-42.61	RMS	33.57	-21.84	1.59	-95.23	39.30	-13.00	-29.61 Vertical
3	7635.00	-55.00	RMS	36.60	-21.25	1.61	-95.23	23.27	-13.00	-42.00 Vertical




Ant. 2

Part 24E Mode 3

WCDMA B2 Ch9262

L




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: WCDMA B2 Ch9262

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3705.00	-61.63	RMS	29.64	-23.74	1.68	-95.23	26.02	-13.00	-48.63	Horizontal
2	5557.00	-56.84	RMS	32.73	-21.83	1.54	-95.23	25.95	-13.00	-43.84	Horizontal
3	7410.00	-55.07	RMS	36.88	-21.25	1.45	-95.23	23.08	-13.00	-42.07	Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: WCDMA B2 Ch9262

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3705.00	-62.11	RMS	29.64	-23.74	1.68	-95.23	25.54	-13.00	-49.11	Vertical
2	5557.00	-57.93	RMS	32.73	-21.83	1.54	-95.23	24.86	-13.00	-44.93	Vertical
3	7410.00	-55.51	RMS	36.88	-21.25	1.45	-95.23	22.64	-13.00	-42.51	Vertical




Ant. 2

Part 24E Mode 3

WCDMA B2 Ch9400

M




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: WCDMA B2 Ch9400

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3760.00	-61.69	RMS	30.04	-23.62	1.67	-95.23	25.45	-13.00	-48.69 Horizontal
2	5640.00	-55.82	RMS	33.06	-21.84	1.54	-95.23	26.65	-13.00	-42.82 Horizontal
3	7520.00	-54.94	RMS	36.66	-21.17	1.55	-95.23	23.25	-13.00	-41.94 Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: WCDMA B2 Ch9400

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3760.00	-61.44	RMS	30.04	-23.62	1.67	-95.23	25.70	-13.00	-48.44 Vertical
2	5640.00	-56.51	RMS	33.06	-21.84	1.54	-95.23	25.96	-13.00	-43.51 Vertical
3	7520.00	-55.59	RMS	36.66	-21.17	1.55	-95.23	22.60	-13.00	-42.59 Vertical




Ant. 2

Part 24E Mode 3

WCDMA B2 Ch9538

H




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: WCDMA B2 Ch9538

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3815.00	-60.72	RMS	30.32	-23.53	1.68	-95.23	26.04	-13.00	-47.72	Horizontal
2	5723.00	-57.09	RMS	33.54	-21.84	1.59	-95.23	24.85	-13.00	-44.09	Horizontal
3	7630.00	-55.55	RMS	36.60	-21.25	1.62	-95.23	22.71	-13.00	-42.55	Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: WCDMA B2 Ch9538

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3815.00	-60.94	RMS	30.32	-23.53	1.68	-95.23	25.82	-13.00	-47.94	Vertical
2	5723.00	-58.00	RMS	33.54	-21.84	1.59	-95.23	23.94	-13.00	-45.00	Vertical
3	7630.00	-55.40	RMS	36.60	-21.25	1.62	-95.23	22.86	-13.00	-42.40	Vertical




Ant. 0

Part 24E Mode 2

GPRS 1900 Ch661

M




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: GPRS 1900 Ch661

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
	MHz	dBm		Factor	1		g			
1	3760.00	-60.92	RMS	30.04	-23.62	1.67	-95.23	26.22	-13.00	-47.92 Horizontal
2	5640.00	-58.36	RMS	33.06	-21.84	1.54	-95.23	24.11	-13.00	-45.36 Horizontal
3	7520.00	-54.79	RMS	36.66	-21.17	1.55	-95.23	23.40	-13.00	-41.79 Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: GPRS 1900 Ch661

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin Pol	
	MHz	dBm		Factor	1		g			
1	3760.00	-60.62	RMS	30.04	-23.62	1.67	-95.23	26.52	-13.00	-47.62 Vertical
2	5640.00	-58.26	RMS	33.06	-21.84	1.54	-95.23	24.21	-13.00	-45.26 Vertical
3	7520.00	-54.68	RMS	36.66	-21.17	1.55	-95.23	23.51	-13.00	-41.68 Vertical




Ant. 0

Part 24E Mode 4

WCDMA B2 Ch9400

M




Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Horizontal

: WCDMA B2 Ch9400

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3760.00	-61.11	RMS	30.04	-23.62	1.67	-95.23	26.03	-13.00	-48.11	Horizontal
2	5640.00	-58.29	RMS	33.06	-21.84	1.54	-95.23	24.18	-13.00	-45.29	Horizontal
3	7520.00	-54.43	RMS	36.66	-21.17	1.55	-95.23	23.76	-13.00	-41.43	Horizontal



Site : 03CH21-HY

Condition: -13 1m BBHA9170_1223_250702 Vertical

: WCDMA B2 Ch9400

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBm	dB		
1	3760.00	-60.84	RMS	30.04	-23.62	1.67	-95.23	26.30	-13.00	-47.84	Vertical
2	5640.00	-58.34	RMS	33.06	-21.84	1.54	-95.23	24.13	-13.00	-45.34	Vertical
3	7520.00	-54.89	RMS	36.66	-21.17	1.55	-95.23	23.30	-13.00	-41.89	Vertical




Ant. 2

Part 27L Mode 1

WCDMA B4 Ch1312

L




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B4 Ch1312

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3425.00	-63.89	RMS	28.35	-23.94	1.88	-95.23	25.05	-13.00	-50.89	Horizontal
2	5137.00	-52.33	RMS	32.50	-21.67	2.09	-95.23	29.98	-13.00	-39.33	Horizontal
3	6850.00	-56.68	RMS	36.00	-21.56	1.46	-95.23	22.65	-13.00	-43.68	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B4 Ch1312

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3425.00	-63.56	RMS	28.35	-23.94	1.88	-95.23	25.38	-13.00	-50.56	Vertical
2	5137.00	-54.78	RMS	32.50	-21.67	2.09	-95.23	27.53	-13.00	-41.78	Vertical
3	6850.00	-56.68	RMS	36.00	-21.56	1.46	-95.23	22.65	-13.00	-43.68	Vertical




Ant. 2

Part 27L Mode 1

WCDMA B4 Ch1413

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B4 Ch1413

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	dB			dBuV	dBm		
1	3465.00	-63.40	RMS	28.49	-24.00	1.84	-95.23	25.50	-13.00	-50.40	Horizontal
2	5198.00	-52.46	RMS	32.50	-21.72	2.00	-95.23	29.99	-13.00	-39.46	Horizontal
3	6930.00	-56.18	RMS	36.06	-21.58	1.44	-95.23	23.13	-13.00	-43.18	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B4 Ch1413

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	dB			dBuV	dBm		
1	3465.00	-63.57	RMS	28.49	-24.00	1.84	-95.23	25.33	-13.00	-50.57	Vertical
2	5198.00	-55.47	RMS	32.50	-21.72	2.00	-95.23	26.98	-13.00	-42.47	Vertical
3	6930.00	-56.35	RMS	36.06	-21.58	1.44	-95.23	22.96	-13.00	-43.35	Vertical




Ant. 2

Part 27L Mode 1

WCDMA B4 Ch1513

H




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B4 Ch1513

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3505.00	-63.62	RMS	28.74	-24.04	1.79	-95.23	25.12	-13.00	-50.62	Horizontal
2	5258.00	-53.93	RMS	32.38	-21.73	1.89	-95.23	28.76	-13.00	-40.93	Horizontal
3	7010.00	-56.01	RMS	36.18	-21.59	1.43	-95.23	23.20	-13.00	-43.01	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B4 Ch1513

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3505.00	-63.52	RMS	28.74	-24.04	1.79	-95.23	25.22	-13.00	-50.52	Vertical
2	5258.00	-55.86	RMS	32.38	-21.73	1.89	-95.23	26.83	-13.00	-42.86	Vertical
3	7010.00	-55.97	RMS	36.18	-21.59	1.43	-95.23	23.24	-13.00	-42.97	Vertical




Ant. 0

Part 27L Mode 2

WCDMA B4 Ch1413

M




Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Horizontal

: WCDMA B4 Ch1413

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3465.00	-63.26	RMS	28.49	-24.00	1.84	-95.23	25.64	-13.00	-50.26	Horizontal
2	5198.00	-57.08	RMS	32.50	-21.72	2.00	-95.23	25.37	-13.00	-44.08	Horizontal
3	6930.00	-56.71	RMS	36.06	-21.58	1.44	-95.23	22.60	-13.00	-43.71	Horizontal



Site : 03CH21-HY

Condition: -13 3m DRH18-E_LE2C03A18EN_250807 Vertical

: WCDMA B4 Ch1413

	Freq Level		Detector	Ant Amp\Cb Filter		EIRPCF	Readin g	Limit		Margin	Pol
	MHz	dBm		Factor	1			dBuV	dBm		
1	3465.00	-63.61	RMS	28.49	-24.00	1.84	-95.23	25.29	-13.00	-50.61	Vertical
2	5198.00	-57.60	RMS	32.50	-21.72	2.00	-95.23	24.85	-13.00	-44.60	Vertical
3	6930.00	-56.47	RMS	36.06	-21.58	1.44	-95.23	22.84	-13.00	-43.47	Vertical




Ant. 2

Part 24E Mode 1

GPRS 1900 Ch661

M




Site : 03CH21-HY

Condition: -13 3m LF_63303&001_251126 Horizontal

: EDGE 1900 Ch661

: #1 is fundamental signal which can be ignored.

1	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm						g			
1	1880.00	-10.24	RMS	25.10	-24.94	0.60	-95.23	84.23	-13.00	2.76	Horizontal



Site : 03CH21-HY

Condition: -13 3m LF_63303&001_251126 Vertical

: EDGE 1900 Ch661

: #1 is fundamental signal which can be ignored.

1	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm						g			
1	1880.00	-11.92	RMS	25.10	-24.94	0.60	-95.23	82.55	-13.00	1.08	Vertical