



FCC RADIO TEST REPORT

FCC ID : A4RGHH4K
Equipment : Wireless Device
Model Name : GHH4K
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : 47 CFR FCC Part 15.519

The product was received on Mar 10, 2025, and testing was performed from Mar 19, 2025 to Mar. 29, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Type of EUT.....	6
1.4 Testing Applied Standards	6
1.5 Testing Location Information	7
1.6 Measurement Uncertainty	7
2 Test Configuration of EUT	8
2.1 Test Mode.....	8
2.2 The Worst Case Measurement Configuration	9
2.3 Test Setup Diagram.....	10
2.4 Support Unit used in test configuration and system	10
3 Transmitter Test Result	11
3.1 AC Power-line Conducted Emissions	11
3.2 UWB bandwidth	12
3.3 Technical requirements for hand held UWB systems	19
3.4 Peak Power Measurement	22
3.5 Radiated Emissions	29
4 Test Equipment and Calibration Data	61
Appendix A. Conducted Emissions Test Results	
Appendix B. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR511001J	01	Initial issue of report	Apr. 28, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1	15.203	Antenna Requirement	PASS	15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	15.207
3.2	15.503	UWB Bandwidth	PASS	≥ 500MHz
3.3	15.519(a)(1)	Technical requirements for Hand Held UWB systems	PASS	15.519(a)(1)
3.4	15.519(e)	Peak Power Measurement	PASS	≤ 0 dBm/50MHz
3.5	15.519(c) /15.519(d)	Radiated Emissions	PASS	UWB Emissions: 15.519(c) GPS Emissions: 15.519(d) Digital Emissions: 15.209

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Clio Lo

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, BLE, BLE ASK, BLE GFSK, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, UWB, 60GHz and GNSS.
Antenna Type UWB: PIFA Antenna

Antenna information		
6489.6 MHz	Peak Gain (dBi)	1.8
7987.2 MHz	Peak Gain (dBi)	2.8

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

EUT Information List	
S/N	Performed Test Item
51181WRCVW219X	Equivalent Isotropic Radiated Power
	Radiated Spurious Emission
51181WRCVW219R	Conducted Emission

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Type of EUT

Operational Condition	
EUT Power Type	AC mains: AC voltage 120 V
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
☐	Other:

1.4 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark: The TAF code is not including all the FCC KDB listed without accreditation.

1.5 Testing Location Information

Test Site	Sporton International Inc. Wensan Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	CO07-HY	03CH20-HY

Note: The test site complies with ANSI C63.4 2014 requirement.
FCC designation No.: TW3786

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
Conduction	CO07-HY	Louis Chung	21.5~23.6 °C 48.2~53.6 %	Mar. 29, 2025
Radiated	03CH20-HY	John Chuang, David Dai and Sam Chou	19.1~19.7 °C 65~69.8 %	Mar. 19, 2025~ Mar. 25, 2025

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
AC Conduction (150kHz ~ 30MHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1000MHz)	6.7 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 6GHz)	5.4 dB	Confidence levels of 95%
Radiated Emission (6GHz ~ 18GHz)	5.6 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.7 dB	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Mode



Test Configuration					
Config	Channel	Modulation	Config	STS Nums	Payload Length (bytes)
Mode 1	5	BPRF9	0	0	127
Mode 2	5	BPRF10	0	0	127
Mode 3	5	BPRF9	1	1	127
Mode 4	5	BPRF10	1	1	127
Mode 5	5	BPRF9	3	1	0
Mode 6	5	BPRF10	3	1	0
Mode 7	5	HPRF27	0	0	255
Mode 8	5	HPRF27	1	1	255
Mode 9	5	HPRF27	3	1	0
Mode 10	9	BPRF9	0	0	127
Mode 11	9	BPRF10	0	0	127
Mode 12	9	BPRF9	1	1	127
Mode 13	9	BPRF10	1	1	127
Mode 14	9	BPRF9	3	1	0
Mode 15	9	BPRF10	3	1	0
Mode 16	9	HPRF27	0	0	255
Mode 17	9	HPRF27	1	1	255
Mode 18	9	HPRF27	3	1	0

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	CTX
1	Adapter Mode
Remark: Please refer to 15.207 which states, "Measurements to demonstrate compliance with the conducted limits are not required for devices employ Battery for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines".	

The Worst Case Mode for Following Conformance Tests			
Tests Item	UWB Bandwidth, Peak Power Measurement, Radiated Emissions		
Test Condition	Radiated measurement		
Operating Mode	CTX		
1	Adapter Mode		
Mode 1 configuration was tested and found to be the worst case and measured during the test.			
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
CH05		V	
CH09			V
Remark: The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find as worst plane, and recorded in this report.			

2.3 Test Setup Diagram



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	N/A	N/A	N/A	N/A

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
■ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result

Please refer to Appendix A.

3.2 UWB bandwidth

3.2.1 UWB bandwidth Limit

UWB bandwidth Limit
UWB bandwidth ≥ 500 MHz or Fractional bandwidth ≥ 0.2 ; Fractional bandwidth $= 2(f_H - f_L) / (f_H + f_L)$


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures


Test Method
■ For the UWB bandwidth shall be measured using one of the options below:
■ Refer as ANSI C63.10, clause 6.9.2 and clause 10.1 for UWB bandwidth testing.


3.2.4 Test Setup





3.2.5 Test Result of UWB Bandwidth


Test mode	F _L (MHz)	F _H (MHz)	UWB Bandwidth (MHz)	Bandwidth limit (MHz)	Result	Pol [H/V]
1	6213	6749	536	≥ 500	Pass	H
2	6230	6735	505	≥ 500	Pass	H
3	6210	6755	545	≥ 500	Pass	H
4	6231	6735	504	≥ 500	Pass	H
5	6207	6752	545	≥ 500	Pass	H
6	6205	6772	567	≥ 500	Pass	H
7	6214	6756	542	≥ 500	Pass	H
8	6213	6761	548	≥ 500	Pass	H
9	6207	6761	554	≥ 500	Pass	H
10	7701	8255	554	≥ 500	Pass	H
11	7718	8232	514	≥ 500	Pass	H
12	7698	8253	555	≥ 500	Pass	H
13	7718	8245	527	≥ 500	Pass	H
14	7700	8260	560	≥ 500	Pass	H
15	7689	8256	567	≥ 500	Pass	H
16	7701	8256	555	≥ 500	Pass	H
17	7702	8256	554	≥ 500	Pass	H
18	7696	8246	550	≥ 500	Pass	H











3.3 Technical requirements for hand held UWB systems

3.3.1 Technical Requirements for transmission Limit

FCC 15.519(a) (1) A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgment of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting.

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedure


Follow the test step as below:

1. Turn on both EUT and companion receiver.
2. Set the EUT to TX mode, and EUT starts polling.
3. Set the companion receiver to associate EUT and EUT starts to transmit.
4. Disable the RX function of the companion receiver to disassociate the EUT.
5. Check if EUT stop transmitting once step 4 is made.

3.3.4 Test Setup




3.3.5 Test Result



M1 to M2: Set the EUT to TX mode, and EUT starts polling.

M2 to M3: Set the companion receiver to associate EUT and EUT starts to transmit.

M3: Disable the TX function of EUT. EUT stops transmitting and polling.



M1 to M2: Set the EUT to TX mode, and EUT starts polling.

M2 to M3: Set the companion receiver to associate EUT and EUT starts to transmit.

M3: RX function of the companion receiver is disabled. EUT disassociates the companion receiver and stops transmitting, but continues polling.



Plot 3 is zoom in plot of M2 to M3 (transmission)

Plot 4 is zoom in plot after M3 (polling only)

3.4 Peak Power Measurement

3.4.1 Peak Power Measurement Limit

Peak Power Measurement Limit
$P_{eirr} = 0 \text{ dBm/50MHz}$


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures


Test Method
Peak Power Measurement
- Refer as ANSI C63.10, clause 10.3.1 for radiated measurement procedure testing. - Refer as ANSI C63.10, clause 10.3.2 for measurement distance is 3m. - Refer as ANSI C63.10, clause 10.3.5 for peak detector procedure testing. - Refer as ANSI C63.10, clause 10.3.6 for bandwidth conversion of peak power.
- Frequency of max peak power is pre-located: The span bandwidth is continuously reduced to find the worst frequency. Once the worst frequency is found, the setting of spectrum analyzer is set as below: - Central frequency: Worst frequency point - Span: Zero span - RBW: 50MHz - VBW: 80MHz - Detector: Peak detector - Trace: Max hold


3.4.4 Test Setup



3.4.5 Test Result of Peak Power Measurement

Peak Measurement Result							
Test Mode	Freq. (MHz)	E-Field (dBuV/m)	ERIP _{50MHz} (dBm)	ERIP _{50MHz} Limit (dBm)	Margin (dB)	Result	Pol [H/V]
1	6495	91.73	-3.5	0	-3.5	Pass	H
2	6488	92.46	-2.77	0	-2.77	Pass	H
3	6488	91.56	-3.67	0	-3.67	Pass	H
4	6496	92.38	-2.85	0	-2.85	Pass	H
5	6427	85.59	-9.64	0	-9.64	Pass	H
6	6428	85.89	-9.34	0	-9.34	Pass	H
7	6365	84.79	-10.44	0	-10.44	Pass	H
8	6365	84.34	-10.89	0	-10.89	Pass	H
9	6428	85.52	-9.71	0	-9.71	Pass	H
10	7745	92.06	-3.17	0	-3.17	Pass	V
11	7735	92.39	-2.84	0	-2.84	Pass	V
12	7739	91.59	-3.64	0	-3.64	Pass	V
13	7742	91.36	-3.87	0	-3.87	Pass	V
14	7792	84.87	-10.36	0	-10.36	Pass	V
15	7800	85.18	-10.05	0	-10.05	Pass	V
16	7863	84.69	-10.54	0	-10.54	Pass	V
17	7861	84.95	-10.28	0	-10.28	Pass	V
18	7924	84.4	-10.83	0	-10.83	Pass	V
Note 1: EIRP [dBm] = E-Field [dBuV/m] - 95.23; Note 2: Measurement worst emissions of receive antenna polarization.							








Pre-located worst frequency Plots


Mode 9



Site : 03CH20-HV
Condition : PEAK_POWER 3m HF_01200_02360_241101 Horizontal
Project : RBU10000.000kHz VBU10000.000kHz Suf11.000sec
Detector : 511001
Channel : 05
Modulation : HPRF27
Conf1 : 1
STS Num : 1
Payload Length : 0
RFS Power : 0x10
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
1	6428.00	85.52	95.23	-9.71	74.17	34.97	14.34	37.96	0.00	251	250 Peak


Mode 10



Site : 03CH20-HV
Condition : PEAK_POWER 3m HF_01200_02360_241101 VERTICAL
Project : RBU10000.000kHz VBU10000.000kHz Suf11.000sec
Detector : 511001
Channel : 05
Modulation : HPRF9
Conf1 : 0
STS Num : 0
Payload Length : 127
RFS Power : 0x10
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
1	7745.00	92.06	95.23	-3.17	78.52	36.68	15.77	38.83	0.00	180	238 Peak


Mode 11



Site : 03CH20-HV
Condition : PEAK_POWER 3m HF_01200_02360_241101 VERTICAL
Project : RBU10000.000kHz VBU10000.000kHz Suf11.000sec
Detector : 511001
Channel : 05
Modulation : HPRF10
Conf1 : 0
STS Num : 0
Payload Length : 127
RFS Power : 0x10
Adaptive : 0x01
Calibration : 0x00


Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
1	7735.00	92.39	95.23	-2.84	78.85	36.68	15.76	38.82	0.00	180	238 Peak


Mode 12



Site : 03CH20-HV
Condition : PEAK_POWER 3m HF_01200_02360_241101 VERTICAL
Project : RBU10000.000kHz VBU10000.000kHz Suf11.000sec
Detector : 511001
Channel : 05
Modulation : HPRF9
Conf1 : 0
STS Num : 1
Payload Length : 127
RFS Power : 0x10
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
1	7739.00	91.59	95.23	-3.64	78.84	36.68	15.77	38.82	0.00	180	238 Peak





3.5 Radiated Emissions

3.5.1 Radiated Emissions Limit

Radiated Emissions below 960MHz and Emissions from Digital Circuitry Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Radiated Emissions above 960MHz Limit	
Frequency Range (MHz)	EIRP (dBm), RBW = 1MHz
960-1610	-75.3
1610-1990	-63.3
1990-3100	-61.3
3100-10600	-41.3
Above 10600	-61.3

Note: Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)

Radiated Emissions in GPS Bands Limit	
Frequency Range (MHz)	EIRP (dBm), RBW ≥ 1kHz
1164-1240	-85.3
1559-1610	-85.3

Note E (dBuV/m) = EIRP (dBm) + 95.23, example, E(dBuV/m) = -85.3 + 95.23 = 9.93dBuV/m

3.5.2 Measuring Instruments




Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures


Test Method for Radiated Emissions above 960MHz	
■ Radiated Emissions above 960MHz	
■	Refer as ANSI C63.10, clause 10.3.1 for radiated measurement procedure testing.
■	Refer as ANSI C63.10, clause 10.3.2 for measurement distance is 3m. In some cases, it may be necessary to measure the radiated UWB emissions at a closer distance to obtain enough signal and margin to overcome the measurement system noise floor. Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
■	Refer as ANSI C63.10, clause 10.3.4 for rms detector procedure testing.
■	Refer as ANSI C63.10, clause 10.3.7 for evaluating AVG-PSD (RBW=1MHz).
■	Refer as ANSI C63.10, clause 10.3.10 for evaluating AVG-PSD in GPS Band (RBW≥1kHz).
■ For radiated measurement.	
■	Refer as ANSI C63.10, clause 10.3.8 following eirp can be used radiated test configuration.
■	Refer as ANSI C63.10, clause 10.3.9 following eirp can be directly determined using the field strength.

Test Method for Radiated Emissions below 960MHz and Emissions from Digital Circuitry	
■ Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements) for above 30MHz-960MHz; 40dB/decade for frequency below 30MHz.	
■ For the transmitter unwanted emissions shall be measured using following options below:	
■	Refer as ANSI C63.10, clause 4.1.4 Detector functions and selection of bandwidth
□	Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions. Adjusted by a “duty cycle correction factor”, derived from 20log (dwell time/100 ms). Average emission = peak emission + 20 log (duty cycle).
■	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
■ For radiated measurement.	
■	Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
■	Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
■	Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.
■	If the noise floor can't meet the limit, the test distance will be shorten and described in the report.
■ Any unwanted emissions level shall not exceed the fundamental emission level.	


3.5.4 Test Setup





Radiated Emissions from 1GHz to 1.61 GHz



Radiated Emissions from 1.61 GHz to 10.60 GHz



Radiated Emissions from 10.60 GHz to 18GHz

Radiated Emissions above 18GHz


Note 1: Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna and the frequency range of 1 GHz to 40 GHz using a calibrated horn antenna.

Note 2: If test distance other than 3m is used, the used test distance will be recorded in test result.

3.5.5 Radiated Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Average Power Spectral Density

Test mode	Frequency (MHz)	Emission Level (dBuV/m)	Emission Limit (dBm/MHz)	Emission Limit (dBuV/m)	Margin (dB)	Result	Pol [H/V]
1	6443	53.48	-41.3	53.93	-0.45	Pass	H
2	6440	53.53	-41.3	53.93	-0.4	Pass	H
3	6442	53.83	-41.3	53.93	-0.1	Pass	H
4	6491	53.19	-41.3	53.93	-0.74	Pass	H
5	6491	53.85	-41.3	53.93	-0.08	Pass	H
6	6440	53.79	-41.3	53.93	-0.14	Pass	H
7	6441	53.19	-41.3	53.93	-0.74	Pass	H
8	6432	53.39	-41.3	53.93	-0.54	Pass	H
9	6441	53.6	-41.3	53.93	-0.33	Pass	H
10	7766	52.49	-41.3	53.93	-1.44	Pass	V
11	7952	52.5	-41.3	53.93	-1.43	Pass	V
12	7770	52.12	-41.3	53.93	-1.81	Pass	V
13	7950	52.52	-41.3	53.93	-1.41	Pass	V
14	7946	52.85	-41.3	53.93	-1.08	Pass	V
15	7770	53.72	-41.3	53.93	-0.21	Pass	V
16	7774	52.32	-41.3	53.93	-1.61	Pass	V
17	7949	52.85	-41.3	53.93	-1.08	Pass	V
18	7774	52.45	-41.3	53.93	-1.48	Pass	V



Radiated Emissions (Fundamental)

Operating Function

Adapter Mode


Polarization

H

Test Distance

3m


Mode 1



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal
RBU:1000.000kHz VBU:3000.000kHz SWT:1.000sec
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 0
STS Num : 0
Payload Length: 255
RPS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Loss	Apos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6443.00	53.48	53.93	-0.45	42.02	35.06	14.36	37.96	0.00	251	Average


Mode 2



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal
RBU:1000.000kHz VBU:3000.000kHz SWT:1.000sec
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF10
Config : 0
STS Num : 0
Payload Length: 127
RPS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Loss	Apos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6440.00	53.53	53.93	-0.40	42.09	35.04	14.36	37.96	0.00	249	Average

Mode 3



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal
RBU:1000.000kHz VBU:3000.000kHz SWT:1.000sec
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 1
STS Num : 1
Payload Length: 127
RPS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Loss	Apos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	6442.00	53.83	53.93	-0.10	42.36	35.05	14.36	37.96	0.00	254	Average



Radiated Emissions (Fundamental)

Operating Function

Adapter Mode


Polarization

H

Test Distance

3m


Mode 4



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 3
STS Num : 1
Payload Length: 127
RFS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg	
1	6491.00	53.19	53.93	-0.74	41.48	35.26	14.41	37.96	0.00	250	244	Average


Mode 5



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 3
STS Num : 1
Payload Length: 0
RFS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg	
1	6491.00	53.05	53.93	-0.08	42.14	35.26	14.41	37.96	0.00	251	261	Average




Mode 6






Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_91280_02360_241101 HORIZONTAL
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF10
Config : 3
STS Num : 1
Payload Length: 0
RFS Power : 0x19
Adaptive : 0x00
Calibration : 0x01

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dB	dB	dB	dB	dB	dB	cm	deg	
1	6440.00	53.79	53.93	-0.14	42.35	35.04	14.36	37.96	0.00	251	248	Average






Radiated Emissions (Fundamental)																																																																																																																					
Operating Function	Adapter Mode	Polarization		H																																																																																																																	
		Test Distance		3m																																																																																																																	
Mode 7					Mode 8																																																																																																																
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal Project : 511001 Detector : Average Channel : 05 Modulation : HPRF27 Config : 0 STS Num : 0 Payload Length: 255 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 6441.00</td><td>53.19</td><td>53.93</td><td>-0.74</td><td>41.74</td><td>35.05</td><td>14.36</td><td>37.96</td><td>0.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>251</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>253 Average</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor			Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg	1 6441.00	53.19	53.93	-0.74	41.74	35.05	14.36	37.96	0.00									251									253 Average	 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal Project : 511001 Detector : Average Channel : 05 Modulation : HPRF27 Config : 1 STS Num : 1 Payload Length: 255 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 6432.00</td><td>53.39</td><td>53.93</td><td>-0.54</td><td>42.01</td><td>34.99</td><td>14.35</td><td>37.96</td><td>0.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>252</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>254 Average</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor			Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg	1 6432.00	53.39	53.93	-0.54	42.01	34.99	14.35	37.96	0.00									252									254 Average
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																													
Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																															
Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg																																																																																																													
1 6441.00	53.19	53.93	-0.74	41.74	35.05	14.36	37.96	0.00																																																																																																													
								251																																																																																																													
								253 Average																																																																																																													
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																													
Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																															
Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg																																																																																																													
1 6432.00	53.39	53.93	-0.54	42.01	34.99	14.35	37.96	0.00																																																																																																													
								252																																																																																																													
								254 Average																																																																																																													
Mode 9																																																																																																																					
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 Horizontal Project : 511001 Detector : Average Channel : 05 Modulation : HPRF27 Config : 3 STS Num : 1 Payload Length: 0 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 6441.00</td><td>53.00</td><td>53.93</td><td>-0.93</td><td>42.15</td><td>35.05</td><td>14.36</td><td>37.96</td><td>0.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>251</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>250 Average</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor			Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg	1 6441.00	53.00	53.93	-0.93	42.15	35.05	14.36	37.96	0.00									251									250 Average																																																											
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																													
Freq Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																															
Hz	dBuV/m	dBuV/m	dB	dB	dB	dB	cm	deg																																																																																																													
1 6441.00	53.00	53.93	-0.93	42.15	35.05	14.36	37.96	0.00																																																																																																													
								251																																																																																																													
								250 Average																																																																																																													






Radiated Emissions (Fundamental)																																																																																			
Operating Function	Adapter Mode				Polarization	V																																																																													
					Test Distance	3m																																																																													
Mode 10					Mode 11																																																																														
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF9 Config : 0 STS Num : 0 Payload Length: 127 RIS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7766.00</td><td>52.49</td><td>53.93</td><td>-1.44</td><td>38.64</td><td>36.70</td><td>15.79</td><td>38.64</td><td>0.00</td><td>100</td><td>236</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 7766.00	52.49	53.93	-1.44	38.64	36.70	15.79	38.64	0.00	100	236	Average	 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF10 Config : 0 STS Num : 0 Payload Length: 127 RIS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7952.00</td><td>52.50</td><td>53.93</td><td>-1.43</td><td>38.30</td><td>37.10</td><td>16.09</td><td>38.99</td><td>0.00</td><td>100</td><td>239</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 7952.00	52.50	53.93	-1.43	38.30	37.10	16.09	38.99	0.00	100	239	Average
Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 7766.00	52.49	53.93	-1.44	38.64	36.70	15.79	38.64	0.00	100	236	Average																																																																								
Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 7952.00	52.50	53.93	-1.43	38.30	37.10	16.09	38.99	0.00	100	239	Average																																																																								
Mode 12																																																																																			
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF9 Config : 1 STS Num : 1 Payload Length: 127 RIS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Hz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7770.00</td><td>52.12</td><td>53.93</td><td>-1.81</td><td>38.46</td><td>36.72</td><td>15.79</td><td>38.65</td><td>0.00</td><td>100</td><td>238</td><td>Average</td></tr></table>					Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 7770.00	52.12	53.93	-1.81	38.46	36.72	15.79	38.65	0.00	100	238	Average																																											
Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Hz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																									
1 7770.00	52.12	53.93	-1.81	38.46	36.72	15.79	38.65	0.00	100	238	Average																																																																								




Radiated Emissions (Fundamental)																																																																																										
Operating Function	Adapter Mode		Polarization	V																																																																																						
			Test Distance	3m																																																																																						
Mode 13			Mode 14																																																																																							
																																																																																										
Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF10 Config : 1 STS Num : 1 Payload Length: 127 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7950.00</td><td>52.52</td><td>53.93</td><td>-1.41</td><td>39.33</td><td>37.10</td><td>16.08</td><td>30.99</td><td>0.00</td><td>100</td><td>230</td><td>Average</td></tr></table>			Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	7950.00	52.52	53.93	-1.41	39.33	37.10	16.08	30.99	0.00	100	230	Average	Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF9 Config : 3 STS Num : 1 Payload Length: 0 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7946.00</td><td>52.05</td><td>53.93</td><td>-1.08</td><td>38.66</td><td>37.10</td><td>16.08</td><td>30.99</td><td>0.00</td><td>100</td><td>239</td><td>Average</td></tr></table>										Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	7946.00	52.05	53.93	-1.08	38.66	37.10	16.08	30.99	0.00	100	239	Average
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1	7950.00	52.52	53.93	-1.41	39.33	37.10	16.08	30.99	0.00	100	230	Average																																																																														
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1	7946.00	52.05	53.93	-1.08	38.66	37.10	16.08	30.99	0.00	100	239	Average																																																																														
Mode 15																																																																																										
																																																																																										
Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : BPRF10 Config : 3 STS Num : 1 Payload Length: 0 RFS Power : 0x19 Adaptive : 0x00 Calibration : 0x01 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7770.00</td><td>53.72</td><td>53.93</td><td>-0.21</td><td>40.00</td><td>36.72</td><td>15.79</td><td>30.85</td><td>0.00</td><td>100</td><td>239</td><td>Average</td></tr></table>			Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1	7770.00	53.72	53.93	-0.21	40.00	36.72	15.79	30.85	0.00	100	239	Average																																																	
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1	7770.00	53.72	53.93	-0.21	40.00	36.72	15.79	30.85	0.00	100	239	Average																																																																														



Radiated Emissions (Fundamental)																																																																																										
Operating Function	Adapter Mode				Polarization	V																																																																																				
					Test Distance	3m																																																																																				
Mode 16						Mode 17																																																																																				
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : HPRF27 Config : 0 STS Num : 0 Payload Length: 255 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7774.00</td><td>52.32</td><td>53.93</td><td>-1.61</td><td>36.63</td><td>36.74</td><td>15.00</td><td>36.85</td><td>0.00</td><td></td><td>100</td><td>239</td><td>Average</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1 7774.00	52.32	53.93	-1.61	36.63	36.74	15.00	36.85	0.00		100	239	Average	 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : HPRF27 Config : 1 STS Num : 1 Payload Length: 255 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7949.00</td><td>52.85</td><td>53.93</td><td>-1.08</td><td>36.66</td><td>37.18</td><td>16.00</td><td>36.99</td><td>0.00</td><td></td><td>100</td><td>236</td><td>Average</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1 7949.00	52.85	53.93	-1.08	36.66	37.18	16.00	36.99	0.00		100	236	Average
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1 7774.00	52.32	53.93	-1.61	36.63	36.74	15.00	36.85	0.00		100	239	Average																																																																														
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1 7949.00	52.85	53.93	-1.08	36.66	37.18	16.00	36.99	0.00		100	236	Average																																																																														
Mode 18																																																																																										
 Site : 03CH20-HY Condition : FCC UWB HAND 3m HF_91280_02360_241101 VERTICAL Project : 511001 Detector : Average Channel : 09 Modulation : HPRF27 Config : 3 STS Num : 3 Payload Length: 0 RFS Power : 0x19 Adaptive : 0x01 Calibration : 0x00 <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1 7774.00</td><td>52.45</td><td>53.93</td><td>-1.48</td><td>36.76</td><td>36.74</td><td>15.00</td><td>36.85</td><td>0.00</td><td></td><td>100</td><td>239</td><td>Average</td></tr></table>						Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg		1 7774.00	52.45	53.93	-1.48	36.76	36.74	15.00	36.85	0.00		100	239	Average																																														
Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																															
1 7774.00	52.45	53.93	-1.48	36.76	36.74	15.00	36.85	0.00		100	239	Average																																																																														




3.5.7 Radiated Emissions (30MHz – 1GHz)





CH05 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 5	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : QP 3m Bilog_55606 & 08_241127 VERTICAL
: RBW:120.000kHz VBW:300.000kHz SWT:1.000sec
Project : 511001
Detector : Peak
Channel : 05
Modulation : BPRF9
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	54.25	27.88	40.00	-12.12		49.08	13.00	1.30	35.73	0.23	--	--	Peak
2	100.81	30.87	43.50	-12.63		48.21	16.33	1.79	35.68	0.22	--	--	Peak
3	201.69	29.50	43.50	-14.00		47.17	15.11	2.53	35.51	0.20	--	--	Peak
4	261.83	22.82	46.00	-23.18		34.89	20.24	2.87	35.37	0.19	--	--	Peak
5	571.26	28.66	46.00	-17.34		32.63	26.24	4.23	34.55	0.11	--	--	Peak
6	902.03	36.96	46.00	-9.04		35.71	29.10	5.31	33.32	0.16	--	--	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Peak emission setting: RBW=120kHz; VBW = 300kHz.



CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 15	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : QP 3m Bilog_55606 & 08_241127 HORIZONTAL
RBW:120.000kHz VBW:300.000kHz SWT:1.000sec
Project : 511001
Detector : PEAK
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x18
Adaptive : 0x00
Calibration : 0x01

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	32.91	23.62	40.00		-16.38	34.92	23.21	1.01	35.75	0.23	--	--	Peak
2	101.78	29.29	43.50		-14.21	46.50	16.45	1.80	35.68	0.22	--	--	Peak
3	195.87	32.41	43.50		-11.09	50.24	15.00	2.49	35.52	0.20	--	--	Peak
4	646.92	30.08	46.00		-15.92	33.21	26.50	4.50	34.28	0.15	--	--	Peak
5	838.98	32.23	46.00		-13.77	31.93	28.61	5.11	33.53	0.11	--	--	Peak
6	922.40	33.94	46.00		-12.06	32.16	29.54	5.36	33.25	0.13	--	--	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Peak emission setting: RBW=120kHz; VBW = 300kHz.



CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 15	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : QP 3m Bilog_55606 & 08_241127 VERTICAL
RBW:120.000kHz VBW:300.000kHz SWT:1.000sec
Project : 511001
Detector : PEAK
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x18
Adaptive : 0x00
Calibration : 0x01

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	100.81	29.79	43.50	-13.71		47.13	16.33	1.79	35.68	0.22	--	--	Peak
2	100.81	29.79	43.50	-13.71		47.13	16.33	1.79	35.68	0.22	--	--	Peak
3	194.90	29.39	43.50	-14.11		47.23	14.99	2.49	35.52	0.20	--	--	Peak
4	304.51	22.78	46.00	-23.22		35.41	19.35	3.09	35.26	0.19	--	--	Peak
5	638.19	30.10	46.00	-15.90		33.23	26.57	4.47	34.31	0.14	--	--	Peak
6	857.41	34.02	46.00	-11.98		33.05	29.15	5.17	33.46	0.11	--	--	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Peak emission setting: RBW=120kHz; VBW = 300kHz.

3.5.8 Radiated Emissions (960MHz – 18GHz)

CH05 Radiated Emissions (960MHz – 18GHz)			
Test Mode	Mode 5	Polarization	H
Operating Function	Adapter Mode		
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.		



Site : 03CH20-HY
 Condition : FCC UWB HAND 3m HF_91200_02360_241101 Horizontal
 Project : 511001
 Detector : Average
 Channel : 05
 Modulation : BPRF9
 Config : 3
 STS Num : 1
 Payload Length : 0
 RMS Power : 0x19
 Adaptive : 0x01
 Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	976.04	16.46	19.93	-3.47	28.49	31.08	5.50	33.05	-15.56	--	--	Average
2	1158.60	18.16	19.93	-1.77	31.37	25.99	5.99	35.65	-9.54	--	--	Average
3	1955.04	27.02	31.93	-4.91	29.21	26.15	7.78	36.12	0.00	--	--	Average
4	3042.28	30.20	33.93	-3.73	26.75	29.70	9.87	36.12	0.00	--	--	Average
5	6437.50	53.70	53.93	-0.23	42.29	35.02	14.35	37.96	0.00	--	--	Average
6	17992.60	31.33	33.93	-2.60	24.66	43.16	24.53	45.46	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 5: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 6: #5 is fundamental signal.


Note 7:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
 (Note: Aux Factor = Distance extrapolation factor)
Example: Corrected Reading: 31.22 (dB/m) + 5.51 (dB) + 25.67 (dBuV) – 31.37 (dB) + 0.23 dB + (-15.56) (dB) = 15.70 (dBuV/m)



CH05 Radiated Emissions (960MHz – 18GHz)

Test Mode	Mode 5	Polarization	V
Operating Function	Adapter Mode		
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.		



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_9120D_02360_241101 Vertical
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 3
STS Num : 1
Payload Length : 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	cm	deg	
1	975.20	16.49	19.93	-3.44	28.51	31.09	5.50	33.05	-15.56	--	--	Average
2	1161.04	18.17	19.93	-1.76	31.37	26.00	5.99	35.65	-9.54	--	--	Average
3	1960.36	27.01	31.93	-4.92	29.24	26.10	7.79	36.12	0.00	--	--	Average
4	3022.30	29.90	33.93	-4.03	26.45	29.70	9.84	36.09	0.00	--	--	Average
5	6490.00	50.97	53.93	-2.96	39.26	35.26	14.41	37.96	0.00	--	--	Average
6	17985.20	31.34	33.93	-2.59	24.71	43.11	24.53	45.45	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 5: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 6: #5 is fundamental signal.


Note 7:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)



CH09 Radiated Emissions (960MHz – 18GHz)

Test Mode	Mode 15	Polarization	H
Operating Function	Adapter Mode		
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.		



Site : 03CH20-HY
Condition : FCC UWB HAND 3m HF_9120D_02360_241101 Horizontal
Project : RBW:1000.000kHz VBW:3000.000kHz SWT:18.000sec
Detector : 511001
Channel : Average
Modulation : 09
Config : BPRF10
STS Nums : 3
Payload Length: 1
RMS Power : 0
Adaptive : 0x18
Calibration : 0x01

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	976.04	16.43	19.93	-3.50	28.46	31.08	5.50	33.05	-15.56	--	--	Average
2	1161.04	18.17	19.93	-1.76	31.37	26.00	5.99	35.65	-9.54	--	--	Average
3	1952.38	27.09	31.93	-4.84	29.26	26.18	7.77	36.12	0.00	--	--	Average
4	3032.29	29.88	33.93	-4.05	26.42	29.70	9.86	36.10	0.00	--	--	Average
5	7780.00	53.47	53.93	-0.46	39.74	36.78	15.80	38.85	0.00	--	--	Average
6	17985.20	31.32	33.93	-2.61	24.69	43.11	24.53	45.45	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 5: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.


Note 6: #5 is fundamental signal.

Note 7:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)



CH09 Radiated Emissions (960MHz – 18GHz)			
Test Mode	Mode 15	Polarization	V
Operating Function	Adapter Mode		
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.		



Site : 03CH20-HY
 Condition : FCC UWB HAND 3m HF_9120D_02360_241101 Vertical
 Project : 511001
 Detector : Average
 Channel : 09
 Modulation : BPRF10
 Config : 3
 STS Nums : 1
 Payload Length: 0
 RNS Power : 0x18
 Adaptive : 0x00
 Calibration : 0x01

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	975.84	16.44	19.93	-3.49	28.47	31.08	5.50	33.03	-15.56	--	--	Average
2	1159.21	18.15	19.93	-1.78	31.36	25.99	5.99	35.65	-9.54	--	--	Average
3	1954.66	26.99	31.93	-4.94	29.18	26.15	7.78	36.12	0.00	--	--	Average
4	3034.51	29.92	33.93	-4.01	26.46	29.70	9.86	36.10	0.00	--	--	Average
5	7787.50	53.84	53.93	-0.09	40.06	36.83	15.81	38.86	0.00	--	--	Average
6	17992.60	31.19	33.93	-2.74	24.52	43.16	24.53	45.46	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 5: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.


Note 6: #5 is fundamental signal.

Note 7:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)




3.5.9 Radiated Emissions (1164MHz – 1240MHz)





CH05 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 5	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Vertical
Project : 511001
Detector : Peak
Channel : 05
Modulation : BPRF9
Config : 3
STS Num : 1
Payload Length : 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 1239.85	-0.62	9.93		-10.55	2.97	25.90	6.20	35.69	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: E (dBuV/m) = EIRP Limit (dBm) + 95.23. E(dBuV/m) = -85.3 + 95.23 = 9.93dBuV/m.



CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 15	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Horizontal
Project : 511001
Detector : Peak
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	1239.16	-0.93	9.93	-10.86	2.65	25.92	6.19	35.69	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.



CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 15	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Vertical
RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
Project : 511001
Detector : Peak
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	1169.93	-1.13	9.93	-11.06	2.50	26.00	6.02	35.65	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.


3.5.10 Radiated Emissions (1559MHz – 1610MHz)





CH05 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 5	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Vertical
Project : RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
Detector : Peak
Channel : 05
Modulation : BPRF9
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	1591.59	-1.42	9.93		-11.35	2.06	25.37	7.01	35.86	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.



CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 15	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Horizontal
Project : 511001
Detector : Peak
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	1590.42	-1.69	9.93	-11.62	1.77	25.39	7.01	35.86	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.



CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 15	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : UWB_GPS 3m HF_9120D_02360_241101 Vertical
Project : 511001
Detector : Peak
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	1590.26	-1.85	9.93	-11.78	1.61	25.39	7.01	35.86	0.00	100	0	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 5: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.


3.5.11 Radiated Emissions (18GHz – 40GHz)





CH05 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 5	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH20-HY
Condition : FCC UWB HAND 1m BBHA9170_1224_240624 Vertical
Project : 511001
Detector : Average
Channel : 05
Modulation : BPRF9
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x19
Adaptive : 0x01
Calibration : 0x00

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	39454.00	32.30	33.93	-1.63	49.66	45.34	9.09	56.23	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 5:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)



CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 15	Polarization	H
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH20-HY
Condition : FCC UWB HAND 1m BBHA9170_1224_240624 Horizontal
Project : 511001
Detector : Average
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x18
Adaptive : 0x00
Calibration : 0x01

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 39454.00	32.28	33.93		-1.65	49.64	45.34	9.09	56.23	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 5:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)



CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 15	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH20-HY
Condition : FCC UWB HAND 1m BBHA9170_1224_240624 Vertical
Project : 511001
Detector : Average
Channel : 09
Modulation : BPRF10
Config : 3
STS Nums : 1
Payload Length: 0
RMS Power : 0x18
Adaptive : 0x00
Calibration : 0x01

Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1 39468.00	32.25	33.93	-1.68	49.42	45.48	9.13	56.22	-15.56	--	--	Average

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: Average emission setting: RBW=1MHz; VBW=3MHz.

Note 5:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: Aux Factor = Distance extrapolation factor)



4 Test Equipment and Calibration Data

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 16, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Oct. 15, 2025	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Aug. 28, 2025	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 27, 2024	Mar 19, 2025 ~ Mar. 25, 2025	May 26, 2025	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar 19, 2025 ~ Mar. 25, 2025	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar 19, 2025 ~ Mar. 25, 2025	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar 19, 2025 ~ Mar. 25, 2025	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 09, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Dec. 08, 2025	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00802N1 D01N-06	55606 & 08	30MHz~1GHz	Nov. 27, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Nov. 26, 2025	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 01, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Oct. 31, 2025	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz-40GHz	Jun. 24, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Jun. 23, 2025	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Dec. 31, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Dec. 30, 2025	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 12, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Nov. 11, 2025	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,8040 15/2,804027/2	N/A	Jan. 16, 2025	Mar 19, 2025 ~ Mar. 25, 2025	Jan. 15, 2026	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP211382	N/A	Mar. 27, 2024	Mar 19, 2025 ~ Mar. 25, 2025	Mar. 26, 2025	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Mar 19, 2025 ~ Mar. 25, 2025	N/A	Radiation (03CH20-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Mar. 29, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 29, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Mar. 29, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Mar. 29, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Mar. 29, 2025	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Mar. 29, 2025	Sep. 22, 2025	Conduction (CO07-HY)




Appendix A. AC Conducted Emission Test Results

EUT Information

Report NO :
Test Mode :
Test Voltage :
Phase :

511001
Mode 1
120Vac/60Hz
Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.150000	---	25.93	56.00	30.07	L1	FLO	20.0
0.150000	42.31	---	66.00	23.69	L1	FLO	20.0
0.184650	---	20.44	54.27	33.83	L1	FLO	20.0
0.184650	35.10	---	64.27	29.17	L1	FLO	20.0
0.222000	---	17.94	52.74	34.80	L1	FLO	20.0
0.222000	28.31	---	62.74	34.43	L1	FLO	20.0
0.413160	---	22.69	47.59	24.90	L1	FLO	20.0
0.413160	36.29	---	57.59	21.30	L1	FLO	20.0
0.632670	---	19.15	46.00	26.85	L1	FLO	20.0
0.632670	40.63	---	56.00	15.37	L1	FLO	20.0
0.654000	---	21.28	46.00	24.72	L1	FLO	20.0
0.654000	40.40	---	56.00	15.60	L1	FLO	20.0
0.678750	---	26.13	46.00	19.87	L1	FLO	20.0
0.678750	39.70	---	56.00	16.30	L1	FLO	20.0
1.311000	---	18.03	46.00	27.97	L1	FLO	20.0
1.311000	32.43	---	56.00	23.57	L1	FLO	20.0
12.970500	---	24.82	50.00	25.18	L1	FLO	20.5
12.970500	28.95	---	60.00	31.05	L1	FLO	20.5
21.750000	---	19.21	50.00	30.79	L1	FLO	20.9

21.750000	23.44	---	60.00	36.56	L1	FLO	20.9
-----------	-------	-----	-------	-------	----	-----	------

EUT Information

Report NO : 511001
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.168990	---	19.63	55.01	35.38	N	FLO	20.0
0.168990	40.21	---	65.01	24.80	N	FLO	20.0
0.186000	---	22.32	54.21	31.89	N	FLO	20.0
0.186000	36.63	---	64.21	27.58	N	FLO	20.0
0.221820	---	23.21	52.75	29.54	N	FLO	20.0
0.221820	35.99	---	62.75	26.76	N	FLO	20.0
0.237750	---	14.44	52.17	37.73	N	FLO	20.0
0.237750	23.98	---	62.17	38.19	N	FLO	20.0
0.405780	---	32.38	47.73	15.35	N	FLO	20.0
0.405780	36.40	---	57.73	21.33	N	FLO	20.0
0.663000	---	20.57	46.00	25.43	N	FLO	20.0
0.663000	39.34	---	56.00	16.66	N	FLO	20.0
1.303080	---	18.63	46.00	27.37	N	FLO	20.0
1.303080	31.43	---	56.00	24.57	N	FLO	20.0
12.342390	---	21.03	50.00	28.97	N	FLO	20.5
12.342390	24.87	---	60.00	35.13	N	FLO	20.5
21.760350	---	19.21	50.00	30.79	N	FLO	20.9
21.760350	23.50	---	60.00	36.50	N	FLO	20.9