The following test report with report number FR5N0815-01L is an addendum to the RF spot check test report for FCC ID: A4RGM45K variant model GM45K.
It contains test data from FCC ID: A4RG7SWN reference model G7SWN that is referenced in the variant model GM45K RF spot check report.

FCC RADIO TEST REPORT

FCC ID	:	**A4RG7SWN**
Equipment	:	**Phone**
Model Name	:	**G7SWN**
Applicant	:	**Google LLC** **1600 Amphitheatre Parkway,** **Mountain View, CA, 94043 USA**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Nov. 25, 2025 and testing was performed from Dec. 09, 2025 to Mar. 07, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 6
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 9
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Output Power Measurement 12
3.3 Power Spectral Density Measurement 13
3.4 Conducted Band Edges and Spurious Emission Measurement 14
3.5 Radiated Band Edges and Spurious Emission Measurement 15
3.6 AC Conducted Emission Measurement 19
3.7 Antenna Requirements 21
4 List of Measuring Equipment **22**
5 Measurement Uncertainty **24**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR5N0815-01L	01	Initial issue of report	Apr. 10, 2026
FR5N0815-01L	02	Revise Test Mode This report is an updated version, replacing the report issued on Apr. 10, 2026.	May 05, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx. **Antenna Type** Bluetooth: **<Ant. 3>:** IFA Antenna **<Ant. 4>:** IFA Antenna

EUT Information List	
S/N	**Performed Test Item**
61061FDKX00033	RF Conducted Measurement
61061FDKX0002L	Radiated Spurious Emission
61061FDKX0003L	Conducted Emission

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant.3: -3.6 Ant.4: -1.8

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	-	-	27	2429	54	2456
	-	-	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	-	-	50	2452	-	-
	-	-	51	2453	-	-
	-	-	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Adapter or Earphone), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find X plane with Adapter for <Ant. 3> and <Ant. 4> as worst plane.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases		
Test Item	**Data Rate / Modulation**	
Conducted Test Cases	**Bluetooth LE 1Mbps CS GFSK**	**Bluetooth LE 2Mbps CS GFSK**
	Mode 1: CH02_2404 MHz Mode 2: CH38_2440 MHz Mode 3: CH76_2478 MHz	Mode 4: CH02_2404 MHz Mode 5: CH38_2440 MHz Mode 6: CH76_2478 MHz
AC Conducted Emission	Mode 4 : Bluetooth-LE CS Channel 38 Tx + USB Cable 2 (Charging from AC Adapter)	

Remark:
1. For Radiated Test Cases, the tests were performed with USB Cable 2.
2. During the preliminary test, both charging modes (Adapter mode and WPC Rx mode) were verified. It is determined that the adaptor mode is the worst case for official test.
3. The detailed Radiated test modes are shown in Appendix C.

2.3 Connection Diagram of Test System



Conduction Test Setup									
No.	Power Source	Connection Type	Test Mode						
			4	-	-	-	-	-	-
B1	AC : 120V/60Hz	AC Power Cable	X	-	-	-	-	-	-

Radiation Tx Test Setup									
No.	Power Source	Connection Type	Test Mode						
			1~16	-	-	-	-	-	-
B1	AC : 120V/60Hz	AC Power Cable	X	-	-	-	-	-	-

2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Adapter	N/A	GW8L7	N/A	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “BT DUT Control GUI.exe (Ver 09-04-25)” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW ≥ 3 * RBW. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) ≥ 3 * RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as "-".
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as "-".
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW = 100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW = 3 MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9kHz~30MHz	Mar. 06, 2025	Dec. 09, 2025~ Feb. 11, 2026	Mar. 05, 2026	Radiation (03CH11-HY)
Bilog Antenna with 6dB pad	TESEQ & VGT	CBL 6111D & VFA_Z-04002-N-06	66925 & 24006	30MHz~1GHz	Feb. 19, 2025	Dec. 09, 2025~ Feb. 11, 2026	Feb. 18, 2026	Radiation (03CH11-HY)
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-01620	1GHz~18GHz	Sep. 15, 2025	Dec. 09, 2025~ Feb. 11, 2026	Sep. 14, 2026	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1225	18GHz~40GHz	Jul. 02, 2025	Dec. 09, 2025~ Feb. 11, 2026	Jul. 01, 2026	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 06, 2025	Dec. 09, 2025~ Feb. 11, 2026	Dec. 05, 2026	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Mar. 24, 2025	Dec. 09, 2025~ Feb. 11, 2026	Mar. 23, 2026	Radiation (03CH11-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz~18GHz	Jan. 21, 2025	Dec. 09, 2025~ Jan. 19, 2026	Jan. 20, 2026	Radiation (03CH11-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz~18GHz	Jan. 20, 2026	Jan. 20, 2026~ Feb. 11, 2026	Jan. 19, 2027	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	May 26, 2025	Dec. 09, 2025~ Feb. 11, 2026	May 25, 2026	Radiation (03CH11-HY)
Signal Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 23, 2025	Dec. 09, 2025~ Feb. 11, 2026	Oct. 22, 2026	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY55420170	20MHz~8.4GHz	Jul. 22, 2025	Dec. 09, 2025~ Feb. 11, 2026	Jul. 21, 2026	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303B	TP200880	N/A	Aug. 26, 2025	Dec. 09, 2025~ Feb. 11, 2026	Aug. 25, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804013/2	30MHz~40GHz	Mar. 05, 2025	Dec. 09, 2025~ Feb. 11, 2026	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Dec. 09, 2025~ Feb. 11, 2026	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	30MHz~40GHz	Mar. 05, 2025	Dec. 09, 2025~ Feb. 11, 2026	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	805139/2	30MHz~40GHz	May 10, 2025	Dec. 09, 2025~ Feb. 11, 2026	May 09, 2026	Radiation (03CH11-HY)
Notch Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 09, 2025	Dec. 09, 2025~ Feb. 11, 2026	Sep. 08, 2026	Radiation (03CH11-HY)
Notch Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1.53GHz Low Pass Filter	Sep. 09, 2025	Dec. 09, 2025~ Feb. 11, 2026	Sep. 08, 2026	Radiation (03CH11-HY)
Attenuator	HONOVA	5910 SMA-50-005	0028	N/A	Sep. 09, 2025	Dec. 09, 2025~ Feb. 11, 2026	Sep. 08, 2026	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 09, 2025~ Feb. 11, 2026	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Dec. 09, 2025~ Feb. 11, 2026	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Dec. 09, 2025~ Feb. 11, 2026	N/A	Radiation (03CH11-HY)
Software	Audix	E3	RK-002391	N/A	N/A	Dec. 09, 2025~ Feb. 11, 2026	N/A	Radiation (03CH11-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Feb. 12, 2026~ Feb. 27, 2026	Nov. 03, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Feb. 12, 2026~ Feb. 27, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Feb. 12, 2026~ Feb. 27, 2026	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900067 (BOX7)	N/A	Jul. 02, 2025	Feb. 12, 2026~ Feb. 27, 2026	Jul. 01, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Feb. 12, 2026~ Feb. 27, 2026	N/A	Conducted (TH05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Feb. 08, 2026~ Mar. 07, 2026	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Feb. 08, 2026~ Mar. 01, 2026	Mar. 02, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 02, 2026	Mar. 02, 2026~ Mar. 07, 2026	Mar. 01, 2027	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Feb. 08, 2026~ Mar. 07, 2026	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 21, 2025	Feb. 08, 2026~ Mar. 07, 2026	Oct. 20, 2026	Conduction (CO07-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Feb. 08, 2026~ Mar. 07, 2026	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Feb. 08, 2026~ Mar. 07, 2026	N/A	Conduction (CO07-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.5 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.7 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.9 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Joseph Hu	Temperature:	21~25	°C
Test Date:	2026/02/12~2026/02/27	Relative Humidity:	51~54	%

<Ant. 3>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE CS GFSK	1Mbps	1	2	2404	1.070	0.684	0.50	Pass
	1Mbps	1	38	2440	1.070	0.690	0.50	Pass
	1Mbps	1	76	2478	1.068	0.687	0.50	Pass
BLE CS GFSK	2Mbps	1	2	2404	2.108	1.198	0.50	Pass
	2Mbps	1	38	2440	2.117	1.153	0.50	Pass
	2Mbps	1	76	2478	2.117	1.192	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE CS GFSK	1Mbps	1	2	2404	19.40	30.00	-3.60	15.80	36.00	Pass
	1Mbps	1	38	2440	19.30	30.00	-3.60	15.70	36.00	Pass
	1Mbps	1	76	2478	19.81	30.00	-3.60	16.21	36.00	Pass
BLE CS GFSK	2Mbps	1	2	2404	19.45	30.00	-3.60	15.85	36.00	Pass
	2Mbps	1	38	2440	19.40	30.00	-3.60	15.80	36.00	Pass
	2Mbps	1	76	2478	19.81	30.00	-3.60	16.21	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE CS GFSK	1Mbps	1	2	2404	19.27	2.89	-3.60	8.00	Pass
	1Mbps	1	38	2440	18.66	1.47	-3.60	8.00	Pass
	1Mbps	1	76	2478	18.99	2.63	-3.60	8.00	Pass
BLE CS GFSK	2Mbps	1	2	2404	18.81	-2.14	-3.60	8.00	Pass
	2Mbps	1	38	2440	18.33	-2.88	-3.60	8.00	Pass
	2Mbps	1	76	2478	18.70	-2.38	-3.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<Ant. 4>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE CS GFSK	1Mbps	1	2	2404	1.071	0.684	0.50	Pass
	1Mbps	1	38	2440	1.069	0.697	0.50	Pass
	1Mbps	1	76	2478	1.066	0.693	0.50	Pass
BLE CS GFSK	2Mbps	1	2	2404	2.110	1.142	0.50	Pass
	2Mbps	1	38	2440	2.109	1.128	0.50	Pass
	2Mbps	1	76	2478	2.111	1.230	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE CS GFSK	1Mbps	1	2	2404	18.69	30.00	-1.80	16.89	36.00	Pass
	1Mbps	1	38	2440	18.43	30.00	-1.80	16.63	36.00	Pass
	1Mbps	1	76	2478	18.71	30.00	-1.80	16.91	36.00	Pass
BLE CS GFSK	2Mbps	1	2	2404	18.53	30.00	-1.80	16.73	36.00	Pass
	2Mbps	1	38	2440	18.86	30.00	-1.80	17.06	36.00	Pass
	2Mbps	1	76	2478	19.40	30.00	-1.80	17.60	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE CS GFSK	1Mbps	1	2	2404	17.27	0.68	-1.80	8.00	Pass
	1Mbps	1	38	2440	17.85	0.70	-1.80	8.00	Pass
	1Mbps	1	76	2478	18.34	0.46	-1.80	8.00	Pass
BLE CS GFSK	2Mbps	1	2	2404	17.12	-4.17	-1.80	8.00	Pass
	2Mbps	1	38	2440	17.62	-3.80	-1.80	8.00	Pass
	2Mbps	1	76	2478	18.06	-3.06	-1.80	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Number of TX = 1, Ant. 3 (Measured)

6dB Bandwidth

<1Mbps>

6 dB Bandwidth Plot on Channel 02	6 dB Bandwidth Plot on Channel 38
	
6 dB Bandwidth Plot on Channel 76	
	

<2Mbps>

6 dB Bandwidth Plot on Channel 02	6 dB Bandwidth Plot on Channel 38
	
6 dB Bandwidth Plot on Channel 76	
	

99% Occupied Bandwidth

<1Mbps>

99% Occupied Bandwidth Plot on Channel 02



99% Occupied Bandwidth Plot on Channel 38



99% Occupied Bandwidth Plot on Channel 76



<2Mbps>

99% Occupied Bandwidth Plot on Channel 02	99% Occupied Bandwidth Plot on Channel 38
	
99% Occupied Bandwidth Plot on Channel 76	
	

Power Spectral Density (dBm/3kHz)

<1Mbps>

Power Density (dBm/3kHz) Plot Channel 02	Power Density (dBm/3kHz) Plot Channel 38
	
Power Density (dBm/3kHz) Plot Channel 76	
	

<2Mbps>

Power Density (dBm/3kHz) Plot Channel 02	Power Density (dBm/3kHz) Plot Channel 38
	
Power Density (dBm/3kHz) Plot Channel 76	
	

Band Edge and Conducted Spurious Emission

<1Mbps>

Channel 02	
100kHz PSD reference Level Plot	**Plot on Channel 02**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 38

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 76

100kHz PSD reference Level Plot



Plot on Channel 76



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



<2Mbps>

Channel 02	
100kHz PSD reference Level Plot	**Plot on Channel 02**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 38

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 76

100kHz PSD reference Level Plot



Plot on Channel 76



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Number of TX = 1, Ant. 4 (Measured)

6dB Bandwidth

<1Mbps>

6 dB Bandwidth Plot on Channel 02	6 dB Bandwidth Plot on Channel 38
	
6 dB Bandwidth Plot on Channel 76	
	

<2Mbps>

6 dB Bandwidth Plot on Channel 02	6 dB Bandwidth Plot on Channel 38
	
6 dB Bandwidth Plot on Channel 76	
	

99% Occupied Bandwidth

<1Mbps>

99% Occupied Bandwidth Plot on Channel 02



99% Occupied Bandwidth Plot on Channel 38



99% Occupied Bandwidth Plot on Channel 76



<2Mbps>

99% Occupied Bandwidth Plot on Channel 02	99% Occupied Bandwidth Plot on Channel 38
	
99% Occupied Bandwidth Plot on Channel 76	
	

Power Spectral Density (dBm/3kHz)

<1Mbps>

Power Density (dBm/3kHz) Plot Channel 02	Power Density (dBm/3kHz) Plot Channel 38
	
Power Density (dBm/3kHz) Plot Channel 76	
	

<2Mbps>

Power Density (dBm/3kHz) Plot Channel 02	Power Density (dBm/3kHz) Plot Channel 38
	
Power Density (dBm/3kHz) Plot Channel 76	
	

Band Edge and Conducted Spurious Emission

<1Mbps>

Channel 02	
100kHz PSD reference Level Plot	**Plot on Channel 02**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 38

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 76

100kHz PSD reference Level Plot



Plot on Channel 76



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



<2Mbps>

Channel 02	
100kHz PSD reference Level Plot	**Plot on Channel 02**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 38

100kHz PSD reference Level Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Channel 76

100kHz PSD reference Level Plot



Plot on Channel 76



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	**Temperature :**	15.4~19.3℃
		Relative Humidity :	42.1~48.8%

EUT Information

Report NO :	5N0813-01
Test Mode :	Mode 4
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.157560	---	21.48	55.59	34.11	L1	ON	20.0
0.157560	40.60	---	65.59	24.99	L1	ON	20.0
0.179115	---	29.80	54.53	24.73	L1	ON	20.0
0.179115	44.31	---	64.53	20.22	L1	ON	20.0
0.197250	---	17.49	53.73	36.24	L1	ON	20.0
0.197250	35.66	---	63.73	28.07	L1	ON	20.0
0.669750	---	25.59	46.00	20.41	L1	ON	20.0
0.669750	31.35	---	56.00	24.65	L1	ON	20.0
4.625070	---	18.20	46.00	27.80	L1	ON	20.2
4.625070	24.90	---	56.00	31.10	L1	ON	20.2
21.799950	---	22.72	50.00	27.28	L1	ON	20.9
21.799950	26.88	---	60.00	33.12	L1	ON	20.9

EUT Information

Report NO :	5N0813-01
Test Mode :	Mode 4
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.175605	---	30.77	54.69	23.92	N	ON	20.0
0.175605	45.67	---	64.69	19.02	N	ON	20.0
0.237750	---	14.93	52.17	37.24	N	ON	20.0
0.237750	28.22	---	62.17	33.95	N	ON	20.0
0.604500	---	12.91	46.00	33.09	N	ON	20.0
0.604500	14.60	---	56.00	41.40	N	ON	20.0
0.655260	---	24.44	46.00	21.56	N	ON	20.0
0.655260	30.73	---	56.00	25.27	N	ON	20.0
0.708000	---	15.58	46.00	30.42	N	ON	20.0
0.708000	23.57	---	56.00	32.43	N	ON	20.0
21.678495	---	21.24	50.00	28.76	N	ON	20.9
21.678495	25.60	---	60.00	34.40	N	ON	20.9

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Bill Chang, Daniel Lee, Fu Chen and Troye Hsieh	**Temperature :**	19.1~21.9°C
		Relative Humidity :	50.1~66.9%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	3	BLE CS GFSK	02	2404	1Mbps	-	-
Mode 2	2400-2483.5	3	BLE CS GFSK	38	2440	1Mbps	-	-
Mode 3	2400-2483.5	3	BLE CS GFSK	76	2478	1Mbps	-	-
Mode 4	2400-2483.5	3	BLE CS GFSK	02	2404	2Mbps	-	-
Mode 5	2400-2483.5	3	BLE CS GFSK	38	2440	2Mbps	-	-
Mode 6	2400-2483.5	3	BLE CS GFSK	76	2478	2Mbps	-	-
Mode 13	2400-2483.5	3	BLE CS GFSK	76	2478	2Mbps	-	SHF
Mode 15	2400-2483.5	3	BLE CS GFSK	76	2478	2Mbps	-	LF
Mode 7	2400-2483.5	4	BLE CS GFSK	02	2404	1Mbps	-	-
Mode 8	2400-2483.5	4	BLE CS GFSK	38	2440	1Mbps	-	-
Mode 9	2400-2483.5	4	BLE CS GFSK	76	2478	1Mbps	-	-
Mode 10	2400-2483.5	4	BLE CS GFSK	02	2404	2Mbps	-	-
Mode 11	2400-2483.5	4	BLE CS GFSK	38	2440	2Mbps	-	-
Mode 12	2400-2483.5	4	BLE CS GFSK	76	2478	2Mbps	-	-
Mode 14	2400-2483.5	4	BLE CS GFSK	38	2440	2Mbps	-	SHF
Mode 16	2400-2483.5	4	BLE CS GFSK	38	2440	2Mbps	-	LF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	BLE CS GFSK	02	2374.95	47.38	54.00	-6.62	V	Avg.	Pass	-	Band Edge
	BLE CS GFSK	02	4808.00	40.88	74.00	-33.12	V	Peak	Pass	-	Harmonic
2	BLE CS GFSK	38	2499.52	48.16	54.00	-5.84	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	38	7320.00	43.85	74.00	-30.15	H	Peak	Pass	-	Harmonic
3	BLE CS GFSK	76	2491.73	48.32	54.00	-5.68	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	76	7434.00	43.89	74.00	-30.11	H	Peak	Pass	-	Harmonic
4	BLE CS GFSK	02	2379.84	48.46	54.00	-5.54	V	Avg.	Pass	-	Band Edge
	BLE CS GFSK	02	4808.00	41.78	74.00	-32.22	V	Peak	Pass	-	Harmonic
5	BLE CS GFSK	38	2488.96	49.08	54.00	-4.92	V	Avg.	Pass	-	Band Edge
	BLE CS GFSK	38	7320.00	43.71	74.00	-30.29	H	Peak	Pass	-	Harmonic
6	BLE CS GFSK	76	2499.32	49.10	54.00	-4.90	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	76	7434.00	44.46	74.00	-29.54	H	Peak	Pass	-	Harmonic
13	SHF	76	24698.57	41.13	74.00	-32.87	H	Peak	Pass	-	SHF
15	LF	76	30.00	31.38	40.00	-8.62	V	Peak	Pass	-	LF
7	BLE CS GFSK	02	2389.43	47.48	54.00	-6.52	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	02	4808.00	41.25	74.00	-32.75	V	Peak	Pass	-	Harmonic
8	BLE CS GFSK	38	2487.46	47.85	54.00	-6.15	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	38	7320.00	42.96	74.00	-31.04	V	Peak	Pass	-	Harmonic
9	BLE CS GFSK	76	2484.09	48.11	54.00	-5.89	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	76	7434.00	44.44	74.00	-29.56	H	Peak	Pass	-	Harmonic
10	BLE CS GFSK	02	2382.57	49.08	54.00	-4.92	V	Avg.	Pass	-	Band Edge
	BLE CS GFSK	02	4808.00	40.21	74.00	-33.79	V	Peak	Pass	-	Harmonic
11	BLE CS GFSK	38	2491.36	49.38	54.00	-4.62	V	Avg.	Pass	-	Band Edge
	BLE CS GFSK	38	7320.00	44.35	74.00	-29.65	H	Peak	Pass	-	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
12	BLE CS GFSK	76	2491.64	48.99	54.00	-5.01	H	Avg.	Pass	-	Band Edge
	BLE CS GFSK	76	7434.00	44.00	74.00	-30.00	H	Peak	Pass	-	Harmonic
14	SHF	38	24777.71	40.15	74.00	-33.85	H	Peak	Pass	-	SHF
16	LF	38	30.97	32.25	40.00	-7.75	V	Peak	Pass	-	LF

Mode	1	
	Band Edge	
	2400-2483.5_BLE CS GFSK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2349.01 53.53 74.00 -20.47 42.71 27.20 6.74 33.24 10.12 141 29 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 114.23 ------ ------ 103.14 27.34 6.82 33.19 10.12 141 29 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2350.42 47.20 54.00 -6.80 36.38 27.20 6.74 33.24 10.12 141 29 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 114.12 ------ ------ 103.03 27.34 6.82 33.19 10.12 141 29 Average

Mode	1	
	Band Edge	
	2400-2483.5_BLE CS GFSK_CH02_2404MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2371.29 53.97 74.00 -20.03 43.10 27.20 6.77 33.22 10.12 389 101 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 110.87 ------ ------ 99.78 27.34 6.82 33.19 10.12 389 101 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2374.95 47.38 54.00 -6.62 36.50 27.20 6.78 33.22 10.12 389 101 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 110.47 ------ ------ 99.38 27.34 6.82 33.19 10.12 389 101 Average

Mode	1	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4808.00 40.41 74.00 -33.59 63.95 32.33 10.35 67.17 0.95 -- -- Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL Mode : 1 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4808.00 40.88 74.00 -33.12 64.42 32.33 10.35 67.17 0.95 -- -- Peak

Mode	1	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 1 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 1 Setting : 22
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 1 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 1 Setting : 22

Mode	2	
	Band Edge - L	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2354.07 53.63 74.00 -20.37 42.80 27.20 6.74 33.23 10.12 229 32 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 112.79 ------ ------ 101.49 27.50 6.84 33.16 10.12 229 32 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2385.01 47.04 54.00 -6.96 36.08 27.25 6.80 33.21 10.12 229 32 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 112.49 ------ ------ 101.19 27.50 6.84 33.16 10.12 229 32 Average

Mode	2	
	Band Edge - R	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2488.48 53.83 74.00 -20.17 42.18 27.77 6.87 33.11 10.12 229 32 Peak	Blank
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2499.52 48.16 54.00 -5.84 36.46 27.80 6.88 33.10 10.12 229 32 Average	Blank

Mode	2	
	Band Edge - L	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2383.71 53.24 74.00 -20.76 42.30 27.24 6.79 33.21 10.12 300 105 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 109.28 ------ ------ 97.98 27.50 6.84 33.16 10.12 300 105 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2331.19 47.04 54.00 -6.96 36.27 27.20 6.71 33.26 10.12 300 105 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 109.04 ------ ------ 97.74 27.50 6.84 33.16 10.12 300 105 Average

Mode	2	
	Band Edge - R	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2493.52 53.90 74.00 -20.10 42.21 27.80 6.88 33.11 10.12 300 105 Peak	Blank
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2489.62 47.79 54.00 -6.21 36.12 27.79 6.87 33.11 10.12 300 105 Average	Blank

Mode	2	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 40.48 74.00 -33.52 63.36 32.62 10.66 67.11 0.95 -- -- Peak 2 7320.00 43.85 74.00 -30.15 59.20 36.82 13.74 66.10 0.19 -- -- Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL Mode : 2 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 41.05 74.00 -32.95 63.93 32.62 10.66 67.11 0.95 -- -- Peak 2 7320.00 43.38 74.00 -30.62 58.73 36.82 13.74 66.10 0.19 -- -- Peak

Mode	2	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 2 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 2 Setting : 22
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 2 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 2 Setting : 22

Mode	3	
	Band Edge	
	2400-2483.5_BLE CS GFSK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2485.19 54.86 74.00 -19.14 43.28 27.70 6.87 33.11 10.12 187 30 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2478.00 112.26 ------ ------ 100.79 27.60 6.87 33.12 10.12 187 30 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2491.73 48.32 54.00 -5.68 36.63 27.80 6.88 33.11 10.12 187 30 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2478.00 112.15 ------ ------ 100.68 27.60 6.87 33.12 10.12 187 30 Average

Mode	3	
	Band Edge	
	2400-2483.5_BLE CS GFSK_CH76_2478MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2495.78 54.44 74.00 -19.56 42.74 27.80 6.88 33.10 10.12 400 117 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2478.00 108.73 ------ ------ 97.26 27.60 6.87 33.12 10.12 400 117 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2499.69 47.79 54.00 -6.21 36.09 27.80 6.88 33.10 10.12 400 117 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL : RBW:1000.000kHz VBW:24.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2478.00 108.49 ------ ------ 97.02 27.60 6.87 33.12 10.12 400 117 Average

Mode	3	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4956.00 42.64 74.00 -31.36 64.82 32.92 10.99 67.05 0.96 -- -- Peak 2 7434.00 43.89 74.00 -30.11 59.74 36.30 13.85 66.18 0.18 -- -- Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 VERTICAL Mode : 3 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4956.00 42.28 74.00 -31.72 64.46 32.92 10.99 67.05 0.96 -- -- Peak 2 7434.00 43.52 74.00 -30.48 59.37 36.30 13.85 66.18 0.18 -- -- Peak

Mode	3	
	Harmonic	
	2400-2483.5_BLE CS GFSK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 3 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 3 Setting : 22
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL Mode : 3 Setting : 22	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 VERTICAL Mode : 3 Setting : 22

Mode	4	
	Band Edge	
	2400-2483.5_BLE CS GFSK_CH02_2404MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2351.55 53.30 74.00 -20.70 42.48 27.20 6.74 33.24 10.12 200 31 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 111.79 ------ ------ 100.70 27.34 6.82 33.19 10.12 200 31 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2376.55 48.30 54.00 -5.70 37.41 27.20 6.78 33.21 10.12 200 31 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:39.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 22 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2404.00 111.06 ------ ------ 99.97 27.34 6.82 33.19 10.12 200 31 Average