The following test report with report number FR5N0815-01D is an addendum to the RF spot check test report for FCC ID: A4RGM45K variant model GM45K.
It contains test data from FCC ID: A4RG7SWN reference model G7SWN that is referenced in the variant model GM45K RF spot check report.

FCC RADIO TEST REPORT

FCC ID	:	A4RG7SWN
Equipment	:	Phone
Model Name	:	G7SWN
Applicant	:	Google LLC 1600 Amphitheatre Parkway, Mountain View, CA, 94043 USA
Standard	:	FCC Part 15 Subpart C §15.225

The product was received on Dec. 03, 2025 and testing was performed from Dec. 11, 2025 to Feb. 12, 2026. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1. General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2. Test Configuration of Equipment Under Test **7**
2.1 Descriptions of Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Table for Supporting Units 9
2.4 EUT Operation Test Setup 9
3. Test Results **10**
3.1 AC Power Line Conducted Emissions Measurement 10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement 12
3.3 Frequency Stability Measurement 13
3.4 Field Strength of Fundamental Emissions and Mask Measurement 14
3.5 Radiated Emissions Measurement 16
3.6 Antenna Requirements 19
4. List of Measuring Equipment **20**
5. Measurement Uncertainty **21**
Appendix A. Test Results of Conducted Emission Test
Appendix B. Test Results of Near Field Test Items
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
Appendix C. Test Results of Radiated Test Items
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)
Appendix D. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR5N0815-01D	01	Initial issue of report	Mar. 06, 2025
FR5N0815-01D	02	Revised Test Configuration of Equipment Under Test This report is an updated version, replacing the report issued on Mar. 06, 2025	May 05, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	-
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Pass	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	-
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	-
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Yuri Huang

1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs GSM/WCDMA/LTE/5G NR/NTN , Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx. **Antenna Type** NFC: Loop Antenna

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

EUT Information List	
S/N	Performed Test Item
61061FDKX00036	RF Near Field
61061FDKX00035	Conducted Emission
5B111FDDW0000R	Radiated Spurious Emission

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. **Remark:** The RF Near Field test item subcontracted to Sporton International Inc. Wensan Laboratory.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB 414788 D01 Radiated Test Site v01r01
- FCC Part 15 Subpart C §15.225
- ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in reader mode with NFC tag (four NFC type A, B, F, V) and without reading tag. Based on the highest field strength of fundamental and spurious emissions, the worst case with tag (type F) was determined during the pre-scan and recorded in this report.

The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and three receiving antenna orientations (parallel, perpendicular, and ground-parallel) for Loop Antenna, and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions Z plane with adaptor were reported in this report.

Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + WLAN Idle + NFC Read + USB cable 2 (Type C) + BT Idle + Adapter
Remark: For Radiated Test Cases, the tests were performed with USB Cable 2	

2.2 Connection Diagram of Test System



Conduction Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	-	-	-	-	-	-
A1	BT Earphone	Bluetooth	X	-	-	-	-	-	-
A2	System Simulator	GSM	X	-	-	-	-	-	-
A3	AP router	WiFi	X	-	-	-	-	-	-
A4	NFC Card	NFC	X	-	-	-	-	-	-
No.	**Power Source**	**Connection Type**	**1**	**-**	**-**	**-**	**-**	**-**	**-**
B1	AC : 120V/60Hz	AC Power Cable	X	-	-	-	-	-	-

Radiation Tx Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	7
A1	NFC Card	NFC	X	X					
No.	**Power Source**	**Connection Type**	**1**	**2**	**3**	**4**	**5**	**6**	**7**
B1	AC : 110V/60Hz	AC Power Cable	X						
No.	**Setup Peripherals**	**Connection Type**	**1**	**2**	**3**	**4**	**5**	**6**	**7**
C1	Adapter	USB to Type C	X						
C2	Earphone	Earphone jack		X					

2.3 Table for Supporting Units

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Google	G7T9J/G7YPJ	N/A	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
4.	Adapter	Honor	GW8L7 LPS PS2	N/A	N/A	N/A
5.	NFC Card	N/A	N/A	N/A	N/A	N/A
6.	NFC Card	Winso	N/A	N/A	N/A	N/A
7.	Earphone	Apple	A3046	FCC DoC	N/A	Unshielded,1.2m

Remark: Applicant has ensured support unit would not be attached with the product on the market, support unit is provided by lab for testing.

2.4 EUT Operation Test Setup

The EUT is programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmitting signal (Power Level: Default) at 13.56MHz.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB and 99% emission bandwidth in the specific band 13.553~13.567 MHz.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max Hold Mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20 dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed by using a new battery.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT has transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ±100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Near Field Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

Remark:

1. The field strength test result is in 3m test distance, follow test rules the test data use distance extrapolation factor and reported in this report at 30m test result.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna is fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9 kHz.
   Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated test below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT is placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower is placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna is varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower is scanned (from 1 M to 4 M) and then the turntable is rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30 MHz, loop antenna has to be used for measurement and the recorded data shall be QP measured by receiver.
8. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.

3.5.5 Test Setup

For radiated test below 30MHz



For radiated test above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark:

1. There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.
2. After pre-scan three receiving antenna orientations parallel (horizontal), perpendicular(vertical), and ground-parallel for Loop Antenna, the worst case is receiving antenna parallel.

3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

b) Unique (non-standard) antenna connector.

(3) Use of a standard connector is also allowed if the connector is within the transmitter enclosure and can only be accessed by disassembly of the transmitter, where such disassembly is not normally required. The user manual must not show that user has access to the connector.

4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Feb. 06, 2026	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 16, 2025	Feb. 06, 2026	Dec. 15, 2026	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Feb. 06, 2026	Jun. 25, 2026	Conduction (CO05-HY)
Two-Line V-Network	Rohde & Schwarz	ENV216	100081	N/A	Jul. 25, 2025	Feb. 06, 2026	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Feb. 06, 2026	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	00691	N/A	Jul. 29, 2025	Feb. 06, 2026	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 14, 2025	Feb. 06, 2026	Oct. 13, 2026	Conduction (CO05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 30, 2025	Feb. 12, 2026	Sep. 29, 2026	Conducted (TH05-HY)
DC Power Supply	GW Instek	GPE-2323	GEU871221	0V~64V ; 0A~6A	Apr. 14, 2025	Feb. 12, 2026	Apr. 13, 2026	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SU-242	93000763	-30℃ ~95℃	Jan. 05, 2026	Feb. 12, 2026	Jan. 04, 2027	Conducted (TH05-HY)
Hygrometer	TECPEL	DTM-303B	TP200886	N/A	Mar. 03, 2025	Feb. 12, 2026	Mar. 02, 2026	Conducted (TH05-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 23,2025	Dec. 11, 2025	Jan. 22,2026	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35419 & 03	30MHz~1GHz	Apr. 21,2025	Dec. 11, 2025	Apr. 20,2026	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 06,2025	Dec. 11, 2025	Mar. 05,2026	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	Sep. 30,2025	Dec. 11, 2025	Sep. 29,2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4 MY15682/4	30MHz to 18GHz	Feb. 20,2025	Dec. 11, 2025	Feb. 19,2026	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/4 MY24971/4	9kHz to 30MHz	Feb. 20,2025	Dec. 11, 2025	Feb. 19,2026	Radiation (03CH07-HY)
Antenna Mast	MF	MF-7802	N/A	Control Turn table	N/A	Dec. 11, 2025	N/A	Radiation (03CH07-HY)
Controller	EMEC	EM1000	N/A	Control Ant Mast	N/A	Dec. 11, 2025	N/A	Radiation (03CH07-HY)
Antenna Mast	EMEC	AM-BS-4500E	N/A	Boresight mast 1M~4M	N/A	Dec. 11, 2025	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Dec. 11, 2025	N/A	Radiation (03CH07-HY)
Software	Audix	E3	RK-002396	N/A	N/A	Dec. 11, 2025	N/A	Radiation (03CH07-HY)
USB Data Logger	TECPEL	TR-32	HE17XB2495	N/A	Feb. 24,2025	Dec. 11, 2025	Feb. 23,2026	Radiation (03CH07-HY)

5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.8 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.3 dB

Appendix A. Test Results of Conducted Emission Test

<Original>
EUT Information

Report NO :	5N0815-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.165750	---	28.49	55.17	26.68	L1	OFF	19.8
0.165750	49.50	---	65.17	15.67	L1	OFF	19.8
0.195000	---	21.20	53.82	32.62	L1	OFF	19.8
0.195000	29.53	---	63.82	34.29	L1	OFF	19.8
0.258000	---	24.94	51.50	26.56	L1	OFF	19.8
0.258000	39.15	---	61.50	22.35	L1	OFF	19.8
0.267000	---	24.92	51.21	26.29	L1	OFF	19.8
0.267000	38.26	---	61.21	22.95	L1	OFF	19.8
0.505500	---	20.56	46.00	25.44	L1	OFF	19.8
0.505500	26.00	---	56.00	30.00	L1	OFF	19.8
13.560000	---	56.69	50.00	-6.69	L1	OFF	20.6
13.560000	56.74	---	60.00	3.26	L1	OFF	20.6
23.554500	---	26.87	50.00	23.13	L1	OFF	20.6
23.554500	32.20	---	60.00	27.80	L1	OFF	20.6

EUT Information

Report NO :	5N0815-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	22.98	55.88	32.90	N	OFF	19.8
0.152250	30.18	---	65.88	35.70	N	OFF	19.8
0.168000	---	22.43	55.06	32.63	N	OFF	19.8
0.168000	31.21	---	65.06	33.85	N	OFF	19.8
0.181500	---	29.07	54.42	25.35	N	OFF	19.8
0.181500	44.05	---	64.42	20.37	N	OFF	19.8
0.217500	---	20.52	52.91	32.39	N	OFF	19.8
0.217500	26.21	---	62.91	36.70	N	OFF	19.8
0.609000	---	19.10	46.00	26.90	N	OFF	19.8
0.609000	24.12	---	56.00	31.88	N	OFF	19.8
6.380250	---	22.08	50.00	27.92	N	OFF	20.2
6.380250	27.30	---	60.00	32.70	N	OFF	20.2
13.560000	---	56.77	50.00	-6.77	N	OFF	20.6
13.560000	56.83	---	60.00	3.17	N	OFF	20.6

<Terminal>
EUT Information

Report NO :	5N0815-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	22.54	50.00	27.46	L1	OFF	20.6
13.560000	27.86	---	60.00	32.14	L1	OFF	20.6

EUT Information

Report NO :	5N0815-01
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	23.02	50.00	26.98	N	OFF	20.6
13.560000	28.24	---	60.00	31.76	N	OFF	20.6

Appendix B. Test Results of Near Field Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
			
20dB Bandwidth (kHz)	2.64	**99% OccupiedBW(kHz)**	2.24
Frequency range (MHz)	**f_L > 13.553**	13.55872	**Test Result**
	f_H < 13.567	13.56136	**Complies**

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (℃)	Time (min)	Measurement Frequency (MHz)
3.9	13.560040	**-20**	**0**	13.560120
3.6	13.560040		**2**	13.560120
4.4	13.560040		**5**	13.560120
			10	13.560120
		-10	**0**	13.560120
			2	13.560120
			5	13.560120
			10	13.560120
		0	**0**	13.560120
			2	13.560120
			5	13.560120
			10	13.560120
		10	**0**	13.560100
			2	13.560100
			5	13.560100
			10	13.560090
		20	**0**	13.560060
			2	13.560060
			5	13.560060
			10	13.560060
		30	**0**	13.560040
			2	13.560040
			5	13.560040
			10	13.560040
		40	**0**	13.560020
			2	13.560020
			5	13.560020
			10	13.560020

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vdc)	Measurement Frequency (MHz)	Temperature (℃)	Time (min)	Measurement Frequency (MHz)
		50	0	13.560020
			2	13.560020
			5	13.560020
			10	13.560020
Max.Deviation (MHz)	0.000040	Max.Deviation (MHz)		0.000120
Max.Deviation (ppm)	2.9499	Max.Deviation (ppm)		8.8496
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(H)_100315 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	ReadLevel	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	26.39	-57.61	84.00	45.35	20.64	0.40	100	191	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB) = 40 log (30/3) = 40 (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

Test Mode :	NFC Tx	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(V)_100315 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	23.45	-60.55	84.00	42.41	20.64	0.40	100	273	QP

Note :

1. Distance extrapolation factor = 40 log (specific distance / test distance) (dB) = 40 log (30/3) = 40 (dB)
2. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx	Polarization :	Horizontal



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(H)_100315 HORIZONTAL
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	0.06	-29.18	-61.53	32.35	32.56	18.25	0.01	---	---	Average
2	0.07	-38.31	-69.65	31.34	23.78	17.90	0.01	---	---	Average
3	0.09	-37.33	-65.64	28.31	25.04	17.62	0.01	---	---	QP
4	0.13	-34.28	-59.94	25.66	27.90	17.80	0.02	---	---	Average
5	0.25	-38.13	-57.71	19.58	23.74	18.10	0.03	---	---	Average
6	1.68	-8.12	-31.20	23.08	13.54	18.20	0.14	---	---	QP
7	11.14	-3.49	-32.99	29.50	15.43	20.71	0.37	---	---	QP
8	13.56	26.39	-3.11	29.50	45.35	20.64	0.40	---	---	QP
9	24.35	-2.22	-31.72	29.50	14.65	22.59	0.54	---	---	QP
10	27.57	-1.14	-30.64	29.50	15.19	23.10	0.57	---	---	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
   EX.:
   For below 490kHz Distance extrapolation factor = 40 log (300/3) = 80 (dB)
   For 490kHz to 30MHz Distance extrapolation factor = 40 log (30/3) = 40 (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

Test Mode :	NFC Tx	Polarization :	Vertical



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(V)_100315 VERTICAL
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	0.06	-29.45	-61.65	32.20	32.37	18.17	0.01	---	---	Average
2	0.07	-38.72	-69.77	31.05	23.46	17.81	0.01	---	---	Average
3	0.09	-38.50	-66.81	28.31	23.87	17.62	0.01	---	---	QP
4	0.13	-39.26	-64.92	25.66	22.92	17.80	0.02	---	---	Average
5	0.25	-41.19	-60.71	19.52	20.68	18.10	0.03	---	---	Average
6	1.68	-7.41	-30.53	23.12	14.25	18.20	0.14	---	---	QP
7	8.31	-3.45	-32.95	29.50	16.34	19.90	0.31	---	---	QP
8	13.56	23.45	-6.05	29.50	42.41	20.64	0.40	---	---	QP
9	23.79	-1.54	-31.04	29.50	15.83	22.10	0.53	---	---	QP
10	27.71	-1.19	-30.69	29.50	15.14	23.10	0.57	---	---	QP

Note :

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
   EX.:
   For below 490kHz Distance extrapolation factor = 40 log (300/3) = 80 (dB)
   For 490kHz to 30MHz Distance extrapolation factor = 40 log (30/3) = 40 (dB)
3. Level = Antenna Factor + Cable Loss + Read Level - Distance extrapolation factor.
4. 13.56 MHz is fundamental signal which can be ignored

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx	Polarization :	Horizontal



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6)_H HORIZONTAL
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	ReadLevel	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	50.25	27.89	-12.11	40.00	42.24	14.36	1.29	30.00	---	---	Peak
2	94.80	31.03	-12.47	43.50	43.90	15.32	1.77	29.96	---	---	Peak
3	203.34	34.21	-9.29	43.50	46.48	15.14	2.53	29.94	---	---	Peak
4	217.11	31.73	-14.27	46.00	43.92	15.13	2.60	29.92	---	---	Peak
5	859.30	33.51	-12.49	46.00	28.36	29.29	5.06	29.20	---	---	Peak
6	958.70	34.17	-11.83	46.00	26.64	30.88	5.35	28.70	---	---	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.

Test Mode :	NFC Tx	Polarization :	Vertical



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6)_H VERTICAL
Project : 5N0813
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	33.39	-6.61	40.00	39.12	23.68	0.58	29.99	---	---	Peak
2	40.68	34.26	-5.74	40.00	43.88	19.22	1.18	30.02	100	180	QP
3	67.80	36.92	-3.08	40.00	53.15	12.23	1.48	29.94	119	57	QP
4	785.80	31.33	-14.67	46.00	27.86	28.14	4.82	29.49	---	---	Peak
5	874.00	32.06	-13.94	46.00	26.99	29.15	5.08	29.16	---	---	Peak
6	953.10	33.78	-12.22	46.00	26.44	30.75	5.33	28.74	---	---	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.
4. The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.