



FCC RADIO TEST REPORT

The following test report with report number FR5N0815-01O is an addendum to the RF spot check test report for FCC ID: A4RGM45K variant model GM45K. It contains test data from FCC ID: A4RG7SWN reference model G7SWN that is referenced in the variant model GM45K RF spot check report.




FCC RADIO TEST REPORT

FCC ID : A4RG7SWN
Equipment : Phone
Model Name : G7SWN
Applicant : Google LLC
1600 Amphitheatre Parkway,
Mountain View, CA, 94043 USA
Standard : 47 CFR FCC Part 15.519

The product was received on Dec. 09, 2025, and testing was performed from Dec. 12, 2025 to Mar. 09, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Type of EUT	6
1.4 Testing Applied Standards	6
1.5 Testing Location Information	7
1.6 Measurement Uncertainty	7
2 Test Configuration of EUT	8
2.1 Test Mode.....	8
2.2 The Worst Case Measurement Configuration.....	9
2.3 Test Setup Diagram	10
2.4 Support Unit used in test configuration and system	10
3 Transmitter Test Result	11
3.1 AC Power-line Conducted Emissions	11
3.2 UWB bandwidth.....	12
3.3 Technical requirements for hand held UWB systems	18
3.4 Peak Power Measurement	21
3.5 Radiated Emissions.....	27
4 Test Equipment and Calibration Data	75
Appendix A. Conducted Emissions Test Results	
Appendix B. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR5N0815-01O	01	Initial issue of report	Mar. 16, 2026
FR5N0815-01O	02	Revised Appendix B. Setup Photographs This report is an updated version, replacing the report issued on Apr. 20, 2026.	May 06, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1	15.203	Antenna Requirement	PASS	15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	15.207
3.2	15.503	UWB Bandwidth	PASS	≥ 500MHz
3.3	15.519(a)(1)	Technical requirements for Hand Held UWB systems	PASS	15.519(a)(1)
3.4	15.519(e)	Peak Power Measurement	PASS	≤ 0 dBm/50MHz
3.5	15.519(c) /15.519(d)	Radiated Emissions	PASS	UWB Emissions: 15.519(c) GPS Emissions: 15.519(d) Digital Emissions: 15.209

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: William Chen

Report Producer: Vina Su

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs GSM/WCDMA/LTE/5G NR/NTN, Bluetooth, BLE, BLE channel sounding, Thread, Wi-Fi 802.11be, NFC, WPC Rx, UWB and GNSS Rx.		
Antenna Type UWB: <Antenna 3>: IFA Antenna <Antenna 5>: IFA Antenna <Patch Antenna>: PIFA Antenna		
Antenna information		
6489.6 MHz	Peak Gain (dBi)	<Antenna 5>: - 0.64
7987.2 MHz	Peak Gain (dBi)	<Antenna 3>: 1.40 <Antenna 5>: -0.51 <Patch Antenna>: 3.02

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

EUT Information List	
S/N	Performed Test Item
61061FDKX0003L	AC Conducted Emission
5B111FDDW0000M	Equivalent Isotropic Radiated Power
	Radiated Spurious Emission

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Type of EUT

Operational Condition	
EUT Power Type	AC mains: AC voltage 120 V
Type of EUT	
☒	Stand-alone
☐	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
☐	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
☐	Other:

1.4 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2020 + Cor.1-2023
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark: The TAF code is not including all the FCC KDB listed without accreditation.

1.5 Testing Location Information

Test Site	Sporton International Inc. Wensan Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	CO07-HY	03CH20-HY 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.
FCC designation No.: TW3786

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
Conduction	CO07-HY	Louis Chung	15.4~18.0 °C 42.1~45.6 %	Feb. 09, 2026
Radiated	03CH22-HY	Bill Chang, York Huang and Ken Kuo	20.9~24.6 °C 56.1~68.7 %	Dec. 12, 2025~ Dec. 31, 2025
Radiated	03CH20-HY	David Dai	18.9~20.6 °C 60.2~69.5 %	Mar 09, 2026

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
AC Conduction (150kHz ~ 30MHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1000MHz)	6.6 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 6GHz)	5.2 dB	Confidence levels of 95%
Radiated Emission (6GHz ~ 18GHz)	5.0 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	5.7 dB	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Mode



Test Configuration					
Mode	Antenna	Channel	Modulation	Case	Payload Length (bytes)
1	Antenna 3	9	BPRF	1	125
2	Antenna 5	5	BPRF	1	125
3	Antenna 5	9	BPRF	1	125
4	Patch Antenna	9	BPRF	1	125
5	Antenna 3	9	BPRF	2	125
6	Antenna 5	5	BPRF	2	125
7	Antenna 5	9	BPRF	2	125
8	Patch Antenna	9	BPRF	2	125
9	Antenna 3	9	BPRF	3	NA
10	Antenna 5	5	BPRF	3	NA
11	Antenna 5	9	BPRF	3	NA
12	Patch Antenna	9	BPRF	3	NA
13	Antenna 3	9	HPRF	4	150
14	Antenna 5	5	HPRF	4	150
15	Antenna 5	9	HPRF	4	150
16	Patch Antenna	9	HPRF	4	150
17	Antenna 3	9	HPRF	5	150
18	Antenna 5	5	HPRF	5	150
19	Antenna 5	9	HPRF	5	150
20	Patch Antenna	9	HPRF	5	150
21	Antenna 3	9	HPRF	6	N/A
22	Antenna 5	5	HPRF	6	N/A
23	Antenna 5	9	HPRF	6	N/A
24	Patch Antenna	9	HPRF	6	N/A
25	Antenna 3	9	HPRF	7	N/A
26	Antenna 5	5	HPRF	7	N/A
27	Antenna 5	9	HPRF	7	N/A
28	Patch Antenna	9	HPRF	7	N/A

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	CTX
1	Adapter Mode
Remark: Please refer to 15.207 which states, "Measurements to demonstrate compliance with the conducted limits are not required for devices employ Battery for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines".	

The Worst Case Mode for Following Conformance Tests			
Tests Item	Radiated Emissions		
Test Condition	Radiated measurement		
Operating Mode	CTX		
6, 12, 13, 19	Adaptor Mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Antenna 3 CH09		V	
Antenna 5 CH05		V	
Antenna 5 CH09			V
Patch Antenna CH09			V
Remark: - The measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find as worst plane, and recorded in this report. - For UWB Bandwidth Measurement, all modes are performed and only the maximum bandwidth plot per antenna per channel is shown in the test report, which is Case 3: Mode 9, 10, 11, 12. - For Peak Power Measurement, all modes are performed and only the worst case plot per antenna per channel is shown in the test report, which is Case 1: Mode 1, 2, 3, 4.			

2.3 Test Setup Diagram



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	NOTE BOOK	Dell	Latitude E6320	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
2.	Adapter	Google	GWBL7 LPS SP2	N/A	N/A	

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method	
■	Refer as ANSI C63.10-2020 + Cor.1-2023, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result

Please refer to Appendix A.

3.2 UWB bandwidth

3.2.1 UWB bandwidth Limit

UWB bandwidth Limit
UWB bandwidth ≥ 500 MHz or Fractional bandwidth ≥ 0.2 ; Fractional bandwidth = $2(f_H - f_L) / (f_H + f_L)$


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
For the UWB bandwidth shall be measured using one of the options below:
Refer as ANSI C63.10, clause 6.9.2 and clause 10.1 for UWB bandwidth testing.

3.2.4 Test Setup




3.2.5 Test Result of UWB Bandwidth

Test mode	F _L (MHz)	F _H (MHz)	UWB Bandwidth (MHz)	Bandwidth limit (MHz)	Result	Pol [H/V]
1	7713	8260	547	≥ 500	Pass	H
2	6216	6763	547	≥ 500	Pass	H
3	7715	8261	546	≥ 500	Pass	H
4	7714	8260	546	≥ 500	Pass	H
5	7713	8260	547	≥ 500	Pass	V
6	6216	6763	547	≥ 500	Pass	H
7	7716	8260	544	≥ 500	Pass	V
8	7714	8260	546	≥ 500	Pass	H
9	7704	8260	556	≥ 500	Pass	V
10	6216	6763	547	≥ 500	Pass	H
11	7716	8261	545	≥ 500	Pass	H
12	7714	8260	546	≥ 500	Pass	H
13	7713	8260	547	≥ 500	Pass	V
14	6216	6763	547	≥ 500	Pass	H
15	7716	8261	545	≥ 500	Pass	H
16	7713	8260	547	≥ 500	Pass	H
17	7714	8260	546	≥ 500	Pass	H
18	6217	6763	546	≥ 500	Pass	H
19	7716	8261	545	≥ 500	Pass	H
20	7714	8260	546	≥ 500	Pass	H
21	7713	8260	547	≥ 500	Pass	V
22	6216	6763	547	≥ 500	Pass	H
23	7715	8261	546	≥ 500	Pass	H
24	7713	8260	547	≥ 500	Pass	H
25	7704	8260	556	≥ 500	Pass	V
26	6217	6762	545	≥ 500	Pass	H
27	7715	8261	546	≥ 500	Pass	V
28	7714	8259	545	≥ 500	Pass	H



UWB Bandwidth
Antenna 3 Channel 9

Mode 9 – Bandwidth 8260MHz – 7704MHz = 556MHz




Site : 03CH22-HY
Condition : 3m DRH18-E_LE2C04A18EN_250520 Vertical
Project : 5N0813
Detector : Peak
SN : 58111FDDW000M
Antenna : 3L
Modulation : BPSK
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes) : 20
Sweep point(pts) : 1001

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	Factor	cm	deg	
1	7704.00	60.25	-----	-----	44.24	36.99	14.61	36.48	0.00	0.89	--	--	Peak
2	7717.00	70.91	-----	-----	54.93	36.97	14.62	36.50	0.00	0.89	--	--	Peak
3	8260.00	57.76	-----	-----	41.85	37.08	15.11	37.21	0.00	0.93	--	--	Peak



UWB Bandwidth
Antenna 5 Channel 5

Mode 10 – Bandwidth 6763MHz – 6216MHz = 547MHz




Site : 03CH22-HY
Condition : 3% DRH15-E_LE2C04A18EN_250520 Horizontal
Project : R8W:1000.000kHz VBW:3000.000kHz SWT:3.000sec
Detector : 5N0813
SN : Peak
Antenna : 5B111FDDW000M
Modulation : 5
Channel : BPRF
Test Case Number : CH5
Payload Length (bytes): Case 3
Sweep point(pts): 20
Sweep point(pts): 1001

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	6216.00	58.64	-----	-----	44.46	34.93	13.21	34.98	1.02	0.00	--	--	Peak
2	6521.00	71.73	-----	-----	56.43	36.04	13.43	35.16	0.99	0.00	--	--	Peak
3	6763.00	57.63	-----	-----	41.68	36.45	13.80	35.49	0.99	0.00	--	--	Peak



UWB Bandwidth
Antenna 5 Channel 9

Mode 11 – 8261MHz – 7716MHz = 545MHz




Site : 03CH22-HY
Condition : 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : 80W:1000.000kHz VBW:3000.000kHz SwT:3.000sec
Detector : 5N0813
SN : Peak
Antenna : 5B111FDDW000M
Modulation : BPRF
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes): 20
Sweep point(pts) : 1001

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	7716.00	65.83	-----	-----	49.71	36.97	14.62	36.49	1.02	0.00	--	--	Peak
2	8257.00	75.93	-----	-----	59.85	37.09	15.11	37.21	1.09	0.00	--	--	Peak
3	8261.00	63.75	-----	-----	47.68	37.08	15.11	37.21	1.09	0.00	--	--	Peak



UWB Bandwidth
Patch Antenna Channel 9
Mode 12 – 8260MHz – 7714MHz = 546MHz



	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	Loss	Factor	Factor	Factor	cm	deg	
1	7714.00	61.14	-----	-----	-----	45.03	36.97	14.61	36.49	1.02	0.00	--	--	Peak
2	8018.00	72.05	-----	-----	-----	55.78	37.10	15.05	36.94	1.06	0.00	--	--	Peak
3	8260.00	59.63	-----	-----	-----	43.56	37.08	15.11	37.21	1.09	0.00	--	--	Peak

3.3 Technical requirements for hand held UWB systems

3.3.1 Technical Requirements for transmission Limit

FCC 15.519(a) (1) A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgment of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting.

3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedure

Follow the test step as below:


1. Turn on both EUT and companion receiver.
2. Set the EUT to TX mode, and EUT starts polling.
3. Set the companion receiver to associate EUT and EUT starts to transmit.
4. Disable the RX function of the companion receiver to disassociate the EUT.
5. Check if EUT stop transmitting once step 4 is made.

3.3.4 Test Setup






3.3.5 Test Result



M1 to M2: Set the EUT to TX mode, and EUT starts polling.

M2 to M3: Set the companion receiver to associate EUT and EUT starts to transmit.

M3: Disable the TX function of EUT. EUT stops transmitting and polling.



M1 to M2: Set the EUT to TX mode, and EUT starts polling.

M2 to M3: Set the companion receiver to associate EUT and EUT starts to transmit.

M3: RX function of the companion receiver is disabled. EUT disassociates the companion receiver and stops transmitting, but continues polling.



Plot 3 is zoom in plot of M2 to M3 (polling and transmission)

Plot 4 is zoom in plot after M3 (polling only)

3.4 Peak Power Measurement

3.4.1 Peak Power Measurement Limit

Peak Power Measurement Limit
$P_{eirr} = 0 \text{ dBm/50MHz}$


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
- Peak Power Measurement - Refer as ANSI C63.10, clause 10.3.1 for radiated measurement procedure testing. - Refer as ANSI C63.10, clause 10.3.2 for measurement distance is 3m. - Refer as ANSI C63.10, clause 10.3.5 for peak detector procedure testing. - Refer as ANSI C63.10, clause 10.3.6 for bandwidth conversion of peak power. - Frequency of max peak power is pre-located: The span bandwidth is continuously reduced to find the worst frequency. Once the worst frequency is found, the setting of spectrum analyzer is set as below: - Central frequency: Worst frequency point - Span: Zero span - RBW: 50MHz - VBW: 80MHz - Detector: Peak detector - Trace: Max hold

3.4.4 Test Setup




3.4.5 Test Result of Peak Power Measurement

Peak Measurement Result							
Test Mode	Freq. (MHz)	E-Field (dBuV/m)	EIRP _{50MHz} (dBm)	EIRP _{50MHz} Limit (dBm)	Margin (dB)	Result	Pol [H/V]
1	7987	94.46	-0.77	0	-0.77	Pass	H
2	6492	93.93	-1.30	0	-1.30	Pass	H
3	7996	91.32	-3.91	0	-3.91	Pass	H
4	7995	94.84	-0.39	0	-0.39	Pass	H
5	7989	93.32	-1.91	0	-1.91	Pass	V
6	6482	93.58	-1.65	0	-1.65	Pass	H
7	7987	91.60	-3.63	0	-3.63	Pass	V
8	7992	93.51	-1.72	0	-1.72	Pass	H
9	7923	87.14	-8.09	0	-8.09	Pass	V
10	6489	87.31	-7.92	0	-7.92	Pass	H
11	8175	87.62	-7.61	0	-7.61	Pass	H
12	7985	88.10	-7.13	0	-7.13	Pass	H
13	7993	84.77	-10.46	0	-10.46	Pass	V
14	6489	85.30	-9.93	0	-9.93	Pass	H
15	8259	85.29	-9.94	0	-9.94	Pass	H
16	7924	88.34	-6.89	0	-6.89	Pass	H
17	7957	87.11	-8.12	0	-8.12	Pass	H
18	6491	88.05	-7.18	0	-7.18	Pass	H
19	8205	86.84	-8.39	0	-8.39	Pass	H
20	7987	88.87	-6.36	0	-6.36	Pass	H
21	7928	82.39	-12.84	0	-12.84	Pass	V
22	6553	83.27	-11.96	0	-11.96	Pass	H
23	8260	85.49	-9.74	0	-9.74	Pass	H
24	7926	83.39	-11.84	0	-11.84	Pass	H
25	7987	86.38	-8.85	0	-8.85	Pass	V
26	6489	87.16	-8.07	0	-8.07	Pass	H
27	8176	86.72	-8.51	0	-8.51	Pass	V
28	7988	87.66	-7.57	0	-7.57	Pass	V
Note 1: EIRP [dBm] = E-Field [dBuV/m] - 95.23; Note 2: Measurement worst emissions of receive antenna polarization.							



Peak Power Measurement Plots
Antenna 3 Channel 9


Mode 1 – Peak Power 94.46 – 95.23 = -0.77 dBm/50MHz





Peak Power Measurement Plots
Antenna 5 Channel 5


Mode 2 – Peak Power 93.93 – 95.23 = -1.30 dBm/50MHz





Peak Power Measurement Plots
Antenna 5 Channel 9


Mode 3 – Peak Power 91.32 – 95.23 = -3.91 dBm/50MHz





Peak Power Measurement Plots
Patch Antenna Channel 9

Mode 4 – Peak Power 94.84 – 95.23 = -0.39 dBm/50MHz



Site : 03CH22-HY
Condition : PEAK_POWER 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : 5N0813
Detector : Peak
SM : 58111FDDW000M
Antenna : Patch
Modulation : BPRF
Channel : CH9
Test Case Number : Case 1
Payload Length (bytes): 125

Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1 7995.00	94.84	95.23	-0.39	78.55	37.10	15.04	36.91	1.06	0.00	--	--	Peak

3.5 Radiated Emissions

3.5.1 Radiated Emissions Limit

Radiated Emissions below 960MHz and Emissions from Digital Circuitry Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Radiated Emissions above 960MHz Limit	
Frequency Range (MHz)	EIRP (dBm), RBW = 1MHz
960-1610	-75.3
1610-1990	-63.3
1990-3100	-61.3
3100-10600	-41.3
Above 10600	-61.3

Note: Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)

Radiated Emissions in GPS Bands Limit	
Frequency Range (MHz)	EIRP (dBm), RBW ≥ 1kHz
1164-1240	-85.3
1559-1610	-85.3

Note E (dBuV/m) = EIRP (dBm) + 95.23, example, E(dBuV/m) = -85.3 + 95.23 = 9.93dBuV/m

3.5.2 Measuring Instruments




Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures


Test Method for Radiated Emissions above 960MHz	
■ Radiated Emissions above 960MHz	
■	Refer as ANSI C63.10, clause 10.3.1 for radiated measurement procedure testing.
■	Refer as ANSI C63.10, clause 10.3.2 for measurement distance is 3m. In some cases, it may be necessary to measure the radiated UWB emissions at a closer distance to obtain enough signal and margin to overcome the measurement system noise floor. Distance extrapolation factor = $20 \log(\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
■	Refer as ANSI C63.10, clause 10.3.4 for rms detector procedure testing.
■	Refer as ANSI C63.10, clause 10.3.7 for evaluating AVG-PSD (RBW=1MHz).
■	Refer as ANSI C63.10, clause 10.3.10 for evaluating AVG-PSD in GPS Band (RBW $\geq$ 1kHz).
■ For radiated measurement.	
■	Refer as ANSI C63.10, clause 10.3.8 following eirp can be used radiated test configuration.
■	Refer as ANSI C63.10, clause 10.3.9 following eirp can be directly determined using the field strength.

Test Method for Radiated Emissions below 960MHz and Emissions from Digital Circuitry	
■ Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements) for above 30MHz-960MHz; 40dB/decade for frequency below 30MHz.	
■ For the transmitter unwanted emissions shall be measured using following options below:	
■	Refer as ANSI C63.10, clause 4.1.4 Detector functions and selection of bandwidth
☐	Refer as ANSI C63.10, clause 4.1.4.2.4 average value of pulsed emissions. Adjusted by a "duty cycle correction factor", derived from $20 \log(\text{dwell time}/100 \text{ ms})$. Average emission = peak emission + $20 \log(\text{duty cycle})$.
■	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
■ For radiated measurement.	
■	Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
■	Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
■	Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.
■	If the noise floor can't meet the limit, the test distance will be shorten and described in the report.
■ Any unwanted emissions level shall not exceed the fundamental emission level.	


3.5.4 Test Setup





Radiated Emissions from 1GHz to 1.61 GHz



Radiated Emissions from 1.61 GHz to 10.60 GHz



Radiated Emissions from 10.60 GHz to 18GHz

Radiated Emissions above 18GHz


Note 1: Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna and the frequency range of 1 GHz to 40 GHz using a calibrated horn antenna.

Note 2: If test distance other than 3m is used, the used test distance will be recorded in test result.

3.5.5 Radiated Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.


3.5.6 Average Power Spectral Density

Test mode	Frequency (MHz)	Emission Level (dBuV/m)	Emission Limit (dBm/MHz)	Emission Limit (dBuV/m)	Margin (dB)	Result	Pol [H/V]
1	7957	53.72	-41.3	53.93	-0.21	Pass	H
2	6522	53.77	-41.3	53.93	-0.16	Pass	H
3	8144	53.41	-41.3	53.93	-0.52	Pass	H
4	8019	53.82	-41.3	53.93	-0.11	Pass	H
5	7957	53.55	-41.3	53.93	-0.38	Pass	V
6	6522	53.83	-41.3	53.93	-0.10	Pass	H
7	8144	53.77	-41.3	53.93	-0.16	Pass	V
8	8019	53.69	-41.3	53.93	-0.24	Pass	H
9	7933	53.20	-41.3	53.93	-0.73	Pass	V
10	6524	53.58	-41.3	53.93	-0.35	Pass	H
11	8155	53.80	-41.3	53.93	-0.13	Pass	H
12	8022	53.87	-41.3	53.93	-0.06	Pass	H
13	7939	53.77	-41.3	53.93	-0.16	Pass	V
14	6491	53.76	-41.3	53.93	-0.17	Pass	H
15	8156	53.79	-41.3	53.93	-0.14	Pass	H
16	8003	53.36	-41.3	53.93	-0.57	Pass	H
17	7943	53.74	-41.3	53.93	-0.19	Pass	H
18	6491	53.74	-41.3	53.93	-0.19	Pass	H
19	8154	53.86	-41.3	53.93	-0.07	Pass	H
20	7988	53.75	-41.3	53.93	-0.18	Pass	H
21	7939	53.56	-41.3	53.93	-0.37	Pass	V
22	6519	53.80	-41.3	53.93	-0.13	Pass	H
23	8162	53.67	-41.3	53.93	-0.26	Pass	H
24	8002	53.59	-41.3	53.93	-0.34	Pass	H
25	7947	53.63	-41.3	53.93	-0.30	Pass	V
26	6511	53.79	-41.3	53.93	-0.14	Pass	H
27	8154	53.78	-41.3	53.93	-0.15	Pass	V
28	7947	53.75	-41.3	53.93	-0.18	Pass	H



Average Power Spectral Density Plots
Antenna 5 Channel 5

Mode 6 – Emission Level 53.83 dBuV/m




Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : RBW:1000.000kHz VBW:3000.000kHz SWT:1.000sec
Detector : SN0813
SN : Average
Antenna : 5B111FDDW000M
Modulation : 5
Channel : BPRF
Test Case Number : CH5
Payload Length (bytes) : Case 2
Sweep point(pts) : 125
Sweep point(pts) : 1001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	6522.00	53.83	53.93	-0.10		38.53	36.04	13.43	35.16	0.99	0.00	--	--	Average

Average Power Spectral Density Plots
Patch Antenna Channel 9

Mode 12 – Emission Level 53.87 dBuV/m




Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : RBW:1000.000kHz VBW:3000.000kHz SWT:1.000sec
Detector : SN0813
SN : Average
Antenna : Patch5B111FDDW000M
Modulation : 5
Channel : BPRF
Test Case Number : CH9
Payload Length (bytes) : Case 3
Sweep point(pts) : 20
Sweep point(pts) : 1001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	8022.00	53.87	53.93	-0.06		37.60	37.10	15.05	36.94	1.06	0.00	--	--	Average



Average Power Spectral Density Plots
Antenna 3 Channel 9

Mode 13 – Emission Level 53.77 dBuV/m




Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : RBW:1000.000kHz VBW:3000.000kHz SWT:1.000sec
Detector : SN0813
SN : Average
Antenna : 5B111FDDW000M
Modulation : 3L
Channel : HPRF
Test Case Number : CH9
Payload Length (bytes) : Case 4
Sweep point(pts) : 150
Sweep point(pts) : 1001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	7939.00	53.77	53.93	-0.16		37.69	37.10	14.93	36.83	0.00	0.88	--	--	Average

Average Power Spectral Density Plots
Antenna 5 Channel 9


Mode 19 Emission Level 53.93 dBuV/m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : RBW:1000.000kHz VBW:3000.000kHz SWT:1.000sec
Detector : SN0813
SN : Average
Antenna : 5B111FDDW000M
Modulation : 5
Channel : HPRF
Test Case Number : CH9
Payload Length (bytes) : Case 5
Sweep point(pts) : 150
Sweep point(pts) : 1001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	8154.00	53.86	53.93	-0.07		37.63	37.20	15.04	37.09	1.08	0.00	--	--	Average


3.5.7 Radiated Emissions (30MHz – 1GHz)





Antenna 5 CH05 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 6	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
Condition : QP 3m Bilog_55606 & 08_251126 VERTICAL
Mode : 6
Project : 5N0813
Detector : Peak
SW : 5B111FDDW000M
Antenna : 5
Modulation : BPRF
Channel : CH5
Test Case Number : Case 2
Payload Length (bytes) : 125
300-3000MHz : ponit:1001 SWT:1.0sec
300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	Factor	dB	deg	
1	41.64	33.70	40.00	-6.30	49.80	18.49	1.08	35.79	0.12	0.00	--	--	Peak
2	206.54	30.37	43.50	-13.13	48.19	15.13	2.49	35.50	0.06	0.00	--	--	Peak
3	271.53	28.21	46.00	-17.79	41.78	18.83	2.86	35.35	0.09	0.00	--	--	Peak
4	511.12	29.76	46.00	-16.24	36.34	24.12	3.94	34.73	0.09	0.00	--	--	Peak
5	819.58	31.69	46.00	-14.31	32.28	27.90	5.00	33.65	0.16	0.00	--	--	Peak
6	956.35	34.32	46.00	-11.68	30.87	30.88	5.42	33.16	0.31	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Patch Antenna CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 12	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 HORIZONTAL
 Mode : 12
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes) : 20
 30-300MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	30.97	24.04	40.00	-15.96	34.81	23.98	0.92	35.81	0.14	0.00	--	--	Peak
2	207.51	34.43	43.50	-9.07	52.21	15.16	2.49	35.49	0.06	0.00	--	--	Peak
3	267.65	32.70	46.00	-13.30	45.78	19.35	2.84	35.36	0.09	0.00	--	--	Peak
4	278.32	32.19	46.00	-13.81	45.77	18.77	2.90	35.34	0.09	0.00	--	--	Peak
5	746.83	32.01	46.00	-13.99	32.88	28.05	4.79	33.92	0.21	0.00	--	--	Peak
6	950.53	34.91	46.00	-11.09	31.74	30.65	5.40	33.18	0.30	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Patch Antenna CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 12	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 VERTICAL
 Mode : 12
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes) : 20
 30-300MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	35.82	33.54	40.00	-6.46	46.65	21.59	0.99	35.80	0.11	0.00	--	--	Peak
2	205.57	31.34	43.50	-12.16	49.18	15.12	2.48	35.50	0.06	0.00	--	--	Peak
3	269.59	27.83	46.00	-18.17	41.22	19.03	2.85	35.36	0.09	0.00	--	--	Peak
4	497.54	29.97	46.00	-16.03	36.85	23.93	3.88	34.78	0.09	0.00	--	--	Peak
5	776.90	31.41	46.00	-14.59	32.04	28.14	4.86	33.82	0.19	0.00	--	--	Peak
6	957.32	35.04	46.00	-10.96	31.59	30.87	5.42	33.15	0.31	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Antenna 3 CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 13	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 HORIZONTAL
 Mode : 13
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes) : 150
 30-300MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	31.94	23.52	40.00	-16.48	34.96	23.31	0.93	35.81	0.13	0.00	--	--	Peak
2	207.51	34.78	43.50	-8.72	52.56	15.16	2.49	35.49	0.06	0.00	--	--	Peak
3	268.62	32.39	46.00	-13.61	45.63	19.18	2.85	35.36	0.09	0.00	--	--	Peak
4	274.44	32.16	46.00	-13.84	45.82	18.72	2.88	35.35	0.09	0.00	--	--	Peak
5	812.79	31.45	46.00	-14.55	32.24	27.77	4.97	33.69	0.16	0.00	--	--	Peak
6	956.35	34.40	46.00	-11.60	30.95	30.88	5.42	33.16	0.31	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Antenna 3 CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 13	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 VERTICAL
 Mode : 13
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes) : 150
 300-3000MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	42.61	33.40	40.00	-6.60	50.08	17.89	1.09	35.78	0.12	0.00	--	--	Peak
2	205.57	31.52	43.50	-11.98	49.36	15.12	2.48	35.50	0.06	0.00	--	--	Peak
3	269.59	27.23	46.00	-18.77	40.62	19.03	2.85	35.36	0.09	0.00	--	--	Peak
4	499.48	29.41	46.00	-16.59	36.25	23.95	3.89	34.77	0.09	0.00	--	--	Peak
5	776.84	31.48	46.00	-14.52	32.13	28.11	4.87	33.82	0.19	0.00	--	--	Peak
6	957.32	35.43	46.00	-10.57	31.98	30.87	5.42	33.15	0.31	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Antenna 5 CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 19	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 HORIZONTAL
 Mode : 19
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : 5
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 5
 Payload Length (bytes) : 150
 300-3000MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	32.91	23.56	40.00	-16.44	34.90	23.38	0.95	35.80	0.13	0.00	--	--	Peak
2	208.48	35.32	43.50	-8.18	53.07	15.18	2.50	35.49	0.06	0.00	--	--	Peak
3	267.65	32.28	46.00	-13.72	45.36	19.35	2.84	35.36	0.09	0.00	--	--	Peak
4	274.44	32.54	46.00	-13.46	46.20	18.72	2.88	35.35	0.09	0.00	--	--	Peak
5	731.31	32.28	46.00	-13.72	33.63	27.68	4.74	33.98	0.21	0.00	--	--	Peak
6	945.68	34.37	46.00	-11.63	31.53	30.36	5.39	33.20	0.29	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

Antenna 5 CH09 Radiated Emissions (30MHz – 1GHz)

Test Mode	Mode 19	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH20-HY
 Condition : QP 3m Bilog_55606 & 08_251126 VERTICAL
 Mode : 19
 Project : 5N0813
 Detector : Peak
 SW : 5B111FDDW000M
 Antenna : 5
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 5
 Payload Length (bytes) : 150
 30-300MHz : ponit:1001 SWT:1.0sec
 300-1000MHz : ponit:1001 SWT:1.0sec


	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	Factor	dB	deg	
1	46.49	33.44	40.00	-6.56	52.03	15.91	1.13	35.77	0.14	0.00	--	--	Peak
2	206.54	32.13	43.50	-11.37	49.95	15.13	2.49	35.50	0.06	0.00	--	--	Peak
3	270.56	27.48	46.00	-18.52	40.96	18.92	2.86	35.35	0.09	0.00	--	--	Peak
4	498.51	29.86	46.00	-16.14	36.71	23.95	3.88	34.77	0.09	0.00	--	--	Peak
5	731.31	34.25	46.00	-11.75	35.60	27.68	4.74	33.98	0.21	0.00	--	--	Peak
6	956.35	34.57	46.00	-11.43	31.12	30.88	5.42	33.16	0.31	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Peak emission setting: RBW=120kHz; VBW = 300kHz.

3.5.8 Radiated Emissions (960MHz – 18GHz)

Antenna 5 CH05 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 6				Polarization				H				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : 5N0813
Detector : Average
SN : 5B111FDDW000M
Antenna : 5
Modulation : BPRF
Channel : CH5
Test Case Number : Case 2
Payload Length (bytes) : 125
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-4750MHz : ponit:4001 SWT:4.0sec
4750-10600MHz : ponit:6001 SWT:6.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	Level	Factor	Loss	Factor	Factor	Factor	cm	deg	
1	966.16	14.86	19.93	-5.07	25.02	31.10	5.10	31.05	0.25	-15.56	--	--	Average
2	1410.53	14.77	19.93	-5.16	25.55	24.59	6.13	31.96	-9.54	0.00	--	--	Average
3	1936.80	26.73	31.93	-5.20	26.10	25.63	7.27	32.27	0.00	0.00	--	--	Average
4	3010.09	28.23	33.93	-5.70	23.61	28.34	8.95	32.67	0.00	0.00	--	--	Average
5	6460.00	53.84	53.93	-0.09	39.56	36.00	13.39	35.11	0.00	0.00	--	--	Average
6	14499.80	28.24	33.93	-5.69	24.69	42.40	20.16	43.45	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.


Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)
Example:
Corrected Reading: 42.40 (dB/m) + 20.16 (dB) + 24.69 (dBuV) – 43.45 (dB) + (-15.56) (dB) = 28.24 (dBuV/m)

Antenna 5 CH05 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 6				Polarization				V				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Vertical
Project : SN0813
Detector : Average
SN : 5B111FDDW000M
Antenna : 5
Modulation : BPRF
Channel : CH5
Test Case Number : Case 2
Payload Length (bytes) : 125
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-4750MHz : ponit:4001 SWT:4.0sec
4750-10600MHz : ponit:6001 SWT:6.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	966.20	14.88	19.93	-5.05	25.04	31.10	5.10	31.05	0.25	-15.56	--	--	Average
2	1411.75	14.89	19.93	-5.04	25.67	24.58	6.14	31.96	-9.54	0.00	--	--	Average
3	1940.98	25.47	31.93	-6.46	24.87	25.60	7.28	32.28	0.00	0.00	--	--	Average
4	3013.42	28.30	33.93	-5.63	23.71	28.32	8.95	32.68	0.00	0.00	--	--	Average
5	6527.50	47.25	53.93	-6.68	32.92	36.06	13.44	35.17	0.00	0.00	--	--	Average
6	14485.00	28.09	33.93	-5.84	24.59	42.34	20.14	43.42	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.


Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

Patch Antenna CH09 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 12				Polarization				H				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : Patch
Modulation : BPRF
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes) : 20
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	Loss	Factor	Factor	Factor	cm	deg	
1	964.88	14.84	19.93	-5.09		25.03	31.09	5.10	31.06	0.24	-15.56	--	--	Average
2	1408.70	15.31	19.93	-4.62		26.09	24.59	6.13	31.96	-9.54	0.00	--	--	Average
3	1944.78	25.94	31.93	-5.99		25.33	25.60	7.29	32.28	0.00	0.00	--	--	Average
4	3012.31	28.72	33.93	-5.21		24.12	28.33	8.95	32.68	0.00	0.00	--	--	Average
5	7952.50	53.84	53.93	-0.09		38.63	37.10	14.96	36.85	0.00	0.00	--	--	Average
6	14514.60	28.59	33.93	-5.34		25.04	42.40	20.17	43.46	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)


Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)

Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)

(Note: For test item below 1GHz, Aux = Filter loss)

(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

Patch Antenna CH09 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 12				Polarization				V				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 VERTICAL
Project : 5N0813
Detector : Average
SN : 5B111FDDW000M
Antenna : Patch
Modulation : BPRF
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes): 20
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	966.16	14.81	19.93	-5.12	24.97	31.10	5.10	31.05	0.25	-15.56	--	--	--	Average
2	1406.87	15.30	19.93	-4.63	26.10	24.57	6.13	31.96	-9.54	0.00	--	--	--	Average
3	1937.18	25.96	31.93	-5.97	25.33	25.63	7.27	32.27	0.00	0.00	--	--	--	Average
4	3015.64	28.75	33.93	-5.18	24.17	28.31	8.95	32.68	0.00	0.00	--	--	--	Average
5	7960.00	52.46	53.93	-1.47	37.25	37.10	14.97	36.86	0.00	0.00	--	--	--	Average
6	14699.60	28.56	33.93	-5.37	24.98	42.50	20.29	43.65	-15.56	0.00	--	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.


Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

Antenna 3 CH09 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 13				Polarization				H				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 3L
Modulation : HPRF
Channel : CH9
Test Case Number : Case 4
Payload Length (bytes) : 150
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	Factor	cm	deg	
1	964.48	14.81	19.93	-5.12	25.02	31.08	5.10	31.07	0.24	-15.56	--	--	Average
2	1409.31	15.39	19.93	-4.54	26.17	24.59	6.13	31.96	-9.54	0.00	--	--	Average
3	1934.14	25.99	31.93	-5.94	25.33	25.66	7.27	32.27	0.00	0.00	--	--	Average
4	3007.87	28.76	33.93	-5.17	24.14	28.35	8.94	32.67	0.00	0.00	--	--	Average
5	7952.50	53.79	53.93	-0.14	38.58	37.10	14.96	36.85	0.00	0.00	--	--	Average
6	14499.80	28.60	33.93	-5.33	25.05	42.40	20.16	43.45	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.


Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

Antenna 3 CH09 Radiated Emissions (960MHz – 18GHz)													
Test Mode	Mode 13				Polarization				V				
Operating Function	Adapter Mode												
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.												



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 3L
Modulation : HPRF
Channel : CH9
Test Case Number : Case 4
Payload Length (bytes) : 150
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	964.68	14.80	19.93	-5.13	25.01	31.08	5.10	31.07	0.24	-15.56	--	--	Average
2	1407.48	15.37	19.93	-4.56	26.17	24.57	6.13	31.96	-9.54	0.00	--	--	Average
3	1760.86	26.65	31.93	-5.28	27.09	24.80	6.91	32.15	0.00	0.00	--	--	Average
4	3015.64	28.77	33.93	-5.16	24.19	28.31	8.95	32.68	0.00	0.00	--	--	Average
5	7967.50	52.73	53.93	-1.20	37.51	37.10	14.99	36.87	0.00	0.00	--	--	Average
6	14810.60	28.65	33.93	-5.28	25.24	42.38	20.36	43.77	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.


Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.

Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

Antenna 5 CH09 Radiated Emissions (960MHz – 18GHz)														
Test Mode	Mode 19				Polarization				H					
Operating Function	Adapter Mode													
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.													



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : 5N0813
Detector : Average
SN : 5B111FDDW000M
Antenna : 5
Modulation : HPRF
Channel : CH9
Test Case Number : Case 5
Payload Length (bytes) : 150
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	965.32	14.82	19.93	-5.11	24.99	31.10	5.10	31.06	0.25	-15.56	--	--	--	Average
2	1403.82	15.28	19.93	-4.65	26.12	24.54	6.12	31.96	-9.54	0.00	--	--	--	Average
3	1954.66	25.89	31.93	-6.04	25.18	25.69	7.31	32.29	0.00	0.00	--	--	--	Average
4	3015.64	28.73	33.93	-5.20	24.15	28.31	8.95	32.68	0.00	0.00	--	--	--	Average
5	8170.00	53.86	53.93	-0.07	38.73	37.20	15.04	37.11	0.00	0.00	--	--	--	Average
6	14499.80	28.62	33.93	-5.31	25.07	42.40	20.16	43.45	-15.56	0.00	--	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.


Note 5:

- Distance extrapolation factor = 20 log (test distance [X m]/specific distance [3 m]) (dB)
Example: Distance extrapolation factor = 20log (0.5m/3m) = -15.56 (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)



Antenna 5 CH09 Radiated Emissions (960MHz – 18GHz)

Test Mode	Mode 19	Polarization	V
Operating Function	Adapter Mode		
Test Distance	The test distance between the receiving antenna and the EUT is as following: 3m for 1.61 GHz ~ 10.60 GHz frequency range, 1 m for 1GHz ~ 1.61 GHz, and 0.5 m for other frequency ranges.		



Site : 03CH22-HY
Condition : FCC_UWB_HAND 3m DRH18-E_LE2C04A18EN_250520 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 5
Modulation : HPRF
Channel : CH9
Test Case Number : Case 5
Payload Length (bytes) : 150
960-1000MHz : ponit:1001 SWT:1.0sec
1000-1610MHz : ponit:1001 SWT:1.0sec
1610-1990MHz : ponit:1001 SWT:1.0sec
1990-3100MHz : ponit:2001 SWT:2.0sec
3100-10600MHz : ponit:18001 SWT:18.0sec
10600-18000MHz : ponit:18001 SWT:18.0sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	Loss	Factor	Factor	Factor	cm	deg	
1	965.40	14.80	19.93	-5.13	24.97	31.10	5.10	31.06	0.25	-15.56	--	--	Average
2	1409.31	14.80	19.93	-5.13	25.58	24.59	6.13	31.96	-9.54	0.00	--	--	Average
3	1937.94	25.44	31.93	-6.49	24.82	25.62	7.28	32.28	0.00	0.00	--	--	Average
4	3017.86	28.18	33.93	-5.75	23.61	28.29	8.96	32.68	0.00	0.00	--	--	Average
5	8155.00	52.85	53.93	-1.08	37.70	37.20	15.04	37.09	0.00	0.00	--	--	Average
6	14536.80	28.14	33.93	-5.79	24.61	42.40	20.18	43.49	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting outside GPS Bands: RBW=1MHz; VBW=3MHz.

Note 3: Average emission setting in GPS bands: RBW=1kHz; VBW=3kHz.

Note 4: #5 is fundamental signal.


Note 5:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux Factor (dB) = Level (dBuV/m)
(Note: For test item below 1GHz, Aux = Filter loss)
(Note: For test item above 1GHz, Aux = Distance extrapolation factor)

3.5.9 Radiated Emissions (1164MHz – 1240MHz)

Antenna 5 CH05 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 6	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : BPRF
 Channel : CH5
 Test Case Number : Case 2
 Payload Length (bytes) : 125
 Sweep point(pts) : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1200.40	-3.23	9.93	-13.16		-1.00	24.00	5.73	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: E (dBuV/m) = EIRP Limit (dBm) + 95.23. E(dBuV/m) = -85.3 + 95.23 = 9.93dBuV/m.

Antenna 5 CH05 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 6	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 : RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : BPRF
 Channel : CH5
 Test Case Number : Case 2
 Payload Length (bytes): 125
 Sweep point(pts) : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1207.85	-2.80	9.93	-12.73		-0.58	24.00	5.74	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Patch Antenna CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 12	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes) : 20
 Sweep point : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1210.66	-2.61	9.93	-12.54		-0.41	24.01	5.75	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Patch Antenna CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 12	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes): 20
 Sweep point : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1210.66	-2.61	9.93	-12.54		-0.41	24.01	5.75	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 13	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 : RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes): 150
 Sweep point : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1200.18	-2.05	9.93		-11.98	0.18	24.00	5.73	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 13	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes): 150
 Sweep point : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1218.87	-2.36	9.93		-12.29	-0.26	24.09	5.77	31.96	0.00	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.



Antenna 5 CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 19	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
Project : 5N0813
Detector : Peak
SN : 5B111FDDW000M
Antenna : 5
Modulation : HPRF
Channel : CH9
Test Case Number : Case 5
Payload Length (bytes): 150
Sweep point : 80001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1207.78	-2.76	9.93		-12.69	-0.54	24.00	5.74	31.96	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 5 CH09 Radiated Emissions (1164MHz – 1240MHz)

Test Mode	Mode 19	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 5
 Payload Length (bytes): 150
 Sweep point : 80001


	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1207.78	-2.58	9.93	-12.51		-0.36	24.00	5.74	31.96	0.00	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.


Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

3.5.10 Radiated Emissions (1559MHz – 1610MHz)



Patch Antenna CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 6	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : BPRF
 Channel : CH5
 Test Case Number : Case 2
 Payload Length (bytes): 125
 Sweep point(pts) : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1593.32	-2.03	9.93		-11.96	-1.08	24.50	6.58	32.03	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 12	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes): 20
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1601.74	-1.75	9.93	-11.68		-0.82	24.50	6.60	32.03	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 12	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 : RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : Patch
 Modulation : BPRF
 Channel : CH9
 Test Case Number : Case 3
 Payload Length (bytes): 20
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1599.90	-1.87	9.93	-11.80		-0.94	24.50	6.60	32.03	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 13	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes): 150
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1569.20	-1.80	9.93		-11.73	-0.70	24.39	6.52	32.01	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 3 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 13	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 3L
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 4
 Payload Length (bytes): 150
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1566.14	-1.64	9.93		-11.57	-0.50	24.36	6.51	32.01	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

Antenna 5 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 19	Polarization	H
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Horizontal
 Project : 5N0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 5
 Payload Length (bytes): 150
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	0.00	-1.50	9.93		-11.43	-0.57	24.50	6.60	32.03	0.00	0.00	--	--	Peak


Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: E (dBuV/m) = EIRP Limit (dBm) + 95.23. E(dBuV/m) = -85.3 + 95.23 = 9.93dBuV/m.

Antenna 5 CH09 Radiated Emissions (1559MHz – 1610MHz)

Test Mode	Mode 19	Polarization	V
Operating Function	Adapter Mode	Test Distance	3m



Site : 03CH22-HY
 Condition : UWB_GPS 3m DRH18-E_LE2C04A18EN_250520 Vertical
 : RBW:1.000kHz VBW:3.000kHz SWT:40.000sec
 Project : SN0813
 Detector : Peak
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : HPRF
 Channel : CH9
 Test Case Number : Case 5
 Payload Length (bytes): 150
 Sweep point : 51001

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	1581.08	-1.88	9.93		-11.81	-0.82	24.41	6.55	32.02	0.00	0.00	--	--	Peak

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)


Note 2: Average emission setting: RBW=1kHz; VBW=3kHz.

Note 3: $E \text{ (dBuV/m)} = \text{EIRP Limit (dBm)} + 95.23$. $E \text{ (dBuV/m)} = -85.3 + 95.23 = 9.93 \text{ dBuV/m}$.

3.5.11 Radiated Emissions (18GHz – 40GHz)

Antenna 5 CH05 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 6	Polarization	H
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
 Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 Horizontal
 Project : 5N0813
 Detector : Average
 SN : 5B111FDDW000M
 Antenna : 5
 Modulation : BPRF
 Channel : CH5
 Test Case Number : Case 2
 Payload Length (bytes) : 125
 18000-26000MHz : ponit:18001 SWT:18sec
 26000-40000MHz : ponit:18001 SWT:18sec

Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1 39468.00	32.44	33.93	-1.49	54.65	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Antenna 5 CH05 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 6	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 5
Modulation : BPRF
Channel : CH5
Test Case Number : Case 2
Payload Length (bytes) : 125
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.43	33.93	-1.50	54.64	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Patch Antenna CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 12	Polarization	H
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 Horizontal
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : Patch
Modulation : BPRF
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes) : 20
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.40	33.93	-1.53	54.61	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Patch Antenna CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 12	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : Patch
Modulation : BPRF
Channel : CH9
Test Case Number : Case 3
Payload Length (bytes) : 20
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.44	33.93	-1.49		54.65	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Antenna 3 CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 13	Polarization	H
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 Horizontal
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 3L
Modulation : HPRF
Channel : CH9
Test Case Number : Case 4
Payload Length (bytes) : 150
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.39	33.93		-1.54	54.60	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Antenna 3 CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 13	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 3L
Modulation : HPRF
Channel : CH9
Test Case Number : Case 4
Payload Length (bytes) : 150
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.51	33.93	-1.42		54.72	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Antenna 5 CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 19	Polarization	H
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 Horizontal
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 5
Modulation : HPRF
Channel : CH9
Test Case Number : Case 5
Payload Length (bytes) : 150
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.40	33.93	-1.53	54.61	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.


Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



Antenna 5 CH09 Radiated Emissions (18GHz – 40GHz)

Test Mode	Mode 19	Polarization	V
Operating Function	Adapter Mode	Test Distance	0.5m



Site : 03CH22-HY
Condition : FCC_UWB_HAND 1m BBHA9170_1225_250702 VERTICAL
Project : SN0813
Detector : Average
SN : SB111FDDW000M
Antenna : 5
Modulation : HPRF
Channel : CH9
Test Case Number : Case 5
Payload Length (bytes) : 150
18000-26000MHz : ponit:18001 SWT:18sec
26000-40000MHz : ponit:18001 SWT:18sec

	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	Aux2	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m		dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	
1	39468.00	32.48	33.93	-1.45		54.69	46.13	9.22	62.00	-15.56	0.00	--	--	Average

Note 1: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 2: Average emission setting: RBW=1MHz; VBW=3MHz.

Note 3:

- Distance extrapolation factor = $20 \log (\text{test distance [X m]}/\text{specific distance [3 m]})$ (dB)
Example: Distance extrapolation factor = $20 \log (0.5\text{m}/3\text{m}) = -15.56$ (dB)
- Corrected Reading: Antenna Factor (dB/m) + Cable Loss (dB) + Read Level (dBuV) - Preamp Factor (dB) + Aux (dB) = Level (dBuV/m)
(Note: Aux = Distance extrapolation factor)



4 Test Equipment and Calibration Data

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9kHz~30MHz	Dec. 11, 2025	Dec. 12, 2025~ Dec. 31, 2025	Dec. 10, 2026	Radiation (03CH22-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Nov. 26, 2025	Dec. 12, 2025~ Dec. 31, 2025	Nov. 25, 2026	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 13, 2025	Dec. 12, 2025~ Dec. 31, 2025	Jul. 12, 2026	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18EN	1GHz~18GHz	May. 20, 2025	Dec. 12, 2025~ Dec. 31, 2025	May. 19, 2026	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1225	18GHz~40GHz	Jul. 02, 2025	Dec. 12, 2025~ Dec. 31, 2025	Jul. 01, 2026	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 26, 2025	Dec. 12, 2025~ Dec. 31, 2025	Sep. 25, 2026	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060871	18~40GHz	Dec. 02, 2025	Dec. 12, 2025~ Dec. 31, 2025	Dec. 01, 2026	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 22, 2025	Dec. 12, 2025~ Dec. 31, 2025	Sep. 21, 2026	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP201998	N/A	Nov. 06, 2025	Dec. 12, 2025~ Dec. 31, 2025	Nov. 05, 2026	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Dec. 12, 2025~ Dec. 31, 2025	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Dec. 12, 2025~ Dec. 31, 2025	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Dec. 12, 2025~ Dec. 31, 2025	N/A	Radiation (03CH22-HY)
Software	Audix	E3 6.09824_2019122	RK-002347	N/A	N/A	Dec. 12, 2025~ Dec. 31, 2025	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Dec. 12, 2025~ Dec. 31, 2025	Mar. 04, 2026	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,804611/2,804615/2	N/A	May. 19, 2025	Dec. 12, 2025~ Dec. 31, 2025	May. 18, 2026	Radiation (03CH22-HY)
Spectrum Analyzer	Rohde & Schwarz	FSW43	101456	RBW 50MHz	Feb. 20, 2025	Dec. 12, 2025~ Dec. 31, 2025	Fed. 19, 2026	Radiation (03CH22-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 16, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Oct. 15, 2026	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Dec. 10, 2026	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar. 09, 2026 ~ Mar. 09, 2026	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 09, 2026 ~ Mar. 09, 2026	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 09, 2026 ~ Mar. 09, 2026	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	10Hz~44GHz	Dec. 10, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Dec. 09, 2026	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N-06	47020 & 06	30MHz~1GHz	Oct. 04, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Oct. 03, 2026	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz~1000MHz	Dec. 30, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Dec. 29, 2026	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,804015/2,804027/2	N/A	Jan. 15, 2026	Mar. 09, 2026 ~ Mar. 09, 2026	Jan. 14, 2027	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP211382	N/A	Mar. 31, 2025	Mar. 09, 2026 ~ Mar. 09, 2026	Mar. 30, 2026	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Mar. 09, 2026 ~ Mar. 09, 2026	N/A	Radiation (03CH20-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Feb. 9, 2026	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Feb. 9, 2026	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2025	Feb. 9, 2026	Oct. 19, 2026	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 3, 2025	Feb. 9, 2026	Mar. 2, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Feb. 9, 2026	Mar. 23, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Oct. 21, 2025	Feb. 9, 2026	Oct. 20, 2026	Conduction (CO07-HY)




Appendix A. AC Conducted Emission Test Results

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	25.70	56.00	30.30	L1	ON	20.2
0.150000	46.34	---	66.00	19.66	L1	ON	20.2
0.170250	---	30.77	54.95	24.18	L1	ON	20.1
0.170250	45.69	---	64.95	19.26	L1	ON	20.1
0.192750	---	18.94	53.92	34.98	L1	ON	20.1
0.192750	33.45	---	63.92	30.47	L1	ON	20.1
0.201750	---	17.56	53.54	35.98	L1	ON	20.1
0.201750	32.25	---	63.54	31.29	L1	ON	20.1
0.667500	---	12.96	46.00	33.04	L1	ON	20.0
0.667500	20.84	---	56.00	35.16	L1	ON	20.0
15.148500	---	23.18	50.00	26.82	L1	ON	20.6
15.148500	27.87	---	60.00	32.13	L1	ON	20.6

EUT Information

Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.12	55.88	27.76	N	ON	20.1
0.152250	44.66	---	65.88	21.22	N	ON	20.1
0.161250	---	32.27	55.40	23.13	N	ON	20.1
0.161250	47.07	---	65.40	18.33	N	ON	20.1
0.215250	---	19.73	53.00	33.27	N	ON	20.1
0.215250	37.59	---	63.00	25.41	N	ON	20.1
0.656250	---	19.99	46.00	26.01	N	ON	20.0
0.656250	29.29	---	56.00	26.71	N	ON	20.0
0.730500	---	13.18	46.00	32.82	N	ON	20.0
0.730500	21.95	---	56.00	34.05	N	ON	20.0
14.811000	---	22.08	50.00	27.92	N	ON	20.6
14.811000	26.42	---	60.00	33.58	N	ON	20.6