FCC RADIO TEST REPORT

FCC ID	:	**A4RGD1YQ**
Equipment	:	**Phone**
Model Name	:	**GD1YQ**
Applicant	:	**Google LLC** **1600 Amphitheatre Parkway,** **Mountain View, California, 94043 USA**
Standard	:	**FCC Part 15 Subpart C §15.225**

The product was received on Apr. 16, 2020 and testing was started from May 05, 2020 and completed on Jul. 09, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Reviewed by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1. General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 5
1.3 Modification of EUT 5
1.4 Testing Location 6
1.5 Applicable Standards 6
2. Test Configuration of Equipment Under Test **7**
2.1 Descriptions of Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Table for Supporting Units 9
2.4 EUT Operation Test Setup 9
3. Test Results **10**
3.1 AC Power Line Conducted Emissions Measurement 10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement 12
3.3 Frequency Stability Measurement 13
3.4 Field Strength of Fundamental Emissions and Mask Measurement 14
3.5 Radiated Emissions Measurement 16
3.6 Antenna Requirements 19
4. List of Measuring Equipment **20**
5. Uncertainty of Evaluation **22**
Appendix A. Test Results of Conducted Emission Test
Appendix B. Test Results of Conducted Test Items
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
Appendix C. Test Results of Radiated Test Items
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)

History of this test report

Report No.	Version	Description	Issued Date
FR011718-01D	01	Initial issue of report	Jul. 14, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	Under limit 13.07 dB at 0.206MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 19.83 dBμV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	Under limit 1.63 dB at 40.800MHz
3.6	15.203	Antenna Requirements	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Celery Wei

1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Phone
Model Name	GD1YQ
FCC ID	A4RGD1YQ
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/ NFC/GNSS/WPC/WPT WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE

Remark: The above EUT's information was declared by manufacturer.

EUT Information List	
S/N	Performed Test Item
03311FDD40001W	Conducted Emission
06021FDD4000B2	Radiated Spurious Emission
03281FDD400020	RF Conducted Measurement

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency	13.553 ~ 13.567MHz
Channel Number	1
Antenna Type	Loop Antenna
Type of Modulation	ASK

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	**Sporton Site No.**		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	Louis Chung	Tom Lee	Jesse Wang and Stan Hsieh
Temperature	22~24℃	23~25℃	23.5~25.7℃
Relative Humidity	53~55%	42~50%	56~62%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The NFC test is performed with app “NXP” installed in the mobile phone. It can enable continuous transmission with type A/B/F/V tag respectively.

Pre-scanned tests, X, Y, Z, and Accessory (Adapter or Earphone) in three orthogonal panels to determine the final configuration (Z plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + WLAN Idle + Bluetooth Idle + NFC Read + USB cable (Charging from Adapter 2)
Remark: For Radiated Test Cases, the tests were performed with Adapter 2.	

2.2 Connection Diagram of Test System

<AC Conducted Emission Mode>



<Radiated Emission Mode with Adapter>



<Radiated Emission Mode with Earphone>



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Google	G1007/ G1008	A4RG1007	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
4.	NFC Card	N/A	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The RF test items, utility “NXP” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

For terminal test result, the testing follows FCC KDB 174176.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

Note:

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

(2) with dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc × 10^6 ppm and the limit is less than ±100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
   Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark:

1. There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.
2. According to C63.10 radiated Test, the EUT pre-scanned horizontal, vertical, and ground-parallel three polarization's, the worst case is horizontal & vertical polarization, test data of two mode was reported.

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	35419 & 03	30MHz~1GHz	Apr. 29, 2020	Jul. 08, 2020~ Jul. 09, 2020	Apr. 28, 2021	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Dec. 06, 2019	Jul. 08, 2020 ~ Jul. 09, 2020	Dec. 05, 2020	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY532900 53	20Hz~26.5GHz	May 21, 2020	Jul. 08, 2020 ~ Jul. 09, 2020	May 20, 2021	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Dec. 26, 2019	Jul. 08, 2020 ~ Jul. 09, 2020	Dec. 25, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz~1GHz	May 19, 2020	Jul. 08, 2020 ~ Jul. 09, 2020	May 18, 2021	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24971/ 4, MY28655/ 4	9kHz~30MHz	Feb. 25, 2020	Jul. 08, 2020 ~ Jul. 09, 2020	Feb. 24, 2021	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY28655/ 4, MY24971/ 4, MY15682/ 4	30MHz~1GHz	Feb. 25, 2020	Jul. 08, 2020 ~ Jul. 09, 2020	Feb. 24, 2021	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Jul. 08, 2020 ~ Jul. 09, 2020	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208 368	Control Ant Mast	N/A	Jul. 08, 2020 ~ Jul. 09, 2020	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jul. 08, 2020 ~ Jul. 09, 2020	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Jul. 08, 2020 ~ Jul. 09, 2020	N/A	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	N/A	N/A	N/A	Jul. 08, 2020 ~ Jul. 09, 2020	N/A	Radiation (03CH07-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 24, 2020~ Jun. 30, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jun. 24, 2020~ Jun. 30, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jun. 24, 2020~ Jun. 30, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jun. 24, 2020~ Jun. 30, 2020	Nov. 14, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jun. 24, 2020~ Jun. 30, 2020	Nov. 19, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 24, 2020~ Jun. 30, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jun. 24, 2020~ Jun. 30, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jun. 24, 2020~ Jun. 30, 2020	Jan. 01, 2021	Conduction (CO05-HY)
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Apr. 09, 2020	May 05, 2020	Apr. 08, 2021	Conducted (TH03-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 26, 2020	May 05, 2020	Mar. 25, 2021	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Sep. 04, 2019	May 05, 2020	Sep. 03, 2020	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Nov. 26, 2019	May 05, 2020	Nov. 25, 2020	Conducted (TH03-HY)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.6

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.6

Appendix A Test Results of Conducted Emission Test

Test Engineer :	Tom Lee	**Temperature :**	23~25℃
		Relative Humidity :	42~50%

EUT Information

Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.205980	---	40.30	53.37	13.07	L1	OFF	19.6
0.205980	50.27	---	63.37	13.10	L1	OFF	19.6
0.298500	---	28.78	50.28	21.50	L1	OFF	19.6
0.298500	38.42	---	60.28	21.86	L1	OFF	19.6
0.438090	---	30.58	47.10	16.52	L1	OFF	19.6
0.438090	40.37	---	57.10	16.73	L1	OFF	19.6
0.573000	---	27.63	46.00	18.37	L1	OFF	19.6
0.573000	34.96	---	56.00	21.04	L1	OFF	19.6
0.759750	---	26.55	46.00	19.45	L1	OFF	19.6
0.759750	34.32	---	56.00	21.68	L1	OFF	19.6
2.129550	---	25.22	46.00	20.78	L1	OFF	19.6
2.129550	33.39	---	56.00	22.61	L1	OFF	19.6
6.095400	---	26.27	50.00	23.73	L1	OFF	19.9
6.095400	33.10	---	60.00	26.90	L1	OFF	19.9
13.560000	---	57.43	50.00	-7.43	L1	OFF	20.2
13.560000	58.85	---	60.00	1.15	L1	OFF	20.2

EUT Information

Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.209670	---	38.74	53.22	14.48	N	OFF	19.5
0.209670	47.45	---	63.22	15.77	N	OFF	19.5
0.317670	---	29.82	49.77	19.95	N	OFF	19.5
0.317670	39.10	---	59.77	20.67	N	OFF	19.5
0.432420	---	30.55	47.21	16.66	N	OFF	19.5
0.432420	40.59	---	57.21	16.62	N	OFF	19.5
0.575250	---	26.68	46.00	19.32	N	OFF	19.5
0.575250	35.08	---	56.00	20.92	N	OFF	19.5
0.757140	---	27.40	46.00	18.60	N	OFF	19.5
0.757140	37.76	---	56.00	18.24	N	OFF	19.5
1.495500	---	24.85	46.00	21.15	N	OFF	19.6
1.495500	35.46	---	56.00	20.54	N	OFF	19.6
5.998650	---	25.96	50.00	24.04	N	OFF	19.7
5.998650	31.80	---	60.00	28.20	N	OFF	19.7
13.560000	---	59.55	50.00	-9.55	N	OFF	19.9
13.560000	60.52	---	60.00	-0.52	N	OFF	19.9

EUT Information

Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.25	50.00	24.75	L1	OFF	20.2
13.560000	26.67	---	60.00	33.33	L1	OFF	20.2

EUT Information

Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000	---	25.09	50.00	24.91	N	OFF	19.9
13.560000	26.56	---	60.00	33.44	N	OFF	19.9

Appendix B Test Results of Test Item

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
			
20dB Bandwidth (kHz)	2.640	**99% OccupiedBW(kHz)**	2.240
Frequency range (MHz)	**f_L > 13.553**	13.55862	**Test Result**
	f_H < 13.567	13.56126	**Complies**

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
120	13.559940	**-20**	**0**	13.560020
102	13.559940		**2**	13.560020
138	13.559940		**5**	13.560020
			10	13.560010
		-10	**0**	13.560040
			2	13.560040
			5	13.560040
			10	13.560040
		0	**0**	13.560040
			2	13.560040
			5	13.560040
			10	13.560040
		10	**0**	13.560020
			2	13.560020
			5	13.560020
			10	13.560020
		20	**0**	13.559940
			2	13.559940
			5	13.559900
			10	13.559910
		30	**0**	13.559960
			2	13.559960
			5	13.559960
			10	13.559960
		40	**0**	13.559940
			2	13.559920
			5	13.559920
			10	13.559550

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
		50	0	13.559910
			2	13.559900
			5	13.559900
			10	13.559900
Max.Deviation (MHz)	-0.000060	Max.Deviation (MHz)		-0.000450
Max.Deviation (ppm)	-4.4248	Max.Deviation (ppm)		-33.1858
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

Appendix C Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx with Adapter	Test Frequency (MHz)	13.56



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	19.83	40	-64.17	84	38.36	21.06	0.41	100	275	QP

Test Mode :	NFC Tx with Adapter	Test Frequency (MHz)	13.56



Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	16.34	40	-67.66	84	34.87	21.06	0.41	100	0	QP

Test Mode :	NFC Tx with Earphone	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(H)_100315 HORIZONTAL

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	19.76	40	-64.24	84	38.29	21.06	0.41	100	269	QP

Test Mode :	NFC Tx with Earphone	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP_ANT(V)_100315 VERTICAL

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
13.56	17.01	40	-66.99	84	35.54	21.06	0.41	100	0	QP

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx with Adapter	Polarization :	Horizontal



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(H)_100315 HORIZONTAL

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01318	-19.4	80	-64.61	45.21	41.78	18.7	0.12	-	-	Average
0.07503	-30.22	80	-60.32	30.1	30.62	19	0.16	-	-	Average
0.09378	-35.77	80	-63.93	28.16	25.56	18.5	0.17	-	-	QP
0.11092	-38.61	80	-65.31	26.7	22.71	18.5	0.18	-	-	Average
0.2163	-27.13	80	-48.03	20.9	33.79	18.84	0.24	-	-	Average
0.49	-2.48	40	-16.28	13.8	17.99	19.2	0.33	100	0	QP
13.56	19.83	40	-9.67	29.5	38.36	21.06	0.41	-	-	QP
14.112	-2.94	40	-32.44	29.5	15.53	21.11	0.42	-	-	QP
18.934	-2.59	40	-32.09	29.5	15.43	21.59	0.39	-	-	QP
29.635	-1.35	40	-30.85	29.5	15.29	22.47	0.89	-	-	QP

Test Mode :	NFC Tx with Adapter	Polarization :	Vertical



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(V)_100315 VERTICAL

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01318	-20.13	80	-65.34	45.21	41.05	18.7	0.12	-	-	Average
0.07401	-29.5	80	-59.72	30.22	31.34	19	0.16	-	-	Average
0.09248	-40.46	80	-68.74	28.28	20.87	18.5	0.17	-	-	QP
0.11088	-42.66	80	-69.37	26.71	18.66	18.5	0.18	-	-	Average
0.15102	-32.12	80	-56.14	24.02	29.01	18.67	0.2	-	-	Average
1.279	-3.31	40	-28.78	25.47	17.39	18.97	0.33	100	0	QP
13.56	16.34	40	-13.16	29.5	34.87	21.06	0.41	-	-	QP
14.152	-3.21	40	-32.71	29.5	15.25	21.12	0.42	-	-	QP
21.724	-2.61	40	-32.11	29.5	15.15	21.84	0.4	-	-	QP
29.05	-0.86	40	-30.36	29.5	15.89	22.42	0.83	-	-	QP

Test Mode :	NFC Tx with Earphone	Polarization :	Horizontal



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(H)_100315 HORIZONTAL

Frequency (MHz)	Level (dBµV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01318	-19.13	80	-64.34	45.21	42.05	18.7	0.12	-	-	Average
0.07419	-30.69	80	-60.89	30.2	30.15	19	0.16	-	-	Average
0.0967	-45.43	80	-73.33	27.9	15.9	18.5	0.17	-	-	QP
0.11176	-49.35	80	-75.99	26.64	11.97	18.5	0.18	-	-	Average
0.1517	-33.74	80	-57.72	23.98	27.39	18.67	0.2	-	-	Average
0.6402	-3.15	40	-34.63	31.48	17.38	19.14	0.33	-	-	QP
13.56	19.76	40	-9.74	29.5	38.29	21.06	0.41	-	-	QP
14.6	-2.83	40	-32.33	29.5	15.59	21.16	0.42	-	-	QP
23.56	-2.26	40	-31.76	29.5	15.34	21.98	0.42	-	-	QP
29.275	-1.49	40	-30.99	29.5	15.21	22.44	0.86	100	0	QP

Test Mode :	NFC Tx with Earphone	Polarization :	Vertical



Site : 03CH07-HY
Condition : 15.209 LIMIT LINE 3m LOOP_ANT(V)_100315 VERTICAL

Frequency (MHz)	Level (dBμV/m)	Distance extrapolation Factor (dB)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01303	-21.12	80	-66.43	45.31	40.06	18.7	0.12	-	-	Average
0.07431	-31.2	80	-61.38	30.18	29.64	19	0.16	-	-	Average
0.0943	-45.5	80	-73.61	28.11	15.83	18.5	0.17	-	-	QP
0.13164	-49.28	80	-74.5	25.22	11.94	18.59	0.19	-	-	Average
0.15102	-33.69	80	-57.71	24.02	27.44	18.67	0.2	-	-	Average
7.444	-3.38	40	-32.88	29.5	16.03	20.19	0.4	-	-	QP
9.528	-3.05	40	-32.55	29.5	15.95	20.6	0.4	-	-	QP
13.56	17.01	40	-12.49	29.5	35.54	21.06	0.41	-	-	QP
23.11	-2.99	40	-32.49	29.5	14.65	21.95	0.41	-	-	QP
29.67	-1.88	40	-31.38	29.5	14.75	22.47	0.9	100	0	QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
3. Limit line = specific limits (dBμV) + distance extrapolation factor
4. 13.56 MHz is fundamental signal which can be ignored

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx with Adapter	Polarization :	Horizontal



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6) HORIZONTAL

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	31.59	-8.41	40	36.35	24.32	0.93	30.01	100	0	Peak
40.8	30.16	-9.84	40	40.08	19	1.08	30	-	-	Peak
164.73	29.48	-14.02	43.5	41.3	15.96	2.16	29.94	-	-	Peak
737.5	30.13	-15.87	46	27.65	27.47	4.6	29.59	-	-	Peak
842.5	31.08	-14.92	46	26.87	28.52	4.94	29.25	-	-	Peak
946.8	33.62	-12.38	46	27.12	29.97	5.25	28.72	-	-	Peak

Test Mode :	NFC Tx with Adapter	Polarization :	Vertical



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6) VERTICAL

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	31.08	-8.92	40	35.84	24.32	0.93	30.01	-	-	Peak
40.8	38.37	-1.63	40	48.29	19	1.08	30	100	0	QP
81.3	23.83	-16.17	40	38.84	13.46	1.51	29.98	-	-	Peak
764.1	29.74	-16.26	46	26.78	27.79	4.7	29.53	-	-	Peak
841.8	32.19	-13.81	46	28	28.51	4.94	29.26	-	-	Peak
944	34.06	-11.94	46	27.76	29.8	5.24	28.74	-	-	Peak

Test Mode :	NFC Tx with Earphone	Polarization :	Horizontal



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6) HORIZONTAL

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	31.58	-8.42	40	36.34	24.32	0.93	30.01	100	0	Peak
40.8	30.15	-9.85	40	40.07	19	1.08	30	-	-	Peak
81.3	20.82	-19.18	40	35.83	13.46	1.51	29.98	-	-	Peak
744.5	30.23	-15.77	46	27.41	27.77	4.62	29.57	-	-	Peak
853.7	31.6	-14.4	46	27.02	28.81	4.97	29.2	-	-	Peak
959.4	33.6	-12.4	46	26.55	30.41	5.29	28.65	-	-	Peak

Test Mode :	NFC Tx with Earphone	Polarization :	Vertical



Site : 03CH07-HY
Condition : QP 3m LF-ANT-35419(6) VERTICAL

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30	31.96	-8.04	40	36.72	24.32	0.93	30.01	-	-	Peak
40.8	35.01	-4.99	40	44.93	19	1.08	30	100	176	QP
67.8	21.46	-18.54	40	38	12.06	1.38	29.98	-	-	Peak
752.2	30.32	-15.68	46	27.48	27.74	4.65	29.55	-	-	Peak
869.1	32.33	-13.67	46	27.55	28.89	5.02	29.13	-	-	Peak
958.7	33.86	-12.14	46	26.79	30.44	5.28	28.65	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.

———THE END———