











Mode	5																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																									
ANT	3																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg.																																																																																										
	Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>40.36</td><td>74.00</td><td>-33.64</td><td>62.44</td><td>32.62</td><td>10.88</td><td>66.02</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>-13.62</td><td>54.00</td><td>-67.62</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7320.00</td><td>45.00</td><td>74.00</td><td>-29.00</td><td>59.88</td><td>36.78</td><td>13.36</td><td>65.46</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>-8.98</td><td>54.00</td><td>-62.98</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	40.36	74.00	-33.64	62.44	32.62	10.88	66.02	0.44	--	PEAK	2	4880.00	-13.62	54.00	-67.62	--	--	--	--	--	--	AVERAGE	3	7320.00	45.00	74.00	-29.00	59.88	36.78	13.36	65.46	0.44	--	PEAK	4	7320.00	-8.98	54.00	-62.98	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4880.00	40.36	74.00	-33.64	62.44	32.62	10.88	66.02	0.44	--	PEAK																																																																															
2	4880.00	-13.62	54.00	-67.62	--	--	--	--	--	--	AVERAGE																																																																															
3	7320.00	45.00	74.00	-29.00	59.88	36.78	13.36	65.46	0.44	--	PEAK																																																																															
4	7320.00	-8.98	54.00	-62.98	--	--	--	--	--	--	AVERAGE																																																																															





Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





Mode	6																																																																																																																													
	Band Edge																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																													
ANT	3																																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.76</td><td>61.95</td><td>74.00</td><td>-12.05</td><td>46.57</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>196</td><td>218</td><td>PEAK</td></tr><tr><td>2</td><td>2483.76</td><td>7.97</td><td>54.00</td><td>-46.03</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.76	61.95	74.00	-12.05	46.57	27.70	7.64	29.88	9.92	196	218	PEAK	2	2483.76	7.97	54.00	-46.03	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>116.11</td><td>-----</td><td>-----</td><td>100.75</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>196</td><td>218</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>62.13</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	116.11	-----	-----	100.75	27.68	7.65	29.89	9.92	196	218	PEAK	2	2478.00	62.13	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2483.76	61.95	74.00	-12.05	46.57	27.70	7.64	29.88	9.92	196	218	PEAK																																																																																																																		
2	2483.76	7.97	54.00	-46.03	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2478.00	116.11	-----	-----	100.75	27.68	7.65	29.89	9.92	196	218	PEAK																																																																																																																		
2	2478.00	62.13	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		







Mode	6																																																																																																																								
	Band Edge																																																																																																																								
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																								
ANT	3																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	 Level (dBuV/m) Frequency (MHz) PEAK_BE_74						 Level (dBuV/m) Frequency (MHz) PEAK_74																																																																																																																		
Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.57</td><td>63.47</td><td>74.00</td><td>-10.53</td><td>48.09</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>100</td><td>278 PEAK</td></tr><tr><td>2</td><td>2483.57</td><td>9.49</td><td>54.00</td><td>-44.51</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table> Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>118.16</td><td>-----</td><td>-----</td><td>102.80</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>100</td><td>278 PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>64.18</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.57	63.47	74.00	-10.53	48.09	27.70	7.64	29.88	9.92	100	278 PEAK	2	2483.57	9.49	54.00	-44.51	--	--	--	--	--	--	AVERAGE		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	118.16	-----	-----	102.80	27.68	7.65	29.89	9.92	100	278 PEAK	2	2478.00	64.18	-----	-----	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2483.57	63.47	74.00	-10.53	48.09	27.70	7.64	29.88	9.92	100	278 PEAK																																																																																																														
2	2483.57	9.49	54.00	-44.51	--	--	--	--	--	--	AVERAGE																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2478.00	118.16	-----	-----	102.80	27.68	7.65	29.89	9.92	100	278 PEAK																																																																																																														
2	2478.00	64.18	-----	-----	--	--	--	--	--	--	AVERAGE																																																																																																														





Mode	6										
	Harmonic										
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz										
ANT	3										
Pol.	Horizontal										
Peak Avg.											
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg	
1	4956.00	40.94	74.00	-33.06	62.28	33.01	11.08	65.88	0.45	--	PEAK
2	4956.00	-13.04	54.00	-67.04	--	--	--	--	--	--	AVERAGE
3	7434.00	44.42	74.00	-29.58	59.68	36.33	13.47	65.46	0.40	--	PEAK
4	7434.00	-9.56	54.00	-63.56	--	--	--	--	--	--	AVERAGE

Peak Avg.												
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark			
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		
1	4956.00	42.84	74.00	-31.16	64.18	33.01	11.08	65.88	0.45	300	190	PEAK
2	4956.00	-11.14	54.00	-65.14	--	--	--	--	--	--	--	AVERAGE
3	7434.00	44.71	74.00	-29.29	59.97	36.33	13.47	65.46	0.40	--	--	PEAK
4	7434.00	-9.27	54.00	-63.27	--	--	--	--	--	--	--	AVERAGE





Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL



Mode	13																																																																																																																
	LF																																																																																																																
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																
ANT	3																																																																																																																
Pol.	Horizontal						Vertical																																																																																																										
QP/ Peak																																																																																																																	
	Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06 HORIZONTAL																																																																																																																
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>78.50</td><td>22.53</td><td>40.00</td><td>-17.47</td><td>40.47</td><td>13.31</td><td>1.15</td><td>32.40</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>199.75</td><td>34.24</td><td>43.50</td><td>-9.26</td><td>49.67</td><td>14.99</td><td>1.97</td><td>32.39</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>252.13</td><td>31.05</td><td>46.00</td><td>-14.95</td><td>42.47</td><td>18.75</td><td>2.25</td><td>32.42</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>286.00</td><td>32.51</td><td>46.00</td><td>-13.49</td><td>43.47</td><td>19.02</td><td>2.43</td><td>32.41</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>737.13</td><td>29.37</td><td>46.00</td><td>-16.63</td><td>29.92</td><td>27.96</td><td>4.06</td><td>32.57</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>945.68</td><td>31.85</td><td>46.00</td><td>-14.15</td><td>28.25</td><td>30.62</td><td>4.54</td><td>31.56</td><td>0.00</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	78.50	22.53	40.00	-17.47	40.47	13.31	1.15	32.40	0.00	--	Peak	2	199.75	34.24	43.50	-9.26	49.67	14.99	1.97	32.39	0.00	--	Peak	3	252.13	31.05	46.00	-14.95	42.47	18.75	2.25	32.42	0.00	--	Peak	4	286.00	32.51	46.00	-13.49	43.47	19.02	2.43	32.41	0.00	--	Peak	5	737.13	29.37	46.00	-16.63	29.92	27.96	4.06	32.57	0.00	--	Peak	6	945.68	31.85	46.00	-14.15	28.25	30.62	4.54	31.56	0.00	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																								
1	78.50	22.53	40.00	-17.47	40.47	13.31	1.15	32.40	0.00	--	Peak																																																																																																						
2	199.75	34.24	43.50	-9.26	49.67	14.99	1.97	32.39	0.00	--	Peak																																																																																																						
3	252.13	31.05	46.00	-14.95	42.47	18.75	2.25	32.42	0.00	--	Peak																																																																																																						
4	286.00	32.51	46.00	-13.49	43.47	19.02	2.43	32.41	0.00	--	Peak																																																																																																						
5	737.13	29.37	46.00	-16.63	29.92	27.96	4.06	32.57	0.00	--	Peak																																																																																																						
6	945.68	31.85	46.00	-14.15	28.25	30.62	4.54	31.56	0.00	--	Peak																																																																																																						
																																																																																																																	
Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06 VERTICAL																																																																																																																	
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>41.64</td><td>31.96</td><td>40.00</td><td>-8.04</td><td>45.01</td><td>18.57</td><td>0.85</td><td>32.47</td><td>0.00</td><td>100</td><td>327 QP</td></tr><tr><td>2</td><td>198.78</td><td>30.59</td><td>43.50</td><td>-12.91</td><td>46.09</td><td>14.93</td><td>1.96</td><td>32.39</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>252.13</td><td>28.34</td><td>46.00</td><td>-17.66</td><td>39.76</td><td>18.75</td><td>2.25</td><td>32.42</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>404.42</td><td>28.50</td><td>46.00</td><td>-17.42</td><td>36.09</td><td>21.99</td><td>3.01</td><td>32.51</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>709.00</td><td>31.95</td><td>46.00</td><td>-14.05</td><td>34.00</td><td>26.68</td><td>3.99</td><td>32.72</td><td>0.00</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>952.47</td><td>33.28</td><td>46.00</td><td>-12.72</td><td>29.45</td><td>30.77</td><td>4.56</td><td>31.50</td><td>0.00</td><td>--</td><td>Peak</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	41.64	31.96	40.00	-8.04	45.01	18.57	0.85	32.47	0.00	100	327 QP	2	198.78	30.59	43.50	-12.91	46.09	14.93	1.96	32.39	0.00	--	Peak	3	252.13	28.34	46.00	-17.66	39.76	18.75	2.25	32.42	0.00	--	Peak	4	404.42	28.50	46.00	-17.42	36.09	21.99	3.01	32.51	0.00	--	Peak	5	709.00	31.95	46.00	-14.05	34.00	26.68	3.99	32.72	0.00	--	Peak	6	952.47	33.28	46.00	-12.72	29.45	30.77	4.56	31.50	0.00	--	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																								
Freq	Level	Line Margin	Level	Factor	Loss	Factor	Factor																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																								
1	41.64	31.96	40.00	-8.04	45.01	18.57	0.85	32.47	0.00	100	327 QP																																																																																																						
2	198.78	30.59	43.50	-12.91	46.09	14.93	1.96	32.39	0.00	--	Peak																																																																																																						
3	252.13	28.34	46.00	-17.66	39.76	18.75	2.25	32.42	0.00	--	Peak																																																																																																						
4	404.42	28.50	46.00	-17.42	36.09	21.99	3.01	32.51	0.00	--	Peak																																																																																																						
5	709.00	31.95	46.00	-14.05	34.00	26.68	3.99	32.72	0.00	--	Peak																																																																																																						
6	952.47	33.28	46.00	-12.72	29.45	30.77	4.56	31.50	0.00	--	Peak																																																																																																						





Mode	14																																																																																							
	SHF																																																																																							
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																							
ANT	3																																																																																							
Pol.	Horizontal	Vertical																																																																																						
Peak	 Site : 03CH16-HY Condition: PEAK_74 1m SHF_00993_231124 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24124.74</td><td>38.75</td><td>74.00</td><td>-35.25</td><td>56.39</td><td>38.75</td><td>6.95</td><td>53.80</td><td>-9.54</td><td>--</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	24124.74	38.75	74.00	-35.25	56.39	38.75	6.95	53.80	-9.54	--	PEAK	 Site : 03CH16-HY Condition: PEAK_74 1m SHF_00993_231124 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>25653.64</td><td>38.53</td><td>74.00</td><td>-35.47</td><td>55.27</td><td>38.99</td><td>7.11</td><td>53.30</td><td>-9.54</td><td>--</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	25653.64	38.53	74.00	-35.47	55.27	38.99	7.11	53.30	-9.54	--	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	24124.74	38.75	74.00	-35.25	56.39	38.75	6.95	53.80	-9.54	--	PEAK																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	25653.64	38.53	74.00	-35.47	55.27	38.99	7.11	53.30	-9.54	--	PEAK																																																																													





<Ant. 4>



<1Mbps>

Mode	7																																																																																																															
	Band Edge																																																																																																															
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																															
ANT	4																																																																																																															
Pol.	Horizontal	Fundamental																																																																																																														
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2382.66</td><td>56.06</td><td>74.00</td><td>-17.94</td><td>41.15</td><td>27.23</td><td>7.68</td><td>29.92</td><td>9.92</td><td>312</td><td>309 PEAK</td></tr><tr><td>2</td><td>2382.66</td><td>2.08</td><td>54.00</td><td>-51.92</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2382.66	56.06	74.00	-17.94	41.15	27.23	7.68	29.92	9.92	312	309 PEAK	2	2382.66	2.08	54.00	-51.92	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2404.00</td><td>107.73</td><td>-----</td><td>-----</td><td>92.61</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>312</td><td>309 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>53.75</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	107.73	-----	-----	92.61	27.40	7.71	29.91	9.92	312	309 PEAK	2	2404.00	53.75	-----	-----	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	2382.66	56.06	74.00	-17.94	41.15	27.23	7.68	29.92	9.92	312	309 PEAK																																																																																																					
2	2382.66	2.08	54.00	-51.92	--	--	--	--	--	--	AVERAGE																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																						
1	2404.00	107.73	-----	-----	92.61	27.40	7.71	29.91	9.92	312	309 PEAK																																																																																																					
2	2404.00	53.75	-----	-----	--	--	--	--	--	--	AVERAGE																																																																																																					







Mode	7																																																																																																																			
	Band Edge																																																																																																																			
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																			
ANT	4																																																																																																																			
Pol.	Vertical	Fundamental																																																																																																																		
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2318.55</td><td>55.99</td><td>74.00</td><td>-18.01</td><td>41.33</td><td>27.10</td><td>7.57</td><td>29.93</td><td>9.92</td><td>302</td><td>270</td><td>PEAK</td></tr><tr><td>2</td><td>2318.55</td><td>2.01</td><td>54.00</td><td>-51.99</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2318.55	55.99	74.00	-18.01	41.33	27.10	7.57	29.93	9.92	302	270	PEAK	2	2318.55	2.01	54.00	-51.99	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2404.00</td><td>107.71</td><td>-----</td><td>-----</td><td>92.59</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>302</td><td>270</td><td>PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>53.73</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	107.71	-----	-----	92.59	27.40	7.71	29.91	9.92	302	270	PEAK	2	2404.00	53.73	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																										
1	2318.55	55.99	74.00	-18.01	41.33	27.10	7.57	29.93	9.92	302	270	PEAK																																																																																																								
2	2318.55	2.01	54.00	-51.99	--	--	--	--	--	--	--	AVERAGE																																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																										
1	2404.00	107.71	-----	-----	92.59	27.40	7.71	29.91	9.92	302	270	PEAK																																																																																																								
2	2404.00	53.73	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																								





Mode	7																																																																												
	Harmonic																																																																												
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																												
ANT	4																																																																												
Pol.	Horizontal						Vertical																																																																						
Peak Avg.																																																																													
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL																																																																						
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4808.00</td><td>39.40</td><td>74.00</td><td>-34.60</td><td>62.10</td><td>32.33</td><td>10.69</td><td>66.16</td><td>0.44</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-14.58</td><td>54.00</td><td>-68.58</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4808.00	39.40	74.00	-34.60	62.10	32.33	10.69	66.16	0.44	--	--	PEAK	2	4808.00	-14.58	54.00	-68.58	--	--	--	--	--	--	--	AVERAGE
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				Remark																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																			
1	4808.00	39.40	74.00	-34.60	62.10	32.33	10.69	66.16	0.44	--	--	PEAK																																																																	
2	4808.00	-14.58	54.00	-68.58	--	--	--	--	--	--	--	AVERAGE																																																																	
<table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th><th></th></tr><tr><td>1</td><td>4808.00</td><td>40.18</td><td>74.00</td><td>-33.82</td><td>62.88</td><td>32.33</td><td>10.69</td><td>66.16</td><td>0.44</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-13.80</td><td>54.00</td><td>-67.80</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>															Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg			1	4808.00	40.18	74.00	-33.82	62.88	32.33	10.69	66.16	0.44	--	--	PEAK	2	4808.00	-13.80	54.00	-67.80	--	--	--	--	--	--	--	AVERAGE
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor				Remark																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																			
1	4808.00	40.18	74.00	-33.82	62.88	32.33	10.69	66.16	0.44	--	--	PEAK																																																																	
2	4808.00	-13.80	54.00	-67.80	--	--	--	--	--	--	--	AVERAGE																																																																	




Mode	7	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





Mode	8																																																																																																																								
	Band Edge - L																																																																																																																								
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																								
ANT	4																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak																																																																																																																									
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																		
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2328.20</td><td>56.10</td><td>74.00</td><td>-17.90</td><td>41.43</td><td>27.10</td><td>7.58</td><td>29.93</td><td>9.92</td><td>307</td><td>309 PEAK</td></tr><tr><td>2</td><td>2328.20</td><td>2.12</td><td>54.00</td><td>-51.88</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>-- AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2328.20	56.10	74.00	-17.90	41.43	27.10	7.58	29.93	9.92	307	309 PEAK	2	2328.20	2.12	54.00	-51.88	--	--	--	--	--	--	-- AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>109.09</td><td>-----</td><td>-----</td><td>93.79</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>307</td><td>309 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>55.11</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>-- AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	109.09	-----	-----	93.79	27.60	7.68	29.90	9.92	307	309 PEAK	2	2440.00	55.11	-----	-----	--	--	--	--	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2328.20	56.10	74.00	-17.90	41.43	27.10	7.58	29.93	9.92	307	309 PEAK																																																																																																														
2	2328.20	2.12	54.00	-51.88	--	--	--	--	--	--	-- AVERAGE																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2440.00	109.09	-----	-----	93.79	27.60	7.68	29.90	9.92	307	309 PEAK																																																																																																														
2	2440.00	55.11	-----	-----	--	--	--	--	--	--	-- AVERAGE																																																																																																														




Mode	8																																																									
	Band Edge - R																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																									
ANT	4																																																									
Pol.	Horizontal	Fundamental																																																								
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>2498.32</td><td>56.67</td><td>74.00</td><td>-17.33</td><td></td><td>41.30</td><td>27.70</td><td>7.63</td><td>29.88</td><td>9.92</td><td>307</td><td>309</td><td>PEAK</td></tr><tr><td>2</td><td>2498.32</td><td>2.69</td><td>54.00</td><td>-51.31</td><td></td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	2498.32	56.67	74.00	-17.33		41.30	27.70	7.63	29.88	9.92	307	309	PEAK	2	2498.32	2.69	54.00	-51.31		--	--	--	--	--	--	--	AVERAGE	Blank
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																													
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																														
1	2498.32	56.67	74.00	-17.33		41.30	27.70	7.63	29.88	9.92	307	309	PEAK																																													
2	2498.32	2.69	54.00	-51.31		--	--	--	--	--	--	--	AVERAGE																																													





Mode	8																																																																																																																													
	Band Edge - L																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Vertical						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2319.75</td><td>56.41</td><td>74.00</td><td>-17.59</td><td>41.75</td><td>27.10</td><td>7.57</td><td>29.93</td><td>9.92</td><td>174</td><td>277</td><td>PEAK</td></tr><tr><td>2</td><td>2319.75</td><td>2.43</td><td>54.00</td><td>-51.57</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2319.75	56.41	74.00	-17.59	41.75	27.10	7.57	29.93	9.92	174	277	PEAK	2	2319.75	2.43	54.00	-51.57	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>109.33</td><td>-----</td><td>-----</td><td>94.03</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>174</td><td>277</td><td>PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>55.35</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	109.33	-----	-----	94.03	27.60	7.68	29.90	9.92	174	277	PEAK	2	2440.00	55.35	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2319.75	56.41	74.00	-17.59	41.75	27.10	7.57	29.93	9.92	174	277	PEAK																																																																																																																		
2	2319.75	2.43	54.00	-51.57	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2440.00	109.33	-----	-----	94.03	27.60	7.68	29.90	9.92	174	277	PEAK																																																																																																																		
2	2440.00	55.35	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		







Mode	8																																																										
	Band Edge - R																																																										
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																										
ANT	4																																																										
Pol.	Vertical	Fundamental																																																									
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240320 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2489.68</td><td>56.72</td><td>74.00</td><td>-17.28</td><td>41.34</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>174</td><td>277</td><td>PEAK</td></tr><tr><td>2</td><td>2489.68</td><td>2.74</td><td>54.00</td><td>-51.26</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2489.68	56.72	74.00	-17.28	41.34	27.70	7.64	29.88	9.92	174	277	PEAK	2	2489.68	2.74	54.00	-51.26	--	--	--	--	--	--	--	AVERAGE	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																	
1	2489.68	56.72	74.00	-17.28	41.34	27.70	7.64	29.88	9.92	174	277	PEAK																																															
2	2489.68	2.74	54.00	-51.26	--	--	--	--	--	--	--	AVERAGE																																															





Mode	8																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																									
ANT	4																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg.																																																																																										
	Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4880.00</td><td>39.55</td><td>74.00</td><td>-34.45</td><td>61.63</td><td>32.62</td><td>10.88</td><td>66.02</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4880.00</td><td>-14.43</td><td>54.00</td><td>-68.43</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7320.00</td><td>45.50</td><td>74.00</td><td>-28.50</td><td>60.38</td><td>36.78</td><td>13.36</td><td>65.46</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7320.00</td><td>-8.48</td><td>54.00</td><td>-62.48</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4880.00	39.55	74.00	-34.45	61.63	32.62	10.88	66.02	0.44	--	PEAK	2	4880.00	-14.43	54.00	-68.43	--	--	--	--	--	--	AVERAGE	3	7320.00	45.50	74.00	-28.50	60.38	36.78	13.36	65.46	0.44	--	PEAK	4	7320.00	-8.48	54.00	-62.48	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4880.00	39.55	74.00	-34.45	61.63	32.62	10.88	66.02	0.44	--	PEAK																																																																															
2	4880.00	-14.43	54.00	-68.43	--	--	--	--	--	--	AVERAGE																																																																															
3	7320.00	45.50	74.00	-28.50	60.38	36.78	13.36	65.46	0.44	--	PEAK																																																																															
4	7320.00	-8.48	54.00	-62.48	--	--	--	--	--	--	AVERAGE																																																																															





Mode	8	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





Mode	9																																																																																																																												
	Band Edge																																																																																																																												
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																												
ANT	4																																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																																						
Peak																																																																																																																													
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.36</td><td>57.46</td><td>74.00</td><td>-16.54</td><td>42.08</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>266</td><td>304</td><td>PEAK</td></tr><tr><td>2</td><td>2484.36</td><td>3.48</td><td>54.00</td><td>-50.52</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.36	57.46	74.00	-16.54	42.08	27.70	7.64	29.88	9.92	266	304	PEAK	2	2484.36	3.48	54.00	-50.52	--	--	--	--	--	--	--	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>109.38</td><td>-----</td><td>-----</td><td>94.02</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>266</td><td>304</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>55.40</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	109.38	-----	-----	94.02	27.68	7.65	29.89	9.92	266	304	PEAK	2	2478.00	55.40	-----	-----	--	--	--	--	--	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2484.36	57.46	74.00	-16.54	42.08	27.70	7.64	29.88	9.92	266	304	PEAK																																																																																																																	
2	2484.36	3.48	54.00	-50.52	--	--	--	--	--	--	--	AVERAGE																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2478.00	109.38	-----	-----	94.02	27.68	7.65	29.89	9.92	266	304	PEAK																																																																																																																	
2	2478.00	55.40	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																	







Mode	9																																																																																																																												
	Band Edge																																																																																																																												
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																												
ANT	4																																																																																																																												
Pol.	Vertical						Fundamental																																																																																																																						
Peak																																																																																																																													
	Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2485.06</td><td>57.82</td><td>74.00</td><td>-16.18</td><td>42.44</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>155</td><td>277</td><td>PEAK</td></tr><tr><td>2</td><td>2485.06</td><td>3.84</td><td>54.00</td><td>-50.16</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.06	57.82	74.00	-16.18	42.44	27.70	7.64	29.88	9.92	155	277	PEAK	2	2485.06	3.84	54.00	-50.16	--	--	--	--	--	--	--	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>2478.00</td><td>111.41</td><td>-----</td><td>-----</td><td>96.05</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>155</td><td>277</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>57.43</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	111.41	-----	-----	96.05	27.68	7.65	29.89	9.92	155	277	PEAK	2	2478.00	57.43	-----	-----	--	--	--	--	--	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2485.06	57.82	74.00	-16.18	42.44	27.70	7.64	29.88	9.92	155	277	PEAK																																																																																																																	
2	2485.06	3.84	54.00	-50.16	--	--	--	--	--	--	--	AVERAGE																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	2478.00	111.41	-----	-----	96.05	27.68	7.65	29.89	9.92	155	277	PEAK																																																																																																																	
2	2478.00	57.43	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																	





Mode	9																																																																																									
	Harmonic																																																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																									
ANT	4																																																																																									
Pol.	Horizontal						Vertical																																																																																			
Peak Avg.																																																																																										
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL																																																																																			
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>40.81</td><td>74.00</td><td>-33.19</td><td>62.15</td><td>33.01</td><td>11.08</td><td>65.88</td><td>0.45</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>-13.17</td><td>54.00</td><td>-67.17</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7434.00</td><td>44.68</td><td>74.00</td><td>-29.32</td><td>59.94</td><td>36.33</td><td>13.47</td><td>65.46</td><td>0.40</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7434.00</td><td>-9.30</td><td>54.00</td><td>-63.30</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	40.81	74.00	-33.19	62.15	33.01	11.08	65.88	0.45	--	PEAK	2	4956.00	-13.17	54.00	-67.17	--	--	--	--	--	--	AVERAGE	3	7434.00	44.68	74.00	-29.32	59.94	36.33	13.47	65.46	0.40	--	PEAK	4	7434.00	-9.30	54.00	-63.30	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																
1	4956.00	40.81	74.00	-33.19	62.15	33.01	11.08	65.88	0.45	--	PEAK																																																																															
2	4956.00	-13.17	54.00	-67.17	--	--	--	--	--	--	AVERAGE																																																																															
3	7434.00	44.68	74.00	-29.32	59.94	36.33	13.47	65.46	0.40	--	PEAK																																																																															
4	7434.00	-9.30	54.00	-63.30	--	--	--	--	--	--	AVERAGE																																																																															





Mode	9	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





<2Mbps>

Mode	10																																																																																																																													
	Band Edge																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2316.96</td><td>55.99</td><td>74.00</td><td>-18.01</td><td>41.34</td><td>27.10</td><td>7.56</td><td>29.93</td><td>9.92</td><td>311</td><td>221</td><td>PEAK</td></tr><tr><td>2</td><td>2316.96</td><td>0.07</td><td>54.00</td><td>-53.93</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2316.96	55.99	74.00	-18.01	41.34	27.10	7.56	29.93	9.92	311	221	PEAK	2	2316.96	0.07	54.00	-53.93	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2404.00</td><td>108.35</td><td>-----</td><td>-----</td><td>93.23</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>311</td><td>221</td><td>PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>52.43</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	108.35	-----	-----	93.23	27.40	7.71	29.91	9.92	311	221	PEAK	2	2404.00	52.43	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2316.96	55.99	74.00	-18.01	41.34	27.10	7.56	29.93	9.92	311	221	PEAK																																																																																																																		
2	2316.96	0.07	54.00	-53.93	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2404.00	108.35	-----	-----	93.23	27.40	7.71	29.91	9.92	311	221	PEAK																																																																																																																		
2	2404.00	52.43	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		







Mode	10																																																																																																																									
	Band Edge																																																																																																																									
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																									
ANT	4																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																			
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2345.91</td><td>56.09</td><td>74.00</td><td>-17.91</td><td>41.38</td><td>27.10</td><td>7.62</td><td>29.93</td><td>9.92</td><td>272</td><td>274 PEAK</td></tr><tr><td>2</td><td>2345.91</td><td>0.17</td><td>54.00</td><td>-53.83</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>-- AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2345.91	56.09	74.00	-17.91	41.38	27.10	7.62	29.93	9.92	272	274 PEAK	2	2345.91	0.17	54.00	-53.83	--	--	--	--	--	--	-- AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2404.00</td><td>100.28</td><td>-----</td><td>-----</td><td>93.16</td><td>27.40</td><td>7.71</td><td>29.91</td><td>9.92</td><td>272</td><td>274 PEAK</td></tr><tr><td>2</td><td>2404.00</td><td>52.36</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>-- AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2404.00	100.28	-----	-----	93.16	27.40	7.71	29.91	9.92	272	274 PEAK	2	2404.00	52.36	-----	-----	--	--	--	--	--	--	-- AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2345.91	56.09	74.00	-17.91	41.38	27.10	7.62	29.93	9.92	272	274 PEAK																																																																																																															
2	2345.91	0.17	54.00	-53.83	--	--	--	--	--	--	-- AVERAGE																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	2404.00	100.28	-----	-----	93.16	27.40	7.71	29.91	9.92	272	274 PEAK																																																																																																															
2	2404.00	52.36	-----	-----	--	--	--	--	--	--	-- AVERAGE																																																																																																															





Mode	10																																																																																																																								
	Harmonic																																																																																																																								
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz																																																																																																																								
ANT	4																																																																																																																								
Pol.	Horizontal						Vertical																																																																																																																		
Peak Avg.																																																																																																																									
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL																																																																																																																		
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4808.00</td><td>38.70</td><td>74.00</td><td>-35.30</td><td>61.40</td><td>32.33</td><td>10.69</td><td>66.16</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-17.22</td><td>54.00</td><td>-71.22</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4808.00	38.70	74.00	-35.30	61.40	32.33	10.69	66.16	0.44	--	PEAK	2	4808.00	-17.22	54.00	-71.22	--	--	--	--	--	--	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4808.00</td><td>39.42</td><td>74.00</td><td>-34.58</td><td>62.12</td><td>32.33</td><td>10.69</td><td>66.16</td><td>0.44</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4808.00</td><td>-16.50</td><td>54.00</td><td>-70.50</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4808.00	39.42	74.00	-34.58	62.12	32.33	10.69	66.16	0.44	--	PEAK	2	4808.00	-16.50	54.00	-70.50	--	--	--	--	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4808.00	38.70	74.00	-35.30	61.40	32.33	10.69	66.16	0.44	--	PEAK																																																																																																														
2	4808.00	-17.22	54.00	-71.22	--	--	--	--	--	--	AVERAGE																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	4808.00	39.42	74.00	-34.58	62.12	32.33	10.69	66.16	0.44	--	PEAK																																																																																																														
2	4808.00	-16.50	54.00	-70.50	--	--	--	--	--	--	AVERAGE																																																																																																														




Mode	10	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH02_2404MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





Mode	11																																																																																																																													
	Band Edge - L																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2382.41</td><td>55.67</td><td>74.00</td><td>-18.33</td><td>40.77</td><td>27.22</td><td>7.68</td><td>29.92</td><td>9.92</td><td>305</td><td>224</td><td>PEAK</td></tr><tr><td>2</td><td>2382.41</td><td>-0.25</td><td>54.00</td><td>-54.25</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2382.41	55.67	74.00	-18.33	40.77	27.22	7.68	29.92	9.92	305	224	PEAK	2	2382.41	-0.25	54.00	-54.25	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>108.93</td><td>-----</td><td>-----</td><td>93.63</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>305</td><td>224</td><td>PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>53.01</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	108.93	-----	-----	93.63	27.60	7.68	29.90	9.92	305	224	PEAK	2	2440.00	53.01	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2382.41	55.67	74.00	-18.33	40.77	27.22	7.68	29.92	9.92	305	224	PEAK																																																																																																																		
2	2382.41	-0.25	54.00	-54.25	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2440.00	108.93	-----	-----	93.63	27.60	7.68	29.90	9.92	305	224	PEAK																																																																																																																		
2	2440.00	53.01	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		




Mode	11																																																																			
	Band Edge - R																																																																			
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																			
ANT	4																																																																			
Pol.	Horizontal						Fundamental																																																													
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2489.50</td><td>56.53</td><td>74.00</td><td>-17.47</td><td>41.15</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>305</td><td>224</td><td>PEAK</td></tr><tr><td>2</td><td>2489.50</td><td>0.61</td><td>54.00</td><td>-53.39</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	cm	deg	1	2489.50	56.53	74.00	-17.47	41.15	27.70	7.64	29.88	9.92	305	224	PEAK	2	2489.50	0.61	54.00	-53.39	--	--	--	--	--	--	--	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																											
	MHz	dBuV/m	dBuV/m	dB	dB	dB/m	dB	dB	cm	deg																																																										
1	2489.50	56.53	74.00	-17.47	41.15	27.70	7.64	29.88	9.92	305	224	PEAK																																																								
2	2489.50	0.61	54.00	-53.39	--	--	--	--	--	--	--	AVERAGE																																																								





Mode	11																																																																																																																								
	Band Edge - L																																																																																																																								
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																																																																								
ANT	4																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2342.37</td><td>56.05</td><td>74.00</td><td>-17.95</td><td>41.35</td><td>27.10</td><td>7.61</td><td>29.93</td><td>9.92</td><td>330</td><td>275 PEAK</td></tr><tr><td>2</td><td>2342.37</td><td>0.13</td><td>54.00</td><td>-53.87</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2342.37	56.05	74.00	-17.95	41.35	27.10	7.61	29.93	9.92	330	275 PEAK	2	2342.37	0.13	54.00	-53.87	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2440.00</td><td>110.73</td><td>-----</td><td>-----</td><td>95.43</td><td>27.60</td><td>7.68</td><td>29.90</td><td>9.92</td><td>330</td><td>275 PEAK</td></tr><tr><td>2</td><td>2440.00</td><td>54.81</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2440.00	110.73	-----	-----	95.43	27.60	7.68	29.90	9.92	330	275 PEAK	2	2440.00	54.81	-----	-----	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2342.37	56.05	74.00	-17.95	41.35	27.10	7.61	29.93	9.92	330	275 PEAK																																																																																																														
2	2342.37	0.13	54.00	-53.87	--	--	--	--	--	--	AVERAGE																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2440.00	110.73	-----	-----	95.43	27.60	7.68	29.90	9.92	330	275 PEAK																																																																																																														
2	2440.00	54.81	-----	-----	--	--	--	--	--	--	AVERAGE																																																																																																														







Mode	11																																																																			
	Band Edge - R																																																																			
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz																																																																			
ANT	4																																																																			
Pol.	Vertical						Fundamental																																																													
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240320 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2499.82</td><td>56.51</td><td>74.00</td><td>-17.49</td><td>41.14</td><td>27.70</td><td>7.63</td><td>29.88</td><td>9.92</td><td>330</td><td>275</td><td>PEAK</td></tr><tr><td>2</td><td>2499.82</td><td>0.59</td><td>54.00</td><td>-53.41</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2499.82	56.51	74.00	-17.49	41.14	27.70	7.63	29.88	9.92	330	275	PEAK	2	2499.82	0.59	54.00	-53.41	--	--	--	--	--	--	--	AVERAGE	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																										
1	2499.82	56.51	74.00	-17.49	41.14	27.70	7.63	29.88	9.92	330	275	PEAK																																																								
2	2499.82	0.59	54.00	-53.41	--	--	--	--	--	--	--	AVERAGE																																																								





Mode	11												
	Harmonic												
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz												
ANT	4												
Pol.	Horizontal						Vertical						
Peak Avg.													
	Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91280-1522_240328 VERTICAL						
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg
1	4880.00	40.41	74.00	-33.59	62.49	32.62	10.88	66.02	0.44	--	--	--	PEAK
2	4880.00	-15.51	54.00	-69.51	--	--	--	--	--	--	--	--	AVERAGE
3	7320.00	44.74	74.00	-29.26	59.62	36.78	13.36	65.46	0.44	--	--	--	PEAK
4	7320.00	-11.18	54.00	-65.18	--	--	--	--	--	--	--	--	AVERAGE
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	dB	cm	deg
1	4880.00	40.46	74.00	-33.54	62.54	32.62	10.88	66.02	0.44	--	--	--	PEAK
2	4880.00	-15.46	54.00	-69.46	--	--	--	--	--	--	--	--	AVERAGE
3	7320.00	45.01	74.00	-28.99	59.09	36.78	13.36	65.46	0.44	--	--	--	PEAK
4	7320.00	-10.91	54.00	-64.91	--	--	--	--	--	--	--	--	AVERAGE





Mode	11	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH38_2440MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
17.7G ~18G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL





Mode	12																																																																																																																													
	Band Edge																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.02</td><td>58.01</td><td>74.00</td><td>-15.99</td><td>42.63</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>294</td><td>335</td><td>PEAK</td></tr><tr><td>2</td><td>2485.02</td><td>2.09</td><td>54.00</td><td>-51.91</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.02	58.01	74.00	-15.99	42.63	27.70	7.64	29.88	9.92	294	335	PEAK	2	2485.02	2.09	54.00	-51.91	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>107.86</td><td>-----</td><td>-----</td><td>92.50</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>294</td><td>335</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>51.94</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	107.86	-----	-----	92.50	27.68	7.65	29.89	9.92	294	335	PEAK	2	2478.00	51.94	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2485.02	58.01	74.00	-15.99	42.63	27.70	7.64	29.88	9.92	294	335	PEAK																																																																																																																		
2	2485.02	2.09	54.00	-51.91	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2478.00	107.86	-----	-----	92.50	27.68	7.65	29.89	9.92	294	335	PEAK																																																																																																																		
2	2478.00	51.94	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		







Mode	12																																																																																																																													
	Band Edge																																																																																																																													
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																																													
ANT	4																																																																																																																													
Pol.	Vertical						Fundamental																																																																																																																							
Peak	 Site : 03CH16-HY Condition: PEAK_BE_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.11</td><td>57.89</td><td>74.00</td><td>-16.11</td><td>42.51</td><td>27.70</td><td>7.64</td><td>29.88</td><td>9.92</td><td>194</td><td>274</td><td>PEAK</td></tr><tr><td>2</td><td>2485.11</td><td>1.97</td><td>54.00</td><td>-52.03</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.11	57.89	74.00	-16.11	42.51	27.70	7.64	29.88	9.92	194	274	PEAK	2	2485.11	1.97	54.00	-52.03	--	--	--	--	--	--	--	AVERAGE	 Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>110.44</td><td>-----</td><td>-----</td><td>95.00</td><td>27.68</td><td>7.65</td><td>29.89</td><td>9.92</td><td>194</td><td>274</td><td>PEAK</td></tr><tr><td>2</td><td>2478.00</td><td>54.52</td><td>-----</td><td>-----</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	110.44	-----	-----	95.00	27.68	7.65	29.89	9.92	194	274	PEAK	2	2478.00	54.52	-----	-----	--	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2485.11	57.89	74.00	-16.11	42.51	27.70	7.64	29.88	9.92	194	274	PEAK																																																																																																																		
2	2485.11	1.97	54.00	-52.03	--	--	--	--	--	--	--	AVERAGE																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	2478.00	110.44	-----	-----	95.00	27.68	7.65	29.89	9.92	194	274	PEAK																																																																																																																		
2	2478.00	54.52	-----	-----	--	--	--	--	--	--	--	AVERAGE																																																																																																																		





Mode	12																																																																																										
	Harmonic																																																																																										
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																										
ANT	4																																																																																										
Pol.	Horizontal						Vertical																																																																																				
Peak Avg.																																																																																											
	Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 3m 91200-1522_240328 VERTICAL																																																																																				
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>41.24</td><td>74.00</td><td>-32.76</td><td>62.58</td><td>33.01</td><td>11.08</td><td>65.88</td><td>0.45</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>4956.00</td><td>-14.68</td><td>54.00</td><td>-68.68</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>7434.00</td><td>43.98</td><td>74.00</td><td>-30.02</td><td>59.24</td><td>36.33</td><td>13.47</td><td>65.46</td><td>0.40</td><td>--</td><td>PEAK</td></tr><tr><td>4</td><td>7434.00</td><td>-11.94</td><td>54.00</td><td>-65.94</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>--</td><td>AVERAGE</td></tr></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	41.24	74.00	-32.76	62.58	33.01	11.08	65.88	0.45	--	PEAK	2	4956.00	-14.68	54.00	-68.68	--	--	--	--	--	--	AVERAGE	3	7434.00	43.98	74.00	-30.02	59.24	36.33	13.47	65.46	0.40	--	PEAK	4	7434.00	-11.94	54.00	-65.94	--	--	--	--	--	--	AVERAGE
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																	
1	4956.00	41.24	74.00	-32.76	62.58	33.01	11.08	65.88	0.45	--	PEAK																																																																																
2	4956.00	-14.68	54.00	-68.68	--	--	--	--	--	--	AVERAGE																																																																																
3	7434.00	43.98	74.00	-30.02	59.24	36.33	13.47	65.46	0.40	--	PEAK																																																																																
4	7434.00	-11.94	54.00	-65.94	--	--	--	--	--	--	AVERAGE																																																																																





Mode	12	
	Harmonic	
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz	
ANT	4	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg.	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL
	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 HORIZONTAL	 Site : 03CH16-HY Condition: AVG_54 3m 91280-1522_240328 VERTICAL



Mode	15																																																																																																							
	LF																																																																																																							
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																																							
ANT	4																																																																																																							
Pol.	Horizontal										Vertical																																																																																													
QP/ Peak																																																																																																								
	Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06 HORIZONTAL																																																																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>78.50</td><td>21.54</td><td>40.00</td><td>-18.46</td><td>39.48</td><td>13.31</td><td>1.15</td><td>32.40</td><td>0.00 -- -- Peak</td></tr><tr><td>2</td><td>199.75</td><td>34.13</td><td>43.50</td><td>-9.37</td><td>49.56</td><td>14.99</td><td>1.97</td><td>32.39</td><td>0.00 -- -- Peak</td></tr><tr><td>3</td><td>252.13</td><td>30.59</td><td>46.00</td><td>-15.41</td><td>42.01</td><td>18.75</td><td>2.25</td><td>32.42</td><td>0.00 -- -- Peak</td></tr><tr><td>4</td><td>287.05</td><td>32.47</td><td>46.00</td><td>-13.53</td><td>43.39</td><td>19.05</td><td>2.44</td><td>32.41</td><td>0.00 -- -- Peak</td></tr><tr><td>5</td><td>608.87</td><td>32.30</td><td>46.00</td><td>-13.70</td><td>34.67</td><td>26.45</td><td>3.88</td><td>32.70</td><td>0.00 -- -- Peak</td></tr><tr><td>6</td><td>939.86</td><td>32.21</td><td>46.00</td><td>-13.79</td><td>28.90</td><td>30.39</td><td>4.52</td><td>31.60</td><td>0.00 -- -- Peak</td></tr></table>																Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	78.50	21.54	40.00	-18.46	39.48	13.31	1.15	32.40	0.00 -- -- Peak	2	199.75	34.13	43.50	-9.37	49.56	14.99	1.97	32.39	0.00 -- -- Peak	3	252.13	30.59	46.00	-15.41	42.01	18.75	2.25	32.42	0.00 -- -- Peak	4	287.05	32.47	46.00	-13.53	43.39	19.05	2.44	32.41	0.00 -- -- Peak	5	608.87	32.30	46.00	-13.70	34.67	26.45	3.88	32.70	0.00 -- -- Peak	6	939.86	32.21	46.00	-13.79	28.90	30.39	4.52	31.60
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																															
1	78.50	21.54	40.00	-18.46	39.48	13.31	1.15	32.40	0.00 -- -- Peak																																																																																															
2	199.75	34.13	43.50	-9.37	49.56	14.99	1.97	32.39	0.00 -- -- Peak																																																																																															
3	252.13	30.59	46.00	-15.41	42.01	18.75	2.25	32.42	0.00 -- -- Peak																																																																																															
4	287.05	32.47	46.00	-13.53	43.39	19.05	2.44	32.41	0.00 -- -- Peak																																																																																															
5	608.87	32.30	46.00	-13.70	34.67	26.45	3.88	32.70	0.00 -- -- Peak																																																																																															
6	939.86	32.21	46.00	-13.79	28.90	30.39	4.52	31.60	0.00 -- -- Peak																																																																																															
																																																																																																								
Site : 03CH16-HY Condition: QP 3m CBL6111D&00802N1D01N-06_47020 & 06 VERTICAL																																																																																																								
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>41.64</td><td>32.05</td><td>40.00</td><td>-7.95</td><td>45.10</td><td>18.57</td><td>0.85</td><td>32.47</td><td>0.00 100 329 QP</td></tr><tr><td>2</td><td>198.78</td><td>31.05</td><td>43.50</td><td>-12.45</td><td>46.55</td><td>14.93</td><td>1.96</td><td>32.39</td><td>0.00 -- -- Peak</td></tr><tr><td>3</td><td>251.16</td><td>28.45</td><td>46.00</td><td>-17.55</td><td>39.99</td><td>18.63</td><td>2.25</td><td>32.42</td><td>0.00 -- -- Peak</td></tr><tr><td>4</td><td>285.11</td><td>28.31</td><td>46.00</td><td>-17.69</td><td>39.30</td><td>18.99</td><td>2.43</td><td>32.41</td><td>0.00 -- -- Peak</td></tr><tr><td>5</td><td>737.13</td><td>29.70</td><td>46.00</td><td>-16.30</td><td>30.25</td><td>27.96</td><td>4.06</td><td>32.57</td><td>0.00 -- -- Peak</td></tr><tr><td>6</td><td>947.62</td><td>33.54</td><td>46.00</td><td>-12.46</td><td>29.81</td><td>30.73</td><td>4.54</td><td>31.54</td><td>0.00 -- -- Peak</td></tr></table>																Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	41.64	32.05	40.00	-7.95	45.10	18.57	0.85	32.47	0.00 100 329 QP	2	198.78	31.05	43.50	-12.45	46.55	14.93	1.96	32.39	0.00 -- -- Peak	3	251.16	28.45	46.00	-17.55	39.99	18.63	2.25	32.42	0.00 -- -- Peak	4	285.11	28.31	46.00	-17.69	39.30	18.99	2.43	32.41	0.00 -- -- Peak	5	737.13	29.70	46.00	-16.30	30.25	27.96	4.06	32.57	0.00 -- -- Peak	6	947.62	33.54	46.00	-12.46	29.81	30.73	4.54	31.54	0.00 -- -- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																															
1	41.64	32.05	40.00	-7.95	45.10	18.57	0.85	32.47	0.00 100 329 QP																																																																																															
2	198.78	31.05	43.50	-12.45	46.55	14.93	1.96	32.39	0.00 -- -- Peak																																																																																															
3	251.16	28.45	46.00	-17.55	39.99	18.63	2.25	32.42	0.00 -- -- Peak																																																																																															
4	285.11	28.31	46.00	-17.69	39.30	18.99	2.43	32.41	0.00 -- -- Peak																																																																																															
5	737.13	29.70	46.00	-16.30	30.25	27.96	4.06	32.57	0.00 -- -- Peak																																																																																															
6	947.62	33.54	46.00	-12.46	29.81	30.73	4.54	31.54	0.00 -- -- Peak																																																																																															



Mode	16																																																																																															
	SHF																																																																																															
	2400-2483.5_Bluetooth-LE_ASK_CH76_2478MHz																																																																																															
ANT	4																																																																																															
Pol.	Horizontal						Vertical																																																																																									
Peak																																																																																																
	Site : 03CH16-HY Condition: PEAK_74 1m SHF_00993_231124 HORIZONTAL						Site : 03CH16-HY Condition: PEAK_74 1m SHF_00993_231124 VERTICAL																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24952.97</td><td>39.16</td><td>74.00</td><td>-34.84</td><td>55.62</td><td>39.29</td><td>7.11</td><td>53.32</td><td>-9.54</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	24952.97	39.16	74.00	-34.84	55.62	39.29	7.11	53.32	-9.54	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>24795.16</td><td>38.98</td><td>74.00</td><td>-35.02</td><td>55.59</td><td>39.19</td><td>7.12</td><td>53.38</td><td>-9.54</td><td>--</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	24795.16	38.98	74.00	-35.02	55.59	39.19	7.12	53.38	-9.54	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																						
1	24952.97	39.16	74.00	-34.84	55.62	39.29	7.11	53.32	-9.54	--	PEAK																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Loss Factor	Factor			Remark																																																																																							
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																						
1	24795.16	38.98	74.00	-35.02	55.59	39.19	7.12	53.38	-9.54	--	PEAK																																																																																					



Appendix D. Duty Cycle Plots

<Ant. 3>

**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = $4 * 0.040 / 100 = 0.16\%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -55.92 \text{ dB}$

Duty Cycle Correction Factor Consideration for AFH mode:

The maximum possible ON time:

$$0.040 \text{ ms} \times 4 = 0.16 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(0.16 \text{ ms}/100 \text{ ms}) = -55.92 \text{ dB}$$

**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = $4 * 0.050 / 100 = 0.20\%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -53.98 \text{ dB}$

Duty Cycle Correction Factor Consideration for AFH mode:

The maximum possible ON time:

$$0.040 \text{ ms} \times 5 = 0.2 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(0.2 \text{ ms}/100 \text{ ms}) = -53.98 \text{ dB}$$



<Ant. 4>

**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = $4 * 0.050 / 100 = 0.20 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -53.98 \text{ dB}$

Duty Cycle Correction Factor Consideration for AFH mode:

The maximum possible ON time:

$$0.040 \text{ ms} \times 5 = 0.2 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(0.2 \text{ ms}/100 \text{ ms}) = -53.98 \text{ dB}$$



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $4 \times 0.040 / 100 = 0.16\%$
2. Worst case Duty cycle correction factor = $20 \times \log(\text{Duty cycle}) = -55.92 \text{ dB}$

Duty Cycle Correction Factor Consideration for AFH mode:

The maximum possible ON time:

$$0.040 \text{ ms} \times 4 = 0.16 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(0.16 \text{ ms}/100 \text{ ms}) = -55.92 \text{ dB}$$

————THE END————