

GK470-接收器项目测试报告

GK470 – Receiver Project Test Report

Antenna Test Report V1.0

RF: 吕杰 (Jie Lv)

电话 (Mobile phone) : 13530413724

日期 (Date) : 2026.05.12

地址 (location) : 深圳市宝安区石岩街道宝源社区奋达科技园二期2号楼
306 (Room 306, Building 2, Phase II, Fenda Technology Park,
Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen City)

@深圳市大泽无线技术有限公司
Shenzhen Daze Wireless Technology Co., Ltd

历史版本 (Revision History)

Version:	Date:	Summary of content:
V1.0	2026.05.12	天线测试报告 (Antenna Test Report)

目录 (Catalogue)

01 项目概况 (Project Overview)

02 测试环境 (Test Environment)

03 天线图片和位置 (Antenna picture and position)

04 天线环境处理 (Antenna environment processing)

05 无源测试 (Passive test)

06 有源测试 (Active test)

07 建议和总结: (Recommendations and Summary:)

项目概况 (Project Overview)


客户名称 Customer Name		项目名 Project Name	天线数目 Antenna Number	天线类型 Antenna Type
川东		GK470-接收器	1	板载天线 (onboard antenna)
天线频段 Frequency Bands				
WIFI		/		
BT	✓	2400-2500MHz		
GNSS		/		
NB		/		
2G		/		
3G		/		
4G		/		
5G		/		

测试标准 (Testing standard)

Name	Parameter	Method	Standard no.
Antenna performance	Radiation efficiency	IEEE Standard Test Procedures for Antennas	ANSIIEEE Std149-2021



测试环境 (Test Environment)

Test Equipment	Agilent E5071B 300 kHz - 8.5 GHz
Test System	SY-24M SISO/MIMO, 400 - 8500MHz




Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Network Analyzer	Agilent	E5071B	—	2025.11.13	2026.11.12
Chamber	Sunyield	SY-24S	—	—	—


测试环境 (Test Environment)



天线图片和位置 (Antenna picture and position)



无源测试：驻波比 (Passive test: VSWR)






无源测试：效率和增益 (Passive test: Efficiency&Gain)




frequency 频率(MHz)	gain 增益(dBi)	efficiency 效率(dB)	efficiency 效率(%)
2400.00	-1.50	-5.23	29.97
2410.00	-1.28	-5.19	30.28
2420.00	-1.57	-5.29	29.57
2430.00	-2.14	-5.39	28.87
2440.00	-1.94	-5.41	28.80
2450.00	-2.03	-5.65	27.22
2460.00	-1.89	-5.66	27.15
2470.00	-1.60	-5.74	26.64
2480.00	-1.98	-6.20	23.99
2490.00	-2.47	-6.67	21.54
2500.00	-2.66	-6.78	21.00

方向图 (Directional diagram)




2400MHz




2450MHz



2500MHz



匹配电路 (Matching circuit)



E1	E2	E3
NA	NA	NA

匹配参数使用原始状态，未进行修改。
(The matching parameters are in their original state and have not been modified.)

建议和总结: (Recommendations and Summary:)

如上为GK470-接收器项目测试报告, 如上请客户评估, 谢谢!
(The above is the test report for the GK470-receiver project.
Please have the customer review it. Thank you!)

