

**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 Issue 4**

TEST REPORT

For

Lenovo Open-Ear Clip-on Earbuds X500

MODEL NUMBER: OW1405

REPORT NUMBER: 4792034137-3-RF-1

ISSUE DATE: January 9, 2026

**FCC ID: A5MOW1405
IC ID: 5903G-OW1405**

Prepared for

**FCC: LENOVO (BEIJING) LTD
IC: LENOVO CHINA**

**FCC Address: 201-H2-6, Floor 2, Building 2, No.6 Shangdi West Road, Haidian
District, Beijing, China**

**IC Address: No.6 Chuang Ye Road, Shangdi Information Industry Haidan District,
Beijing 100085 China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

**Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan,
Guangdong, China**

**Tel: +86 769 22038881
Fax: +86 769 33244054
Website: www.ul.com**

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	January 9, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC 15.203 RSS-GEN Clause 6.8	Pass
AC Power Line Conducted Emission	ANSI C63.10-2020 Clause 6.2	FCC Part 15.207	N/A
Conducted Output Power	ANSI C63.10-2020 Clause 7.8.5	FCC 15.247 (b) (1) RSS-247 Clause 6.2.3.2	Pass
20 dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2020 Clause 6.9.2 & 6.9.3	FCC 15.247 (a) (1) RSS-247 Clause 6.2.3.1 (a) RSS-Gen Clause 6.7	Pass
Carrier Hopping Channel Separation	ANSI C63.10-2020 Clause 7.8.2	FCC 15.247 (a) (1) RSS-247 Clause 6.2.3.1 (a)	Pass
Number of Hopping Frequency	ANSI C63.10-2020 Clause 7.8.3	15.247 (a) (1) III RSS-247 Clause 6.2.3.1 (b)	Pass
Time of Occupancy (Dwell Time)	ANSI C63.10-2020 Clause 7.8.4	15.247 (a) (1) III RSS-247 Clause 6.2.3.1 (b)	Pass
Conducted Bandedge and Spurious Emission	ANSI C63.10-2020 Clause 6.10.4 & Clause 7.8.7	FCC 15.247 (d) RSS-247 Clause 6.6	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2020 Clause 6.4 & 6.5 & 6.6 & 7.8.8	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 6.6 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	Pass
Duty Cycle	ANSI C63.10-2020, Clause 11.6	None; for reporting purposes only.	Pass

Note:

1. N/A: In this whole report not applicable.
2. For ISED, this report is also performed according to ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 standards.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C

ISED RSS-247 Issue 4> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	9
4.1. MEASURING INSTRUMENT CALIBRATION	9
4.2. MEASUREMENT UNCERTAINTY	9
5. EQUIPMENT UNDER TEST	10
5.1. DESCRIPTION OF EUT	10
5.2. CHANNEL LIST	10
5.3. MAXIMUM POWER	10
5.4. TEST CHANNEL CONFIGURATION	11
5.5. THE WORSE CASE POWER SETTING PARAMETER	11
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.7. SUPPORT UNITS FOR SYSTEM TEST	13
6. MEASURING EQUIPMENT AND SOFTWARE USED	14
7. ANTENNA PORT TEST RESULTS	17
7.1. CONDUCTED OUTPUT POWER	17
7.2. 20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH	18
7.3. CARRIER HOPPING CHANNEL SEPARATION	20
7.4. NUMBER OF HOPPING FREQUENCY	22
7.5. TIME OF OCCUPANCY (DWELL TIME)	24
7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSION	26
7.7. DUTY CYCLE	28
8. RADIATED TEST RESULTS	29
8.1. RESTRICTED BANDEDGE-LEFT	37
8.2. RESTRICTED BANDEDGE-RIGHT	42
8.3. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-LEFT	47
8.4. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-RIGHT	53
8.5. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-LEFT	59
8.6. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-RIGHT	71
8.7. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-LEFT	83
8.8. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-RIGHT	85

8.9.	SPURIOUS EMISSIONS(9 KHZ~30 MHZ)	87
8.10.	SPURIOUS EMISSIONS(30 MHZ~1 GHZ)	90
9.	ANTENNA REQUIREMENT	92
10.	TEST DATA-Left.....	93
10.1.	APPENDIX A: 20DB EMISSION BANDWIDTH.....	93
10.1.1.	Test Result	93
10.1.2.	Test Graphs	94
10.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	96
10.2.1.	Test Result	96
10.2.2.	Test Graphs	97
10.3.	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	99
10.3.1.	Test Result	99
10.4.	APPENDIX D: CARRIER FREQUENCY SEPARATION	100
10.4.1.	Test Result	100
10.4.2.	Test Graphs	100
10.5.	APPENDIX E: TIME OF OCCUPANCY	101
10.5.1.	Test Result	101
10.5.2.	Test Graphs	102
10.6.	APPENDIX F: NUMBER OF HOPPING CHANNELS	104
10.6.1.	Test Result	104
10.6.2.	Test Graphs	104
10.7.	APPENDIX G: BAND EDGE MEASUREMENTS	105
10.7.1.	Test Result	105
10.7.2.	Test Graphs	106
10.8.	APPENDIX H: CONDUCTED SPURIOUS EMISSION.....	109
10.8.1.	Test Result	109
10.8.2.	Test Graphs	110
10.9.	APPENDIX I: DUTY CYCLE.....	116
10.9.1.	Test Result	116
10.9.2.	Test Graphs	116
11.	TEST DATA-Right.....	117
11.1.	APPENDIX A: 20DB EMISSION BANDWIDTH.....	117
11.1.1.	Test Result	117
11.1.2.	Test Graphs	118
11.2.	APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	120
11.2.1.	Test Result	120
11.2.2.	Test Graphs	121
11.3.	APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	123
11.3.1.	Test Result	123
11.4.	APPENDIX D: CARRIER FREQUENCY SEPARATION	124
11.4.1.	Test Result	124
11.4.2.	Test Graphs	124

11.5.	<i>APPENDIX E: TIME OF OCCUPANCY</i>	<i>125</i>
11.5.1.	Test Result	125
11.5.2.	Test Graphs	126
11.6.	<i>APPENDIX F: NUMBER OF HOPPING CHANNELS</i>	<i>128</i>
11.6.1.	Test Result	128
11.6.2.	Test Graphs	128
11.7.	<i>APPENDIX G: BAND EDGE MEASUREMENTS</i>	<i>129</i>
11.7.1.	Test Result	129
11.7.2.	Test Graphs	130
11.8.	<i>APPENDIX H: CONDUCTED SPURIOUS EMISSION.....</i>	<i>133</i>
11.8.1.	Test Result	133
11.8.2.	Test Graphs	134
11.9.	<i>APPENDIX I: DUTY CYCLE.....</i>	<i>140</i>
11.9.1.	Test Result	140
11.9.2.	Test Graphs	140

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: FCC: LENOVO (BEIJING) LTD
IC: LENOVO CHINA
Address: FCC Address: 201-H2-6, Floor 2, Building 2, No.6 Shangdi West Road, Haidian District, Beijing, China
IC Address: No.6 Chuang Ye Road, Shangdi Information Industry Haidan District, Beijing 100085 China

Manufacturer Information

Company Name: FCC: LENOVO (BEIJING) LTD
IC: LENOVO CHINA
Address: FCC Address: 201-H2-6, Floor 2, Building 2, No.6 Shangdi West Road, Haidian District, Beijing, China
IC Address: No.6 Chuang Ye Road, Shangdi Information Industry Haidan District, Beijing 100085 China

EUT Information

EUT Name: Lenovo Open-Ear Clip-on Earbuds X500
Model: OW1405
Brand: Lenovo
Sample Received Date: December 16, 2025
Sample Status: Normal
Sample ID: 9234019
Date of Tested: December 16, 2025 to January 9, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C ISED RSS-247 Issue 4	Pass


Prepared By:



Johnson Liu

Laboratory Engineer


Checked By:



Fanny Huang

Project Engineer

Approved By:



Kebo Zhang

Operations Leader

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C ISSED RSS-247 Issue 4, KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2020, ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024 and ISSED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: C-20202, G-20240, R-20248 and T-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber E, the VCCI registration No. is G-20240 and R-20248 Shielding Room F, the VCCI registration No. is C-20202 and T-20202
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Room 101, Building 2, No.4, Information Road, Songshan Lake, Dongguan, Guangdong, China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
20dB Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Carrier Frequency Separation	±1.9%
Maximum Conducted Output Power	±0.743 dB
Number of Hopping Channel	±1.9%
Time of Occupancy	±0.028%
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Lenovo Open-Ear Clip-on Earbuds X500
Model	OW1405

Frequency Range:	2402 MHz to 2480 MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Type of Modulation:	GFSK, $\Pi/4$ DQPSK
Normal Test Voltage:	DC 3.7V 50mAh

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

5.3. MAXIMUM POWER

Right:

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
GFSK	2402 ~ 2480	0-78[79]	3.55
$\Pi/4$ -DQPSK	2402 ~ 2480	0-78[79]	4.48

Left:

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
GFSK	2402 ~ 2480	0-78[79]	3.81
$\Pi/4$ -DQPSK	2402 ~ 2480	0-78[79]	4.64

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
GFSK-DH5	CH 00(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
$\pi/4$ -DQPSK-2DH5	CH 00(Low Channel), CH 39(MID Channel), CH 78(High Channel)	2402 MHz, 2441 MHz, 2480 MHz
GFSK-DH5	Hopping	
$\pi/4$ -DQPSK-2DH5	Hopping	

PACKET TYPE CONFIGURATION

Test Mode	Packet Type	Setting (Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
$\pi/4$ -DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679

5.5. THE WORSE CASE POWER SETTING PARAMETER

WORST-CASE CONFIGURATIONS

Bluetooth Mode	Modulation Technology	Modulation Type	Data Rate (Mbps)
BR	FHSS	GFSK	1Mbit/s
EDR	FHSS	$\pi/4$ -DQPSK	2Mbit/s

Note: Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates.

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		FCC_assist_V1.0.4		
Modulation Type	Transmit Antenna	Test Software setting value		
		CH 00	CH 39	CH 78
GFSK	Left/Right	5	5	5
$\pi/4$ -DQPSK	Left/Right	5	5	5

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
Left	2402-2480	PCB	-0.6
Right	2402-2480	PCB	-1.1

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
$\pi/4$ -DQPSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5.7. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remark
1	PC	Lenovo	E14	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	/	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Dec.27,2024	Dec.26,2025
Power sensor, Power Meter	R&S	OSP120	100921	Dec.26,2025	Dec.25,2026
Vector Signal Generator	R&S	SMBV100A	261637	Sep.12, 2025	Sep.11, 2026
Signal Generator	R&S	SMB100A	178553	Sep.12, 2025	Sep.11, 2026
Signal Analyzer	R&S	FSV40	101118	Sep.12, 2025	Sep.11, 2026
Software					
Description		Manufacturer		Name	Version
For R&S TS 8997 Test System		Rohde & Schwarz		EMC 32	10.60.10
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.12, 2025	Sep.11, 2026
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Sep.12, 2025	Sep.11, 2026
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Sep.12, 2025	Sep.11, 2026
DC power supply	TSSTAKASAGO	ZX-400L	409150160137	Sep.12, 2025	Sep.11, 2026
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Sep.12, 2025	Sep.11, 2026
Attenuator	Aglient	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.27,2024	Dec.26,2025
RF Control Unit	Tonscend	JS0806-2	23B80620666	Dec.26,2025	Dec.25,2026
Software					
Description	Manufacturer	Name			Version
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System			V3.2.22

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Sep.12, 2025	Sep.11, 2026
Two-Line V-Network	R&S	ENV216	101983	Sep.12, 2025	Sep.11, 2026
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Sep.12, 2025	Sep.11, 2026
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Sep.12, 2025	Sep.11, 2026
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	June 28, 2024	June.27 2027
Preamplifier	HP	8447D	2944A09099	Sep.12, 2025	Sep.11, 2026
EMI Measurement Receiver	R&S	ESR26	101377	Sep.12, 2025	Sep.11, 2026
Horn Antenna	TDK	HRN-0118	130940	Dec.10, 2024	Dec.11, 2027
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Sep.12, 2025	Sep.11, 2026
Horn Antenna	Schwarzbeck	BBHA9170	697	Jun 30, 2024	Jun 29, 2027
Preamplifier	TDK	PA-02-2	TRS-307-00003	Sep.12, 2025	Sep.11, 2026
Preamplifier	TDK	PA-02-3	TRS-308-00002	Sep.12, 2025	Sep.11, 2026
Loop antenna	Schwarzbeck	1519B	00008	Dec.09, 2024	Dec.08, 2027
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Sep.12, 2025	Sep.11, 2026
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Sep.12, 2025	Sep.11, 2026
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Sep.16, 2025	Sep.15, 2026
Barometer	Yiyi	Baro	N/A	Sep.19, 2025	Sep.18, 2026
Attenuator	Agilent	8495B	2814a12853	Sep.12, 2025	Sep.11, 2026

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (b) (1) ISED RSS-247 Clause 6.2.3.2	Peak Conducted Output Power	Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel: 1 watt or 30 dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel: 125 mW or 21 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	20.7°C	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix C

7.2. 20 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) RSS-247 Clause 6.2.3.1 (a)	20 dB Bandwidth	None; for reporting purposes only.	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 6.9.

Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20 dB Bandwidth: 1 % to 5 % of the 20 dB bandwidth For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 20 dB Bandwidth: approximately 3×RBW For 99 % Occupied Bandwidth: ≥ 3×RBW
Span	Between 2 times and 5.0 times the OBW
Trace	Max hold
Sweep	Auto couple

a) Use the occupied bandwidth function of the instrument, allow the trace to stabilize and report the measured 99 % occupied bandwidth and 20 dB Bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	20.7°C	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B

7.3. CARRIER HOPPING CHANNEL SEPARATION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1) ISED RSS-247 Clause 6.2.3.1 (a)	Carrier Frequency Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 7.8.2.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥RBW
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Allow the trace to stabilize and use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

TEST SETUP



TEST ENVIRONMENT

Temperature	20.7°C	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. NUMBER OF HOPPING FREQUENCY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 6.2.3.1 (b)	Number of Hopping Frequency	at least 15 hopping channels

TEST PROCEDURE


Refer to ANSI C63.10-2020 clause 7.8.3.

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
Trace	Max hold
Sweep time	No faster than coupled (auto) time

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer, count the quantity of peaks to get the number of hopping channels.

TEST SETUP



TEST ENVIRONMENT

Temperature	20.7℃	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix F

7.5. TIME OF OCCUPANCY (DWELL TIME)

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III ISED RSS-247 Clause 6.2.3.1 (b)	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 7.8.4.

Connect the EUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected transmission time per hop
VBW	$\geq$ RBW
Span	Zero span, centered on a hopping channel
Trace	Clear-write, single sweep
Sweep time	Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this

Use the marker-delta function to determine the transmit time per hop (Burst Width). If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

For FHSS Mode (79 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (1600/2) * 31.6 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (1600/4) * 31.6 / (\text{channel number})$


DH5/3DH5 Dwell Time: $\text{Burst Width} * (1600/6) * 31.6 / (\text{channel number})$

For AFHSS Mode (20 Channel):

DH1/3DH1 Dwell Time: $\text{Burst Width} * (800/2) * 8 / (\text{channel number})$

DH3/3DH3 Dwell Time: $\text{Burst Width} * (800/4) * 8 / (\text{channel number})$

DH5/3DH5 Dwell Time: $\text{Burst Width} * (800/6) * 8 / (\text{channel number})$

TEST SETUP**TEST ENVIRONMENT**

Temperature	20.7℃	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.6. CONDUCTED BANDEDGE AND SPURIOUS EMISSION

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 4		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 6.6	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 7.8.7.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x 20dB bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum

TEST SETUP**TEST ENVIRONMENT**

Temperature	20.7℃	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix G&H

7.7. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2020 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	20.7°C	Relative Humidity	55.9%
Atmosphere Pressure	101kPa	Test Voltage	DC 3.7V

TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Eason He
-----------	-----------------	---------	----------

TEST RESULTS

Please refer to section "Test Data" - Appendix I

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3280 - 3287	
16.42 - 16.423	3332 - 3339	
16.60475 - 16.60525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5480	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.7. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.7.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.7.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.7.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1GHz



TEST ENVIRONMENT

Temperature	20.3℃	Relative Humidity	57.3%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	January 8, 2026	Test By	Stipe Zheng
-----------	-----------------	---------	-------------

TEST RESULTS


8.1. RESTRICTED BANDEDGE-LEFT

Test Mode:	GFSK PK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2316.100	17.70	31.63	49.33	74.00	-24.67	peak
2	2390.000	15.73	31.99	47.72	74.00	-26.28	peak

Test Mode:	GFSK PK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.900	17.01	31.88	48.89	74.00	-25.11	peak
2	2390.000	15.44	31.99	47.43	74.00	-26.57	peak

Test Mode:	GFSK PK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.96	32.35	50.31	74.00	-23.69	peak
2	2483.900	18.54	32.35	50.89	74.00	-23.11	peak

Test Mode:	$\Pi/4$ -DQPSK PK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2371.400	16.85	31.90	48.75	74.00	-25.25	peak
2	2390.000	15.72	31.99	47.71	74.00	-26.29	peak


Test Mode:	$\Pi/4$ -DQPSK PK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	18.67	32.35	51.02	74.00	-22.98	peak
2	2483.750	19.00	32.35	51.35	74.00	-22.65	peak


8.2. RESTRICTED BANDEDGE-RIGHT

Test Mode:	GFSK PK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2388.500	16.61	31.98	48.59	74.00	-25.41	peak
2	2390.000	15.64	31.99	47.63	74.00	-26.37	peak

Test Mode:	GFSK PK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2362.000	16.84	31.85	48.69	74.00	-25.31	peak
2	2390.000	15.30	31.99	47.29	74.00	-26.71	peak

Test Mode:	GFSK PK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.92	32.35	50.27	74.00	-23.73	peak
2	2483.650	18.80	32.35	51.15	74.00	-22.85	peak

Test Mode:	Pi	Frequency(MHz):	4
Test Voltage:	2402		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2366.400	16.81	31.88	48.69	74.00	-25.31	peak
2	2390.000	15.55	31.99	47.54	74.00	-26.46	peak


Test Mode:	Pi	Frequency(MHz):	4
Test Voltage:	2480		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	17.78	32.35	50.13	74.00	-23.87	peak
2	2483.625	18.88	32.35	51.23	74.00	-22.77	peak


8.3. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-LEFT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1116.000	52.62	-13.39	39.23	74.00	-34.77	peak
2	1514.000	47.86	-11.59	36.27	74.00	-37.73	peak
3	2210.000	48.74	-9.66	39.08	74.00	-34.92	peak
4	2354.000	48.87	-8.74	40.13	74.00	-33.87	peak
5	2402.000	47.59	-8.46	39.13	/	/	Fundamental
6	2594.000	55.48	-7.55	47.93	74.00	-26.07	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1020.000	50.07	-13.81	36.26	74.00	-37.74	peak
2	1428.000	47.95	-11.96	35.99	74.00	-38.01	peak
3	1908.000	46.63	-10.12	36.51	74.00	-37.49	peak
4	2402.000	51.47	-8.46	43.01	/	/	Fundamental
5	2594.000	51.02	-7.55	43.47	74.00	-30.53	peak
6	2978.000	44.89	-6.13	38.76	74.00	-35.24	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1114.000	51.24	-13.39	37.85	74.00	-36.15	peak
2	1678.000	46.71	-11.02	35.69	74.00	-38.31	peak
3	2250.000	49.96	-9.40	40.56	74.00	-33.44	peak
4	2441.000	47.43	-8.26	39.17	/	/	Fundamental
5	2634.000	54.08	-7.41	46.67	74.00	-27.33	peak
6	2826.000	46.92	-6.71	40.21	74.00	-33.79	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1068.000	48.87	-13.60	35.27	74.00	-38.73	peak
2	1478.000	47.34	-11.74	35.60	74.00	-38.40	peak
3	1740.000	46.76	-10.81	35.95	74.00	-38.05	peak
4	2250.000	47.94	-9.40	38.54	74.00	-35.46	peak
5	2476.000	45.51	-8.10	37.41	74.00	-36.59	peak
6	2634.000	47.03	-7.41	39.62	74.00	-34.38	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1116.000	51.62	-13.39	38.23	74.00	-35.77	peak
2	1620.000	46.67	-11.22	35.45	74.00	-38.55	peak
3	2288.000	52.13	-9.17	42.96	74.00	-31.04	peak
4	2480.000	48.40	-8.08	40.32	/	/	Fundamental
5	2672.000	53.77	-7.27	46.50	74.00	-27.50	peak
6	2864.000	47.38	-6.57	40.81	74.00	-33.19	peak


Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1236.000	47.41	-12.85	34.56	74.00	-39.44	peak
2	1612.000	46.79	-11.25	35.54	74.00	-38.46	peak
3	1788.000	46.65	-10.64	36.01	74.00	-37.99	peak
4	2288.000	47.92	-9.17	38.75	74.00	-35.25	peak
5	2480.000	46.51	-8.08	38.43	/	/	Fundamental
6	2672.000	46.15	-7.27	38.88	74.00	-35.12	peak


8.4. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)-RIGHT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1164.000	54.19	-13.17	41.02	74.00	-32.98	peak
2	1728.000	47.17	-10.85	36.32	74.00	-37.68	peak
3	1962.000	46.68	-9.88	36.80	74.00	-37.20	peak
4	2402.000	47.85	-8.46	39.39	/	/	Fundamental
5	2594.000	58.19	-7.55	50.64	74.00	-23.36	peak
6	2786.000	49.31	-6.86	42.45	74.00	-31.55	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1020.000	51.21	-13.81	37.40	74.00	-36.60	peak
2	1664.000	47.16	-11.06	36.10	74.00	-37.90	peak
3	2210.000	47.35	-9.66	37.69	74.00	-36.31	peak
4	2402.000	52.45	-8.46	43.99	/	/	Fundamental
5	2594.000	57.73	-7.55	50.18	74.00	-23.82	peak
6	2786.000	49.74	-6.86	42.88	74.00	-31.12	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1020.000	51.48	-13.81	37.67	74.00	-36.33	peak
2	1428.000	48.99	-11.96	37.03	74.00	-36.97	peak
3	2250.000	50.14	-9.40	40.74	74.00	-33.26	peak
4	2441.000	50.16	-8.26	41.90	/	/	Fundamental
5	2634.000	57.29	-7.41	49.88	74.00	-24.12	peak
6	2826.000	49.40	-6.71	42.69	74.00	-31.31	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1020.000	51.25	-13.81	37.44	74.00	-36.56	peak
2	1404.000	47.92	-12.07	35.85	74.00	-38.15	peak
3	1910.000	47.16	-10.11	37.05	74.00	-36.95	peak
4	2441.000	47.88	-8.26	39.62	/	/	Fundamental
5	2634.000	57.96	-7.41	50.55	74.00	-23.45	peak
6	2826.000	49.70	-6.71	42.99	74.00	-31.01	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1188.000	50.97	-13.06	37.91	74.00	-36.09	peak
2	1586.000	46.86	-11.34	35.52	74.00	-38.48	peak
3	1914.000	46.32	-10.09	36.23	74.00	-37.77	peak
4	2288.000	49.11	-9.17	39.94	74.00	-34.06	peak
5	2480.000	49.76	-8.08	41.68	/	/	Fundamental
6	2672.000	52.29	-7.27	45.02	74.00	-28.98	peak


Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1244.000	47.82	-12.81	35.01	74.00	-38.99	peak
2	1476.000	48.35	-11.75	36.60	74.00	-37.40	peak
3	1960.000	46.34	-9.89	36.45	74.00	-37.55	peak
4	2480.000	48.91	-8.08	40.83	/	/	Fundamental
5	2672.000	57.97	-7.27	50.70	74.00	-23.30	peak
6	2864.000	49.36	-6.57	42.79	74.00	-31.21	peak


8.5. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-LEFT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	46.75	0.19	46.94	74.00	-27.06	peak
2	7290.000	36.67	6.67	43.34	74.00	-30.66	peak
3	10545.000	33.83	14.16	47.99	74.00	-26.01	peak
4	12360.000	28.90	18.91	47.81	74.00	-26.19	peak
5	13875.000	26.45	23.59	50.04	74.00	-23.96	peak
6	18000.000	22.90	27.98	50.88	74.00	-23.12	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.28	0.19	43.47	74.00	-30.53	peak
2	6735.000	38.20	5.14	43.34	74.00	-30.66	peak
3	9645.000	35.76	11.55	47.31	74.00	-26.69	peak
4	11025.000	32.35	15.44	47.79	74.00	-26.21	peak
5	13935.000	25.98	23.81	49.79	74.00	-24.21	peak
6	17850.000	22.57	27.04	49.61	74.00	-24.39	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	45.36	0.35	45.71	74.00	-28.29	peak
2	7320.000	36.96	6.64	43.60	74.00	-30.40	peak
3	9765.000	36.30	12.09	48.39	74.00	-25.61	peak
4	11415.000	31.08	16.55	47.63	74.00	-26.37	peak
5	13950.000	26.04	23.87	49.91	74.00	-24.09	peak
6	17895.000	23.34	27.32	50.66	74.00	-23.34	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.18	0.35	42.53	74.00	-31.47	peak
2	7305.000	36.96	6.65	43.61	74.00	-30.39	peak
3	9765.000	35.72	12.09	47.81	74.00	-26.19	peak
4	12360.000	28.32	18.91	47.23	74.00	-26.77	peak
5	13830.000	25.61	23.41	49.02	74.00	-24.98	peak
6	17880.000	22.46	27.23	49.69	74.00	-24.31	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	46.18	0.51	46.69	74.00	-27.31	peak
2	7320.000	37.02	6.64	43.66	74.00	-30.34	peak
3	9915.000	37.66	12.42	50.08	74.00	-23.92	peak
4	12840.000	27.79	19.52	47.31	74.00	-26.69	peak
5	13635.000	26.52	22.84	49.36	74.00	-24.64	peak
6	17925.000	22.00	27.50	49.50	74.00	-24.50	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	41.77	0.51	42.28	74.00	-31.72	peak
2	6900.000	37.57	5.67	43.24	74.00	-30.76	peak
3	9915.000	35.85	12.42	48.27	74.00	-25.73	peak
4	12765.000	27.84	19.43	47.27	74.00	-26.73	peak
5	13860.000	25.90	23.52	49.42	74.00	-24.58	peak
6	17985.000	22.10	27.88	49.98	74.00	-24.02	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	46.68	0.19	46.87	74.00	-27.13	peak
2	7290.000	36.84	6.67	43.51	74.00	-30.49	peak
3	9600.000	36.73	11.35	48.08	74.00	-25.92	peak
4	11520.000	31.52	16.89	48.41	74.00	-25.59	peak
5	13785.000	27.16	23.24	50.40	74.00	-23.60	peak
6	18000.000	22.49	27.98	50.47	74.00	-23.53	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.03	0.19	43.22	74.00	-30.78	peak
2	6810.000	38.38	5.38	43.76	74.00	-30.24	peak
3	9840.000	34.55	12.31	46.86	74.00	-27.14	peak
4	11040.000	34.53	15.49	50.02	74.00	-23.98	peak
5	13905.000	26.06	23.69	49.75	74.00	-24.25	peak
6	17820.000	23.29	26.84	50.13	74.00	-23.87	peak

Test Mode:	Π/4-DQPSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4890.000	44.98	0.38	45.36	74.00	-28.64	peak
2	7305.000	36.66	6.65	43.31	74.00	-30.69	peak
3	9765.000	36.16	12.09	48.25	74.00	-25.75	peak
4	11100.000	32.82	15.70	48.52	74.00	-25.48	peak
5	13770.000	27.42	23.22	50.64	74.00	-23.36	peak
6	17895.000	23.02	27.32	50.34	74.00	-23.66	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	41.98	0.35	42.33	74.00	-31.67	peak
2	7320.000	36.34	6.64	42.98	74.00	-31.02	peak
3	9765.000	36.79	12.09	48.88	74.00	-25.12	peak
4	11475.000	30.93	16.74	47.67	74.00	-26.33	peak
5	13950.000	26.37	23.87	50.24	74.00	-23.76	peak
6	17835.000	22.86	26.94	49.80	74.00	-24.20	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	45.16	0.51	45.67	74.00	-28.33	peak
2	6915.000	37.77	5.73	43.50	74.00	-30.50	peak
3	9915.000	38.79	12.42	51.21	74.00	-22.79	peak
4	9915.000	35.24	12.42	47.66	54.00	-6.34	AVG
5	12405.000	28.24	18.97	47.21	74.00	-26.79	peak
6	13905.000	25.94	23.69	49.63	74.00	-24.37	peak
7	17940.000	23.00	27.61	50.61	74.00	-23.39	peak


Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5895.000	40.06	2.34	42.40	74.00	-31.60	peak
2	7935.000	36.64	7.80	44.44	74.00	-29.56	peak
3	9915.000	36.26	12.42	48.68	74.00	-25.32	peak
4	11265.000	33.12	16.18	49.30	74.00	-24.70	peak
5	13890.000	26.44	23.64	50.08	74.00	-23.92	peak
6	17805.000	23.17	26.75	49.92	74.00	-24.08	peak


8.6. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)-RIGHT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	42.97	0.19	43.16	74.00	-30.84	peak
2	7290.000	36.70	6.67	43.37	74.00	-30.63	peak
3	9600.000	37.56	11.35	48.91	74.00	-25.09	peak
4	11475.000	30.89	16.74	47.63	74.00	-26.37	peak
5	13635.000	26.86	22.84	49.70	74.00	-24.30	peak
6	17865.000	23.33	27.13	50.46	74.00	-23.54	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.17	0.19	43.36	74.00	-30.64	peak
2	7200.000	37.83	6.75	44.58	74.00	-29.42	peak
3	9600.000	37.03	11.35	48.38	74.00	-25.62	peak
4	11490.000	30.86	16.79	47.65	74.00	-26.35	peak
5	13980.000	25.67	23.98	49.65	74.00	-24.35	peak
6	18000.000	22.22	27.98	50.20	74.00	-23.80	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.26	0.35	43.61	74.00	-30.39	peak
2	7320.000	37.56	6.64	44.20	74.00	-29.80	peak
3	9765.000	35.50	12.09	47.59	74.00	-26.41	peak
4	11040.000	30.94	15.49	46.43	74.00	-27.57	peak
5	13830.000	26.78	23.41	50.19	74.00	-23.81	peak
6	17985.000	21.54	27.88	49.42	74.00	-24.58	peak

Test Mode:	GFSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.20	0.35	43.55	74.00	-30.45	peak
2	7320.000	38.02	6.64	44.66	74.00	-29.34	peak
3	9765.000	36.81	12.09	48.90	74.00	-25.10	peak
4	12540.000	27.96	19.18	47.14	74.00	-26.86	peak
5	13935.000	25.51	23.81	49.32	74.00	-24.68	peak
6	17865.000	22.96	27.13	50.09	74.00	-23.91	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	42.23	0.51	42.74	74.00	-31.26	peak
2	6900.000	38.90	5.67	44.57	74.00	-29.43	peak
3	9915.000	35.98	12.42	48.40	74.00	-25.60	peak
4	11565.000	29.52	17.03	46.55	74.00	-27.45	peak
5	13965.000	25.68	23.93	49.61	74.00	-24.39	peak
6	17850.000	23.15	27.04	50.19	74.00	-23.81	peak

Test Mode:	GFSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	44.36	0.51	44.87	74.00	-29.13	peak
2	7275.000	37.14	6.69	43.83	74.00	-30.17	peak
3	9915.000	36.23	12.42	48.65	74.00	-25.35	peak
4	10680.000	32.74	14.53	47.27	74.00	-26.73	peak
5	13935.000	26.08	23.81	49.89	74.00	-24.11	peak
6	17955.000	21.74	27.69	49.43	74.00	-24.57	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	42.62	0.19	42.81	74.00	-31.19	peak
2	7305.000	36.24	6.65	42.89	74.00	-31.11	peak
3	9600.000	37.71	11.35	49.06	74.00	-24.94	peak
4	10650.000	33.13	14.44	47.57	74.00	-26.43	peak
5	13830.000	26.08	23.41	49.49	74.00	-24.51	peak
6	18000.000	21.90	27.98	49.88	74.00	-24.12	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4800.000	43.07	0.19	43.26	74.00	-30.74	peak
2	7200.000	36.80	6.75	43.55	74.00	-30.45	peak
3	9600.000	37.94	11.35	49.29	74.00	-24.71	peak
4	11490.000	31.70	16.79	48.49	74.00	-25.51	peak
5	13875.000	26.91	23.59	50.50	74.00	-23.50	peak
6	17895.000	22.85	27.32	50.17	74.00	-23.83	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2441
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.89	0.35	43.24	74.00	-30.76	peak
2	7320.000	36.74	6.64	43.38	74.00	-30.62	peak
3	9765.000	36.72	12.09	48.81	74.00	-25.19	peak
4	11535.000	30.60	16.93	47.53	74.00	-26.47	peak
5	13695.000	26.19	23.00	49.19	74.00	-24.81	peak
6	17865.000	22.46	27.13	49.59	74.00	-24.41	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2441
Polarity:	Vertical	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	43.10	0.35	43.45	74.00	-30.55	peak
2	7320.000	38.16	6.64	44.80	74.00	-29.20	peak
3	9765.000	36.89	12.09	48.98	74.00	-25.02	peak
4	10695.000	32.70	14.57	47.27	74.00	-26.73	peak
5	13695.000	26.74	23.00	49.74	74.00	-24.26	peak
6	17865.000	23.15	27.13	50.28	74.00	-23.72	peak

Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2480
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	43.09	0.51	43.60	74.00	-30.40	peak
2	7305.000	36.83	6.65	43.48	74.00	-30.52	peak
3	9915.000	37.22	12.42	49.64	74.00	-24.36	peak
4	11970.000	29.90	18.19	48.09	74.00	-25.91	peak
5	13845.000	26.65	23.46	50.11	74.00	-23.89	peak
6	17940.000	22.46	27.61	50.07	74.00	-23.93	peak


Test Mode:	$\Pi/4$ -DQPSK	Frequency(MHz):	2480
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	44.46	0.51	44.97	74.00	-29.03	peak
2	7320.000	36.46	6.64	43.10	74.00	-30.90	peak
3	9915.000	36.38	12.42	48.80	74.00	-25.20	peak
4	12360.000	29.54	18.91	48.45	74.00	-25.55	peak
5	13695.000	27.29	23.00	50.29	74.00	-23.71	peak
6	17925.000	22.52	27.50	50.02	74.00	-23.98	peak


8.7. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-LEFT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18168.000	50.76	-5.50	45.26	74.00	-28.74	peak
2	19968.000	50.48	-5.42	45.06	74.00	-28.94	peak
3	21664.000	50.15	-4.45	45.70	74.00	-28.30	peak
4	23008.000	49.25	-3.44	45.81	74.00	-28.19	peak
5	23800.000	48.91	-3.11	45.80	74.00	-28.20	peak
6	25944.000	46.45	-0.96	45.49	74.00	-28.51	peak


Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18624.000	49.33	-5.34	43.99	74.00	-30.01	peak
2	19552.000	49.63	-5.49	44.14	74.00	-29.86	peak
3	21984.000	48.39	-4.47	43.92	74.00	-30.08	peak
4	22688.000	47.82	-3.74	44.08	74.00	-29.92	peak
5	25304.000	46.08	-1.70	44.38	74.00	-29.62	peak
6	26000.000	46.50	-1.06	45.44	74.00	-28.56	peak


8.8. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)-RIGHT

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18192.000	49.48	-5.51	43.97	74.00	-30.03	peak
2	19896.000	49.51	-5.37	44.14	74.00	-29.86	peak
3	22160.000	49.58	-4.31	45.27	74.00	-28.73	peak
4	23592.000	48.48	-3.16	45.32	74.00	-28.68	peak
5	24720.000	47.36	-2.33	45.03	74.00	-28.97	peak
6	25520.000	47.18	-1.69	45.49	74.00	-28.51	peak


Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18280.000	49.25	-5.52	43.73	74.00	-30.27	peak
2	20552.000	50.15	-5.30	44.85	74.00	-29.15	peak
3	21848.000	49.08	-4.39	44.69	74.00	-29.31	peak
4	23360.000	48.10	-3.26	44.84	74.00	-29.16	peak
5	24632.000	46.96	-2.31	44.65	74.00	-29.35	peak
6	25656.000	45.68	-1.05	44.63	74.00	-29.37	peak


8.9. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0114	75.00	-101.40	-26.40	46.46	-77.90	-5.04	-72.86	peak
2	0.0212	70.54	-101.35	-30.81	41.07	-82.31	-10.43	-71.88	peak
3	0.0427	65.67	-101.45	-35.78	34.99	-87.28	-16.51	-70.77	peak
4	0.0616	62.13	-101.53	-39.40	31.81	-90.90	-19.69	-71.21	peak
5	0.0942	60.33	-101.75	-41.42	28.12	-92.92	-23.38	-69.54	peak
6	0.1300	57.43	-101.70	-44.27	25.33	-95.77	-26.17	-69.60	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.1718	74.44	-101.67	-27.23	22.91	-78.73	-28.59	-50.14	peak
2	0.1966	70.18	-101.71	-31.53	21.73	-83.03	-29.77	-53.26	peak
3	0.2452	66.58	-101.80	-35.22	19.81	-86.72	-31.69	-55.03	peak
4	0.2973	63.73	-101.85	-38.12	18.14	-89.62	-33.36	-56.26	peak
5	0.3684	61.48	-101.93	-40.45	16.27	-91.95	-35.23	-56.72	peak
6	0.4364	58.36	-101.99	-43.63	14.80	-95.13	-36.70	-58.43	peak


Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5785	64.90	-62.08	2.82	32.36	-48.68	-19.14	-29.54	peak
2	1.2882	60.42	-62.14	-1.72	25.41	-53.22	-26.09	-27.13	peak
3	2.5935	56.61	-61.68	-5.07	29.54	-56.57	-21.96	-34.61	peak
4	3.8246	56.70	-61.38	-4.68	29.54	-56.18	-21.96	-34.22	peak
5	10.1393	55.78	-60.81	-5.03	29.54	-56.53	-21.96	-34.57	peak
6	29.3213	54.30	-60.02	-5.72	29.54	-57.22	-21.96	-35.26	peak


8.10. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Horizontal	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	55.2200	33.23	-15.19	18.04	40.00	-21.96	peak
2	180.3500	22.15	-11.92	10.23	43.50	-33.27	peak
3	376.2900	23.07	-9.50	13.57	46.00	-32.43	peak
4	556.7100	23.86	-6.60	17.26	46.00	-28.74	peak
5	751.6800	26.96	-3.37	23.59	46.00	-22.41	peak
6	945.6800	26.78	-0.62	26.16	46.00	-19.84	peak

Test Mode:	GFSK	Frequency(MHz):	2402
Polarity:	Vertical	Test Voltage:	DC 3.7V



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	51.3400	33.27	-15.25	18.02	40.00	-21.98	peak
2	189.0800	22.13	-12.04	10.09	43.50	-33.41	peak
3	477.1700	24.16	-7.54	16.62	46.00	-29.38	peak
4	627.5200	23.99	-5.46	18.53	46.00	-27.47	peak
5	804.0600	25.13	-2.48	22.65	46.00	-23.35	peak
6	991.2700	26.23	0.15	26.38	54.00	-27.62	peak

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass


10. TEST DATA-Left


10.1. APPENDIX A: 20DB EMISSION BANDWIDTH

10.1.1. Test Result


Test Mode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Verdict
DH5	Ant1	2402	0.94	2401.49	2402.43	PASS
		2441	0.94	2440.49	2441.43	PASS
		2480	0.94	2479.49	2480.43	PASS
2DH5	Ant1	2402	1.27	2401.30	2402.58	PASS
		2441	1.28	2440.30	2441.58	PASS
		2480	1.27	2479.30	2480.58	PASS

10.1.2. Test Graphs






2DH5 Ant1_2402



2DH5 Ant1_2441





2DH5 Ant1_2480

10.2. APPENDIX B: OCCUPIED CHANNEL BANDWIDTH**10.2.1. Test Result**


Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
DH5	Ant1	2402	0.92308	2401.4905	2402.4136	PASS
		2441	0.92008	2440.4905	2441.4106	PASS
		2480	0.92607	2479.4875	2480.4136	PASS
2DH5	Ant1	2402	1.2288	2401.3317	2402.5604	PASS
		2441	1.2288	2440.3287	2441.5574	PASS
		2480	1.2348	2479.3257	2480.5604	PASS

10.2.2. Test Graphs






2DH5 Ant1 2402



2DH5 Ant1 2441



2DH5 Ant1 2480

10.3. APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER

10.3.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Peak Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	3.57	≤30	PASS
		2441	3.81	≤30	PASS
		2480	3.56	≤30	PASS
2DH5	Ant1	2402	4.27	≤20.97	PASS
		2441	4.64	≤20.97	PASS
		2480	4.34	≤20.97	PASS


Test Mode	Antenna	Frequency[MHz]	Average Result[dBm]	EIRP[dBm]	Limit[dBm]	Verdict
DH5	Ant1	2402	3.06	2.46	≤30	PASS
		2441	3.27	2.67	≤30	PASS
		2480	3.09	2.49	≤30	PASS
2DH5	Ant1	2402	3.75	3.15	≤20.97	PASS
		2441	4.11	3.51	≤20.97	PASS
		2480	3.79	3.19	≤20.97	PASS

10.4. APPENDIX D: CARRIER FREQUENCY SEPARATION

10.4.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	Hop	1.003	≥ 0.940	PASS
2DH5	Ant1	Hop	1.003	≥ 0.853	PASS

10.4.2. Test Graphs




10.5. APPENDIX E: TIME OF OCCUPANCY


10.5.1. Test Result

FHSS Mode						
Test Mode	Antenna	Channel	BurstWidth [ms]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.378	0.121	≤0.4	PASS
DH3	Ant1	Hop	1.626	0.260	≤0.4	PASS
DH5	Ant1	Hop	2.867	0.306	≤0.4	PASS
2DH1	Ant1	Hop	0.386	0.124	≤0.4	PASS
2DH3	Ant1	Hop	1.63	0.261	≤0.4	PASS
2DH5	Ant1	Hop	2.874	0.307	≤0.4	PASS


AFHSS Mode						
Test Mode	Antenna	Channel	BurstWidth [ms]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.378	0.060	≤0.4	PASS
DH3	Ant1	Hop	1.626	0.130	≤0.4	PASS
DH5	Ant1	Hop	2.867	0.153	≤0.4	PASS
2DH1	Ant1	Hop	0.386	0.062	≤0.4	PASS
2DH3	Ant1	Hop	1.63	0.130	≤0.4	PASS
2DH5	Ant1	Hop	2.874	0.153	≤0.4	PASS

10.5.2. Test Graphs






2DH1_Ant1_Hop



2DH3_Ant1_Hop




2DH5_Ant1_Hop

10.6. APPENDIX F: NUMBER OF HOPPING CHANNELS

10.6.1. Test Result

Test Mode	Antenna	Frequency[MHz]	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS


10.6.2. Test Graphs




10.7. APPENDIX G: BAND EDGE MEASUREMENTS**10.7.1. Test Result**


Test Mode	Antenna	ChName	Frequency [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	2.08	-35.68	≤ -17.92	PASS
		High	2480	2.10	-35.26	≤ -17.9	PASS
		Low	Hop 2402	1.88	-36.32	≤ -18.12	PASS
		High	Hop 2480	2.19	-34.75	≤ -17.81	PASS
2DH5	Ant1	Low	2402	2.00	-37.16	≤ -18	PASS
		High	2480	1.98	-34.53	≤ -18.02	PASS
		Low	Hop 2402	0.29	-36.35	≤ -19.71	PASS
		High	Hop 2480	1.50	-34.41	≤ -18.5	PASS

10.7.2. Test Graphs







DH5 Ant1 High Hop 2480




2DH5 Ant1 Low 2402



2DH5 Ant1 High 2480



2DH5 Ant1 Low Hop 2402




2DH5 Ant1 High Hop 2480


10.8. APPENDIX H: CONDUCTED SPURIOUS EMISSION

10.8.1. Test Result


Test Mode	Antenna	Frequency[MHz]	FreqRange [MHz]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	2.17	---	PASS
			30~1000	-45.28	≤-17.83	PASS
			1000~26500	-39.15	≤-17.83	PASS
		2441	Reference	2.45	---	PASS
			30~1000	-44.99	≤-17.55	PASS
			1000~26500	-39.4	≤-17.55	PASS
		2480	Reference	2.03	---	PASS
			30~1000	-44.86	≤-17.97	PASS
			1000~26500	-39.34	≤-17.97	PASS
2DH5	Ant1	2402	Reference	2.00	---	PASS
			30~1000	-45.28	≤-18	PASS
			1000~26500	-39.85	≤-18	PASS
		2441	Reference	2.39	---	PASS
			30~1000	-45.25	≤-17.61	PASS
			1000~26500	-39.55	≤-17.61	PASS
		2480	Reference	1.97	---	PASS
			30~1000	-44.69	≤-18.03	PASS
			1000~26500	-39.82	≤-18.03	PASS

10.8.2. Test Graphs







DH5_Ant1_2441_0~Reference




DH5_Ant1_2441_30~1000




DH5_Ant1_2441_1000~26500




DH5_Ant1_2480_0~Reference




DH5_Ant1_2480_30~1000




DH5_Ant1_2480_1000~26500




2DH5_Ant1_2402_0~Reference




2DH5_Ant1_2402_30~1000




2DH5_Ant1_2402_1000~26500




2DH5_Ant1_2441_0~Reference




2DH5_Ant1_2441_30~1000




2DH5_Ant1_2441_1000~26500



2DH5_Ant1_2480_0~Reference



2DH5_Ant1_2480_30~1000



2DH5_Ant1_2480_1000~26500

10.9. APPENDIX I: DUTY CYCLE

10.9.1. Test Result

Test Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
DH5	2.88	3.74	0.7701	77.01	1.13	0.35	1
2DH5	2.88	3.73	0.7721	77.21	1.12	0.35	1

Note:

Duty Cycle Correction Factor = $10 \log (1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

10.9.2. Test Graphs



11. TEST DATA-Right

11.1. APPENDIX A: 20DB EMISSION BANDWIDTH

11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	20db EBW[MHz]	FL[MHz]	FH[MHz]	Verdict
DH5	Ant1	2402	0.95	2401.49	2402.43	PASS
		2441	0.94	2440.49	2441.43	PASS
		2480	0.95	2479.48	2480.43	PASS
2DH5	Ant1	2402	1.27	2401.30	2402.58	PASS
		2441	1.27	2440.30	2441.58	PASS
		2480	1.27	2479.30	2480.57	PASS