

Test report No: 6223821.50

TEST REPORT

Radio Spectrum Matters (RF)

Identification of item tested	KitchenAid Smart Thermometer
Trademark	KitchenAid
Model and /or type reference	KTH11BM
Features	USB 5Vdc, 0.35A; Repeater battery : 0.35AH, 1.3Wh
FCC ID	A5UTTIVNWMT02
ISED Number	10248A-TTIVNWMT02
Applicant's name / address	Whirlpool Corporation 2000 N M-63 Benton Harbor, Michigan 49022, United States
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10-2020+Cor 1-2023+C63.10a-2024 + Errata to c63.10a-2024 RSS-Gen Issue 5 / RSS-247 Issue 3
Verdict Summary	IN COMPLIANCE
Prepared by (name / position & signature)	Adrian Shi Technical Supervisor 
Approved by (name / position & signature)	Lei Chen Senior Project Manager 
Date of issue	2025-10-12
Report template No	TRF_Part15C_247_RF03 V1.0

INDEX

	page
Competences and Guarantees	4
General conditions	4
Uncertainty	4
Environmental conditions.....	5
Possible test case verdicts.....	5
Definition of symbols used in this test report	5
Abbreviations.....	5
Document History	6
Remarks and Comments	6
1 General Information.....	7
1.1 General Description of the Item(s).....	7
1.2 Test date.....	8
2 Description of Test Setup.....	9
2.1 Operating mode(s) used for tests	9
2.2 Support / Auxiliary equipment / unit / software for the EUT	9
2.3 Test Configuration / Block diagram used for tests.....	9
3 Verdict summary section.....	10
3.1 Standards.....	10
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	10
3.3 Overview of results	10
3.4 Test Facility	11
3.5 Measurement procedure.....	12
4 Test Results.....	13
4.1 AC Power Line Conducted Emission	13
4.2 Emissions in restricted frequency bands	16
4.3 Emissions in non-restricted frequency band	32
4.4 Duty Cycle.....	41
4.5 Radiated Emission Band Edge.....	43
4.6 DTS Bandwidth & Occupied Bandwidth	60
4.7 Fundamental emission output power	63
4.8 Power Spectral Density	65
4.9 Antenna Requirement	67
5 Identification of the Equipment Under Test	68
Annex 1 – Measurement Uncertainty	69



Annex 2 – Used Equipment.....70

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.
5. The information provided by the customer in this report may affect the validity of the results, the test lab is not responsible for it.
6. This report will not be used for social proof function in China market.

UNCERTAINTY

For all measurements where guidance for the calculation of the instrumentation uncertainty of a measurement is specified in the product standard, the measurement instrumentation uncertainty has been calculated and applied in accordance with these standards.

Uncertainties have been calculated according to the Dekra internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%. Refer to the Annex 1 for further information.

The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to calculate the uncertainty associated with the measurement result, unless the specification, standard or customer have special requirements

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%
Atmospheric pressure	86 kPa – 106 kPa

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

DEFINITION OF SYMBOLS USED IN THIS TEST REPORT

☒ Indicates that the listed condition, standard or equipment is applicable for this report/test/EUT.			
☐ Indicates that the listed condition, standard or equipment is not applicable for this report/test/EUT.			
Decimal separator used in this report	☒	Comma (,)	☐ Point (.)

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
Tx	: Transmitter
Rx	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report nr.	Date	Description
6223821.50	2025-10-12	First release.

REMARKS AND COMMENTS

The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).

The test results relate only to the samples tested.

This report shall not be reproduced, except in full, without the written approval.

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Description of the item..... :	KitchenAid Smart Thermometer
Model / Type number..... :	KTH11BM
Trademark..... :	KitchenAid
FCC ID..... :	A5UTTIVNWMT02
ISED Number :	10248A-TTIVNWMT02
Test Sample Number..... :	6183426.01
Manufacturer :	KitchenAid Global LLC Kitchenaid Portable Appliance Tech,ST JOSEPH TECHNOLOGY CENTER, 303 Upton Dr., St Joseph, MI, 49085, USA

Mode of Operation	Bluetooth BLE					
Operating frequency range(s)	2402~2480 MHz					
Type of Modulation	GFSK					
PHYs	☒	LE 1M	☒	LE 2M	☒	LE Coded S=2/8
Data Rate	☒	1 Mbps	☒	2 Mbps	☒	500/125 Kbps
Antenna type	Repeater: PCB Antenna Probe: Metal antenna					
Antenna gain	Repeater: 3.8 dBi Probe: -3.1 dBi					
Number of channel.....	40					

Note: Antenna information was provided from applicant.

Rated power supply..... :	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	☐	AC:	☐	☐	☐	☐	☐
	☒	DC: 5V (Repeater)					
	☒	Battery: 3V (Probe)					
Mounting position..... :	☐	Table top equipment					
	☐	Wall/Ceiling mounted equipment					
	☐	Floor standing equipment					
	☒	Hand-held equipment					
	☐	Other:					

Intended use of the Equipment Under Test (EUT)
The product is KitchenAid Smart Thermometer which supports BLE function and it is divided into probe and repeater two parts, each part using different Bluetooth modules.

1.2 **Test date**

Test Location	DEKRA Testing and Certification (Shanghai) Ltd. No.250, Jiangchangsan Road, Jing'an District, Shanghai, China
Date of receipt of test item	2025-04-10
Date (s) of performance of tests	2025-04-16~2025-09-25

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.

Operating mode	Operating mode description	Used for methods	
		Conducted	Radiated
1	Transmitting (Repeater)	☒	☒
2	Transmitting (Probe)	☒	☒
Supplemental information: ---			

2.2 Support / Auxiliary equipment / unit / software for the EUT

The EUT has been tested with the following auxiliary equipment / unit / software:

Auxiliary equipment / unit / software	Type / Version	Serial number	Manufacturer	Supplied by
nRFgo Studio	V1.21.2.10	N/A	N/A	Applicant
Laptop	Latitude 3430	7XB4DS3	DELL	DEKRA
Supplemental information: ---				

2.3 Test Configuration / Block diagram used for tests

Refer to Annex 3.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.247	2022	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Corrigendum 1	2023	
Amendment 1	2024	
Errata to Amendment 1	2024	
KDB 558074 D01 v05r02	2019	Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247
RSS-Gen Issue 5	2018	General Requirements for Compliance of Radio Apparatus
Amendment 1	2019	
Amendment 2	2021	
RSS-247 Issue 3	2023	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

3.3 Overview of results

FCC measurement			
Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	FCC 15.207	PASS	---
Emissions in restricted frequency bands	FCC 15.247(d), 15.209, 15.205	PASS	---
Duty cycle	ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024	PASS	---
Emissions in non-restricted frequency bands	FCC 15.247(d)	PASS	---
Radiated Emission Band Edge	FCC 15.247(d), 15.209, 15.205	PASS	---
Fundamental emission output power	FCC 15.247(b)(3)	PASS	---
DTS Bandwidth	FCC 15.247(a)(2)	PASS	---
Power Spectral Density	FCC 15.247(e)	PASS	---
Antenna Requirement	FCC 15.203	PASS	---
Supplementary information: ---			

RSS measurement			
Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	RSS-Gen Issue 5 Section 8.8	PASS	---
Emissions in restricted frequency bands	RSS-Gen Issue 5 Section 8.9 & 8.10	PASS	---
Duty cycle	ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024	PASS	---
Emissions in non-restricted frequency bands	RSS-247 Issue 2 Section 5.5	PASS	---
Radiated Emission Band Edge	RSS-Gen Issue 5 Section 8.9 & 8.10	PASS	---
Fundamental emission output power	RSS-247 Issue 2 Section 5.4(d)	PASS	---
DTS Bandwidth & Occupied Bandwidth	RSS-Gen Issue 5 Section 6.7 RSS-247 Issue 2 Section 5.2(a)	PASS	---
Power Spectral Density	RSS-247 Issue 2 Section 5.2(b)	PASS	---
Antenna Requirement	RSS-Gen Issue 5 Section 6.8	PASS	---
Supplementary information: ---			

3.4 Test Facility

FCC Designation Number	:	A5UTTIVNWMT02
ISED CAB identifier Number	:	10248A-TTIVNWMT02

3.5 Measurement procedure

The EUT was controlled by USB Cable provided by applicant which connected to laptop. After connected, run the software “nRFgo Studio” supplied by manufacturer to control the EUT work in required test mode as below table.

Repeater

Mode	Modulation	Data Rate	Channel Number	Frequency (MHz)	Power Setting
BLE	GFSK	1Mbps	00	2402	3
			19	2440	3
			39	2480	3
BLE	GFSK	2Mbps	00	2402	3
			19	2440	3
			39	2480	3
BLE	GFSK	LE Coded S=2	00	2402	3
			19	2440	3
			39	2480	3
BLE	GFSK	LE Coded S=8	00	2402	3
			19	2440	3
			39	2480	3

Probe

Mode	Modulation	Data Rate	Channel Number	Frequency (MHz)	Power Setting
BLE	GFSK	1Mbps	00	2402	8
			19	2440	8
			39	2480	8
BLE	GFSK	2Mbps	00	2402	8
			19	2440	8
			39	2480	8
BLE	GFSK	LE Coded S=2	00	2402	8
			19	2440	8
			39	2480	8
BLE	GFSK	LE Coded S=8	00	2402	8
			19	2440	8
			39	2480	8

4 TEST RESULTS


4.1	AC Power Line Conducted Emission	VERDICT: PASS
-----	----------------------------------	---------------

Limit

FCC Part 15 Subpart C Paragraph 15.207 & RSS-Gen Issue 5 Section 8.8				
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]	IF BW	Detector(s)
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾	9 KHz	QP, AV
0,50 - 5,0	56	46	9 KHz	QP, AV
5,0 - 30	60	50	9 KHz	QP, AV

¹⁾ At the transition frequency, the lower limit applies.
²⁾ The limit decreases linearly with the logarithm of the frequency.


Test Configuration



Performed measurements

Port under test			Terminal							
☒	AC mains input power		☒	N	☒	L1	☐	L2	☐	L3
☐	DC input power		☐	Positive (+)			☐	Negative (-)		
Test method applied			☒	Artificial mains network						
			☐	Voltage probe						
Test setup			☒	Table top	☐	Artificial hand applied				
			☐	Floor standing	☐	Other:				
			Refer to the Annex 2 for test setup photo(s).							
Operating mode(s) used			Mode 1, Mode 2							
Remark			All above modes were evaluated but only shown the worst data in the report.							

See next page.

Measurement data		Port under test	AC mains input power																																																															
Operating mode / voltage / frequency used during the test			Mode 1 / 120 Vac / 60 Hz																																																															
 <table><tr><th>Frequency [MHz]</th><th>QPK Level [dBµV]</th><th>QPK Limit [dBµV]</th><th>QPK Margin [dB]</th><th>CAV Level [dBµV]</th><th>CAV: AVG Limit [dBµV]</th><th>CAV Margin [dB]</th><th>Correction [dB]</th><th>Line</th></tr><tr><td>0.407</td><td>30.48</td><td>57.72</td><td>27.24</td><td>23.14</td><td>47.72</td><td>24.58</td><td>9.73</td><td>N</td></tr><tr><td>0.575</td><td>36.76</td><td>56.00</td><td>19.24</td><td>29.13</td><td>46.00</td><td>16.87</td><td>9.67</td><td>N</td></tr><tr><td>0.636</td><td>28.64</td><td>56.00</td><td>27.36</td><td>20.97</td><td>46.00</td><td>25.03</td><td>9.62</td><td>N</td></tr><tr><td>0.836</td><td>30.02</td><td>56.00</td><td>25.98</td><td>22.37</td><td>46.00</td><td>23.63</td><td>9.62</td><td>N</td></tr><tr><td>5.267</td><td>22.99</td><td>60.00</td><td>37.01</td><td>14.21</td><td>50.00</td><td>35.79</td><td>9.71</td><td>N</td></tr><tr><td>21.368</td><td>19.35</td><td>60.00</td><td>40.65</td><td>11.39</td><td>50.00</td><td>38.61</td><td>9.97</td><td>N</td></tr></table>				Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line	0.407	30.48	57.72	27.24	23.14	47.72	24.58	9.73	N	0.575	36.76	56.00	19.24	29.13	46.00	16.87	9.67	N	0.636	28.64	56.00	27.36	20.97	46.00	25.03	9.62	N	0.836	30.02	56.00	25.98	22.37	46.00	23.63	9.62	N	5.267	22.99	60.00	37.01	14.21	50.00	35.79	9.71	N	21.368	19.35	60.00	40.65	11.39	50.00	38.61	9.97	N
Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line																																																										
0.407	30.48	57.72	27.24	23.14	47.72	24.58	9.73	N																																																										
0.575	36.76	56.00	19.24	29.13	46.00	16.87	9.67	N																																																										
0.636	28.64	56.00	27.36	20.97	46.00	25.03	9.62	N																																																										
0.836	30.02	56.00	25.98	22.37	46.00	23.63	9.62	N																																																										
5.267	22.99	60.00	37.01	14.21	50.00	35.79	9.71	N																																																										
21.368	19.35	60.00	40.65	11.39	50.00	38.61	9.97	N																																																										
Remark	1. QPK Level [dBµV]=Reading QPK Level [dBµV] + Correction [dB] 2. CAV Level [dBµV]=Reading CAV Level [dBµV] + Correction [dB] 3. Correction [dB]= AMN VDF [dB] + Cable Loss [dB]																																																																	

Measurement data			Port under test	AC mains input power				
Operating mode / voltage / frequency used during the test			Mode 1 / 120 Vac / 60 Hz					
Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line
0.371	29.48	58.49	29.01	22.50	48.49	25.99	9.69	L1
0.578	39.75	56.00	16.25	33.57	46.00	12.43	9.70	L1
0.787	30.15	56.00	25.85	23.06	46.00	22.94	9.68	L1
1.140	26.80	56.00	29.20	19.84	46.00	26.16	9.68	L1
5.120	21.84	60.00	38.16	12.40	50.00	37.60	9.78	L1
22.151	22.03	60.00	37.97	11.19	50.00	38.81	9.96	L1
Remark	1. QPK Level [dBµV]=Reading QPK Level [dBµV] + Correction [dB] 2. CAV Level [dBµV]=Reading CAV Level [dBµV] + Correction [dB] 3. Correction [dB]= AMN VDF [dB] + Cable Loss [dB]							

4.2	Emissions in restricted frequency bands	VERDICT: PASS
-----	---	---------------

Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d), 15.205, 15.209 & RSS-Gen Issue 5 Section 8.9 & 8.10	
Restricted Bands of operation for FCC			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 –16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975–12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675–12.57725	322 – 335.4	3600 – 4400	Above 38.6
13.36 – 13.41	--	--	--
Restricted Bands of operation for ISED			
0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475 - 156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	--
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	--
8.41425 - 8.41475	240 - 285	5350 - 5460	--
12.29 - 12.293	322 - 335.4	7250 - 7750	--
12.51975 - 12.52025	399.9 - 410	8025 - 8500	--
12.57675 - 12.57725	608 - 614	--	--

Restricted Band Emissions Limit


Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength (dB $\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)

Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).


Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

Test Configuration


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




Performed measurements

Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	1. The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report. 2. The EUT is working in the Normal link mode below 1 GHz. 3. All above modes were evaluated but only shown the worst data in the report.	

Results

Emissions in restricted frequency bands


30MHz – 1GHz, Normal Mode, Repeater



Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	47.400	10.36	40.00	29.64	21.21	H	8.8	2
1	54.300	9.09	40.00	30.91	20.82	H	350.4	1
1	115.110	6.47	43.50	37.03	17.77	H	227.2	1
1	202.260	7.70	43.50	35.80	18.90	H	152.7	1
1	557.190	15.97	46.00	30.03	26.63	H	111.7	2
1	956.100	21.84	46.00	24.16	31.78	H	160	1

1. QPK Level [dBµV/m]=Reading QPK Level [dBµV/m] + Correction [dB/m]
2. Correction [dB/m]=Antenna Factor [dB/m] + Cable Loss [dB]


30MHz – 1GHz, Normal Mode, Repeater



Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	37.920	10.92	40.00	29.08	19.05	V	265.2	1
1	62.340	9.38	40.00	30.62	19.24	V	21	1
1	103.800	7.70	43.50	35.80	19.12	V	21	1
1	194.640	8.06	43.50	35.44	19.37	V	133.3	1.5
1	296.400	10.34	46.00	35.66	21.41	V	280.6	1.5
1	944.340	21.66	46.00	24.34	31.79	V	140.9	1.5

1. QPK Level [dBµV/m]=Reading QPK Level [dBµV/m] + Correction [dB/m]
2. Correction [dB/m]=Antenna Factor [dB/m] + Cable Loss [dB]


30MHz – 1GHz, Normal Mode, Probe



Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	45.390	9.83	40.00	30.17	20.86	H	94.3	1
1	99.780	7.23	43.50	36.27	19.05	H	171.5	2
1	197.820	8.19	43.50	35.31	19.48	H	57.6	1
1	328.050	10.88	46.00	35.12	22.22	H	325	2
1	508.710	15.18	46.00	30.82	25.96	H	87.1	1
1	756.630	19.85	46.00	26.15	30.31	H	242.5	1

1. QPK Level [dBμV/m]=Reading QPK Level [dBμV/m] + Correction [dB/m]
2. Correction [dB/m]=Antenna Factor [dB/m] + Cable Loss [dB]


30MHz – 1GHz, Normal Mode, Probe



Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	47.490	10.35	40.00	29.65	21.23	V	269.3	1
1	101.310	7.15	43.50	36.35	19.18	V	218.2	1
1	210.000	7.50	43.50	36.00	18.71	V	225.8	1
1	297.660	10.43	46.00	35.57	21.41	V	237.8	1.5
1	425.730	13.75	46.00	32.25	24.74	V	332.5	1.5
1	933.570	21.67	46.00	24.33	31.77	V	274.2	1.5

1. QPK Level [dBµV/m]=Reading QPK Level [dBµV/m] + Correction [dB/m]
2. Correction [dB/m]=Antenna Factor [dB/m] + Cable Loss [dB]


1GHz – 10th Harmonic, Repeater
2402MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2578.50	33.3	41.79	8.460	54.00	12.21	AV	Verti	PASS
2	3995.63	39.1	50.35	11.240	74.00	23.65	PK	Verti	PASS
3	4804.38	32.2	44.23	12.040	54.00	9.77	AV	Verti	PASS
4	4947.50	40.2	52.16	11.930	74.00	21.84	PK	Verti	PASS
5	7206.88	32.3	49.26	16.990	54.00	4.74	AV	Verti	PASS
6	7484.38	40.3	57.69	17.350	74.00	16.31	PK	Verti	PASS
7	12008.67	30.4	41.78	11.420	54.00	12.22	AV	Verti	PASS
8	12077.33	37.7	49.36	11.700	74.00	24.64	PK	Verti	PASS
9	14926.67	36.9	50.65	13.730	74.00	23.35	PK	Verti	PASS
10	14993.33	28.9	43.04	14.120	54.00	10.96	AV	Verti	PASS
11	17618.67	28.6	47.46	18.890	54.00	6.54	AV	Verti	PASS
12	17828.00	37.3	56.16	18.880	74.00	17.84	PK	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2402MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2546.00	41.8	50.46	8.710	74.00	23.54	PK	Hori	PASS
2	3993.13	30.2	41.46	11.230	54.00	12.54	AV	Hori	PASS
3	4803.75	31.7	43.71	12.050	54.00	10.29	AV	Hori	PASS
4	4820.63	40.0	51.99	11.960	74.00	22.01	PK	Hori	PASS
5	7206.88	32.5	49.53	16.990	54.00	4.47	AV	Hori	PASS
6	7487.50	39.6	56.93	17.350	74.00	17.07	PK	Hori	PASS
7	12060.00	38.2	49.85	11.630	74.00	24.15	PK	Hori	PASS
8	12107.33	30.7	42.42	11.720	54.00	11.58	AV	Hori	PASS
9	14884.67	37.3	50.78	13.530	74.00	23.22	PK	Hori	PASS
10	14990.00	29.5	43.55	14.100	54.00	10.45	AV	Hori	PASS
11	17592.67	36.8	55.68	18.930	74.00	18.32	PK	Hori	PASS
12	17596.67	28.7	47.69	18.980	54.00	6.31	AV	Hori	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level

2480MHz, 1Mbps




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	3893.75	39.8	50.37	10.550	74.00	23.63	PK	Verti	PASS
2	3993.13	30.4	41.62	11.230	54.00	12.38	AV	Verti	PASS
3	4826.25	30.9	42.88	11.940	54.00	11.12	AV	Verti	PASS
4	4827.50	40.2	52.16	11.930	74.00	21.84	PK	Verti	PASS
5	7439.38	34.6	51.97	17.340	54.00	2.03	AV	Verti	PASS
6	7440.63	40.6	57.90	17.340	74.00	16.10	PK	Verti	PASS
7	12038.67	30.6	42.14	11.540	54.00	11.86	AV	Verti	PASS
8	12121.33	37.5	49.07	11.570	74.00	24.93	PK	Verti	PASS
9	14730.00	30.9	43.55	12.630	54.00	10.45	AV	Verti	PASS
10	14926.67	37.4	51.14	13.730	74.00	22.86	PK	Verti	PASS
11	16498.00	30.2	47.63	17.470	54.00	6.37	AV	Verti	PASS
12	17630.67	36.6	55.40	18.810	74.00	18.60	PK	Verti	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	3005.00	39.0	50.25	11.250	74.00	23.75	PK	Hori	PASS
2	3966.88	30.3	41.28	11.030	54.00	12.72	AV	Hori	PASS
3	4810.00	30.6	42.60	12.020	54.00	11.40	AV	Hori	PASS
4	4943.75	40.1	51.94	11.890	74.00	22.06	PK	Hori	PASS
5	7440.00	34.5	51.80	17.340	54.00	2.20	AV	Hori	PASS
6	7440.63	42.5	59.84	17.340	74.00	14.16	PK	Hori	PASS
7	12077.33	29.8	41.47	11.700	54.00	12.53	AV	Hori	PASS
8	12083.33	38.6	50.28	11.720	74.00	23.72	PK	Hori	PASS
9	14614.00	31.0	43.59	12.620	54.00	10.41	AV	Hori	PASS
10	14999.33	37.3	51.41	14.160	74.00	22.59	PK	Hori	PASS
11	16508.00	37.8	55.11	17.360	74.00	18.89	PK	Hori	PASS
12	17840.67	29.3	48.15	18.830	54.00	5.85	AV	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

1GHz – 10th Harmonic, Probe
2402MHz, 1Mbps




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2970.25	40.0	49.94	9.990	74.00	24.06	PK	Verti	PASS
2	3971.25	30.2	41.30	11.070	54.00	12.70	AV	Verti	PASS
3	4803.75	32.6	44.67	12.050	54.00	9.33	AV	Verti	PASS
4	4845.63	41.0	52.86	11.840	74.00	21.14	PK	Verti	PASS
5	7206.88	32.9	49.92	16.990	54.00	4.08	AV	Verti	PASS
6	7483.75	39.5	56.87	17.350	74.00	17.13	PK	Verti	PASS
7	12011.33	41.6	53.01	11.430	54.00	0.99	AV	Verti	PASS
8	12011.33	45.4	56.79	11.430	74.00	17.21	PK	Verti	PASS
9	14986.67	37.6	51.69	14.080	74.00	22.31	PK	Verti	PASS
10	14990.00	29.9	43.95	14.100	54.00	10.05	AV	Verti	PASS
11	17828.00	36.6	55.50	18.880	74.00	18.50	PK	Verti	PASS
12	17899.33	28.8	47.38	18.620	54.00	6.62	AV	Verti	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

2402MHz, 1Mbps




Suspected Data List

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	3010.63	30.4	41.61	11.180	54.00	12.39	AV	Hori	PASS
2	3810.00	39.4	50.25	10.830	74.00	23.75	PK	Hori	PASS
3	4803.75	30.9	42.94	12.050	54.00	11.06	AV	Hori	PASS
4	4893.75	40.2	51.75	11.590	74.00	22.25	PK	Hori	PASS
5	7278.75	30.5	47.94	17.480	54.00	6.06	AV	Hori	PASS
6	7303.75	39.6	57.20	17.610	74.00	16.80	PK	Hori	PASS
7	12008.67	36.2	47.61	11.420	54.00	6.39	AV	Hori	PASS
8	12011.33	41.9	53.36	11.430	74.00	20.64	PK	Hori	PASS
9	14944.67	38.2	52.02	13.840	74.00	21.98	PK	Hori	PASS
10	14988.67	29.6	43.65	14.090	54.00	10.35	AV	Hori	PASS
11	17816.00	28.9	47.77	18.920	54.00	6.23	AV	Hori	PASS
12	17894.67	36.8	55.47	18.640	74.00	18.53	PK	Hori	PASS

Note: (1) Level = Reading + Factor
(2) Margin = Limit - Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	3597.50	31.1	41.78	10.720	54.00	12.22	AV	Verti	PASS
2	3971.25	39.5	50.57	11.070	74.00	23.43	PK	Verti	PASS
3	4818.13	30.5	42.48	11.980	54.00	11.52	AV	Verti	PASS
4	4826.88	39.7	51.65	11.940	74.00	22.35	PK	Verti	PASS
5	7441.25	41.1	58.46	17.340	74.00	15.54	PK	Verti	PASS
6	7488.13	30.8	48.18	17.350	54.00	5.82	AV	Verti	PASS
7	12398.67	37.8	47.81	10.030	54.00	6.19	AV	Verti	PASS
8	12399.33	42.9	52.87	10.020	74.00	21.13	PK	Verti	PASS
9	14985.33	29.7	43.79	14.070	54.00	10.21	AV	Verti	PASS
10	14994.00	37.7	51.82	14.130	74.00	22.18	PK	Verti	PASS
11	17844.00	36.6	55.42	18.820	74.00	18.58	PK	Verti	PASS
12	17850.00	29.0	47.76	18.810	54.00	6.24	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2608.25	33.6	41.85	8.300	54.00	12.15	AV	Hori	PASS
2	3998.13	39.0	50.25	11.260	74.00	23.75	PK	Hori	PASS
3	4817.50	30.7	42.71	11.980	54.00	11.29	AV	Hori	PASS
4	4835.63	40.0	51.92	11.890	74.00	22.08	PK	Hori	PASS
5	7240.00	40.1	57.31	17.210	74.00	16.69	PK	Hori	PASS
6	7288.13	30.2	47.76	17.540	54.00	6.24	AV	Hori	PASS
7	12398.67	34.8	44.79	10.030	54.00	9.21	AV	Hori	PASS
8	12398.67	40.2	50.24	10.030	74.00	23.76	PK	Hori	PASS
9	14980.67	29.7	43.78	14.050	54.00	10.22	AV	Hori	PASS
10	14984.67	37.3	51.40	14.070	74.00	22.60	PK	Hori	PASS
11	17831.33	28.9	47.75	18.860	54.00	6.25	AV	Hori	PASS
12	17846.67	36.4	55.26	18.820	74.00	18.74	PK	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

4.3 Emissions in non-restricted frequency band	VERDICT: PASS
---	----------------------


Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d) & RSS-247 Issue 2 Section 5.5	
RF Output power (Detection methods)	Limit(dB)	
RF Output power(Average detector)	30dBc(Note1)	
RF Output power(PK detector)	20dBc(Note2)	

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD by Level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD by Level in 100 kHz (i.e., 20 dBc).

Test Configuration





Performed measurements


Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	All above modes were evaluated but only shown the worst data in the report.	

See next page


Results
Emissions in non-restricted frequency band (Repeater)
2402MHz, 1Mbps



2480MHz, 1Mbps




02:11:26 PM 09/19/2025




02:11:31 PM 09/19/2025

2402MHz, 2Mbps




02:12:21 PM 09/19/2025




02:12:26 PM 09/19/2025

2480MHz, 2Mbps




02:14:04 PM 09/19/2025




02:14:10 PM 09/19/2025

Emissions in non-restricted frequency band (Probe)
2402MHz, 1Mbps




08:34:18 PM 06/19/2025




08:34:23 PM 06/19/2025

2480MHz, 1Mbps




08:36:17 PM 06/19/2025




08:36:23 PM 06/19/2025

2402MHz, 2Mbps




08:37:27 PM 06/19/2025




08:37:33 PM 06/19/2025

2480MHz, 2Mbps



08:39:03 PM 06/19/2025




08:39:08 PM 06/19/2025

4.4	Duty Cycle	VERDICT: PASS
-----	------------	---------------

Limit

N/A

Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	For reporting purpose only	

See next page.

Results Repeater

Mode	CH.	Test Freq. (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
BLE 1Mbps	00	2402	85.52	0.68	0.47
	19	2440	85.52	0.68	0.47
	39	2480	85.52	0.68	0.47
BLE 2Mbps	00	2402	57.61	2.40	0.93
	19	2440	57.60	2.40	0.93
	39	2480	57.61	2.40	0.93
BLE S2	00	2402	91.33	0.39	0
	19	2440	91.33	0.39	0
	39	2480	91.33	0.39	0
BLE S8	00	2402	100	0	0
	19	2440	100	0	0
	39	2480	100	0	0

Probe

Mode	CH.	Test Freq. (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
BLE 1Mbps	00	2402	85.54	0.68	0.47
	19	2440	85.52	0.68	0.47
	39	2480	85.52	0.68	0.47
BLE 2Mbps	00	2402	57.60	2.40	0.93
	19	2440	57.61	2.40	0.93
	39	2480	57.60	2.40	0.93
BLE S2	00	2402	91.32	0.39	0.22
	19	2440	91.32	0.39	0.22
	39	2480	91.32	0.39	0.22
BLE S8	00	2402	100	0	0
	19	2440	95.59	0.20	0
	39	2480	100	0	0

Note:

According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: VBW $\geq$ 1/T will be used.


4.5	Radiated Emission Band Edge	VERDICT: PASS
-----	------------------------------------	----------------------

Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d), 15.205, 15.209 & RSS-Gen Issue 5 Section 8.9 & 8.10			
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits .

Test Configuration




Performed measurements

Port under test	Enclosure port	
Test method applied	☐	Conducted measurement
	☒	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	All above modes were evaluated but only shown the worst data in the report.	

See next page

Results


**Radiated Emission Band Edge (Repeater)
2402MHz, 1Mbps**



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2321.99	35.8	41.69	5.890	54.00	12.31	AV	Verti	PASS
2	2370.94	44.7	50.47	5.730	74.00	23.53	PK	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

2402MHz, 1Mbps




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2322.01	43.0	48.93	5.890	54.00	5.07	AV	Hori	PASS
2	2322.45	47.9	53.73	5.880	74.00	20.27	PK	Hori	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.64	33.6	40.97	7.380	54.00	13.03	AV	Verti	PASS
2	2487.60	44.8	52.24	7.470	74.00	21.76	PK	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.67	45.9	53.29	7.390	74.00	20.71	PK	Hori	PASS
2	2495.98	36.8	44.45	7.650	54.00	9.55	AV	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2402MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2321.88	34.0	39.89	5.890	54.00	14.11	AV	Verti	PASS
2	2324.35	44.0	49.87	5.880	74.00	24.13	PK	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2402MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2322.07	40.6	46.53	5.890	54.00	7.47	AV	Hori	PASS
2	2322.45	46.2	52.12	5.880	74.00	21.88	PK	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2480MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2487.47	45.8	53.21	7.460	74.00	20.79	PK	Verti	PASS
2	2487.47	33.9	41.35	7.460	54.00	12.65	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2480MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.51	36.1	43.52	7.380	54.00	10.48	AV	Hori	PASS
2	2484.04	46.7	54.08	7.390	74.00	19.92	PK	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


Radiated Emission Band Edge (Probe)
2402MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2317.87	44.5	50.35	5.900	74.00	23.65	PK	Verti	PASS
2	2317.95	33.5	39.44	5.900	54.00	14.56	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

2402MHz, 1Mbps




Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2317.98	32.7	38.61	5.900	54.00	15.39	AV	Hori	PASS
2	2328.28	44.1	50.00	5.870	74.00	24.00	PK	Hori	PASS

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2487.44	45.5	52.97	7.460	74.00	21.03	PK	Verti	PASS
2	2487.44	34.1	41.52	7.460	54.00	12.48	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2480MHz, 1Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2494.47	32.0	39.58	7.620	54.00	14.42	AV	Hori	PASS
2	2497.61	43.8	51.47	7.680	74.00	22.53	PK	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2402MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2311.50	43.9	49.84	5.920	74.00	24.16	PK	Verti	PASS
2	2321.36	32.6	38.51	5.890	54.00	15.49	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2402MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2320.76	44.2	50.13	5.890	74.00	23.87	PK	Hori	PASS
2	2322.29	33.3	39.14	5.890	54.00	14.86	AV	Hori	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level


2480MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2487.42	44.0	51.42	7.460	74.00	22.58	PK	Verti	PASS
2	2487.45	33.0	40.45	7.460	54.00	13.55	AV	Verti	PASS

Note:(1)Level=Reading+Factor
(2)Margin=Limit-Level

2480MHz, 2Mbps



Suspected Data List									
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2493.38	44.5	52.08	7.590	74.00	21.92	PK	Hori	PASS
2	2497.44	32.0	39.65	7.680	54.00	14.35	AV	Hori	PASS

Note:(1)Level=Reading+Factor


(2)Margin=Limit-Level

4.6	DTS Bandwidth & Occupied Bandwidth	VERDICT: PASS
-----	---	----------------------

Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247 (a)(2)
Systems using digital modulation techniques operate in the 2400-2483.5 MHz .The minimum 6 dB bandwidth shall be at least 500 kHz	
Standard	RSS-Gen Issue 5 Section 6.7 & RSS-247 Issue 2 Section 5.2(a)
The occupied bandwidth or the "99% emission bandwidth" is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs. The occupied bandwidth should within the required frequency range.	
The minimum 6 dB bandwidth shall be 500 kHz.	

Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

Results

Repeater

Mode	CH.	Test Freq. (MHz)	6dB Occupied Bandwidth (MHz)	Limit (MHz)	Result
BLE 1Mbps	00	2402	0.687	>0.5	Pass
	19	2440	0.689	>0.5	Pass
	39	2480	0.690	>0.5	Pass
BLE 2Mbps	00	2402	1.140	>0.5	Pass
	19	2440	1.146	>0.5	Pass
	39	2480	1.143	>0.5	Pass
S=2	00	2402	0.689	>0.5	Pass
	19	2440	0.691	>0.5	Pass
	39	2480	0.683	>0.5	Pass
S=8	00	2402	0.611	>0.5	Pass
	19	2440	0.630	>0.5	Pass
	39	2480	0.615	>0.5	Pass

Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
BLE 1Mbps	00	2402	1.050	Within frequency range	Pass
	19	2440	1.052	Within frequency range	Pass
	39	2480	1.054	Within frequency range	Pass
BLE 2Mbps	00	2402	2.020	Within frequency range	Pass
	19	2440	2.025	Within frequency range	Pass
	39	2480	2.032	Within frequency range	Pass
S=2	00	2402	1.041	Within frequency range	Pass
	19	2440	1.045	Within frequency range	Pass
	39	2480	1.041	Within frequency range	Pass
S=8	00	2402	1.074	Within frequency range	Pass
	19	2440	1.071	Within frequency range	Pass
	39	2480	1.075	Within frequency range	Pass

Probe

Mode	CH.	Test Freq. (MHz)	6dB Occupied Bandwidth (MHz)	Limit (MHz)	Result
BLE 1Mbps	00	2402	0.685	>0.5	Pass
	19	2440	0.701	>0.5	Pass
	39	2480	0.695	>0.5	Pass
BLE 2Mbps	00	2402	1.146	>0.5	Pass
	19	2440	1.152	>0.5	Pass
	39	2480	1.139	>0.5	Pass
S=2	00	2402	0.698	>0.5	Pass
	19	2440	0.693	>0.5	Pass
	39	2480	0.705	>0.5	Pass
S=8	00	2402	0.613	>0.5	Pass
	19	2440	0.618	>0.5	Pass
	39	2480	0.611	>0.5	Pass

Mode	CH.	Test Freq. (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
BLE 1Mbps	00	2402	1.053	Within frequency range	Pass
	19	2440	1.053	Within frequency range	Pass
	39	2480	1.056	Within frequency range	Pass
BLE 2Mbps	00	2402	2.030	Within frequency range	Pass
	19	2440	2.040	Within frequency range	Pass
	39	2480	2.037	Within frequency range	Pass
S=2	00	2402	1.039	Within frequency range	Pass
	19	2440	1.041	Within frequency range	Pass
	39	2480	1.043	Within frequency range	Pass
S=8	00	2402	1.074	Within frequency range	Pass
	19	2440	1.077	Within frequency range	Pass
	39	2480	1.080	Within frequency range	Pass


4.7	Fundamental emission output power	VERDICT: PASS
-----	--	----------------------

Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3) & RSS-247 Issue 2 Section 5.4(d)
☒	GTX < 6dBi	Pout≤30dBm, EIRP≤36dBm
☐	GTX > 6dBi	
☐	Non-Fix point-point	Pout≤30-(GTX -6), EIRP≤36dBm
☐	Fix point-point	Pout≤30-[(GTX-6)]/3, EIRP≤36dBm
☐	Point-to-multipoint	Pout≤30-(GTX-6) , EIRP≤36dBm
☐	Overlap Beams	Pout≤30-[(GTX-6)]/3, EIRP≤36dBm
☐	Aggregate power transmitted simultaneously on all beams	Pout≤30-[(GTX-6)]/3, EIRP≤36dBm
☐	singby LE directional beam	Pout≤30-[(GTX-6)]/3+8dB, EIRP≤36dBm

Note 1 : GTX directional gain of transmitting antennas.
Note 2 : Pout is maximum peak conducted output power .
Note 3 : EIRP is equivalent isotropically radiated power.

Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

See next page.

Results

Repeater

Mode	Channel	Test Frequency (MHz)	Output Power (dBm)	Output Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Result
BLE 1Mbps	00	2402	4.74	≤30	8.54	≤36	Pass
	19	2440	4.87	≤30	8.67	≤36	Pass
	39	2480	4.07	≤30	7.87	≤36	Pass
BLE 2Mbps	00	2402	4.74	≤30	8.54	≤36	Pass
	19	2440	4.87	≤30	8.67	≤36	Pass
	39	2480	4.06	≤30	7.86	≤36	Pass
BLE S2	00	2402	4.75	≤30	8.55	≤36	Pass
	19	2440	4.88	≤30	8.68	≤36	Pass
	39	2480	4.06	≤30	7.86	≤36	Pass
BLE S8	00	2402	4.76	≤30	8.56	≤36	Pass
	19	2440	4.87	≤30	8.67	≤36	Pass
	39	2480	4.06	≤30	7.86	≤36	Pass

Note: EIRP = Output Power + Antenna Gain

Repeater: 3.8 dBi

Probe

Mode	Channel	Test Frequency (MHz)	Output Power (dBm)	Output Power Limit (dBm)	EIRP (dBm)	EIRP Limit (dBm)	Result
BLE 1Mbps	00	2402	7.80	≤30	4.70	≤36	Pass
	19	2440	7.48	≤30	4.38	≤36	Pass
	39	2480	8.28	≤30	5.18	≤36	Pass
BLE 2Mbps	00	2402	7.81	≤30	4.71	≤36	Pass
	19	2440	7.50	≤30	4.40	≤36	Pass
	39	2480	8.32	≤30	5.22	≤36	Pass
BLE S2	00	2402	7.82	≤30	4.72	≤36	Pass
	19	2440	7.51	≤30	4.41	≤36	Pass
	39	2480	8.32	≤30	5.22	≤36	Pass
BLE S8	00	2402	7.83	≤30	4.73	≤36	Pass
	19	2440	7.52	≤30	4.42	≤36	Pass
	39	2480	8.32	≤30	5.22	≤36	Pass

Note: EIRP = Output Power + Antenna Gain


Probe: -3.1 dBi

4.8	Power Spectral Density	VERDICT: PASS
-----	------------------------	---------------

Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247 (b)(3) & RSS-247 Issue 2 Section 5.2(b)
Power Spectral Density $\leq 8\text{dBm}/3\text{kHz}$	

Test Configuration



Performed measurements

Port under test	Antenna port	
Test method applied	☒	Conducted measurement
	☐	Radiated measurement
Test setup	Refer to the Annex 3 for test setup photo(s).	
Operating mode(s) used	Mode 1, Mode 2	
Remark	---	

See next page.

Results

Repeater

Mode	Channel	Test Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
BLE 1Mbps	00	2402	4.64	≤8	Pass
	19	2440	4.79	≤8	Pass
	39	2480	3.92	≤8	Pass
BLE 2Mbps	00	2402	4.61	≤8	Pass
	19	2440	4.76	≤8	Pass
	39	2480	3.22	≤8	Pass
BLE S2	00	2402	4.07	≤8	Pass
	19	2440	4.68	≤8	Pass
	39	2480	3.59	≤8	Pass
BLE S8	00	2402	3.54	≤8	Pass
	19	2440	1.49	≤8	Pass
	39	2480	0.63	≤8	Pass

Probe

Mode	Channel	Test Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm/3kHz)	Result
BLE 1Mbps	00	2402	-8.74	≤8	Pass
	19	2440	-9.01	≤8	Pass
	39	2480	-8.04	≤8	Pass
BLE 2Mbps	00	2402	-9.96	≤8	Pass
	19	2440	-10.28	≤8	Pass
	39	2480	-9.52	≤8	Pass
BLE S2	00	2402	1.37	≤8	Pass
	19	2440	1.22	≤8	Pass
	39	2480	2.02	≤8	Pass
BLE S8	00	2402	1.72	≤8	Pass
	19	2440	1.43	≤8	Pass
	39	2480	2.22	≤8	Pass

4.9	Antenna Requirement	VERDICT: PASS
-----	----------------------------	----------------------

Limit

Standard	FCC Part 15 Subpart C Paragraph 15.203
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.	
Standard	RSS-Gen Issue 5 Section 6.8
A transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.	

Antenna Connector Construction

☒	The use of a permanently attached antenna
☒	The antenna use of a unique coupling to the intentional radiator
☐	The use of a nonstandard antenna jack or electrical connector
Please refer to the attached document "Internal Photograph" to show the antenna connector.	

5 IDENTIFICATION OF THE EQUIPMENT UNDER TEST

Remark: The test setup photo and EUT Photo please see appendix.

ANNEX 1 – MEASUREMENT UNCERTAINTY

Emission tests		U_{LAB}	U_{CISPR}
Conducted disturbance - Shielded Room No.1 150 kHz – 30 MHz	AMN: R&S ENV216	2.6 dB	3.4 dB
Radiated disturbance - Anechoic Chamber No.1 30 MHz – 1000 MHz	Horizontal polarization	4.8 dB	6.3 dB
	Vertical polarization	5.4 dB	

Test Item	Uncertainty	
Radio frequency	1.3 ppm	
RF power, conducted	0.16 dB	
Dwell Time	2.02 ms	
Spurious emissions, radiated - Anechoic Chamber No.2	(30MHz~1GHz)	Horizontal: 3.83 dB
		Vertical: 3.82 dB
	(1GHz~8GHz)	Horizontal: 4.18 dB
		Vertical: 3.92 dB
	(8GHz~12.75GHz)	Horizontal: 4.16 dB
		Vertical: 4.98 dB
	(12.75GHz~18GHz)	Horizontal: 4.51 dB
		Vertical: 3.81 dB
	(18GHz~40GHz)	Horizontal: 3.79 dB
		Vertical: 3.80 dB
Humidity	1.4 %	
Temperature	0.5 °C	

ANNEX 2 – USED EQUIPMENT

For AC Power Line Conducted Emission - Shielded Room No.1 (FCC/IC)

Equipment Name	Manufacturer	Type/Model	Serial Number	Last Cal Date	Cal Due date
EMI Test Receiver	ROHDE & SCHWARZ	ESR3	102958	2025/06/15	2026/06/14
Artificial Mains Network	ROHDE & SCHWARZ	ENV216	102772	2025/06/15	2026/06/14
Software	ROHDE & SCHWARZ	ELEKTRA	4.32.0	N/A	N/A

For Radiated Emission (30 MHz to 1000 MHz) - Anechoic Chamber No.1 (FCC/IC)

Equipment Name	Manufacturer	Type/Model	Serial Number	Last Cal Date	Cal Due date
EMI Test Receiver	ROHDE & SCHWARZ	ESR7	102433	2025/11/21	2026/11/20
Open Switch and Control Unit	ROHDE & SCHWARZ	OSP220	102232	N/A	N/A
Software	ROHDE & SCHWARZ	ELEKTRA	4.20.2	N/A	N/A

For Spurious Emissions Test - Anechoic Chamber No.2

Equipment Name	Manufacturer	Type/Model	Serial Number	Last Cal Date	Cal Due date
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	171082	2025/01/21	2026/01/20
Signal & Spectrum Analyzer	ROHDE & SCHWARZ	FSV3044	101286	2025/01/21	2026/01/20
FILTERBANK	ROHDE & SCHWARZ	N/A	100778	N/A	N/A
Open Switch and Control Unit	ROHDE & SCHWARZ	OSP220	102454	N/A	N/A
System Controller Interface	ROHDE & SCHWARZ	SCI-200	520020123	N/A	N/A
Trilog Broadband Antenna	Schwarzbeck	VULB9163	01514	2025/03/14	2026/03/13
Wave Guide Antenna	Schwarzbeck	3117	00240298	2025/03/05	2026/03/04
Antenna	Schwarzbeck	QMS-00208	27745	2025/03/05	2026/03/04
Antenna	Schwarzbeck	QMS-00880	27646	2025/03/17	2026/03/16
Pre-Amplifier	ROHDE & SCHWARZ	SCU08F1	101136	2025/01/21	2026/01/20
Pre-Amplifier	ROHDE & SCHWARZ	SCU18F	100971	2025/02/24	2026/02/23
Pre-Amplifier	ROHDE & SCHWARZ	SCU18F	100970	2025/02/24	2026/02/23
Pre-Amplifier	ROHDE &	SCU40F1	100631	2025/02/24	2026/02/23

	SCHWARZ				
Software	ROHDE & SCHWARZ	ELEKTRA	4.52.1	N/A	N/A

For other test items - Shielded Room (RF)

Equipment Name	Manufacturer	Type/Model	Serial Number	Last Cal Date	Cal Due date
Vector signal generator	ROHDE & SCHWARZ	SMM100A	101780	2025/01/21	2026/01/20
Open switch and control platform	ROHDE & SCHWARZ	OSP150	100856	2025/11/23	2026/11/22
Signal & Spectrum Analyzer	ROHDE & SCHWARZ	FSV3044	101287	2025/02/24	2026/02/23
Wireless Connectivity Tester	ROHDE & SCHWARZ	CMW270	102651	2025/01/21	2026/01/20
Signal Generator	ROHDE & SCHWARZ	SMB100A	183222	2025/01/21	2026/01/20
DC Power Supply	apc	ADC-0800100-15	D222120022	2025/11/23	2026/11/22
AC Power Supply	apc	KDF-11005GS	F322120041	2025/01/21	2026/01/20
Temperature & Humidity Chamber	HESON	HS-225B	CDW230301-01	2025/02/18	2026/02/17
Software	MWRFTtest	MTS 8310	2.0.0.0	N/A	N/A

--- END ---