



RESEARCH & ENGINEERING ■ 750 MONTE RD ■ BENTON HARBOR, MI 49022


Sample Label for Whirlpool WiFi Module

Overall dimensions 44.05mm x 19.05mm

Font sizes as indicated


QR code contains SAID and MAC ADDR information 8mm x 8mm

CE mark is 6mm x 6mm



Actual Size

- NOTES:
- PART MARKING:
PARTS TO BE MARKED WITH: "SEE DETAIL B" PER WHIRLPOOL SPEC C033
INFORMATION REQUIRED ON THE BAR CODE
WHIRLPOOL P/N, PART SERIAL NUMBER, & DATE CODE
 - ADHESIVE BACKED LABELS MUST MEET M4 GRADE-2
 - PART REVISIONS REQUIRE WHIRLPOOL ENGINEERING CODES AND LAB APPROVAL.
 - COMPONENT(S) REFERENCED HEREIN SHALL COMPLY WITH WHIRLPOOL'S
CURRENT SPECIFICATIONS, INCLUDING ITS RESTRICTED MATERIALS LIST
SPECIFICATION GES0084 - US & CANADA COLUMN, AND ALL ANNEXES.
 - REWORK - REWORKED BOARDS MUST BE CLEARLY MARK FOR VISUAL IDENTIFICATION
 - COMPLY WITH PE20 ECM TEST REQUIREMENTS SPECIFICATION W10862068
 - SUPPLIER MUST COMPLY WITH GES0168 GENERAL ECM REQUIREMENTS SPECIFICATION.
 - DISPLAY, LIGHTING, SENSOR AND AUDIO PERFORMANCE BOUNDARY SAMPLE
TEST EQUIPMENT PASS/FAIL LIMITS TO BE REVIEWED AND
APPROVED BY WHIRLPOOL ENGINEERING.
 - TIGHTEN SCREWS TO 0.4±0.15 Nm. SCREWS MUST BE FULLY SEATED.
ALL SNAPS MUST BE FULLY ENGAGED
 - RELIABILITY REQUIREMENT
1 YEAR: RELIABILITY 99.5% AT 90% CONFIDENCE
4 YEARS: RELIABILITY 99% AT 90% CONFIDENCE
10 YEARS: RELIABILITY 95% AT 90% CONFIDENCE
 - DISPLAY FPC TO BE FULLY INSERTED TO THE CONNECTOR.
 - WHEN PURCHASED NOT AS PART OF A HMI ASSEMBLY
A. ASSEMBLY MUST CONFORM TO SHIPPING AND STORAGE PER ISTA 3E,
WITH FOLLOWING ATMOSPHERIC CONDITIONS:
EXTREME COLD, UNCONTROLLED RH AT -29°C
HOT, HUMID AT 38°C THEN EXTREME HEAT, MODERATE RH AT 60°C
B. DISPLAY MUST BE COVERED WITH PROTECTIVE FILM WITH PULL TAB FOR REMOVAL.
 - 100% INSPECTION FOR THE FOLLOWING ITEMS:
A. DISPLAY: (CONDITIONS: 0°, LED = 20mA, CENTER, CIE1931)
LUMINANCE (LV): 350cd/m2 MIN, 450cd/m2 TYPICAL
RED R=255±/-0 G=48±28-48 B=23±80-23
GREEN R=98±55-98 G=25±0/-1 B=0±10/-0
BLUE R=0±115/-0 G=0±82/-0 B=255±/-0
WHITE R=187±68/-161 G=209±21/-51 B=254±0/-56
LCD PIXEL DEFECTS PER ISO 13406-2, CLASS-3 GUIDELINES
CONTRAST RATIO (CR): 600 MIN, 800 TYPICAL (CONDITIONS: 0°, CENTER)
ULTRA LOW POWER MODE: 0.1W MAX
MAX OPERATION MODE: 3.5W
B. ON-BOARD SPEAKER:
RATED POWER = 0.5 WATT
SPL 73±2db (0.1W/0.1M AVERAGE AT 2kHz to 5kHz)
IMPEDANCE @ 1kHz = 80HMS±15%
CONE MATERIAL: POLYARYLATE-COMPOUND
OPERATING TEMP. = 0° TO 85°C
STORAGE TEMP. = 0° TO 85°C
C. WIFI:
ANTENNA "A" 802.11B TX PWR: 16±4dBm
ANTENNA "B" 802.11B TX PWR: 16±4dBm
D. DISPLAY UNIFORMITY (DELTA LV): 80% MIN (CONDITIONS: 0°, WHITE)
 - SAID LABEL PLACEMENT
A. WHEN MODULE IS SHIPPED AS PART OF HMI ASSEMBLY:
TEAR OFF "PORTION-1" AND "PORTION-2" ALONG THE PERFORATION.
ADHERE "PORTION-1" IN THE LOCATION SHOWN AND "PORTION-2" OF SAID LABEL
MUST BE PLACED ON HMI ASSEMBLY (REFER HMI ASSEMBLY FOR LOCATION)
THIS "PORTION-2" WILL BE REMOVED AT APPLIANCE MFG. SITE AND
PLACED ON APPLIANCE IN A LOCATION EASILY ACCESSIBLE TO CONSUMER.
B. WHEN MODULE IS SHIPPED AS STANDALONE ASSEMBLY:
TEAR OFF "PORTION-1" AND "PORTION-2" ALONG THE PERFORATION.
ADHERE "PORTION-1" IN THE LOCATION SHOWN AND "PORTION-2" OF SAID LABEL
SHOULD BE TAPED TO DISPLAY PROTECTIVE FILM WITH A REMOVABLE TAPE.
THIS "PORTION-2" WILL BE REMOVED AT APPLIANCE MFG. SITE AND
PLACED ON APPLIANCE IN A LOCATION EASILY ACCESSIBLE TO CONSUMER.



ISO VIEW
FOR REFERENCE ONLY
SCALE 1:1

REV	DESCRIPTION OF CHANGE	LOC	BY	C.N.	DATE
A	RELEASE W10912629, W10912631 AND W10912630	A5-1	BEHEM	2072362	18-AUG-2016
	CHECKED BY	---	SUBRAS		
B	CALLOUT "MYKAR, REAR COVER, PCBA & SPEAKER HIDDEN" WAS REAR COVER, PCBA & SPEAKER HIDDEN	G3-2			
	ADD "ON BOARD-SPKR, MYKAR" TO ASSEMBLY	H5-2	KIREEK	2094313	16-JAN-2017
	UPDATED PART CHART	---			
	W10912631, W10912630 AND W10912629 TO REV B	G1-2			
	CHECKED BY	---	SUBRAS		17-JAN-2017
	DISPLAY, 3-5, GEBL "W1086069 OR W10910307"	H4-2			
	REAR_CVR_TRMLN - W1095074 WAS TRMLN_REAR_CVR_GEBL - W10912634	H6-2			
	21" SCREEN "W1099149" WAS "W10006580 OR EQUIVALENT"	G7-2			
	REMOVED NOTE "REFER P/N W10464871 FOR FAKRA CONNECTOR"	F5-2			
	REMOVED "CONNECTIVITY" COLUMN	H9-2			
	REMOVED "BACK VIEW"	F8-2	KIREEK	2095231	04-APR-2017
	REMOVED NOTE "SNAPS SEE NOTE 9"	F2-2			
	ADDED VIEW C-C	F7-2			
	ADDED CALLOUT DISPLAY & DISPLAY COVER HIDDEN	H7-2			
	DETAIL B ROTATED 90°	F11-2			
	"PART MARKING LABEL" SIZE CHANGE	E11-2			
	ADDED DIM (10.84) & (22.02)	E8-2			
	ADDED CALLOUT DETAIL A	E6-2			
	W10912631, W10912630 AND W10912629 TO REV C	G1-2			
	CHECKED BY	---	SUBRAS		07-APR-2017

THIS DRAWING IS THE PROPERTY OF WHIRLPOOL. IT CONTAINS CONFIDENTIAL INFORMATION BELONGING TO AND/OR ENTITLED TO WHIRLPOOL. IT IS DISCLOSED IN CONFIDENCE AND SHALL NOT BE REPRODUCED, DISCLOSED OR USED EXCEPT IN A MANNER AND FOR A PURPOSE EXPRESSLY PERMITTED BY WHIRLPOOL IN WRITING.

VENDORS SHALL NOT REVEAL ANY PHYSICAL, DIMENSIONAL, OR PERFORMANCE CHARACTERISTICS UNLESS AUTHORIZED IN WRITING BY WHIRLPOOL ENGINEERING GROUP.

WHIRLPOOL TEST SPECIFICATIONS, IF ANY, ARE NOT INTENDED TO ASSUME ANY RESPONSIBILITY FOR SUBSEQUENT PROBLEMS WITH OR CAUSED BY THE PART, COMPONENT, OR ASSEMBLY PROVIDED BY THE SUPPLIER, AND DO NOT RELIEVE THE SUPPLIER OF ITS OBLIGATIONS INCLUDING, BUT NOT LIMITED TO, THE NEED TO PERFORM ITS OWN TESTING, INSPECTION AND QUALITY CONTROL, AND ASSURING FITNESS FOR USE. ANY WHIRLPOOL RECOMMENDED TEST AND ITS OUTCOME DO NOT IN ANYWAY LIMIT OR CHANGE THE WARRANTY CONTAINED IN WHIRLPOOL'S PURCHASE ORDER OR SUPPLY AGREEMENT.

REVISION	THIRD ANGLE PROJECTION	CREATION DATE
DETAIL SCALE	1:1	29-JUL-2016
DO NOT SCALE FROM		DRAWN BY
		BEHEM
DESCRIPTION (ENGLISH)	TRMLN_ASM, GEBL	
DESCRIPTION (LOCAL)	---	
WHIRLPOOL		
Whirlpool Corporation Benton Harbor, MI USA		
DRAWING SIZE	SHEET	DRAWING REV
A1	1 OF 2	W10912629
		C

In some European factories the letter "W" of the part code mentioned herein will be automatically replaced by the number "4000" (e.g. "W12345678" becomes "400012345678")

