EMC TEST REPORT

Applicant:	MUNIC
Address:	100 Avenue de Stalingrad 94800 Villejuif – France

Manufacturer or Supplier:	MUNIC
Address:	100 Avenue de Stalingrad 94800 Villejuif – France
Product:	telematics embedded system
Brand Name:	MUNIC
Model Name:	C4D-4G4USAA_V8+
FCC ID:	A6GC4D-4G4USV8
Date of tests:	Nov. 15, 2021 ~Dec. 02, 2021

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

☐ **FCC Part 15, Subpart B, Class A**
☒ **FCC Part 15, Subpart B, Class B**
☒ **ANSI C63.4:2014**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Simon Date: Dec. 03, 2021	Luke Lu Date: Dec. 03, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen51800, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.sw@bureauveritas.com

TABLE OF CONTENTS

RELEASE CONTROL RECORD 3

1 GENERAL INFORMATION 4

1.1 GENERAL DESCRIPTION OF EUT 4
1.2 SUMMARY OF TEST RESULTS 6
1.3 MEASUREMENT UNCERTAINTY 6
1.4 DESCRIPTION OF TEST MODES 7
1.5 DESCRIPTION OF SUPPORT UNITS 8

2 EMISSION TEST 9

2.1 CONDUCTED EMISSION MEASUREMENT 9
2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 9
2.1.2 TEST INSTRUMENTS 9
2.1.3 TEST PROCEDURES 10
2.1.4 DEVIATION FROM TEST STANDARD 10
2.1.5 TEST SETUP 11
2.1.6 EUT OPERATING CONDITIONS 11
2.1.7 TEST RESULTS 12
2.2 RADIATED EMISSION MEASUREMENT 14
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 14
2.2.2 TEST INSTRUMENTS 15
2.2.3 TEST PROCEDURE 16
2.2.4 DEVIATION FROM TEST STANDARD 17
2.2.5 TEST SETUP 18
2.2.6 EUT OPERATING CONDITIONS 18
2.2.7 TEST RESULTS 19

3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 23

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P21090018EM01	Original release	Dec. 03, 2021

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT	telematics embedded system	
BRAND NAME	MUNIC	
MODEL NAME	C4D-4G4USAA_V8+	
NOMINAL VOLTAGE	DC13.7V	
MODULATION TYPE	**BT_LE**	GFSK
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK
	WLAN	DSSS, OFDM
	LTE	QPSK/16QAM
OPERATING FREQUENCY	**Bluetooth/BT_LE**	2402MHz ~ 2480MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20/40) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5500 ~ 5700MHz, 5745 ~ 5825 MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT20)/ ac(VHT40) / ac(VHT80)
OPERATING FREQUENCY	**LTE**	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 1710.7MHz ~ 1779.3MHz (FOR LTE Band66) 665.5MHz ~ 695.5MHz (FOR LTE Band71)
HW VERSION	HW.01	
SW VERSION	SW.01	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. C4D-4G4USAA_V8+ have ESIM and SIM two modes, respectively corresponding to MFF2 SIM and 4FF SIM detail describe in PED , pre-scan two models. worst case mode MFF2 SIM is reflected in this report

List of Accessory:

ACCESSORIES	BRAND	MODEL	SPECIFICATION
Battery 1	Howell	Li-polymer 552535H	Capacity：Li-ion, 450mAh
Battery 2	Akkutronics	382530-PTL	Capacity：Li-ion, 450mAh

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B		
Standard Section	**Test Item**	**Result**
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance
	Radiated Emission Test (Above 1GHz)	Compliance

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GMHz	±4.98dB
	1GMHz ~6GMHz	±4.70dB
	6GMHz ~18GMHz	±4.60dB

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	DC13.7V Working+Config

Conducted emission test	
1	DC13.7V Working+Config

NOTE:

1. For conducted emission test, Pre-scan all mode, mode 1 was the worst case and only this mode was presented in this report.
2. For radiated emission test, Pre-scan all mode, test mode 1 was the worst case and only this mode was presented in this report

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR All TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC Source	Kikusui/JP	PMX18-5A	N/A	N/A
2	DC Cable	kistler	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	N/A
3	N/A

2 EMISSION TEST

2.1 CONDUCTED EMISSION MEASUREMENT

2.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 a CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 b CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 03,21	Mar. 02, 22
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 25,21	Feb. 24, 22

NOTE: 1. The test was performed in CE shielded room.

.

2.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.

2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	**TESTED BY**	Carl xie

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.158000	---	10.20	55.57	45.37	L1	ON	9.7
0.158000	28.62	---	65.57	36.95	L1	ON	9.7
0.980000	---	4.66	46.00	41.34	L1	ON	9.7
0.980000	6.99	---	56.00	49.01	L1	ON	9.7
1.828000	---	15.96	46.00	30.04	L1	ON	9.7
1.828000	17.44	---	56.00	38.56	L1	ON	9.7
2.184000	---	17.46	46.00	28.54	L1	ON	9.7
2.184000	18.88	---	56.00	37.12	L1	ON	9.7
4.372000	---	3.80	46.00	42.20	L1	ON	9.7
4.372000	5.16	---	56.00	50.84	L1	ON	9.7
21.660000	---	9.81	50.00	40.19	L1	ON	9.8
21.660000	13.59	---	60.00	46.41	L1	ON	9.8

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



TEST VOLTAGE	Input 120 Vac, 60 Hz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	**TESTED BY**	Carl xie

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.162000	---	8.61	55.36	46.75	N	ON	9.7
0.162000	27.13	---	65.36	38.23	N	ON	9.7
1.872000	---	16.26	46.00	29.74	N	ON	9.8
1.872000	17.72	---	56.00	38.28	N	ON	9.8
2.184000	---	17.82	46.00	28.18	N	ON	9.8
2.184000	19.30	---	56.00	36.70	N	ON	9.8
3.880000	---	3.85	46.00	42.15	N	ON	9.8
3.880000	5.16	---	56.00	50.84	N	ON	9.8
10.608000	---	6.49	50.00	43.51	N	ON	9.8
10.608000	8.87	---	60.00	51.13	N	ON	9.8
22.236000	---	6.89	50.00	43.11	N	ON	9.9
22.236000	9.87	---	60.00	50.13	N	ON	9.9

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)

Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dBµV/m)		
Frequencies (MHz)	**FCC 15B / ICES-003, Class A**	**FCC 15B / ICES-003, Class B**
30-88	49	40
88-216	53.5	43.5
216-960	56	46
960-1000	59.5	54
Above 1000	Avg: 59.5 Peak: 79.5	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40GHz, whichever is lower

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 05,21	Mar. 04,22
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 22,21	Apr. 21,22
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02,21	Jun. 01,22

Frequency range above 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Horn Antenna	ETS-LINDGREN	3117	00168728	May. 19,20	May. 18,23
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 22,21	Apr. 21,22
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 03,21	Jun. 02,22

NOTE: 1. The test was performed in 3m chamber.
2. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.

<Frequency Range above 1GHz>

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
6. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
7. Margin value = Emission level – Limit value.

2.2.4 DEVIATION FROM TEST STANDARD

No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

2.2.7 TEST RESULTS

Below 1GHz worst case：

TEST VOLTAGE	DC 13.7V	**FREQUENCY RANGE**	30-1000 MHz
ENVIRONMENTAL CONDITIONS	25.3deg. C, 51 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Quasi-Peak, 120 kHz
TESTED BY	Jace Hu		

	Freq	Read Level	Ant Factor	Preamp Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	APos	TPos	Rema
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	30.639	27.38	23.64	28.81	0.00	0.64	22.85	40.00	-17.15	---	---	QP
2	35.016	27.96	22.89	28.81	0.00	0.75	22.79	40.00	-17.21	---	---	QP
3	45.733	35.34	16.06	28.79	0.00	0.83	23.44	40.00	-16.56	---	---	QP
4	598.707	27.42	26.25	29.45	0.00	2.27	26.49	46.00	-19.51	---	---	QP
5	723.793	28.00	28.55	29.33	0.00	2.42	29.64	46.00	-16.36	---	---	QP
6 PP	887.398	27.39	30.25	28.93	0.00	2.75	31.46	46.00	-14.54	---	---	QP

REMARKS:
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.



TEST VOLTAGE	DC 13.7V	**FREQUENCY RANGE**	30-1000 MHz
ENVIRONMENTAL CONDITIONS	25.3deg. C, 51 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Quasi-Peak, 120 kHz
TESTED BY	Jace Hu		

	Freq	Read Level	Ant Factor	Preamp Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	APos	TPos	Rem
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	33.335	27.74	23.37	28.81	0.00	0.71	23.01	40.00	-16.99	---	---	QP
2	43.845	33.39	17.42	28.79	0.00	0.85	22.87	40.00	-17.13	---	---	QP
3	47.703	34.63	14.83	28.78	0.00	0.81	21.49	40.00	-18.51	---	---	QP
4	723.793	27.26	28.55	29.33	0.00	2.42	28.90	46.00	-17.10	---	---	QP
5	804.252	27.51	29.07	29.17	0.00	2.58	29.99	46.00	-16.01	---	---	QP
6 PP	938.714	27.18	30.13	28.78	0.00	2.95	31.48	46.00	-14.52	---	---	QP

REMARKS:
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above equipment noise floor are reported.



Above 1GHz worst case

TEST VOLTAGE	DC 13.7V	**FREQUENCY RANGE**	1-18 GHz
ENVIRONMENTAL CONDITIONS	25.3deg. C, 51 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

	Freq	Read Level	Ant Factor	Preamp Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	APos	TPos	Rem
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	9629.201	41.09	37.46	45.73	0.00	13.78	46.60	74.00	-27.40	---	---	Peak
2	10503.250	41.04	38.20	45.89	0.00	14.04	47.39	74.00	-26.61	---	---	Peak
3	11259.290	40.33	38.71	45.57	0.00	14.11	47.58	74.00	-26.42	---	---	Peak
4	13396.090	37.31	39.28	43.83	0.00	15.85	48.61	74.00	-25.39	---	---	Peak
5	16217.810	38.20	41.16	46.43	0.00	17.33	50.26	74.00	-23.74	---	---	Peak
6	PP16791.350	37.68	41.97	46.95	0.00	17.59	50.29	74.00	-23.71	---	---	Peak

REMARKS: 1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 30GHz. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet
4. Only emissions significantly above equipment noise floor are reported.



TEST VOLTAGE	DC 13.7V	**FREQUENCY RANGE**	1-18 GHz
ENVIRONMENTAL CONDITIONS	25.3deg. C, 51 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Peak/Average, 1 MHz
TESTED BY	Jace Hu		

	Freq	Read Level	Ant Factor	Preamp Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	APos	TPos	Rem
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	cm	deg	
1	5211.218	44.31	34.95	46.22	0.00	9.84	42.88	74.00	-31.12	---	---	Peak
2	7506.207	42.28	36.50	46.29	0.00	11.71	44.20	74.00	-29.80	---	---	Peak
3	9685.139	41.22	37.52	45.79	0.00	13.84	46.79	74.00	-27.21	---	---	Peak
4	10874.700	41.72	38.42	45.23	0.00	13.95	48.86	74.00	-25.14	---	---	Peak
5	14527.680	37.18	39.44	43.86	0.00	16.40	49.16	74.00	-24.84	---	---	Peak
6	PP16694.370	37.42	41.81	46.83	0.00	17.54	49.94	74.00	-24.06	---	---	Peak

REMARKS: 1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 30GHz. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet
4. Only emissions significantly above equipment noise floor are reported.



3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---