



## Operational Description

This device is a Dual Band AC1750 Access Point, which operates in both of 2.4GHz and 5GHz bands; the maximum data rate could be up to 1299.9Mbps which OFDM technique. If the signal to noise ratio is too poor which could not support 1299.9Mbps, the 11Mbps data rate with DSSS technique will be applied.

The transmitter of the EUT is powered by 12Vdc from AC adapter or 48Vdc from POE. The antennas are as below:

**For 2.4GHz: PIFA antenna with 4.0dBi gain**

**For 5.0GHz: PIFA antenna with 5.0dBi gain**

The other instruction, please have a look at the user's manual.

FCC 15.407(c) states: The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met"

Data transmission is always initiated by software, which is then pass down through the MAC, through the digital and analog baseband, and finally to the RF chip. Several special packets (ACKs, CTS, PSpoll, etc...) are initiated by the MAC. There are the only ways the digital baseband portion will turn on the RF transmitter, which it then turns off at the end of the packet. Therefore, the transmitter will be on only while one of the aforementioned packets are being transmitted.