

FCC ID: A94-RC48T1-27



## EMISSION -- TESTREPORT

Testreport file no. : **T 20670-1-01 NF** Date : July 17, 2001  
of issue

Model / Type No. : RC48T1-27

Kind of product : Remote Control (Audio / Video Products)

Applicant : Bose Corporation

Manufacturer : Bose Corporation

Licence holder : Bose Corporation

Address : The Mountain  
Framingham, MA, 01701, USA

**Test result** accrdg. to the  
regulation(s) at page 3

:

**POSITIVE**

This testreport with appendix consists of 29 pages.  
The testresult only responds to the tested sample. It is not allowed to copy  
this report even partly without the allowance of the testlaboratory.

**DIRECTORY**

|                                                                           | Page  |
|---------------------------------------------------------------------------|-------|
| <b><u>A) Documentation</u></b>                                            |       |
| Directory                                                                 | 2     |
| Test regulations                                                          | 3     |
| General information                                                       | 4-5   |
| Discovery of worst case condition                                         | 6     |
| Equipment under Test                                                      | 16    |
| Summary                                                                   | 17    |
| <b><u>B) Testdata</u></b>                                                 |       |
| Conducted emissions 10/150 kHz - 30 MHz                                   | 7     |
| Spurious emissions (magnetic field) 10 kHz - 30 MHz                       | 8-9   |
| Spurious emissions (electric field) 30 MHz - 1000 MHz                     | 10-11 |
| Spurious emissions (electric field) 1 GHz - 18 GHz                        | 12-13 |
| Radiated power of the fundamental wave                                    | 14    |
| Conducted power of the fundamental wave measured on the antenna terminals | 15    |
| <b><u>Attachment</u></b>                                                  |       |
| A) Testdata                                                               | A1-A4 |
| B) List of Test Equipment                                                 | B1    |
| C) Photos of the test setup                                               | C1    |
| D) Technical description of the test sample (e.g.CDF, Declaration)        | D1-D3 |
| E) Photos of the EuT                                                      | E1-E3 |
| F) Measurement Protocol for FCC, VCCI and AUSTEL                          | --    |

**TEST REGULATIONS**

The tests were performed according to following regulations :

- o - EN 50081-1 / 2.1991
- o - EN 50081-2 / 7.1993

-----

- o - EN 55011 / 3.1991

- o - Group 1
- o - class A
- o - Group 2
- o - class B

- o - EN 55014 / 4.1993

- o - Household appliances and similar
- o - tools
- o - Semiconductor devices

- o - EN 55014 / A2:1990
- o - EN 55104 / 5.1995

Category:

- o - EN 55015 / A1:1990
- o - EN 55015 / 12.1993

- o - EN 55022 / 5.1995

- o - class A
- o - class B

- o - prEN 55103-1 / 3.1995
- o - prEN 50121-3-2 / 3.1995
- o - EN 60601-1-2 / 4.1994

- o - VCCI

- o - class 1
- o - class 2

- - Part 15 Subpart C (15.227)
- o - Part 15 Subpart C (15.209)

**ADDRESS OF THE TEST LABORATORY**

■ - MIKES BABT PRODUCT SERVICE GmbH  
Ohmstrasse 2-4  
D - 94342 Strasskirchen

o - \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**ENVIRONMENTAL CONDITIONS**

Temperature: \_\_\_\_\_ 15-35 ° C  
Humidity \_\_\_\_\_ 45-60 %  
Atmospheric pressure \_\_\_\_\_ 860-1060 mbar

**POWER SUPPLY SYSTEM UTILIZED**

Power supply system : Battery Unom = 6.0 V DC

**STATEMENT OF MEASUREMENT UNCERTAINTY**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities that can account for a nominal measurement error of  $\pm 4\text{dB}$ . Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

**SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)**

The EuT is a Remote Control to operate audio and video units/systems.

Number of received/tested samples: 1 / 1

Serial Number: Preproduction Sample

**DEFINITIONS FOR SYMBOLS USED IN THIS TEST REPORT**

■ - Black box indicates that the listed condition, standard or equipment is applicable for this Report.  
o - Blank box indicates that the listed condition, standard or equipment was not applicable for this Report.

**M E A S U R E M E N T P R O T O C O L F O R F C C , V C C I**  
**A N D A U S T E L**

**Test Methodology**

Conducted and radiated emission testing is performed according to the procedures in International Special Committee on Radio Interference (CISPR) Publication 22 (1993), European Standard EN 55022 and Australian Standard AS 3548 (which are based on CISPR 22).

The Japanese standard, "Voluntary Control Council for Interference (VCCI) by Data Processing Equipment and Electronic Office Machines, Technical Requirements" is technically equivalent to CISPR 22 (1993). For official compliance, a conformance report must be sent to and accepted by the VCCI.

In compliance with FCC Docket 92-152, "Harmonization of Rules for Digital Devices Incorporate International Standards", testing for FCC compliance may be done following the ANSI C63.4-1992 procedures and using the FCC limits or the CISPR 22 Limits.

**Measurement Error**

The test system for conducted emissions is defined as the LISN, tuned receiver and coaxial cable. The test system for spurious emissions is defined as the antenna, the pre-amplifier, the tuned receiver and the coaxial cable. These test systems have an expected error of  $\pm 3$  dB. The equipment comprising the test systems are calibrated on an annual basis.

**Justification**

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum emissions from the unit.

**General Standard Information**

The test methods used comply with CISPR Publication 22 (1993), EN 55022 (1987) and AS 3548 (1992) - "Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment" and with ANSI C63.4-1992 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

For detailed description of each measurement please refer to section testresults.

**DISCOVERY OF WORST CASE MEASUREMENT CONDITION:**

The Remote Control RC48T1-27 is designed for the operation at a fixed transmitter frequency of 27.145 MHz. To find out the worst case conditions for the complete measurement the following tests have been performed:

- Measurement of the radiated fieldstrength of the operating frequency measured in permanent operation mode in the specified channel. This measurement have been performed in order to find out the maximum transmitted fieldstrength of the Remote Control.
- Measurement of the radiated spurious emissions measured in permanent operation mode in the specified channel. This measurement have been performed in order to find out the maximum spurious emissions of the Remote Control.

Based on this testresults, the measurements have been performed completely on the specified channel. This testresults are documented in the following sections of the testreport.

**TEST RESULT****CONDUCTED EMISSIONS - 10/150 kHz - 30 MHz**

|                                |
|--------------------------------|
| <p>■ - Test not applicable</p> |
|--------------------------------|

**Test location :**

- o - Shielded room no. 1
- o - Shielded room no. 2
- o - Shielded room no. 3
- o - Shielded room no. 4
- o - Shielded room no. 5
- o - Shielded room no. 6
- o - Shielded room no. 7
- o - Anechoic chamber
- o - Full compact chamber

For TEST EQUIPMENT USED please refer to ATTACHMENT B: \_\_\_\_\_

**Description of Measurement**

The final level, expressed in dB $\mu$ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the FCC Limit or to the CISPR limit, which is equivalent to the Australian AS 3548 limit.

To convert between dB $\mu$ V and  $\mu$ V, the following conversions apply:

$$\text{dB}\mu\text{V} = 20(\log \mu\text{V})$$

$$\mu\text{V} = \text{Inverse log}(\text{dB}\mu\text{V}/20)$$

Conducted emissions on the 50 Hz and/or 60 Hz power interface of the EUT are measured in the frequency range of 150 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasipeak detection, and a Line Impedance Stabilization Network (LISN), with 50 $\Omega$ /50  $\mu$ H (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimeters above the floor and is positioned 40 centimeters from the vertical ground plane (wall) of the screen room. If the minimum passing margin appears to be less than 20 dB with a peak mode measurement, the emissions are remeasured using a tuned receiver with quasipeak and average detection and recorded on the data sheets.

**Testresult**

The requirements are

**0 - MET**

**0 - NOT MET**

Min. limit margin

\_\_\_\_\_ dB at \_\_\_\_\_ MHz

Max. limit exceeding

\_\_\_\_\_ dB at \_\_\_\_\_ MHz

Remarks: NOT APPLICABLE

**SPURIOUS EMISSION**

Spurious emissions from the EUT are measured in the frequency range of 9 kHz to 30 MHz using a tuned receiver and a shielded loop antenna. The antenna was positioned 3, 10 or 30 meters horizontally from the EUT. Measurements have been made in all three orthogonal axes and the shielded loop antenna was rotated to locate the maximum of the emissions.

Spurious emissions from the EUT are measured in the frequency range of 30 MHz to 10 times the highest used frequency using a tuned receiver and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasipeak detection and measurements above 1000 MHz are made with a 1 MHz/6 dB bandwidth and peak detection, remeasurement of results which may be critical will be repeated in average mode. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80

**File No. T 20670-1-01 NF , Page 7 of 17**

centimeters above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Interface cables that are closer than 40 centimeters to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimeters from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna was positioned 3, 10 or 30 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees.

#### **SPURIOUS EMISSION (MAGNETIC FIELD) 9 kHz - 30 MHz**

##### **■ - Test not applicable**

- o - in a shielded room
  - o - at a non - reflecting open-site
- and
- o - in a testdistance of 3 meters.
  - o - in a testdistance of 30 meters.

For TEST EQUIPMENT USED please refer to ATTACHMENT B: SER1

#### **Description of Measurement**

The final level, expressed in dB $\mu$ V/m, is arrived at by taking the reading from the EMI receiver (Level dB $\mu$ V) and adding the antenna correction factor and cable loss factor (Factor dB) to it. This result then has to be compared with the relevant FCC limit.

The resolution bandwidth during the measurement is as follows:

9 kHz - 150 kHz: ResBW: 200 Hz

150 kHz - 30 MHz: ResBW: 10 kHz

Example:

| Frequency<br>(MHz) | Level<br>(dB $\mu$ V) | + | Factor<br>(dB) | = | Level<br>(dB $\mu$ V/m) | Limit<br>(dB $\mu$ V/m) | = | Delta<br>(dB) |
|--------------------|-----------------------|---|----------------|---|-------------------------|-------------------------|---|---------------|
| 1.705              | 5                     | + | 20             | = | 25                      | 30                      | = | 5             |

**Testresult in detail:**

| Frequency<br>[MHz] | L: PK<br>[dBµV] | L: AV<br>[dBµV] | L: QP<br>[dBµV] | Correct.<br>[dB] | L: PK<br>[dBµV/m] | L: AV<br>[dBµV/m] | L: QP<br>[dBµV/m] | Limit<br>[dBµV/m] |
|--------------------|-----------------|-----------------|-----------------|------------------|-------------------|-------------------|-------------------|-------------------|
|                    |                 |                 |                 |                  |                   |                   |                   |                   |
|                    |                 |                 |                 |                  |                   |                   |                   |                   |
|                    |                 |                 |                 |                  |                   |                   |                   |                   |

The requirements are

**0 - MET****0 - NOT MET**

Min. limit margin

\_\_\_\_\_ dB

\_\_\_\_\_ MHz

Min. limit margin

\_\_\_\_\_ dB

\_\_\_\_\_ MHz

Remarks:

---



---



---



---

**SPURIOUS EMISSIONS (electric field) 30 MHz - 1000 MHz**

|                         |
|-------------------------|
| 0 - Test not applicable |
|-------------------------|

- - Open-site 1
- o - Open-site 2
- - 3 meters
- o - 10 meters
- o - 30 meters

For TEST EQUIPMENT USED please refer to ATTACHMENT B:

SER2**Description of Measurement**

The final level, expressed in dBµV/m, is arrived by taking the reading from the EMI receiver (Level dBµV) and adding the correction factors and cable loss factor (Factor dB) to it. This is done automatically in the EMI receiver, where the correction factors are stored. This result then has the FCC or CISPR limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets at page 24 - 25. The CISPR 22 limit is equivalent to the Australian AS 3548 limit.

Example:

|                    |                 |   |                |   |                   |                   |   |               |
|--------------------|-----------------|---|----------------|---|-------------------|-------------------|---|---------------|
| Frequency<br>(MHz) | Level<br>(dBµV) | + | Factor<br>(dB) | = | Level<br>(dBµV/m) | Limit<br>(dBµV/m) | = | Delta<br>(dB) |
| 719                | 75              | + | 32.6           | = | 107.6             | 110               | = | -2.4          |

| Frequency<br>[MHz] | L: PK<br>[dBµV] | L: AV<br>[dBµV] | L: QP<br>[dBµV] | Correct.<br>[dB] | L: PK<br>[dBµV/m] | L: AV<br>[dBµV/m] | L: QP<br>[dBµV/m] | Limit<br>[dBµV/m] |
|--------------------|-----------------|-----------------|-----------------|------------------|-------------------|-------------------|-------------------|-------------------|
| 81.7               | 21.0            | 1.0             | 17.0            | 13.5             | 34.5              | 14.5              | 30.5              | 40.0              |
|                    |                 |                 |                 |                  |                   |                   |                   |                   |
|                    |                 |                 |                 |                  |                   |                   |                   |                   |

### Testresult

The requirements are

■ - MET

**0 - NOT MET**

Min. limit margin

9.5 dB

81.7 MHz

Min. limit margin

\_\_\_\_\_ dB

\_\_\_\_\_ MHz

Remarks: The limits are kept.

The measurement was performed up to the 10<sup>th</sup> harmonic

(271.45 MHz)

---

**SPURIOUS EMISSION 1 GHz - 18 GHz**

|                         |
|-------------------------|
| ■ - Test not applicable |
|-------------------------|

**Testlocation :**

- o - Open-site 1
- o - Open-site 2
- o - Anechoic chamber
- o - Full compact chamber

- o - 1 meters
- o - 3 meters
- o - 10 meters

For TEST EQUIPMENT USED please refer to ATTACHMENT B: \_\_\_\_\_

**Description of Measurement**

The final level, expressed in dB $\mu$ V/m, is arrived by taking the reading from the Spectrumalyzer in dB $\mu$ V and adding the correction factors of the test setup incl. cables.

Example of the correction value at 1.8 GHz

| Level reading at<br>1.8 GHz | Correction<br>EMCO 3115 | correction<br>Amplifier<br>AWT 4534 + cable | Correction<br>Factor<br>(summarized) | corrected<br>level |
|-----------------------------|-------------------------|---------------------------------------------|--------------------------------------|--------------------|
| 56 dB $\mu$ V               | +27.3 dB                | -41.2 dB                                    | -15.8 dB                             | 42.1 dB $\mu$ V/m  |

**Testresult in detail:**

| Frequency<br>[MHz] | L: PK<br>[dB $\mu$ V] | L: AV<br>[dB $\mu$ V] | L: QP<br>[dB $\mu$ V] | Correct.<br>[dB] | L: PK<br>[dB $\mu$ V/m] | L: AV<br>[dB $\mu$ V/m] | L: QP<br>[dB $\mu$ V/m] | Limit<br>[dB $\mu$ V/m] |
|--------------------|-----------------------|-----------------------|-----------------------|------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |

**Testresult**

The requirements are

**0 - MET**

**0 - NOT MET**

Min. limit margin

\_\_\_\_\_ dB

\_\_\_\_\_ MHz

Min. limit margin

\_\_\_\_\_ dB

\_\_\_\_\_ MHz

Remarks: \_\_\_\_\_ NOT APPLICABLE \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

**FIELD STRENGTH OF THE FUNDAMENTAL WAVE**

0 - Test not applicable

- - Open-site 1
- o - Open-site 2
- - 3 meters
- o - 10 meters
- o - 30 meters

For TEST EQUIPMENT USED please refer to ATTACHMENT B:

CPR2

**Description of Measurement**

The final level, expressed in dB $\mu$ V/m, is arrived by taking the reading from the EMI receiver (Level dB $\mu$ V) and adding the correction factors and cable loss factor (Factor dB) to it. This is done automatically in the EMI receiver, where the correction factors are stored. This result then has the FCC or CISPR limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets at page 24 - 25. The CISPR 22 limit is equivalent to the Australian AS 3548 limit.

Example:

|           |              |   |        |   |                |   |                     |   |       |
|-----------|--------------|---|--------|---|----------------|---|---------------------|---|-------|
| Frequency | Level        | + | Factor | = | Level          | - | Limit               | = | Delta |
| (MHz)     | (dB $\mu$ V) |   | (dB)   |   | (dB $\mu$ V/m) |   | (dB $\mu$ V/m) (dB) |   |       |
| 315       | 45           | + | 22.5   | = | 67.5           | - | 74.3                | = | -6.8  |

**Testresult in detail:**

| Frequency<br>[MHz] | L: PK<br>[dB $\mu$ V] | L: AV<br>[dB $\mu$ V] | L: QP<br>[dB $\mu$ V] | Correct.<br>[dB] | L: PK<br>[dB $\mu$ V/m] | L: AV<br>[dB $\mu$ V/m] | L: QP<br>[dB $\mu$ V/m] | Limit<br>[dB $\mu$ V/m] |
|--------------------|-----------------------|-----------------------|-----------------------|------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| 27.145             | 55.0                  | 35.0                  | 50.8                  | +11              | 66.0                    | 46.0                    | 61.8                    | 80.0                    |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |
|                    |                       |                       |                       |                  |                         |                         |                         |                         |

**Testresult**

The requirements are

■ - MET

o - NOT MET

Min. limit margin >10.0 dB 27.145 MHz

Min. limit margin \_\_\_\_\_ dB \_\_\_\_\_ MHz

Remarks: The limits are kept. Duty factor correction was not calculated,  
because the Peak-level meets the AV-limit.

**CONDUCTED POWER OF THE FUNDAMENTAL WAVE MEASURED**  
**ON THE ANTENNA TERMINALS**

■ - Test not applicable

**Testlocation :**

- o - Shielded room no. 1
- o - Shielded room no. 2
- o - Shielded room no. 3
- o - Shielded room no. 4
- o - Shielded room no. 5
- o - Shielded room no. 6
- o - Shielded room no. 7
- o - Anechoic chamber
- o - Full compact chamber
- o - Climatic test chamber VLK

For TEST EQUIPMENT USED please refer to ATTACHMENT B: \_\_\_\_\_

**Description of Measurement**

The conducted power of the fundamental wave measured on the antenna terminals in a climatic test chamber. The antenna jack was connected to the input of a communication test receiver. The internal batteries have been removed also and a variable DC power supply was used instead. The measurements have been made with the EUT unmodulated. During the test the supply voltage and the temperature were varied and applied simultaneously. The lower supply voltage was given by the manufacturer. In case the equipment was switching off before, the switch off voltage was used instead.

**Testresult**

The requirements are

**0 - MET**

**0 - NOT MET**

| Frequency range of equipment |                        |           |           |           |           |           |           |           |
|------------------------------|------------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Tempera-<br>ture/°C          | DC supply<br>voltage/V | Power/dBm | Power/dBm | Power/dBm | Power/dBm | Power/dBm | Power/dBm | Power/dBm |
| -30                          |                        |           |           |           |           |           |           |           |
| -20                          |                        |           |           |           |           |           |           |           |
| -10                          |                        |           |           |           |           |           |           |           |
| 0                            |                        |           |           |           |           |           |           |           |
| +10                          |                        |           |           |           |           |           |           |           |
| +20                          |                        |           |           |           |           |           |           |           |
| +30                          |                        |           |           |           |           |           |           |           |
| +40                          |                        |           |           |           |           |           |           |           |
| +50                          |                        |           |           |           |           |           |           |           |

Remarks: \_\_\_\_\_ NOT APPLICABLE \_\_\_\_\_



## SUMMARY

### GENERAL REMARKS:

The product RC48T1-27 has been tested on the following frequency:  
TX-Mode: 27.145 MHz

### FINAL JUDGEMENT:

The requirements according to the technical regulations and tested operation modes are

■ - met.

o - not met.

The equipment under test

■ - **Fulfills** the general approval requirements cited on page 3.

o - **Does not** fulfill the general approval requirements cited on page 3.


Date of receipt of test sample : accdg. to storage record

Testing Start Date : May 30, 2001

Testing End Date : Juni 12, 2001


- MIKES BABT PRODUCT SERVICE GmbH -

i.V.



Günter Mikes  
Dipl.-Ing.(FH)

Test-engineer



Nikolaus Fischer

Tue 2001 Jun 12 08:41

REF 90.0 dB $\mu$ V

MKR 27.147 MHz


10dB/

A\_Max

Posi B\_Blank

Norm

80.36 dB $\mu$ V



CENTER 27.145 MHz

SPAN 2.000 MHz

\*RBW 1 kHz

VBW 1 kHz

SWP 4.0 s

\*ATT 10dB

Preamp

Auftragsnr.: T 20670

Kunde: ROSE

Gerät: REMOTE CONTROL

Modell: HRC

Ser.Nr.:

Norm:

Unterpunkt:

Messung: MBW

Bemerkung: 1 kHz

FCC ID A94-RC48T1-27

A1 of A4

Tue 2001 Jun 12 08:39

REF 90.0 dBμV

MKR 27.151 MHz

10dB/


A\_Max

Posi

B\_Blank

Norm

83.35 dBμV



CENTER 27.145 MHz

SPAN 2.000 MHz

\*RBW 10 kHz

VBW 10 kHz

SWP 40 ms

\*ATT 10dB

Preamp

Auftragsnr.: T 20670

Kunde: BOSE

Gerät: REMOTE CONTROL

Modell: NRC

Ser.Nr.:

Norm:

Unterpunkt:

Messung: MBW


Bemerkung:

10kHz

FCC ID A94-RC48T1-27

A2 OF A4

|               |       |      |         |      |                |
|---------------|-------|------|---------|------|----------------|
| REF 90.0 dBμV |       |      |         |      | MKR 27.147 MHz |
| 10dB/         | A_Max | Posi | B_Blank | Norm | 83.63 dBμV     |



## Preamp

|              |                |
|--------------|----------------|
| Auftragsnr.: | T20670         |
| Kunde:       | BOSE           |
| Gerät:       | REMOTE CONTROL |
| Modell:      | HRC            |
| Ser.Nr.:     |                |
| Norm:        |                |
| Unterpunkt:  |                |
| Messung:     | MBW            |
| Bemerkung:   | 30 kHz         |

[illegible]

A3 OF A4

Tue 2001 Jun 12 08:36

REF 90.0 dB $\mu$ V

MKR 27.147 MHz


10dB/

A\_Max

Posi B\_Blank

Norm

83.74 dB $\mu$ V



CENTER 27.145 MHz

SPAN 2.000 MHz

\*RBW 100 kHz

VBW 100 kHz

SWP 20 ms

\*ATT 10dB

Preamp

Auftragsnr.: T 20670

Kunde: BOSE

Gerät: REMOTE CONTROL

Modell: NRC

Ser.Nr.:

Norm:

Unterpunkt:

Messung: MBW

Bemerkung:

100 kHz

FCC ID A947 RC48 T1-27

A4 OF A4

## Attachment : B

### List of Test Equipment

All test instruments used, in addition to the test accessories, are calibrated and verified regularly.

FCC ID A 9 4 - R C 4 8 T 1 - 2 7

Test Report No: T 20670-1-01 NF

Beginning of Testing: 30-Mai-2001

| Test ID | Model Type     | Kind of Equipment     | Manufacturer            | Equipment No.   |
|---------|----------------|-----------------------|-------------------------|-----------------|
| CPR2    | HCC            | Controller Ant.-Mast  | Rohde & Schwarz München | 04-07/59-97-001 |
|         | RG 214 U       | Antenna cable 2 m     | Huber+Suhner            | 04-07/60-89-463 |
|         | HF 7/8 inch    | Antenna cable 13 m    | Huber+Suhner            | 04-07/60-99-001 |
|         | HF 7/8 inch    | Antenna cable 20 m    | Huber+Suhner            | 04-07/60-99-002 |
|         | HF 7/8 inch    | Antenna cable 40 m    | Huber+Suhner            | 04-07/60-99-003 |
|         | KR - 200       | Coax Antenna Switch   | Rosenberger HF-Technik  | 04-07/60-99-004 |
|         | VULB - 9165    | Super-Broadband-Anten | Schwarzbeck G.          | 04-07/62-00-001 |
|         | ESVP           | Test Receiver         | Rohde & Schwarz München | 04-07/63-89-008 |
|         | ESVP-EZM       | Spectrum Monitor      | Rohde & Schwarz München | 04-07/74-86-016 |
|         | Antennenmast   | Antenna mast          | Rohde & Schwarz München | 04-07/92-97-001 |
| MB      | 27 MHz-Antenna | Rod Antenna           | MIKES PRODUCT SERVICE   | 04-07/62-97-001 |
|         | R 3162         | Spectrum Analyzer     | Advantest               | 04-07/74-00-001 |
| SER2    | HCC            | Controller Ant.-Mast  | Rohde & Schwarz München | 04-07/59-97-001 |
|         | RG 214 U       | Antenna cable 2 m     | Huber+Suhner            | 04-07/60-89-463 |
|         | HF 7/8 inch    | Antenna cable 13 m    | Huber+Suhner            | 04-07/60-99-001 |
|         | HF 7/8 inch    | Antenna cable 20 m    | Huber+Suhner            | 04-07/60-99-002 |
|         | HF 7/8 inch    | Antenna cable 40 m    | Huber+Suhner            | 04-07/60-99-003 |
|         | KR - 200       | Coax Antenna Switch   | Rosenberger HF-Technik  | 04-07/60-99-004 |
|         | VULB - 9165    | Super-Broadband-Anten | Schwarzbeck G.          | 04-07/62-00-001 |
|         | ESVP           | Test Receiver         | Rohde & Schwarz München | 04-07/63-89-008 |
|         | ESVP-EZM       | Spectrum Monitor      | Rohde & Schwarz München | 04-07/74-86-016 |
|         | Antennenmast   | Antenna mast          | Rohde & Schwarz München | 04-07/92-97-001 |

**CONSTRUCTIONAL DATAFORM FOR TESTING OF RADIO EQUIPMENT**

|                 |                                                                    |                   |     |
|-----------------|--------------------------------------------------------------------|-------------------|-----|
| Licence holder: | Bose Corporation                                                   |                   |     |
| Address:        | The Mountain, Framingham, MA, 01701, USA                           |                   |     |
| Manufacturer:   | Bose                                                               |                   |     |
| Address:        |                                                                    |                   |     |
| Type:           | Remote control                                                     |                   |     |
| Model:          | RC28T1-27, RC28T2-27, RC28S2-27<br>RC48T1-27, RC48T2-27, RC48S2-27 |                   |     |
| Serial-No.:     |                                                                    | Protection class: | III |

**Additional informations to the above named model:**

|                                                         |                             |                  |                           |
|---------------------------------------------------------|-----------------------------|------------------|---------------------------|
| <b>Antenna:</b><br><b>transmitter:</b>                  | Type: Internal              |                  |                           |
|                                                         | Length/size: 45mm           |                  |                           |
|                                                         | <b>receiver:</b>            |                  |                           |
|                                                         | Type: Not applicable        |                  |                           |
| <b>Power supply of the transmitter:</b><br><b>Type:</b> | Length/size: Not applicable |                  |                           |
|                                                         | <b>Battery (AAA x 4)</b>    | nominal voltage: | <b>6.0 V</b>              |
|                                                         |                             | lowest voltage:  | <b>V</b>                  |
|                                                         |                             | highest voltage: | <b>V</b>                  |
| <b>Power supply of the receiver:</b><br><b>Type:</b>    |                             |                  | nominal voltage: <b>V</b> |

**Ancillary equipment:**

|                           |             |                   |
|---------------------------|-------------|-------------------|
| Description: <b>None.</b> | Type:       | Serial-no.:       |
| Description: _____        | Type: _____ | Serial-no.: _____ |
| Description: _____        | Type: _____ | Serial-no.: _____ |

**Extreme temperature range in which the approval test should be performed:**

X Category I: General (-20°C to +55°C)

O Category II: Portable (-10°C to +55°C)

O Category III: Equipment for normal indoor use (0°C to +55°C)

**Connectable cables:**

| Name of the cable | Digital                                            | Length/m | shielded                                           |
|-------------------|----------------------------------------------------|----------|----------------------------------------------------|
| None.             | <input type="radio"/> yes <input type="radio"/> no |          | <input type="radio"/> yes <input type="radio"/> no |
|                   | <input type="radio"/> yes <input type="radio"/> no |          | <input type="radio"/> yes <input type="radio"/> no |
|                   | <input type="radio"/> yes <input type="radio"/> no |          | <input type="radio"/> yes <input type="radio"/> no |

O If applicable, if necessary complete overleaf

Page D1

MIKES BABT PRODUCT SERVICE GmbH Ohmstr. 2-4 D-94342 Strasskirchen

Tel.: +49 94 24 94 07-0 Fax.: +49 94 24 94 07-60

Rev.No.: 2.1

|                                                                                                |                                                                                                                                                                                                                                                       |                                                     |                               |
|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|-------------------------------|
| <b>Type designation:</b><br>RC28T1-27, RC28T2-27, RC28S2-27<br>RC48T1-27, RC48T2-27, RC48S2-27 |                                                                                                                                                                                                                                                       |                                                     |                               |
| <b>Name and type designation of individual units comprising the radio equipment:</b>           |                                                                                                                                                                                                                                                       |                                                     |                               |
| <b>Type of equipment:</b>                                                                      |                                                                                                                                                                                                                                                       |                                                     |                               |
| <input type="checkbox"/> Radiotelephone equipment                                              | <input checked="" type="checkbox"/> Remote-control equipment                                                                                                                                                                                          | <input type="checkbox"/> Radiomaritime equipment    | <input type="checkbox"/> LPD  |
| <input type="checkbox"/> One-way radiotelephone equipment                                      | <input type="checkbox"/> Inductive loop system                                                                                                                                                                                                        | <input type="checkbox"/> Inland waterways equipment | <input type="checkbox"/> RLAN |
| <input type="checkbox"/> Personal paging system                                                | <input type="checkbox"/> Radio-relay system                                                                                                                                                                                                           | <input type="checkbox"/> Radionavigation equipm.    | <input type="checkbox"/>      |
| <input type="checkbox"/> Satellite earth station                                               | <input type="checkbox"/> CB radiotelephone equipment                                                                                                                                                                                                  | <input type="checkbox"/> Antenna                    | <input type="checkbox"/>      |
| <input type="checkbox"/> Data transmission equipment                                           | <input type="checkbox"/> Movement detector                                                                                                                                                                                                            | <input type="checkbox"/> Aeronautical equipment     | <input type="checkbox"/>      |
| <b>Technical characteristics:</b>                                                              |                                                                                                                                                                                                                                                       |                                                     |                               |
|                                                                                                | Transmitter-receiver                                                                                                                                                                                                                                  | Transmitter                                         | Receiver                      |
| Frequency range                                                                                |                                                                                                                                                                                                                                                       | 27.145 MHz                                          |                               |
| Maximum no. of channels                                                                        |                                                                                                                                                                                                                                                       | 1                                                   |                               |
| Channel spacing                                                                                |                                                                                                                                                                                                                                                       | 10 kHz                                              |                               |
| Class of emission (type of modulation)                                                         |                                                                                                                                                                                                                                                       | 10K0A1D                                             |                               |
| Maximum RF output power                                                                        |                                                                                                                                                                                                                                                       |                                                     |                               |
| Maximum effective radiated power (ERP)                                                         |                                                                                                                                                                                                                                                       | -10 dBm                                             |                               |
| Output power variable                                                                          |                                                                                                                                                                                                                                                       | ---                                                 |                               |
| Channel switching frequency range                                                              |                                                                                                                                                                                                                                                       | ---                                                 |                               |
| Method of frequency generation                                                                 | <input type="checkbox"/> Synthesizer <input checked="" type="checkbox"/> Crystal <input type="checkbox"/> Other                                                                                                                                       |                                                     |                               |
| Frequency generation TX                                                                        |                                                                                                                                                                                                                                                       |                                                     |                               |
| Frequency generation RX                                                                        |                                                                                                                                                                                                                                                       |                                                     |                               |
| IF                                                                                             | 1st IF                                                                                                                                                                                                                                                | 2nd IF                                              | 3rd IF                        |
| Integral selective calling                                                                     |                                                                                                                                                                                                                                                       |                                                     |                               |
| Audio-frequency interface level at external data socket                                        |                                                                                                                                                                                                                                                       |                                                     |                               |
| Modes of operation                                                                             | <input type="checkbox"/> Duplex mode <input type="checkbox"/> Semi-duplex mode <input checked="" type="checkbox"/> Simplex mode                                                                                                                       |                                                     |                               |
| Power source                                                                                   | <input type="checkbox"/> Mains <input type="checkbox"/> Vehicle-regulated <input checked="" type="checkbox"/> Integral                                                                                                                                |                                                     |                               |
| Antenna socket                                                                                 | <input type="checkbox"/> BNC <input type="checkbox"/> TNC <input type="checkbox"/> N<br><input type="checkbox"/> M <input type="checkbox"/> UHF <input type="checkbox"/> Adapter<br><input checked="" type="checkbox"/> None <input type="checkbox"/> |                                                     |                               |
| <b>Test specifications:</b>                                                                    |                                                                                                                                                                                                                                                       |                                                     |                               |

O If applicable, if necessary complete overleaf

Page D 2

MIKES BABT PRODUCT SERVICE GmbH Ohmstr. 2-4 D-94342 Strasskirchen

Tel.: +49 94 24 94 07-0 Fax.: +49 94 24 94 07-60

Rev.No.: 3.2

**Declarations:**

- We declare that the above information are correct and the named model was supplied with the maximum configuration to the accredited test laboratory.

Framingham, MA, date 28 JUN 01  
place of issue

Jon J. Kante  
Seal and signature of applicant

**O If applicable, if necessary complete overleaf**

**Page D 3**