**PCTEST ENGINEERING LABORATORY, INC.**

6660 – B Dobbin Road · Columbia, MD 21045 · USA

Telephone 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com> (email: randy@pctestlab.com)**CERTIFICATE OF COMPLIANCE****MANUFACTURER NAME & ADDRESS:**NEC AMERICA INC.
6535 N. State Hwy. 161
Irving, TX 75039-2402**DATE & LOCATION OF TESTING:**Date(s) of Tests: April 17, 2006
Test Report S/N: 0604100252-R2
Test Site: PCTEST Lab, Columbia, MD**FCC ID:** A98-KMP6J1CH
APPLICANT: NEC AMERICA INC.**SUMMARY:****FCC ID:** A98-KMP6J1CH
Equipment EUT Type: Single-Band PCS GSM/ EDGE Phone Model: KMP6J1CH1-4A w/ Bluetooth
Max. Output Power: 0.00087 W Conducted
Frequency Range: 2402 – 2480 MHz
FCC Classification: FCC Part 15 Frequency Hopping Spread Spectrum Transceiver (DSS)
FCC Rule Part(s): Parts 15.247; ANSI C-63.4-2001

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C-63.4-2001. If the EUT contains any additional embedded transmitters, then those transmitters were active during all tests. The EUT complies with Industry Bluetooth Standards.

Grant Conditions: Output is peak conducted. This Bluetooth device is approved for use with the handset described in this filing.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President

TABLE OF CONTENTS

ATTESTATION STATEMENTS.....	1
1.0 INTRODUCTION	3
1.1 EVALUATION PROCEDURE.....	3
1.2 SCOPE.....	3
1.3 PCTEST TEST LOCATION.....	3
2.0 PRODUCT INFORMATION.....	4
2.1 EQUIPMENT DESCRIPTION.....	4
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	4
3.0 DESCRIPTION OF TEST.....	5
3.1 CONDUCTED EMISSIONS.....	5
3.2 RADIATED EMISSIONS.....	6
4.0 ANTENNA REQUIREMENTS.....	7
5.0 TEST EQUIPMENT CALIBRATION DATA.....	8
6.0 CONCLUSION	9
EXHIBIT A – TEST RESULTS.....	10
SUMMARY.....	10
20DB BANDWIDTH MEASUREMENT (HANDSET).....	11
OUTPUT POWER MEASUREMENT.....	14
BAND EDGE COMPLIANCE	17
CARRIER FREQUENCY SEPARATION.....	18
DWELL TIME	19
CHANNEL SPACING.....	20
RADIATED HARMONIC MEASUREMENTS (CONT.)	21-26
CONDUCTED SPURIOUS MEASUREMENTS	24
CONDUCTED SPURIOUS MEASUREMENTS	25
CONDUCTED SPURIOUS MEASUREMENTS	26
CONDUCTED SPURIOUS MEASUREMENTS	26
CONDUCTED SPURIOUS MEASUREMENTS	26
RADIATED RESTRICTED BAN MEASUREMENTS	29-30
LINE-CONDUCTED TEST DATA.....	31
EXHIBIT B – LABELING REQUIREMENTS.....	32-33
EXHIBIT C – BLOCK DIAGRAM/ SCHEMATICS	34
EXHIBIT D – OPERATIONAL DESCRIPTION.....	35
EXHIBIT E – TEST SETUP PHOTOGRAPHS.....	36
EXHIBIT F - EUT EXTERNAL/ INTERNAL PHOTOGRAPHS	37
EXHIBIT G - USER'S MANUAL	38

Attestation Statements

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 1 of 38



MEASUREMENT REPORT



FCC Part 15.247 Measurement Report Cover Page

A. General Information

APPLICANT NEC AMERICA INC.
APPLICANT ADDRESS 6535 N. State Hwy. 161
 Irving, TX 75039-2402

TEST SITE PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S) Parts 15.247; ANSI C-63.4-2001
MODEL NAME(S) KMP6J1CH1-4A
FCC ID A98-KMP6J1CH
Test Device Serial No.: S/N: 004401040006112 ☐ Production ☒ Pre-Production ☐ Engineering
FCC CLASSIFICATION FCC Part 15 Spread Spectrum Transceiver (DSS)
Method/ System: FHSS Sequence Spread Spectrum (FHSS)
DATE(S) OF TEST April 17, 2006
TESTS REPORT S/N: 0604100252-R2

A.1 Test Facility / NVLAP Accreditation

Measurements were performed at PCTEST Engineering Lab in Columbia, MD 21045, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC 2451).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules.
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 2 of 38

1.0 INTRODUCTION

1.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2001) and FCC Public Notice dated July 12, 1995 entitled "Guidance on Measurement for Direct Sequence Spread Spectrum System" were used in the measurement of **NEC AMERICA INC. FCC ID: A98-KMP6J1CH**.

Deviation from measurement procedure.....NONE

1.2 Scope

Measurement & determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.3 PCTEST Test Location

The map at the right shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Intern'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1.2-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 2002.




Figure 1.3-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 3 of 38

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Single-Band PCS GSM/ EDGE Phone with Bluetooth.**

- This Bluetooth module has been tested by Bluetooth Qualification Lab, and we confirm the following:
 - A) The hopping sequence is pseudorandom
 - B) All channels were used equally on average
 - C) The receiver input bandwidth equals the transmit bandwidth
 - D) The receiver hops in sequence with the transmit signal
- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

2.2 EMI Suppression Device(s) / Modifications

EMI suppression device(s) added and/or modifications made during testing.

- None

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 4 of 38

3.0 DESCRIPTION OF TEST

3.1 Conducted Emissions




Figure 3.1-1. Shielded Enclosure Line-Conducted Test Facility




Figure 3.1-2. Line Conducted Emission Test Set-Up




Figure 3.1-3. Wooden Table & Bonded LISNs




Figure 3.1-4. LISN Schematic Diagram

The line-conducted facility is located inside a 16'x20'x10' shielded enclosure, manufactured by Ray Proof Series 81 (see Figure 3.1-1). The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 1.5m away from the sidewall of the shielded room (see Figure 3.1-2). Solar Electronics and EMCO Model 3725/2 (10kHz-30MHz) 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room (See Figure 3.1-3). The EUT is powered from the Solar LISN and the support equipment is powered from the EMCO LISN. Power to the LISNs are filtered by a high-current high-insertion loss Ray Proof power line filter (100dB 14Hz-10GHz). The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure. All electrical cables are shielded by braided tinned copper zipper tubing with an inner diameter of ½". If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the Solar LISN. The LISN schematic diagram is shown (See Figure 3.1-4). All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT. The spectrum was scanned from 150kHz to 30Mhz with a 20msec. sweep time. The frequencies producing the maximum level were re-examined using an EMI/Field Intensity Meter and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak and average mode. The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission. Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; scrolling H patter to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Exhibit M. Each EME reported was calibrated using the HP8640B signal generator.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 5 of 38

3.2 Radiated Emissions




Figure 3.2-1. Meter Test Site




Figure 3.2-2. Dimensions of Outdoor Test Site




Figure 3.2-3. Turntable and System Setup




Figure 3.2-4. Normalized Site Attenuation Curves (H&V)

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna was noted for each frequency found. The spectrum was scanned from 30 to 200 MHz using bi-conical antenna and from 200 to 1000 MHz using log-spiral antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using Roberts™ Dipole antennas or horn antenna (see Figure 3.2-1). The test equipment was placed on a wooden and plastic bench situated on a 1.5 x 2 meter area adjacent to the measurement area (see Figure 3.2-2). Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1 MHz depending on the frequency or type of signal. Above 1GHz the detector function was set to CISPR average mode (RBW = 1MHz, VBW = 10Hz).

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table (see Figure 3.2-3). The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed; scrolling H pattern to the EUT and/or support equipment, and powering the monitor from the floor mounted outlet box and the computer aux AC outlet, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Exhibit E-G. Each EME reported was calibrated using the HP8640B signal generator. The Theoretical Normalized Site Attenuation Curves for both horizontal and vertical polarization are shown in Figure 3.2-4.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 6 of 38

4.0 ANTENNA REQUIREMENTS

An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the applicant can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with this requirement.

The antennas are **permanently attached antennae**.

There are no provisions for connection to an external antenna.

Conclusion:

The **Single-Band PCS GSM/ EDGE Phone with Bluetooth** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)
0	2402
:	:
39	2441
:	:
78	2480

Table 4.1 Frequency/ Channel Operations

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 7 of 38

5.0 TEST EQUIPMENT CALIBRATION DATA

TYPE	MODEL	CAL DUE DATE	S/N
Microwave Spectrum Analyzer	HP 8566 (100Hz-22GHz)	12/5/2006	3638A08713
Microwave Spectrum Analyzer	HP 8566 (100Hz-22GHz)	4/17/2006	2542A11898
Spectrum Analyzer/Tracking Generator	HP 8591A (9kHz-18GHz)	3/24/2007	3144A02458
Spectrum Analyzer	HP 8591A (9kHz-18GHz)	4/23/2006	3108A02053
Spectrum Analyzer	HP 8594A (9kHz-29GHz)	11/2/2006	3051A00187
Signal Generator	HP 8650B (500Hz-1GHz)	6/2/2006	2232A19558
Signal Generator	HP 8640B (500Hz-1GHz)	6/2/2006	1851A09816
Signal Generator	Rohde & Schwarz (0.1-1GHz)	9/22/2006	894215012
Aitech/Eaton Receiver	NM 3757A-SL (30MHz-1GHz)	4/12/2006	0792-03271
Aitech/Eaton Receiver	NM 3757A (30MHz-1GHz)	3/11/2007	0805-03334
Aitech/Eaton Receiver	NM 17127A (0.1-32MHz)	9/17/2006	0608-03241
Quasi-Peak Adapter	HP 85650A	8/9/2006	2043A00301
Aitech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	3/11/2007	0194-04082
RG58 Coax Test Cable	No.167	3/26/2007	n/a
Harmonic/Flicker Test System	HP 6841A (IEC 555-23)	11/15/2006	3531A00115
Broadband Amplifier	HP 8447D	2/26/2007	1145A00470
Broadband Amplifier	HP 8447D	2/26/2007	1937A03348
Horn Antenna (2)	EMCO Model 3115 (1-18GHz)	3/15/2007	9704-5182, 9205-3874
Horn Antenna	EMCO Model 3116 (18-40GHz)	3/28/2007	9203-2178
Biconical Antenna (3)	Eaton 94455-1	1/26/2007	1295, 1332, 1277
Roberts Dipoles	Compliance Design (1 set) A100	8/11/2006	5118
EMCO LSN (3)	3816/2, 3816/2, 3725/2	10/26/2006	1077, 1079, 2099
50-ohm Terminator	n/a	n/a	n/a
Microwave Preamp 30dB Gain	HP 83017A (0.5-26.5GHz)	3/26/2007	3123A00181
Microwave Cables	MicroCoax (1.0-26.5GHz)	2/26/2007	n/a
Spectrum Analyzer	HP 8591A	6/18/2006	3034A01395
Modulation Analyzer	HP 8901A	6/26/2006	2432A03467
Microwave Survey Meter	Holaday Model 1501 (2.45GHz)	2/21/2007	80931
Digital Thermometer	Extech Instruments 421305	3/15/2007	426966
Attenuator	4108 (6dB)	3/26/2007	n/a
Shielded Screen Room	RF Lindgren Model 26-2/2-0	n/a	6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81	4/15/2006	F2437 (PCT278)
Environmental Chamber	Associated Systems 1025	8/8/2006	PCT285
OATS	n/a	12/31/2006	n/a

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Table 5-1. Annual Test Equipment Calibration Schedule

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 8 of 38

6.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Single-Band PCS GSM/ EDGE Phone with Bluetooth** is in compliance with Part 15C of the FCC Rules.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 9 of 38

EXHIBIT A – Test Results

Summary

The intentional radiator has been tested in a simulated typical installation to demonstrate compliance with the relevant FCC performance and procedural standards.

The radio was transmitting at full power on the specified channels and at a data rate(s) specified above. The channels tested are high, middle and low of the allocated bands.

Final system data was gathered in a mode that tended to maximize emissions by varying the orientation of the EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Method/System: Frequency Hopping Spread Spectrum (FHSS)

Number of channels: 79

FCC Part Section(s)	RSS 210 Section	Test Description	Test Limit	Result
<u>TRANSMITTER MODE (TX)</u>				
15.247(a)(2)		20dB Bandwidth	< 1 MHz	Pass
15.247(b)	6.22(o)(a3)	Transmitter Output Power	< 1 Watt	Pass
15.247(c)	5.9.1 6.2.2(o)(e1)	Occupied BandEdge Out-of-Band Emissions (BandEdge at 20dB below)	Radiated <20dBc. Emissions in restricted bands must meet the radiated limits detailed in 15.207	Pass
15.205 15.209	6.2.1 6.3	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	< FCC 15.209 limits or < RSS-210 table 3 limits Emissions in restricted bands must meet the radiated limits detailed in 15.209	Pass
15.207	6.6	AC Conducted Emissions 150kHz – 30MHz	EN55022	Pass
<u>RECEIVER MODE (RX)</u>				
15.207	7.4	AC Conducted Emissions 150kHz – 30MHz	Class B = 250µV	Pass
15.209	7.3	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.209 limits or < RSS-210 table 3 limits	Pass

Table A-1. Summary of Test Results

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 10 of 38

EXHIBIT A – Test Results (Cont.)

20dB Bandwidth Measurement (Handset)

§15.247(a)(2)

The bandwidth at 20dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the receive antenna while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 30 kHz (10dB/div)
VBW = 30 kHz
Span = 1.5 MHz
Ref. Level = -0.63 dBm
Sweep = 2.04 ms

Frequency (MHz)	Channel No.	Test Results	
		20dB Bandwidth (kHz)	Pass / Fail
2402	0	956	Pass
2441	39	959	Pass
2480	78	967	Pass

– See next pages for actual measured spectrum plots

Table A-2. Conducted Bandwidth Measurements






Figure A-1. Test Instrument & Measurement Setup

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 11 of 38



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 12 of 38



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 13 of 38

EXHIBIT A – Test Results (Cont.)

Output Power Measurement

§15.247(b)

Measurement is made while the EUT is operating in non-hopping transmission mode

Minimum Standard – The transmitter peak output power shall not exceed 1 watt.

Frequency (MHz)	Channel No.	Conducted Power	
		dBm	mW
2402.00	0	-0.63	0.865
2441.00	39	-0.75	0.841
2480.00	78	-0.85	0.822

Table A-3. Output Power Measurements






Figure A-3. Test Instrument & Measurement Setup





PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 15 of 38



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 16 of 38

EXHIBIT A – Test Results (Cont.)


Band Edge Compliance



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 17 of 38

EXHIBIT A – Test Results (Cont.)

Carrier Frequency Separation




PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 18 of 38

EXHIBIT A – Test Results (Cont.)

Dwell Time

§15.247(b) / §15.205 & §15.209





PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 19 of 38

EXHIBIT A – Test Results (Cont.)

Channel Hopping

§15.247(b) / §15.205 & §15.209



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 20 of 38

EXHIBIT A – Test Results (Cont.)

Radiated Harmonic Measurements (Cont.)

§15.247(b) / §15.205 & §15.209

Distance of Measurements: 3 Meters

Channel: 00

FREQ. (MHz)	LEVEL (dBm)	AFCL (dB)	POL (H/V)	F/S (dBuV/m)	F/S (uV/m)	MARGIN (dB)
4804.00	-108.32	40.6	H	39.3	92.0	-14.7
7206.00	-106.16	45.8	H	46.6	214.8	-7.4
9608.00	-135.00	49.6	H	21.6	12.0	-32.4
12010.00	-135.00	52.1	H	24.1	16.0	-29.9

Table A-8. Harmonic Measurements




Figure A-7. Radiated limits at 3 meters.

NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table G-1. (Note: * = Restricted Band measured frequency)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 1 GHz, the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 21 of 38

EXHIBIT A – Test Results (Cont.)

Radiated Harmonic Measurements (Cont.)

§15.247(b) / §15.205 & §15.209

Distance of Measurements: 3 Meters

Channel: 39

FREQ. (MHz)	LEVEL (dBm)	AFCL (dB)	POL (H/V)	F/S (dBuV/m)	F/S (MV/m)	MARGIN (dB)
4882.00	-106.56	40.5	H	40.9	111.4	-13.1
7323.00	-105.60	47.3	H	48.7	272.3	-5.3
9764.00	-135.00	50.1	H	22.1	12.7	-31.9
12205.00	-135.00	52.5	H	24.5	16.8	-29.5

Table A-9. Radiated Fundamental & Harmonic Measurements




Figure A-8. Radiated limits at 3 meters.

NOTES:

1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table G-1. (Note: * = Restricted Band measured frequency)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new/fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 1 GHz, the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 22 of 38

EXHIBIT A – Test Results (Cont.)

Radiated Harmonic Measurements (Cont.)

§15.247(b) / §15.205 & §15.209

Distance of Measurements: 3 Meters

Channel: 78

FREQ. (MHz)	LEVEL (dBm)	AFCL (dB)	POL (H/V)	TOTAL (dBuV/m)	F/S (MV/m)	MARGIN (dB)
4960.00	-105.18	40.6	H	42.4	132.1	-11.6
7440.00	-103.21	45.9	H	49.7	305.1	-4.3
9920.00	-135.00	49.4	H	21.4	11.7	-32.6
12400.00	-135.00	53.4	H	25.4	18.5	-28.7

Table A-10. Radiated Fundamental & Harmonic Measurements




Figure A-9. Radiated limits at 3 meters.

NOTES:



1. All harmonics in the restricted bands specified in §15.205 are below the limit shown in Table G-1. (Note: * = Restricted Band measured frequency)
2. All harmonics/spurs are at least 20 dB below the highest emission in the authorized band using RBW = 100kHz
3. Average Measurements > 1GHz using RBW = 1 MHz VBW = 10 Hz
4. The peak emissions above 1 GHz are not more than 20 dB above the average limit.
5. The antenna is manipulated through typical positions, polarity and length during the tests.
6. The EUT is supplied with nominal AC voltage or/and a new /fully-recharged battery.
7. The spectrum is measured from 9kHz to the 10th harmonic and the worst-case emissions are reported.
8. < - 135 dBm are below the analyzer floor level.
9. Above 1 GHz, the limit is 500 μ V/m (54dB μ /m) at 3 meters radiated.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 23 of 38

EXHIBIT A – Test Results (Cont.)

Conducted Spurious Measurements

\$15.205 / \$15.209




PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 24 of 38

EXHIBIT A – Test Results (Cont.)

Conducted Spurious Measurements

§15.205 / §15.209





PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 25 of 38

EXHIBIT A – Test Results (Cont.)

Conducted Spurious Measurements

\$15.205 / \$15.209





PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 26 of 38

EXHIBIT A – Test Results (Cont.)

Conducted Spurious Measurements

\$15.205 / \$15.209




PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 27 of 38

EXHIBIT A – Test Results (Cont.)

Conducted Spurious Measurements

§15.205 / §15.209



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 28 of 38

EXHIBIT A – Test Results (Cont.)

Radiated Restricted Band Measurements

§15.205 / §15.209

Special attention is made for the EUT's harmonic and spurious radiated emission in the restricted bands of operations. The EUT was tested from 9kHz and up to the tenth harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average measurement was used, using RBW 1MHz – VBW 10Hz and linearly polarized horn antennas. All harmonics/spurs are at least 20dB below the highest emission in the authorized band using RBW = 100kHz. In addition, peak measurements were taken to ensure that the peak levels are not more than 20dB above the average limit. All out of band emissions, other than those created by the spreading sequence, data sequence, and the carrier modulation must not exceed the limits show in Table G-1 per Section 15.209.

Frequency	F/S (mV/m)	Measured Distance (Meters)
0.009 – 0.490 MHz	2400 / F (kHz)	300
0.490 – 1.705 MHz	24000 / F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table A-18. Restricted Band Limits

TEST MEASUREMENT EQUIPMENT

Agilent E4448A	PSA Spectrum Analyzer 3 Hz - 50GHz
HP 8566B	Spectrum Analyzer 100Hz – 22GHz
HP 83017A	Microwave Analyzer 40dB Gain (0.5 – 26.5GHz)
HP 3784A	Digital Transmission Analyzer
EMCO 3115	Horn Antenna (1 – 18GHz)
HP 8495A	20dB Attenuator (DC-40GHz) 0 –70dB
HP 8493B	10dB Attenuator
MicroCoax Cables	Low Loss Microwave Cables (1 – 26.5GHz)
CDI Dipoles	Dipole Antennas (30 – 1000MHz)
EMCO 3116	Horn Antenna (18 – 40GHz)

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 29 of 38

EXHIBIT A – Test Results (Cont.)

Radiated Restricted Band Measurements (Cont.)

§15.205 / §15.209 courtesy

Operating Frequency: 2480 MHz

Channel Number: 78

FREQ (MHz)	Level (dBm)	AFCL (dB/m)	POL (H/V)	F/S (dBμV/m)	F/S (uV/M)	Margin (dB)
2483.5	-110.9	33.0	H	27.9	24.7	-26.1
2487.6	-109.4	33.0	H	29.4	29.4	-24.6
2488.0	-109.6	33.1	H	29.2	28.7	-24.8
2491.4	-110.3	33.1	H	28.5	26.5	-25.5
2495.9	-110.9	33.2	H	27.9	24.7	-26.1
2496.8	-110.0	33.2	H	28.8	27.4	-25.2

Table A-19. Radiated Restricted Band Measurements at 3-meters

NOTES:


1. The antenna is manipulated through typical positions, polarity and length during the testing.
2. The EUT is supplied with the minimal AC voltage or /and a new /fully re-charged battery.
3. The spectrum is measured from 9kHz up to the 10th harmonic and the worst-case emissions are reported.
4. The conducted limits are shown on Figure A-14. Above 1 GHz the limit is 500μV/m.
5. < -135 dBm is below the analyzer measurement floor level.
6. The peak emissions above 1 GHz are not more than 20 dB above average limit.

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 30 of 38


EXHIBIT A – Test Results (Cont.)

Line-Conducted Test Data

§15.207



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	2.291	28.58	56.00	-27.42	22.96	46.00	-23.04
2	2.170	32.26	56.00	-23.74	23.80	46.00	-22.20
3	2.046	33.96	56.00	-22.04	23.14	46.00	-22.86
4	2.172	32.05	56.00	-23.95	23.58	46.00	-22.42
5	1.976	30.60	56.00	-25.40	23.50	46.00	-22.50
6	2.528	29.70	56.00	-26.30	23.25	46.00	-22.75
7	1.938	32.25	56.00	-23.75	23.21	46.00	-22.79
8	1.977	30.48	56.00	-25.52	23.18	46.00	-22.82
9	1.889	29.90	56.00	-26.10	23.38	46.00	-22.62
10	1.932	36.49	56.00	-19.51	23.50	46.00	-22.50



No.	Freq. [MHz]	Quasi-Pk [dBuV]	Limit [dBuV]	Margin [dB]	Average [dBuV]	Limit [dBuV]	Margin [dB]
1	2.081	46.85	56.00	-9.15	22.70	46.00	-23.30
2	2.272	26.37	56.00	-29.63	22.66	46.00	-23.34
3	2.035	28.02	56.00	-27.98	22.76	46.00	-23.24
4	2.276	26.88	56.00	-29.12	22.62	46.00	-23.38
5	1.904	28.43	56.00	-27.57	22.88	46.00	-23.12
6	2.508	26.81	56.00	-29.19	22.72	46.00	-23.28
7	1.968	27.06	56.00	-28.94	22.68	46.00	-23.32
8	1.766	26.43	56.00	-29.57	22.62	46.00	-23.38
9	1.879	27.29	56.00	-28.71	22.64	46.00	-23.36
10	1.910	27.86	56.00	-28.14	22.71	46.00	-23.29

Notes:

- All Modes of operation were investigated and the worst-case emissions are reported.
- The limit for Class B device(s) from 150kHz to 30MHz are Specified in EN55022.
- Line A = Phase; Line B = Neutral
- Deviations to the Specifications: *None*.

PCTEST LAB TEST REPORT 15.247	PCTEST ENGINEERING & LAB., INC.	FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 31 of 38

EXHIBIT B – Labeling Requirements

Sample Label & Location

New Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The sample label shown below shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name, FCC ID, and the FCC logo must be displayed on the device per Section 15.19 (b)(2).



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 32 of 38

EXHIBIT B – Labeling Requirements (Cont.)

Sample Label & Location



PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 33 of 38

EXHIBIT C – Block Diagram/Schematics

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH	Page 34 of 38

EXHIBIT D – Operational Description

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT	 Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH Page 35 of 38

EXHIBIT E – Test Setup Photographs

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT	 Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH Page 36 of 38

EXHIBIT F – EUT External/ Internal Photographs

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT	 Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM/ EDGE Phone w/ Bluetooth	FCC ID: A98-KMP6J1CH Page 37 of 38

EXHIBIT G – User’s Manual

PCTEST LAB TEST REPORT 15.247		FCC CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0604100252-R2	Test Dates: April 17, 2006	EUT Type: Single-Band PCS GSM / EDGE Phone w / Bluetooth	FCC ID: A98-KMP6J1CH	Page 38 of 38