



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 24 Certification

Applicant Name:
NEC Corporation of America
Radio Communications Systems Division
6535 N. State Highway 161
Irving, TX 75039

Date of Testing:
September 6 - 7, 2006
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0608280741

FCC ID: A98-KMP7N2L1

APPLICANT: NEC CORPORATION OF AMERICA

Application Type: Certification
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §24(E)
EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth
Model(s): KMP7N2L1
Tx Frequency Range: 1850.20 - 1909.80MHz (PCS GSM)
Rx Frequency Range: 1930.20 - 1989.80MHz (PCS GSM)
Max. RF Output Power: 1.959 W EIRP PCS GSM (32.92 dBm)
Max. SAR Measurement: 0.75 W/kg PCS GSM Head SAR; 1.01 W/kg PCS GPRS Body SAR
Emission Designator(s): 319KGXW (GSM)
Test Device Serial No.: identical prototype [S/N: 00440120010757]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is EIRP for Part 24. SAR compliance for body-worn operating configuration is based on a separation distance of 1.5cm between the back of the unit and the body of the user. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. Belt clips or holsters may not contain metallic components.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.



Randy Ortanez
President



FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 1 of 21

TABLE OF CONTENTS

FCC PART 24 MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 MEASUREMENT PROCEDURE	4
1.2 SCOPE	4
1.3 TESTING FACILITY	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION	5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
3.0 DESCRIPTION OF TESTS	6
3.1 OCCUPIED BANDWIDTH EMISSION LIMITS	6
3.2 PCS - BASE FREQUENCY BLOCKS	6
3.3 PCS - MOBILE FREQUENCY BLOCKS	6
3.4 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	7
3.5 FREQUENCIES	7
3.6 RADIATED SPURIOUS AND HARMONIC EMISSIONS	7
3.7 FREQUENCY STABILITY / TEMPERATURE VARIATION	7
4.0 TEST EQUIPMENT CALIBRATION DATA	9
5.0 SAMPLE CALCULATIONS	10
6.0 TEST RESULTS	11
6.1 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT MEASUREMENTS	12
6.2 PCS GSM RADIATED MEASUREMENTS	13
6.3 FREQUENCY STABILITY (PCS GSM)	16
7.0 CONCLUSION	18
EXHIBIT A - PLOT(S) OF EMISSIONS	19
EXHIBIT B – TEST SETUP PHOTOGRAPHS	20
EXHIBIT C – INTERNAL/EXTERNAL PHOTOGRAPHS	21



MEASUREMENT REPORT




FCC Part 24

A. §2.1033 General Information

APPLICANT: NEC Corporation of America
APPLICANT ADDRESS: Radio Communications Systems Division
 6535 N. State Highway 161, Irving, TX 75039
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §24(E)
MODEL NAME: KMP7N2L1
FCC ID: A98-KMP7N2L1
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
EMISSION DESIGNATOR(S): 319KGXW (GSM)
MODE: GSM
FREQUENCY TOLERANCE: $\pm 0.00025\%$ (2.5 ppm)
Test Device Serial No.: 00440120010757 ☐ Production ☒ Pre-Production ☐ Engineering
DATE(S) OF TEST: September 6 - 7, 2006
TEST REPORT S/N: 0608280741

A.1 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 3 of 21	

1.0 INTRODUCTION

1.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 1-1). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.





Figure 1-1. Diagram of 3-meter outdoor test range

Deviation from Measurement Procedure.....None

1.2 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.3 Testing Facility



These measurement tests were conducted at PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.

Figure 1-3. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 4 of 21

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **NEC Single-Band PCS GSM/GPRS Phone with Bluetooth FCC ID: A98-KMP7N2L1**. The EUT consisted of the following component(s):

Manufacturer / Description	FCC ID	Serial Number
NEC Single-Band PCS GSM/GPRS Phone with Bluetooth	A98-KMP7N2L1	00440120010757

Table 2-1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

EMI suppression device(s) added and/or modifications made during testing.

- None


3.0 DESCRIPTION OF TESTS

3.1 Occupied Bandwidth Emission Limits

§2.1049, 24.238(a)

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

3.2 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

3.3 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 6 of 21	

3.4 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500 Hz tone at a level of 16 dB greater than that required to provide 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with one port terminated in 50 Ω) and an 870 MHz to 890 MHz band-pass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the band-pass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90 dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the band-pass filter insertion loss to be calibrated.

3.5 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

3.6 Radiated Spurious and Harmonic Emissions

§2.1051, 24.238(a); RSS-132 (4.5.1.1)

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested using a PCL of 0 in the PCS Band.

3.7 Frequency Stability / Temperature Variation

§2.1055, 24.235; RSS-132 (4.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 7 of 21

3.7 Frequency Stability / Temperature Variation (Cont'd)

§2.1055, 24.235; RSS-132 (4.3)

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight "soak" at -30°C without any power applied.
3. After the overnight "soak" at -30°C (usually 14-16 hours), the equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 8 of 21	

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

TYPE	MODEL	CAL. DUE DATE	CAL. INTERVAL	SERIAL No.
Microwave Spectrum Analyzer	Agilent E4448A (3Hz-50GHz)	09/19/06	Annual	US42510244
Spectrum Analyzer	HP 8591A (9kHz-1.8GHz)	10/15/06	Annual	3108A02053
Spectrum Analyzer	HP 8566B (100Hz-22GHz)	12/22/06	Annual	3638A08713
PSG Analog Signal Generator	Agilent E8257D (250kHz-20GHz)	02/11/07	Annual	MY45470194
5 Watt Amplifier	5S1G4 (800MHz-4.2GHz)	N/A	N/A	22332
Universal Radio Communication Tester	CMU200	04/20/07	Annual	836370/079
Universal Power Meter	Gigatronics 8651A (50MHz-18GHz)	07/28/07	Annual	1834052
Power Sensor	Gigatronics 80701A	04/11/07	Annual	1833460
Quasi-Peak Adapter	HP 85650A	12/22/06	Annual	2043A00301
Preamplifier	HP 8449B (1-26.5GHz)	12/22/06	Annual	3008A00985
Attenuation/Switch Driver	HP 11713A	12/22/06	Annual	N/A
Preselector	HP 85685A (20Hz-2GHz)	12/22/06	Annual	N/A
6dB Res BW Spec. Analyzer Display	OPT 462	12/22/06	Annual	3701A22204
Horn Antenna	EMCO Model 3115 (1-18GHz)	08/25/07	Bi-Annual	9704-5182
Horn Antenna	EMCO Model 3116 (18-40GHz)	08/25/07	Bi-Annual	9203-2178
Roberts Dipoles	Compliance Design (1 set) A100	08/31/07	Annual	5118
10dB Attenuator	HP 8493B	N/A	Annual	N/A
Bi-Directional Coupler	PE2208-6	N/A	Annual	N/A
Microwave Cables	MicroCoax (1.0-26.5GHz)	02/26/07	Annual	N/A

Table 4-1. Test Equipment

5.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

Spurious Radiated Emission - PCS Band

Example: Channel 512 PCS Mode 2nd Harmonic (3700.40 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 10 of 21	

6.0 TEST RESULTS

Summary

The intentional radiator has been tested in a simulated typical installation to demonstrate compliance with the relevant FCC performance and procedural standards. The radio was transmitting at full power on the specified channels. The channels tested are high, middle and low of the allocated bands. Final system data was gathered in a mode that tended to maximize emissions by varying the orientation of the EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization. This device was tested using a PCL of 0 in the PCS Band.

Method/System: PCS Licensed Transmitter Held to Ear (PCE)

Mode(s): GSM

FCC Part Section(s)	RSS Section	Test Description	Test Limit	Test Condition	Test Result
<u>TRANSMITTER MODE (TX)</u>					
2.1049, 24.238(a)	N/A	Occupied Bandwidth	N/A	CONDUCTED	N/A
24.238(a)	RSS-132 (4.5.1.1)	Band Edge / Conducted Spurious Emissions	< 43 + log ₁₀ (P[Watts]) at Band Edge / for all out-of-band emissions		PASS
2.1046	N/A	Transmitter Conducted Output Power	N/A		N/A
24.232(c)	RSS-132 (4.4) [SRSP-510 (5.1.2)]	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP	RADIATED	PASS
2.1051, 24.238(a)	RSS-132 (4.5.1.1)	Undesirable Emissions	< 43 + log ₁₀ (P[Watts]) for all out-of-band emissions		PASS
2.1055, 24.235	RSS-132 (4.3)	Frequency Stability	< 2.5 ppm		PASS
<u>RECEIVER MODE (RX)</u>					
15.107	RSS-210 (7.4)	AC Conducted Emissions 150kHz – 30MHz	EN55022	Line Conducted	PASS
15.109	RSS-132 (4.6) [RSS-Gen (7.2.2)] / RSS-210 (7.3)	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.209 limits or < RSS-210 table 3 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS
<u>RF EXPOSURE (SAR)</u>					
2.1093	RSS-102	SAR Test or MPE	1.6 W/kg (SAR Limit)	3 Channels	PASS

Table 6-1. Summary of Test Results

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 11 of 21	

6.1 Equivalent Isotropic Radiated Power Output Measurements

§24.232(c); RSS-132 (4.4), [SRSP-510 (5.1.2)]

Radiated measurements at 3 meters

Supply Voltage: 3.8 VDC

Modulation: PCS GSM

FREQ. (MHz)	REF. LEVEL (dBm)	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Battery
1850.20	-10.311	H	95	32.770	1.892	Standard
1880.00	-10.581	H	95	32.670	1.849	Standard
1909.80	-10.501	H	95	32.920	1.959	Standard

Table 6-2. Equivalent Isotropic Radiated Power Output Data

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested using a PCL of 0 in the PCS Band. This unit was tested with its standard battery.

6.2 PCS GSM Radiated Measurements

S2.1051, 24.238(a); RSS-132 (4.5.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 32.920 dBm = 1.959 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 45.92 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-52.00	6.10	-45.90	H	78.8
5550.60	-54.85	6.70	-48.15	H	81.1
7400.80	-66.07	6.80	-59.27	H	92.2
9251.00	-85.68	6.50	-79.18	H	112.1
11101.20	-84.38	7.00	-77.38	H	110.3

Table 6-3. Data for Radiated Harmonics (Low Channel)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested using a PCL of 0 in the PCS Band. This unit was tested with its standard battery.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 13 of 21



PCS GSM Radiated Measurements (Cont'd)

§2.1051, 24.238(a); RSS-132 (4.5.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 661
MEASURED OUTPUT POWER: 32.920 dBm = 1.959 W
MODULATION SIGNAL: GSM
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10}(W) =$ 45.92 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-48.45	6.10	-42.35	H	75.3
5640.00	-40.03	6.70	-33.33	H	66.2
7520.00	-62.42	6.80	-55.62	H	88.5
9400.00	-85.78	6.50	-79.28	H	112.2
11280.00	-83.78	7.00	-76.78	H	109.7

Table 6-4. Data for Radiated Harmonics (Mid Channel)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested using a PCL of 0 in the PCS Band. This unit was tested with its standard battery.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 14 of 21



PCS GSM Radiated Measurements (Cont'd)

§2.1051, 24.238(a); RSS-132 (4.5.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz
CHANNEL: 810
MEASURED OUTPUT POWER: 32.920 dBm = 1.959 W
MODULATION SIGNAL: GSM
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10}(W) =$ 45.92 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-48.39	6.10	-42.29	H	75.2
5729.40	-45.97	6.70	-39.27	H	72.2
7639.20	-65.15	6.80	-58.35	H	91.3
9549.00	-85.68	6.50	-79.18	H	112.1
11458.80	-83.98	7.00	-76.98	H	109.9

Table 6-5. Data for Radiated Harmonics (High Channel)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested using a PCL of 0 in the PCS Band. This unit was tested with its standard battery.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page 15 of 21



6.3 Frequency Stability (PCS GSM)

S2.1055, 24.235; RSS-132 (4.3)

OPERATING FREQUENCY: 1,880,000,008 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 3.8 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.80	+ 20 (Ref)	1,880,000,008	0.00	0.000000
100 %		-30	1,880,000,102	-94.00	-0.000005
100 %		-20	1,880,000,177	-169.20	-0.000009
100 %		-10	1,880,000,083	-75.20	-0.000004
100 %		0	1,879,999,764	244.40	0.000013
100 %		10	1,879,999,688	319.60	0.000017
100 %		20	1,880,000,177	-169.20	-0.000009
100 %		25	1,879,999,839	169.20	0.000009
100 %		30	1,880,000,215	-206.80	-0.000011
100 %		40	1,880,000,252	-244.40	-0.000013
100 %		50	1,880,000,158	-150.40	-0.000008
100 %		60	1,880,000,177	-169.20	-0.000009
85 %	3.23	20	1,879,999,782	225.60	0.000012
115 %	4.37	20	1,879,999,839	169.20	0.000009
BATT. ENDPOINT	3.02	20	1,879,999,858	150.40	0.000008


Table 6-6. PCS GSM Frequency Deviation Data

Note: This unit was tested with its standard battery.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 16 of 21	

Frequency Stability (PCS GSM) (Cont'd)

§2.1055, 24.235; RSS-132 (4.3)



Plot 6-1. PCS GSM Frequency Deviation Graph

Note: This unit was tested with its standard battery.

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 17 of 21	


7.0 CONCLUSION

The data collected shows that the NEC Single-Band PCS GSM/GPRS Phone with Bluetooth FCC ID: A98-KMP7N2L1 complies with all the requirements of Parts 2 and 24 of the FCC rules.


FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 18 of 21	

EXHIBIT A - PLOT(S) OF EMISSIONS

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 19 of 21	




Plot A-1. Conducted Spurious (PCS GSM – Ch. 512)




Plot A-2. Conducted Spurious (PCS GSM – Ch. 512)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 GSM MODE CONDUCTED PLOTS		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page A1




Plot A-3. Band Edge (PCS GSM – Ch. 512)




Plot A-4. Conducted Spurious (PCS GSM – Ch. 661)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 GSM MODE CONDUCTED PLOTS		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page A2




Plot A-5. Conducted Spurious (PCS GSM – Ch. 661)




Plot A-6. Occupied Bandwidth (PCS GSM – Ch. 661)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 GSM MODE CONDUCTED PLOTS		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page A3




Plot A-7. Conducted Spurious (PCS GSM – Ch. 810)



Plot A-8. Conducted Spurious (PCS GSM – Ch. 810)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 GSM MODE CONDUCTED PLOTS		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page A4



Plot A-9. Band Edge (PCS GSM – Ch. 810)

FCC ID: A98-KMP7N2L1		FCC Pt. 24 GSM MODE CONDUCTED PLOTS		Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth		Page A5

EXHIBIT B – TEST SETUP PHOTOGRAPHS

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 20 of 21	

EXHIBIT C – INTERNAL/EXTERNAL PHOTOGRAPHS

FCC ID: A98-KMP7N2L1		FCC Pt. 24 MEASUREMENT REPORT (GSM/GPRS)	NEC	Reviewed by: Quality Manager
Test Report S/N: 0608280741	Test Dates: September 6 - 7, 2006	EUT Type: Single-Band PCS GSM/GPRS Phone with Bluetooth	Page 21 of 21	