

April 11, 2025

FCC ID: ACJ932AN2402

To whom it may concern,

We, UL Japan, Inc, hereby declare that CAR DISPLAY AUDIO, model: AN2402 (FCC ID: ACJ932AN2402) of Panasonic Automotive Systems Co., Ltd.¹ is exempt from RF exposure SAR evaluation because the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(i)(B). This method is used at separation distances d (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive) for single RF sources. P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d / 20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$$

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

When the minimum separation distance is shorter than 0.5 cm, 0.5 cm is applied.

¹ The Grantee name in the FCC application is "Panasonic Corporation of North America".

The SAR evaluation exemption threshold is calculated as below.

[Bluetooth (BR / EDR) part]

P_{th} (mW)	3060
f (GHz)	2.48
$ERP_{20\text{ cm}}$ (mW)	3060
d (cm)	20.0

Conducted Power	(dBm)	-0.50
	(mW)	0.89
Antenna Gain	(dBi)	5.00
EIRP	(dBm)	4.50
ERP	(dBm)	2.36
	(mW)	1.72

The Maximum time-averaged power or ERP whichever greater is 1.8 mW.
(Rounded up to two decimals place)

[WLAN 5 GHz part]

P_{th} (mW)	3060
f (GHz)	5805
$ERP_{20\text{ cm}}$ (mW)	3060
d (cm)	20.0

Conducted Power	(dBm)	6.50
	(mW)	4.47
Antenna Gain	(dBi)	3.00
EIRP	(dBm)	9.50
ERP	(dBm)	7.36
	(mW)	5.45

The Maximum time-averaged power or ERP whichever greater is 5.5 mW.
(Rounded up to two decimals place)

Transmitters used in mobile exposure conditions for simultaneous transmission operations according to KDB447498 D04.

Value is calculated using the following formula according to the Code of Federal Regulation title 47 section 1.1307(b)(3)(ii)(B).

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^a \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

[Bluetooth (BR / EDR) part and WLAN 5 GHz part]

$$1.8 / 3060 + 5.5 / 3060 = 0.0006 + 0.0018 = 0.0024 < 1$$

Thank you for your attention to this matter.

T. Shimada

Takumi Shimada
Engineer