

Report No.: RF171229E06

FCC ID: ACJ96NKX-HNC710

Test Model: KX-HNC710

Received Date: Dec. 29, 2017

Test Date: Jan. 15 to 17, 2018

Issued Date: Jan. 25, 2018

Applicant: Panasonic Corporation of North America

Address: Two Riverfront Plaza, 9th Floor, Newark, NJ 07102-5490 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.2.1 Test Mode Applicability and Tested Channel Detail	9
3.3 Duty Cycle of Test Signal	11
3.4 Description of Support Units	12
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures.....	18
4.1.4 Deviation from Test Standard	18
4.1.5 Test Setup.....	19
4.1.6 EUT Operating Conditions.....	20
4.1.7 Test Results	21
4.2 Conducted Emission Measurement	31
4.2.1 Limits of Conducted Emission Measurement	31
4.2.2 Test Instruments	31
4.2.3 Test Procedures.....	32
4.2.4 Deviation from Test Standard	32
4.2.5 Test Setup.....	32
4.2.6 EUT Operating Conditions.....	32
4.2.7 Test Results (Mode 1).....	33
4.2.8 Test Results (Mode 2).....	35
4.3 6dB Bandwidth Measurement	37
4.3.1 Limits of 6dB Bandwidth Measurement	37
4.3.2 Test Setup.....	37
4.3.3 Test Instruments	37
4.3.4 Test Procedure	37
4.3.5 Deviation from Test Standard	37
4.3.6 EUT Operating Conditions.....	37
4.3.7 Test Result.....	38
4.4 Occupied Bandwidth Measurement	40
4.4.1 Test Setup.....	40
4.4.2 Test Instruments	40
4.4.3 Test Procedure	40
4.4.4 Deviation from Test Standard	40
4.4.5 EUT Operating Conditions.....	40
4.4.6 Test Results	41
4.5 Conducted Output Power Measurement.....	43
4.5.1 Limits of Conducted Output Power Measurement	43
4.5.2 Test Setup.....	43
4.5.3 Test Instruments	43
4.5.4 Test Procedures.....	43
4.5.5 Deviation from Test Standard	43
4.5.6 EUT Operating Conditions.....	43

4.5.7 Test Results	44
4.6 Power Spectral Density Measurement.....	46
4.6.1 Limits of Power Spectral Density Measurement	46
4.6.2 Test Setup.....	46
4.6.3 Test Instruments	46
4.6.4 Test Procedure	46
4.6.5 Deviation from Test Standard	46
4.6.6 EUT Operating Condition	46
4.6.7 Test Results	47
4.7 Conducted Out of Band Emission Measurement.....	49
4.7.1 Limits of Conducted Out of Band Emission Measurement.....	49
4.7.2 Test Setup.....	49
4.7.3 Test Instruments	49
4.7.4 Test Procedure	49
4.7.5 Deviation from Test Standard	49
4.7.6 EUT Operating Condition	49
4.7.7 Test Results	49
5 Pictures of Test Arrangements.....	53
Appendix – Information on the Testing Laboratories	54

Release Control Record

Issue No.	Description	Date Issued
RF171229E06	Original release.	Jan. 25, 2018

1 Certificate of Conformity

Product: HomeHawk Outdoor

Brand: Panasonic

Test Model: KX-HNC710

Sample Status: ENGINEERING SAMPLE

Applicant: Panasonic Corporation of North America

Test Date: Jan. 15 to 17, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu , **Date:** Jan. 25, 2018
Wendy Wu / Specialist

Approved by : May Chen , **Date:** Jan. 25, 2018
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.51dB at 0.56406MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2483.50MHz, 2390.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.
-	Occupied Bandwidth Measurement	PASS	Meet the requirement of limit.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.53 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.08 dB
	6GHz ~ 18GHz	4.98 dB
	18GHz ~ 40GHz	5.19 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	HomeHawk Outdoor
Brand	Panasonic
Test Model	KX-HNC710
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	3.8Vdc from battery (internal) or 5Vdc from USB interface
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	802.11b: up to 11Mbps 802.11g: up to 54Mbps 802.11n: up to 72.2Mbps
Operating Frequency	2.412 ~ 2.462GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20): 11
Output Power	353.183mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Cable Supplied	Micro USB cable x 1 (Shielding, 1m)

Note:

1. The EUT must be supplied with a battery (internal) as following table:

Brand	Model No.	Spec.
Highpower	SP924550-5000mAh	3.8Vdc, 5000mAh

2. The antennas provided to the EUT, please refer to the following table:

Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (cm)
Chain 0	WHA YU	C037-511479-A	2.3	2.4~2.4835	PIFA	soldering	75
Chain 1		C037-511480-A	1.9	2.4~2.4835	PIFA	soldering	85

Note: The max gain was selected for final test.

3. The EUT incorporates a SISO function.

MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11b	1 ~ 11Mbps	1TX diversity	1RX diversity
802.11g	6 ~ 54Mbps	1TX diversity	1RX diversity
802.11n (HT20)	MCS 0~7	1TX diversity	1RX diversity

4. For the radiated emissions, the EUT was pre-tested under the following modes:

Test Mode	Description
Mode A	Power from battery
Mode B	Power from adapter

From the above modes, the worst case was found in **Mode B**. Therefore only the test data of the mode was recorded in this report.

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	√	√	Power from adapter
2	-	-	√	-	Power from Laptop

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

2. "-" means no effect.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11g	1 to 11	6	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
802.11n (HT20)	1 to 11	1, 6, 11	OFDM	BPSK	6.5

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	22deg. C, 69%RH	120Vac, 60Hz	Rey Chen
RE<1G	23deg. C, 70%RH	120Vac, 60Hz	Andy Ho
PLC	25deg. C, 75%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin

3.3 Duty Cycle of Test Signal

If duty cycle of test signal is $\geq 98\%$, duty factor is not required.

802.11b: Duty cycle = $12.456/12.512 = 0.996$

802.11g: Duty cycle = $2.062/2.084 = 0.989$,

802.11n (HT20): Duty cycle = $1.919/1.949 = 0.985$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
B.	USB Adapter	ASUS	EXA1205UA	NA	NA	Provided by Lab
C.	Test Tool	ALPHA	NA	NA	NA	Supplied by client


Note:

1. All power cords of the above support units are non-shielded (1.8m).


ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB Cable	1	1.8	Yes	0	Supplied by client
2.	USB Cable	1	1	Yes	0	Supplied by client
3.	Console Cable	1	0.5	No	0	Supplied by client(for RF Setup)

3.4.1 Configuration of System under Test

Mode 1:



Mode 2



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
KDB 558074 D01 DTS Meas Guidance v04
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	July 12, 2017	July 11, 2018
Pre-Amplifier ^(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna ^(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 17, 2017	Jan. 16, 2018
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 06, 2017	May 05, 2018
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 29, 2017	Nov. 28, 2018
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 01, 2017	Mar. 31, 2018
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Oct. 03, 2017	Oct. 02, 2018
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Dec. 12, 2017	Dec. 11, 2018
Pre-Amplifier EMCI	EMC12630SE	980384	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160922 150317 150322	Feb. 02, 2017 Mar. 29, 2017 Mar. 29, 2017	Feb. 01, 2018 Mar. 28, 2018 Mar. 28, 2018
Spectrum Analyzer Keysight	N9030A	MY54490679	July 25, 2017	July 24, 2018
Pre-Amplifier EMCI	EMC184045SE	980386	Feb. 02, 2017	Feb. 01, 2018
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 14, 2017	Dec. 13, 2018
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 11, 2018	Jan. 10, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Spectrum Analyzer R&S	FSv40	100964	July 1, 2017	June 30, 2018
Power meter Anritsu	ML2495A	1014008	May 11, 2017	May 10, 2018
Power sensor Anritsu	MA2411B	0917122	May 11, 2017	May 10, 2018

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The CANADA Site Registration No. is 20331-1
5. Loop antenna was used for all emissions below 30 MHz.
6. Tested Date: Jan. 15 to 16, 2018

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop which is placed on remote site.
- Controlling software (HyperTerminal paste KX-HNC710_wl command) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data:

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	62.1 PK	74.0	-11.9	1.36 H	20	63.3	-1.2
2	2390.00	53.9 AV	54.0	-0.1	1.36 H	20	55.1	-1.2
3	*2412.00	112.5 PK			1.36 H	20	113.8	-1.3
4	*2412.00	110.3 AV			1.36 H	20	111.6	-1.3
5	4824.00	39.7 PK	74.0	-34.3	1.56 H	196	36.6	3.1
6	4824.00	31.2 AV	54.0	-22.8	1.56 H	196	28.1	3.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.4 PK	74.0	-15.6	1.18 V	67	59.6	-1.2
2	2390.00	47.6 AV	54.0	-6.4	1.18 V	67	48.8	-1.2
3	*2412.00	109.0 PK			1.18 V	67	110.3	-1.3
4	*2412.00	106.9 AV			1.18 V	67	108.2	-1.3
5	4824.00	41.9 PK	74.0	-32.1	2.26 V	138	38.8	3.1
6	4824.00	37.1 AV	54.0	-16.9	2.26 V	138	34.0	3.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2388.00	58.9 PK	74.0	-15.1	1.31 H	30	60.1	-1.2
2	2388.00	49.8 AV	54.0	-4.2	1.31 H	30	51.0	-1.2
3	*2437.00	112.1 PK			1.31 H	30	113.7	-1.6
4	*2437.00	110.1 AV			1.31 H	30	111.7	-1.6
5	2485.80	59.9 PK	74.0	-14.1	1.31 H	30	61.3	-1.4
6	2485.80	50.4 AV	54.0	-3.6	1.31 H	30	51.8	-1.4
7	4874.00	40.5 PK	74.0	-33.5	1.46 H	190	37.3	3.2
8	4874.00	31.9 AV	54.0	-22.1	1.46 H	190	28.7	3.2
9	7311.00	43.6 PK	74.0	-30.4	1.64 H	35	34.7	8.9
10	7311.00	30.2 AV	54.0	-23.8	1.64 H	35	21.3	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2388.00	55.2 PK	74.0	-18.8	1.18 V	62	56.4	-1.2
2	2388.00	46.2 AV	54.0	-7.8	1.18 V	62	47.4	-1.2
3	*2437.00	108.6 PK			1.18 V	62	110.2	-1.6
4	*2437.00	106.7 AV			1.18 V	62	108.3	-1.6
5	2485.80	56.2 PK	74.0	-17.8	1.18 V	62	57.6	-1.4
6	2485.80	46.8 AV	54.0	-7.2	1.18 V	62	48.2	-1.4
7	4874.00	42.2 PK	74.0	-31.8	2.35 V	155	39.0	3.2
8	4874.00	37.0 AV	54.0	-17.0	2.35 V	155	33.8	3.2
9	7311.00	43.2 PK	74.0	-30.8	1.31 V	324	34.3	8.9
10	7311.00	29.8 AV	54.0	-24.2	1.31 V	324	20.9	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.7 PK			1.42 H	24	115.3	-1.6
2	*2462.00	111.5 AV			1.42 H	24	113.1	-1.6
3	2483.50	62.6 PK	74.0	-11.4	1.42 H	24	64.1	-1.5
4	2483.50	53.8 AV	54.0	-0.2	1.42 H	24	55.3	-1.5
5	4924.00	40.3 PK	74.0	-33.7	1.51 H	184	37.0	3.3
6	4924.00	31.5 AV	54.0	-22.5	1.51 H	184	28.2	3.3
7	7386.00	43.4 PK	74.0	-30.6	1.59 H	22	34.2	9.2
8	7386.00	30.2 AV	54.0	-23.8	1.59 H	22	21.0	9.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	110.2 PK			1.23 V	68	111.8	-1.6
2	*2462.00	108.1 AV			1.23 V	68	109.7	-1.6
3	2483.50	58.9 PK	74.0	-15.1	1.23 V	68	60.4	-1.5
4	2483.50	50.2 AV	54.0	-3.8	1.23 V	68	51.7	-1.5
5	4924.00	42.6 PK	74.0	-31.4	2.30 V	147	39.3	3.3
6	4924.00	37.5 AV	54.0	-16.5	2.30 V	147	34.2	3.3
7	7386.00	43.5 PK	74.0	-30.5	1.28 V	332	34.3	9.2
8	7386.00	30.3 AV	54.0	-23.7	1.28 V	332	21.1	9.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.2 PK	74.0	-5.8	1.00 H	216	69.4	-1.2
2	2390.00	53.8 AV	54.0	-0.2	1.00 H	216	55.0	-1.2
3	*2412.00	108.3 PK			1.00 H	216	109.6	-1.3
4	*2412.00	97.3 AV			1.00 H	216	98.6	-1.3
5	4824.00	40.5 PK	74.0	-33.5	1.54 H	171	37.4	3.1
6	4824.00	31.7 AV	54.0	-22.3	1.54 H	171	28.6	3.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	64.5 PK	74.0	-9.5	1.13 V	80	65.7	-1.2
2	2390.00	50.2 AV	54.0	-3.8	1.13 V	80	51.4	-1.2
3	*2412.00	104.8 PK			1.13 V	80	106.1	-1.3
4	*2412.00	93.9 AV			1.13 V	80	95.2	-1.3
5	4824.00	42.0 PK	74.0	-32.0	2.32 V	161	38.9	3.1
6	4824.00	37.1 AV	54.0	-16.9	2.32 V	161	34.0	3.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.9 PK	74.0	-12.1	1.13 H	21	63.1	-1.2
2	2390.00	47.7 AV	54.0	-6.3	1.13 H	21	48.9	-1.2
3	*2437.00	112.3 PK			1.13 H	21	113.9	-1.6
4	*2437.00	101.9 AV			1.13 H	21	103.5	-1.6
5	2483.50	62.6 PK	74.0	-11.4	1.13 H	21	64.1	-1.5
6	2483.50	47.3 AV	54.0	-6.7	1.13 H	21	48.8	-1.5
7	4874.00	40.7 PK	74.0	-33.3	1.56 H	171	37.5	3.2
8	4874.00	31.7 AV	54.0	-22.3	1.56 H	171	28.5	3.2
9	7311.00	43.6 PK	74.0	-30.4	1.56 H	9	34.7	8.9
10	7311.00	30.6 AV	54.0	-23.4	1.56 H	9	21.7	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	58.2 PK	74.0	-15.8	1.17 V	70	59.4	-1.2
2	2390.00	44.1 AV	54.0	-9.9	1.17 V	70	45.3	-1.2
3	*2437.00	108.8 PK			1.17 V	70	110.4	-1.6
4	*2437.00	98.5 AV			1.17 V	70	100.1	-1.6
5	2483.50	58.9 PK	74.0	-15.1	1.17 V	70	60.4	-1.5
6	2483.50	43.7 AV	54.0	-10.3	1.17 V	70	45.2	-1.5
7	4874.00	42.4 PK	74.0	-31.6	2.25 V	133	39.2	3.2
8	4874.00	37.5 AV	54.0	-16.5	2.25 V	133	34.3	3.2
9	7311.00	43.4 PK	74.0	-30.6	1.31 V	326	34.5	8.9
10	7311.00	30.2 AV	54.0	-23.8	1.31 V	326	21.3	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.7 PK			1.28 H	214	110.3	-1.6
2	*2462.00	97.4 AV			1.28 H	214	99.0	-1.6
3	2483.50	73.7 PK	74.0	-0.3	1.28 H	214	75.2	-1.5
4	2483.50	51.6 AV	54.0	-2.4	1.28 H	214	53.1	-1.5
5	4924.00	39.8 PK	74.0	-34.2	1.56 H	182	36.5	3.3
6	4924.00	31.3 AV	54.0	-22.7	1.56 H	182	28.0	3.3
7	7386.00	43.4 PK	74.0	-30.6	1.61 H	25	34.2	9.2
8	7386.00	30.3 AV	54.0	-23.7	1.61 H	25	21.1	9.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	105.2 PK			1.22 V	69	106.8	-1.6
2	*2462.00	94.0 AV			1.22 V	69	95.6	-1.6
3	2483.50	70.0 PK	74.0	-4.0	1.22 V	69	71.5	-1.5
4	2483.50	48.0 AV	54.0	-6.0	1.22 V	69	49.5	-1.5
5	4924.00	42.9 PK	74.0	-31.1	2.35 V	153	39.6	3.3
6	4924.00	37.5 AV	54.0	-16.5	2.35 V	153	34.2	3.3
7	7386.00	43.5 PK	74.0	-30.5	1.23 V	336	34.3	9.2
8	7386.00	30.0 AV	54.0	-24.0	1.23 V	336	20.8	9.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11n (HT20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	69.4 PK	74.0	-4.6	2.65 H	316	70.6	-1.2
2	2390.00	53.8 AV	54.0	-0.2	2.65 H	316	55.0	-1.2
3	*2412.00	106.5 PK			2.65 H	316	107.8	-1.3
4	*2412.00	96.8 AV			2.65 H	316	98.1	-1.3
5	4824.00	40.1 PK	74.0	-33.9	1.56 H	177	37.0	3.1
6	4824.00	31.6 AV	54.0	-22.4	1.56 H	177	28.5	3.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.7 PK	74.0	-8.3	1.12 V	64	66.9	-1.2
2	2390.00	50.2 AV	54.0	-3.8	1.12 V	64	51.4	-1.2
3	*2412.00	103.0 PK			1.12 V	64	104.3	-1.3
4	*2412.00	93.4 AV			1.12 V	64	94.7	-1.3
5	4824.00	42.8 PK	74.0	-31.2	2.29 V	159	39.7	3.1
6	4824.00	37.7 AV	54.0	-16.3	2.29 V	159	34.6	3.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	61.6 PK	74.0	-12.4	1.19 H	35	62.8	-1.2
2	2390.00	47.6 AV	54.0	-6.4	1.19 H	35	48.8	-1.2
3	*2437.00	112.5 PK			1.18 H	19	114.1	-1.6
4	*2437.00	102.2 AV			1.18 H	19	103.8	-1.6
5	2483.50	62.5 PK	74.0	-11.5	1.13 H	14	64.0	-1.5
6	2483.50	47.0 AV	54.0	-7.0	1.13 H	14	48.5	-1.5
7	4874.00	40.4 PK	74.0	-33.6	1.55 H	181	37.2	3.2
8	4874.00	31.4 AV	54.0	-22.6	1.55 H	181	28.2	3.2
9	7311.00	42.9 PK	74.0	-31.1	1.64 H	34	34.0	8.9
10	7311.00	30.0 AV	54.0	-24.0	1.64 H	34	21.1	8.9

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	1.19 V	66	59.1	-1.2
2	2390.00	44.0 AV	54.0	-10.0	1.19 V	66	45.2	-1.2
3	*2437.00	109.0 PK			1.19 V	66	110.6	-1.6
4	*2437.00	98.8 AV			1.19 V	66	100.4	-1.6
5	2483.50	58.8 PK	74.0	-15.2	1.19 V	66	60.3	-1.5
6	2483.50	43.4 AV	54.0	-10.6	1.19 V	66	44.9	-1.5
7	4874.00	42.7 PK	74.0	-31.3	2.25 V	141	39.5	3.2
8	4874.00	37.6 AV	54.0	-16.4	2.25 V	141	34.4	3.2
9	7311.00	43.8 PK	74.0	-30.2	1.29 V	328	34.9	8.9
10	7311.00	30.7 AV	54.0	-23.3	1.29 V	328	21.8	8.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.2 PK			1.28 H	213	107.8	-1.6
2	*2462.00	94.6 AV			1.28 H	213	96.2	-1.6
3	2483.50	73.2 PK	74.0	-0.8	1.28 H	213	74.7	-1.5
4	2483.50	50.1 AV	54.0	-3.9	1.28 H	213	51.6	-1.5
5	4924.00	40.4 PK	74.0	-33.6	1.49 H	188	37.1	3.3
6	4924.00	31.4 AV	54.0	-22.6	1.49 H	188	28.1	3.3
7	7386.00	43.8 PK	74.0	-30.2	1.59 H	15	34.6	9.2
8	7386.00	30.5 AV	54.0	-23.5	1.59 H	15	21.3	9.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	102.7 PK			1.22 V	55	104.3	-1.6
2	*2462.00	91.2 AV			1.22 V	55	92.8	-1.6
3	2483.50	69.5 PK	74.0	-4.5	1.22 V	55	71.0	-1.5
4	2483.50	46.5 AV	54.0	-7.5	1.22 V	55	48.0	-1.5
5	4924.00	42.1 PK	74.0	-31.9	2.35 V	143	38.8	3.3
6	4924.00	37.0 AV	54.0	-17.0	2.35 V	143	33.7	3.3
7	7386.00	43.5 PK	74.0	-30.5	1.33 V	347	34.3	9.2
8	7386.00	30.5 AV	54.0	-23.5	1.33 V	347	21.3	9.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:

802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	84.32	19.3 QP	40.0	-20.7	2.00 H	243	37.9	-18.6
2	167.74	20.6 QP	43.5	-22.9	2.00 H	138	34.1	-13.5
3	216.24	21.3 QP	46.0	-24.7	1.50 H	205	37.4	-16.1
4	239.52	21.3 QP	46.0	-24.7	1.50 H	238	36.0	-14.7
5	396.66	20.8 QP	46.0	-25.2	1.00 H	206	31.0	-10.2
6	959.26	28.2 QP	46.0	-17.8	1.00 H	268	29.1	-0.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	19.7 QP	40.0	-20.3	1.00 V	221	33.7	-14.0
2	84.32	20.9 QP	40.0	-19.1	1.00 V	203	39.5	-18.6
3	216.24	18.7 QP	46.0	-27.3	1.50 V	179	34.8	-16.1
4	528.58	22.5 QP	46.0	-23.5	1.50 V	278	29.8	-7.3
5	769.14	25.0 QP	46.0	-21.0	1.50 V	318	27.8	-2.8
6	959.26	29.4 QP	46.0	-16.6	2.00 V	228	30.3	-0.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Nov. 01, 2017	Oct. 31, 2018
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Nov. 15, 2016	Nov. 14, 2018
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 03, 2017	June 02, 2018
50 ohms Terminator	N/A	EMC-02	Sep. 22, 2017	Sep. 21, 2018
RF Cable	5D-FB	COCCAB-001	Sep. 29, 2017	Sep. 28, 2018
10 dB PAD Mini-Circuits	HAT-10+	CONATT-004	June 18, 2017	June 17, 2018
Software BVADT	BVADT_Cond_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. 1.
- 3 Tested Date: Jan. 17, 2018

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results (Mode 1)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	-----------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	10.14	33.54	22.79	43.68	32.93	64.98	54.98	-21.30	-22.05
2	0.21250	10.15	33.63	24.84	43.78	34.99	63.11	53.11	-19.33	-18.12
3	0.24375	10.16	31.96	23.63	42.12	33.79	61.97	51.97	-19.85	-18.18
4	0.56406	10.21	29.30	21.28	39.51	31.49	56.00	46.00	-16.49	-14.51
5	0.92734	10.24	18.79	9.22	29.03	19.46	56.00	46.00	-26.97	-26.54
6	14.57813	11.14	14.99	8.19	26.13	19.33	60.00	50.00	-33.87	-30.67

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17734	10.05	35.17	24.65	45.22	34.70	64.61	54.61	-19.39	-19.91
2	0.20859	10.05	32.54	22.80	42.59	32.85	63.26	53.26	-20.67	-20.41
3	0.24766	10.06	30.21	21.51	40.27	31.57	61.84	51.84	-21.57	-20.27
4	0.55625	10.11	26.27	21.10	36.38	31.21	56.00	46.00	-19.62	-14.79
5	1.92969	10.18	20.11	11.77	30.29	21.95	56.00	46.00	-25.71	-24.05
6	14.42188	10.94	13.51	8.08	24.45	19.02	60.00	50.00	-35.55	-30.98

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.2.8 Test Results (Mode 2)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.14	35.51	17.00	45.65	27.14	66.00	56.00	-20.35	-28.86
2	0.20859	10.15	31.70	13.69	41.85	23.84	63.26	53.26	-21.41	-29.42
3	0.82578	10.24	22.69	6.84	32.93	17.08	56.00	46.00	-23.07	-28.92
4	2.64453	10.35	24.77	13.68	35.12	24.03	56.00	46.00	-20.88	-21.97
5	10.83203	10.87	19.58	12.00	30.45	22.87	60.00	50.00	-29.55	-27.13
6	18.17188	11.39	14.77	8.01	26.16	19.40	60.00	50.00	-33.84	-30.60

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16172	10.05	34.47	14.10	44.52	24.15	65.38	55.38	-20.86	-31.23
2	0.20469	10.05	33.50	13.31	43.55	23.36	63.42	53.42	-19.87	-30.06
3	0.52500	10.10	22.98	8.29	33.08	18.39	56.00	46.00	-22.92	-27.61
4	3.32031	10.25	23.86	13.94	34.11	24.19	56.00	46.00	-21.89	-21.81
5	7.47266	10.49	20.02	11.54	30.51	22.03	60.00	50.00	-29.49	-27.97
6	11.05078	10.71	18.90	11.65	29.61	22.36	60.00	50.00	-30.39	-27.64

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	8.55	0.5	PASS
6	2437	9.52	0.5	PASS
11	2462	8.08	0.5	PASS

802.11g


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	16.54	0.5	PASS
6	2437	16.47	0.5	PASS
11	2462	16.48	0.5	PASS

802.11n (HT20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	17.71	0.5	PASS
6	2437	17.70	0.5	PASS
11	2462	17.73	0.5	PASS

Spectrum Plot of Worst Value


802.11b : CH11



802.11g : CH6




802.11n (HT20) : CH6



4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.4.4 Deviation from Test Standard

No deviation.

4.4.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.6 Test Results

802.11b

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
1	2412	12.72
6	2437	15.12
11	2462	12.84

802.11g


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
1	2412	17.04
6	2437	22.08
11	2462	17.28

802.11n (HT20)


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
1	2412	18.24
6	2437	23.28
11	2462	18.12

Spectrum Plot of Worst Value


802.11b : CH6



802.11g : CH6



802.11n (HT20) : CH6




4.5 Conducted Output Power Measurement

4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedures

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

Same as Item 4.3.6.

4.5.7 Test Results

FOR PEAK POWER

802.11b

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	220.8	23.44	30.00	Pass
6	2437	318.42	25.03	30.00	Pass
11	2462	218.273	23.39	30.00	Pass

802.11g

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	214.289	23.31	30.00	Pass
6	2437	353.183	25.48	30.00	Pass
11	2462	213.304	23.29	30.00	Pass

802.11n (HT20)

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
1	2412	212.814	23.28	30.00	Pass
6	2437	349.14	25.43	30.00	Pass
11	2462	192.752	22.85	30.00	Pass

FOR AVERAGE POWER

802.11b

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	124.738	20.96
6	2437	215.774	23.34
11	2462	124.451	20.95

802.11g

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	41.495	16.18
6	2437	144.877	21.61
11	2462	40.365	16.06

802.11n (HT20)


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	32.81	15.16
6	2437	145.546	21.63
11	2462	28.249	14.51

4.6 Power Spectral Density Measurement

4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Same as Item 4.3.6

4.6.7 Test Results

802.11b

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-1.53	8	Pass
6	2437	0.33	8	Pass
11	2462	-1.04	8	Pass

802.11g


Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-9.53	8	Pass
6	2437	-4.38	8	Pass
11	2462	-9.50	8	Pass

802.11n (HT20)


Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
1	2412	-9.04	8	Pass
6	2437	-4.03	8	Pass
11	2462	-10.09	8	Pass

Spectrum Plot of Worst Value


802.11b : CH6



802.11g : CH6



802.11n (HT20) : CH6




4.7 Conducted Out of Band Emission Measurement

4.7.1 Limits of Conducted Out of Band Emission Measurement

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition



Same as Item 4.3.6

4.7.7 Test Results



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

802.11b



CH 1




CH 6




CH 11



CH 1 Band edge





CH 11 Band edge





802.11g



CH 1





CH 6



CH 11





CH 1 Band edge





802.11n (HT20)



CH 1




CH 6




CH 11



CH 1 Band edge



CH 11 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linkou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---