

FCC 15C – Product Information

EUT AND PRODUCT INFORMATION

Type of Equipment	Wireless Indoor Camera
Applicant Name	Panasonic Corporation of North America
Address	Two Riverfront Plaza, 9th Floor Newark, NJ 07102-5490
Contact	Ben Botros
Telephone	+1-(201) 348-7760
Email	ben.botros@us.panasonic.com
Brand Name	Panasonic
Model Number	KX-HNC850
Hardware Version	
Software Version	
FCC ID	ACJ96NKX-HNC850
IC ID	IC:216A-KXHNC855

1. Basic Information			
FCC 15 Part	☒ 15.247	☐ 15.249	☒ Other
Please specify if other: 15.407			
Type of Equipment	☐ FHSS	☒ DTS	☐ Other
Please specify if other:			
Classification of EUT	☒ Portable	☐ Mobile	☐ Fixed
Lowest Operating Frequency	2412MHz		
Highest Operating Frequency	2462MHz		
Nominal Output Power	30mW		
Maximum Duty Cycle (in actual use)	60%		
Operating Mode (list all)	IEEE802.11b/g/n (HT20)		
Modulation Type (list all)	Digital (DSSS, OFDM)		
Nominal 99% Bandwidth	18MHz		
Maximum Number of channels	11		
Channel Separation	5MHz		
Number of Antennas	1		
Antenna Diversity Supported	☐ Yes	☒ No	
Smart Antenna System	☐ Yes	☒ No	
Reduced output power on any channels	☐ Yes	☒ No	
If YES, please specify:			

FCC 15C – Product Information

2. FHSS Equipment (fill in if FHSS Equipment, FCC 15.247)		
Adaptive Frequency Hopping	☐ Yes	☒ No
If YES, please specify minimum number of hopping channels :		

3. DTS Equipment (fill in if DTS Equipment, FCC 15.247)	
Nominal 6 dB Bandwidth	18MHz

4. Bluetooth Equipment (fill in if Bluetooth Equipment)		
BT 2.0 EDR ?	☐ Yes	☐ No
BT 3.0 HS ?	☐ Yes	☐ No
BT Low Energy	☐ Yes	☐ No

5. 2.4GHz WLAN Equipment (fill in if 2.4GHz WLAN Equipment)				
Supported Operating Modes	☒ 802.11b	☒ 802.11g	☒ 802.11n	☐ 802.11ac
Supported Channel Bandwidths	☐ 40 MHz			
Number of Antennas	1			
Antenna Diversity Supported	☐ Yes		☒ No	
Smart Antenna System	☐ Yes		☒ No	
If Smart Antenna System supported, please specify number of streams				
If number of channels differ in any of the operating modes, please specify:				

6. 5GHz WLAN Equipment (fill in if 5GHz WLAN Equipment)				
Supported Operating Modes	☒ 802.11a	☒ 802.11n	☐ 802.11ac	
Supported Frequency Bands	☒ 5180 – 5240 MHz		☒ 5260 – 5320 MHz	
	☒ 5500 – 5720 MHz		☒ 5745 – 5825 MHz	
Device type	☐ Master		☒ Slave	
DFS	☐ Yes (Master or Slave with DFS capability)		☒ No (Slave without DFS capability)	
Supported Channel Bandwidths	☐ 40 MHz	☐ 80 MHz	☐ 160 MHz	
Number of Antennas	1 Integral Antenna (Maximum Antenna Gain 2.9dBi)			
Antenna Diversity Supported	☐ Yes		☒ No	
Smart Antenna System	☐ Yes		☒ No	
If Smart Antenna System supported, please specify number of streams				
If Output Power is reduced on any channels in one of the Frequency Bands, please specify:				
If number of channels differ in any of the operating modes, please specify:				

FCC 15C – Product Information

6. Power Supply and Connections			
Type of Power Supply	☒ Mains	☐ Battery	☐ Other
Please specify if other than Mains			
Nominal Voltage	120V AC		
Please specify all connections on the EUT:			

ADDITIONAL REMARKS:

This is a DFS Client Device without Radar Detection

DECLARED BY:

March 5, 2019

Ben Botros



FCC 15C – Product Information

About this document

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15C. The form must be completed by the applicant and submitted to Nemko before testing is started.

Preparation of Equipment for Testing

Note (a): Number of samples for testing

In general, the following samples are needed for FCC 15C testing:

RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is normally needed even if the equipment has more than one antenna, however EUTs with Smart Antenna Systems must have antenna connectors on all antennas.

Radiated Tests:

One sample with integral antennas. This sample will be used to measure Radiated Emissions, Antenna Gain, Part 15B and Power-Line Conducted tests.

If it is not possible to mount antenna connector(s) on the EUT all tests will be performed radiated or with a test jig. In this case the applicant shall always supply a value for the antenna gain.

Note (b): Power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with new or fully charged batteries.

Note (c): Test Modes

Most RF tests are performed with the EUT in force transmit mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

All tests will normally be performed on 3 channels and with all supported modulation types.

Frequency hopping equipment will be tested both with hopping active and without hopping.

Equipment with digital modulations other than Frequency hopping should transmit with as high duty cycle as possible.