

Amended June 11, 2004
ITPD-04-F030A

Federal Communications Commission
7435 Oakland Mills Road
Columbia, MD 21046 USA

Subject: Authority to Act as FCC Agent and Request for Confidentiality
Panasonic Personal Computer With Intel WLAN and Sierra CDMA
Model CF-29 Family / TCB Certification for FCC ID: ACJ9TGCF-29A

To Whom It May Concern:


On behalf of Applicant Matsushita Electric Industrial Co., Ltd. and their agent Matsushita Electronic Corporation of America, we hereby authorize PCTEST Engineering Laboratory, Inc., to act on our behalf in matters relating to FCC equipment authorization, including the signing of documents relating to these matters. Any and all acts carried out by PCTEST on our behalf shall have the same effect as acts of our own.

This project represents Panasonic Personal Computer Model CF-29 Family (CF-29mk2). This product will be marketed with: (1) CPU type Pentium-M-1.3 GHz; (2) Intel WLAN Module Model WM3B2200BG, which was separately Part 15C certified under FCC ID: PD9WM3B2200BG for operation within 2412~2462 MHz with 0.056 watts conducted RF output power; and (3) Sierra CDMA Module Model SB555, which was separately Parts 22H and 24E certified under FCC ID: N7NSB555 for operation within 824~849 and 1850~1910 MHz with 0.224watts conducted RF output power. This product's LCD panel will house 2 pattern WLAN antennas with left antenna TX/RX Inverter F Type with 1.86 dBi antenna gain and the right antenna RX only Inverter F Type with 2.86 dBi antenna gain; and the CDMA whip antenna with 2.15 dBi antenna gain. These two transceivers are co-located and may transmit simultaneously. These wireless devices will be installed under our control and this final configuration will always be marketed under new end product FCC ID: ACJ9TGCF-29A.

This product contains unique external antenna connector(s), which may connect to future optional Car Mounter or Port Replicator. The basic PC User Manual will contain all general RF exposure warning notices, which includes notice that this equipment has been approved for portable operation, and unless otherwise advised in separate supplemental instructions for individual wireless transmitter(s), requires minimum 1.5 cm spacing. Also, it advises connection to optional Car Mounter or Port Replicator external mounted antenna(s) are for mobile operation with minimum 20 cm spacing requirement, must be professionally installed and cannot exceed recommended maximum antenna dBi gain. Refer to provided samples of User Manuals for exact wording. In the near future, we will submit Class II Permissive Change Application to report additional test data performed with optional external Radiall/Larsen WLAN antenna, type MS3E2400TNC.

In accordance with provisions of Section 0.457(d) of the Commission's Rules and Section 552(b)(4) of the Freedom of Information Act, we request confidentiality for both transceivers' exhibits for Operation Description, Parts List & Tune-Up Procedure, Block Diagram(s) and Schematic Diagram(s). The WLAN is not user adjustable and does not have any Tune-Up Procedure. These exhibits contain proprietary, confidential and trade secrets material, which would not be routinely made available for public inspection.

Sincerely yours,


Richard Mullen
Group Manager

