




# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
<http://www.pctestlab.com>



## MEASUREMENT REPORT FCC Part 22 & 24 / IC RSS-132/RSS-133

**Applicant Name:**  
Panasonic Corporation of North America  
One Panasonic Way, 4B-8  
Secaucus, NJ 07094  
United States

**Date of Testing:**  
May 27 - 28, 2010  
**Test Site/Location:**  
PCTEST Lab., Columbia, MD, USA  
**Test Report Serial No.:**  
0Y1004160652.ACJ

**FCC ID:** ACJ9TGCF-312

**IC CERTIFICATION NO.:** 216A-CF312

**APPLICANT:** PANASONIC CORPORATION OF NORTH AMERICA

**Application Type:** Certification  
**FCC Classification:** PCS Licensed Transmitter (PCB)  
**FCC Rule Part(s):** §2; §22(H), §24(E)  
**IC Specification(s):** RSS-132 Issue 2; RSS-133 Issue 5  
**EUT Type:** Toughbook Model: CF-31  
**Model(s):** CF-31  
**IC Model(s):** CF-312  
**Tx Frequency Range:** 824.20 - 848.80MHz (Cell. GSM) / 1850.20 - 1909.80MHz (PCS GSM)  
826.40 - 846.60MHz (Cell. WCDMA) / 1852.4 - 1907.6MHz (PCS WCDMA)  
824.70 - 848.31MHz (Cell. CDMA) / 1851.25 - 1908.75MHz (PCS CDMA)  
**Max. RF Output Power:** 1.321 W ERP Cell. GSM (31.21 dBm) / 1.285 W EIRP PCS GSM (31.09 dBm)  
0.265 W ERP Cell. WCDMA (24.23 dBm) / 0.457 W EIRP PCS WCDMA (26.6 dBm)  
0.255 W ERP Cell. CDMA (24.06 dBm) / 0.281 W EIRP PCS CDMA (24.49 dBm)  
0.558 W ERP EDGE850 (27.47 dBm) 0.527 W EIRP EDGE1900 (27.22 dBm)  
**Emission Designator(s):** 246KGXW (Cellular GSM), 240KGXW (PCS GSM), 245KG7W (EDGE850),  
240KG7W (EDGE1900), 4M18F9W (Cellular WCDMA), 4M19F9W (PCS WCDMA),  
1M27F9W (Cellular CDMA), 1M27F9W (PCS CDMA)  
**Test Device Serial No.:** identical prototype [S/N: 0AKSA00552]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**Grant Conditions:** Power output listed is ERP for Part 22 and EIRP for Part 24. This device also contains functions that are not operational in U.S. territories. This report is applicable only to U.S. operations.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

  
Randy Ortanez  
President




|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 1 of 82                    |

# TABLE OF CONTENTS


|                                                              |    |
|--------------------------------------------------------------|----|
| FCC PART 22 & 24 MEASUREMENT REPORT.....                     | 3  |
| 1.0 INTRODUCTION.....                                        | 4  |
| 1.1 SCOPE .....                                              | 4  |
| 1.2 TESTING FACILITY.....                                    | 4  |
| 2.0 PRODUCT INFORMATION.....                                 | 5  |
| 2.1 EQUIPMENT DESCRIPTION .....                              | 5  |
| 2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS .....            | 5  |
| 2.3 LABELING REQUIREMENTS.....                               | 5  |
| 3.0 DESCRIPTION OF TESTS .....                               | 6  |
| 3.1 MEASUREMENT PROCEDURE .....                              | 6  |
| 3.2 OCCUPIED BANDWIDTH .....                                 | 6  |
| 3.3 CELLULAR - BASE FREQUENCY BLOCKS.....                    | 6  |
| 3.4 CELLULAR - MOBILE FREQUENCY BLOCKS.....                  | 7  |
| 3.5 PCS - BASE FREQUENCY BLOCKS.....                         | 7  |
| 3.6 PCS - MOBILE FREQUENCY BLOCKS.....                       | 7  |
| 3.7 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL..... | 7  |
| 3.8 RADIATED POWER AND RADIATED SPURIOUS EMISSIONS .....     | 8  |
| 3.9 PEAK-AVERAGE RATIO.....                                  | 8  |
| 3.10 FREQUENCY STABILITY / TEMPERATURE VARIATION .....       | 9  |
| 4.0 TEST EQUIPMENT CALIBRATION DATA .....                    | 10 |
| 5.0 SAMPLE CALCULATIONS .....                                | 11 |
| 6.0 TEST RESULTS.....                                        | 12 |
| 6.1 SUMMARY.....                                             | 12 |
| 6.2 TRANSMITTER CONDUCTED OUTPUT POWER .....                 | 13 |
| 6.3 EFFECTIVE RADIATED POWER OUTPUT DATA .....               | 15 |
| 6.4 EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA.....     | 16 |
| 6.5 CELLULAR GSM RADIATED MEASUREMENTS .....                 | 17 |
| 6.6 CELLULAR WCDMA RADIATED MEASUREMENTS .....               | 20 |
| 6.7 CELLULAR CDMA RADIATED MEASUREMENTS.....                 | 23 |
| 6.8 PCS GSM RADIATED MEASUREMENTS .....                      | 26 |
| 6.9 PCS WCDMA RADIATED MEASUREMENTS .....                    | 29 |
| 6.10 PCS CDMA RADIATED MEASUREMENTS.....                     | 32 |
| 6.11 CELLULAR GSM FREQUENCY STABILITY MEASUREMENTS.....      | 35 |
| 6.12 CELLULAR WCDMA FREQUENCY STABILITY MEASUREMENTS .....   | 37 |
| 6.13 CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS .....    | 39 |
| 6.14 PCS GSM FREQUENCY STABILITY MEASUREMENTS.....           | 41 |
| 6.15 PCS WCDMA FREQUENCY STABILITY MEASUREMENTS .....        | 43 |
| 6.16 PCS CDMA FREQUENCY STABILITY MEASUREMENTS.....          | 45 |
| 6.17 RECEIVER SPURIOUS EMISSIONS .....                       | 47 |
| 7.0 PLOTS OF EMISSIONS.....                                  | 48 |
| 8.0 CONCLUSION.....                                          | 82 |

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 2 of 82                    |



## MEASUREMENT REPORT

### FCC Part 22 & 24




#### §2.1033 General Information

**APPLICANT:** Panasonic Corporation of North America  
**APPLICANT ADDRESS:** One Panasonic Way, 4B-8  
 Secaucus, NJ 07094, United States  
**TEST SITE:** PCTEST ENGINEERING LABORATORY, INC.  
**TEST SITE ADDRESS:** 6660-B Dobbin Road, Columbia, MD 21045 USA  
**FCC RULE PART(S):** §2; §22(H), §24(E)  
**BASE MODEL:** CF-31  
**FCC ID:** ACJ9TGCF-312  
**FCC CLASSIFICATION:** PCS Licensed Transmitter (PCB)  
**EMISSION DESIGNATOR(S):** 246KGXW (Cellular GSM), 240KGXW (PCS GSM), 245KG7W (EDGE850),  
 240KG7W (EDGE1900), 4M18F9W (Cellular WCDMA), 4M19F9W (PCS  
 WCDMA), 1M27F9W (Cellular CDMA), 1M27F9W (PCS CDMA)  
**MODE:** GSM/EDGE/CDMA/WCDMA  
**FREQUENCY TOLERANCE:**  $\pm 0.00025\%$  (2.5 ppm)  
**Test Device Serial No.:** 0AKSA00552 ☐ Production ☒ Pre-Production ☐ Engineering  
**DATE(S) OF TEST:** May 27 - 28, 2010  
**TEST REPORT S/N:** 0Y1004160652.ACJ

#### Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 3 of 82                    |

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

### 1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity are, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 4 of 82                    |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Panasonic Toughbook Model: CF-31** **FCC ID: ACJ9TGCF-312**. The EUT consisted of the following component(s):

| Trade Name / Base Model           | FCC ID       | Description                |
|-----------------------------------|--------------|----------------------------|
| Panasonic / Model: CF-31          | ACJ9TGCF-312 | Toughbook Model: CF-31     |
| Atheros / Model: AR5B95           | PPD-AR5B95   | 802.11b/g/n Module         |
| Alps / Model: UGNZA               | N/A          | Bluetooth 2.1+EDR Module   |
| Sierra Wireless / Model: GOBI2000 | N7NGOBI2     | CDMA/GSM/EDGE/WCDMA Module |

Table 2-1. EUT Equipment Description

### 2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

### 2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

*This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).


Please see attachment for FCC ID label and label location.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 5 of 82                    |

## 3.0 DESCRIPTION OF TESTS

### 3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.



**Figure 3-1. Diagram of 3-meter outdoor test range**


Deviation from Measurement Procedure.....None

### 3.2 Occupied Bandwidth

§2.1049, RSS-Gen (4.6.1)

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

### 3.3 Cellular - Base Frequency Blocks



**BLOCK 1:** 869 – 880 MHz (A\* Low + A)


**BLOCK 3:** 890 – 891.5 MHz (A\* High)

**BLOCK 2:** 880 – 890 MHz (B)

**BLOCK 4:** 891.5 – 894 MHz (B\*)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 6 of 82                    |


### 3.4 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A\* Low + A)  
BLOCK 2: 835 – 845 MHz (B)

BLOCK 3: 845 – 846.5 MHz (A\* High)  
BLOCK 4: 846.5 – 849 MHz (B\*)


### 3.5 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)  
BLOCK 2: 1945 – 1950 MHz (D)  
BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 4: 1965 – 1970 MHz (E)  
BLOCK 5: 1970 – 1975 MHz (F)  
BLOCK 6: 1975 – 1990 MHz (C)

### 3.6 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)  
BLOCK 2: 1865 – 1870 MHz (D)  
BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 4: 1885 – 1890 MHz (E)  
BLOCK 5: 1890 – 1895 MHz (F)  
BLOCK 6: 1895 – 1910 MHz (C)

### 3.7 Spurious and Harmonic Emissions at Antenna Terminal

\$2.1051, 22.917(a), 24.238(a)(b); RSS-132 (4.5.1), RSS-133 (6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 7 of 82                    |

### 3.8 Radiated Power and Radiated Spurious Emissions

**§2.1053, 22.917(a), 22.913(a), 24.232(c), 24.238(a); RSS-132 (4.5.1), RSS-133 (6.5.1)**

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

For radiated power measurements below 1GHz, a half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

For radiated power measurements above 1GHz, a Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

Radiated spurious emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10<sup>th</sup> harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits.

### 3.9 Peak-Average Ratio

**§24.232(d); RSS-133 (6.4)**

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA and WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              | Page 8 of 82                                                                          |                                 |

### 3.10 Frequency Stability / Temperature Variation

#### §2.1055, 22.355, 24.235; RSS-132 (4.3) / RSS-133 (6.3)

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

*Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.*

#### **Time Period and Procedure:**

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 9 of 82                    |

## 4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

| Manufacturer    | Model     | Description                        | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|-----------------|-----------|------------------------------------|------------|--------------|------------|---------------|
| -               | 263-10dB  | (DC-18GHz) 10 dB Attenuator        | N/A        |              | N/A        | N/A           |
| -               | No.166    | (1000-26500MHz) Microwave RF Cable | N/A        |              | N/A        | N/A           |
| -               | No.167    | (100kHz - 100MHz) RG58 Coax Cable  | N/A        |              | N/A        | N/A           |
| Agilent         | 11713A    | Attenuation/Switch Driver          | 12/2/2009  | Annual       | 12/2/2010  | 3439A02645    |
| Agilent         | 8449B     | (1-26.5GHz) Pre-Amplifier          | 12/2/2009  | Annual       | 12/2/2010  | 3008A00985    |
| Agilent         | 85650A    | Quasi-Peak Adapter                 | 12/2/2009  | Annual       | 12/2/2010  | 3303A01872    |
| Agilent         | 8566B     | (100Hz-22GHz) Spectrum Analyzer    | 12/2/2009  | Annual       | 12/2/2010  | 3638A08713    |
| Agilent         | E8257D    | (250kHz-20GHz) Signal Generator    | 3/30/2010  | Annual       | 3/30/2011  | MY45470194    |
| Agilent         | E8267C    | Vector Signal Generator            | 9/29/2009  | Biennial     | 9/29/2011  | US42340152    |
| Agilent         | N9020A    | MXA Signal Analyzer                | 10/22/2009 | Annual       | 10/22/2010 | US46470561    |
| Anritsu         | ML2495A   | Power Meter                        | 10/12/2009 | Annual       | 10/12/2010 | 941001        |
| Emco            | 3115      | Horn Antenna (1-18GHz)             | 4/8/2010   | Biennial     | 4/8/2012   | 9205-3874     |
| Espec           | ESX-2CA   | Environmental Chamber              | 4/1/2010   | Annual       | 4/1/2011   | 17620         |
| MiniCircuits    | VHF-1300+ | High Pass Filter                   | N/A        |              | N/A        | 30716         |
| MiniCircuits    | VHF-3100+ | High Pass Filter                   | N/A        |              | N/A        | 30721         |
| Rohde & Schwarz | CMU200    | Base Station Simulator             | 9/11/2009  | Annual       | 9/11/2010  | 836371/0079   |
| Rohde & Schwarz | FSQ 26    | Spectrum Analyzer                  | 9/19/2009  | Annual       | 9/19/2010  | 200452        |
| Schwarzbeck     | UHA9105   | Dipole Antenna (400 - 1GHz) Rx     | 7/17/2009  | Biennial     | 7/17/2011  | 9105-2404     |
| Schwarzbeck     | UHA9105   | Dipole Antenna (400 - 1GHz) Tx     | 7/17/2009  | Biennial     | 7/17/2011  | 9105-2403     |
| Sunol           | DRH-118   | Horn Antenna (1 - 18GHz)           | 5/14/2009  | Biennial     | 5/14/2011  | A050307       |
| Sunol           | JB5       | Bi-Log Antenna (30M - 5GHz)        | 7/17/2009  | Biennial     | 7/17/2011  | A051107       |

**Table 4-1. Test Equipment**

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 10 of 82                   |

## 5.0 SAMPLE CALCULATIONS

### GSM Emission Designator

**Emission Designator = 250KGXW**

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

### WCDMA Emission Designator

**Emission Designator = 4M16F9W**

WCDMA BW = 4.16 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### CDMA Emission Designator

**Emission Designator = 1M27F9W**

CDMA BW = 1.27 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

### Spurious Radiated Emission - PCS Band

**Example: GSM Channel 512 PCS Mode 2<sup>nd</sup> Harmonic (3700.40 MHz)**

The average power meter reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminal is adjusted to produce a reading of -81.0 dBm on the power meter. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3700.40 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 11 of 82                   |

## 6.0 TEST RESULTS

### 6.1 Summary

Company Name: Panasonic Corporation of North America  
 FCC ID: ACJ9TGCF-312  
 FCC Classification: PCS Licensed Transmitter (PCB)  
 Mode(s): GSM/EDGE/CDMA/WCDMA

| FCC Part Section(s)                    | RSS Section(s)                      | Test Description                         | Test Limit                                                                         | Test Condition | Test Result | Reference                                   |
|----------------------------------------|-------------------------------------|------------------------------------------|------------------------------------------------------------------------------------|----------------|-------------|---------------------------------------------|
| TRANSMITTER MODE (TX)                  |                                     |                                          |                                                                                    |                |             |                                             |
| 2.1049, 22.917(a), 24.238(a)           | RSS-Gen (4.6.1)<br>RSS-133 (2.3)    | Occupied Bandwidth                       | N/A                                                                                | CONDUCTED      | PASS        | Section 7.0                                 |
| 2.1051, 22.917(a), 24.238(a)           | RSS-132 (4.5.1)<br>RSS-133 (6.5.1)  | Band Edge / Conducted Spurious Emissions | < 43 + log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions |                | PASS        | Section 7.0                                 |
| 2.1046                                 | RSS-133 (6.4)                       | Transmitter Conducted Output Power       | N/A                                                                                |                | PASS        | Section 6.2                                 |
| 24.232(d)                              | RSS-132 (4.4)<br>RSS-133 (4.1)      | Peak-Average Ratio                       | < 13 dB                                                                            |                | PASS        | Section 7.0                                 |
| 22.913(a)(2)                           | RSS-132 (4.4)<br>[SRSP-503(5.1.3)]  | Effective Radiated Power                 | < 7 Watts max. ERP                                                                 | RADIATED       | PASS        | Section 6.3                                 |
| 24.232(c)                              | RSS-133 (6.4)<br>[SRSP-510 (5.1.2)] | Equivalent Isotropic Radiated Power      | < 2 Watts max. EIRP                                                                |                | PASS        | Section 6.4                                 |
| 2.1053, 22.917(a), 24.238(a)           | RSS-132 (4.5.1)<br>RSS-133 (6.5.1)  | Undesirable Emissions                    | < 43 + log <sub>10</sub> (P[Watts]) for all out-of-band emissions                  |                | PASS        | Sections 6.5, 6.6, 6.7, 6.8, 6.9, 6.10      |
| 2.1055, 22.355, 24.235                 | RSS-132 (4.3)<br>RSS-133 (6.3)      | Frequency Stability                      | < 2.5 ppm                                                                          |                | PASS        | Sections 6.11, 6.12, 6.13, 6.14, 6.15, 6.16 |
| RECEIVER MODE (RX) / DIGITAL EMISSIONS |                                     |                                          |                                                                                    |                |             |                                             |
| N/A                                    | RSS-132 (4.6)<br>RSS-133 (6.6)      | Receiver Spurious Emissions Limits       | < RSS-Gen limits [Section 6; Table 1]                                              | RADIATED       | PASS        | Section 6.17                                |

**Table 6-1. Summary of Test Results**

**Note:**

The conducted plots shown in Section 7.0 of this test report dated “2009” are still applicable to the licensed transmitter used in this device.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 12 of 82                   |

## 6.2 Transmitter Conducted Output Power

### §2.1046

A base station simulator (Rhode and Schwartz Model: CMU200) was used to establish communication with the **Panasonic Toughbook Model: CF-31 FCC ID: ACJ9TGCF-312**. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits.. The GSM, WCDMA, and CDMA conducted powers are reported below, respectively.

|          |     | RF Conducted Power Table |                         |                         |                         |
|----------|-----|--------------------------|-------------------------|-------------------------|-------------------------|
|          |     | GPRS Data                |                         | EDGE Data               |                         |
|          |     | GPRS [dBm]<br>1 Tx Slot  | GPRS [dBm]<br>2 Tx Slot | EDGE [dBm]<br>1 Tx Slot | EDGE [dBm]<br>2 Tx Slot |
| Cellular | 128 | 32.90                    | 32.84                   | 27.82                   | 27.79                   |
|          | 190 | 32.58                    | 32.55                   | 27.57                   | 27.54                   |
|          | 251 | 32.09                    | 32.05                   | 27.19                   | 27.16                   |
| PCS      | 512 | 29.79                    | 29.74                   | 20.80                   | 20.81                   |
|          | 661 | 30.18                    | 30.12                   | 21.20                   | 21.16                   |
|          | 810 | 30.11                    | 30.05                   | 21.21                   | 21.16                   |

Table 6-2. GSM Conducted Output Powers


| Mode  | 3GPP 34.121 Subtest | Cellular Band [dBm] |       |       | PCS Band [dBm] |       |       |
|-------|---------------------|---------------------|-------|-------|----------------|-------|-------|
|       |                     | 4132                | 4183  | 4233  | 9262           | 9400  | 9538  |
| WCDMA | 12.2 kbps RMC       | 24.67               | 24.51 | 24.46 | 24.32          | 24.38 | 24.02 |
| HSDPA | Subtest 1           | 24.65               | 24.48 | 24.42 | 24.27          | 24.36 | 24.01 |
|       | Subtest 2           | 24.69               | 24.50 | 24.41 | 24.15          | 24.42 | 24.00 |
|       | Subtest 3           | 24.15               | 23.95 | 23.84 | 23.78          | 23.95 | 23.48 |
|       | Subtest 4           | 24.17               | 23.98 | 23.86 | 23.82          | 23.98 | 23.48 |
| HSUPA | Subtest 1           | 24.63               | 24.43 | 24.42 | 24.35          | 24.45 | 23.87 |
|       | Subtest 2           | 22.62               | 22.40 | 22.38 | 22.32          | 22.43 | 21.89 |
|       | Subtest 3           | 23.65               | 23.36 | 23.37 | 23.31          | 23.40 | 22.81 |
|       | Subtest 4           | 22.57               | 22.33 | 22.32 | 22.24          | 22.47 | 21.90 |
|       | Subtest 5           | 24.59               | 24.34 | 24.31 | 24.27          | 24.41 | 23.81 |

Table 6-3. WCDMA Conducted Output Powers

|                                      |                                                                                     |                                                               |  |  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|--|--|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  |  |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |  |  |                                                                                       | Page 13 of 82                   |

| Band     | Channel         | TDSO<br>SO32<br>[dBm] | 1x EvDO<br>Rev. 0<br>[dBm] | 1x EvDO<br>Rev. 0<br>[dBm] | 1x EvDO<br>Rev. A<br>[dBm] | 1x EvDO<br>Rev. A<br>[dBm] |
|----------|-----------------|-----------------------|----------------------------|----------------------------|----------------------------|----------------------------|
|          | F-RC            | RC3                   | (FTAP)                     | (RTAP)                     | (FETAP)                    | (RETAP)                    |
|          | Vocoder<br>Rate | N/A                   | N/A                        | N/A                        | N/A                        | N/A                        |
| Cellular | 1013            | 24.68                 | 24.76                      | 24.15                      | 24.97                      | 23.86                      |
|          | 384             | 24.58                 | 24.38                      | 23.67                      | 24.61                      | 23.72                      |
|          | 777             | 24.57                 | 24.36                      | 23.67                      | 24.57                      | 23.67                      |
| PCS      | 25              | 25.04                 | 24.98                      | 24.76                      | 25.17                      | 24.24                      |
|          | 600             | 25.08                 | 24.90                      | 25.00                      | 25.07                      | 24.28                      |
|          | 1175            | 25.11                 | 24.87                      | 24.63                      | 24.94                      | 24.01                      |

**Table 6-4. CDMA Conducted Output Powers**



**Figure 6-1. GSM/WCDMA/CDMA Conducted Power Test Setup Diagram**

### 6.3 Effective Radiated Power Output Data

§22.913(a)(2); RSS-132 (4.4) [SRSP-503(5.1.3)]

| Frequency [MHz] | Mode    | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBd] | Pol [H/V] | ERP [dBm] | ERP [Watts] | Battery Type |
|-----------------|---------|----------------------|------------------------|--------------------|-----------|-----------|-------------|--------------|
| 824.20          | GSM850  | -6.780               | 30.56                  | 0.00               | H         | 30.56     | 1.138       | Standard     |
| 836.60          | GSM850  | -6.130               | 31.21                  | 0.00               | H         | 31.21     | 1.321       | Standard     |
| 848.80          | GSM850  | -7.540               | 29.80                  | 0.00               | H         | 29.80     | 0.955       | Standard     |
| 836.60          | EDGE850 | -9.870               | 27.47                  | 0.00               | H         | 27.47     | 0.558       | Standard     |

Table 6-5. Effective Radiated Power Output Data (GSM)

| Frequency [MHz] | Mode     | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBd] | Pol [H/V] | ERP [dBm] | ERP [Watts] | Battery Type |
|-----------------|----------|----------------------|------------------------|--------------------|-----------|-----------|-------------|--------------|
| 826.40          | WCDMA850 | -15.970              | 23.58                  | 0.00               | V         | 23.58     | 0.228       | Standard     |
| 836.60          | WCDMA850 | -16.050              | 23.50                  | 0.00               | V         | 23.50     | 0.224       | Standard     |
| 846.60          | WCDMA850 | -15.320              | 24.23                  | 0.00               | V         | 24.23     | 0.265       | Standard     |

Table 6-6. Effective Radiated Power Output Data (WCDMA)

| Frequency [MHz] | Mode    | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBd] | Pol [H/V] | ERP [dBm] | ERP [Watts] | Battery Type |
|-----------------|---------|----------------------|------------------------|--------------------|-----------|-----------|-------------|--------------|
| 824.70          | CDMA850 | -14.570              | 22.77                  | 0.00               | H         | 22.77     | 0.189       | Standard     |
| 836.52          | CDMA850 | -13.280              | 24.06                  | 0.00               | H         | 24.06     | 0.255       | Standard     |
| 848.31          | CDMA850 | -14.110              | 23.23                  | 0.00               | H         | 23.23     | 0.210       | Standard     |

Table 6-7. Effective Radiated Power Output Data (CDMA)

#### NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 15 of 82                   |

## 6.4 Equivalent Isotropic Radiated Power Output Data

§24.232(c); RSS-133 (6.4) [SRSP-510 (5.1.2)]

| Frequency [MHz] | Mode     | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | EIRP [dBm] | EIRP [Watts] | Battery Type |
|-----------------|----------|----------------------|------------------------|--------------------|-----------|------------|--------------|--------------|
| 1850.20         | GSM1900  | -9.550               | 23.09                  | 8.00               | H         | 31.09      | 1.285        | Standard     |
| 1880.00         | GSM1900  | -9.960               | 22.68                  | 8.00               | H         | 30.68      | 1.169        | Standard     |
| 1909.80         | GSM1900  | -10.110              | 22.53                  | 8.00               | H         | 30.53      | 1.130        | Standard     |
| 1850.20         | EDGE1900 | -13.420              | 19.22                  | 8.00               | H         | 27.22      | 0.527        | Standard     |

Table 6-8. Equivalent Isotropic Radiated Power Output Data (GSM)

| Frequency [MHz] | Mode      | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | EIRP [dBm] | EIRP [Watts] | Battery Type |
|-----------------|-----------|----------------------|------------------------|--------------------|-----------|------------|--------------|--------------|
| 1852.40         | WCDMA1900 | -15.470              | 18.46                  | 8.00               | V         | 26.46      | 0.443        | Standard     |
| 1880.00         | WCDMA1900 | -15.330              | 18.60                  | 8.00               | V         | 26.60      | 0.457        | Standard     |
| 1907.60         | WCDMA1900 | -15.860              | 18.07                  | 8.00               | V         | 26.07      | 0.405        | Standard     |

Table 6-9. Equivalent Isotropic Radiated Power Output Data (WCDMA)

| Frequency [MHz] | Mode     | Measured Level [dBm] | Substitute Level [dBm] | Antenna Gain [dBi] | Pol [H/V] | EIRP [dBm] | EIRP [Watts] | Battery Type |
|-----------------|----------|----------------------|------------------------|--------------------|-----------|------------|--------------|--------------|
| 1851.25         | CDMA1900 | -16.150              | 16.49                  | 8.00               | H         | 24.49      | 0.281        | Standard     |
| 1880.00         | CDMA1900 | -16.490              | 16.15                  | 8.00               | H         | 24.15      | 0.260        | Standard     |
| 1908.75         | CDMA1900 | -17.100              | 15.54                  | 8.00               | H         | 23.54      | 0.226        | Standard     |

Table 6-10. Equivalent Isotropic Radiated Power Output Data (CDMA)

### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 16 of 82                   |

## 6.5 Cellular GSM Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.20 MHz  
 CHANNEL: 128  
 MEASURED OUTPUT POWER: 31.210 dBm = 1.321 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.21 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1648.40         | -46.15                          | 6.42                          | -39.74                        | H         | 70.9  |
| 2472.60         | -50.84                          | 6.74                          | -44.10                        | H         | 75.3  |
| 3296.80         | -63.11                          | 7.55                          | -55.56                        | H         | 86.8  |
| 4121.00         | -93.68                          | 7.56                          | -86.12                        | H         | 117.3 |
| 4945.20         | -93.37                          | 9.05                          | -84.32                        | H         | 115.5 |

Table 6-11. Radiated Spurious Data (Cellular GSM Mode – Ch. 128)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 17 of 82                   |

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 190  
 MEASURED OUTPUT POWER: 31.210 dBm = 1.321 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 44.21$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1673.20         | -49.96                          | 6.43                          | -43.53                        | H         | 74.7  |
| 2509.80         | -54.01                          | 6.77                          | -47.24                        | H         | 78.5  |
| 3346.40         | -61.97                          | 7.55                          | -54.42                        | H         | 85.6  |
| 4183.00         | -93.95                          | 7.81                          | -86.14                        | H         | 117.3 |
| 5019.60         | -93.03                          | 9.02                          | -84.00                        | H         | 115.2 |

Table 6-12. Radiated Spurious Data (Cellular GSM Mode – Ch. 190)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 18 of 82                   |

## Cellular GSM Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.80 MHz  
 CHANNEL: 251  
 MEASURED OUTPUT POWER: 31.210 dBm = 1.321 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.21 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1697.60         | -55.58                          | 6.44                          | -49.15                        | H         | 80.4  |
| 2546.40         | -52.56                          | 6.83                          | -45.73                        | H         | 76.9  |
| 3395.20         | -61.31                          | 7.55                          | -53.76                        | H         | 85.0  |
| 4244.00         | -94.20                          | 8.06                          | -86.15                        | H         | 117.4 |
| 5092.80         | -92.56                          | 8.91                          | -83.64                        | H         | 114.9 |

Table 6-13. Radiated Spurious Data (Cellular GSM Mode – Ch. 251)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 19 of 82                   |

## 6.6 Cellular WCDMA Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 826.40 MHz  
 CHANNEL: 4132  
 MEASURED OUTPUT POWER: 24.230 dBm = 0.265 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.23 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1652.80         | -66.81                          | 6.42                          | -60.39                        | V         | 84.6  |
| 2479.20         | -97.76                          | 6.74                          | -91.02                        | V         | 115.3 |
| 3305.60         | -96.25                          | 7.55                          | -88.70                        | V         | 112.9 |
| 4132.00         | -93.73                          | 7.60                          | -86.13                        | V         | 110.4 |
| 4958.40         | -93.32                          | 9.05                          | -84.27                        | V         | 108.5 |

Table 6-14. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4132)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 20 of 82                   |

## Cellular WCDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz  
 CHANNEL: 4183  
 MEASURED OUTPUT POWER: 24.230 dBm = 0.265 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.23 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1673.20         | -66.67                          | 6.42                          | -60.25                        | V         | 84.5  |
| 2509.80         | -97.69                          | 6.76                          | -90.93                        | V         | 115.2 |
| 3346.40         | -96.15                          | 7.55                          | -88.60                        | V         | 112.8 |
| 4183.00         | -93.91                          | 7.78                          | -86.13                        | V         | 110.4 |
| 5019.60         | -93.09                          | 9.04                          | -84.05                        | V         | 108.3 |

Table 6-15. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4183)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 21 of 82                   |

## Cellular WCDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 846.60 MHz  
 CHANNEL: 4233  
 MEASURED OUTPUT POWER: 24.230 dBm = 0.265 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.23 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1693.20         | -64.66                          | 6.43                          | -58.22                        | V         | 82.5  |
| 2539.80         | -97.65                          | 6.82                          | -90.83                        | V         | 115.1 |
| 3386.40         | -96.01                          | 7.55                          | -88.46                        | V         | 112.7 |
| 4233.00         | -94.16                          | 8.01                          | -86.15                        | V         | 110.4 |
| 5079.60         | -92.64                          | 8.93                          | -83.71                        | V         | 107.9 |

Table 6-16. Radiated Spurious Data (Cellular WCDMA Mode – Ch. 4233)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 22 of 82                   |

## 6.7 Cellular CDMA Radiated Measurements

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz  
 CHANNEL: 1013  
 MEASURED OUTPUT POWER: 24.060 dBm = 0.255 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.06 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1649.40         | -66.83                          | 6.42                          | -60.41                        | H         | 84.5  |
| 2474.10         | -63.08                          | 6.74                          | -56.34                        | H         | 80.4  |
| 3298.80         | -60.02                          | 7.55                          | -52.47                        | H         | 76.5  |
| 4123.50         | -56.97                          | 7.57                          | -49.40                        | H         | 73.5  |
| 4948.20         | -93.36                          | 9.05                          | -84.31                        | H         | 108.4 |

**Table 6-17. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 23 of 82                   |

## Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz  
 CHANNEL: 384  
 MEASURED OUTPUT POWER: 24.060 dBm = 0.255 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.06 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1673.04         | -60.81                          | 6.43                          | -54.38                        | H         | 78.4  |
| 2509.56         | -60.20                          | 6.77                          | -53.44                        | H         | 77.5  |
| 3346.08         | -55.43                          | 7.55                          | -47.88                        | H         | 71.9  |
| 4182.60         | -93.94                          | 7.81                          | -86.14                        | H         | 110.2 |
| 5019.12         | -93.03                          | 9.02                          | -84.01                        | H         | 108.1 |

Table 6-18. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 24 of 82                   |

## Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a); RSS-132 (4.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz  
 CHANNEL: 777  
 MEASURED OUTPUT POWER: 24.060 dBm = 0.255 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  37.06 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBd) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 1696.62         | -58.54                          | 6.44                          | -52.10                        | H         | 76.2  |
| 2544.93         | -60.61                          | 6.83                          | -53.78                        | H         | 77.8  |
| 3393.24         | -61.29                          | 7.55                          | -53.74                        | H         | 77.8  |
| 4241.55         | -56.74                          | 8.05                          | -48.70                        | H         | 72.8  |
| 5089.86         | -92.58                          | 8.92                          | -83.66                        | H         | 107.7 |

Table 6-19. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 25 of 82                   |

## 6.8 PCS GSM Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz  
 CHANNEL: 512  
 MEASURED OUTPUT POWER: 31.090 dBm = 1.285 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.09 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3700.40         | -57.30                          | 9.49                          | -47.80                        | H         | 78.9  |
| 5550.60         | -57.03                          | 10.41                         | -46.63                        | H         | 77.7  |
| 7400.80         | -88.95                          | 11.08                         | -77.87                        | H         | 109.0 |
| 9251.00         | -87.80                          | 12.26                         | -75.54                        | H         | 106.6 |
| 11101.20        | -85.98                          | 13.19                         | -72.79                        | H         | 103.9 |

**Table 6-20. Radiated Spurious Data (PCS GSM Mode – Ch. 512)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 26 of 82                   |

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 661  
 MEASURED OUTPUT POWER: 31.090 dBm = 1.285 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 44.09$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3760.00         | -57.01                          | 9.43                          | -47.58                        | H         | 78.7  |
| 5640.00         | -54.24                          | 10.24                         | -44.00                        | H         | 75.1  |
| 7520.00         | -88.85                          | 11.12                         | -77.73                        | H         | 108.8 |
| 9400.00         | -88.05                          | 12.32                         | -75.73                        | H         | 106.8 |
| 11280.00        | -85.29                          | 13.17                         | -72.12                        | H         | 103.2 |

Table 6-21. Radiated Spurious Data (PCS GSM Mode – Ch. 661)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 27 of 82                   |

## PCS GSM Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz  
 CHANNEL: 810  
 MEASURED OUTPUT POWER: 31.090 dBm = 1.285 W  
 MODULATION SIGNAL: GSM (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  44.09 dBc

| FREQUENCY<br>(MHz) | LEVEL @<br>ANTENNA<br>TERMINALS<br>(dBm) | SUBSTITUTE<br>ANTENNA GAIN<br>(dBi) | SPURIOUS<br>EMISSION<br>LEVEL<br>(dBm) | POL<br>(H/V) | (dBc) |
|--------------------|------------------------------------------|-------------------------------------|----------------------------------------|--------------|-------|
| 3819.60            | -59.73                                   | 9.37                                | -50.36                                 | H            | 81.4  |
| 5729.40            | -55.68                                   | 10.08                               | -45.61                                 | H            | 76.7  |
| 7639.20            | -88.81                                   | 11.21                               | -77.60                                 | H            | 108.7 |
| 9549.00            | -88.16                                   | 12.38                               | -75.78                                 | H            | 106.9 |
| 11458.80           | -84.60                                   | 13.15                               | -71.45                                 | H            | 102.5 |

**Table 6-22. Radiated Spurious Data (PCS GSM Mode – Ch. 810)**

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 28 of 82                   |

## 6.9 PCS WCDMA Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1852.40 MHz  
 CHANNEL: 9262  
 MEASURED OUTPUT POWER: 26.600 dBm = 0.457 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  39.60 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3704.80         | -40.27                          | 9.49                          | -30.78                        | V         | 57.4  |
| 5557.20         | -55.27                          | 10.39                         | -44.88                        | V         | 71.5  |
| 7409.60         | -88.94                          | 11.08                         | -77.86                        | V         | 104.5 |
| 9262.00         | -87.82                          | 12.27                         | -75.56                        | V         | 102.2 |
| 11114.40        | -85.93                          | 13.19                         | -72.74                        | V         | 99.3  |

Table 6-23. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9262)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 29 of 82                   |

## PCS WCDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 9400  
 MEASURED OUTPUT POWER: 26.600 dBm = 0.457 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 39.60$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3760.00         | -42.01                          | 9.43                          | -32.58                        | V         | 59.2  |
| 5640.00         | -56.98                          | 10.24                         | -46.74                        | V         | 73.3  |
| 7520.00         | -88.85                          | 11.12                         | -77.73                        | V         | 104.3 |
| 9400.00         | -88.05                          | 12.32                         | -75.73                        | V         | 102.3 |
| 11280.00        | -85.29                          | 13.17                         | -72.12                        | V         | 98.7  |

Table 6-24. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9400)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 30 of 82                   |

## PCS WCDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1907.60 MHz  
 CHANNEL: 9538  
 MEASURED OUTPUT POWER: 26.600 dBm = 0.457 W  
 MODULATION SIGNAL: WCDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) =$  39.60 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3815.20         | -51.66                          | 9.38                          | -42.28                        | V         | 68.9  |
| 5722.80         | -57.56                          | 10.09                         | -47.47                        | V         | 74.1  |
| 7630.40         | -88.81                          | 11.21                         | -77.61                        | V         | 104.2 |
| 9538.00         | -88.17                          | 12.37                         | -75.80                        | V         | 102.4 |
| 11445.60        | -84.65                          | 13.16                         | -71.50                        | V         | 98.1  |

Table 6-25. Radiated Spurious Data (PCS WCDMA Mode – Ch. 9538)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 31 of 82                   |

## 6.10 PCS CDMA Radiated Measurements

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz  
 CHANNEL: 25  
 MEASURED OUTPUT POWER: 24.490 dBm = 0.281 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10}(W) =$  37.49 dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3702.50         | -40.83                          | 9.49                          | -31.34                        | H         | 55.8  |
| 5553.75         | -54.53                          | 10.40                         | -44.13                        | H         | 68.6  |
| 7405.00         | -88.94                          | 11.08                         | -77.86                        | H         | 102.4 |
| 9256.25         | -87.81                          | 12.26                         | -75.55                        | H         | 100.0 |
| 11107.50        | -85.96                          | 13.19                         | -72.77                        | H         | 97.3  |

Table 6-26. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEVDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 32 of 82                   |

## PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz  
 CHANNEL: 600  
 MEASURED OUTPUT POWER: 24.490 dBm = 0.281 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 37.49$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3760.00         | -40.71                          | 9.43                          | -31.28                        | H         | 55.8  |
| 5640.00         | -53.83                          | 10.24                         | -43.59                        | H         | 68.1  |
| 7520.00         | -88.85                          | 11.12                         | -77.73                        | H         | 102.2 |
| 9400.00         | -88.05                          | 12.32                         | -75.73                        | H         | 100.2 |
| 11280.00        | -85.29                          | 13.17                         | -72.12                        | H         | 96.6  |

Table 6-27. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 33 of 82                   |

## PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a); RSS-133 (6.5.1)

### Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz  
 CHANNEL: 1175  
 MEASURED OUTPUT POWER: 24.490 dBm = 0.281 W  
 MODULATION SIGNAL: CDMA (Internal)  
 DISTANCE: 3 meters  
 LIMIT:  $43 + 10 \log_{10} (W) = 37.49$  dBc

| FREQUENCY (MHz) | LEVEL @ ANTENNA TERMINALS (dBm) | SUBSTITUTE ANTENNA GAIN (dBi) | SPURIOUS EMISSION LEVEL (dBm) | POL (H/V) | (dBc) |
|-----------------|---------------------------------|-------------------------------|-------------------------------|-----------|-------|
| 3817.50         | -44.75                          | 9.37                          | -35.37                        | H         | 59.9  |
| 5726.25         | -53.99                          | 10.08                         | -43.91                        | H         | 68.4  |
| 7635.00         | -88.81                          | 11.21                         | -77.60                        | H         | 102.1 |
| 9543.75         | -88.16                          | 12.38                         | -75.79                        | H         | 100.3 |
| 11452.50        | -84.63                          | 13.15                         | -71.47                        | H         | 96.0  |

Table 6-28. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

#### NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all configurations and the highest power is reported in WCDMA mode with HSDPA Inactive at 12.2 kbps RMC and TPC bits all set to "1" and in GPRS mode while transmitting with one slot active. In CDMA mode, this device was tested under all configurations and the worst case is reported in 1xEvDO Rev. A FETAP mode with "All Up" power control bits. This unit was tested with its standard battery. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found in the setup with the lid open. The data reported in the table above was measured in this test setup.

|                                      |                                                                                     |                                                               |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT (CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                           |                                                                                       | Page 34 of 82                   |

## 6.11 Cellular GSM Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 190

REFERENCE VOLTAGE: 10.65 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 10.65       | + 20 (Ref) | 836,599,989    | -11             | -0.000001     |
| 100 %          |             | - 30       | 836,600,016    | 16              | 0.000002      |
| 100 %          |             | - 20       | 836,599,991    | -9              | -0.000001     |
| 100 %          |             | - 10       | 836,600,015    | 15              | 0.000002      |
| 100 %          |             | 0          | 836,599,986    | -14             | -0.000002     |
| 100 %          |             | + 10       | 836,600,007    | 7               | 0.000001      |
| 100 %          |             | + 20       | 836,600,018    | 18              | 0.000002      |
| 100 %          |             | + 30       | 836,600,003    | 3               | 0.000000      |
| 100 %          |             | + 40       | 836,600,014    | 14              | 0.000002      |
| 100 %          |             | + 50       | 836,599,996    | -4              | 0.000000      |
| 115 %          | 12.25       | + 20       | 836,599,989    | -11             | -0.000001     |
| BATT. ENDPOINT | 9.37        | + 20       | 836,599,990    | -10             | -0.000001     |

**Table 6-29. Frequency Stability Data (Cellular GSM Mode – Ch. 190)**

## Cellular GSM Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



**Figure 6-2. Frequency Stability Graph (Cellular GSM Mode – Ch. 190)**

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 36 of 82                   |

## 6.12 Cellular WCDMA Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,600,000 Hz

CHANNEL: 4183

REFERENCE VOLTAGE: 10.65 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 10.65       | + 20 (Ref) | 836,600,024    | 24              | 0.000003      |
| 100 %          |             | - 30       | 836,600,007    | 7               | 0.000001      |
| 100 %          |             | - 20       | 836,600,018    | 18              | 0.000002      |
| 100 %          |             | - 10       | 836,600,014    | 14              | 0.000002      |
| 100 %          |             | 0          | 836,599,994    | -6              | -0.000001     |
| 100 %          |             | + 10       | 836,600,017    | 17              | 0.000002      |
| 100 %          |             | + 20       | 836,600,012    | 12              | 0.000001      |
| 100 %          |             | + 30       | 836,600,021    | 21              | 0.000003      |
| 100 %          |             | + 40       | 836,599,991    | -9              | -0.000001     |
| 100 %          |             | + 50       | 836,599,984    | -16             | -0.000002     |
| 115 %          | 12.25       | + 20       | 836,599,985    | -15             | -0.000002     |
| BATT. ENDPOINT | 9.37        | + 20       | 836,599,997    | -3              | 0.000000      |

**Table 6-30. Frequency Stability Data (Cellular WCDMA Mode – Ch. 4183)**

## Cellular WCDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



**Figure 6-3. Frequency Stability Graph (Cellular WCDMA Mode – Ch. 4183)**

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 38 of 82                   |

## 6.13 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355; RSS-132 (4.3)

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 10.65 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 10.65       | + 20 (Ref) | 836,519,992    | -8              | -0.000001     |
| 100 %          |             | - 30       | 836,519,982    | -18             | -0.000002     |
| 100 %          |             | - 20       | 836,519,986    | -14             | -0.000002     |
| 100 %          |             | - 10       | 836,520,003    | 3               | 0.000000      |
| 100 %          |             | 0          | 836,520,015    | 15              | 0.000002      |
| 100 %          |             | + 10       | 836,519,993    | -7              | -0.000001     |
| 100 %          |             | + 20       | 836,519,998    | -2              | 0.000000      |
| 100 %          |             | + 30       | 836,520,012    | 12              | 0.000001      |
| 100 %          |             | + 40       | 836,519,989    | -11             | -0.000001     |
| 100 %          |             | + 50       | 836,520,013    | 13              | 0.000002      |
| 115 %          | 12.25       | + 20       | 836,519,987    | -13             | -0.000002     |
| BATT. ENDPOINT | 9.37        | + 20       | 836,520,010    | 10              | 0.000001      |

**Table 6-31. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)**

## Cellular CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355; RSS-132 (4.3)



**Figure 6-4. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)**

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 40 of 82                   |

## 6.14 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 661

REFERENCE VOLTAGE: 7.4 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 7.40        | + 20 (Ref) | 1,879,999,995  | -5              | 0.000000      |
| 100 %          |             | - 30       | 1,880,000,007  | 7               | 0.000000      |
| 100 %          |             | - 20       | 1,880,000,015  | 15              | 0.000001      |
| 100 %          |             | - 10       | 1,880,000,009  | 9               | 0.000000      |
| 100 %          |             | 0          | 1,880,000,011  | 11              | 0.000001      |
| 100 %          |             | + 10       | 1,879,999,998  | -2              | 0.000000      |
| 100 %          |             | + 20       | 1,880,000,007  | 7               | 0.000000      |
| 100 %          |             | + 30       | 1,879,999,990  | -10             | -0.000001     |
| 100 %          |             | + 40       | 1,879,999,996  | -4              | 0.000000      |
| 100 %          |             | + 50       | 1,879,999,988  | -12             | -0.000001     |
| 115 %          | 8.51        | + 20       | 1,879,999,989  | -11             | -0.000001     |
| BATT. ENDPOINT | 6.53        | + 20       | 1,880,000,018  | 18              | 0.000001      |

**Table 6-32. Frequency Stability Data (PCS GSM Mode – Ch. 661)**

## PCS GSM Frequency Stability Measurements (Cont'd)

§2.1055, 24.235; RSS-133 (6.3)



**Figure 6-5. Frequency Stability Graph (PCS GSM Mode – Ch. 661)**

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 42 of 82                   |

## 6.15 PCS WCDMA Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 9400

REFERENCE VOLTAGE: 10.65 VDC


DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 10.65       | + 20 (Ref) | 1,879,999,980  | -20             | -0.000001     |
| 100 %          |             | - 30       | 1,879,999,982  | -18             | -0.000001     |
| 100 %          |             | - 20       | 1,879,999,992  | -8              | 0.000000      |
| 100 %          |             | - 10       | 1,879,999,989  | -11             | -0.000001     |
| 100 %          |             | 0          | 1,880,000,008  | 8               | 0.000000      |
| 100 %          |             | + 10       | 1,879,999,994  | -6              | 0.000000      |
| 100 %          |             | + 20       | 1,879,999,986  | -14             | -0.000001     |
| 100 %          |             | + 30       | 1,879,999,981  | -19             | -0.000001     |
| 100 %          |             | + 40       | 1,880,000,018  | 18              | 0.000001      |
| 100 %          |             | + 50       | 1,880,000,012  | 12              | 0.000001      |
| 115 %          | 12.25       | + 20       | 1,880,000,021  | 21              | 0.000001      |
| BATT. ENDPOINT | 9.37        | + 20       | 1,880,000,017  | 17              | 0.000001      |

**Table 6-33. Frequency Stability Data (PCS WCDMA Mode – Ch. 9400)**

## PCS WCDMA Frequency Stability Measurements (Cont'd)

§2.1055, 24.235; RSS-133 (6.3)



**Figure 6-6. Frequency Stability Graph (PCS WCDMA Mode – Ch. 9400)**

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 44 of 82                   |

## 6.16 PCS CDMA Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 600


REFERENCE VOLTAGE: 10.65 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

| VOLTAGE (%)    | POWER (VDC) | TEMP (°C)  | FREQUENCY (Hz) | Freq. Dev. (Hz) | Deviation (%) |
|----------------|-------------|------------|----------------|-----------------|---------------|
| 100 %          | 10.65       | + 20 (Ref) | 1,880,000,015  | 15              | 0.000001      |
| 100 %          |             | - 30       | 1,880,000,007  | 7               | 0.000000      |
| 100 %          |             | - 20       | 1,880,000,022  | 22              | 0.000001      |
| 100 %          |             | - 10       | 1,879,999,984  | -16             | -0.000001     |
| 100 %          |             | 0          | 1,880,000,010  | 10              | 0.000001      |
| 100 %          |             | + 10       | 1,880,000,013  | 13              | 0.000001      |
| 100 %          |             | + 20       | 1,880,000,014  | 14              | 0.000001      |
| 100 %          |             | + 30       | 1,880,000,006  | 6               | 0.000000      |
| 100 %          |             | + 40       | 1,880,000,015  | 15              | 0.000001      |
| 100 %          |             | + 50       | 1,880,000,022  | 22              | 0.000001      |
| 115 %          | 12.25       | + 20       | 1,880,000,017  | 17              | 0.000001      |
| BATT. ENDPOINT | 9.37        | + 20       | 1,880,000,008  | 8               | 0.000000      |

**Table 6-34. Frequency Stability Data (PCS CDMA Mode – Ch. 600)**

**PCS CDMA Frequency Stability Measurements (Cont'd)**  
**§2.1055, 24.235; RSS-133 (6.3)**



**Figure 6-7. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)**


|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 46 of 82                   |

## 6.17 Receiver Spurious Emissions

**RSS-132 (4.6), RSS-133 (6.6)**

| Frequency [MHz] | Level [dBm] | AFCL [dB] | Pol [H/V] | Height [m] | Azimuth [degrees] | Field Strength [dB $\mu$ V/m] | Limit [dB $\mu$ V/m] | Margin [dB] |
|-----------------|-------------|-----------|-----------|------------|-------------------|-------------------------------|----------------------|-------------|
| 43.18           | -97.69      | 12.56     | H         | 1.0        | 325               | 21.87                         | 40.00                | -18.13      |
| 95.33           | -98.92      | 11.25     | H         | 1.0        | 43                | 19.33                         | 43.52                | -24.19      |
| 174.59          | -98.27      | 14.06     | V         | 2.1        | 244               | 22.79                         | 43.52                | -20.73      |
| 216.74          | -99.72      | 14.02     | V         | 2.3        | 110               | 21.30                         | 46.02                | -24.72      |
| 283.42          | -99.56      | 15.12     | H         | 1.1        | 198               | 22.55                         | 46.02                | -23.47      |
| 359.26          | -98.35      | 17.34     | H         | 1.0        | 347               | 25.99                         | 46.02                | -20.04      |

**Table 6-35. Radiated Measurements at 3-meters**



**Figure 6-8. 3-Meter Limits**


### NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. Radiated emissions were measured from 30MHz to three times that of the highest tunable frequency or local oscillator.
3. The radiated limits are shown on Figure 6-8. Above 960MHz the limit is 500 $\mu$ V/m.


1. All readings are calibrated by a Signal Generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
2. AFCL = Antenna Factor and Cable Loss
3. Measurements are made using CISPR quasi-peak mode. Average measurements are recorded above 1GHz.

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 47 of 82                   |

## 7.0 PLOTS OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)




Plot 7-2. Conducted Spurious Plot (Cellular GSM Mode – Ch. 128)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 48 of 82                   |




Plot 7-3. Band Edge Plot (Cellular GSM Mode – Ch. 128)




Plot 7-4. Conducted Spurious (Cellular GSM Mode – Ch. 190)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 49 of 82                   |




Plot 7-5. Conducted Spurious Plot (Cellular GSM Mode – Ch. 190)




Plot 7-6. Occupied Bandwidth Plot (Cellular GSM Mode – Ch. 190)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 50 of 82                   |




Plot 7-7. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)




Plot 7-8. Conducted Spurious Plot (Cellular GSM Mode – Ch. 251)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 51 of 82                   |




Plot 7-9. Band Edge Plot (Cellular GSM Mode – Ch. 251)




Plot 7-10. Occupied Bandwidth Plot (EDGE850 Mode – Ch. 190)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 52 of 82                   |




Plot 7-11. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-12. Conducted Spurious Plot (PCS GSM Mode – Ch. 512)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 53 of 82                   |




Plot 7-13. Band Edge Plot (PCS GSM Mode – Ch. 512)




Plot 7-14. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 54 of 82                   |




Plot 7-15. Conducted Spurious Plot (PCS GSM Mode – Ch. 661)




Plot 7-16. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 55 of 82                   |




Plot 7-17. Peak-Average Ratio Plot (PCS GSM Mode – Ch. 661)




Plot 7-18. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 56 of 82                   |




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)




Plot 7-20. Band Edge Plot (PCS GSM Mode – Ch. 810)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 57 of 82                   |




Plot 7-21. Occupied Bandwidth Plot (EDGE1900 Mode – Ch. 661)




Plot 7-22. Peak-Average Ratio Plot (EDGE1900 Mode – Ch. 661)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 58 of 82                   |




Plot 7-23. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-24. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4132)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 59 of 82                   |




Plot 7-25. Band Edge Plot (Cellular WCDMA Mode – Ch. 4132)




Plot 7-26. 4MHz Span Plot (Cellular WCDMA Mode – Ch. 4132)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 60 of 82                   |




Plot 7-27. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-28. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4183)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 61 of 82                   |




Plot 7-29. Occupied Bandwidth Plot (Cellular WCDMA Mode – Ch. 4183)




Plot 7-30. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 62 of 82                   |



Plot 7-31. Conducted Spurious Plot (Cellular WCDMA Mode – Ch. 4233)




Plot 7-32. Band Edge Plot (Cellular WCDMA Mode – Ch. 4233)


|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 63 of 82                   |



© 2010 PCTEST Engineering Laboratory, Inc.




Plot 7-35. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-36. Band Edge Plot (PCS WCDMA Mode – Ch. 9262)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 65 of 82                   |




Plot 7-37. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9262)




Plot 7-38. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 66 of 82                   |




Plot 7-39. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-40. Occupied Bandwidth Plot (PCS WCDMA Mode – Ch. 9400)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 67 of 82                   |




Plot 7-41. Peak-Average Ratio Plot (PCS WCDMA Mode – Ch. 9400)




Plot 7-42. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 68 of 82                   |




Plot 7-43. Conducted Spurious Plot (PCS WCDMA Mode – Ch. 9538)




Plot 7-44. Band Edge Plot (PCS WCDMA Mode – Ch. 9538)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 69 of 82                   |




Plot 7-45. 4MHz Span Plot (PCS WCDMA Mode – Ch. 9538)




Plot 7-46. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 70 of 82                   |




Plot 7-47. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-48. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 71 of 82                   |




Plot 7-49. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-50. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 72 of 82                   |




Plot 7-51. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-52. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 1013)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 73 of 82                   |




Plot 7-53. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-54. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 74 of 82                   |




Plot 7-55. Band Edge Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-56. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 75 of 82                   |




Plot 7-57. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-58. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 76 of 82                   |




Plot 7-59. Band Edge Plot (PCS CDMA Mode – Ch. 25)




Plot 7-60. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 77 of 82                   |




Plot 7-61. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-62. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 78 of 82                   |




Plot 7-63. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)




Plot 7-64. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 79 of 82                   |




Plot 7-65. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)




Plot 7-66. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 80 of 82                   |



Plot 7-67. Band Edge Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-68. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

|                                      |                                               |                                                                  |                  |                                 |
|--------------------------------------|-----------------------------------------------|------------------------------------------------------------------|------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 | <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) | <b>Panasonic</b> | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010              | EUT Type:<br>Toughbook Model: CF-31                              |                  | Page 81 of 82                   |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Panasonic Toughbook Model: CF-31 FCC ID: ACJ9TGCF-312** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules and RSS-132 and RSS-133 of the Industry Canada rules.

|                                      |                                                                                     |                                                                  |                                                                                       |                                 |
|--------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: ACJ9TGCF-312                 |  | FCC Pt. 22/24 GSM/EDGE/CDMA/WCDMA TEST REPORT<br>(CERTIFICATION) |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1004160652.ACJ | Test Dates:<br>May 27 - 28, 2010                                                    | EUT Type:<br>Toughbook Model: CF-31                              |                                                                                       | Page 82 of 82                   |