

RF Exposure Evaluation - Maximum Permissible Exposure (MPE)

1. Introduction

This document attempts to prove the safety of radiation generated by RF devices to the human body. The limit for Maximum Permissible Exposure (MPE), specified in FCC 1.1210, is listed below. The power generated by this product is measured by a power meter. Through use of the Friis transmission formula and the maximum gain of the antenna, the distance from the product at which compliance with the MPE limit is achieved may be calculated. Alternatively, near field measurements may be performed to demonstrate compliance at a specific measurement distance.

Near field probe: Wandel & Goltermann EMR-200.

2. RF Exposure Limit

According to FCC 1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures				
30-300	61.4	.163	1.0	6
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B) Limits For General Population / Uncontrolled Exposure				
30-300	27.5	.073	.2	30
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2)$

Where:

P_d = power density in mW/cm² (MPE limit)

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

Ref.: David K. Cheng, Field and Wave Electromagnetics, Second Edition, Page 640, Eq. (11.133)

PCTEST MPE REPORT	 FCC CERTIFICATION REPORT			REVIEWED BY: QUALITY MANAGER
TEST REPORT S/N: 0606160520	TEST DATES: July 11, 2006	TEST TYPE: Notebook PC w/ Intel WLAN, Novatel HSDPA, and Taiyo Yuden Bluetooth	FCC ID: ACJ9TGCF-742	PAGE 1 OF 3

4. EUT Operating Condition

Software provided by the client enabled the EUT to transmit and receive data at lowest, middle, and highest channels individually.

5. Climate Condition

The temperature and relative humidity: 22°C and 78% RH

6. Measurement Results

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
824.2	32.27	20 cm	0.0567	0.0120	0.0353	0.0414	549
2412	18.54						
2402	-0.06						

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
836.6	32.28	20cm	0.0577	0.0262	0.0410	0.0438	558
2437	18.40						
2441	0.04						

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
848.8	32.58	20cm	0.0548	0.0193	0.0377	0.0449	566
2462	18.06						
2480	-1.01						

Note: Data is taken with all transmitters (WLAN, HSDPA, and Bluetooth) operating simultaneously.

7. Conclusion

The device meets the mobile 20cm separation distance as specified in Section 2.1091 of the FCC Rules. An appropriate RF exposure compliance statement will be placed in the user's manual.

PCTEST MPE REPORT	 FCC CERTIFICATION REPORT				REVIEWED BY: QUALITY MANAGER
TEST REPORT S/N: 0606160520	TEST DATES: July 11, 2006	EUT TYPE: Notebook PC w/ Intel WLAN, Novatel HSDPA, and Taiyo Yuden Bluetooth	FCC ID: ACJ9TGCF-742	PAGE 2 OF 3	

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
1850.2	29.52	20cm	0.0427	0.0180	0.0246	0.0371	1.0
5745	18.58						
2402	-0.06						

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
1880	29.37	20cm	0.0403	0.0189	0.0231	0.0348	1.0
5785	18.93						
2441	0.04						

Frequency (MHz)	Conducted Level (dBm)	Measurement Distance	Front MPE reading mW/cm^2	Rear MPE reading mW/cm^2	Right MPE reading mW/cm^2	Left MPE reading mW/cm^2	Limit mW/cm^2
1909.8	29.41	20cm	0.0436	0.0212	0.0257	0.0368	1.0
5825	19.31						
2480	-1.01						

Note: Data is taken with all transmitters (WLAN, HSDPA, and Bluetooth) operating simultaneously.

8. Conclusion

The device meets the mobile 20cm separation distance as specified in Section 2.1091 of the FCC Rules. An appropriate RF exposure compliance statement will be placed in the user's manual.

PCTEST MPE REPORT	 FCC CERTIFICATION REPORT				REVIEWED BY: QUALITY MANAGER
TEST REPORT S/N: 0606160520	TEST DATES: July 11, 2006	EUT TYPE: Notebook PC w/ Intel WLAN, Novatel HSDPA, and Taiyo Yuden Bluetooth	FCC ID: ACJ9TGCF-742	PAGE 3 OF 3	