



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 24 & 22 Certification

Applicant Name:

Panasonic Corporation of North America
One Panasonic Way, 4B-8
Secaucus, NJ 07094
United States

Date of Testing:

July 7 - July 10, 2006

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0606160519-G

FCC ID:

ACJ9TGCF-742

APPLICANT:

PANASONIC CORPORATION OF NORTH AMERICA

Application Type:

Certification

FCC Classification:

PCS Licensed Transmitter (PCB)

FCC Rule Part(s):

§24(E), §22(H); §2

EUT Type:

Panasonic Toughbook Model: CF-74

Model(s):

CF-74

Tx Frequency Range:

824.20 - 848.80MHz (Cellular GPRS) / 1850.20 - 1909.80MHz (PCS GPRS)

Rx Frequency Range:

869.20 - 893.80MHz (Cellular GPRS) / 1930.20 - 1989.80MHz (PCS GPRS)

Max. RF Output Power:

1.590 W ERP Cellular GPRS (32.013 dBm) /

0.672 W EIRP PCS GPRS (28.274 dBm) /

0.651 W ERP EDGE850 (28.134 dBm) /

0.473 W EIRP EDGE1900 (26.748 dBm)

Emission Designator(s):

278KGXW (Cellular GPRS) / 277KGXW (PCS GPRS) / 246KG7W (EDGE)

Test Device Serial No.:

identical prototype [S/N: 6BKSA00034R]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 1 of 25

TABLE OF CONTENTS

1.0	SCOPE	3
2.0	INTRODUCTION	4
2.1	TESTING FACILITY	4
2.2	MEASUREMENT PROCEDURE	4
3.0	INSERTS	5
4.0	DESCRIPTION OF TESTS	6
4.1	OCCUPIED BANDWIDTH EMISSION LIMITS	6
4.2	CELLULAR - BASE FREQUENCY BLOCKS	6
4.3	CELLULAR - MOBILE FREQUENCY BLOCKS	6
4.4	PCS - BASE FREQUENCY BLOCKS	7
4.5	PCS - MOBILE FREQUENCY BLOCKS	7
4.6	SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	8
4.7	FREQUENCIES	8
4.8	RADIATED SPURIOUS AND HARMONIC EMISSIONS	8
4.9	FREQUENCY STABILITY / TEMPERATURE VARIATION	9
5.0	EFFECTIVE RADIATED POWER	10
5.1	EFFECTIVE RADIATED POWER OUTPUT DATA	10
6.0	EQUIVALENT ISOTROPIC RADIATED POWER	11
6.1	EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA	11
7.0	RADIATED MEASUREMENTS	12
7.1	CELLULAR GPRS RADIATED MEASUREMENTS	12
7.2	PCS GPRS RADIATED MEASUREMENTS	15
8.0	FREQUENCY STABILITY	18
8.1	FREQUENCY STABILITY (CELLULAR GPRS)	18
8.2	FREQUENCY STABILITY (PCS GPRS)	20
9.0	PLOT(S) OF EMISSIONS	22
10.0	TEST EQUIPMENT	23
11.0	SAMPLE CALCULATIONS	24
12.0	CONCLUSION	25
ATTACHMENT A:	TEST PLOTS	
ATTACHMENT B:	TEST SETUP PHOTOGRAPHS	
ATTACHMENT C:	EXTERNAL PHOTOGRAPHS	
ATTACHMENT D:	INTERNAL PHOTOGRAPHS	

1.0 SCOPE



Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.



§2.1033 General Information

Applicant Name: Panasonic Corporation of North America
 Address: One Panasonic Way, 4B-8
 Secaucus, NJ 07094
 United States

- FCC ID: ACJ9TGCF-742
- Quantity: Quantity production is planned
- Emission Designators: 278KGXW (Cellular GPRS) / 277KGXW (PCS GPRS) / 246KG7W (EDGE)
- Tx Freq. Range: 824.20 - 848.80MHz (Cellular GPRS)
 1850.20 - 1909.80MHz (PCS GPRS)
- Rx Freq. Range: 869.20 - 893.80MHz (Cellular GPRS)
 1930.20 - 1989.80MHz (PCS GPRS)
- Max. Power Rating: 1.590 W ERP Cellular GPRS (32.013 dBm) /
 0.672 W EIRP PCS GPRS (28.274 dBm) /
 0.651 W ERP EDGE850 (28.134 dBm) /
 0.473 W EIRP EDGE1900 (26.748 dBm)
- FCC Classification(s): PCS Licensed Transmitter (PCB)
- Equipment (EUT) Type: Panasonic Toughbook Model: CF-74
- Modulation(s): GMSK / 8PSK
- Frequency Tolerance: $\pm 0.00025\%$ (2.5 ppm)
- FCC Rule Part(s): § 24(E), §22(H)
- Dates of Tests: July 7 - July 10, 2006
- Place of Tests: PCTEST Lab, Columbia, MD U.S.A.
- Test Report S/N: 0606160519-G

Note: Deviation from measurement procedure - None

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 3 of 25

2.0 INTRODUCTION

2.1 Testing Facility




Figure 1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area.

These measurement tests were conducted at PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on October 19, 1992.

2.2 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure2). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 2. Diagram of 3-meter outdoor test range

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 4 of 25

3.0 INSERTS

Function of Active Devices (Confidential)

Block & Schematic Diagrams (Confidential)

Operating Instructions

Parts List & Tune-Up Procedure (Confidential)

Description of Freq. Stabilization Circuit (Confidential)

Description for Suppression of Spurious Radiation, for Limiting Modulation, and Harmonic Suppression Circuits (Confidential)

** These exhibits are not included within this report.*


PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 5 of 25

4.0 DESCRIPTION OF TESTS


4.1 Occupied Bandwidth Emission Limits

- On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee's frequency block edges, both upper and lower, as the design permits.
- The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

4.2 Cellular - Base Frequency Blocks




4.3 Cellular - Mobile Frequency Blocks



PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 6 of 25

4.4 PCS - Base Frequency Blocks



BLOCK 1: 1930 – 1945 MHz (A)

BLOCK 4: 1965 – 1970 MHz (E)


BLOCK 2: 1945 – 1950 MHz (D)

BLOCK 5: 1970 – 1975 MHz (F)

BLOCK 3: 1950 – 1965 MHz (B)

BLOCK 6: 1975 – 1990 MHz (C)

4.5 PCS - Mobile Frequency Blocks



BLOCK 1: 1850 – 1865 MHz (A)

BLOCK 4: 1885 – 1890 MHz (E)

BLOCK 2: 1865 – 1870 MHz (D)

BLOCK 5: 1890 – 1895 MHz (F)

BLOCK 3: 1870 – 1885 MHz (B)

BLOCK 6: 1895 – 1910 MHz (C)

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT			FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 7 of 25	

4.6 Spurious and Harmonic Emissions at Antenna Terminal

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to 10 GHz. The transmitter is modulated with a 2500 Hz tone at a level of 16 dB greater than that required to provide 50% modulation.

At the input terminals of the spectrum analyzer, an isolator (RF circulator with one port terminated in 50 Ω) and an 870 MHz to 890 MHz band-pass filter is connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The rejection of the band-pass filter to signals in the 825 – 845 MHz range is adequate to limit the transmit energy from the test transceiver which appears to a level which will allow the analyzer to measure signals less than –90 dBm. Calibration of the test receiver is performed in the 870 – 890 MHz range to insure accuracy to allow variation in the band-pass filter insertion loss to be calibrated.

4.7 Frequencies

At the input terminals of the spectrum analyzer, an isolator (RF pad) and a high-pass filter are connected between the test transceiver (for conducted tests) or the receive antenna (for radiated tests) and the analyzer. The high-pass filter (signals below 1.6 GHz) is to limit the fundamental frequency from interfering with the measurement of low-level spurious and harmonic emissions and to ensure that the preamplifier is not saturated.

4.8 Radiated Spurious and Harmonic Emissions

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 8 of 25

4.9 Frequency Stability / Temperature Variation

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +60°C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ± 0.00025 (± 2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter and the individual oscillators is measured at room temperature (22°C to 25°C to provide a reference).
2. The equipment is subjected to an overnight “soak” at -30°C without any power applied.
3. After the overnight “soak” at -30°C (usually 14-16 hours), the equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter and the individual oscillators is made within a three minute interval after applying power to the transmitter.
4. Frequency measurements are made at 10°C interval up to room temperature. At least a period of one and one half-hour is provided to allow stabilization of the equipment at each temperature level.
5. Again the transmitter carrier frequency and the individual oscillators is measured at room temperature to begin measurement of the upper temperature levels.
6. Frequency measurements are at 10 intervals starting at -30°C up to +50°C allowing at least two hours at each temperature for stabilization. In all measurements the frequency is measured within three minutes after re-applying power to the transmitter.
7. The artificial load is mounted external to the temperature chamber.

NOTE: The EUT is tested down to the battery endpoint.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 9 of 25

5.0 EFFECTIVE RADIATED POWER

5.1 Effective Radiated Power Output Data

POWER: High (GPRS Mode)

Freq. Tuned (MHz)	REF. LEVEL (dBm)	Mode	POL (H/V)	ERP (W)	ERP (dBm)	BATTERY
824.20	-9.485	GPRS	H	1.509	31.788	Standard
836.60	-9.420	GPRS	H	1.590	32.013	Standard
848.80	-9.621	GPRS	H	1.571	31.962	Standard
836.60	-13.449	EDGE850	H	0.651	28.134	Standard

Note: This unit was tested with its standard battery.

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 10 of 25

6.0 EQUIVALENT ISOTROPIC RADIATED POWER

6.1 Equivalent Isotropic Radiated Power Output Data

Radiated measurements at 3 meters

Supply Voltage: 11.1 VDC

Modulation: PCS GPRS

FREQ. (MHz)	REF. LEVEL (dBm)	Mode	POL (H/V)	Azimuth (o angle)	EIRP (dBm)	EIRP (W)	Battery
1850.20	-14.807	GPRS	H	95	28.274	0.672	Standard
1880.00	-15.248	GPRS	H	95	28.003	0.631	Standard
1909.80	-15.545	GPRS	H	95	27.876	0.613	Standard
1850.20	-16.673	EDGE1900	H	95	26.748	0.473	Standard

Note: This unit was tested with its standard battery.

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 11 of 25

7.0 RADIATED MEASUREMENTS

7.1 Cellular GPRS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.20 MHz
 CHANNEL: 128
 MEASURED OUTPUT POWER: 32.013 dBm = 1.590 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W)$: 45.01 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1648.40	-57.73	6.10	-51.63	H	83.6
2472.60	-62.15	6.70	-55.45	H	87.5
3296.80	-65.29	6.80	-58.49	H	90.5
4121.00	-64.28	6.50	-57.78	V	89.8
4945.20	-84.38	7.00	-77.38	H	109.4

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 12 of 25

7.1 Cellular GPRS Radiated Measurements (Cont'd)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.60 MHz
 CHANNEL: 190
 MEASURED OUTPUT POWER: 32.013 dBm = 1.590 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 45.01 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.20	-57.13	6.10	-51.03	H	83.0
2509.80	-61.86	6.70	-55.16	V	87.2
3346.40	-63.90	6.80	-57.10	V	89.1
4183.00	-63.21	6.50	-56.71	V	88.7
5019.60	-83.88	7.00	-76.88	H	108.9

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

7.1 Cellular GPRS Radiated Measurements (Cont'd)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.80 MHz
 CHANNEL: 251
 MEASURED OUTPUT POWER: 32.013 dBm = 1.590 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 45.01 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1697.60	-58.14	6.10	-52.04	H	84.1
2546.40	-62.36	6.70	-55.66	V	87.7
3395.20	-64.11	6.80	-57.31	V	89.3
4244.00	-64.05	6.50	-57.55	V	89.6
5092.80	-83.98	7.00	-76.98	H	109.0

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 14 of 25

7.2 PCS GPRS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 28.274 dBm = 0.672 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.27 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-60.70	6.10	-54.60	V	82.9
5550.60	-48.45	6.70	-41.75	V	70.0
7400.80	-67.57	6.80	-60.77	H	89.0
9251.00	-85.68	6.50	-79.18	V	107.5
11101.20	-84.38	7.00	-77.38	H	105.7

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 15 of 25

7.2 PCS GPRS Radiated Measurements (Cont'd)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 28.274 dBm = 0.672 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.27 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-64.65	6.10	-58.55	V	86.8
5640.00	-51.13	6.70	-44.43	H	72.7
7520.00	-67.52	6.80	-60.72	V	89.0
9400.00	-85.78	6.50	-79.28	H	107.6
11280.00	-83.78	7.00	-76.78	H	105.1

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 16 of 25

7.2 PCS GPRS Radiated Measurements (Cont'd)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 28.274 dBm = 0.672 W
 MODULATION SIGNAL: GSM
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 41.27 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-62.89	6.10	-56.79	V	85.1
5729.40	-41.97	6.70	-35.27	H	63.5
7639.20	-67.35	6.80	-60.55	H	88.8
9549.00	-85.68	6.50	-79.18	H	107.5
11458.80	-83.98	7.00	-76.98	H	105.3

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-A-2001, Aug. 15, 2001:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 17 of 25

8.0 FREQUENCY STABILITY

8.1 Frequency Stability (Cellular GPRS)

OPERATING FREQUENCY: 836,600,004 Hz


CHANNEL: 190

REFERENCE VOLTAGE: 11.1 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	11.10	+ 20 (Ref)	836,600,004	0.00	0.000000
100 %		-30	836,600,046	-41.83	-0.000005
100 %		-20	836,599,971	33.46	0.000004
100 %		-10	836,599,895	108.76	0.000013
100 %		0	836,599,912	92.03	0.000011
100 %		10	836,599,937	66.93	0.000008
100 %		20	836,600,063	-58.56	-0.000007
100 %		25	836,600,121	-117.12	-0.000014
100 %		30	836,600,012	-8.37	-0.000001
100 %		40	836,599,979	25.10	0.000003
100 %		50	836,600,079	-75.29	-0.000009
100 %		60	836,599,937	66.93	0.000008
85 %	9.44	20	836,600,063	-58.56	-0.000007
115 %	12.77	20	836,600,104	-100.39	-0.000012
BATT. ENDPOINT	8.96	20	836,600,029	-25.10	-0.000003

8.1 Frequency Stability (Cellular GPRS) (Cont'd)



PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 19 of 25

8.2 Frequency Stability (PCS GPRS)

OPERATING FREQUENCY: 1,880,000,003 Hz


CHANNEL: 661

REFERENCE VOLTAGE: 11.1 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQ. (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	11.10	+ 20 (Ref)	1,880,000,003	0.00	0.000000
100 %		-30	1,880,000,153	-150.40	-0.000008
100 %		-20	1,880,000,229	-225.60	-0.000012
100 %		-10	1,879,999,928	75.20	0.000004
100 %		0	1,879,999,702	300.80	0.000016
100 %		10	1,879,999,796	206.80	0.000011
100 %		20	1,879,999,853	150.40	0.000008
100 %		25	1,880,000,135	-131.60	-0.000007
100 %		30	1,880,000,172	-169.20	-0.000009
100 %		40	1,880,000,078	-75.20	-0.000004
100 %		50	1,880,000,247	-244.40	-0.000013
100 %		60	1,880,000,153	-150.40	-0.000008
85 %	9.44	20	1,880,000,135	-131.60	-0.000007
115 %	12.77	20	1,880,000,059	-56.40	-0.000003
BATT. ENDPOINT	8.95	20	1,879,999,853	150.40	0.000008

8.2 Frequency Stability (PCS GPRS) (Cont'd)



PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 21 of 25

9.0 PLOT(S) OF EMISSIONS

(SEE ATTACHMENT A)

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 22 of 25

10.0 TEST EQUIPMENT

TYPE	MODEL	CAL. DUE DATE	CAL. INTERVAL	SERIAL No.
Microwave Spectrum Analyzer	Agilent E4448A (3Hz-50GHz)	09/19/06	Annual	US42510244
Spectrum Analyzer/Tracking Generator	HP 8591A (9kHz-1.8GHz)	09/12/06	Annual	3144A02458
Spectrum Analyzer	HP 8566B (100Hz-2.5GHz/2-22GHz)	12/22/06	Annual	3638A08713
Signal Generator	HP 8640D (500Hz-1GHz)	12/07/07	Annual	3613A00315
PSG Analog Signal Generator	Agilent E8257D (250kHz-20GHz)	03/08/07	Annual	MY45470194
5 Watt Amplifier	5S1G4 (800MHz-4.2GHz)	N/A	N/A	22332
Universal Radio Communication Tester	CMU200	04/20/07	Annual	836370/079
Universal Power Meter	Gigatronics 8651A (50MHz-18GHz)	07/28/07	Annual	1834052
Power Sensor	Gigatronics 80701A	04/11/07	Annual	1833460
Quasi-Peak Adapter	HP 85650A	08/09/06	Annual	2043A00301
Preamplifier	HP 8449B (1-26.5GHz)	12/22/06	Annual	3008A00985
Attenuation/Switch Driver	HP 11713A	12/22/06	Annual	N/A
Preselector	HP 85685A (20Hz-2GHz)	12/22/06	Annual	N/A
6dB Res BW Spec. Analyzer Display	OPT 462	12/22/06	Annual	3701A22204
Ailtech/Eaton Adapter	CCA-7 CISPR/ANSI QP Adapter	12/19/06	Annual	0194-04082
Ailtech/Eaton Receiver	NM 37/57A (30MHz – 1GHz)	06/07/07	Annual	0805-03334
Broadband Amplifier (2)	HP 8447D (0.1 – 1300MHz)	N/A	N/A	2443A01900, 1937A03348
Horn Antenna	EMCO Model 3115 (1-18GHz)	08/25/07	Annual	9704-5182
Horn Antenna	EMCO Model 3116 (18-40GHz)	08/25/07	Annual	9203-2178
Roberts Dipoles	Compliance Design (1 set) A100	08/31/06	Annual	5118
EMCO Dipoles (2)	N/A	05/08/08	Annual	00023951
EMCO LISN (3)	3816/2, 3816/2, 3725/2	10/26/06	Annual	1077, 1079, 2099
10dB Attenuator	HP 8493B	N/A	N/A	N/A
Microwave Cables	MicroCoax (1.0-26.5GHz)	02/26/07	Annual	N/A
Shielded Screen Room	RF Lindgren Model 26-2/2-0	N/A	N/A	6710 (PCT270)
Shielded Semi-Anechoic Chamber	Ray Proof Model S81	N/A	N/A	R2437 (PCT278)
Environmental Chamber	Associated Systems 1025	08/08/06	Annual	PCT285
OATS	N/A	12/31/2006	Tri-annual	N/A

Table 10-1. Test Equipment

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 23 of 25

11.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 250KGXW

GSM BW = 250 kHz

G = Phase Modulation

X = Cases not otherwise covered

W = Combination (Audio/Data)

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 24 of 25

12.0 CONCLUSION

The data collected shows that the Panasonic Toughbook Model: CF-74 FCC ID: ACJ9TGCF-742 complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

PCTEST™ PT. 22/24 GPRS-HSDPA TEST REPORT		FCC MEASUREMENT REPORT (GPRS-HSDPA)		Reviewed by: Quality Manager
Test Report S/N: 0606160519-G	Test Dates: July 7 - July 10, 2006	EUT Type: Panasonic Toughbook Model: CF-74	FCC ID: ACJ9TGCF-742	Page 25 of 25