



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

Applicant Name:

Panasonic Corporation of North America
One Panasonic Way, 4B-8
Secaucus, NJ 07094
United States

Date of Testing:

08/11-12/2008 and 09/28-10/08/2009

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0909041657.ACJ

FCC ID:

ACJ9TGCF-U15

APPLICANT:

PANASONIC CORPORATION OF NORTH AMERICA

EUT Type:

Handheld PC with 802.11abgn with Bluetooth and WWAN

Application Type:

Certification

FCC Rule Part(s):

CFR §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]

FCC Classification:

FCC Part 15 Frequency Hopping Spread Spectrum Transceiver (DSS)

Unlicensed Transmitter National Infrastructure (UNII)

PCS Licensed Transmitter (PCB) / Digital Transmission System (DTS)

Model(s):

CF-U1

Tx Frequency:

824.70 - 848.31 MHz (Cellular CDMA) / 1850.20 - 1909.80 MHz (GSM PCS)

876.20 - 914.8 MHz (GSM 900) / 1850.2 - 1908.8 MHz (GSM1900)

826.4 - 846.6 MHz (WCDMA850) / 1852.4 - 1907.6 MHz (WCDMA1900)

2402 - 2480 MHz (Bluetooth) / 2412 - 2462 MHz (WLAN 802.11b/g/a/n)

5180 - 5240 MHz, 5260 - 5320 MHz, 5500 - 5700 MHz, 5745 - 5825 MHz (WLAN 802.11a/11/n)

Conducted Power:

32.9 dBm GSM 850 / 30.18 dBm GSM 1900

24.67 dBm UMTS V / 24.38 dBm UMTS II

24.76 dBm Cell. CDMA EVDO / 25.00 dBm PCS CDMA EVDO

Max. Body SAR

0.51 W/kg GPRS850 / 0.10 W/kg GPRS1900

Measurement:

0.42 W/kg WCDMA850 / 0.16 W/kg WCDMA1900

0.39 W/kg Cellular CDMA / 0.13 W/kg PCS CDMA

0.39 W/kg EVDO Rev.0 / 0.14 W/kg PCS EVDO Rev.0 / 0.052 W/kg Bluetooth

0.061 W/kg WLAN 802.11b / 0.051 W/kg WLAN 802.11g / 0.045 W/kg WLAN 802.11n 2.4 GHz

0.090 W/kg WLAN 802.11a 5.2 GHz / 0.093 W/kg WLAN 802.11n 5.2 GHz

0.068 W/kg WLAN 802.11a 5.3 GHz / 0.077 W/kg WLAN 802.11n 5.3 GHz

0.104 W/kg WLAN 802.11a 5.5 GHz / 0.103 W/kg WLAN 802.11n 5.5 GHz

0.064 W/kg WLAN 802.11a 5.8 GHz / 0.044 W/kg WLAN 802.11n 5.8 GHz

Test Device Serial No.:

Pre-Production [S/N: 9GKSA00076]

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001), IEEE 1528-2003 and in applicable Industry Canada Radio Standards Specifications (RSS); for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 1 of 43

T A B L E O F C O N T E N T S

1	INTRODUCTION	3
2	TEST SITE LOCATION	4
3	SAR MEASUREMENT SETUP	5
4	DASY E-FIELD PROBE SYSTEM	7
5	PROBE CALIBRATION PROCESS	8
6	PHANTOM AND EQUIVALENT TISSUES.....	9
7	DOSIMETRIC ASSESSMENT & PHANTOM SPECS.....	10
8	DEFINITION OF REFERENCE POINTS	11
9	FCC 3G MEASUREMENT PROCEDURES.....	15
10	MULTIPLE ANTENNA & SEPARATION DISTANCES	17
11	ANSI/IEEE C95.1-1992 RF EXPOSURE LIMITS.....	24
12	MEASUREMENT UNCERTAINTIES	25
13	SYSTEM VERIFICATION.....	26
14	SAR DATA SUMMARY	28
15	EQUIPMENT LIST	39
16	CONCLUSION.....	41
17	REFERENCES	42

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 2 of 43

1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz[2] and Health Canada RF Exposure Guidelines Safety Code 6 [26]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [3] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dV} \right)$$

Figure 1-1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]


FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 3 of 43

2 TEST SITE LOCATION

2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC (See Figure 2).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.



3 SAR MEASUREMENT SETUP

3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium 4 computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Gateway Pentium 4 2.53 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

3.3 System Electronics




Figure 3-1
SAR Measurement System Setup

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

FCC ID: ACJ9TGCF-U15	 PCTEST ENGINEERING LABORATORY, INC.	CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 5 of 43

3.4 Automated Test System Specifications

Positioner

Robot: Stäubli Unimation Corp. Robot RX60L
Repeatability: 0.02 mm
No. of Axes: 6

Data Acquisition Electronic System (DAE)

Cell Controller

Processor: Pentium 4
Clock Speed: 2.53 GHz
Operating System: Windows XP Professional

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic
Software: DASY4, SEMCAD software
Connecting Lines: Optical Downlink for data and status info
Optical upload for commands and clock

PC Interface Card

Function: 166MHz low power Pentium MMX 32MB chipdisk
Link to DAE
16-bit A/D converter for surface detection system
Two Serial & Ethernet link to robotics
Direct emergency stop output for robot

Phantom

Type: SAM Twin Phantom (V4.0)
Shell Material: Composite
Thickness: 2.0 ± 0.2 mm



Figure 3-2
DASY4 SAR Measurement System

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 6 of 43

4.1 Probe Measurement System



Figure 4-1
SAR System

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration [7] (see Figure 4-3) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach

and looks for the maximum using a 2nd order fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

4.2 Probe Specifications

Model:	ES3DV3, EX3DV4
Frequency Range:	10 MHz – 6.0 GHz (EX3DV4) 10 MHz – 4 GHz (ES3DV3)
Calibration:	In brain and muscle simulating tissue at Frequencies from 835 up to 5800MHz
Linearity:	± 0.2 dB (30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB (30 MHz to 4 GHz) for ES3DV3
Dynamic Range:	10 mW/kg – 100 W/kg
Probe Length:	330 mm
Probe Tip Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9mm for ES3DV3)
Tip-Center:	1 mm (2.0 mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields



Figure 4-2
Near-Field Probe



Figure 4-3
Triangular Probe Configuration

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 7 of 43

5 PROBE CALIBRATION PROCESS

5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = simulated tissue conductivity,

ρ = Tissue density (1.25 g/cm³ for brain tissue)

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;




Figure 5-1 E-Field and Temperature measurements at 900MHz [7]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [7]

FCC ID: ACJ9TGCF-U15	 PCTEST ENGINEERING LABORATORY, INC.	CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 8 of 43

6 PHANTOM AND EQUIVALENT TISSUES

6.1 SAM Phantoms



Figure 6-1
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

6.2 Brain & Muscle Simulating Mixture Characterization




Figure 6-2
Head Simulated

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 6-1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in IEEE-1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrrove [13]. (See Table 6-1)

Table 6-1
Composition of the Brain & Muscle Tissue Equivalent Matter

Frequency (MHz)	300	450	835	900				1450	1800				1900		1950	2000	2100			2450	3000
Recipe #	1	1	3	1	1	2	3	1	1	2	2	3	1	2	4	1	1	2	2	3	2
Ingredient: (% by weight)																					
1,2-Propanediol							64.81														
Bactericide	0.19	0.19	0.50	0.10	0.10		0.50					0.50								0.50	
Diacetin			48.90				49.20					49.43								49.75	
DGSE								45.41	47.00	13.84	44.92		44.94	13.84	45.00	50.00	50.00	7.99	7.99		7.99
HEC	0.98	0.98		1.00	1.00																
NaCl	5.95	3.95	1.70	1.45	1.48	0.79	1.10	0.67	0.36	0.35	0.18	0.64	0.18	0.35				0.16	0.16		0.16
Sucrose	55.32	56.32		57.00	56.50																
Triton X-100										30.45				30.45				19.97	19.97		19.97
Water	37.56	38.56	48.90	40.45	40.92	34.40	49.20	53.80	52.64	55.36	54.90	49.43	54.90	55.36	55.00	50.00	50.00	71.88	71.88	49.75	71.88
Measured dielectric parameters																					
ϵ'_p	46.00	43.4	44.3	41.6	41.2	41.8	42.7	40.9	39.3	41	40.4	39.2	39.9	41	40.1	37	36.8	41.1	40.3	39.2	37.9
σ (S/m)	0.86	0.85	0.9	0.9	0.98	0.97	0.99	1.21	1.39	1.38	1.4	1.4	1.42	1.38	1.41	1.4	1.51	1.55	1.88	1.82	2.46
Temp. (°C)	22	22	20	22	22	22	20	22	22	21	22	20	21	21	20	22	22	20	20	20	20
Target dielectric parameters: (Table 2)																					
ϵ'_p	45.30	43.50	41.5	41.50				40.5	40.0								39.80			39.2	38.3
σ (S/m)	0.87	0.87	0.9	0.97				1.2	1.4								1.49			1.8	2.4
NOTE—Multiple columns for any single frequency are optional recipes. Recipe #, reference: 1 (Kasali et al. [B85]), 2 (Vignosa [B143]), 3 (Peyman and Gabriel [B119]), 4 (Poullaga et al. [B50]).																					

NOTE—Multiple columns for any single frequency are optional recipes. Recipe #, reference: 1 (Kanda et al. [B85]), 2 (Vigneron [B145]), 3 (Vigneron and Gabriel [B119]), 4 (Fitzpatrick et al. [B50]).

*The formulas containing Triton X-100 and corresponding measured parameters are under review and verification.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 9 of 43

7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed point was measured and used as a reference value.
2. The SAR distribution at the exposed side of the phantom was measured at a distance of 3.0mm from the inner surface of the shell. The horizontal grid spacing was 15mm x 15mm.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Figure 7-1):
 - a. The data at the surface was extrapolated since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in the z-axis. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - b. The maximum interpolated value was found with a software algorithm. Around this maximum, the SAR values averaged over the spatial volumes (1g or 10g) were computed using 3D-Spline interpolation. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 1, was re-measured to measure drift. If the value drifted by more than 5%, the evaluation was repeated.




Figure 7-1
Sample SAR Area Scan

7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.



Figure 7-2
SAM Twin Phantom Shell

FCC ID: ACJ9TGCF-U15	 PCTEST ENGINEERING LABORATORY, INC.	CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 10 of 43

8.1 SAR for Notebooks and Lap-touching Devices

Lap-touching devices that have transmitting antennas located less than 20 cm from the lap of the user require routine SAR evaluation. Such devices are considered portable and are capable of being held to the body. Devices are to be setup touching the phantom and are configured with maximum output power during SAR assessment for a worst-case SAR evaluation.



Figure 8-1
Notebook Setup for SAR

8.2 Integral Antenna PCMCIA and CompactFlash Cards

KDB 497522. Integral-antenna PCMCIA and CompactFlash radio cards are common module-like devices meant to be purchased and installed without tools or special skills by consumers. The common host configurations (platforms, categories) are notebook (laptop) computers with PCMCIA slot(s) in the keyboard section, and PDAs (personal digital assistants or palmtop computers). Integral-antenna radio cards installed in PDAs with body-worn and/or held-to-ear configurations, and in all notebook computers, must be evaluated under portable RF exposure conditions per 47 C.F.R. 2.1093(b). To better represent the range of near field topography and environment of various notebook and PDA hosts, SAR evaluation using a minimum of three hosts within each platform type (three PDAs, three notebooks, etc.) is recommended by FCC. Hosts shall be modern, current-market, and expected final installations for the PC Cards.



Figure 8-2
CompactFlash radio card in PDA
host configuration

For notebook computers with multiple card slots (e.g., two stacked), RF exposure should be evaluated with the transmitter installed in the slot(s) producing the highest SAR (See Figure 8-3). The minimum number of positions that should be evaluated for notebook computers and body-worn PDAs are bottom-face in parallel and in contact (0 cm) with flat phantom, and device perpendicular to phantom with recommended spacing of 1.5 cm.



Figure 8-3
PCMCIA Radio Card in a
notebook host configuration

8.3 Positioning for Convertible and Slate Tablet Computers



Figure 8-4
Tablet Computer Form Factors




Figure 8-5
Tablet PC Body SAR

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 11 of 43

KDB 447498. Tablet (notepad) computers are tested in a lap-held position with the bottom of the computer in direct contact against a flat phantom for all user-enabled portrait and landscape positions.

8.4 SAR Testing with IEEE 802.11 a/b/g Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.



8.4.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

8.4.2 Frequency Channel Configurations [22]

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels. These are referred to as the “default test channels”. 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 12 of 43

Table 8-1
802.11 Test Channels per FCC Requirements

Mode	GHz	Channel	Turbo Channel	"Default Test Channels"			
				§15.247		UNII	
				802.11b	802.11g		
802.11 b/g	2.412	1		√	▽		
	2.437	6	6	√	▽		
	2.462	11		√	▽		
802.11a	5.18	36				√	
	5.20	40	42 (5.21 GHz)				*
	5.22	44					*
	5.24	48	50 (5.25 GHz)			√	
	5.26	52				√	
	5.28	56	58 (5.29 GHz)				*
	5.30	60					*
	5.32	64				√	
	5.500	100	Unknown				*
	5.520	104				√	
	5.540	108					*
	5.560	112					*
	5.580	116				√	
	5.600	120					*
	5.620	124				√	
	5.640	128					*
	5.660	132					*
	5.680	136				√	
	5.700	140					*
UNII or §15.247	5.745	149		√		√	
	5.765	153	152 (5.76 GHz)		*		*
	5.785	157		√			*
	5.805	161	160 (5.80 GHz)		*	√	
	§15.247	5.825	165	√			

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN	Page 13 of 43	

8.5 Device Conducted Powers (802.11abgn WLAN)

Mode	Freq [MHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]											
					Data Rate [Mbps]											
					1	2	5.5	11								
802.11b	2412	1	N/A	A	12.52	12.35	12.17	12.05								
802.11b	2437	6	N/A	A	14.33	14.15	14.01	13.91								
802.11b	2462	11	N/A	A	12.82	12.72	12.57	12.49								

Mode	Freq [MHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]							
					Data Rate [Mbps]							
					6	9	12	18	24	36	48	54
802.11g	2412	1	N/A	A	13.60	13.61	13.59	13.58	13.47	13.23	13.25	12.12
802.11g	2437	6	N/A	A	15.29	15.31	15.27	15.25	15.12	15.05	13.52	11.44
802.11g	2462	11	N/A	A	14.08	14.09	14.04	13.99	13.90	13.76	13.67	11.54

Mode	Freq [MHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]							
					Data Rate [Mbps]							
					13.5	27	40	54	81	108	122	135
802.11n	2422	3	N/A	A	13.29	13.20	13.06	12.91	12.81	12.74	11.36	9.76
802.11n	2437	6	N/A	A	15.21	15.12	14.99	15.28	15.16	13.61	11.72	9.63
802.11n	2452	9	N/A	A	15.29	15.27	15.15	14.99	14.88	13.32	11.44	9.32

Mode	Freq [MHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]							
					Data Rate [Mbps]							
					6	9	12	18	24	36	48	54
802.11a	5180	36	N/A	A	12.55	12.30	12.32	12.30	12.16	12.50	11.94	9.54
802.11a	5200	40	N/A	A	13.67	13.70	13.73	13.78	13.18	13.53	11.93	9.65
802.11a	5220	44	N/A	A	13.50	13.51	13.41	13.43	13.30	13.17	11.84	9.84
802.11a	5240	48	N/A	A	13.38	13.88	13.32	13.37	13.25	13.61	11.87	9.41
802.11a	5260	52	N/A	A	13.46	13.42	13.15	13.17	13.07	13.62	11.89	9.33
802.11a	5280	56	N/A	A	13.26	13.25	13.28	13.30	13.19	12.95	11.55	9.50
802.11a	5300	60	N/A	A	12.66	13.20	13.18	13.24	13.09	12.94	11.02	8.99
802.11a	5320	64	N/A	A	12.40	12.30	12.33	12.36	12.70	12.45	10.61	8.90
802.11a	5745	149	N/A	A	13.20	13.07	13.05	13.46	12.98	12.88	11.52	9.50
802.11a	5765	153	N/A	A	13.13	13.09	12.97	13.02	12.90	12.83	11.41	9.41
802.11a	5785	157	N/A	A	12.48	12.45	12.84	12.81	12.75	12.65	11.16	9.22
802.11a	5805	161	N/A	A	12.59	12.43	12.31	12.32	12.18	12.09	11.13	9.24
802.11a	5825	165	N/A	A	11.99	11.94	11.91	11.89	12.36	11.46	10.65	8.74

Mode	Freq [MHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]							
					Data Rate [Mbps]							
					13.5	27	40	54	81	108	122	135
802.11n	5190	38	N/A	A	12.06	11.95	11.87	11.73	11.61	11.49	9.04	6.91
802.11n	5230	46	N/A	A	13.74	13.60	13.50	13.41	13.25	11.40	8.84	7.37
802.11n	5270	54	N/A	A	12.58	12.55	12.44	12.73	12.61	11.12	9.03	7.02
802.11n	5310	62	N/A	A	12.00	11.80	11.78	11.89	12.17	10.06	8.10	6.19
802.11n	5755	151	N/A	A	12.79	12.64	12.46	12.33	12.24	10.75	8.83	7.20
802.11n	5795	159	N/A	A	12.19	12.02	11.95	11.83	11.75	10.35	8.39	6.97

ver. 2006.10

Mode	Freq [GHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]										
					Data Rate [Mbps]										
					6	9	12	18	24	36	48	54			
802.11a	5.500	100	N/A	A	12.95	12.96	12.92	12.91	12.75	12.64	11.00	8.93			
802.11a	5.520	104	N/A	A	12.83	12.86	12.82	12.79	12.72	12.90	11.46	9.41			
802.11a	5.540	108	N/A	A	13.35	13.25	13.24	13.81	13.70	13.53	11.63	9.50			
802.11a	5.560	112	N/A	A	13.40	13.33	13.27	13.26	13.16	12.99	12.09	10.07			
802.11a	5.580	116	N/A	A	14.13	14.04	14.23	14.08	14.05	14.04	12.38	10.36			
802.11a	5.600	120	N/A	A	13.74	13.70	13.66	13.59	13.54	13.35	11.94	9.64			
802.11a	5.620	124	N/A	A	13.35	13.24	13.21	13.23	13.14	13.03	11.60	9.60			
802.11a	5.640	128	N/A	A	13.46	13.28	13.25	13.23	13.07	13.12	11.55	9.55			
802.11a	5.660	132	N/A	A	13.03	13.00	12.89	12.88	12.75	13.11	11.70	9.70			
802.11a	5.680	136	N/A	A	13.00	12.95	12.84	12.83	12.79	12.61	11.19	9.21			
802.11a	5.700	140	N/A	A	13.18	13.15	13.10	13.12	13.05	12.91	11.44	9.47			

Mode	Freq [GHz]	Channel	Power Cont [dBm]	Tx Chain	Conducted Power [dBm]										
					Data Rate [Mbps]										
					13.5	27	40	54	81	108	122	135			
802.11n	5.510	102	N/A	A	12.67	12.61	12.37	12.17	12.08	10.52	8.54	6.98			
802.11n	5.590	118	N/A	A	13.67	13.43	13.40	13.15	12.93	11.52	9.55	7.70			
802.11n	5.670	134	N/A	A	12.89	13.60	13.00	13.14	13.08	11.22	9.31	7.82			

ver. 2006.10

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 14 of 43

Power measurements were performed using a base station simulator under digital average power.

9.1 Procedures Used to Establish RF Signal for SAR

The handset was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, this was configured with the base station simulator. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5% occurred, the tests were repeated.

9.2 SAR Measurement Conditions for UMTS

9.2.1 Output Power Verification

Maximum output power is verified on the High, Middle and Low channels according to the general descriptions in section 5.2 of 3GPP TS 34.121, using the appropriate RMC or AMR with TPC (transmit power control) set to all "1s".

9.2.2 Head SAR Measurements

SAR for head exposure configurations is measured using the 12.2 kbps RMC with TPC bits configured to all "1s". SAR in AMR configurations is not required when the maximum average output of each RF channel for 12.2 kbps AMR is less than ¼ dB higher than that measured in 12.2 kbps RMC. Otherwise, SAR is measured on the maximum output channel in 12.2 AMR with a 3.4 kbps SRB (signaling radio bearer) using the exposure configuration that results in the highest SAR for that RF channel in 12.2 RMC.

9.2.3 Body SAR Measurements

SAR for body exposure configurations is measured using the 12.2 kbps RMC with the TPC bits all "1s".

9.2.4 Handsets with HSDPA

Body SAR is not required for handsets with HSDPA capabilities when the maximum average output of each RF channel with HSDPA active is less than ¼ dB higher than that measured without HSDPA using 12.2 kbps RMC and the maximum SAR for 12.2 kbps RMC is ≤ 75% of the SAR limit. Otherwise, SAR is measured for HSDPA, using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, using the highest body SAR configuration in 12.2 kbps RMC without HSDPA, on the maximum output channel with the body exposure configuration that results in the highest SAR in 12.2 kbps RMC for that RF channel.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 15 of 43

9.3 RF Conducted Powers: CF-U1 (WWAN)

		RF Conducted Power Table			
		GPRS Data		EDGE Data	
Band	Channel	GPRS [dBm] 1 Tx Slot	GPRS [dBm] 2 Tx Slot	EDGE [dBm] 1 Tx Slot	EDGE [dBm] 2 Tx Slot
Cellular	128	32.90	32.84	27.82	27.79
	190	32.58	32.55	27.57	27.54
	251	32.09	32.05	27.19	27.16
PCS	512	29.79	29.74	20.80	20.81
	661	30.18	30.12	21.20	21.16
	810	30.11	30.05	21.21	21.16

Band	Channel	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]	1x EvDO Rev. A [dBm]
	F-RC	RC3	(FTAP)	(RTAP)	(FETAP)	(RETAP)
	Vocoder Rate	N/A	N/A	N/A	N/A	N/A
Cellular	1013	24.68	24.76	24.15	24.97	23.86
	384	24.58	24.38	23.67	24.61	23.72
	777	24.57	24.36	23.67	24.57	23.67
PCS	25	25.04	24.98	24.76	25.17	24.24
	600	25.08	24.90	25.00	25.07	24.28
	1175	25.11	24.87	24.63	24.97	24.01

3GPP Release Version	Mode	3GPP 34.121 Subtest	Cellular Band [dBm]			PCS Band [dBm]			β_c	β_d	β_c/β_d	HSDPA FRC	MPR
			4132	4183	4233	9262	9400	9538					
99	WCDMA	12.2 kbps RMC	24.67	24.51	24.46	24.32	24.38	24.02	-	-	-	-	-
6	HSDPA	Subtest 1	24.65	24.48	24.42	24.27	24.36	24.01	2/15	15/15	2/15	H-SET 1	0
6		Subtest 2	24.69	24.50	24.41	24.15	24.42	24.00	12/15	15/15	12/15	H-SET 1	0
6		Subtest 3	24.15	23.95	23.84	23.78	23.95	23.48	15/15	8/15	15/8	H-SET 1	0.5
6		Subtest 4	24.17	23.98	23.86	23.82	23.98	23.48	15/15	4/15	15/4	H-SET 1	0.5
6	HSUPA	Subtest 1	24.63	24.43	24.42	24.35	24.45	23.87	11/15	15/15	11/15	H-SET 1	0
6		Subtest 2	22.62	22.40	22.38	22.32	22.43	21.89	6/15	15/15	6/15	H-SET 1	2
6		Subtest 3	23.65	23.36	23.37	23.31	23.40	22.81	15/15	9/15	15/9	H-SET 1	1
6		Subtest 4	22.57	22.33	22.32	22.24	22.47	21.90	2/15	15/15	2/15	H-SET 1	2
6		Subtest 5	24.59	24.34	24.31	24.27	24.41	23.81	15/15	15/15	15/15	H-SET 1	0




Figure 9-1
Power Measurement Setup

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 16 of 43

Table 10-1 Maximum Conducted Power

Maximum Conducted Power						
Transmitter	Frequency Band	Highest Frequency	Conducted Power		60/f (GHz)	>60/f
	MHz	MHz	dBm	mW	mW	
GSM GPRS850	835	848.80	32.90	1,949.84	70.69	yes
GSM GPRS1900	1880	1,880.00	30.18	1,042.32	31.91	yes
WCDMA850	836	836.60	24.67	293.09	71.72	yes
WCDMA1900	1880	1,880.00	24.38	274.16	31.91	yes
Cell CDMA	835	836.60	24.68	293.76	71.72	yes
PCS CDMA	1880	1,880.00	25.11	324.34	31.91	yes
EVDO Rev.0	835	848.31	24.76	299.23	70.73	yes
EVDO Rev.0	1880	1,908.75	25.00	316.23	31.43	yes
EVDO Rev.A	835	848.31	24.97	314.05	70.73	yes
EVDO Rev.A	1880	1,908.75	25.17	328.85	31.43	yes
Bluetooth	2441	2,480.00	13.67	23.28	24.19	no
802.11b	2437	2,462.00	14.33	27.10	24.37	yes
802.11g	2437	2,462.00	15.31	33.96	24.37	yes
802.11a	5200	5,240.00	13.88	24.43	11.45	yes
802.11a	5300	5,320.00	13.62	23.01	11.28	yes
802.11a	5500	5,600.00	14.23	26.49	10.71	yes
802.11a	5785	5,825.00	13.46	22.18	10.30	yes
802.11n	2437	2,462.00	15.29	33.81	24.37	yes
802.11n	5200	5,240.00	13.74	23.66	11.45	yes
802.11n	5300	5,320.00	12.73	18.75	11.28	yes
802.11n	5500	5,600.00	13.67	23.28	10.71	yes
802.11n	5785	5,825.00	12.79	19.01	10.30	yes

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 17 of 43

Table 10-2 Co-Transmission

Co-Transmission																		
TX		GPRS	GPRS	WCDMA	WCDMA	BT	802.11b	802.11g	802.11a	802.11a	802.11a	802.11a	802.11n	802.11n	802.11n	802.11n	802.11n	802.11n
	Freq	850	1900	850	1900	2441	2437	2437	5200	5300	5500	5800	2437	5200	5300	5500	5800	5800
GPRS	850	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
GPRS	1900	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WCDMA	850	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
WCDMA	1900	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
BT	2441	yes	yes	yes	yes	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
802.11b	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11g	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5200	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5300	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5500	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5800	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5200	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5300	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5500	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5800	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Table 10-3 Co-Transmission

Co-Transmission																		
TX		CDMA	CDMA	EVDO	EVDO	BT	802.11b	802.11g	802.11a	802.11a	802.11a	802.11a	802.11n	802.11n	802.11n	802.11n	802.11n	802.11n
	Freq	Cellular	PCS	Cellular	PCS	2441	2437	2437	5200	5300	5500	5800	2437	5200	5300	5500	5800	5800
CDMA	Cellular	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
CDMA	PCS	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
EVDO	Cellular	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
EVDO	PCS	N/A	N/A	N/A	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
BT	2441	yes	yes	yes	yes	N/A	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
802.11b	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11g	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5200	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5300	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5500	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11a	5800	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	2437	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5200	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5300	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5500	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
802.11n	5800	yes	yes	yes	yes	yes	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Table 10-4 Distance – Antenna to Antenna

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 18 of 43

Distance - Antenna to Antenna			
Antenna	WWAN	WLAN	BT
WWAN	N/A	92	63
WLAN	92	N/A	168
BT	63	168	N/A
WWAN: GSM,WCDMA,CDMA, EVDO; WLAN: 802.11abgn Unit: mm			

Table 10-5 Distance – Antenna to Body

Distance - Antenna to Body			
Position	Antenna		
	WWAN	WLAN	BT
Bottom	40	20	27
Edge- Bottom	142	123	60
Edge- Right	100	10	171
Edge- Left	22	171	9
WWAN: GSM,WCDMA,CDMA, EVDO; WLAN: 802.11abgn Unit: mm			

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN	Page 19 of 43	

Table 10-6 Summary of Σ SAR

Position	SAR Result [W/kg]														
	GPRS	GPRS	BT	802.11b	802.11g	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	Sigma SAR
	850	1900	2441	2437	2437	2437	5200	5200	5300	5300	5500	5500	5800	5800	
Bottom	0.238		0.051	0.061											0.350
Bottom	0.238		0.051		0.051										0.340
Bottom	0.238		0.051			0.045									0.334
Bottom	0.238		0.051				0.090								0.379
Bottom	0.238		0.051					0.093							0.382
Bottom	0.238		0.051						0.068						0.357
Bottom	0.238		0.051							0.077					0.366
Bottom	0.238		0.051								0.104				0.393
Bottom	0.238		0.051									0.103			0.392
Bottom	0.238		0.051										0.064		0.353
Bottom	0.238		0.051											0.044	0.333
Bottom		0.095	0.051	0.061											0.207
Bottom		0.095	0.051		0.051										0.197
Bottom		0.095	0.051			0.045									0.191
Bottom		0.095	0.051				0.090								0.236
Bottom		0.095	0.051					0.093							0.239
Bottom		0.095	0.051						0.068						0.214
Bottom		0.095	0.051							0.077					0.223
Bottom		0.095	0.051								0.104				0.250
Bottom		0.095	0.051									0.103			0.249
Bottom		0.095	0.051										0.064		0.210
Bottom		0.095	0.051											0.044	0.190
Edge	0.507		0.052	0.021											0.580
Edge	0.507		0.052		0.018										0.577
Edge	0.507		0.052			0.017									0.576
Edge	0.507		0.052				0.016								0.575
Edge	0.507		0.052					0.016							0.575
Edge	0.507		0.052						0.019						0.578
Edge	0.507		0.052							0.017					0.576
Edge	0.507		0.052								0.022				0.581
Edge	0.507		0.052									0.022			0.581
Edge	0.507		0.052										0.020		0.579
Edge	0.507		0.052											0.021	0.580
Edge		0.083	0.052	0.021											0.156
Edge		0.083	0.052		0.018										0.153
Edge		0.083	0.052			0.017									0.152
Edge		0.083	0.052				0.016								0.151
Edge		0.083	0.052					0.016							0.151
Edge		0.083	0.052						0.019						0.154
Edge		0.083	0.052							0.017					0.152
Edge		0.083	0.052								0.022				0.157
Edge		0.083	0.052									0.022			0.157
Edge		0.083	0.052										0.020		0.155
Edge		0.083	0.052											0.021	0.156

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 20 of 43

Table 10-7 Summary of Σ SAR

Position	SAR Result [W/kg]															Sigma SAR
	WCDMA	WCDMA	BT	802.11b	802.11g	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n		
	850	1900	2441	2437	2437	2437	5200	5200	5300	5300	5500	5500	5800	5800		
Bottom	0.225		0.051	0.061											0.337	
Bottom	0.225		0.051		0.051										0.327	
Bottom	0.225		0.051			0.045									0.321	
Bottom	0.225		0.051				0.090								0.366	
Bottom	0.225		0.051					0.093							0.369	
Bottom	0.225		0.051						0.068						0.344	
Bottom	0.225		0.051							0.077					0.353	
Bottom	0.225		0.051								0.104				0.380	
Bottom	0.225		0.051									0.103			0.379	
Bottom	0.225		0.051										0.064		0.340	
Bottom	0.225		0.051											0.044	0.320	
Bottom		0.115	0.051	0.061											0.227	
Bottom		0.115	0.051		0.051										0.217	
Bottom		0.115	0.051			0.045									0.211	
Bottom		0.115	0.051				0.090								0.256	
Bottom		0.115	0.051					0.093							0.259	
Bottom		0.115	0.051						0.068						0.234	
Bottom		0.115	0.051							0.077					0.243	
Bottom		0.115	0.051								0.104				0.270	
Bottom		0.115	0.051									0.103			0.269	
Bottom		0.115	0.051										0.064		0.230	
Bottom		0.115	0.051											0.044	0.210	
Edge	0.424		0.052	0.021											0.497	
Edge	0.424		0.052		0.018										0.494	
Edge	0.424		0.052			0.017									0.493	
Edge	0.424		0.052				0.016								0.492	
Edge	0.424		0.052					0.016							0.492	
Edge	0.424		0.052						0.019						0.495	
Edge	0.424		0.052							0.017					0.493	
Edge	0.424		0.052								0.022				0.498	
Edge	0.424		0.052									0.022			0.498	
Edge	0.424		0.052										0.020		0.496	
Edge	0.424		0.052											0.021	0.497	
Edge		0.161	0.052	0.021											0.234	
Edge		0.161	0.052		0.018										0.231	
Edge		0.161	0.052			0.017									0.230	
Edge		0.161	0.052				0.016								0.229	
Edge		0.161	0.052					0.016							0.229	
Edge		0.161	0.052						0.019						0.232	
Edge		0.161	0.052							0.017					0.230	
Edge		0.161	0.052								0.022				0.235	
Edge		0.161	0.052									0.022			0.235	
Edge		0.161	0.052										0.020		0.233	
Edge		0.161	0.052											0.021	0.234	

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN	Page 21 of 43	

Table 10-8 Summary of Σ SAR

Position	SAR Result [W/kg]														
	CDMA	CDMA	BT	802.11b	802.11g	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	Sigma SAR
	Cellular	1880	2441	2437	2437	2437	5200	5200	5300	5300	5500	5500	5800	5800	
Bottom	0.212		0.051	0.061											0.324
Bottom	0.212		0.051		0.051										0.314
Bottom	0.212		0.051			0.045									0.308
Bottom	0.212		0.051				0.090								0.353
Bottom	0.212		0.051					0.093							0.356
Bottom	0.212		0.051						0.068						0.331
Bottom	0.212		0.051							0.077					0.340
Bottom	0.212		0.051								0.104				0.367
Bottom	0.212		0.051									0.103			0.366
Bottom	0.212		0.051										0.064		0.327
Bottom	0.212		0.051											0.044	0.307
Bottom		0.114	0.051	0.061											0.226
Bottom		0.114	0.051		0.051										0.216
Bottom		0.114	0.051			0.045									0.210
Bottom		0.114	0.051				0.090								0.255
Bottom		0.114	0.051					0.093							0.258
Bottom		0.114	0.051						0.068						0.233
Bottom		0.114	0.051							0.077					0.242
Bottom		0.114	0.051								0.104				0.269
Bottom		0.114	0.051									0.103			0.268
Bottom		0.114	0.051										0.064		0.229
Bottom		0.114	0.051											0.044	0.209
Edge	0.394		0.052	0.021											0.467
Edge	0.394		0.052		0.018										0.464
Edge	0.394		0.052			0.017									0.463
Edge	0.394		0.052				0.016								0.462
Edge	0.394		0.052					0.016							0.462
Edge	0.394		0.052						0.019						0.465
Edge	0.394		0.052							0.017					0.463
Edge	0.394		0.052								0.022				0.468
Edge	0.394		0.052									0.022			0.468
Edge	0.394		0.052										0.020		0.466
Edge	0.394		0.052											0.021	0.467
Edge		0.130	0.052	0.021											0.203
Edge		0.130	0.052		0.018										0.200
Edge		0.130	0.052			0.017									0.199
Edge		0.130	0.052				0.016								0.198
Edge		0.130	0.052					0.016							0.198
Edge		0.130	0.052						0.019						0.201
Edge		0.130	0.052							0.017					0.199
Edge		0.130	0.052								0.022				0.204
Edge		0.130	0.052									0.022			0.204
Edge		0.130	0.052										0.020		0.202
Edge		0.130	0.052											0.021	0.203

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN	Page 22 of 43	

Table 10-9 Summary of Σ SAR

Position	SAR Result [W/kg]															Sigma SAR
	EVDO Rev.0	EVDO Rev.0	BT	802.11b	802.11g	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n	802.11a	802.11n		
	Cellular	PCS	2441	2437	2437	2437	5200	5200	5300	5300	5500	5500	5800	5800		
Bottom	0.190		0.051	0.061											0.302	
Bottom	0.190		0.051		0.051										0.292	
Bottom	0.190		0.051			0.045									0.286	
Bottom	0.190		0.051				0.090								0.331	
Bottom	0.190		0.051					0.093							0.334	
Bottom	0.190		0.051						0.068						0.309	
Bottom	0.190		0.051							0.077					0.318	
Bottom	0.190		0.051								0.104				0.345	
Bottom	0.190		0.051									0.103			0.344	
Bottom	0.190		0.051										0.064		0.305	
Bottom	0.190		0.051											0.044	0.285	
Bottom		0.091	0.051	0.061											0.203	
Bottom		0.091	0.051		0.051										0.193	
Bottom		0.091	0.051			0.045									0.187	
Bottom		0.091	0.051				0.090								0.232	
Bottom		0.091	0.051					0.093							0.235	
Bottom		0.091	0.051						0.068						0.210	
Bottom		0.091	0.051							0.077					0.219	
Bottom		0.091	0.051								0.104				0.246	
Bottom		0.091	0.051									0.103			0.245	
Bottom		0.091	0.051										0.064		0.206	
Bottom		0.091	0.051											0.044	0.186	
Edge	0.385		0.052	0.021											0.458	
Edge	0.385		0.052		0.018										0.455	
Edge	0.385		0.052			0.017									0.454	
Edge	0.385		0.052				0.016								0.453	
Edge	0.385		0.052					0.016							0.453	
Edge	0.385		0.052						0.019						0.456	
Edge	0.385		0.052							0.017					0.454	
Edge	0.385		0.052								0.022				0.459	
Edge	0.385		0.052									0.022			0.459	
Edge	0.385		0.052										0.020		0.457	
Edge	0.385		0.052											0.021	0.458	
Edge		0.135	0.052	0.021											0.208	
Edge		0.135	0.052		0.018										0.205	
Edge		0.135	0.052			0.017									0.204	
Edge		0.135	0.052				0.016								0.203	
Edge		0.135	0.052					0.016							0.203	
Edge		0.135	0.052						0.019						0.206	
Edge		0.135	0.052							0.017					0.204	
Edge		0.135	0.052								0.022				0.209	
Edge		0.135	0.052									0.022			0.209	
Edge		0.135	0.052										0.020		0.207	
Edge		0.135	0.052											0.021	0.208	

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 23 of 43

11 ANSI/IEEE C95.1-1992 RF EXPOSURE LIMITS

11.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

11.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 11-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
SPATIAL PEAK SAR Brain	1.6	8.0
SPATIAL AVERAGE SAR Whole Body	0.08	0.4
SPATIAL PEAK SAR Hands, Feet, Ankles, Wrists	4.0	20

1 The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

2 The Spatial Average value of the SAR averaged over the whole body.

3 The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 24 of 43

12 MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E2.1	6.6	N	1	1.0	1.0	6.6	6.6	∞
Axial Isotropy	E2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.4	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.7	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 25 of 43

13 SYSTEM VERIFICATION

13.1 Tissue Verification

Table 13-1
Measured Tissue Properties

Calibrated Date:	Tissue Type	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
09/28/2009	835M	820	0.983	54.93	0.97	55.20	1.34%	-0.49%
		835	0.997	54.80	0.97	55.20	2.78%	-0.72%
		850	1.010	54.66	0.97	55.20	4.12%	-0.98%
09/28/2009	1900M	1850	1.447	52.53	1.52	53.30	-4.80%	-1.44%
		1880	1.467	52.32	1.52	53.30	-3.49%	-1.84%
		1910	1.505	52.10	1.52	53.30	-0.99%	-2.25%

Tissue Type	Conductivity: σ (S/m)			Relative Permittivity: ϵ			Calibration Date
	Target	Measured	Deviation	Target	Measured	Deviation	
2450MHz Brain	1.80	1.76	-2.22%	39.20	38.42	-1.99%	08/11/2008
2450MHz Muscle	1.95	1.92	-1.54%	52.70	51.77	-1.76%	08/11/2008
5200MHz Muscle	5.30	5.41	+2.08%	49.00	49.81	+1.65%	08/11/2009
5300MHz Muscle	5.42	5.32	-1.85%	48.90	47.59	-2.68%	08/11/2008
5500MHz Muscle	5.65	5.82	+3.01%	48.60	49.31	+1.46%	08/11/2008
5800MHz Muscle	6.00	6.12	+2.00%	48.20	49.55	+2.80%	08/11/2008

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 26 of 43

Test System Verification

Prior to assessment, the system is verified to $\pm 10\%$ of the specifications at by using the system validation kit(s). (Graphic Plots Attached)

Table 13-2
System Verification Results

System Verification TARGET & MEASURED									
Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Tissue Frequency (MHz)	Dipole SN	Tissue Type	Targeted SAR _{1g} (mW)	Measured SAR _{1g} (mW)	Deviation (%)
09/28/2009	23.7	22.6	0.100	1900	5d080	Muscle	4.05	4.27	5.43%
09/29/2009	23.9	22.8	0.100	1900	5d080	Muscle	4.05	4.19	3.46%
09/30/2009	24.2	23.1	0.100	835	4d026	Muscle	0.98	1.01	3.27%
10/02/2009	24.3	23.4	0.100	835	4d026	Muscle	0.98	1.03	5.32%

Date	Frequency	Ambient Temp	Liquid Temp	Input Power	Target SAR	Measured SAR	Deviation
	MHz	°C	°C	mW	W/kg	W/kg	%
08/11/2008	2450	23.8	22.5	100	5.41	5.56	+2.77
08/11/2008	5200	23.9	22.7	100	7.23	7.70	+6.50
08/12/2008	5500	23.6	22.4	100	7.68	8.22	+7.03
08/12/2008	5800	23.8	22.7	100	6.73	7.04	+4.61




Figure 13-1
System Verification Setup Diagram



Figure 13-2
System Verification Setup Photo

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 27 of 43

14 SAR DATA SUMMARY

14.1 GSM GPRS Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Slot	Spacing (cm)	SAR
MHz	Ch.		Start	End					(W/kg)
836.6	190	GPRS850	32.55	32.79	Bottom	-	2x	0.0	0.238
836.6	190	GPRS850	32.55	32.63	Edge	Bottom	2x	0.0	0.081
836.6	190	GPRS850	32.55	32.76	Edge	Right	2x	0.0	0.213
836.6	190	GPRS850	32.55	33.06	Edge	Left	2x	0.0	0.507
836.6	190	EGPRS850	27.54	27.93	Edge	Left	2x	0.0	0.388
1880.0	661	GPRS1900	30.12	30.22	Bottom	-	2x	0.0	0.095
1880.0	661	GPRS1900	30.12	30.15	Edge	Bottom	2x	0.0	0.033
1880.0	661	GPRS1900	30.12	30.14	Edge	Right	2x	0.0	0.021
1880.0	661	GPRS1900	30.12	30.20	Edge	Left	2x	0.0	0.083
1880.0	661	EGPRS1900	21.16	21.25	Bottom	-	2x	0.0	0.087
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

FCC ID: ACJ9TGCF-U15	 PCTEST ENGINEERING LABORATORY, INC.	CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 28 of 43

14.2 WCDMA Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	HSPA	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	SAR (W/kg)
MHz	Ch.			Start	End				
836.60	4183	WCDMA850	Inactive	24.67	24.90	Bottom	-	0.0	0.225
836.60	4183	WCDMA850	Inactive	24.67	24.77	Edge	Bottom	0.0	0.104
836.60	4183	WCDMA850	Inactive	24.67	24.81	Edge	Right	0.0	0.137
836.60	4183	WCDMA850	Inactive	24.67	25.09	Edge	Left	0.0	0.424
1880.00	9400	WCDMA1900	Inactive	24.38	24.50	Bottom	-	0.0	0.115
1880.00	9400	WCDMA1900	Inactive	24.38	24.41	Edge	Bottom	0.0	0.032
1880.00	9400	WCDMA1900	Inactive	24.38	24.44	Edge	Right	0.0	0.059
1880.00	9400	WCDMA1900	Inactive	24.38	24.54	Edge	Left	0.0	0.161
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						Body 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. WCDMA mode was tested under RMC 12.2 kbps with HSPA Inactive

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 29 of 43

14.3 CDMA Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Service	SAR
MHz	Ch.		Start	End					(W/kg)
836.52	384	Cellular CDMA	24.58	24.79	Bottom	-	0.0	TDSO32	0.212
836.52	384	Cellular CDMA	24.58	24.67	Edge	Bottom	0.0	TDSO32	0.090
836.52	384	Cellular CDMA	24.58	24.71	Edge	Right	0.0	TDSO32	0.126
836.52	384	Cellular CDMA	24.58	24.97	Edge	Left	0.0	TDSO32	0.394
1880.00	600	PCS CDMA	25.08	25.19	Bottom	-	0.0	TDSO32	0.114
1880.00	600	PCS CDMA	25.08	25.11	Edge	Bottom	0.0	TDSO32	0.033
1880.00	600	PCS CDMA	25.08	25.14	Edge	Right	0.0	TDSO32	0.060
1880.00	600	PCS CDMA	25.08	25.21	Edge	Left	0.0	TDSO32	0.130
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. CDMA2000 mode was tested under RC3/TDSO32

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 30 of 43

14.4 Cellular EVDO Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	SAR	Test Protocol
MHz	Ch.		Start	End				(W/kg)	
836.60	384	EVDO Cellular Rev.0	24.38	24.57	Bottom	-	0.0	0.189	FTAP
836.60	384	EVDO Cellular Rev.0	24.90	25.09	Bottom	-	0.0	0.190	RTAP
836.60	384	EVDO Cellular Rev.0	24.38	24.47	Edge	Bottom	0.0	0.094	FTAP
836.60	384	EVDO Cellular Rev.0	24.90	25.00	Edge	Bottom	0.0	0.100	RTAP
836.60	384	EVDO Cellular Rev.0	24.38	24.48	Edge	Right	0.0	0.102	FTAP
836.60	384	EVDO Cellular Rev.0	24.90	25.00	Edge	Right	0.0	0.098	RTAP
836.60	384	EVDO Cellular Rev.0	24.38	24.75	Edge	Left	0.0	0.372	FTAP
836.60	384	EVDO Cellular Rev.0	24.90	25.29	Edge	Left	0.0	0.385	RTAP
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 31 of 43

14.5 PCS EVDO Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	SAR	Test Protocol
MHz	Ch.		Start	End				(W/kg)	
1880.00	600	EVDO PCS Rev.0	24.90	24.99	Bottom	-	0.0	0.091	FTAP
1880.00	600	EVDO PCS Rev.0	25.00	25.09	Bottom	-	0.0	0.088	RTAP
1880.00	600	EVDO PCS Rev.0	24.90	24.93	Edge	Bottom	0.0	0.033	FTAP
1880.00	600	EVDO PCS Rev.0	25.00	25.03	Edge	Bottom	0.0	0.032	RTAP
1880.00	600	EVDO PCS Rev.0	24.90	24.96	Edge	Right	0.0	0.062	FTAP
1880.00	600	EVDO PCS Rev.0	25.00	25.05	Edge	Right	0.0	0.051	RTAP
1880.00	600	EVDO PCS Rev.0	24.90	25.04	Edge	Left	0.0	0.135	FTAP
1880.00	600	EVDO PCS Rev.0	25.00	25.13	Edge	Left	0.0	0.132	RTAP
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July, 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 32 of 43

14.6 Bluetooth Body SAR Results

MEASUREMENT RESULTS									
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	SAR	Remarks
MHz	Ch.		Start	End				(W/kg)	
2441	39	FHSS	13.67	13.87	Laptop	-	0.0	0.051	
2441	39	FHSS	13.67	13.80	Tablet	Bottom	0.0	0.052	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT					Body				
Spatial Peak					1.6 W/kg (mW/g)				
Uncontrolled Exposure/General Population					averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 33 of 43

14.7 IEEE 802.11b/11g/11n Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Data Rate (Mbps)	SAR	Remarks
MHz	Ch.		Start	End					(W/kg)	
2412	1	DSSS	12.52	12.70	Laptop	-	0.0	1	0.059	802.11b
2437	6	DSSS	14.33	14.46	Laptop	-	0.0	1	0.061	802.11b
2462	11	DSSS	12.82	12.71	Laptop	-	0.0	1	0.052	802.11b
2412	1	DSSS	12.52	12.65	Tablet	Bottom	0.0	1	0.016	802.11b
2437	6	DSSS	14.33	14.47	Tablet	Bottom	0.0	1	0.020	802.11b
2462	11	DSSS	12.82	13.01	Tablet	Bottom	0.0	1	0.021	802.11b
2412	1	OFDM	13.60	13.57	Laptop	-	0.0	6	0.051	802.11g
2437	6	OFDM	15.29	15.14	Laptop	-	0.0	6	0.050	802.11g
2462	11	OFDM	14.08	14.10	Laptop	-	0.0	6	0.046	802.11g
2412	1	OFDM	13.60	13.75	Tablet	Bottom	0.0	6	0.016	802.11g
2437	6	OFDM	15.29	15.48	Tablet	Bottom	0.0	6	0.018	802.11g
2462	11	OFDM	14.08	14.21	Tablet	Bottom	0.0	6	0.017	802.11g
2422	3	OFDM	13.29	13.43	Laptop	-	0.0	13.5	0.045	802.11n
2437	6	OFDM	15.21	15.38	Laptop	-	0.0	13.5	0.043	802.11n
2452	9	OFDM	15.29	15.43	Laptop	-	0.0	13.5	0.044	802.11n
2422	3	OFDM	13.29	13.43	Tablet	Bottom	0.0	13.5	0.012	802.11n
2437	6	OFDM	15.21	15.34	Tablet	Bottom	0.0	13.5	0.015	802.11n
2452	9	OFDM	15.29	15.19	Tablet	Bottom	0.0	13.5	0.017	802.11n
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram					

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 34 of 43

14.8 IEEE 802.11a/11n 5.2GHz Band Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Data Rate (Mbps)	SAR	Remarks
MHz	Ch.		Start	End					(W/kg)	
5200	40	OFDM	13.67	13.85	Laptop	-	0.0	6	0.090	802.11a
5240	48	OFDM	13.38	13.53	Laptop	-	0.0	6	0.086	802.11a
5200	40	OFDM	13.67	13.66	Tablet	Bottom	0.0	6	0.016	802.11a
5240	48	OFDM	13.38	13.54	Tablet	Bottom	0.0	6	0.013	802.11a
5190	38	OFDM	12.06	12.20	Laptop	-	0.0	13.5	0.093	802.11n
5230	46	OFDM	13.74	13.89	Laptop	-	0.0	13.5	0.086	802.11n
5190	38	OFDM	12.06	12.23	Tablet	Bottom	0.0	13.5	0.011	802.11n
5230	46	OFDM	13.74	13.90	Tablet	Bottom	0.0	13.5	0.016	802.11n
ANSI / IEEE C95.1 1992 - SAFETY LIMIT					Body					
Spatial Peak					1.6 W/kg (mW/g)					
Uncontrolled Exposure/General Population					averaged over 1 gram					

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Ch.40 was tested instead of Ch.36 since it is the maximum output channel.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 35 of 43

14.9 IEEE 802.11a/11n 5.3GHz Band Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Data Rate (Mbps)	SAR	Remarks
MHz	Ch.		Start	End					(W/kg)	
5260	52	OFDM	13.46	13.65	Laptop	-	0.0	6	0.061	802.11a
5300	60	OFDM	12.66	12.84	Laptop	-	0.0	6	0.068	802.11a
5260	52	OFDM	13.46	13.60	Tablet	Bottom	0.0	6	0.018	802.11a
5300	60	OFDM	12.66	12.81	Tablet	Bottom	0.0	6	0.019	802.11a
5270	54	OFDM	12.58	12.71	Laptop	-	0.0	13.5	0.077	802.11n
5310	62	OFDM	12.00	12.18	Laptop	-	0.0	13.5	0.068	802.11n
5270	54	OFDM	12.58	12.72	Tablet	Bottom	0.0	13.5	0.015	802.11n
5310	62	OFDM	12.00	12.17	Tablet	Bottom	0.0	13.5	0.015	802.11n
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram					

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.
6. Ch.60 was tested instead of Ch.64 since it is the maximum output channel.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 36 of 43

14.10 IEEE 802.11a/11n 5.5GHz Band Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Data Rate (Mbps)	SAR	Remarks
MHz	Ch.		Start	End					(W/kg)	
5540	108	OFDM	13.35	13.27	Laptop	-	0.0	6	0.100	802.11a
5580	116	OFDM	14.13	14.14	Laptop	-	0.0	6	0.101	802.11a
5600	120	OFDM	13.74	13.68	Laptop	-	0.0	6	0.104	802.11a
5660	132	OFDM	13.03	13.22	Laptop	-	0.0	6	0.050	802.11a
5540	108	OFDM	13.35	13.49	Tablet	Bottom	0.0	6	0.022	802.11a
5580	116	OFDM	14.13	14.40	Tablet	Bottom	0.0	6	0.018	802.11a
5600	120	OFDM	13.74	13.90	Tablet	Bottom	0.0	6	0.019	802.11a
5660	132	OFDM	13.03	13.19	Tablet	Bottom	0.0	6	0.021	802.11a
5510	102	OFDM	12.67	12.59	Laptop	-	0.0	13.5	0.101	802.11n
5590	118	OFDM	13.67	13.61	Laptop	-	0.0	13.5	0.103	802.11n
5670	134	OFDM	12.89	13.01	Laptop	-	0.0	13.5	0.061	802.11n
5510	102	OFDM	12.67	12.81	Tablet	Bottom	0.0	13.5	0.022	802.11n
5590	118	OFDM	13.67	13.83	Tablet	Bottom	0.0	13.5	0.021	802.11n
5670	134	OFDM	12.89	13.05	Tablet	Bottom	0.0	13.5	0.021	802.11n
ANSI / IEEE C95.1 1992 - SAFETY LIMIT					Body					
Spatial Peak					1.6 W/kg (mW/g)					
Uncontrolled Exposure/General Population					averaged over 1 gram					

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 37 of 43

14.11 IEEE 802.11a/11n 5.8GHz Band Body SAR Results

MEASUREMENT RESULTS										
FREQUENCY		Modulation	Conducted Power [dBm]		Test Position	LCD Side	Spacing (cm)	Data Rate (Mbps)	SAR	Remarks
MHz	Ch.		Start	End					(W/kg)	
5745	149	OFDM	13.20	13.33	Laptop	-	0.0	6	0.064	802.11a
5785	157	OFDM	12.48	12.61	Laptop	-	0.0	6	0.054	802.11a
5825	165	OFDM	11.99	12.16	Laptop	-	0.0	6	0.040	802.11a
5745	149	OFDM	13.20	13.33	Tablet	Bottom	0.0	6	0.020	802.11a
5785	157	OFDM	12.48	12.63	Tablet	Bottom	0.0	6	0.018	802.11a
5825	165	OFDM	11.99	12.16	Tablet	Bottom	0.0	6	0.020	802.11a
5755	151	OFDM	12.79	12.92	Laptop	-	0.0	13.5	0.034	802.11n
5795	159	OFDM	12.19	12.33	Laptop	-	0.0	13.5	0.044	802.11n
5755	151	OFDM	12.79	12.94	Tablet	Bottom	0.0	13.5	0.021	802.11n
5795	159	OFDM	12.19	12.32	Tablet	Bottom	0.0	13.5	0.020	802.11n
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population					Body 1.6 W/kg (mW/g) averaged over 1 gram					

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard batteries were investigated.
4. Tissue parameters and temperatures are listed on the SAR plots
5. Liquid tissue depth is 15.1 cm. $\pm$ 0.1.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 38 of 43

15 EQUIPMENT LIST

August 11-12, 2008

Manufacturer	Model	Description	Calibration Date	Cal Interval	Calibration Due	Serial No.
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/11/07	Biennial	10/10/09	3613A00315
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/12/08	Annual	3/12/09	JP38020182
Agilent	E5515C	Wireless Communications Test Set	6/8/07	Biennial	6/8/09	GB46110872
Agilent	E5515C	Wireless Communications Test Set	6/8/07	Biennial	6/8/09	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/31/07	Biennial	8/31/09	GB41450275
Agilent	E6651A	Mobile WiMAX Tester	8/23/07	Biennial	8/22/09	MY47310109
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/8/07	Biennial	3/8/09	MY45470194
Index SAR	IXTL-010	Dielectric Measurement Kit	N/A		N/A	
Index SAR	IXTL-030	30MM TEM line for 6 GHz	N/A		N/A	
Rohde & Schwarz	CMU200	Base Station Simulator	5/29/08	Annual	5/29/09	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	9/7/07	Annual	9/6/08	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	12/6/07	Annual	12/5/08	107826
Rohde & Schwarz	CMU200	Base Station Simulator	12/13/07	Annual	12/13/08	109892
Rohde & Schwarz	NRVD	Dual Channel Power Meter	12/12/06	Biennial	12/11/08	101695
Rohde & Schwarz	NRVS	Single Channel Power Meter	7/3/07	Biennial	7/2/09	835360/0079
Rohde & Schwarz	NRV-Z32	Peak Power Sensor (100uW-2W)	12/21/06	Biennial	12/20/08	100155
Rohde & Schwarz	NRV-Z33	Peak Power Sensor (1mW-20W)	11/28/06	Biennial	11/27/08	100004
Rohde & Schwarz	NRV-Z53	Power Sensor	7/3/07	Biennial	7/2/09	846076/0007
SPEAG	D1450V2	1450 MHz SAR Dipole	6/11/07	Biennial	6/10/09	1025
SPEAG	D1765V2	1765 MHz SAR Dipole	6/11/07	Biennial	6/10/09	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	1/23/07	Biennial	1/22/09	502
SPEAG	D1900V2	1900 MHz SAR Dipole	1/23/07	Biennial	1/22/09	5d080
SPEAG	D2300V2	2300 MHz SAR Dipole	3/6/08	Biennial	3/6/10	1008
SPEAG	D2450V2	2450 MHz SAR Dipole	9/26/07	Biennial	9/25/09	719
SPEAG	D2450V2	2450 MHz SAR Dipole	1/17/07	Biennial	1/16/09	797
SPEAG	D2600V2	2600 MHz SAR Dipole	1/30/08	Biennial	1/29/10	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	9/25/07	Biennial	9/24/09	1007
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/24/07	Biennial	1/23/09	1057
SPEAG	D835V2	835 MHz SAR Dipole	1/8/07	Biennial	1/7/09	4d047
SPEAG	D835V2	835 MHz SAR Dipole	8/27/07	Biennial	8/26/09	4d026
SPEAG	DAE3	Dasy Data Acquisition Electronics	11/13/07	Annual	11/12/08	455
SPEAG	DAE4	Dasy Data Acquisition Electronics	8/29/07	Annual	8/28/08	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/30/08	Annual	1/29/09	649
SPEAG	ES3DV2	SAR Probe	10/23/07	Annual	10/22/08	3022
SPEAG	EX3DV4	SAR Probe	8/30/07	Annual	8/29/08	3561
SPEAG	EX3DV4	SAR Probe	1/31/08	Annual	1/30/09	3550

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 39 of 43

09/28/2009 – 10/08/2009

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/11/2007	Biennial	10/11/2009	3613A00315
Agilent	8753E	(30kHz-6GHz) Network Analyzer	3/25/2009	Annual	3/25/2010	JP38020182
Agilent	E5515C	Wireless Communications Test Set	8/25/2009	Biennial	8/25/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/25/2009	Biennial	3/25/2011	MY45470194
Gigatronics	80701A	(0.05-18GHz) Power Sensor	9/9/2009	Annual	9/9/2010	1833460
Gigatronics	8651A	Universal Power Meter	9/9/2009	Annual	9/9/2010	8650319
Rohde & Schwarz	CMU200	Base Station Simulator	9/11/2009	Annual	9/11/2010	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	4/6/2009	Annual	4/6/2010	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	9/4/2009	Annual	9/4/2010	109892
Rohde & Schwarz	NRVD	Dual Channel Power Meter	8/20/2008	Biennial	8/20/2010	101695
Rohde & Schwarz	NRV-Z32	Peak Power Sensor (100uW-2W)	12/5/2008	Biennial	12/5/2010	100155
Rohde & Schwarz	NRV-Z33	Peak Power Sensor (1mW-20W)	12/5/2008	Biennial	12/5/2010	100004
SPEAG	D1450V2	1450 MHz SAR Dipole	5/20/2009	Biennial	5/20/2011	1025
SPEAG	D1765V2	1765 MHz SAR Dipole	5/19/2009	Biennial	5/19/2011	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	1/20/2009	Biennial	1/20/2011	502
SPEAG	D1900V2	1900 MHz SAR Dipole	8/18/2009	Biennial	8/18/2011	5d080
SPEAG	D2300V2	2300 MHz SAR Dipole	3/6/2008	Biennial	3/6/2010	1008
SPEAG	D2450V2	2450 MHz SAR Dipole	8/27/2009	Biennial	8/27/2011	719
SPEAG	D2450V2	2450 MHz SAR Dipole	1/8/2009	Biennial	1/8/2011	797
SPEAG	D2600V2	2600 MHz SAR Dipole	8/12/2009	Biennial	8/12/2011	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/19/2009	Biennial	8/19/2011	1007
SPEAG	D5GHzV2	5 GHz SAR Dipole	1/15/2009	Biennial	1/15/2011	1057
SPEAG	D835V2	835 MHz SAR Dipole	1/19/2009	Biennial	1/19/2011	4d047
SPEAG	D835V2	835 MHz SAR Dipole	8/24/2009	Biennial	8/24/2011	4d026
SPEAG	DAE3	Dasy Data Acquisition Electronics	10/17/2008	Annual	10/17/2009	455
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/14/2009	Annual	5/14/2010	704
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/25/2009	Annual	5/25/2010	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	1/21/2009	Annual	1/21/2010	649
SPEAG	ES3DV2	SAR Probe	9/18/2009	Annual	9/18/2010	3022
SPEAG	EX3DV4	SAR Probe	1/21/2009	Annual	1/21/2010	3550
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/21/2009	Annual	7/21/2010	859
SPEAG	D750V3	750 MHz Dipole	2/19/2009	Biennial	2/19/2011	1003
Rohde & Schwarz	CMU200	Base Station Simulator	6/12/2009	Annual	6/12/2010	836536/0005
Speag	ES3DV3	SAR Probe	4/15/2009	Annual	4/15/2010	3213
Speag	ES3DV3	SAR Probe	4/15/2009	Annual	4/15/2010	3209
Speag	D1640V2	1640 MHz Dipole	8/21/2008	Biennial	8/21/2010	321
Rohde & Schwarz	CMW500	LTE Base Station Simulator	8/25/2009	Annual	8/25/2010	100976

Notes:

The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Validation measurement is performed by PCTEST prior to SAR evaluation. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 40 of 43

16 CONCLUSION

16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28- 10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 41 of 43

17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [5] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 42 of 43

[17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.

[18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

[19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.

[20] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.

[21] FCC SAR Measurement Procedures for 3G Devices v2.0, October 2007

[22] SAR Measurement procedures for IEEE 802.11a/b/g rev 1.2, May 2007

[23] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.

[24] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002

[25] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 2, November 2005

[26] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 1999

[27] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas v01r05 #648474, September 2008

[28] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, Rev 1.1, January 2007

[29] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, #616217, v01r01, April 2008

[30] FCC SAR Measurement Requirements for 3 – 6 GHz Rev1.1, October 2006

[31] FCC Mobile Portable RF Exposure Procedure D01 v03r03, KDB 447498, Jan. 2009

[32] FCC SAR Procedures for Dongle Transmitters D02 v01, KDB 447498, Dec. 2008

[33] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.

FCC ID: ACJ9TGCF-U15		CERTIFICATION REPORT		Reviewed by: Quality Manager
Filename: 0909041657.ACJ	Test Dates: 08/11-12/2008 and 09/28-10/08/2009	EUT Type: Handheld PC with 802.11abgn with Bluetooth and WWAN		Page 43 of 43