



FCC RADIO TEST REPORT

FCC ID : ACJ9TGWL24B
Equipment : Radio Module
Brand Name : Panasonic
Model Name : WL24B
Applicant : Panasonic Corporation of North America
Two Riverfront Plaza, Newark, New Jersey,
07102-5490, USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Mar. 16, 2026 and testing was performed from Mar. 27, 2026 to May 06, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 Test Result	12
3.1 Maximum Conducted Output Power Measurement	12
3.2 Unwanted Emissions Measurement.....	13
3.3 Antenna Requirements.....	18
4 List of Measuring Equipment.....	19
5 Measurement Uncertainty	20
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission Test Result	
Appendix C. Duty Cycle Plots	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR572320-03E	01	Initial issue of report	May 22, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.403	6dB & 26dB Bandwidth	Pass	See Note
-	2.1049	99% Occupied Bandwidth	Pass	See Note
3.1	15.407(a)	Maximum Conducted Output Power	Pass	-
-	15.407(a)	Power Spectral Density	Pass	See Note
3.2	15.407(b)	Unwanted Emissions	Pass	9.55 dB under the limit at 73034 MHz
-	15.207	AC Conducted Emission	Pass	See Note
3.3	15.203	Antenna Requirement	Pass	-

Note:

- For host device, Radiated Spurious Emission is verified and complies with the limit in this test report.
- For host device, the Conducted Output Power is no difference after compared to module (Model: Panasonic WL24B)

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng
Report Producer: Yuri Huang

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax/be, Wi-Fi 5GHz 802.11a/n/ac/ax/be, Wi-Fi 6GHz 802.11ax/be		
Antenna Type WLAN: <Aux Ant. (Chain A)>: PIFA Antenna <Main Ant. (Chain B)>: PIFA Antenna		
Antenna information		
5725 MHz ~ 5850 MHz	Peak Gain (dBi)	Main Ant. (Chain B): 2.34 dBi Aux Ant. (Chain A): 1.91 dBi

Remark:

1. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
2. The product was installed into Personal Computer (Brand Name: Panasonic, Model Name: FZ-34 during test.

1.1.1 Antenna Directional Gain

<For CDD Mode>

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

	Chain	Chain	DG	DG	Power	PSD
	Port 0	Port 1	for	for	Limit	Limit
	Chain A	Chain B	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	1.91	2.34	2.34	5.14	0.00	0.00

Calculation example:

If a device has two antenna, $G_{ANT1} = 1.91$ dBi; $G_{ANT2} = 2.34$ dBi

Directional gain of power measurement = $\max(1.91, 2.34) + 0 = 2.34$ dBi

Directional gain of PSD derived from formula which is

$10 \times \log \{ \{ [10^{(1.91 \text{ dBi} / 20)} + 10^{(2.34 \text{ dBi} / 20)}]^2 \} / 2 \}$

= 5.14 dBi

Power and PSD limit reduction = Composite gain – 6 dBi, (min = 0)



1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW3786

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ FCC Part 15 Subpart E
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and Laptop /Tablet/Convertible mode and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Keyboard), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40 and 802.11be EHT40.
2. The above Frequency and Channel with "#" are 802.11ac VHT80 and 802.11ax HE80 and 802.11be EHT80.



2.2 Test Mode

The final test modes include the worst data rates for each modulation shown in the table below.

Single Mode

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0
802.11ax HE20(Covered by EHT20)	MCS0
802.11ax HE40(Covered by EHT40)	MCS0
802.11ax HE80(Covered by EHT80)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0


MIMO Mode

Modulation	Data Rate
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0
802.11ax HE20(Covered by EHT20)	MCS0
802.11ax HE40(Covered by EHT40)	MCS0
802.11ax HE80(Covered by EHT80)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0

Remark:

1. The detailed Radiated test modes are shown in Appendix B.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	ipod Earphone	Apple	A1285	Doc	N/A	unshielded, 1.2m



2.5 EUT Operation Test Setup

The RF test items, utility "DRTU.09489.24.10.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Maximum Conducted Output Power Measurement

3.1.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.1.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01

3.1.4 Test Setup



3.1.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.2.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading.
When there is no suspected emission found and the emission level is with at least 6 dB margin


against QP limit line, the position is marked as “-”.

7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies.


When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.2.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.2.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result came out very similar.

3.2.6 Test Result of Radiated Band Edges

Please refer to Appendix B.

3.2.7 Duty Cycle

Please refer to Appendix C.

3.2.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.3 Antenna Requirements

3.3.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.3.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-02294	1GHz~18GHz	Jun. 06, 2025	Apr.30 , 2026~ May.06 , 2026	Jun. 05, 2026	Radiation (03CH15-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Mar. 15, 2026	Apr.30 , 2026~ May.06 , 2026	Mar. 16, 2027	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	41912 & 05	30MHz~1GHz	Mar. 16, 2026	Apr.30 , 2026~ May.06 , 2026	Mar. 15, 2027	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1225	18GHz~40GHz	Jul. 02, 2025	Apr.30 , 2026~ May.06 , 2026	Jul. 01, 2026	Radiation (03CH15-HY)
Amplifier	EMEC	EM1G18G	060837	1GHz~18GHz	Feb. 11, 2026	Apr.30 , 2026~ May.06 , 2026	Feb. 10, 2027	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM01G18G	060802	1GHz~18GHz	Feb. 11, 2026	Apr.30 , 2026~ May.06 , 2026	Feb. 10, 2027	Radiation (03CH15-HY)
Preamplifier	EM Electronics	EM18G40G	060801	18GHz~40GHz	May. 26, 2025	Apr.30 , 2026~ May.06 , 2026	May. 25, 2026	Radiation (03CH15-HY)
Spectrum Analyzer	Keysight	N9010B	MY60241058	10Hz~44Gz	Jul. 15, 2025	Apr.30 , 2026~ May.06 , 2026	Jul. 14, 2026	Radiation (03CH15-HY)
EMI Test Reveiver	Keysight	N9038A(MXE)	MY54130085	20Hz~8.4GHz	Oct. 15, 2025	Apr.30 , 2026~ May.06 , 2026	Oct. 14, 2026	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Apr.30 , 2026~ May.06 , 2026	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Apr.30 , 2026~ May.06 , 2026	N/A	Radiation (03CH15-HY)
Software	Audix	E3_V9_230621	RK-002394	N/A	N/A	Apr.30 , 2026~ May.06 , 2026	N/A	Radiation (03CH15-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY519228/2, 803950/2,508 407/2E	30MHz~40GHz	Sep. 24, 2025	Apr.30 , 2026~ May.06 , 2026	Sep. 23, 2026	Radiation (03CH15-HY)
Hygrometer	TECPEL	DTM-302	SN2	N/A	Aug. 26, 2025	Apr.30 , 2026~ May.06 , 2026	Aug. 25, 2026	Radiation (03CH15-HY)
Filter	wright	WHKX8-5872. 5-6750-18000-40ST	SN6	6.75GHz High Pass Filter	Jun. 03, 2025	Apr.30 , 2026~ May.06 , 2026	Jun. 02, 2026	Radiation (03CH15-HY)
Filter	wright	WHKX6-7268- 9200-26500-40 CD	SN2	9GHz High Pass Filter	May. 21, 2025	Apr.30 , 2026~ May.06 , 2026	May. 20, 2026	Radiation (03CH15-HY)
Filter	wright	WLJ4-1000-15 30-6000-40ST	SN4	1.53GHz Low Pass Filter	Jun. 03, 2025	Apr.30 , 2026~ May.06 , 2026	Jun. 02, 2026	Radiation (03CH15-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Mar. 27, 2026 Apr. 07, 2026	Nov. 03, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Mar. 27, 2026 Apr. 07, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Mar. 27, 2026 Apr. 07, 2026	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900067 (BOX7)	N/A	Jul. 02, 2025	Mar. 27, 2026 Apr. 07, 2026	Jul. 01, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_240513	N/A	Conducted Other Test Item	N/A	Mar. 27, 2026 Apr. 07, 2026	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.9 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Cheng Huang	Temperature:	21~25	°C
Test Date:	2026/03/27~2026/04/07	Relative Humidity:	51~54	%

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B	
11a	6Mbps	1	149	5745	8.59	8.50		30.00	30.00	1.91	2.34	Pass
11a	6Mbps	1	157	5785	8.37	8.62		30.00	30.00	1.91	2.34	Pass
11a	6Mbps	1	165	5825	8.55	8.41		30.00	30.00	1.91	2.34	Pass
HT20	MCS0	1	149	5745	8.23	8.13		30.00	30.00	1.91	2.34	Pass
HT20	MCS0	1	157	5785	8.51	8.22		30.00	30.00	1.91	2.34	Pass
HT20	MCS0	1	165	5825	8.14	8.52		30.00	30.00	1.91	2.34	Pass
HT40	MCS0	1	151	5755	8.19	8.50		30.00	30.00	1.91	2.34	Pass
HT40	MCS0	1	159	5795	8.35	8.19		30.00	30.00	1.91	2.34	Pass
VHT20	MCS0	1	149	5745	8.33	8.23		30.00	30.00	1.91	2.34	Pass
VHT20	MCS0	1	157	5785	8.61	8.32		30.00	30.00	1.91	2.34	Pass
VHT20	MCS0	1	165	5825	8.24	8.62		30.00	30.00	1.91	2.34	Pass
VHT40	MCS0	1	151	5755	8.29	8.60		30.00	30.00	1.91	2.34	Pass
VHT40	MCS0	1	159	5795	8.45	8.29		30.00	30.00	1.91	2.34	Pass
VHT80	MCS0	1	155	5775	8.15	8.45		30.00	30.00	1.91	2.34	Pass

Power Setting	
Chain A	Chain B
9	8.5
9	9
9	8.5
9	8.5
9.5	9
9	9
9	9
9.5	9
9	8.5
9.5	9
9	9
9	9
9.5	9
9	9

U-NII-3 MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B	
HT20	MCS0	2	149	5745	8.18	8.54	11.37	30.00		2.34		Pass
HT20	MCS0	2	157	5785	7.93	8.14	11.05	30.00		2.34		Pass
HT20	MCS0	2	165	5825	8.17	8.48	11.34	30.00		2.34		Pass
HT40	MCS0	2	151	5755	8.15	8.32	11.25	30.00		2.34		Pass
HT40	MCS0	2	159	5795	7.78	8.14	10.97	30.00		2.34		Pass
VHT20	MCS0	2	149	5745	8.28	8.64	11.47	30.00		2.34		Pass
VHT20	MCS0	2	157	5785	8.03	8.24	11.15	30.00		2.34		Pass
VHT20	MCS0	2	165	5825	8.27	8.58	11.44	30.00		2.34		Pass
VHT40	MCS0	2	151	5755	8.25	8.52	11.40	30.00		2.34		Pass
VHT40	MCS0	2	159	5795	7.88	8.24	11.07	30.00		2.34		Pass
VHT80	MCS0	2	155	5775	7.96	8.24	11.11	30.00		2.34		Pass

Power Setting	
Chain A	Chain B
9	
9	
9	
9	
9	
9	
9	
9	
9	
9	
9	

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna														
Mod.	Data Rate	NT	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
							Chain B	Chain A	Chain B	SUM	Chain A	Chain B	Chain A	
EHT20	MCS0	1	149	5745	Full	0.06	8.43	8.33		30.00	30.00	1.91	2.34	Pass
EHT20	MCS0	1	157	5785	Full	0.06	8.71	8.42		30.00	30.00	1.91	2.34	Pass
EHT20	MCS0	1	165	5825	Full	0.06	8.34	8.72		30.00	30.00	1.91	2.34	Pass
EHT40	MCS0	1	151	5755	Full	0.05	8.39	8.70		30.00	30.00	1.91	2.34	Pass
EHT40	MCS0	1	159	5795	Full	0.05	8.55	8.39		30.00	30.00	1.91	2.34	Pass
EHT80	MCS0	1	155	5775	Full	0.05	8.25	8.55		30.00	30.00	1.91	2.34	Pass

Power Setting		Restriction
Chain A	Chain B	
9	8.5	Target
9.5	9	Target
9	9	Target
9	9	Target
9.5	9	Target
9	9	Target

U-NII-3 MIMO														
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
							Chain B	Chain A	Chain B	SUM	Chain A	Chain B	Chain A	
EHT20	MCS0	2	149	5745	Full	0.05	8.38	8.74	11.57	30.00		2.34		Pass
EHT20	MCS0	2	157	5785	Full	0.05	8.13	8.34	11.25	30.00		2.34		Pass
EHT20	MCS0	2	165	5825	Full	0.05	8.37	8.68	11.54	30.00		2.34		Pass
EHT40	MCS0	2	151	5755	Full	0.05	8.35	8.62	11.50	30.00		2.34		Pass
EHT40	MCS0	2	159	5795	Full	0.05	7.98	8.34	11.17	30.00		2.34		Pass
EHT80	MCS0	2	155	5775	Full	0.05	8.06	8.34	11.21	30.00		2.34		Pass

Power Setting		Restriction
Chain A	Chain B	
9		Target
9		Target
9		Target
9		Target
9		Target
9		Target



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Sam Pan, Quentin Liu, Bigshow Wang	Temperature :	21.6 ~ 21.9°C
		Relative Humidity :	56 ~ 59 %

Note symbol

-L	Low channel location
-R	High channel location



B1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 13	U-NII-3	5.725-5.85	Chain A	802.11a	149	5745	6Mbps	-	-
Mode 14	U-NII-3	5.725-5.85	Chain B	802.11a	149	5745	6Mbps	-	-
Mode 15	U-NII-3	5.725-5.85	Chain A+B	802.11be EHT20	157	5785	MCS0	Full RU	-
Mode 16	U-NII-3	5.725-5.85	Chain A+B	802.11be EHT20	165	5825	MCS0	Full RU	-
Mode 17	U-NII-3	5.725-5.85	Chain A+B	802.11be EHT80	155	5775	MCS0	Full RU	-
Mode 99	U-NII-3	5.725-5.85	Chain A+B	802.11be EHT80	155	5775	MCS0	Full RU	LF
Mode 100	U-NII-3	5.725-5.85	Chain A+B	802.11be EHT80	155	5775	MCS0	Full RU	SHF

**B2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
13	802.11a	149	5639.99	52.75	68.20	-15.45	H	Peak	Pass	-	Band Edge
	802.11a	149	17235.00	47.76	68.20	-20.44	H	Peak	Pass	-	Harmonic
14	802.11a	149	5637.51	52.15	68.20	-16.05	V	Peak	Pass	-	Band Edge
	802.11a	149	17235.00	46.37	68.20	-21.83	H	Peak	Pass	-	Harmonic
15	802.11be EHT20	157	-	-	-	-	-	-	-	Full RU	Band Edge
	802.11be EHT20	157	17355.00	45.81	68.20	-22.39	V	Peak	Pass	Full RU	Harmonic
16	802.11be EHT20	165	5929.35	52.77	68.20	-15.43	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT20	165	-	-	-	-	-	-	-	Full RU	Harmonic
17	802.11be EHT80	155	5930.65	53.88	68.20	-14.32	H	Peak	Pass	Full RU	Band Edge
	802.11be EHT80	155	-	-	-	-	-	-	-	Full RU	Harmonic



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
99	LF	155	730.34	36.45	46.00	-9.55	V	Peak	Pass	-	LF
100	SHF	155	23100.00	33.59	54.00	-20.41	H	Avg.	Pass	-	SHF



Mode	13																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																										
ANT	Chain A																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5639.99</td><td>52.75</td><td>68.20</td><td>-15.45</td><td>43.24</td><td>33.14</td><td>13.24</td><td>36.87</td><td>0.00</td><td>300</td><td>85</td><td>Peak</td></tr><tr><td>2</td><td>5650.22</td><td>50.48</td><td>68.36</td><td>-17.88</td><td>40.90</td><td>33.20</td><td>13.25</td><td>36.87</td><td>0.00</td><td>300</td><td>85</td><td>Peak</td></tr><tr><td>3</td><td>5700.13</td><td>51.46</td><td>105.24</td><td>-53.78</td><td>41.29</td><td>33.70</td><td>13.33</td><td>36.86</td><td>0.00</td><td>300</td><td>85</td><td>Peak</td></tr><tr><td>4</td><td>5720.13</td><td>51.63</td><td>111.09</td><td>-59.46</td><td>41.36</td><td>33.78</td><td>13.35</td><td>36.86</td><td>0.00</td><td>300</td><td>85</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5639.99	52.75	68.20	-15.45	43.24	33.14	13.24	36.87	0.00	300	85	Peak	2	5650.22	50.48	68.36	-17.88	40.90	33.20	13.25	36.87	0.00	300	85	Peak	3	5700.13	51.46	105.24	-53.78	41.29	33.70	13.33	36.86	0.00	300	85	Peak	4	5720.13	51.63	111.09	-59.46	41.36	33.78	13.35	36.86	0.00	300	85	Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>103.57</td><td>-----</td><td>-----</td><td>93.19</td><td>33.86</td><td>13.38</td><td>36.86</td><td>0.00</td><td>300</td><td>85</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	103.57	-----	-----	93.19	33.86	13.38	36.86	0.00	300	85	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5639.99	52.75	68.20	-15.45	43.24	33.14	13.24	36.87	0.00	300	85	Peak																																																																																																																															
2	5650.22	50.48	68.36	-17.88	40.90	33.20	13.25	36.87	0.00	300	85	Peak																																																																																																																															
3	5700.13	51.46	105.24	-53.78	41.29	33.70	13.33	36.86	0.00	300	85	Peak																																																																																																																															
4	5720.13	51.63	111.09	-59.46	41.36	33.78	13.35	36.86	0.00	300	85	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	103.57	-----	-----	93.19	33.86	13.38	36.86	0.00	300	85	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>95.04</td><td>-----</td><td>-----</td><td>84.66</td><td>33.86</td><td>13.38</td><td>36.86</td><td>0.00</td><td>300</td><td>85</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	95.04	-----	-----	84.66	33.86	13.38	36.86	0.00	300	85	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	95.04	-----	-----	84.66	33.86	13.38	36.86	0.00	300	85	Average																																																																																																																															







Mode	13																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																										
ANT	Chain A																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-04-30 PEAK_BE(B4)_16-24 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5617.05</td><td>51.82</td><td>68.20</td><td>-16.38</td><td>42.50</td><td>33.00</td><td>13.20</td><td>36.88</td><td>0.00</td><td>392</td><td>197</td><td>Peak</td></tr><tr><td>2</td><td>5651.62</td><td>51.56</td><td>69.40</td><td>-17.84</td><td>41.96</td><td>33.22</td><td>13.25</td><td>36.87</td><td>0.00</td><td>392</td><td>197</td><td>Peak</td></tr><tr><td>3</td><td>5700.91</td><td>50.98</td><td>105.45</td><td>-54.47</td><td>40.81</td><td>33.70</td><td>13.33</td><td>36.86</td><td>0.00</td><td>392</td><td>197</td><td>Peak</td></tr><tr><td>4</td><td>5720.28</td><td>49.78</td><td>111.44</td><td>-61.66</td><td>39.51</td><td>33.78</td><td>13.35</td><td>36.86</td><td>0.00</td><td>392</td><td>197</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5617.05	51.82	68.20	-16.38	42.50	33.00	13.20	36.88	0.00	392	197	Peak	2	5651.62	51.56	69.40	-17.84	41.96	33.22	13.25	36.87	0.00	392	197	Peak	3	5700.91	50.98	105.45	-54.47	40.81	33.70	13.33	36.86	0.00	392	197	Peak	4	5720.28	49.78	111.44	-61.66	39.51	33.78	13.35	36.86	0.00	392	197	Peak	Level (dBuV/m) Date: 2026-04-30 PEAK(UNI) Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>101.20</td><td>-----</td><td>-----</td><td>90.79</td><td>33.88</td><td>13.39</td><td>36.86</td><td>0.00</td><td>392</td><td>197</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	101.20	-----	-----	90.79	33.88	13.39	36.86	0.00	392	197	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5617.05	51.82	68.20	-16.38	42.50	33.00	13.20	36.88	0.00	392	197	Peak																																																																																																																															
2	5651.62	51.56	69.40	-17.84	41.96	33.22	13.25	36.87	0.00	392	197	Peak																																																																																																																															
3	5700.91	50.98	105.45	-54.47	40.81	33.70	13.33	36.86	0.00	392	197	Peak																																																																																																																															
4	5720.28	49.78	111.44	-61.66	39.51	33.78	13.35	36.86	0.00	392	197	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	101.20	-----	-----	90.79	33.88	13.39	36.86	0.00	392	197	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 AVG_54 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>93.49</td><td>-----</td><td>-----</td><td>83.11</td><td>33.86</td><td>13.38</td><td>36.86</td><td>0.00</td><td>392</td><td>197</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	93.49	-----	-----	83.11	33.86	13.38	36.86	0.00	392	197	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5745.00	93.49	-----	-----	83.11	33.86	13.38	36.86	0.00	392	197	Average																																																																																																																															



Mode	13																																																																																																									
	Harmonic																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																									
ANT	Chain A																																																																																																									
Pol.	Horizontal	Vertical																																																																																																								
Peak Avg	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11490.00</td><td>47.99</td><td>74.00</td><td>-26.01</td><td>47.10</td><td>39.01</td><td>19.33</td><td>58.03</td><td>0.58</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17235.00</td><td>47.76</td><td>68.20</td><td>-20.44</td><td>45.01</td><td>38.44</td><td>23.89</td><td>60.02</td><td>0.44</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11490.00	47.99	74.00	-26.01	47.10	39.01	19.33	58.03	0.58	--	--	Peak	2	17235.00	47.76	68.20	-20.44	45.01	38.44	23.89	60.02	0.44	--	--	Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>11490.00</td><td>47.33</td><td>74.00</td><td>-26.67</td><td>46.44</td><td>39.01</td><td>19.33</td><td>58.03</td><td>0.58</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>17235.00</td><td>46.93</td><td>68.20</td><td>-21.27</td><td>44.18</td><td>38.44</td><td>23.89</td><td>60.02</td><td>0.44</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	11490.00	47.33	74.00	-26.67	46.44	39.01	19.33	58.03	0.58	--	--	Peak	2	17235.00	46.93	68.20	-21.27	44.18	38.44	23.89	60.02	0.44	--	--	Peak
		Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																															
1	11490.00	47.99	74.00	-26.01	47.10	39.01	19.33	58.03	0.58	--	--	Peak																																																																																														
2	17235.00	47.76	68.20	-20.44	45.01	38.44	23.89	60.02	0.44	--	--	Peak																																																																																														
	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																															
1	11490.00	47.33	74.00	-26.67	46.44	39.01	19.33	58.03	0.58	--	--	Peak																																																																																														
2	17235.00	46.93	68.20	-21.27	44.18	38.44	23.89	60.02	0.44	--	--	Peak																																																																																														



Mode	13	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Chain A	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL



Mode	14																																																																																																																																					
	Band Edge																																																																																																																																					
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																					
ANT	Chain B																																																																																																																																					
Pol.	Horizontal						Fundamental																																																																																																																															
Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5633.33</td><td>51.19</td><td>68.20</td><td>-17.01</td><td>41.74</td><td>33.10</td><td>13.23</td><td>36.88</td><td>0.00</td><td>400</td><td>256 Peak</td></tr><tr><td>2</td><td>5650.38</td><td>49.86</td><td>68.48</td><td>-18.62</td><td>40.28</td><td>33.20</td><td>13.25</td><td>36.87</td><td>0.00</td><td>400</td><td>256 Peak</td></tr><tr><td>3</td><td>5700.91</td><td>50.83</td><td>105.45</td><td>-54.62</td><td>40.66</td><td>33.70</td><td>13.33</td><td>36.86</td><td>0.00</td><td>400</td><td>256 Peak</td></tr><tr><td>4</td><td>5720.28</td><td>49.65</td><td>111.44</td><td>-61.79</td><td>39.38</td><td>33.78</td><td>13.35</td><td>36.86</td><td>0.00</td><td>400</td><td>256 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5633.33	51.19	68.20	-17.01	41.74	33.10	13.23	36.88	0.00	400	256 Peak	2	5650.38	49.86	68.48	-18.62	40.28	33.20	13.25	36.87	0.00	400	256 Peak	3	5700.91	50.83	105.45	-54.62	40.66	33.70	13.33	36.86	0.00	400	256 Peak	4	5720.28	49.65	111.44	-61.79	39.38	33.78	13.35	36.86	0.00	400	256 Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>90.09</td><td>-----</td><td>-----</td><td>79.63</td><td>33.91</td><td>13.40</td><td>36.85</td><td>0.00</td><td>400</td><td>256 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	90.09	-----	-----	79.63	33.91	13.40	36.85	0.00	400	256 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5633.33	51.19	68.20	-17.01	41.74	33.10	13.23	36.88	0.00	400	256 Peak																																																																																																																											
2	5650.38	49.86	68.48	-18.62	40.28	33.20	13.25	36.87	0.00	400	256 Peak																																																																																																																											
3	5700.91	50.83	105.45	-54.62	40.66	33.70	13.33	36.86	0.00	400	256 Peak																																																																																																																											
4	5720.28	49.65	111.44	-61.79	39.38	33.78	13.35	36.86	0.00	400	256 Peak																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5745.00	90.09	-----	-----	79.63	33.91	13.40	36.85	0.00	400	256 Peak																																																																																																																											
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>82.42</td><td>-----</td><td>-----</td><td>71.96</td><td>33.91</td><td>13.40</td><td>36.85</td><td>0.00</td><td>400</td><td>256 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	82.42	-----	-----	71.96	33.91	13.40	36.85	0.00	400	256 Average																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5745.00	82.42	-----	-----	71.96	33.91	13.40	36.85	0.00	400	256 Average																																																																																																																											







	14																																																																																																																																					
Mode	Band Edge																																																																																																																																					
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																					
ANT	Chain B																																																																																																																																					
Pol.	Vertical						Fundamental																																																																																																																															
Peak	Level (dBuV/m) Date: 2026-04-30 PEAK_BE(B4)_16-24 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5637.51</td><td>52.15</td><td>68.20</td><td>-16.05</td><td>42.67</td><td>33.13</td><td>13.23</td><td>36.88</td><td>0.00</td><td>300</td><td>342 Peak</td></tr><tr><td>2</td><td>5650.07</td><td>51.36</td><td>68.25</td><td>-16.89</td><td>41.78</td><td>33.20</td><td>13.25</td><td>36.87</td><td>0.00</td><td>300</td><td>342 Peak</td></tr><tr><td>3</td><td>5703.00</td><td>52.11</td><td>106.06</td><td>-53.95</td><td>41.93</td><td>33.71</td><td>13.33</td><td>36.86</td><td>0.00</td><td>300</td><td>342 Peak</td></tr><tr><td>4</td><td>5720.13</td><td>49.81</td><td>111.09</td><td>-61.28</td><td>39.54</td><td>33.78</td><td>13.35</td><td>36.86</td><td>0.00</td><td>300</td><td>342 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5637.51	52.15	68.20	-16.05	42.67	33.13	13.23	36.88	0.00	300	342 Peak	2	5650.07	51.36	68.25	-16.89	41.78	33.20	13.25	36.87	0.00	300	342 Peak	3	5703.00	52.11	106.06	-53.95	41.93	33.71	13.33	36.86	0.00	300	342 Peak	4	5720.13	49.81	111.09	-61.28	39.54	33.78	13.35	36.86	0.00	300	342 Peak	Level (dBuV/m) Date: 2026-04-30 PEAK(UNI) Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>87.06</td><td>-----</td><td>-----</td><td>76.65</td><td>33.88</td><td>13.39</td><td>36.86</td><td>0.00</td><td>300</td><td>342 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	87.06	-----	-----	76.65	33.88	13.39	36.86	0.00	300	342 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5637.51	52.15	68.20	-16.05	42.67	33.13	13.23	36.88	0.00	300	342 Peak																																																																																																																											
2	5650.07	51.36	68.25	-16.89	41.78	33.20	13.25	36.87	0.00	300	342 Peak																																																																																																																											
3	5703.00	52.11	106.06	-53.95	41.93	33.71	13.33	36.86	0.00	300	342 Peak																																																																																																																											
4	5720.13	49.81	111.09	-61.28	39.54	33.78	13.35	36.86	0.00	300	342 Peak																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5745.00	87.06	-----	-----	76.65	33.88	13.39	36.86	0.00	300	342 Peak																																																																																																																											
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 AVG_54 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:0.510kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5745.00</td><td>79.07</td><td>-----</td><td>-----</td><td>68.69</td><td>33.86</td><td>13.38</td><td>36.86</td><td>0.00</td><td>300</td><td>342 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	79.07	-----	-----	68.69	33.86	13.38	36.86	0.00	300	342 Average																																																																															
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5745.00	79.07	-----	-----	68.69	33.86	13.38	36.86	0.00	300	342 Average																																																																																																																											



Mode	14																																																																																																			
	Harmonic																																																																																																			
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																			
ANT	Chain B																																																																																																			
Pol.	Horizontal	Vertical																																																																																																		
Peak Avg	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 HORIZONTAL <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11490.00</td><td>45.85</td><td>74.00</td><td>-28.15</td><td>44.96</td><td>39.01</td><td>19.33</td><td>58.03</td><td>0.58</td><td>-- -- Peak</td></tr><tr><td>2 17235.00</td><td>46.37</td><td>68.20</td><td>-21.83</td><td>43.62</td><td>38.44</td><td>23.89</td><td>60.02</td><td>0.44</td><td>-- -- Peak</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11490.00	45.85	74.00	-28.15	44.96	39.01	19.33	58.03	0.58	-- -- Peak	2 17235.00	46.37	68.20	-21.83	43.62	38.44	23.89	60.02	0.44	-- -- Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 VERTICAL <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11490.00</td><td>46.14</td><td>74.00</td><td>-27.86</td><td>45.25</td><td>39.01</td><td>19.33</td><td>58.03</td><td>0.58</td><td>-- -- Peak</td></tr><tr><td>2 17235.00</td><td>45.94</td><td>68.20</td><td>-22.26</td><td>43.19</td><td>38.44</td><td>23.89</td><td>60.02</td><td>0.44</td><td>-- -- Peak</td></tr></table>	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11490.00	46.14	74.00	-27.86	45.25	39.01	19.33	58.03	0.58	-- -- Peak	2 17235.00	45.94	68.20	-22.26	43.19	38.44	23.89	60.02	0.44	-- -- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																											
1 11490.00	45.85	74.00	-28.15	44.96	39.01	19.33	58.03	0.58	-- -- Peak																																																																																											
2 17235.00	46.37	68.20	-21.83	43.62	38.44	23.89	60.02	0.44	-- -- Peak																																																																																											
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																											
1 11490.00	46.14	74.00	-27.86	45.25	39.01	19.33	58.03	0.58	-- -- Peak																																																																																											
2 17235.00	45.94	68.20	-22.26	43.19	38.44	23.89	60.02	0.44	-- -- Peak																																																																																											



Mode	14	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	Chain B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30  Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL



Mode	15																																																																																									
	Harmonic																																																																																									
	U-NII-3_5.725-5.85_802.11be EHT20_CH157_Full RU_5785MHz																																																																																									
ANT	Chain A+B																																																																																									
Pol.	Horizontal	Vertical																																																																																								
Peak Avg	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 HORIZONTAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11570.00</td><td>47.02</td><td>74.00</td><td>-26.98</td><td>46.30</td><td>38.72</td><td>19.40</td><td>57.97</td><td>0.57</td><td>--</td><td>-- Peak</td></tr><tr><td>2 17355.00</td><td>45.31</td><td>68.20</td><td>-22.89</td><td>42.27</td><td>38.67</td><td>23.97</td><td>60.04</td><td>0.44</td><td>--</td><td>-- Peak</td></tr></table>	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11570.00	47.02	74.00	-26.98	46.30	38.72	19.40	57.97	0.57	--	-- Peak	2 17355.00	45.31	68.20	-22.89	42.27	38.67	23.97	60.04	0.44	--	-- Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNII) 3m 91280-02294_250606 VERTICAL <table><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11570.00</td><td>44.63</td><td>74.00</td><td>-29.37</td><td>43.91</td><td>38.72</td><td>19.40</td><td>57.97</td><td>0.57</td><td>--</td><td>-- Peak</td></tr><tr><td>2 17355.00</td><td>45.81</td><td>68.20</td><td>-22.39</td><td>42.77</td><td>38.67</td><td>23.97</td><td>60.04</td><td>0.44</td><td>--</td><td>-- Peak</td></tr></table>	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11570.00	44.63	74.00	-29.37	43.91	38.72	19.40	57.97	0.57	--	-- Peak	2 17355.00	45.81	68.20	-22.39	42.77	38.67	23.97	60.04	0.44	--	-- Peak
	Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1 11570.00	47.02	74.00	-26.98	46.30	38.72	19.40	57.97	0.57	--	-- Peak																																																																																
2 17355.00	45.31	68.20	-22.89	42.27	38.67	23.97	60.04	0.44	--	-- Peak																																																																																
Freq	Level	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																
1 11570.00	44.63	74.00	-29.37	43.91	38.72	19.40	57.97	0.57	--	-- Peak																																																																																
2 17355.00	45.81	68.20	-22.39	42.77	38.67	23.97	60.04	0.44	--	-- Peak																																																																																



Mode	15	
	Harmonic	
	U-NII-3_5.725-5.85_802.11be EHT20_CH157_Full RU_5785MHz	
ANT	Chain A+B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL
	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 HORIZONTAL	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91280-02294_250606 VERTICAL



Mode	16																																																																																																																																				
	Band Edge																																																																																																																																				
	U-NII-3_5.725-5.85_802.11be EHT20_CH165_Full RU_5825MHz																																																																																																																																				
ANT	Chain A+B																																																																																																																																				
Pol.	Horizontal						Fundamental																																																																																																																														
Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.96</td><td>49.77</td><td>110.89</td><td>-61.12</td><td>38.92</td><td>34.12</td><td>13.57</td><td>36.84</td><td>0.00</td><td>300</td><td>111 Peak</td></tr><tr><td>2</td><td>5874.00</td><td>51.72</td><td>105.48</td><td>-53.76</td><td>40.74</td><td>34.20</td><td>13.61</td><td>36.83</td><td>0.00</td><td>300</td><td>111 Peak</td></tr><tr><td>3</td><td>5924.49</td><td>51.22</td><td>68.58</td><td>-17.36</td><td>40.09</td><td>34.25</td><td>13.70</td><td>36.82</td><td>0.00</td><td>300</td><td>111 Peak</td></tr><tr><td>4</td><td>5929.35</td><td>52.77</td><td>68.20</td><td>-15.43</td><td>41.64</td><td>34.24</td><td>13.71</td><td>36.82</td><td>0.00</td><td>300</td><td>111 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.96	49.77	110.89	-61.12	38.92	34.12	13.57	36.84	0.00	300	111 Peak	2	5874.00	51.72	105.48	-53.76	40.74	34.20	13.61	36.83	0.00	300	111 Peak	3	5924.49	51.22	68.58	-17.36	40.09	34.25	13.70	36.82	0.00	300	111 Peak	4	5929.35	52.77	68.20	-15.43	41.64	34.24	13.71	36.82	0.00	300	111 Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>98.23</td><td>-----</td><td>-----</td><td>87.46</td><td>34.10</td><td>13.51</td><td>36.84</td><td>0.00</td><td>300</td><td>111 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	98.23	-----	-----	87.46	34.10	13.51	36.84	0.00	300	111 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5854.96	49.77	110.89	-61.12	38.92	34.12	13.57	36.84	0.00	300	111 Peak																																																																																																																										
2	5874.00	51.72	105.48	-53.76	40.74	34.20	13.61	36.83	0.00	300	111 Peak																																																																																																																										
3	5924.49	51.22	68.58	-17.36	40.09	34.25	13.70	36.82	0.00	300	111 Peak																																																																																																																										
4	5929.35	52.77	68.20	-15.43	41.64	34.24	13.71	36.82	0.00	300	111 Peak																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5825.00	98.23	-----	-----	87.46	34.10	13.51	36.84	0.00	300	111 Peak																																																																																																																										
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>91.44</td><td>-----</td><td>-----</td><td>80.67</td><td>34.10</td><td>13.51</td><td>36.84</td><td>0.00</td><td>300</td><td>111 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	91.44	-----	-----	80.67	34.10	13.51	36.84	0.00	300	111 Average																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5825.00	91.44	-----	-----	80.67	34.10	13.51	36.84	0.00	300	111 Average																																																																																																																										



Mode	16																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11be EHT20_CH165_Full RU_5825MHz																																																																																																																																										
ANT	Chain A+B																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.96</td><td>49.50</td><td>110.89</td><td>-61.39</td><td>38.65</td><td>34.12</td><td>13.57</td><td>36.84</td><td>0.00</td><td>338</td><td>360</td><td>Peak</td></tr><tr><td>2</td><td>5873.86</td><td>51.48</td><td>105.52</td><td>-54.04</td><td>40.50</td><td>34.20</td><td>13.61</td><td>36.83</td><td>0.00</td><td>338</td><td>360</td><td>Peak</td></tr><tr><td>3</td><td>5924.49</td><td>50.72</td><td>68.58</td><td>-17.86</td><td>39.59</td><td>34.25</td><td>13.70</td><td>36.82</td><td>0.00</td><td>338</td><td>360</td><td>Peak</td></tr><tr><td>4</td><td>5932.59</td><td>52.01</td><td>68.20</td><td>-16.19</td><td>40.88</td><td>34.23</td><td>13.72</td><td>36.82</td><td>0.00</td><td>338</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.96	49.50	110.89	-61.39	38.65	34.12	13.57	36.84	0.00	338	360	Peak	2	5873.86	51.48	105.52	-54.04	40.50	34.20	13.61	36.83	0.00	338	360	Peak	3	5924.49	50.72	68.58	-17.86	39.59	34.25	13.70	36.82	0.00	338	360	Peak	4	5932.59	52.01	68.20	-16.19	40.88	34.23	13.72	36.82	0.00	338	360	Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>96.16</td><td>-----</td><td>-----</td><td>85.39</td><td>34.10</td><td>13.51</td><td>36.84</td><td>0.00</td><td>338</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	96.16	-----	-----	85.39	34.10	13.51	36.84	0.00	338	360	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5854.96	49.50	110.89	-61.39	38.65	34.12	13.57	36.84	0.00	338	360	Peak																																																																																																																															
2	5873.86	51.48	105.52	-54.04	40.50	34.20	13.61	36.83	0.00	338	360	Peak																																																																																																																															
3	5924.49	50.72	68.58	-17.86	39.59	34.25	13.70	36.82	0.00	338	360	Peak																																																																																																																															
4	5932.59	52.01	68.20	-16.19	40.88	34.23	13.72	36.82	0.00	338	360	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	96.16	-----	-----	85.39	34.10	13.51	36.84	0.00	338	360	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5825.00</td><td>88.45</td><td>-----</td><td>-----</td><td>77.66</td><td>34.10</td><td>13.53</td><td>36.84</td><td>0.00</td><td>338</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	88.45	-----	-----	77.66	34.10	13.53	36.84	0.00	338	360	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	88.45	-----	-----	77.66	34.10	13.53	36.84	0.00	338	360	Average																																																																																																																															



Mode	17																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																																																																										
ANT	Chain A+B																																																																																																																																										
Pol.	Horizontal						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5601.94</td><td>51.02</td><td>68.20</td><td>-17.18</td><td>41.81</td><td>32.91</td><td>13.18</td><td>36.88</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>2</td><td>5652.25</td><td>51.20</td><td>69.87</td><td>-18.67</td><td>41.59</td><td>33.22</td><td>13.26</td><td>36.87</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>3</td><td>5701.27</td><td>50.29</td><td>105.55</td><td>-55.26</td><td>40.11</td><td>33.71</td><td>13.33</td><td>36.86</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>4</td><td>5720.19</td><td>49.97</td><td>111.22</td><td>-61.25</td><td>39.70</td><td>33.78</td><td>13.35</td><td>36.86</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5601.94	51.02	68.20	-17.18	41.81	32.91	13.18	36.88	0.00	350	360	Peak	2	5652.25	51.20	69.87	-18.67	41.59	33.22	13.26	36.87	0.00	350	360	Peak	3	5701.27	50.29	105.55	-55.26	40.11	33.71	13.33	36.86	0.00	350	360	Peak	4	5720.19	49.97	111.22	-61.25	39.70	33.78	13.35	36.86	0.00	350	360	Peak	Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>91.68</td><td>-----</td><td>-----</td><td>81.19</td><td>33.93</td><td>13.41</td><td>36.85</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	91.68	-----	-----	81.19	33.93	13.41	36.85	0.00	350	360	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5601.94	51.02	68.20	-17.18	41.81	32.91	13.18	36.88	0.00	350	360	Peak																																																																																																																															
2	5652.25	51.20	69.87	-18.67	41.59	33.22	13.26	36.87	0.00	350	360	Peak																																																																																																																															
3	5701.27	50.29	105.55	-55.26	40.11	33.71	13.33	36.86	0.00	350	360	Peak																																																																																																																															
4	5720.19	49.97	111.22	-61.25	39.70	33.78	13.35	36.86	0.00	350	360	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	91.68	-----	-----	81.19	33.93	13.41	36.85	0.00	350	360	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>83.85</td><td>-----</td><td>-----</td><td>73.23</td><td>34.03</td><td>13.44</td><td>36.85</td><td>0.00</td><td>350</td><td>360</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	83.85	-----	-----	73.23	34.03	13.44	36.85	0.00	350	360	Average																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	83.85	-----	-----	73.23	34.03	13.44	36.85	0.00	350	360	Average																																																																																																																															




Mode	17																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																				
ANT	Chain A+B																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.97</td><td>50.81</td><td>110.87</td><td>-60.06</td><td>39.96</td><td>34.12</td><td>13.57</td><td>36.84</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>2</td><td>5874.32</td><td>51.88</td><td>105.39</td><td>-53.51</td><td>40.90</td><td>34.20</td><td>13.61</td><td>36.83</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>3</td><td>5924.63</td><td>50.53</td><td>68.47</td><td>-17.94</td><td>39.40</td><td>34.25</td><td>13.70</td><td>36.82</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr><tr><td>4</td><td>5930.65</td><td>53.88</td><td>68.20</td><td>-14.32</td><td>42.75</td><td>34.24</td><td>13.71</td><td>36.82</td><td>0.00</td><td>350</td><td>360</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.97	50.81	110.87	-60.06	39.96	34.12	13.57	36.84	0.00	350	360	Peak	2	5874.32	51.88	105.39	-53.51	40.90	34.20	13.61	36.83	0.00	350	360	Peak	3	5924.63	50.53	68.47	-17.94	39.40	34.25	13.70	36.82	0.00	350	360	Peak	4	5930.65	53.88	68.20	-14.32	42.75	34.24	13.71	36.82	0.00	350	360	Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.97	50.81	110.87	-60.06	39.96	34.12	13.57	36.84	0.00	350	360	Peak																																																																									
2	5874.32	51.88	105.39	-53.51	40.90	34.20	13.61	36.83	0.00	350	360	Peak																																																																									
3	5924.63	50.53	68.47	-17.94	39.40	34.25	13.70	36.82	0.00	350	360	Peak																																																																									
4	5930.65	53.88	68.20	-14.32	42.75	34.24	13.71	36.82	0.00	350	360	Peak																																																																									



Mode	17																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																																																																										
ANT	Chain A+B																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5643.65</td><td>51.80</td><td>68.20</td><td>-16.40</td><td>42.27</td><td>33.16</td><td>13.24</td><td>36.87</td><td>0.00</td><td>229</td><td>126</td><td>Peak</td></tr><tr><td>2</td><td>5650.53</td><td>49.48</td><td>68.59</td><td>-19.11</td><td>39.89</td><td>33.21</td><td>13.25</td><td>36.87</td><td>0.00</td><td>229</td><td>126</td><td>Peak</td></tr><tr><td>3</td><td>5700.41</td><td>52.07</td><td>105.31</td><td>-53.24</td><td>41.90</td><td>33.70</td><td>13.33</td><td>36.86</td><td>0.00</td><td>229</td><td>126</td><td>Peak</td></tr><tr><td>4</td><td>5728.83</td><td>52.73</td><td>112.69</td><td>-59.96</td><td>42.45</td><td>33.78</td><td>13.36</td><td>36.86</td><td>0.00</td><td>229</td><td>126</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5643.65	51.80	68.20	-16.40	42.27	33.16	13.24	36.87	0.00	229	126	Peak	2	5650.53	49.48	68.59	-19.11	39.89	33.21	13.25	36.87	0.00	229	126	Peak	3	5700.41	52.07	105.31	-53.24	41.90	33.70	13.33	36.86	0.00	229	126	Peak	4	5728.83	52.73	112.69	-59.96	42.45	33.78	13.36	36.86	0.00	229	126	Peak	Date: 2026-04-30 Site : 03CH15-HY Condition: PEAK(UNI) 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>93.09</td><td>-----</td><td>-----</td><td>82.53</td><td>33.98</td><td>13.43</td><td>36.85</td><td>0.00</td><td>229</td><td>126</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	93.09	-----	-----	82.53	33.98	13.43	36.85	0.00	229	126	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5643.65	51.80	68.20	-16.40	42.27	33.16	13.24	36.87	0.00	229	126	Peak																																																																																																																															
2	5650.53	49.48	68.59	-19.11	39.89	33.21	13.25	36.87	0.00	229	126	Peak																																																																																																																															
3	5700.41	52.07	105.31	-53.24	41.90	33.70	13.33	36.86	0.00	229	126	Peak																																																																																																																															
4	5728.83	52.73	112.69	-59.96	42.45	33.78	13.36	36.86	0.00	229	126	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	93.09	-----	-----	82.53	33.98	13.43	36.85	0.00	229	126	Peak																																																																																																																															
Avg	Blank						Date: 2026-04-30 Site : 03CH15-HY Condition: AVG_54 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>86.19</td><td>-----</td><td>-----</td><td>75.47</td><td>34.10</td><td>13.47</td><td>36.85</td><td>0.00</td><td>229</td><td>126</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	86.19	-----	-----	75.47	34.10	13.47	36.85	0.00	229	126	Average																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	86.19	-----	-----	75.47	34.10	13.47	36.85	0.00	229	126	Average																																																																																																																															



Mode	17																																																																																
	Band Edge - R																																																																																
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																
ANT	Chain A+B																																																																																
Pol.	Vertical	Fundamental																																																																															
Peak	Date: 2026-04-30  Site : 03CH15-HY Condition: PEAK_BE(B4)_16-24 3m 91200-02294_250606 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.33</td><td>51.49</td><td>112.34</td><td>-60.85</td><td>40.64</td><td>34.12</td><td>13.57</td><td>36.84</td><td>0.00</td><td>229</td><td>126 Peak</td></tr><tr><td>2</td><td>5874.97</td><td>50.56</td><td>105.21</td><td>-54.65</td><td>39.58</td><td>34.20</td><td>13.61</td><td>36.83</td><td>0.00</td><td>229</td><td>126 Peak</td></tr><tr><td>3</td><td>5924.05</td><td>50.48</td><td>68.31</td><td>-17.83</td><td>39.35</td><td>34.25</td><td>13.70</td><td>36.82</td><td>0.00</td><td>229</td><td>126 Peak</td></tr><tr><td>4</td><td>5939.68</td><td>51.89</td><td>68.20</td><td>-16.31</td><td>40.76</td><td>34.22</td><td>13.73</td><td>36.82</td><td>0.00</td><td>229</td><td>126 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.33	51.49	112.34	-60.85	40.64	34.12	13.57	36.84	0.00	229	126 Peak	2	5874.97	50.56	105.21	-54.65	39.58	34.20	13.61	36.83	0.00	229	126 Peak	3	5924.05	50.48	68.31	-17.83	39.35	34.25	13.70	36.82	0.00	229	126 Peak	4	5939.68	51.89	68.20	-16.31	40.76	34.22	13.73	36.82	0.00	229	126 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																							
1	5854.33	51.49	112.34	-60.85	40.64	34.12	13.57	36.84	0.00	229	126 Peak																																																																						
2	5874.97	50.56	105.21	-54.65	39.58	34.20	13.61	36.83	0.00	229	126 Peak																																																																						
3	5924.05	50.48	68.31	-17.83	39.35	34.25	13.70	36.82	0.00	229	126 Peak																																																																						
4	5939.68	51.89	68.20	-16.31	40.76	34.22	13.73	36.82	0.00	229	126 Peak																																																																						



Mode	99																																																																																																																																																																																																																																					
	LF																																																																																																																																																																																																																																					
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																																																																																																																																																																					
ANT	Chain A+B																																																																																																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																																																																																																															
QP/ Peak	Level (dBuV/m) Date: 2026-05-06 Site : 03CH15-HY Condition: QP 3m Bilog_41912 & 05_260318 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>87.23</td><td>21.72</td><td>40.00</td><td>-18.28</td><td>37.93</td><td>14.46</td><td>1.64</td><td>32.39</td><td>0.08</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>88.20</td><td>21.86</td><td>43.50</td><td>-21.64</td><td>37.98</td><td>14.54</td><td>1.65</td><td>32.39</td><td>0.08</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>230.79</td><td>28.98</td><td>46.00</td><td>-17.02</td><td>42.33</td><td>16.24</td><td>2.66</td><td>32.35</td><td>0.10</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>315.18</td><td>25.73</td><td>46.00</td><td>-20.27</td><td>35.49</td><td>19.25</td><td>3.11</td><td>32.29</td><td>0.17</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>707.06</td><td>35.79</td><td>46.00</td><td>-10.21</td><td>36.51</td><td>26.76</td><td>4.66</td><td>32.29</td><td>0.15</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>935.98</td><td>33.59</td><td>46.00</td><td>-12.41</td><td>28.91</td><td>30.21</td><td>5.33</td><td>31.17</td><td>0.31</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	87.23	21.72	40.00	-18.28	37.93	14.46	1.64	32.39	0.08	--	--	Peak	2	88.20	21.86	43.50	-21.64	37.98	14.54	1.65	32.39	0.08	--	--	Peak	3	230.79	28.98	46.00	-17.02	42.33	16.24	2.66	32.35	0.10	--	--	Peak	4	315.18	25.73	46.00	-20.27	35.49	19.25	3.11	32.29	0.17	--	--	Peak	5	707.06	35.79	46.00	-10.21	36.51	26.76	4.66	32.29	0.15	--	--	Peak	6	935.98	33.59	46.00	-12.41	28.91	30.21	5.33	31.17	0.31	--	--	Peak	Level (dBuV/m) Date: 2026-05-06 Site : 03CH15-HY Condition: QP 3m Bilog_41912 & 05_260318 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>42.61</td><td>23.10</td><td>40.00</td><td>-16.90</td><td>36.22</td><td>18.14</td><td>1.11</td><td>32.47</td><td>0.10</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>98.87</td><td>21.23</td><td>43.50</td><td>-22.27</td><td>35.99</td><td>15.79</td><td>1.76</td><td>32.41</td><td>0.10</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>230.79</td><td>28.04</td><td>46.00</td><td>-17.96</td><td>41.39</td><td>16.24</td><td>2.66</td><td>32.35</td><td>0.10</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>460.68</td><td>25.16</td><td>46.00</td><td>-20.84</td><td>30.51</td><td>23.13</td><td>3.76</td><td>32.34</td><td>0.10</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>730.34</td><td>36.45</td><td>46.00</td><td>-9.55</td><td>36.16</td><td>27.67</td><td>4.74</td><td>32.28</td><td>0.16</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>6</td><td>950.53</td><td>33.01</td><td>46.00</td><td>-12.99</td><td>27.40</td><td>30.91</td><td>5.38</td><td>31.04</td><td>0.36</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	42.61	23.10	40.00	-16.90	36.22	18.14	1.11	32.47	0.10	--	--	Peak	2	98.87	21.23	43.50	-22.27	35.99	15.79	1.76	32.41	0.10	--	--	Peak	3	230.79	28.04	46.00	-17.96	41.39	16.24	2.66	32.35	0.10	--	--	Peak	4	460.68	25.16	46.00	-20.84	30.51	23.13	3.76	32.34	0.10	--	--	Peak	5	730.34	36.45	46.00	-9.55	36.16	27.67	4.74	32.28	0.16	--	--	Peak	6	950.53	33.01	46.00	-12.99	27.40	30.91	5.38	31.04	0.36	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																												
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																												
1	87.23	21.72	40.00	-18.28	37.93	14.46	1.64	32.39	0.08	--	--	Peak																																																																																																																																																																																																																										
2	88.20	21.86	43.50	-21.64	37.98	14.54	1.65	32.39	0.08	--	--	Peak																																																																																																																																																																																																																										
3	230.79	28.98	46.00	-17.02	42.33	16.24	2.66	32.35	0.10	--	--	Peak																																																																																																																																																																																																																										
4	315.18	25.73	46.00	-20.27	35.49	19.25	3.11	32.29	0.17	--	--	Peak																																																																																																																																																																																																																										
5	707.06	35.79	46.00	-10.21	36.51	26.76	4.66	32.29	0.15	--	--	Peak																																																																																																																																																																																																																										
6	935.98	33.59	46.00	-12.41	28.91	30.21	5.33	31.17	0.31	--	--	Peak																																																																																																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																																																												
1	42.61	23.10	40.00	-16.90	36.22	18.14	1.11	32.47	0.10	--	--	Peak																																																																																																																																																																																																																										
2	98.87	21.23	43.50	-22.27	35.99	15.79	1.76	32.41	0.10	--	--	Peak																																																																																																																																																																																																																										
3	230.79	28.04	46.00	-17.96	41.39	16.24	2.66	32.35	0.10	--	--	Peak																																																																																																																																																																																																																										
4	460.68	25.16	46.00	-20.84	30.51	23.13	3.76	32.34	0.10	--	--	Peak																																																																																																																																																																																																																										
5	730.34	36.45	46.00	-9.55	36.16	27.67	4.74	32.28	0.16	--	--	Peak																																																																																																																																																																																																																										
6	950.53	33.01	46.00	-12.99	27.40	30.91	5.38	31.04	0.36	--	--	Peak																																																																																																																																																																																																																										




Mode	100																																																																																																																											
	SHF																																																																																																																											
	U-NII-3_5.725-5.85_802.11be EHT80_CH155_Full RU_5775MHz																																																																																																																											
ANT	Chain A+B																																																																																																																											
Pol.	Horizontal	Vertical																																																																																																																										
Peak	Level (dBuV/m) Date: 2026-05-06 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1224_250702 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>23100.00</td><td>43.06</td><td>74.00</td><td>-30.94</td><td>61.77</td><td>38.90</td><td>6.45</td><td>54.52</td><td>-9.54</td><td>150</td><td>21 Peak</td></tr><tr><td>2</td><td>23100.00</td><td>33.59</td><td>54.00</td><td>-20.41</td><td>52.30</td><td>38.90</td><td>6.45</td><td>54.52</td><td>-9.54</td><td>150</td><td>21 Average</td></tr><tr><td>3</td><td>39095.78</td><td>45.58</td><td>74.00</td><td>-28.42</td><td>58.99</td><td>44.68</td><td>8.27</td><td>56.82</td><td>-9.54</td><td>--</td><td>-- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	23100.00	43.06	74.00	-30.94	61.77	38.90	6.45	54.52	-9.54	150	21 Peak	2	23100.00	33.59	54.00	-20.41	52.30	38.90	6.45	54.52	-9.54	150	21 Average	3	39095.78	45.58	74.00	-28.42	58.99	44.68	8.27	56.82	-9.54	--	-- PEAK	Level (dBuV/m) Date: 2026-05-06 Site : 03CH15-HY Condition: PEAK(UNII) 1m SHF_1224_250702 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>25888.46</td><td>39.18</td><td>68.20</td><td>-29.02</td><td>55.86</td><td>39.50</td><td>6.60</td><td>53.24</td><td>-9.54</td><td>--</td><td>-- PEAK</td></tr><tr><td>2</td><td>38796.09</td><td>45.10</td><td>74.00</td><td>-28.90</td><td>58.87</td><td>44.46</td><td>8.29</td><td>56.98</td><td>-9.54</td><td>--</td><td>-- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	25888.46	39.18	68.20	-29.02	55.86	39.50	6.60	53.24	-9.54	--	-- PEAK	2	38796.09	45.10	74.00	-28.90	58.87	44.46	8.29	56.98	-9.54	--	-- PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	23100.00	43.06	74.00	-30.94	61.77	38.90	6.45	54.52	-9.54	150	21 Peak																																																																																																																	
2	23100.00	33.59	54.00	-20.41	52.30	38.90	6.45	54.52	-9.54	150	21 Average																																																																																																																	
3	39095.78	45.58	74.00	-28.42	58.99	44.68	8.27	56.82	-9.54	--	-- PEAK																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	25888.46	39.18	68.20	-29.02	55.86	39.50	6.60	53.24	-9.54	--	-- PEAK																																																																																																																	
2	38796.09	45.10	74.00	-28.90	58.87	44.46	8.29	56.98	-9.54	--	-- PEAK																																																																																																																	




Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Ant A	5GHz 802.11a	97.66	2090	0.48	510Hz
Ant B	5GHz 802.11a	97.65	2080	0.48	510Hz
Ant A+B	5GHz 802.11be EHT20 Full RU	98.76	3980	0.25	10Hz
Ant A+B	5GHz 802.11be EHT80 Full RU	98.88	3990	0.25	10Hz

<Ant. A>



<Ant. B>





MIMO <Ant. A+B>

