



FCC RADIO TEST REPORT

FCC ID : ACJ9TGWL24B
Equipment : Radio Module
Brand Name : Panasonic
Model Name : WL24B
Applicant : Panasonic Corporation of North America
Two Riverfront Plaza, Newark, New Jersey, 07102-5490, USA
Standard : FCC Part 15 Subpart E §15.407

The product was received on Jun. 16, 2026 and testing was performed from Jul. 02, 2026 to Aug. 13, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	7
1.3 Testing Location	7
1.4 Applicable Standards.....	7
2 Test Configuration of Equipment Under Test	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode.....	11
2.3 Connection Diagram of Test System.....	12
2.4 Support Unit used in test configuration and system	12
2.5 EUT Operation Test Setup	12
3 Test Result	13
3.1 Fundamental Maximum EIRP Measurement	13
3.2 Unwanted Emissions Measurement.....	14
3.3 Antenna Requirements.....	18
4 List of Measuring Equipment.....	19
5 Measurement Uncertainty	20
Appendix A. Conducted Test Results	
Appendix B. Radiated Spurious Emission Test Data	
Appendix C. Duty Cycle Plots	
Appendix D. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR612317-02G	01	Initial issue of report	Sep. 07, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
-	15.407(a)(11)	26dB Emission Bandwidth	Pass	See Note
-	2.1049	99% Occupied Bandwidth	Pass	See Note
3.1	15.407(a)	Fundamental Maximum EIRP	Pass	
-	15.407(a)	Fundamental Power Spectral Density	Pass	See Note
-	15.407(b)	In-Band Emissions (Channel Mask)	Pass	See Note
-	15.407(d)(6)	Contention Based Protocol	Pass	See Note
3.2	15.407(b)	Unwanted Emissions	Pass	6.24 dB under the limit at 7251.02 MHz
-	15.207	AC Conducted Emission	Pass	See Note
3.3	15.203	Antenna Requirement	Pass	-

Note:

- For host device, the spot check Radiated Spurious Emission and complies with the limit in this test report.
- For host device, the spot check Conducted Output Power is no difference after compared to module (Model: Panasonic WL24B).

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng
Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax/be, Wi-Fi 5GHz 802.11a/n/ac/ax/be, Wi-Fi 6GHz 802.11ax/be		
Antenna Type WLAN: <Aux Ant. (Chain A)>: Monopole Antenna <Main Ant. (Chain B)>: PIFA Antenna		
Antenna information for Directional Gain		
Aux Antenna (Chain A)	Peak Gain	U-NII-5 : 3.60 dBi U-NII-6 : 2.30 dBi U-NII-7 : 1.75 dBi U-NII-8 : 1.26 dBi
Main Antenna (Chain B)	Peak Gain	U-NII-5 : 4.68 dBi U-NII-6 : 4.60 dBi U-NII-7 : 3.58 dBi U-NII-8 : 3.66 dBi

Remark:

1. The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.
2. The product was installed into Personal Computer (Brand Name: Panasonic, Model Name: FZ-G3 during test

1.1.1 Antenna Directional Gain

Follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01 F2)f)ii)

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where $G_1, G_2, \dots, G_N$ denote single antenna gain.

The directional gain "DG" is calculated as following table.

	Chain	Chain	DG	DG
	Port 0	Port 1	for	for
	Chain A	Chain B	Power	PSD
	(dBi)	(dBi)	(dBi)	(dBi)
U-NII-5	3.60	4.68	4.68	7.17
U-NII-6	2.30	4.60	4.60	6.54
U-NII-7	1.75	3.58	3.58	5.72
U-NII-8	1.26	3.66	3.66	5.55

Calculation example:

If a device has two antenna, $G_{ANT1} = 3.60$ Bi; $G_{ANT2} = 4.68$ dBi

Directional gain of power measurement = $\max(3.60, 4.68) + 0 = 4.68$ dBi

Directional gain of PSD derived from formula which is

$$10 \times \log \left\{ \left[10^{(3.60 \text{ dBi} / 20)} + 10^{(4.68 \text{ dBi} / 20)} \right]^2 / 2 \right\}$$

$$= 7.17 \text{ dBi}$$

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
- ♦FCC KDB 987594 D02 U-NII 6 GHz EMC Measurement v03
- ♦FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦FCC KDB 662911 D01 Multiple Transmitter Output v02r01
- ♦ FCC Part 15 Subpart E
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

2.1 Carrier Frequency and Channel

BW 20M	Channel	1	5	9	13	17	21	25	29
	Freq. (MHz)	5955	5975	5995	6015	6035	6055	6075	6095
BW 40M	Channel	3		11		19		27	
	Freq. (MHz)	5965		6005		6045		6085	
BW 80M	Channel	7				23			
	Freq. (MHz)	5985				6065			
BW 160M	Channel	15							
	Freq. (MHz)	6025							
BW 320M	Channel	31							
	Freq. (MHz)	6105							

BW 20M	Channel	33	37	41	45	49	53	57	61
	Freq. (MHz)	6115	6135	6155	6175	6195	6215	6235	6255
BW 40M	Channel	35		43		51		59	
	Freq. (MHz)	6125		6165		6205		6245	
BW 80M	Channel	39				55			
	Freq. (MHz)	6145				6225			
BW 160M	Channel	47							
	Freq. (MHz)	6185							
BW 320M	Channel	63							
	Freq. (MHz)	6265							



BW 20M	Channel	65	69	73	77	81	85	89	93
	Freq. (MHz)	6275	6295	6315	6335	6355	6375	6395	6415
BW 40M	Channel	67		75		83		91	
	Freq. (MHz)	6285		6325		6365		6405	
BW 80M	Channel	71				87			
	Freq. (MHz)	6305				6385			
BW 160M	Channel	79							
	Freq. (MHz)	6345							
BW 320M	Channel	95							
	Freq. (MHz)	6425							

BW 20M	Channel	97	101	105	109	113	117	121	125
	Freq. (MHz)	6435	6455	6475	6495	6515	6535	6555	6575
BW 40M	Channel	99		107		115		123	
	Freq. (MHz)	6445		6485		6525		6565	
BW 80M	Channel	103				119			
	Freq. (MHz)	6465				6545			
BW 160M	Channel	111							
	Freq. (MHz)	6505							
BW 320M	Channel	127							
	Freq. (MHz)	6585							

BW 20M	Channel	129	133	137	141	145	149	153	157
	Freq. (MHz)	6595	6615	6635	6655	6675	6695	6715	6735
BW 40M	Channel	131		139		147		155	
	Freq. (MHz)	6605		6645		6685		6725	
BW 80M	Channel	135				151			
	Freq. (MHz)	6625				6705			
BW 160M	Channel	143							
	Freq. (MHz)	6665							
BW 320M	Channel	159							
	Freq. (MHz)	6745							



BW 20M	Channel	161	165	169	173	177	181	185	189
	Freq. (MHz)	6755	6775	6795	6815	6835	6855	6875	6895
BW 40M	Channel	163		171		179		187	
	Freq. (MHz)	6765		6805		6845		6885	
BW 80M	Channel	167				183			
	Freq. (MHz)	6785				6865			
BW 160M	Channel	175							
	Freq. (MHz)	6825							
BW 320M	Channel	191							
	Freq. (MHz)	6905							

BW 20M	Channel	193	197	201	205	209	213	217	221
	Freq. (MHz)	6915	6935	6955	6975	6995	7015	7035	7055
BW 40M	Channel	195		203		211		219	
	Freq. (MHz)	6925		6965		7005		7045	
BW 80M	Channel	199				215			
	Freq. (MHz)	6945				7025			
BW 160M	Channel	207							
	Freq. (MHz)	6985							

BW 20M	Channel	225	229
	Freq. (MHz)	7075	7095
BW 40M	Channel	227	
	Freq. (MHz)	7085	

BW 20M	Channel	233							
	Freq. (MHz)	7115							



2.2 Test Mode

The final test modes include the worst data rates for each modulation shown in the table below.

SISO Mode


Modulation	Data Rate
802.11ax HE20(Covered by EHT20)	MCS0
802.11ax HE40(Covered by EHT40)	MCS0
802.11ax HE80(Covered by EHT80)	MCS0
802.11ax HE160(Covered by EHT160)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0
802.11be EHT160	MCS0
802.11be EHT320	MCS0

MIMO Mode

Modulation	Data Rate
802.11ax HE20(Covered by EHT20)	MCS0
802.11ax HE40(Covered by EHT40)	MCS0
802.11ax HE80(Covered by EHT80)	MCS0
802.11ax HE160(Covered by EHT160)	MCS0
802.11be EHT20	MCS0
802.11be EHT40	MCS0
802.11be EHT80	MCS0
802.11be EHT160	MCS0
802.11be EHT320	MCS0

Remark: The detailed Radiated test modes are shown in Appendix B.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Earphone	SAMSUNG	SOUND BY AKG	N/A	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

The RF test items, utility "DRTU.10339.24.40.0" was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

3 Test Result

3.1 Fundamental Maximum EIRP Measurement

3.1.1 Limit of Fundamental Maximum EIRP

<FCC CFR 15.407>

(a)(8) For client devices operating under the control of an indoor access point in the 5.925-7.125 GHz bands, the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.1.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.1.4 Test Setup



3.1.5 Test Result of Fundamental Maximum EIRP

Please refer to Appendix A.

3.2 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.2.1 Limit of Unwanted Emissions

- (1) For transmitters operating within the 5.925-7.125 GHz band: Any emissions outside of the 5.925-7.125 GHz band must not exceed an e.i.r.p. of -27 dBm/MHz.

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27 (RMS)	68.3
- 7 (Peak)	88.3

According 987594 D02 U-NII 6GHz EMC Measurement v03 section G:

Unwanted emissions outside of restricted bands are measured with a RMS detector.

In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

3.2.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.2.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.2.7 Duty Cycle

Please refer to Appendix C.

3.2.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.3 Antenna Requirements

3.3.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.3.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna with 6dB pad	TESEQ & VGT	CBL 6111D & VFA_Z-04002-N-06	66925 & 24006	30MHz~1GHz	Apr. 12, 2026	Aug. 06, 2026~Aug. 13, 2026	Apr. 11, 2027	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Aug. 06, 2026~Aug. 13, 2026	Dec. 10, 2026	Radiation (03CH11-HY)
Double Ridged Guide Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-01620	1GHz~18GHz	Sep. 15, 2025	Aug. 06, 2026~Aug. 13, 2026	Sep. 14, 2026	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1230	18GHz~40GHz	Nov. 05, 2025	Aug. 06, 2026~Aug. 13, 2026	Nov. 04, 2026	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 06, 2025	Aug. 06, 2026~Aug. 13, 2026	Dec. 05, 2026	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Mar. 23, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 22, 2027	Radiation (03CH11-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz~18GHz	Jan. 20, 2026	Aug. 06, 2026~Aug. 13, 2026	Jan. 19, 2027	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 08, 2026	Aug. 06, 2026~Aug. 13, 2026	Jun. 07, 2027	Radiation (03CH11-HY)
Signal Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	May 28, 2026	Aug. 06, 2026~Aug. 13, 2026	May 27, 2027	Radiation (03CH11-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20Hz~8.4GHz	Apr. 30, 2026	Aug. 06, 2026~Aug. 13, 2026	Apr. 29, 2027	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 06, 2026~Aug. 13, 2026	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Aug. 06, 2026~Aug. 13, 2026	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Aug. 06, 2026~Aug. 13, 2026	N/A	Radiation (03CH11-HY)
Software	Audix	E3	RK-002391	N/A	N/A	Aug. 06, 2026~Aug. 13, 2026	N/A	Radiation (03CH11-HY)
USB Data Logger	TECPEL	TR-32	HE17XM6804	N/A	Dec. 15, 2025	Aug. 06, 2026~Aug. 13, 2026	Dec. 14, 2026	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303B	TP200880	N/A	Aug. 26, 2025	Aug. 06, 2026~Aug. 13, 2026	Aug. 25, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804013/2	30M~40G	Mar. 04, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 03, 2027	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 04, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 03, 2027	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	30M~40G	Mar. 04, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 03, 2027	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	805139 2	9K~30M	Mar. 04, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 03, 2027	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	805139 2	30M~40G	Mar. 04, 2026	Aug. 06, 2026~Aug. 13, 2026	Mar. 03, 2027	Radiation (03CH11-HY)
Notch Filter	Titan Microwave Co., Ltd.	T04H80002500 060S01	SN1	8GHz High Pass Filter	Aug. 19, 2025	Aug. 06, 2026~Aug. 13, 2026	Aug. 18, 2026	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-153 0-8000-40SS	SN11	1.53GHz Low Pass Filter	Sep. 09, 2025	Aug. 06, 2026~Aug. 13, 2026	Sep. 08, 2026	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 04, 2025	Jul. 02, 2026~Jul. 04, 2026	Nov. 03, 2026	Conducted (TH05-HY)
USB RF Power Sensor	DARE	RPR3008W	RPR8W-230100 13 (NO:100)	10MHz~8GHz	Jul. 18, 2025	Jul. 02, 2026~Jul. 04, 2026	Jul. 17, 2026	Conducted (TH05-HY)
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Nov. 12, 2025	Jul. 02, 2026~Jul. 04, 2026	Nov. 11, 2026	Conducted (TH05-HY)
Switch Control Mainframe	EM Electronics	EMSW18SE	SW191204 (BOX8)	N/A	Dec. 29, 2025	Jul. 02, 2026~Jul. 04, 2026	Dec. 28, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Jul. 02, 2026~Jul. 04, 2026	N/A	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5 dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
--	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9 dB
--	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2026/7/2~2026/7/4	Relative Humidity:	51~54	%

TEST RESULTS DATA
EIRP Power Table

U-NII-5 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT20	MCS0	1	001	5955	Full	5.40	5.30		3.60	4.68	9.00	9.98	24.00	Pass
EHT20	MCS0	1	045	6175	Full	5.40	5.40		3.60	4.68	9.00	10.08	24.00	Pass
EHT20	MCS0	1	093	6415	Full	5.30	5.40		3.60	4.68	8.90	10.08	24.00	Pass
EHT40	MCS0	1	003	5965	Full	8.30	8.30		3.60	4.68	11.90	12.98	24.00	Pass
EHT40	MCS0	1	043	6165	Full	8.30	8.40		3.60	4.68	11.90	13.08	24.00	Pass
EHT40	MCS0	1	091	6405	Full	8.30	8.40		3.60	4.68	11.90	13.08	24.00	Pass
EHT80	MCS0	1	007	5985	Full	11.30	11.40		3.60	4.68	14.90	16.08	24.00	Pass
EHT80	MCS0	1	039	6145	Full	11.40	11.20		3.60	4.68	15.00	15.88	24.00	Pass
EHT80	MCS0	1	087	6385	Full	11.40	11.20		3.60	4.68	15.00	15.88	24.00	Pass
EHT160	MCS0	1	015	6025	Full	14.20	14.40		3.60	4.68	17.80	19.08	24.00	Pass
EHT160	MCS0	1	079	6345	Full	14.20	14.40		3.60	4.68	17.80	19.08	24.00	Pass
EHT320	MCS0	1	031	6105	Full	16.30	16.30		3.60	4.68	19.90	20.98	24.00	Pass
EHT320	MCS0	1	063	6265	Full	16.30	16.30		3.60	4.68	19.90	20.98	24.00	Pass

U-NII-5 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	SUM		
EHT20	MCS0	2	001	5955	Full	2.30	2.40	5.36	4.68		10.04	24.00	Pass
EHT20	MCS0	2	045	6175	Full	2.40	2.10	5.26	4.68		9.94	24.00	Pass
EHT20	MCS0	2	093	6415	Full	2.40	2.10	5.26	4.68		9.94	24.00	Pass
EHT40	MCS0	2	003	5965	Full	5.10	5.30	8.21	4.68		12.89	24.00	Pass
EHT40	MCS0	2	043	6165	Full	5.40	5.10	8.26	4.68		12.94	24.00	Pass
EHT40	MCS0	2	091	6405	Full	5.40	5.10	8.26	4.68		12.94	24.00	Pass
EHT80	MCS0	2	007	5985	Full	8.20	8.40	11.31	4.68		15.99	24.00	Pass
EHT80	MCS0	2	039	6145	Full	8.40	8.30	11.36	4.68		16.04	24.00	Pass
EHT80	MCS0	2	087	6385	Full	8.30	8.40	11.36	4.68		16.04	24.00	Pass
EHT160	MCS0	2	015	6025	Full	11.20	11.40	14.31	4.68		18.99	24.00	Pass
EHT160	MCS0	2	079	6345	Full	11.40	11.10	14.26	4.68		18.94	24.00	Pass
EHT320	MCS0	2	031	6105	Full	13.40	13.30	16.36	4.68		21.04	24.00	Pass
EHT320	MCS0	2	063	6265	Full	13.30	13.10	16.21	4.68		20.89	24.00	Pass

TEST RESULTS DATA
EIRP Power Table

U-NII-6 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT20	MCS0	1	097	6435	Full	5.30	5.30		2.30	4.60	7.60	9.90	24.00	Pass
EHT20	MCS0	1	105	6475	Full	5.40	5.40		2.30	4.60	7.70	10.00	24.00	Pass
EHT20	MCS0	1	113	6515	Full	5.30	5.20		2.30	4.60	7.60	9.80	24.00	Pass
EHT40	MCS0	1	099	6445	Full	8.20	8.30		2.30	4.60	10.50	12.90	24.00	Pass
EHT40	MCS0	1	107	6485	Full	8.40	8.40		2.30	4.60	10.70	13.00	24.00	Pass
EHT80	MCS0	1	103	6465	Full	11.40	11.20		2.30	4.60	13.70	15.80	24.00	Pass

U-NII-6 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	SUM		
EHT20	MCS0	2	097	6435	Full	2.40	2.40	5.41	4.60		10.01	24.00	Pass
EHT20	MCS0	2	105	6475	Full	2.40	2.40	5.41	4.60		10.01	24.00	Pass
EHT20	MCS0	2	113	6515	Full	2.30	2.10	5.21	4.60		9.81	24.00	Pass
EHT40	MCS0	2	099	6445	Full	5.30	5.40	8.36	4.60		12.96	24.00	Pass
EHT40	MCS0	2	107	6485	Full	5.40	5.30	8.36	4.60		12.96	24.00	Pass
EHT80	MCS0	2	103	6465	Full	8.30	8.30	11.31	4.60		15.91	24.00	Pass

U-NII-6 straddle channel single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT80	MCS0	1	119	6545	Full	11.20	11.30		2.30	4.60	13.50	15.90	24.00	Pass
EHT160	MCS0	1	111	6505	Full	14.30	14.40		2.30	4.60	16.60	19.00	24.00	Pass
EHT320	MCS0	1	095	6425	Full	16.20	16.30		2.30	4.60	18.50	20.90	24.00	Pass
EHT320	MCS0	1	127	6585	Full	16.30	16.40		2.30	4.60	18.60	21.00	24.00	Pass

U-NII-6 straddle channel MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	SUM		
EHT80	MCS0	2	119	6545	Full	8.40	8.10	11.26	4.60		15.86	24.00	Pass
EHT160	MCS0	2	111	6505	Full	11.30	11.10	14.21	4.60		18.81	24.00	Pass
EHT320	MCS0	2	095	6425	Full	13.40	13.20	16.31	4.60		20.91	24.00	Pass
EHT320	MCS0	2	127	6585	Full	13.20	13.10	16.16	4.60		20.76	24.00	Pass

TEST RESULTS DATA
EIRP Power Table

U-NII-7 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT20	MCS0	1	117	6535	Full	5.30	5.40		1.75	3.58	7.05	8.98	24.00	Pass
EHT20	MCS0	1	149	6695	Full	5.40	5.40		1.75	3.58	7.15	8.98	24.00	Pass
EHT20	MCS0	1	181	6855	Full	5.30	5.30		1.75	3.58	7.05	8.88	24.00	Pass
EHT40	MCS0	1	123	6565	Full	8.40	8.10		1.75	3.58	10.15	11.68	24.00	Pass
EHT40	MCS0	1	147	6685	Full	8.20	8.20		1.75	3.58	9.95	11.78	24.00	Pass
EHT40	MCS0	1	179	6845	Full	8.20	8.30		1.75	3.58	9.95	11.88	24.00	Pass
EHT80	MCS0	1	135	6625	Full	11.20	11.30		1.75	3.58	12.95	14.88	24.00	Pass
EHT80	MCS0	1	167	6785	Full	11.30	11.20		1.75	3.58	13.05	14.78	24.00	Pass
EHT160	MCS0	1	143	6665	Full	14.30	14.40		1.75	3.58	16.05	17.98	24.00	Pass

U-NII-7 MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	SUM		
EHT20	MCS0	2	117	6535	Full	2.30	2.10	5.21	3.58		8.79	24.00	Pass
EHT20	MCS0	2	149	6695	Full	2.40	2.40	5.41	3.58		8.99	24.00	Pass
EHT20	MCS0	2	181	6855	Full	2.30	2.10	5.21	3.58		8.79	24.00	Pass
EHT40	MCS0	2	123	6565	Full	5.40	5.20	8.31	3.58		11.89	24.00	Pass
EHT40	MCS0	2	147	6685	Full	5.30	5.30	8.31	3.58		11.89	24.00	Pass
EHT40	MCS0	2	179	6845	Full	5.30	5.20	8.26	3.58		11.84	24.00	Pass
EHT80	MCS0	2	135	6625	Full	8.40	8.20	11.31	3.58		14.89	24.00	Pass
EHT80	MCS0	2	167	6785	Full	8.40	8.30	11.36	3.58		14.94	24.00	Pass
EHT160	MCS0	2	143	6665	Full	11.30	11.10	14.21	3.58		17.79	24.00	Pass

U-NII-7 straddle channel single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT20	MCS0	1	185	6875	Full	5.20	5.20		1.75	3.58	6.95	8.78	24.00	Pass
EHT40	MCS0	1	187	6885	Full	8.30	8.40		1.75	3.58	10.05	11.98	24.00	Pass
EHT80	MCS0	1	183	6865	Full	11.30	11.30		1.75	3.58	13.05	14.88	24.00	Pass
EHT160	MCS0	1	175	6825	Full	14.20	14.30		1.75	3.58	15.95	17.88	24.00	Pass
EHT320	MCS0	1	159	6745	Full	16.40	16.30		1.75	3.58	18.15	19.88	24.00	Pass
EHT320	MCS0	1	191	6905	Full	16.10	16.30		1.75	3.58	17.85	19.88	24.00	Pass

U-NII-7 straddle channel MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	
						Chain A	Chain B	SUM	Chain A	Chain B	SUM			
EHT20	MCS0	2	185	6875	Full	2.40	2.20	5.31	3.58		8.89	24.00	Pass	
EHT40	MCS0	2	187	6885	Full	5.20	5.10	8.16	3.58		11.74	24.00	Pass	
EHT80	MCS0	2	183	6865	Full	8.40	8.20	11.31	3.58		14.89	24.00	Pass	
EHT160	MCS0	2	175	6825	Full	11.10	11.10	14.11	3.58		17.69	24.00	Pass	
EHT320	MCS0	2	159	6745	Full	13.30	13.20	16.26	3.58		19.84	24.00	Pass	
EHT320	MCS0	2	191	6905	Full	13.40	13.40	16.41	3.58		19.99	24.00	Pass	

TEST RESULTS DATA
EIRP Power Table

U-NII-8 single antenna														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	Chain A	Chain B		
EHT20	MCS0	1	209	6995	Full	5.40	5.30		1.26	3.66	6.66	8.96	24.00	Pass
EHT20	MCS0	1	229	7095	Full	5.40	5.30		1.26	3.66	6.66	8.96	24.00	Pass
EHT20	MCS0	1	233	7115	Full	-2.70	-2.60		1.26	3.66	-1.44	1.06	24.00	Pass
EHT40	MCS0	1	227	7085	Full	8.10	8.40		1.26	3.66	9.36	12.06	24.00	Pass
EHT80	MCS0	1	199	6945	Full	11.20	11.40		1.26	3.66	12.46	15.06	24.00	Pass
EHT80	MCS0	1	215	7025	Full	11.40	11.40		1.26	3.66	12.66	15.06	24.00	Pass
EHT160	MCS0	1	207	6985	Full	14.20	14.30		1.26	3.66	15.46	17.96	24.00	Pass

U-NII-8 MIMO														
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Conducted Power (dBm)			DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)	Pass /Fail
						Chain A	Chain B	SUM	Chain A	Chain B	SUM			
EHT20	MCS0	2	209	6995	Full	2.40	2.20	5.31	3.66		8.97		24.00	Pass
EHT20	MCS0	2	229	7095	Full	2.10	2.40	5.26	3.66		8.92		24.00	Pass
EHT20	MCS0	2	233	7115	Full	-5.70	-5.60	-2.64	3.66		1.02		24.00	Pass
EHT40	MCS0	2	227	7085	Full	5.10	5.40	8.26	3.66		11.92		24.00	Pass
EHT80	MCS0	2	199	6945	Full	8.30	8.10	11.21	3.66		14.87		24.00	Pass
EHT80	MCS0	2	215	7025	Full	8.10	8.40	11.26	3.66		14.92		24.00	Pass
EHT160	MCS0	2	207	6985	Full	11.10	11.20	14.16	3.66		17.82		24.00	Pass



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Daniel Lee, Fu Chen and Troye Hsieh	Temperature :	19.1~21.9°C
		Relative Humidity :	50.1~66.9%

Note symbol

-L	Low channel location
-R	High channel location



B1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 31	U-NII-5	5.925-6.425	Chain A+B	802.11be EHT20	1	5955	MCS0	Full RU	-
Mode 32	U-NII-5	5.925-6.425	Chain A+B	802.11be EHT320	31	6105	MCS0	Full RU	-
Mode 33	U-NII-6	6.425-6.525	Chain A+B	802.11be EHT160	111	6505	MCS0	Full RU	-
Mode 34	U-NII-7	6.525-6.875	Chain A+B	802.11be EHT320	159	6745	MCS0	Full RU	-
Mode 35	U-NII-8	6.875-7.125	Chain A+B	802.11be EHT20	233	7115	MCS0	Full RU	-
Mode 36	U-NII-8	6.875-7.125	Chain A+B	802.11be EHT320	191	6905	MCS0	Full RU	-
Mode 37	U-NII-8	6.875-7.125	Chain A+B	802.11be EHT320	191	6905	MCS0	Full RU	LF

**B2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
31	802.11be EHT20	1	5922.63	42.42	68.20	-25.78	V	Avg.	Pass	Full RU	Band Edge
	802.11be EHT20	1	39905.50	45.40	54.00	-8.60	H	Avg.	Pass	Full RU	Harmonic
32	802.11be EHT320	31	5924.68	55.60	68.20	-12.60	V	Avg.	Pass	Full RU	Band Edge
	802.11be EHT320	31	-	-	-	-	-	-	-	Full RU	Harmonic
33	802.11be EHT160	111	-	-	-	-	-	-	-	Full RU	Band Edge
	802.11be EHT160	111	39527.50	45.25	54.00	-8.75	H	Avg.	Pass	Full RU	Harmonic
34	802.11be EHT320	159	7258.30	45.93	54.00	-8.07	H	Avg.	Pass	Full RU	Band Edge
	802.11be EHT320	159	39527.50	45.23	54.00	-8.77	H	Avg.	Pass	Full RU	Harmonic
35	802.11be EHT20	233	7125.01	55.22	68.20	-12.98	H	Avg.	Pass	Full RU	Band Edge
	802.11be EHT20	233	39892.00	45.63	54.00	-8.37	H	Avg.	Pass	Full RU	Harmonic
36	802.11be EHT320	191	7251.02	47.76	54.00	-6.24	H	Avg.	Pass	Full RU	Band Edge



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
36	802.11be EHT320	191	-	-	-	-	-	-	-	Full RU	Harmonic
37	802.11be EHT320	191	958.29	34.02	46.00	-11.98	H	Peak	Pass	-	LF





		31																																																																																																		
Mode	Band Edge																																																																																																			
	U-NII-5_5.925-6.425_802.11be EHT20_CH1_Full RU_5955MHz																																																																																																			
ANT	Chain A+B																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91280_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5896.24</td><td>53.02</td><td>88.20</td><td>-35.18</td><td>40.83</td><td>34.08</td><td>10.80</td><td>32.69</td><td>0.00</td><td>398</td><td>113</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5896.24	53.02	88.20	-35.18	40.83	34.08	10.80	32.69	0.00	398	113	Peak	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91280_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5955.00</td><td>90.10</td><td>-----</td><td>-----</td><td>77.65</td><td>34.19</td><td>10.97</td><td>32.71</td><td>0.00</td><td>398</td><td>113</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5955.00	90.10	-----	-----	77.65	34.19	10.97	32.71	0.00	398	113	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5896.24	53.02	88.20	-35.18	40.83	34.08	10.80	32.69	0.00	398	113	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5955.00	90.10	-----	-----	77.65	34.19	10.97	32.71	0.00	398	113	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91280_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5922.76</td><td>42.36</td><td>68.20</td><td>-25.84</td><td>30.03</td><td>34.15</td><td>10.88</td><td>32.70</td><td>0.00</td><td>398</td><td>113</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5922.76	42.36	68.20	-25.84	30.03	34.15	10.88	32.70	0.00	398	113	Average	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5955.00</td><td>82.64</td><td>-----</td><td>-----</td><td>70.19</td><td>34.19</td><td>10.97</td><td>32.71</td><td>0.00</td><td>398</td><td>113</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5955.00	82.64	-----	-----	70.19	34.19	10.97	32.71	0.00	398	113	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5922.76	42.36	68.20	-25.84	30.03	34.15	10.88	32.70	0.00	398	113	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5955.00	82.64	-----	-----	70.19	34.19	10.97	32.71	0.00	398	113	Average																																																																																								







		31																																																																																																	
Mode	Band Edge																																																																																																		
	U-NII-5_5.925-6.425_802.11be EHT20_CH1_Full RU_5955MHz																																																																																																		
ANT	Chain A+B																																																																																																		
Pol.	Vertical																																																																																																		
Peak	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5883.11</td><td>52.94</td><td>88.20</td><td>-35.26</td><td>40.82</td><td>34.03</td><td>10.77</td><td>32.68</td><td>0.00</td><td>214 314 Peak</td></tr></tbody></table> Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5955.00</td><td>96.64</td><td>-----</td><td>-----</td><td>84.20</td><td>34.20</td><td>10.95</td><td>32.71</td><td>0.00</td><td>214 314 Peak</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5883.11	52.94	88.20	-35.26	40.82	34.03	10.77	32.68	0.00	214 314 Peak		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5955.00	96.64	-----	-----	84.20	34.20	10.95	32.71	0.00	214 314 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																											
1	5883.11	52.94	88.20	-35.26	40.82	34.03	10.77	32.68	0.00	214 314 Peak																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																											
1	5955.00	96.64	-----	-----	84.20	34.20	10.95	32.71	0.00	214 314 Peak																																																																																									
Avg	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5922.63</td><td>42.42</td><td>68.20</td><td>-25.78</td><td>30.09</td><td>34.15</td><td>10.88</td><td>32.70</td><td>0.00</td><td>214 314 Average</td></tr></tbody></table> Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th colspan="2">Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th>cm</th><th>deg</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th></th><th></th></tr></thead><tbody><tr><td>1</td><td>5955.00</td><td>87.85</td><td>-----</td><td>-----</td><td>75.40</td><td>34.19</td><td>10.97</td><td>32.71</td><td>0.00</td><td>214 314 Average</td></tr></tbody></table>												Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5922.63	42.42	68.20	-25.78	30.09	34.15	10.88	32.70	0.00	214 314 Average		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB			1	5955.00	87.85	-----	-----	75.40	34.19	10.97	32.71	0.00	214 314 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																											
1	5922.63	42.42	68.20	-25.78	30.09	34.15	10.88	32.70	0.00	214 314 Average																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor			cm	deg																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																																																											
1	5955.00	87.85	-----	-----	75.40	34.19	10.97	32.71	0.00	214 314 Average																																																																																									



Mode	31																																																																																																																																																																																					
	Harmonic																																																																																																																																																																																					
	U-NII-5_5.925-6.425_802.11be EHT20_CH1_Full RU_5955MHz																																																																																																																																																																																					
ANT	Chain A+B																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
Peak Avg	Level (dBuV/m) Date: 2026-08-13  Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11910.00</td><td>49.28</td><td>74.00</td><td>-24.72</td><td>59.13</td><td>38.60</td><td>17.54</td><td>66.49</td><td>0.50</td><td>-- -- Peak</td></tr><tr><td>2 11910.00</td><td>38.79</td><td>54.00</td><td>-15.21</td><td>48.64</td><td>38.60</td><td>17.54</td><td>66.49</td><td>0.50</td><td>-- -- Average</td></tr><tr><td>3 17865.00</td><td>51.58</td><td>74.00</td><td>-22.42</td><td>56.31</td><td>40.91</td><td>22.28</td><td>68.63</td><td>0.71</td><td>-- -- Peak</td></tr><tr><td>4 17865.00</td><td>43.22</td><td>54.00</td><td>-10.78</td><td>47.95</td><td>40.91</td><td>22.28</td><td>68.63</td><td>0.71</td><td>-- -- Average</td></tr><tr><td>5 39905.50</td><td>53.93</td><td>74.00</td><td>-20.07</td><td>40.55</td><td>44.76</td><td>34.05</td><td>55.89</td><td>-9.54</td><td>-- -- Peak</td></tr><tr><td>6 39905.50</td><td>45.40</td><td>54.00</td><td>-8.60</td><td>32.02</td><td>44.76</td><td>34.05</td><td>55.89</td><td>-9.54</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11910.00	49.28	74.00	-24.72	59.13	38.60	17.54	66.49	0.50	-- -- Peak	2 11910.00	38.79	54.00	-15.21	48.64	38.60	17.54	66.49	0.50	-- -- Average	3 17865.00	51.58	74.00	-22.42	56.31	40.91	22.28	68.63	0.71	-- -- Peak	4 17865.00	43.22	54.00	-10.78	47.95	40.91	22.28	68.63	0.71	-- -- Average	5 39905.50	53.93	74.00	-20.07	40.55	44.76	34.05	55.89	-9.54	-- -- Peak	6 39905.50	45.40	54.00	-8.60	32.02	44.76	34.05	55.89	-9.54	-- -- Average	Level (dBuV/m) Date: 2026-08-13  Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11910.00</td><td>49.15</td><td>74.00</td><td>-24.85</td><td>59.00</td><td>38.60</td><td>17.54</td><td>66.49</td><td>0.50</td><td>-- -- Peak</td></tr><tr><td>2 11910.00</td><td>38.78</td><td>54.00</td><td>-15.22</td><td>48.63</td><td>38.60</td><td>17.54</td><td>66.49</td><td>0.50</td><td>-- -- Average</td></tr><tr><td>3 17865.00</td><td>52.31</td><td>74.00</td><td>-21.69</td><td>57.04</td><td>40.91</td><td>22.28</td><td>68.63</td><td>0.71</td><td>-- -- Peak</td></tr><tr><td>4 17865.00</td><td>43.23</td><td>54.00</td><td>-10.77</td><td>47.96</td><td>40.91</td><td>22.28</td><td>68.63</td><td>0.71</td><td>-- -- Average</td></tr><tr><td>5 39676.00</td><td>54.47</td><td>74.00</td><td>-19.53</td><td>41.42</td><td>44.89</td><td>33.82</td><td>56.12</td><td>-9.54</td><td>-- -- Peak</td></tr><tr><td>6 39676.00</td><td>45.09</td><td>54.00</td><td>-8.91</td><td>32.04</td><td>44.89</td><td>33.82</td><td>56.12</td><td>-9.54</td><td>-- -- Average</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11910.00	49.15	74.00	-24.85	59.00	38.60	17.54	66.49	0.50	-- -- Peak	2 11910.00	38.78	54.00	-15.22	48.63	38.60	17.54	66.49	0.50	-- -- Average	3 17865.00	52.31	74.00	-21.69	57.04	40.91	22.28	68.63	0.71	-- -- Peak	4 17865.00	43.23	54.00	-10.77	47.96	40.91	22.28	68.63	0.71	-- -- Average	5 39676.00	54.47	74.00	-19.53	41.42	44.89	33.82	56.12	-9.54	-- -- Peak	6 39676.00	45.09	54.00	-8.91	32.04	44.89	33.82	56.12	-9.54	-- -- Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 11910.00	49.28	74.00	-24.72	59.13	38.60	17.54	66.49	0.50	-- -- Peak																																																																																																																																																																													
2 11910.00	38.79	54.00	-15.21	48.64	38.60	17.54	66.49	0.50	-- -- Average																																																																																																																																																																													
3 17865.00	51.58	74.00	-22.42	56.31	40.91	22.28	68.63	0.71	-- -- Peak																																																																																																																																																																													
4 17865.00	43.22	54.00	-10.78	47.95	40.91	22.28	68.63	0.71	-- -- Average																																																																																																																																																																													
5 39905.50	53.93	74.00	-20.07	40.55	44.76	34.05	55.89	-9.54	-- -- Peak																																																																																																																																																																													
6 39905.50	45.40	54.00	-8.60	32.02	44.76	34.05	55.89	-9.54	-- -- Average																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1 11910.00	49.15	74.00	-24.85	59.00	38.60	17.54	66.49	0.50	-- -- Peak																																																																																																																																																																													
2 11910.00	38.78	54.00	-15.22	48.63	38.60	17.54	66.49	0.50	-- -- Average																																																																																																																																																																													
3 17865.00	52.31	74.00	-21.69	57.04	40.91	22.28	68.63	0.71	-- -- Peak																																																																																																																																																																													
4 17865.00	43.23	54.00	-10.77	47.96	40.91	22.28	68.63	0.71	-- -- Average																																																																																																																																																																													
5 39676.00	54.47	74.00	-19.53	41.42	44.89	33.82	56.12	-9.54	-- -- Peak																																																																																																																																																																													
6 39676.00	45.09	54.00	-8.91	32.04	44.89	33.82	56.12	-9.54	-- -- Average																																																																																																																																																																													



Mode	31	
	Harmonic	
	U-NII-5_5.925-6.425_802.11be EHT20_CH1_Full RU_5955MHz	
ANT	Chain A+B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL
	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL







38.6G ~40G Avg	Level (dBuV/m) Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Horizontal	Level (dBuV/m) Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Vertical



		32																																																																																																		
Mode	Band Edge																																																																																																			
	U-NII-5_5.925-6.425_802.11be EHT320_CH31_Full RU_6105MHz																																																																																																			
ANT	Chain A+B																																																																																																			
Pol.	Horizontal						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5907.32</td><td>60.43</td><td>88.20</td><td>-27.77</td><td>48.17</td><td>34.11</td><td>10.84</td><td>32.69</td><td>0.00</td><td>400</td><td>110</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5907.32	60.43	88.20	-27.77	48.17	34.11	10.84	32.69	0.00	400	110	Peak	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6105.00</td><td>93.62</td><td>-----</td><td>-----</td><td>81.25</td><td>34.06</td><td>11.10</td><td>32.79</td><td>0.00</td><td>400</td><td>110</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6105.00	93.62	-----	-----	81.25	34.06	11.10	32.79	0.00	400	110	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5907.32	60.43	88.20	-27.77	48.17	34.11	10.84	32.69	0.00	400	110	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	6105.00	93.62	-----	-----	81.25	34.06	11.10	32.79	0.00	400	110	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5922.44</td><td>50.91</td><td>68.20</td><td>-17.29</td><td>38.59</td><td>34.14</td><td>10.88</td><td>32.70</td><td>0.00</td><td>400</td><td>110</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5922.44	50.91	68.20	-17.29	38.59	34.14	10.88	32.70	0.00	400	110	Average	Level (dBuV/m) Date: 2026-08-09 Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6105.00</td><td>83.61</td><td>-----</td><td>-----</td><td>71.22</td><td>34.08</td><td>11.10</td><td>32.79</td><td>0.00</td><td>400</td><td>110</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6105.00	83.61	-----	-----	71.22	34.08	11.10	32.79	0.00	400	110	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5922.44	50.91	68.20	-17.29	38.59	34.14	10.88	32.70	0.00	400	110	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	6105.00	83.61	-----	-----	71.22	34.08	11.10	32.79	0.00	400	110	Average																																																																																								



		32																																																																																																		
Mode	Band Edge																																																																																																			
	U-NII-5_5.925-6.425_802.11be EHT320_CH31_Full RU_6105MHz																																																																																																			
ANT	Chain A+B																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak	Level (dBuV/m) Date: 2026-08-09  Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5919.92</td><td>66.08</td><td>88.20</td><td>-22.12</td><td>53.77</td><td>34.14</td><td>10.87</td><td>32.70</td><td>0.00</td><td>200</td><td>314</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5919.92	66.08	88.20	-22.12	53.77	34.14	10.87	32.70	0.00	200	314	Peak	Level (dBuV/m) Date: 2026-08-09  Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6105.00</td><td>95.53</td><td>-----</td><td>-----</td><td>83.14</td><td>34.10</td><td>11.10</td><td>32.81</td><td>0.00</td><td>200</td><td>314</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6105.00	95.53	-----	-----	83.14	34.10	11.10	32.81	0.00	200	314	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5919.92	66.08	88.20	-22.12	53.77	34.14	10.87	32.70	0.00	200	314	Peak																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	6105.00	95.53	-----	-----	83.14	34.10	11.10	32.81	0.00	200	314	Peak																																																																																								
Avg	Level (dBuV/m) Date: 2026-08-09  Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5924.68</td><td>55.60</td><td>68.20</td><td>-12.60</td><td>43.26</td><td>34.15</td><td>10.89</td><td>32.70</td><td>0.00</td><td>200</td><td>314</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5924.68	55.60	68.20	-12.60	43.26	34.15	10.89	32.70	0.00	200	314	Average	Level (dBuV/m) Date: 2026-08-09  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6105.00</td><td>85.87</td><td>-----</td><td>-----</td><td>73.41</td><td>34.10</td><td>11.10</td><td>32.74</td><td>0.00</td><td>200</td><td>314</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6105.00	85.87	-----	-----	73.41	34.10	11.10	32.74	0.00	200	314	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	5924.68	55.60	68.20	-12.60	43.26	34.15	10.89	32.70	0.00	200	314	Average																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	6105.00	85.87	-----	-----	73.41	34.10	11.10	32.74	0.00	200	314	Average																																																																																								



Mode	33									
	Band Edge									
	U-NII-6_6.425-6.525_802.11be EHT160_CH111_Full RU_6505MHz									
ANT	Chain A+B									
Pol.	Horizontal					Fundamental				
Peak	Blank					Level (dBuV/m)				







Mode	33	
	Band Edge	
	U-NII-6_6.425-6.525_802.11be EHT160_CH111_Full RU_6505MHz	
ANT	Chain A+B	
Pol.	Vertical	Fundamental
Peak	Blank	Level (dBuV/m) <



Mode	33																																																																																																																																																																																
	Harmonic																																																																																																																																																																																
	U-NII-6_6.425-6.525_802.11be EHT160_CH111_Full RU_6505MHz																																																																																																																																																																																
ANT	Chain A+B																																																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																																																										
Peak Avg																																																																																																																																																																																	
	Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 HORIZONTAL						Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 VERTICAL																																																																																																																																																																										
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>13010.00</td><td>51.18</td><td>88.20</td><td>-37.02</td><td>59.96</td><td>39.74</td><td>18.42</td><td>67.37</td><td>0.43</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>19515.00</td><td>36.93</td><td>74.00</td><td>-37.07</td><td>40.83</td><td>38.03</td><td>22.89</td><td>55.28</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39527.50</td><td>55.41</td><td>74.00</td><td>-18.59</td><td>42.20</td><td>45.35</td><td>33.67</td><td>56.27</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39527.50</td><td>45.25</td><td>54.00</td><td>-8.75</td><td>32.04</td><td>45.35</td><td>33.67</td><td>56.27</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	13010.00	51.18	88.20	-37.02	59.96	39.74	18.42	67.37	0.43	--	--	Peak	2	19515.00	36.93	74.00	-37.07	40.83	38.03	22.89	55.28	-9.54	--	--	Peak	3	39527.50	55.41	74.00	-18.59	42.20	45.35	33.67	56.27	-9.54	--	--	Peak	4	39527.50	45.25	54.00	-8.75	32.04	45.35	33.67	56.27	-9.54	--	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>13010.00</td><td>51.19</td><td>88.20</td><td>-37.01</td><td>59.97</td><td>39.74</td><td>18.42</td><td>67.37</td><td>0.43</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>19515.00</td><td>37.08</td><td>74.00</td><td>-36.92</td><td>40.98</td><td>38.03</td><td>22.89</td><td>55.28</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39527.50</td><td>55.47</td><td>74.00</td><td>-18.53</td><td>42.42</td><td>44.89</td><td>33.82</td><td>56.12</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39527.50</td><td>45.09</td><td>54.00</td><td>-8.91</td><td>32.04</td><td>44.89</td><td>33.82</td><td>56.12</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	13010.00	51.19	88.20	-37.01	59.97	39.74	18.42	67.37	0.43	--	--	Peak	2	19515.00	37.08	74.00	-36.92	40.98	38.03	22.89	55.28	-9.54	--	--	Peak	3	39527.50	55.47	74.00	-18.53	42.42	44.89	33.82	56.12	-9.54	--	--	Peak	4	39527.50	45.09	54.00	-8.91	32.04	44.89	33.82	56.12	-9.54	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	13010.00	51.18	88.20	-37.02	59.96	39.74	18.42	67.37	0.43	--	--	Peak																																																																																																																																																																					
2	19515.00	36.93	74.00	-37.07	40.83	38.03	22.89	55.28	-9.54	--	--	Peak																																																																																																																																																																					
3	39527.50	55.41	74.00	-18.59	42.20	45.35	33.67	56.27	-9.54	--	--	Peak																																																																																																																																																																					
4	39527.50	45.25	54.00	-8.75	32.04	45.35	33.67	56.27	-9.54	--	--	Average																																																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	13010.00	51.19	88.20	-37.01	59.97	39.74	18.42	67.37	0.43	--	--	Peak																																																																																																																																																																					
2	19515.00	37.08	74.00	-36.92	40.98	38.03	22.89	55.28	-9.54	--	--	Peak																																																																																																																																																																					
3	39527.50	55.47	74.00	-18.53	42.42	44.89	33.82	56.12	-9.54	--	--	Peak																																																																																																																																																																					
4	39527.50	45.09	54.00	-8.91	32.04	44.89	33.82	56.12	-9.54	--	--	Average																																																																																																																																																																					



Mode	33	
	Harmonic	
	U-NII-6_6.425-6.525_802.11be EHT160_CH111_Full RU_6505MHz	
ANT	Chain A+B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL
	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL



38.6G ~40G Avg	Level (dBuV/m) Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Horizontal	Level (dBuV/m) Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Vertical



		34																																																																																																																												
Mode	Band Edge																																																																																																																													
	U-NII-7_6.525-6.875_802.11be EHT320_CH159_Full RU_6745MHz																																																																																																																													
ANT	Chain A+B																																																																																																																													
Pol.	Horizontal						Fundamental																																																																																																																							
Peak	Level (dBuV/m) Date: 2026-08-10 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 6745 6996. 7247. 7498. 7749. 8000 Frequency (MHz) Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7134.05</td><td>59.03</td><td>88.20</td><td>-29.17</td><td>44.25</td><td>36.44</td><td>11.84</td><td>33.50</td><td>0.00</td><td>206</td><td>239</td><td>Peak</td></tr><tr><td>2</td><td>7258.77</td><td>56.33</td><td>74.00</td><td>-17.67</td><td>41.06</td><td>36.90</td><td>11.94</td><td>33.57</td><td>0.00</td><td>206</td><td>239</td><td>Peak</td></tr><tr><td>3</td><td>7974.90</td><td>56.58</td><td>88.20</td><td>-31.62</td><td>41.09</td><td>36.90</td><td>12.38</td><td>33.79</td><td>0.00</td><td>206</td><td>239</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7134.05	59.03	88.20	-29.17	44.25	36.44	11.84	33.50	0.00	206	239	Peak	2	7258.77	56.33	74.00	-17.67	41.06	36.90	11.94	33.57	0.00	206	239	Peak	3	7974.90	56.58	88.20	-31.62	41.09	36.90	12.38	33.79	0.00	206	239	Peak	Level (dBuV/m) Date: 2026-08-10 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 2400. 3800. 5200. 6600. 8000 Frequency (MHz) Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6745.00</td><td>93.16</td><td>-----</td><td>-----</td><td>79.29</td><td>35.84</td><td>11.14</td><td>33.11</td><td>0.00</td><td>206</td><td>239</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6745.00	93.16	-----	-----	79.29	35.84	11.14	33.11	0.00	206	239	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	7134.05	59.03	88.20	-29.17	44.25	36.44	11.84	33.50	0.00	206	239	Peak																																																																																																																		
2	7258.77	56.33	74.00	-17.67	41.06	36.90	11.94	33.57	0.00	206	239	Peak																																																																																																																		
3	7974.90	56.58	88.20	-31.62	41.09	36.90	12.38	33.79	0.00	206	239	Peak																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	6745.00	93.16	-----	-----	79.29	35.84	11.14	33.11	0.00	206	239	Peak																																																																																																																		
Avg	Level (dBuV/m) Date: 2026-08-10 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 6745 6996. 7247. 7498. 7749. 8000 Frequency (MHz) Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7130.29</td><td>47.19</td><td>68.20</td><td>-21.01</td><td>32.44</td><td>36.42</td><td>11.83</td><td>33.50</td><td>0.00</td><td>206</td><td>239</td><td>Average</td></tr><tr><td>2</td><td>7258.30</td><td>45.93</td><td>54.00</td><td>-8.07</td><td>30.66</td><td>36.90</td><td>11.94</td><td>33.57</td><td>0.00</td><td>206</td><td>239</td><td>Average</td></tr><tr><td>3</td><td>8000.00</td><td>45.70</td><td>68.20</td><td>-22.50</td><td>30.18</td><td>36.90</td><td>12.41</td><td>33.79</td><td>0.00</td><td>206</td><td>239</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7130.29	47.19	68.20	-21.01	32.44	36.42	11.83	33.50	0.00	206	239	Average	2	7258.30	45.93	54.00	-8.07	30.66	36.90	11.94	33.57	0.00	206	239	Average	3	8000.00	45.70	68.20	-22.50	30.18	36.90	12.41	33.79	0.00	206	239	Average	Level (dBuV/m) Date: 2026-08-10 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 2400. 3800. 5200. 6600. 8000 Frequency (MHz) Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6745.00</td><td>83.16</td><td>-----</td><td>-----</td><td>69.56</td><td>35.70</td><td>11.19</td><td>33.29</td><td>0.00</td><td>206</td><td>239</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6745.00	83.16	-----	-----	69.56	35.70	11.19	33.29	0.00	206	239	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	7130.29	47.19	68.20	-21.01	32.44	36.42	11.83	33.50	0.00	206	239	Average																																																																																																																		
2	7258.30	45.93	54.00	-8.07	30.66	36.90	11.94	33.57	0.00	206	239	Average																																																																																																																		
3	8000.00	45.70	68.20	-22.50	30.18	36.90	12.41	33.79	0.00	206	239	Average																																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																				
1	6745.00	83.16	-----	-----	69.56	35.70	11.19	33.29	0.00	206	239	Average																																																																																																																		







		34																																																																																																																											
Mode	Band Edge																																																																																																																												
	U-NII-7_6.525-6.875_802.11be EHT320_CH159_Full RU_6745MHz																																																																																																																												
ANT	Chain A+B																																																																																																																												
Pol.	Vertical						Fundamental																																																																																																																						
Peak	Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7127.78</td><td>55.97</td><td>88.20</td><td>-32.23</td><td>41.23</td><td>36.41</td><td>11.83</td><td>33.50</td><td>0.00</td><td>322</td><td>90</td><td>Peak</td></tr><tr><td>2</td><td>7255.79</td><td>56.27</td><td>74.00</td><td>-17.73</td><td>41.00</td><td>36.90</td><td>11.94</td><td>33.57</td><td>0.00</td><td>322</td><td>90</td><td>Peak</td></tr><tr><td>3</td><td>7998.75</td><td>57.10</td><td>88.20</td><td>-31.10</td><td>41.58</td><td>36.90</td><td>12.41</td><td>33.79</td><td>0.00</td><td>322</td><td>90</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7127.78	55.97	88.20	-32.23	41.23	36.41	11.83	33.50	0.00	322	90	Peak	2	7255.79	56.27	74.00	-17.73	41.00	36.90	11.94	33.57	0.00	322	90	Peak	3	7998.75	57.10	88.20	-31.10	41.58	36.90	12.41	33.79	0.00	322	90	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6745.00</td><td>94.60</td><td>-----</td><td>-----</td><td>80.73</td><td>35.81</td><td>11.16</td><td>33.10</td><td>0.00</td><td>322</td><td>90</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6745.00	94.60	-----	-----	80.73	35.81	11.16	33.10	0.00	322	90	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	7127.78	55.97	88.20	-32.23	41.23	36.41	11.83	33.50	0.00	322	90	Peak																																																																																																																	
2	7255.79	56.27	74.00	-17.73	41.00	36.90	11.94	33.57	0.00	322	90	Peak																																																																																																																	
3	7998.75	57.10	88.20	-31.10	41.58	36.90	12.41	33.79	0.00	322	90	Peak																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	6745.00	94.60	-----	-----	80.73	35.81	11.16	33.10	0.00	322	90	Peak																																																																																																																	
Avg	Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7125.27</td><td>46.67</td><td>68.20</td><td>-21.53</td><td>31.94</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>322</td><td>90</td><td>Average</td></tr><tr><td>2</td><td>7258.77</td><td>45.62</td><td>54.00</td><td>-8.38</td><td>30.35</td><td>36.90</td><td>11.94</td><td>33.57</td><td>0.00</td><td>322</td><td>90</td><td>Average</td></tr><tr><td>3</td><td>7998.75</td><td>45.75</td><td>68.20</td><td>-22.45</td><td>30.23</td><td>36.90</td><td>12.41</td><td>33.79</td><td>0.00</td><td>322</td><td>90</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7125.27	46.67	68.20	-21.53	31.94	36.40	11.83	33.50	0.00	322	90	Average	2	7258.77	45.62	54.00	-8.38	30.35	36.90	11.94	33.57	0.00	322	90	Average	3	7998.75	45.75	68.20	-22.45	30.23	36.90	12.41	33.79	0.00	322	90	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6745.00</td><td>84.29</td><td>-----</td><td>-----</td><td>70.42</td><td>35.83</td><td>11.15</td><td>33.11</td><td>0.00</td><td>322</td><td>90</td><td>Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6745.00	84.29	-----	-----	70.42	35.83	11.15	33.11	0.00	322	90	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																			
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	7125.27	46.67	68.20	-21.53	31.94	36.40	11.83	33.50	0.00	322	90	Average																																																																																																																	
2	7258.77	45.62	54.00	-8.38	30.35	36.90	11.94	33.57	0.00	322	90	Average																																																																																																																	
3	7998.75	45.75	68.20	-22.45	30.23	36.90	12.41	33.79	0.00	322	90	Average																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	6745.00	84.29	-----	-----	70.42	35.83	11.15	33.11	0.00	322	90	Average																																																																																																																	



Mode	34																																																																																																																																																																																	
	Harmonic																																																																																																																																																																																	
	U-NII-7_6.525-6.875_802.11be EHT320_CH159_Full RU_6745MHz																																																																																																																																																																																	
ANT	Chain A+B																																																																																																																																																																																	
Pol.	Horizontal						Vertical																																																																																																																																																																											
Peak Avg	Level (dBuV/m) Date: 2026-08-13 Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>13490.00</td><td>53.62</td><td>88.20</td><td>-34.58</td><td>59.91</td><td>40.26</td><td>19.14</td><td>66.09</td><td>0.40</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>20235.50</td><td>36.82</td><td>74.00</td><td>-37.18</td><td>40.31</td><td>37.97</td><td>23.07</td><td>54.99</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39527.50</td><td>54.41</td><td>74.00</td><td>-19.59</td><td>41.20</td><td>45.35</td><td>33.67</td><td>56.27</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39527.50</td><td>45.23</td><td>54.00</td><td>-8.77</td><td>32.02</td><td>45.35</td><td>33.67</td><td>56.27</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	13490.00	53.62	88.20	-34.58	59.91	40.26	19.14	66.09	0.40	--	--	Peak	2	20235.50	36.82	74.00	-37.18	40.31	37.97	23.07	54.99	-9.54	--	--	Peak	3	39527.50	54.41	74.00	-19.59	41.20	45.35	33.67	56.27	-9.54	--	--	Peak	4	39527.50	45.23	54.00	-8.77	32.02	45.35	33.67	56.27	-9.54	--	--	Average	Level (dBuV/m) Date: 2026-08-13 Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>13490.00</td><td>53.28</td><td>88.20</td><td>-34.92</td><td>59.57</td><td>40.26</td><td>19.14</td><td>66.09</td><td>0.40</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>20235.00</td><td>37.49</td><td>74.00</td><td>-36.51</td><td>40.98</td><td>37.97</td><td>23.07</td><td>54.99</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39176.50</td><td>54.16</td><td>74.00</td><td>-19.84</td><td>42.26</td><td>44.74</td><td>33.32</td><td>56.62</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39176.50</td><td>43.93</td><td>54.00</td><td>-10.07</td><td>32.03</td><td>44.74</td><td>33.32</td><td>56.62</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	13490.00	53.28	88.20	-34.92	59.57	40.26	19.14	66.09	0.40	--	--	Peak	2	20235.00	37.49	74.00	-36.51	40.98	37.97	23.07	54.99	-9.54	--	--	Peak	3	39176.50	54.16	74.00	-19.84	42.26	44.74	33.32	56.62	-9.54	--	--	Peak	4	39176.50	43.93	54.00	-10.07	32.03	44.74	33.32	56.62	-9.54	--	--	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	13490.00	53.62	88.20	-34.58	59.91	40.26	19.14	66.09	0.40	--	--	Peak																																																																																																																																																																						
2	20235.50	36.82	74.00	-37.18	40.31	37.97	23.07	54.99	-9.54	--	--	Peak																																																																																																																																																																						
3	39527.50	54.41	74.00	-19.59	41.20	45.35	33.67	56.27	-9.54	--	--	Peak																																																																																																																																																																						
4	39527.50	45.23	54.00	-8.77	32.02	45.35	33.67	56.27	-9.54	--	--	Average																																																																																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	13490.00	53.28	88.20	-34.92	59.57	40.26	19.14	66.09	0.40	--	--	Peak																																																																																																																																																																						
2	20235.00	37.49	74.00	-36.51	40.98	37.97	23.07	54.99	-9.54	--	--	Peak																																																																																																																																																																						
3	39176.50	54.16	74.00	-19.84	42.26	44.74	33.32	56.62	-9.54	--	--	Peak																																																																																																																																																																						
4	39176.50	43.93	54.00	-10.07	32.03	44.74	33.32	56.62	-9.54	--	--	Average																																																																																																																																																																						



Mode	34	
	Harmonic	
	U-NII-7_6.525-6.875_802.11be EHT320_CH159_Full RU_6745MHz	
ANT	Chain A+B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL
	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL



38.6G ~40G Avg	Level (dBuV/m) Date: 2026-08-12 AVG_54 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Horizontal	Level (dBuV/m) Date: 2026-08-12 AVG_54 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Vertical





		35																																																																																																					
Mode	Band Edge																																																																																																						
	U-NII-8_6.875-7.125_802.11be EHT20_CH233_Full RU_7115MHz																																																																																																						
ANT	Chain A+B																																																																																																						
Pol.	Horizontal						Fundamental																																																																																																
Peak	Level (dBuV/m) Date: 2026-08-09 PEAK_BE(UNII)_6E Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7125.14</td><td>63.51</td><td>88.20</td><td>-24.69</td><td>48.78</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>168</td><td>243</td><td>Peak</td></tr><tr><td>2</td><td>7126.18</td><td>63.88</td><td>88.20</td><td>-24.32</td><td>49.15</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>168</td><td>243</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7125.14	63.51	88.20	-24.69	48.78	36.40	11.83	33.50	0.00	168	243	Peak	2	7126.18	63.88	88.20	-24.32	49.15	36.40	11.83	33.50	0.00	168	243	Peak	Level (dBuV/m) Date: 2026-08-09 PEAK(UNII)_6E Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7115.00</td><td>86.19</td><td>-----</td><td>-----</td><td>71.53</td><td>36.34</td><td>11.81</td><td>33.49</td><td>0.00</td><td>168</td><td>243</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7115.00	86.19	-----	-----	71.53	36.34	11.81	33.49	0.00	168	243	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7125.14	63.51	88.20	-24.69	48.78	36.40	11.83	33.50	0.00	168	243	Peak																																																																																											
2	7126.18	63.88	88.20	-24.32	49.15	36.40	11.83	33.50	0.00	168	243	Peak																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7115.00	86.19	-----	-----	71.53	36.34	11.81	33.49	0.00	168	243	Peak																																																																																											
Avg	Level (dBuV/m) Date: 2026-08-09 AVG_BE(UNII)_6E Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7125.01</td><td>55.22</td><td>68.20</td><td>-12.98</td><td>40.49</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>168</td><td>243</td><td>Average</td></tr><tr><td>2</td><td>7126.05</td><td>53.71</td><td>68.20</td><td>-14.49</td><td>38.98</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>168</td><td>243</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7125.01	55.22	68.20	-12.98	40.49	36.40	11.83	33.50	0.00	168	243	Average	2	7126.05	53.71	68.20	-14.49	38.98	36.40	11.83	33.50	0.00	168	243	Average	Level (dBuV/m) Date: 2026-08-09 AVG(UNII)_6E Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7115.00</td><td>76.97</td><td>-----</td><td>-----</td><td>62.31</td><td>36.34</td><td>11.81</td><td>33.49</td><td>0.00</td><td>168</td><td>243</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7115.00	76.97	-----	-----	62.31	36.34	11.81	33.49	0.00	168	243	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7125.01	55.22	68.20	-12.98	40.49	36.40	11.83	33.50	0.00	168	243	Average																																																																																											
2	7126.05	53.71	68.20	-14.49	38.98	36.40	11.83	33.50	0.00	168	243	Average																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7115.00	76.97	-----	-----	62.31	36.34	11.81	33.49	0.00	168	243	Average																																																																																											







		35																																																																																																					
Mode	Band Edge																																																																																																						
	U-NII-8_6.875-7.125_802.11be EHT20_CH233_Full RU_7115MHz																																																																																																						
ANT	Chain A+B																																																																																																						
Pol.	Vertical						Fundamental																																																																																																
Peak	Level (dBuV/m) Date: 2026-08-09 PEAK_BE(UNII)_6E Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7125.01</td><td>62.51</td><td>88.20</td><td>-25.69</td><td>47.78</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>248</td><td>91</td><td>Peak</td></tr><tr><td>2</td><td>7126.05</td><td>64.12</td><td>88.20</td><td>-24.08</td><td>49.39</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>248</td><td>91</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7125.01	62.51	88.20	-25.69	47.78	36.40	11.83	33.50	0.00	248	91	Peak	2	7126.05	64.12	88.20	-24.08	49.39	36.40	11.83	33.50	0.00	248	91	Peak	Level (dBuV/m) Date: 2026-08-09 PEAK(UNII)_6E Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7115.00</td><td>84.61</td><td>-----</td><td>-----</td><td>69.95</td><td>36.34</td><td>11.81</td><td>33.49</td><td>0.00</td><td>248</td><td>91</td><td>Peak</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7115.00	84.61	-----	-----	69.95	36.34	11.81	33.49	0.00	248	91	Peak
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7125.01	62.51	88.20	-25.69	47.78	36.40	11.83	33.50	0.00	248	91	Peak																																																																																											
2	7126.05	64.12	88.20	-24.08	49.39	36.40	11.83	33.50	0.00	248	91	Peak																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7115.00	84.61	-----	-----	69.95	36.34	11.81	33.49	0.00	248	91	Peak																																																																																											
Avg	Level (dBuV/m) Date: 2026-08-09 AVG_BE(UNII)_6E Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBN:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7125.01</td><td>54.28</td><td>68.20</td><td>-13.92</td><td>39.55</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>248</td><td>91</td><td>Average</td></tr><tr><td>2</td><td>7126.05</td><td>53.09</td><td>68.20</td><td>-15.11</td><td>38.36</td><td>36.40</td><td>11.83</td><td>33.50</td><td>0.00</td><td>248</td><td>91</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7125.01	54.28	68.20	-13.92	39.55	36.40	11.83	33.50	0.00	248	91	Average	2	7126.05	53.09	68.20	-15.11	38.36	36.40	11.83	33.50	0.00	248	91	Average	Level (dBuV/m) Date: 2026-08-09 AVG(UNII)_6E Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBN:0.010kHz SMT:Auto <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>7115.00</td><td>76.81</td><td>-----</td><td>-----</td><td>62.15</td><td>36.34</td><td>11.81</td><td>33.49</td><td>0.00</td><td>248</td><td>91</td><td>Average</td></tr></table>							Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	7115.00	76.81	-----	-----	62.15	36.34	11.81	33.49	0.00	248	91	Average
		Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7125.01	54.28	68.20	-13.92	39.55	36.40	11.83	33.50	0.00	248	91	Average																																																																																											
2	7126.05	53.09	68.20	-15.11	38.36	36.40	11.83	33.50	0.00	248	91	Average																																																																																											
	Freq	Level	Limit	Line Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																												
1	7115.00	76.81	-----	-----	62.15	36.34	11.81	33.49	0.00	248	91	Average																																																																																											



Mode	35																																																																																																																																																																																	
	Harmonic																																																																																																																																																																																	
	U-NII-8_6.875-7.125_802.11be EHT20_CH233_Full RU_7115MHz																																																																																																																																																																																	
ANT	Chain A+B																																																																																																																																																																																	
Pol.	Horizontal						Vertical																																																																																																																																																																											
Peak																																																																																																																																																																																		
	Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 HORIZONTAL						Site : 03CH11-HY Condition: PEAK(UNII) 1m SHF_1230_251205 VERTICAL																																																																																																																																																																											
Avg	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>14230.00</td><td>51.95</td><td>88.20</td><td>-36.25</td><td>57.79</td><td>40.48</td><td>19.93</td><td>66.65</td><td>0.40</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>21345.00</td><td>37.82</td><td>74.00</td><td>-36.18</td><td>40.46</td><td>38.10</td><td>23.74</td><td>54.94</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39892.00</td><td>54.83</td><td>74.00</td><td>-19.17</td><td>41.53</td><td>44.72</td><td>34.03</td><td>55.91</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39892.00</td><td>45.63</td><td>54.00</td><td>-8.37</td><td>32.33</td><td>44.72</td><td>34.03</td><td>55.91</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	14230.00	51.95	88.20	-36.25	57.79	40.48	19.93	66.65	0.40	--	--	Peak	2	21345.00	37.82	74.00	-36.18	40.46	38.10	23.74	54.94	-9.54	--	--	Peak	3	39892.00	54.83	74.00	-19.17	41.53	44.72	34.03	55.91	-9.54	--	--	Peak	4	39892.00	45.63	54.00	-8.37	32.33	44.72	34.03	55.91	-9.54	--	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>14230.00</td><td>52.06</td><td>88.20</td><td>-36.14</td><td>57.90</td><td>40.48</td><td>19.93</td><td>66.65</td><td>0.40</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>21345.00</td><td>38.51</td><td>74.00</td><td>-35.49</td><td>41.15</td><td>38.10</td><td>23.74</td><td>54.94</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>39541.00</td><td>55.49</td><td>74.00</td><td>-18.51</td><td>42.28</td><td>45.32</td><td>33.69</td><td>56.26</td><td>-9.54</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>39541.00</td><td>45.27</td><td>54.00</td><td>-8.73</td><td>32.06</td><td>45.32</td><td>33.69</td><td>56.26</td><td>-9.54</td><td>--</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	14230.00	52.06	88.20	-36.14	57.90	40.48	19.93	66.65	0.40	--	--	Peak	2	21345.00	38.51	74.00	-35.49	41.15	38.10	23.74	54.94	-9.54	--	--	Peak	3	39541.00	55.49	74.00	-18.51	42.28	45.32	33.69	56.26	-9.54	--	--	Peak	4	39541.00	45.27	54.00	-8.73	32.06	45.32	33.69	56.26	-9.54	--	--	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	14230.00	51.95	88.20	-36.25	57.79	40.48	19.93	66.65	0.40	--	--	Peak																																																																																																																																																																						
2	21345.00	37.82	74.00	-36.18	40.46	38.10	23.74	54.94	-9.54	--	--	Peak																																																																																																																																																																						
3	39892.00	54.83	74.00	-19.17	41.53	44.72	34.03	55.91	-9.54	--	--	Peak																																																																																																																																																																						
4	39892.00	45.63	54.00	-8.37	32.33	44.72	34.03	55.91	-9.54	--	--	Average																																																																																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																								
1	14230.00	52.06	88.20	-36.14	57.90	40.48	19.93	66.65	0.40	--	--	Peak																																																																																																																																																																						
2	21345.00	38.51	74.00	-35.49	41.15	38.10	23.74	54.94	-9.54	--	--	Peak																																																																																																																																																																						
3	39541.00	55.49	74.00	-18.51	42.28	45.32	33.69	56.26	-9.54	--	--	Peak																																																																																																																																																																						
4	39541.00	45.27	54.00	-8.73	32.06	45.32	33.69	56.26	-9.54	--	--	Average																																																																																																																																																																						



Mode	35	
	Harmonic	
	U-NII-8_6.875-7.125_802.11be EHT20_CH233_Full RU_7115MHz	
ANT	Chain A+B	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL
	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 HORIZONTAL	Level (dBuV/m) Date: 2026-08-10  Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91280_01620_250915 VERTICAL



38.6G ~40G Avg	Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Horizontal	Date: 2026-08-12 Site : 03CH11-HY Condition: AVG_54 1m SHF_1230_251205 Vertical



		36									
Mode	Band Edge										
	U-NII-8_6.875-7.125_802.11be EHT320_CH191_Full RU_6905MHz										
ANT	Chain A+B										
Pol.	Horizontal										
Peak	<										



		36																																																																																																																											
Mode	Band Edge																																																																																																																												
	U-NII-8_6.875-7.125_802.11be EHT320_CH191_Full RU_6905MHz																																																																																																																												
ANT	Chain A+B																																																																																																																												
Pol.	Vertical						Fundamental																																																																																																																						
Peak	Level (dBuV/m) Date: 2026-08-09 PEAK_BE(UNII)_6E						Level (dBuV/m) Date: 2026-08-09 PEAK(UNII)_6E																																																																																																																						
	Site : 03CH11-HY Condition: PEAK_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Site : 03CH11-HY Condition: PEAK(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7166.71</td><td>58.87</td><td>88.20</td><td>-30.13</td><td>43.14</td><td>36.57</td><td>11.88</td><td>33.52</td><td>0.00</td><td>200</td><td>216</td><td>Peak</td></tr><tr><td>2</td><td>7313.44</td><td>56.88</td><td>74.00</td><td>-17.92</td><td>40.86</td><td>36.85</td><td>11.97</td><td>33.60</td><td>0.00</td><td>200</td><td>216</td><td>Peak</td></tr><tr><td>3</td><td>7935.40</td><td>55.72</td><td>88.20</td><td>-32.48</td><td>40.31</td><td>36.87</td><td>12.32</td><td>33.78</td><td>0.00</td><td>200</td><td>216</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7166.71	58.87	88.20	-30.13	43.14	36.57	11.88	33.52	0.00	200	216	Peak	2	7313.44	56.88	74.00	-17.92	40.86	36.85	11.97	33.60	0.00	200	216	Peak	3	7935.40	55.72	88.20	-32.48	40.31	36.87	12.32	33.78	0.00	200	216	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6905.00</td><td>94.27</td><td>-----</td><td>-----</td><td>80.54</td><td>35.76</td><td>11.28</td><td>33.31</td><td>0.00</td><td>200</td><td>216</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6905.00	94.27	-----	-----	80.54	35.76	11.28	33.31	0.00	200	216
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	7166.71	58.87	88.20	-30.13	43.14	36.57	11.88	33.52	0.00	200	216	Peak																																																																																																																	
2	7313.44	56.88	74.00	-17.92	40.86	36.85	11.97	33.60	0.00	200	216	Peak																																																																																																																	
3	7935.40	55.72	88.20	-32.48	40.31	36.87	12.32	33.78	0.00	200	216	Peak																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	6905.00	94.27	-----	-----	80.54	35.76	11.28	33.31	0.00	200	216	Peak																																																																																																																	
Avg	Level (dBuV/m) Date: 2026-08-09 AVG_BE(UNII)_6E						Level (dBuV/m) Date: 2026-08-09 AVG(UNII)_6E																																																																																																																						
	Site : 03CH11-HY Condition: AVG_BE(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Site : 03CH11-HY Condition: AVG(UNII)_6E 3m 91200_01620_250915 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>7139.33</td><td>47.25</td><td>68.20</td><td>-20.95</td><td>32.46</td><td>36.46</td><td>11.84</td><td>33.51</td><td>0.00</td><td>200</td><td>216</td><td>Average</td></tr><tr><td>2</td><td>7266.35</td><td>46.66</td><td>54.00</td><td>-7.34</td><td>31.38</td><td>36.90</td><td>11.95</td><td>33.57</td><td>0.00</td><td>200</td><td>216</td><td>Average</td></tr><tr><td>3</td><td>8000.00</td><td>45.29</td><td>68.20</td><td>-22.91</td><td>29.77</td><td>36.90</td><td>12.41</td><td>33.79</td><td>0.00</td><td>200</td><td>216</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	7139.33	47.25	68.20	-20.95	32.46	36.46	11.84	33.51	0.00	200	216	Average	2	7266.35	46.66	54.00	-7.34	31.38	36.90	11.95	33.57	0.00	200	216	Average	3	8000.00	45.29	68.20	-22.91	29.77	36.90	12.41	33.79	0.00	200	216	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>6905.00</td><td>84.60</td><td>-----</td><td>-----</td><td>70.94</td><td>35.73</td><td>11.23</td><td>33.30</td><td>0.00</td><td>200</td><td>216</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	6905.00	84.60	-----	-----	70.94	35.73	11.23	33.30	0.00	200	216
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	7139.33	47.25	68.20	-20.95	32.46	36.46	11.84	33.51	0.00	200	216	Average																																																																																																																	
2	7266.35	46.66	54.00	-7.34	31.38	36.90	11.95	33.57	0.00	200	216	Average																																																																																																																	
3	8000.00	45.29	68.20	-22.91	29.77	36.90	12.41	33.79	0.00	200	216	Average																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																			
1	6905.00	84.60	-----	-----	70.94	35.73	11.23	33.30	0.00	200	216	Average																																																																																																																	




Mode	37																																																																																																																																																																																																			
	LF																																																																																																																																																																																																			
	U-NII-8_6.875-7.125_802.11be EHT320_CH191_Full RU_6905MHz																																																																																																																																																																																																			
ANT	Chain A+B																																																																																																																																																																																																			
Pol.	Horizontal	Vertical																																																																																																																																																																																																		
QP/ Peak	Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: QP 3m Bilog_66925 & 24006_260412 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>36.97</td><td>23.27</td><td>40.00</td><td>-16.73</td><td>31.11</td><td>23.23</td><td>0.73</td><td>31.88</td><td>0.08</td><td>-- Peak</td></tr><tr><td>2</td><td>172.59</td><td>27.57</td><td>43.50</td><td>-15.93</td><td>42.44</td><td>15.32</td><td>1.77</td><td>32.02</td><td>0.06</td><td>-- Peak</td></tr><tr><td>3</td><td>278.32</td><td>29.56</td><td>46.00</td><td>-16.44</td><td>40.49</td><td>18.71</td><td>2.22</td><td>31.94</td><td>0.08</td><td>-- Peak</td></tr><tr><td>4</td><td>584.84</td><td>26.38</td><td>46.00</td><td>-19.62</td><td>28.73</td><td>26.03</td><td>3.27</td><td>32.01</td><td>0.36</td><td>-- Peak</td></tr><tr><td>5</td><td>744.89</td><td>32.13</td><td>46.00</td><td>-13.87</td><td>31.00</td><td>27.94</td><td>3.72</td><td>31.89</td><td>0.56</td><td>-- Peak</td></tr><tr><td>6</td><td>958.29</td><td>34.02</td><td>46.00</td><td>-11.98</td><td>29.10</td><td>30.96</td><td>4.17</td><td>30.63</td><td>0.42</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	36.97	23.27	40.00	-16.73	31.11	23.23	0.73	31.88	0.08	-- Peak	2	172.59	27.57	43.50	-15.93	42.44	15.32	1.77	32.02	0.06	-- Peak	3	278.32	29.56	46.00	-16.44	40.49	18.71	2.22	31.94	0.08	-- Peak	4	584.84	26.38	46.00	-19.62	28.73	26.03	3.27	32.01	0.36	-- Peak	5	744.89	32.13	46.00	-13.87	31.00	27.94	3.72	31.89	0.56	-- Peak	6	958.29	34.02	46.00	-11.98	29.10	30.96	4.17	30.63	0.42	-- Peak	Level (dBuV/m) Date: 2026-08-10 Site : 03CH11-HY Condition: QP 3m Bilog_66925 & 24006_260412 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>36.79</td><td>24.83</td><td>40.00</td><td>-15.17</td><td>35.01</td><td>20.99</td><td>0.80</td><td>32.00</td><td>0.03</td><td>-- Peak</td></tr><tr><td>2</td><td>60.07</td><td>25.80</td><td>40.00</td><td>-14.20</td><td>45.05</td><td>11.65</td><td>0.99</td><td>31.98</td><td>0.09</td><td>-- Peak</td></tr><tr><td>3</td><td>288.99</td><td>26.21</td><td>46.00</td><td>-19.79</td><td>36.85</td><td>18.95</td><td>2.27</td><td>31.94</td><td>0.08</td><td>-- Peak</td></tr><tr><td>4</td><td>734.22</td><td>29.13</td><td>46.00</td><td>-16.87</td><td>29.07</td><td>27.68</td><td>3.69</td><td>31.90</td><td>0.59</td><td>-- Peak</td></tr><tr><td>5</td><td>904.94</td><td>33.03</td><td>46.00</td><td>-12.97</td><td>30.52</td><td>29.09</td><td>4.09</td><td>31.14</td><td>0.47</td><td>-- Peak</td></tr><tr><td>6</td><td>948.59</td><td>33.83</td><td>46.00</td><td>-12.17</td><td>29.24</td><td>30.77</td><td>4.14</td><td>30.72</td><td>0.40</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	36.79	24.83	40.00	-15.17	35.01	20.99	0.80	32.00	0.03	-- Peak	2	60.07	25.80	40.00	-14.20	45.05	11.65	0.99	31.98	0.09	-- Peak	3	288.99	26.21	46.00	-19.79	36.85	18.95	2.27	31.94	0.08	-- Peak	4	734.22	29.13	46.00	-16.87	29.07	27.68	3.69	31.90	0.59	-- Peak	5	904.94	33.03	46.00	-12.97	30.52	29.09	4.09	31.14	0.47	-- Peak	6	948.59	33.83	46.00	-12.17	29.24	30.77	4.14	30.72	0.40	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																										
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																										
1	36.97	23.27	40.00	-16.73	31.11	23.23	0.73	31.88	0.08	-- Peak																																																																																																																																																																																										
2	172.59	27.57	43.50	-15.93	42.44	15.32	1.77	32.02	0.06	-- Peak																																																																																																																																																																																										
3	278.32	29.56	46.00	-16.44	40.49	18.71	2.22	31.94	0.08	-- Peak																																																																																																																																																																																										
4	584.84	26.38	46.00	-19.62	28.73	26.03	3.27	32.01	0.36	-- Peak																																																																																																																																																																																										
5	744.89	32.13	46.00	-13.87	31.00	27.94	3.72	31.89	0.56	-- Peak																																																																																																																																																																																										
6	958.29	34.02	46.00	-11.98	29.10	30.96	4.17	30.63	0.42	-- Peak																																																																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																										
1	36.79	24.83	40.00	-15.17	35.01	20.99	0.80	32.00	0.03	-- Peak																																																																																																																																																																																										
2	60.07	25.80	40.00	-14.20	45.05	11.65	0.99	31.98	0.09	-- Peak																																																																																																																																																																																										
3	288.99	26.21	46.00	-19.79	36.85	18.95	2.27	31.94	0.08	-- Peak																																																																																																																																																																																										
4	734.22	29.13	46.00	-16.87	29.07	27.68	3.69	31.90	0.59	-- Peak																																																																																																																																																																																										
5	904.94	33.03	46.00	-12.97	30.52	29.09	4.09	31.14	0.47	-- Peak																																																																																																																																																																																										
6	948.59	33.83	46.00	-12.17	29.24	30.77	4.14	30.72	0.40	-- Peak																																																																																																																																																																																										




Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
Chain A+B	6GHz 802.11be EHT20 Full RU	98.76	-	-	10Hz
Chain A+B	6GHz 802.11be EHT160 Full RU	98.89	-	-	10Hz
Chain A+B	6GHz 802.11be EHT320 Full RU	98.76	-	-	10Hz

802.11be EHT20 Full RU



802.11be EHT160 Full RU



802.11be EHT320 Full RU

