



FCC RADIO TEST REPORT

FCC ID : ACJ9TGWW24E
Equipment : Radio Module
Brand Name : Panasonic
Model Name : WW24E
Applicant : Panasonic Corporation of North America
Two Riverfront Plaza, Newark, New Jersey, 07102-5490, USA
Standard : FCC 47 CFR Part 2, 96

The product was received on Mar. 09, 2026 and testing was performed from Mar. 21, 2026 to Aug. 24, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Site	6
1.4 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode	7
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system	8
2.4 Measurement Results Explanation Example	9
2.5 Frequency List of Low/Middle/High Channels	10
3 Conducted Test Items	12
3.1 Measuring Instruments	12
3.2 Conducted Output Power Measurement	13
3.3 EIRP and Power Density	14
3.4 Occupied Bandwidth	15
3.5 Conducted Band Edge	16
3.6 Conducted Spurious Emission	17
4 Radiated Test Items	18
4.1 Measuring Instruments	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test	19
4.4 Radiated Spurious Emission	20
5 List of Measuring Equipment.....	21
6 Measurement Uncertainty	22
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FG612314-01D	01	Initial issue of report	Sep. 14, 2026
FG612314-01D	02	Revised Appendix A2 This report is an updated version, replacing the report issued on Sep. 14, 2026.	Sep. 23, 2026



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
-	§96.41	Peak-to-Average Ratio	Pass	See Note
3.3	§96.41	Effective Isotropic Radiated Power TRP	Pass	-
		Power Density	Pass	-
3.4	§2.1049	Occupied Bandwidth	Pass	-
3.5	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	-
3.6	§2.1051 §96.41	Conducted Spurious Emission	Pass	-
-	§2.1055	Frequency Stability for Temperature & Voltage	Pass	See Note
4.4	§2.1053 §96.41	Radiated Spurious Emission	Pass	-

Remark:

1. For host device, except for LTE B48B is full test, other band is the spot check Radiated Spurious Emission and complies with the limit in this test report.
2. For host device, except for LTE B48B is full test, other band is the spot check, the Conducted Output Power is no difference after compared to module (Model: WW24E)

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng**Report Producer: Julia Chang**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs WCDMA /LTE/5G NR/NTN	
Antenna Type WWAN: Monopole Antenna	

Remark: The product was installed into Personal Computer (Brand Name: Panasonic, Model Name: FZ-G3(mk1) during test.

Support band and evaluated information	
Supported band	B48, B48B, B48C
Evaluated and Tested band	B48, B48B, B48C

TDD band Power Class				
	PC3			
B48/B48B/B48C	V			

Antenna information(dBi)						
Band	Ant 1 (WWAN-3rd)	Ant 3 (WWAN-4th)		SISO&ENDC Main Ant. #		
B48	2.18	1.21		3&1		

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.



1.3 Testing Site

Test Site	Sporton International Inc. Wensan Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH20-HY
Test Engineer	Kevin Xiao	John Chuang 、 David Dai 、 Sam Chou
Temperature (°C)	21.1~23.3	18.8~22.8
Relative Humidity (%)	50.3~55.2	63.4~70.9

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW3786

1.4 Applied Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168

D01 Power Meas. License Digital Systems v03r01 with maximum output power.

For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and Laptop /Tablet/Convertible mode and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape) and accessory (Keyboard), and adjusting the measurement antenna orientation, following C63.26 exploratory test procedures and only the worst case emissions were reported in this report.

Modulation Type	Modulation
A	QPSK
B	16QAM
C	64QAM
D	256QAM

LTE B48

Test Item	Modulation Type	Bandwidth	RB Size	Channel
Conducted Power	A, B,C	All	1RB	L, M, H
EIRP	A, B,C	All	1RB	L, M, H
RSE	A	Max	1RB	M

Remark:

1. Evaluated all the transmitter signal and reporting worst-case configuration among all modulation types.
2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst-case emissions are reported.

LTE B48C

Test Item	Modulation Type	Bandwidth	RB Size	Channel
Conducted Power	A, B,C,D	All	1RB	L, M, H
EIRP	A, B,C,D	All	1RB	L, M, H
RSE	A	Max	1RB	M

Remark:

1. Evaluated all the transmitter signal and reporting worst-case configuration among all modulation types.
2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst-case emissions are reported.


B48B

Test Item	Modulation Type	Bandwidth	RB Size	Channel
Conducted Power	A, B, C, D	10+10 MHz	1, Half, Full	L, M, H
EIRP	A, B, C, D	10+10 MHz	1, Half, Full	L, M, H
Bandwidth	A, B	10+10 MHz	Full	M
ACLR, Mask	A	10+10 MHz	1RB Full	L, M, H
CSE	A	10+10 MHz	1RB	L, M, H
RSE	A	10+10 MHz	1RB	L, M, H

Remark:

1. Evaluated all the transmitter signal and reporting worst-case configuration among all modulation types.
2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst-case emissions are reported.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Notebook	DELL	Latitude5310	N/A	N/A	N/A
2.	Base Station	Anritsu	MT8821C	N/A	N/A	N/A
3.	Base Station	Anritsu	MT8000A	N/A	N/A	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.5 dB and 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560	3625	3690
15	Channel	55315	55990	56665
	Frequency	3557.5	3625	3692.5
10	Channel	55290	55990	56690
	Frequency	3555	3625	3695
5	Channel	55265	55990	56715
	Frequency	3552.5	3625	3697.5

LTE Band 48B Channel and Frequency List_CA					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
10+10	PCC	Channel	55290	55945	56591
		Frequency	3555	3623.5	3685.1
	SCC	Channel	55389	56044	56690
		Frequency	3564.9	3630.4	3695



LTE Band 48C 3550MHz ~ 3700MHz Channel and Frequency List_CA (Part96)					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	55340	55891	56442
		Frequency	3560	3615.1	3670.2
	SCC	Channel	55538	56089	56640
		Frequency	3579.8	3634.9	3690.0
20 + 15	PCC	Channel	55340	55916	56491
		Frequency	3560	3617.6	3675.1
	SCC	Channel	55511	56087	56662
		Frequency	3577.1	3634.7	3692.2
15 + 20	PCC	Channel	55318	55893	56469
		Frequency	3557.8	3615.3	3672.9
	SCC	Channel	55489	56064	56640
		Frequency	3574.9	3632.4	3690.0
20 + 10	PCC	Channel	55340	55941	56541
		Frequency	3560	3620.1	3680.1
	SCC	Channel	55484	56085	56685
		Frequency	3574.4	3634.5	3694.5
10 + 20	PCC	Channel	55295	55896	56496
		Frequency	3555.5	3615.6	3675.6
	SCC	Channel	55439	56040	56640
		Frequency	3569.9	3630	3690
20 + 5	PCC	Channel	55340	55965	56590
		Frequency	3560	3622.5	3685
	SCC	Channel	55457	56082	56707
		Frequency	3571.7	3634.2	3696.7
5 + 20	PCC	Channel	55273	55896	56523
		Frequency	3553.3	3615.6	3678.3
	SCC	Channel	55390	56015	56640
		Frequency	3565	3627.5	3690.0


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 EIRP and Power Density, Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, and Conducted Spurious Emission



3.1.4 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement

3.2.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 EIRP and Power Density

3.3.1 Description of the EIRP and Power Density Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for LTE Band 48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5.

According to KDB 412172 D01 Power Approach,

$EIRP = PT + GT - LC$, where

PT = transmitter output power in dBm

GT = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

Device	Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a
Category A CBSD	30	20
Category B CBSD	47	37

Remark:

Total channel power is complied with EIRP limit 23dBm/10MHz.

3.3.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 CBRS Eqpt v03 Section 3.2(b)(2)

Determine the EIRP by adding the effective antenna gain to the measured average conducted power level.



3.4 Occupied Bandwidth

3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.4.2 Test Procedures

The testing follows ANSI C63.26-2015 Section 5.4.3 (26dB) and Section 5.4.4 (99OB)

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
3. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
4. Set the detection mode to peak, and the trace mode to max hold.
5. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
6. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
7. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
8. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.5 Conducted Band Edge

3.5.1 Description of Conducted Band Edge Measurement

The conducted power of any End User Device emission outside the fundamental emission (whether in or outside of the authorized band) shall not exceed -13 dBm/MHz within 0 to B megahertz (where B is the bandwidth in megahertz of the assigned channel or multiple contiguous channels of the End User Device) above the upper CBSD-assigned channel edge and within 0 to B megahertz below the lower CBSD-assigned channel edge. At all frequencies greater than B megahertz above the upper CBSD assigned channel edge and less than B megahertz below the lower CBSD-assigned channel edge, the conducted power of any End User Device emission shall not exceed -25 dBm/MHz. Notwithstanding the emission limits in this paragraph, the Adjacent Channel Leakage Ratio for End User Devices shall be at least 30 dB.

3.5.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

For Adjacent Channel Leakage Ratio (ACLR) measurement,

1. The Adjacent Channel Leakage Ratio (ACLR) is the ratio of the average power in the assigned aggregated channel bandwidth to the average power over the equivalent adjacent channel bandwidth.
2. The option ACLR of spectrum analyzer is used and measures the ACLR ratio by setting equivalent channel bandwidth.
3. The measured ACLR ratio shall be at least 30 dB.



3.6 Conducted Spurious Emission

3.6.1 Description of Conducted Spurious Emission Measurement

96.41 (e)(2)

The conducted power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

3.6.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 6.1.

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
6. Set spectrum analyzer with RMS detector.
7. Taking the record of maximum spurious emission.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The test reduction is applied to 1RB case for 10MHz Bandwidth to cover the all operation bandwidths. RBW 500kHz is applied to the 0-1MHz offset from the edge of the frequency block group for 1RB mode in order to represent the worst case condition.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI C63.26-2015 section 5.5.7 Radiated measurement using the field strength method.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. To convert spectrum reading E(dBuV/m) to EIRP(dBm)
$$\text{EIRP(dBm)} = \text{Level (dBuV/m)} + 20\log(d) - 104.77,$$
where d is the distance at which field strength limit is specified in the rules
8. Field Strength Level (dBm) = Spectrum Reading (dBm) + Antenna Factor + Cable Loss + Read Level - Preamp Factor.
9. ERP (dBm) = EIRP (dBm) - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A(MXE)	MY54130085	N/A	Oct. 16, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Oct. 15, 2026	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Dec. 10, 2026	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060873	18GHz~40GHz	Aug. 26, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Aug. 25, 2026	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Jul. 17, 2026 ~ Aug. 24, 2026	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Jul. 17, 2026 ~ Aug. 24, 2026	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Jul. 17, 2026 ~ Aug. 24, 2026	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	10Hz~44GHz	Dec. 10, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Dec. 09, 2026	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01 N-06	47020 & 06	30MHz~1GHz	Oct. 04, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Oct. 03, 2026	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 05, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Nov. 04, 2026	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1230	18GHz-40GHz	Nov. 05, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Nov. 04, 2026	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Dec. 30, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Dec. 29, 2026	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 11, 2025	Jul. 17, 2026 ~ Aug. 24, 2026	Nov. 10, 2026	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,804015/2,25104239	N/A	Apr. 13, 2026	Jul. 17, 2026 ~ Aug. 24, 2026	Apr. 12, 2027	Radiation (03CH20-HY)
Hygrometer	TECPEL	DTM-303A	TP211382	N/A	May. 24, 2026	Jul. 17, 2026 ~ Aug. 24, 2026	May. 23, 2027	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Jul. 17, 2026 ~ Aug. 24, 2026	N/A	Radiation (03CH20-HY)
Radio Communication Analyzer	Anritsu	MT8821C	6262025341	LTE FDD/TDD LTE-2CC ULCA/DLCA	Sep. 16, 2025	Mar. 21, 2026~ Jul. 23, 2026	Sep. 15, 2026	Conducted (TH05-HY)
Power divider	MVE	MVE8283	#Z	0.009MHz-18G Hz	Oct. 16, 2025	Mar. 21, 2026~ Jul. 23, 2026	Oct. 15, 2026	Conducted (TH05-HY)
Power Divider	MVE	MVE8283	F201918	9KHz~40GHz	Dec. 31,2025	Mar. 21, 2026~ Jul. 23, 2026	Dec. 30,2026	Conducted (TH05-HY)
Software	Sporton	LTE Conducted Test Tools	N/A	Conducted Test Item	N/A	Mar. 21, 2026~ Jul. 23, 2026	N/A	Conducted (TH05-HY)
Hygrometer	TECPEL	DTM-303B	TP200886	-10 ~ 50°C / 20 ~ 95%RH	Mar. 04,2026	Mar. 21, 2026~ Jul. 23, 2026	Mar. 03,2027	Conducted (TH05-HY)



6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 6 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.70 dB
---	---------

Uncertainty of Radiated Emission Measurement (6 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.70 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20 dB
---	---------

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power and EIRP)

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 2.18 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+20	100	0	100	0	QPSK	14.94	15.20	15.06	19.19	0.0830
20+20	1	0	1	99		8.42	8.57	8.48		
20+20	1	99	1	0		16.73	17.01	16.84		
20+20	1	0	0	0		16.73	16.80	16.66		
20+20	100	0	100	0	16-QAM	13.92	14.20	14.03	18.71	0.0743
20+20	1	0	1	99		8.94	9.12	8.96		
20+20	1	99	1	0		16.21	16.53	16.36		
20+20	1	0	0	0		16.28	16.49	16.26		
20+20	100	0	100	0	64-QAM	13.87	14.12	14.01	17.71	0.0590
20+20	1	0	1	99		8.87	9.05	8.78		
20+20	1	99	1	0		15.29	15.53	15.38		
20+20	100	0	100	0	256-QAM	11.92	12.21	12.04	14.63	0.0290
20+20	1	0	1	99		8.62	8.77	8.59		
20+20	1	99	1	0		12.10	12.45	12.12		
20+15	100	0	75	0	QPSK	14.89	15.18	15.04	19.13	0.0818
20+15	1	0	1	74		8.44	8.66	8.46		
20+15	1	99	1	0		16.77	16.95	16.82		
20+15	1	0	0	0		16.70	16.87	16.67		
20+15	100	0	75	0	16-QAM	13.92	14.19	14.01	18.68	0.0738
20+15	1	0	1	74		8.85	9.10	8.95		
20+15	1	99	1	0		16.25	16.50	16.38		
20+15	1	0	0	0		16.29	16.48	16.31		
20+15	100	0	75	0	64-QAM	13.93	14.16	13.96	17.8	0.0603
20+15	1	0	1	74		8.85	9.11	8.83		
20+15	1	99	1	0		15.23	15.62	15.44		
20+15	100	0	75	0	256-QAM	11.91	12.20	12.03	14.6	0.0288
20+15	1	0	1	74		8.65	8.78	8.67		
20+15	1	99	1	0		12.01	12.42	12.22		
15+20	75	0	100	0	QPSK	14.94	15.21	15.07	19.15	0.0822
15+20	1	0	1	99		8.38	8.64	8.46		
15+20	1	74	1	0		16.71	16.97	16.84		
15+20	1	0	0	0		16.67	16.82	16.66		
15+20	75	0	100	0	16-QAM	13.95	14.23	14.03	18.70	0.0741
15+20	1	0	1	99		8.95	9.16	8.86		
15+20	1	74	1	0		16.30	16.45	16.48		
15+20	1	0	0	0		16.32	16.52	16.32		
15+20	75	0	100	0	64-QAM	13.94	14.17	14.01	17.66	0.0583
15+20	1	0	1	99		8.79	9.08	8.84		
15+20	1	74	1	0		15.26	15.48	15.47		
15+20	75	0	100	0	256-QAM	11.98	12.21	12.04	14.65	0.0292
15+20	1	0	1	99		8.57	8.74	8.57		
15+20	1	74	1	0		12.03	12.47	12.29		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 2.18 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+10	100	0	50	0	QPSK	14.93	15.17	15.04	19.18	0.0828
20+10	1	0	1	49		8.50	8.73	8.49		
20+10	1	99	1	0		16.79	17.00	16.86		
20+10	1	0	0	0		16.74	16.90	16.69		
20+10	100	0	50	0	16-QAM	13.93	14.21	14.00	18.71	0.0743
20+10	1	0	1	49		8.99	9.20	9.00		
20+10	1	99	1	0		16.32	16.51	16.38		
20+10	1	0	0	0		16.33	16.53	16.39		
20+10	100	0	50	0	64-QAM	13.92	14.16	13.97	17.69	0.0587
20+10	1	0	1	49		8.83	9.11	8.83		
20+10	1	99	1	0		15.27	15.51	15.41		
20+10	100	0	50	0	256-QAM	11.91	12.21	12.01	14.61	0.0289
20+10	1	0	1	49		8.65	8.96	8.54		
20+10	1	99	1	0		12.18	12.43	12.24		
10+20	50	0	100	0	QPSK	14.91	15.23	15.06	19.20	0.0832
10+20	1	0	1	99		8.42	8.73	8.53		
10+20	1	49	1	0		16.75	17.02	16.86		
10+20	1	0	0	0		16.75	16.92	16.76		
10+20	50	0	100	0	16-QAM	13.94	14.23	14.06	18.81	0.0760
10+20	1	0	1	99		8.98	9.21	9.02		
10+20	1	49	1	0		16.33	16.63	16.40		
10+20	1	0	0	0		16.39	16.58	16.43		
10+20	50	0	100	0	64-QAM	13.98	14.18	14.03	17.73	0.0593
10+20	1	0	1	99		8.77	9.09	8.99		
10+20	1	49	1	0		15.25	15.55	15.40		
10+20	50	0	100	0	256-QAM	11.92	12.25	12.08	14.59	0.0288
10+20	1	0	1	99		8.41	8.82	8.61		
10+20	1	49	1	0		12.07	12.41	12.27		
20+5	100	0	25	0	QPSK	14.93	15.16	15.02	19.20	0.0832
20+5	1	0	1	24		8.41	8.72	8.49		
20+5	1	99	1	0		16.85	17.02	16.85		
20+5	1	0	0	0		16.70	16.93	16.72		
20+5	100	0	25	0	16-QAM	13.91	14.20	13.99	18.77	0.0753
20+5	1	0	1	24		8.97	9.24	8.98		
20+5	1	99	1	0		16.27	16.55	16.47		
20+5	1	0	0	0		16.32	16.59	16.46		
20+5	100	0	25	0	64-QAM	13.92	14.16	13.95	17.67	0.0585
20+5	1	0	1	24		8.76	9.09	8.95		
20+5	1	99	1	0		15.25	15.46	15.49		
20+5	100	0	25	0	256-QAM	11.94	12.17	11.99	14.59	0.0288
20+5	1	0	1	24		8.42	8.81	8.61		
20+5	1	99	1	0		12.12	12.41	12.32		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 2.18 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
5+20	25	0	100	0	QPSK	14.90	15.25	15.06	19.21	0.0834
5+20	1	0	1	99		8.36	8.66	8.46		
5+20	1	24	1	0		16.77	17.03	16.88		
5+20	1	0	0	0		16.64	16.90	16.73		
5+20	25	0	100	0	16-QAM	13.94	14.24	14.04	18.82	0.0762
5+20	1	0	1	99		8.83	9.18	8.95		
5+20	1	24	1	0		16.35	16.64	16.44		
5+20	1	0	0	0		16.35	16.55	16.42		
5+20	25	0	100	0	64-QAM	13.90	14.20	14.02	17.85	0.0610
5+20	1	0	1	99		8.72	9.13	9.00		
5+20	1	24	1	0		15.30	15.67	15.42		
5+20	25	0	100	0	256-QAM	11.89	12.23	12.05	14.64	0.0291
5+20	1	0	1	99		8.46	8.81	8.71		
5+20	1	24	1	0		12.02	12.46	12.11		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48B_CA Maximum Average Power [dBm] (GT - LC = 2.18 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
10+10	50	0	50	0	QPSK	15.01	15.27	15.06	19.19	0.0830
10+10	1	0	1	49		6.37	6.70	6.45		
10+10	1	49	1	0		16.74	17.01	16.85		
10+10	1	0	0	0		16.78	17.01	16.83		
10+10	50	0	50	0	16-QAM	13.99	14.28	14.08	18.76	0.0752
10+10	1	0	1	49		6.85	7.22	6.96		
10+10	1	49	1	0		16.35	16.53	16.45		
10+10	1	0	0	0		16.31	16.58	16.41		
10+10	50	0	50	0	64-QAM	14.00	14.24	14.02	17.75	0.0596
10+10	1	0	1	49		6.82	7.08	6.90		
10+10	1	49	1	0		15.24	15.57	15.42		
10+10	50	0	50	0	256-QAM	12.00	12.29	12.03	14.63	0.0290
10+10	1	0	1	49		6.53	6.79	6.84		
10+10	1	49	1	0		12.15	12.45	12.25		
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 2.18 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
20	1	0	QPSK	17.08	17.11	17.33	19.51	0.0893
20	1	49		17.00	17.05	17.17		
20	1	99		17.06	17.06	17.09		
20	50	0		16.19	16.41	16.46		
20	50	24		16.06	16.28	16.38		
20	50	50		16.16	16.24	16.43		
20	100	0		16.12	16.17	16.44		
20	1	0	16-QAM	16.40	16.26	16.38	18.58	0.0721
20	1	49		16.07	16.23	16.27		
20	1	99		16.10	16.11	16.13		
20	50	0		15.08	15.24	15.48		
20	50	24		15.07	15.26	15.36		
20	50	50		15.15	15.15	15.31		
20	100	0		15.06	15.23	15.41		
20	1	0	64-QAM	15.30	15.01	15.39	17.57	0.0571
20	1	49		15.08	15.10	15.27		
20	1	99		15.18	15.00	15.07		
20	50	0		14.21	14.38	14.37		
20	50	24		14.07	14.36	14.42		
20	50	50		14.17	14.19	14.26		
20	100	0		14.07	14.17	14.34		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 2.18 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
15	1	0	QPSK	17.03	17.09	17.20	19.38	0.0867
15	1	37		17.02	17.00	17.09		
15	1	74		17.00	17.00	17.00		
15	36	0		16.09	16.35	16.35		
15	36	20		16.00	16.24	16.28		
15	36	39		16.07	16.15	16.34		
15	75	0		16.03	16.09	16.38		
15	1	0	16-QAM	16.28	16.16	16.34	18.52	0.0711
15	1	37		16.03	16.17	16.17		
15	1	74		16.06	16.07	16.01		
15	36	0		15.03	15.21	15.46		
15	36	20		15.02	15.21	15.28		
15	36	39		15.07	15.03	15.28		
15	75	0		15.04	15.18	15.26		
15	1	0	64-QAM	15.17	15.02	15.31	17.49	0.0561
15	1	37		15.02	15.07	15.12		
15	1	74		15.14	15.00	15.01		
15	36	0		14.08	14.30	14.25		
15	36	20		14.04	14.33	14.29		
15	36	39		14.06	14.05	14.13		
15	75	0		14.03	14.06	14.23		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 2.18 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK	17.07	17.05	17.25	19.43	0.0877
10	1	25		17.01	17.04	17.06		
10	1	49		17.00	17.05	17.00		
10	25	0		16.14	16.35	16.33		
10	25	12		16.02	16.16	16.26		
10	25	25		16.05	16.10	16.40		
10	50	0		16.02	16.11	16.40		
10	1	0	16-QAM	16.28	16.22	16.25	18.46	0.0701
10	1	25		16.00	16.19	16.12		
10	1	49		16.01	16.02	16.08		
10	25	0		15.01	15.21	15.41		
10	25	12		15.00	15.14	15.25		
10	25	25		15.01	15.10	15.17		
10	50	0		15.02	15.17	15.34		
10	1	0	64-QAM	15.22	15.00	15.31	17.49	0.0561
10	1	25		15.06	15.00	15.14		
10	1	49		15.16	15.00	15.02		
10	25	0		14.14	14.27	14.27		
10	25	12		14.00	14.28	14.39		
10	25	25		14.05	14.13	14.13		
10	50	0		14.03	14.10	14.25		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 2.18 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	17.00	17.02	17.20	19.38	0.0867
5	1	12		17.01	17.02	17.07		
5	1	24		17.00	17.00	17.01		
5	12	0		16.10	16.33	16.42		
5	12	7		16.00	16.15	16.25		
5	12	13		16.14	16.22	16.29		
5	25	0		16.03	16.15	16.32		
5	1	0	16-QAM	16.25	16.13	16.36	18.54	0.0714
5	1	12		16.04	16.08	16.18		
5	1	24		16.00	16.03	16.01		
5	12	0		15.00	15.09	15.35		
5	12	7		15.00	15.22	15.26		
5	12	13		15.10	15.02	15.30		
5	25	0		15.01	15.12	15.32		
5	1	0	64-QAM	15.27	15.01	15.25	17.45	0.0556
5	1	12		15.00	15.06	15.19		
5	1	24		15.07	15.01	15.03		
5	12	0		14.10	14.31	14.25		
5	12	7		14.02	14.32	14.40		
5	12	13		14.13	14.04	14.15		
5	25	0		14.04	14.03	14.32		
Limit	EIRP < 23dBm/10MHz			Result			Pass	


Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



LTE Band 48B

26dB Bandwidth


Mode	LTE Band 48B : 26dB BW(MHz)	
	10MHz+10MHz	
BW	QPSK	16QAM
Middle CH	19.60	19.80





Occupied Bandwidth

Mode	LTE Band 48B : 99%OBW(MHz)	
	10MHz+10MHz	
BW	QPSK	16QAM
Middle CH	18.85	18.67






ACLR

LTE Band 48B / 10MHz+10MHz


QPSK

Lowest Channel / 1RB0 and 1RB49

Lowest Channel / 1RB49 and 1RB0




Date: 7.MAY.2026 03:58:15



Date: 7.MAY.2026 03:59:08

Lowest Channel / FullRB

N/A



Date: 7.MAY.2026 03:57:21





LTE Band 48B / 10MHz+10MHz

QPSK


Middle Channel / 1RB0 and 1RB49

Middle Channel / 1RB49 and 1RB0



Middle Channel / FullRB

N/A







LTE Band 48B / 10MHz+10MHz

QPSK


Highest Channel / 1RB0 and 1RB49

Highest Channel / 1RB49 and 1RB0



Highest Channel / FullRB

N/A






Conducted Band Edge

LTE Band 48B / 10MHz+10MHz


QPSK

Lowest Band Edge / 1RB0 and 1RB49




Date: 7.MAY.2026 03:47:17

Middle Band Edge / 1RB0 and 1RB49




Date: 7.MAY.2026 03:51:12

Lowest Band Edge / 1RB49 and 1RB0




Date: 7.MAY.2026 03:48:34

Middle Band Edge / 1RB49 and 1RB0




Date: 7.MAY.2026 03:52:28

Lowest Band Edge / Full RB



Date: 7.MAY.2026 03:46:01

Middle Band Edge / Full RB



Date: 7.MAY.2026 03:49:55




LTE Band 48B / 10MHz+10MHz

QPSK


Highest Band Edge / 1RB0 and 1RB49

N/A




Highest Band Edge / 1RB49 and 1RB0

N/A



Highest Band Edge / Full RB

N/A






Conducted Spurious Emission

LTE Band 48B / 10MHz+10MHz


QPSK

Lowest Channel / 1RB0 and 1RB49

Lowest Channel / 1RB49 and 1RB0




Date: 7.MAY.2026 04:07:36




Date: 7.MAY.2026 04:26:23

Middle Channel / 1RB0 and 1RB49

Middle Channel / 1RB49 and 1RB0



Date: 7.MAY.2026 04:09:09



Date: 7.MAY.2026 04:27:54




LTE Band 48B / 10MHz+10MHz


QPSK

Highest Channel / 1RB0 and 1RB49

Highest Channel / 1RB49 and 1RB0




Date: 7.MAY.2026 04:13:35




Date: 7.MAY.2026 04:32:23

Lowest Channel / 1RB0 and 1RB49

Lowest Channel / 1RB49 and 1RB0



Date: 7.MAY.2026 04:06:07



Date: 7.MAY.2026 04:24:55




LTE Band 48B / 10MHz+10MHz


QPSK

Middle Channel / 1RB0 and 1RB49

Middle Channel / 1RB49 and 1RB0




Date: 7.MAY.2026 04:10:36




Date: 7.MAY.2026 04:29:23

Highest Channel / 1RB0 and 1RB49

Highest Channel / 1RB49 and 1RB0



Date: 7.MAY.2026 04:12:07



Date: 7.MAY.2026 04:30:54



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	John Chuang、David Dai、Sam Chou	Relative Humidity(%):	63.4~70.9
		Temperature(°C):	18.8~22.8

B1. Summary of each worse mode

Mode	Band	Part	Ch	Freq (MHz)	Level (dBm)	Det	Ant Factor (dB)	AmplCbl (dB)	Filter (dB)	EIRPCF (dB)	Reading (dBuV)	Limit (dBm)	Margin (dB)	Pol	Ant
1	LTE B48	Part 96	L	14204	-51.59	RMS	40.28	-24.68	0.88	-95.23	27.16	-40.00	-11.59	V	3
2	LTE CA B48C	Part 96	L	14275	-51.70	RMS	40.15	-24.69	0.87	-95.23	27.21	-40.00	-11.70	V	3
6	LTE CA B48B	Part 96	L	14275	-51.68	RMS	40.15	-24.69	0.87	-95.23	27.23	-40.00	-11.68	H	3




Ant. 3


Part 96 Mode 1

LTE B48 20M Ch55340 1RB0 QPSK

L



Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin	Pol
			Factor	1		g			
MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1 7102.00	-55.17	RMS	36.41	-24.45	1.27	-95.23	26.83	-40.00	-15.17 Horizontal
2 10653.00	-53.98	RMS	39.19	-24.91	0.65	-95.23	26.32	-40.00	-13.98 Horizontal
3 14204.00	-51.93	RMS	40.28	-24.68	0.88	-95.23	26.82	-40.00	-11.93 Horizontal



Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin	Pol
			Factor	1		g			
MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1 7102.00	-55.47	RMS	36.41	-24.45	1.27	-95.23	26.53	-40.00	-15.47 Vertical
2 10653.00	-53.72	RMS	39.19	-24.91	0.65	-95.23	26.58	-40.00	-13.72 Vertical
3 14204.00	-51.59	RMS	40.28	-24.68	0.88	-95.23	27.16	-40.00	-11.59 Vertical




Ant. 3

Part 96 Mode 1

LTE B48 20M Ch55990 1RB0 QPSK

M




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 20M Ch55990 1RB0 QPSK

	Freq	Level	Detector	Ant Factor	Amp\Cb		Filter 1	EIRPCF	Reading	Limit	Margin Pol	
					dB/m	dB						
1	7232.00	-55.05	RMS	36.93	-24.45	1.10	-95.23	26.60	-40.00	-15.05	Horizontal	
2	10848.00	-53.81	RMS	39.00	-24.90	0.66	-95.23	26.66	-40.00	-13.81	Horizontal	
3	14464.00	-52.13	RMS	39.96	-24.73	0.85	-95.23	27.02	-40.00	-12.13	Horizontal	



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 20M Ch55990 1RB0 QPSK

	Freq	Level	Detector	Ant Factor	Amp\Cb		Filter 1	EIRPCF	Reading	Limit	Margin Pol	
					dB/m	dB						
1	7232.00	-55.54	RMS	36.93	-24.45	1.10	-95.23	26.11	-40.00	-15.54	Vertical	
2	10848.00	-54.01	RMS	39.00	-24.90	0.66	-95.23	26.46	-40.00	-14.01	Vertical	
3	14464.00	-52.17	RMS	39.96	-24.73	0.85	-95.23	26.98	-40.00	-12.17	Vertical	




Ant. 3

Part 96 Mode 1

LTE B48 20M Ch56640 1RB0 QPSK

H




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 20M Ch56640 1RB0 QPSK

	Freq Level		Detector	Ant Factor	Amp\Cb Filter 1		EIRPCF	Reading	Limit		Margin	Pol
	MHz	dBm			dB/m	dB	dB	dBuV	dBm	dB		
1	7362.00	-55.88	RMS	36.55	-24.42	1.04	-95.23	26.18	-40.00	-15.88	Horizontal	
2	11043.00	-53.93	RMS	38.90	-24.91	0.66	-95.23	26.65	-40.00	-13.93	Horizontal	
3	14724.00	-52.63	RMS	39.90	-24.86	0.81	-95.23	26.75	-40.00	-12.63	Horizontal	



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 20M Ch56640 1RB0 QPSK

	Freq Level		Detector	Ant Factor	Amp\Cb Filter 1		EIRPCF	Reading	Limit		Margin	Pol
	MHz	dBm			dB/m	dB	dB	dBuV	dBm	dB		
1	7362.00	-55.77	RMS	36.55	-24.42	1.04	-95.23	26.29	-40.00	-15.77	Vertical	
2	11043.00	-53.54	RMS	38.90	-24.91	0.66	-95.23	27.04	-40.00	-13.54	Vertical	
3	14724.00	-53.07	RMS	39.90	-24.86	0.81	-95.23	26.31	-40.00	-13.07	Vertical	




Ant. 3

Part 96 Mode 2

LTE CA B48C 20M + 20M Ch55340 1RB99 QPSK + Ch55538 1RB0 QPSK

L




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 20M Ch55340 1RB99 QPSK

: LTE B48 20M Ch55538 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7137.00	-55.45	RMS	36.62	-24.46	1.21	-95.23		26.41	-40.00	-15.45		Horizontal
2	10706.00	-53.62	RMS	39.10	-24.90	0.65	-95.23		26.76	-40.00	-13.62		Horizontal
3	14275.00	-51.89	RMS	40.15	-24.69	0.87	-95.23		27.02	-40.00	-11.89		Horizontal



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 20M Ch55340 1RB99 QPSK

: LTE B48 20M Ch55538 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7137.00	-55.35	RMS	36.62	-24.46	1.21	-95.23		26.51	-40.00	-15.35		Vertical
2	10706.00	-53.60	RMS	39.10	-24.90	0.65	-95.23		26.78	-40.00	-13.60		Vertical
3	14275.00	-51.70	RMS	40.15	-24.69	0.87	-95.23		27.21	-40.00	-11.70		Vertical




Ant. 3

Part 96 Mode 2

LTE CA B48C 20M + 20M Ch55891 1RB99 QPSK + Ch56089 1RB0 QPSK

M




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 20M Ch55891 1RB99 QPSK

: LTE B48 20M Ch56089 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	Amp\Cb							
	MHz	dBm			1							
1	7248.00	-55.13	RMS	36.99	-24.45	1.09	-95.23	26.47	-40.00	-15.13		Horizontal
2	10872.00	-54.03	RMS	39.04	-24.90	0.66	-95.23	26.40	-40.00	-14.03		Horizontal
3	14496.00	-52.13	RMS	40.08	-24.74	0.84	-95.23	26.92	-40.00	-12.13		Horizontal



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 20M Ch55891 1RB99 QPSK

: LTE B48 20M Ch56089 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	Amp\Cb							
	MHz	dBm			1							
1	7248.00	-55.04	RMS	36.99	-24.45	1.09	-95.23	26.56	-40.00	-15.04		Vertical
2	10872.00	-53.88	RMS	39.04	-24.90	0.66	-95.23	26.55	-40.00	-13.88		Vertical
3	14496.00	-51.97	RMS	40.08	-24.74	0.84	-95.23	27.08	-40.00	-11.97		Vertical




Ant. 3

Part 96 Mode 2


LTE CA B48C 20M + 20M Ch56442 1RB99 QPSK + Ch56640 1RB0 QPSK

H



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1230_251105 Horizontal
: LTE B48 20M Ch56442 1RB99 QPSK
: LTE B48 20M Ch56640 1RB0 QPSK

	Freq	Level	Detector	Ant	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	l			g			
	MHz	dBm		dB/m	dB	dB		dBuV	dBm		
1	7358.00	-55.90	RMS	36.57	-24.42	1.04	-95.23	26.14	-40.00	-15.90	Horizontal
2	11037.00	-53.32	RMS	38.90	-24.91	0.66	-95.23	27.26	-40.00	-13.32	Horizontal
3	14716.00	-52.13	RMS	39.90	-24.86	0.81	-95.23	27.25	-40.00	-12.13	Horizontal



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1230_251105 Vertical
: LTE B48 20M Ch56442 1RB99 QPSK
: LTE B48 20M Ch56640 1RB0 QPSK

	Freq	Level	Detector	Ant Factor	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm			l			g			
1	7358.00	-55.60	RMS		dB/m	dB	dB	dBuV	dBm	dB	
2	11037.00	-53.75	RMS		36.57	-24.42	1.04	-95.23	26.44	-40.00	Vertical
3	11037.00	-53.75	RMS		38.90	-24.91	0.66	-95.23	26.83	-40.00	Vertical
2	14716.00	-52.82	RMS		39.90	-24.86	0.81	-95.23	26.56	-40.00	Vertical




Ant. 3

Part 96 Mode 6

LTE CA B48B 10M + 10M Ch55290 1RB49 QPSK + Ch55389 1RB0 QPSK

L




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 10M Ch55290 1RB99 QPSK

: LTE B48 10M Ch55389 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7137.00	-55.09	RMS	36.62	-24.46	1.21	-95.23	26.77	-40.00	-15.09	Horizontal		
2	10706.00	-53.60	RMS	39.10	-24.90	0.65	-95.23	26.78	-40.00	-13.60	Horizontal		
3	14275.00	-51.68	RMS	40.15	-24.69	0.87	-95.23	27.23	-40.00	-11.68	Horizontal		



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 10M Ch55290 1RB99 QPSK

: LTE B48 10M Ch55389 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7137.00	-55.45	RMS	36.62	-24.46	1.21	-95.23	26.41	-40.00	-15.45	Vertical		
2	10706.00	-53.76	RMS	39.10	-24.90	0.65	-95.23	26.62	-40.00	-13.76	Vertical		
3	14275.00	-51.82	RMS	40.15	-24.69	0.87	-95.23	27.09	-40.00	-11.82	Vertical		




Ant. 3

Part 96 Mode 6


LTE CA B48B 10M + 10M Ch55945 1RB49 QPSK + Ch56044 1RB0 QPSK

M



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1230_251105 Horizontal
: LTE B48 10M Ch55945 1RB99 QPSK
: LTE B48 10M Ch56044 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7248.00	-54.44	RMS	36.99	-24.45	1.09	-95.23		27.16	-40.00	-14.44		Horizontal
2	10872.00	-54.00	RMS	39.04	-24.90	0.66	-95.23		26.43	-40.00	-14.00		Horizontal
3	14496.00	-51.98	RMS	40.08	-24.74	0.84	-95.23		27.07	-40.00	-11.98		Horizontal



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1230_251105 Vertical
: LTE B48 10M Ch55945 1RB99 QPSK
: LTE B48 10M Ch56044 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF		Readin	Limit	Margin		Pol
				Factor	Amp\Cb		1						
	MHz	dBm											
1	7248.00	-54.94	RMS	36.99	-24.45	1.09	-95.23		26.66	-40.00	-14.94		Vertical
2	10872.00	-53.98	RMS	39.04	-24.90	0.66	-95.23		26.45	-40.00	-13.98		Vertical
3	14496.00	-51.76	RMS	40.08	-24.74	0.84	-95.23		27.29	-40.00	-11.76		Vertical




Ant. 3

Part 96 Mode 6

LTE CA B48B 10M + 10M Ch56591 1RB49 QPSK + Ch56690 1RB0 QPSK

H




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Horizontal

: LTE B48 10M Ch55945 1RB99 QPSK

: LTE B48 10M Ch56044 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	Amp\Cb							
	MHz	dBm			1			g				
1	7358.00	-55.50	RMS	36.57	-24.42	1.04	-95.23	26.54	-40.00	-15.50		Horizontal
2	11037.00	-53.53	RMS	38.90	-24.91	0.66	-95.23	27.05	-40.00	-13.53		Horizontal
3	14716.00	-52.81	RMS	39.90	-24.86	0.81	-95.23	26.57	-40.00	-12.81		Horizontal



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1230_251105 Vertical

: LTE B48 10M Ch55945 1RB99 QPSK

: LTE B48 10M Ch56044 1RB0 QPSK

	Freq	Level	Detector	Ant		Filter	EIRPCF	Readin	Limit	Margin		Pol
				Factor	Amp\Cb							
	MHz	dBm			1			g				
1	7358.00	-55.72	RMS	36.57	-24.42	1.04	-95.23	26.32	-40.00	-15.72		Vertical
2	11037.00	-53.84	RMS	38.90	-24.91	0.66	-95.23	26.74	-40.00	-13.84		Vertical
3	14716.00	-52.79	RMS	39.90	-24.86	0.81	-95.23	26.59	-40.00	-12.79		Vertical




Ant. 3

Part 96 Mode 1

LTE B48 20M Ch55340 1RB0 QPSK

L




Site : 03CH20-HY

Condition: -40 3m HF_9120D_02360_251105 Horizontal

: LTE B48 20M Ch55340 1RB0 QPSK

: #1 is fundamental signal which can be ignored.

1	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm		Factor	1						
1	3553.00	-59.47	RMS	29.51	-26.06	0.00	-95.23	32.31	-40.00	-19.47	Horizontal



Site : 03CH20-HY

Condition: -40 3m HF_9120D_02360_251105 Vertical

: LTE B48 20M Ch55340 1RB0 QPSK

: #1 is fundamental signal which can be ignored.

1	Freq	Level	Detector	Ant Amp\Cb		Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm		Factor	1						
1	3553.00	-58.02	RMS	29.51	-26.06	0.00	-95.23	33.76	-40.00	-18.02	Vertical