

## **RF Exposure / SAR Statement**

**No. : 25EE0175-HO-1**

**Applicant : Matsushita Electric Industrial Co., Ltd.**  
**Type of Equipment : Wireless LAN Unit**  
**Model No. : TXANP07VKA1**  
**FCC ID : ACJTXANP07VKA1**

---

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "TXANP07VKA1" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

**Where**

**P = 134.28 mW (Maximum peak output power)**  
**G = 1.45 Numerical Antenna gain; equal 1.60 dBi**  
**r = 20.0 cm**

**For: TXANP07VKA1**

**S = 0.03861 mW/cm<sup>2</sup>**

---

**UL Apex Co., Ltd.**

**Head Office EMC Lab.**

**4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN**

**Telephone : +81 596 24 8116**

**Facsimile : +81 596 24 8124**