MFA M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Date: June 30, 2000

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Icom Incorporated
Equipment: IC-A5
FCC ID: AFJIC-A5
FCC Rules: 87 L

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

NOTE: The applicant has advised that antenna used has a gain of approximately 0 db. The recommended duty cycle is 5% transmitter on, 5% receiver on, 90% standby for a reduction of –13 db.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Morton Flom, P. Eng.

enclosure(s)
cc: Applicant
MF/cvr

LIST OF EXHIBITS
(FCC **CERTIFICATION** (TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Icom Incorporated

FCC ID: AFJIC-A5

BY APPLICANT:

1. LETTER OF AUTHORIZATION

2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)
   ___ LABEL
   ___ LOCATION OF LABEL
   ___ COMPLIANCE STATEMENT
   ___ LOCATION OF COMPLIANCE STATEMENT

3. PHOTOGRAPHS, 2.1033(c)(12)

4. DOCUMENTATION: 2.1033(c)
   (3) USER MANUAL
   (9) TUNE UP INFO
   (10) SCHEMATIC DIAGRAM
   (10) CIRCUIT DESCRIPTION
   BLOCK DIAGRAM
   PARTS LIST
   ACTIVE DEVICES

5. PART 90.203(e) & (g) ATTESTATION

BY M.F.A. INC.

A. TESTIMONIAL & STATEMENT OF CERTIFICATION

B. STATEMENT OF QUALIFICATIONS

M. Flom Associates, Inc. - Global Compliance Center
3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176
www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

Sub-part
2.1033(c):

EQUIPMENT IDENTIFICATION

FCC ID: AFJIC-A5

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

June 30, 2000

SUPERVISED BY: Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

RULE	DESCRIPTION	PAGE
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	6
	Standard Test Conditions and Engineering Practices	7
2.1046(a)	Carrier Output Power (Conducted)	8
2.1051	Unwanted Emissions (Transmitter Conducted)	10
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	13
2.1047(a)	Audio Low Pass Filter (Voice Input)	16
2.1047(a)	Audio Frequency Response	19
2.1047(b)	Modulation Limiting	21
2.1055(a)(1)	Frequency Stability (Temperature Variation)	23
2.1055(b)(1)	Frequency Stability (Voltage Variation)	26
2.202(g)	Necessary Bandwidth and Emission Bandwidth	27

PAGE NO. 1 of 27.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224

c) Report Number: d0060067

d) Client: Icom America, Inc.
2380 - 116th Ave. N. E.
P.O. C-90029
Bellevue, Washington 98009-9029

e) Identification: IC-A5
FCC ID: AFJIC-A5
Description: VHF AM Handheld Aircraft Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: June 30, 2000
EUT Received: June 15, 2000

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:

Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 27.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

87 L

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:

Icom Incorporated
1-6-19 Kamikurazukuri
Hirano-ku
Osaka, Japan 547

MANUFACTURER:

Applicant

(c)(2): FCC ID: AFJIC-A5

MODEL NO: IC-A5

(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 6K00A3E

(c)(5): FREQUENCY RANGE, MHz: 118 to 136.975

(c)(6): POWER RATING, Watts: 1.5
___ Switchable ___ Variable _x_ N/A

(c)(7): MAXIMUM POWER RATING, Watts: 10

PAGE NO. 3 of 27.

INFORMATION FOR PUSH-TO-TALK DEVICES

Type and number of antenna to be used for this device:
¼ wave

Maximum antenna gain for antenna indicated above:
0 db

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?
No

Other hardware or operating restrictions that could limit a person's RF Exposure:
N/A

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:
N/A

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?
N/A

Can device access wire-line services to make phone calls, either directly or through an operator?
No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?
N/A

Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:
N/A

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Association (A2LA) as shown in the scope below.

THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION

ACCREDITED LABORATORY

A2LA has accredited

M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.

President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85225
Morton Flom Phone: 480 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2000 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022, EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1; CNS 13438
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

Revised 2/2/2000

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8370 • Phone: 301 644 3248 • Fax: 301 662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not covered by this laboratory's A2LA accreditation.

PAGE NO. 5 of 27.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE, INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 9.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:
Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

___ ATTACHED EXHIBITS
_X_ N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO. 6 of 27.

Sub-part 2.1033(c)(14): TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

____ 21 – Domestic Public Fixed Radio Services
____ 22 – Public Mobile Services
____ 22 Subpart H - Cellular Radiotelephone Service
____ 22.901(d) - Alternative technologies and auxiliary services
____ 23 – International Fixed Public Radiocommunication services
____ 24 – Personal Communications Services
____ 74 Subpart H - Low Power Auxiliary Stations
____ 80 – Stations in the Maritime Services
____ 80 Subpart E - General Technical Standards
____ 80 Subpart F - Equipment Authorization for Compulsory Ships
____ 80 Subpart K - Private Coast Stations and Marine Utility Stations
____ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
____ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
____ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
____ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
____ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
____ 80 Subpart X - Voluntary Radio Installations
_X_ 87 – Aviation Services
____ 90 – Private Land Mobile Radio Services
____ 94 – Private Operational-Fixed Microwave Service
____ 95 Subpart A - General Mobile Radio Service (GMRS)
____ 95 Subpart C - Radio Control (R/C) Radio Service
____ 95 Subpart D - Citizens Band (CB) Radio Service
____ 95 Subpart E - Family Radio Service
____ 95 Subpart F - Interactive Video and Data Service (IVDS)
____ 97 - Amateur Radio Service
____ 101 – Fixed Microwave Services

STANDARD TEST CONDITIONS and ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 8 of 27.

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: 47 CFR 2.1046(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.

2. Measurement accuracy is ±3%.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = , 188.8, 136.975

POWER SETTING	R. F. POWER, WATTS
High	1.5

SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 9 of 27.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	COAXIAL ATTENUATOR	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	POWER METERS	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	FREQUENCY COUNTER	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 10 of 27.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
   (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
   (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.

2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.

3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz	=	, 188.8, 136.975
SPECTRUM SEARCHED, GHz	=	0 to 10 x F_C
MAXIMUM RESPONSE, Hz	=	562
ALL OTHER EMISSIONS	=	≥ 20 dB BELOW LIMIT
LIMIT(S), dBc -(43+10xLOG P)	=	-44.8 (1.5 Watts)

SUPERVISED BY: Morton Flom, P. Eng.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
TEST B. OUT-OF-BAND SPURIOUS



Transmitter Spurious Emissions

Asset	Description (as applicable)	s/n
(1)	AUDIO OSCILLATOR/GENERATOR	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00012	HP 3312A	1432A11250
(2)	COAXIAL ATTENUATOR	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(3)	FILTERS; NOTCH, HP, LP, BP	
i00126	Eagle TNF-1	100-250
i00125	Eagle TNF-1	50-60
i00124	Eagle TNF-1	250-850
(4)	SPECTRUM ANALYZER	
i00048	HP 8566B	2511A01467
i00029	HP 8563E	3213A00104

PAGE NO. 12 of 27.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
g0060407: 2000-Jun-27 Tue 09:07:00
STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
118.800000	237.602000	-35.4	-67.1	-22.4
127.800000	255.605000	-32.8	-64.5	-19.8
136.975000	273.954000	-33.2	-64.9	-20.2
118.800000	356.397000	-38	-69.7	-25
127.800000	383.404000	-39.8	-71.5	-26.8
136.975000	410.952000	-44	-75.7	-31
118.800000	475.018000	-44.7	-76.4	-31.7
127.800000	511.623000	-42.3	-74	-29.3
136.975000	548.137000	-43.3	-75	-30.3
118.800000	594.090000	-42.9	-74.6	-29.9
127.800000	639.085000	-43.5	-75.2	-30.5
136.975000	684.701000	-44.2	-75.9	-31.2
118.800000	712.732000	-43.8	-75.5	-30.8
127.800000	766.480000	-45	-76.7	-32
136.975000	822.202000	-45	-76.7	-32
118.800000	831.352000	-45	-76.7	-32
127.800000	894.375000	-44.1	-75.8	-31.1
118.800000	950.397000	-44.3	-76	-31.3
136.975000	959.260000	-44.3	-76	-31.3
127.800000	1022.448000	-43.9	-75.6	-30.9
118.800000	1069.304000	-43.9	-75.6	-30.9
136.975000	1095.624000	-43.7	-75.4	-30.7
127.800000	1149.897000	-43.6	-75.3	-30.6
118.800000	1187.551000	-43.8	-75.5	-30.8
136.975000	1232.573000	-45	-76.7	-32
127.800000	1277.591000	-44.2	-75.9	-31.2
118.800000	1306.796000	-44.7	-76.4	-31.7
136.975000	1369.410000	-43.9	-75.6	-30.9
127.800000	1405.554000	-42.4	-74.1	-29.4
118.800000	1425.262000	-44.4	-76.1	-31.4
136.975000	1507.026000	-44.4	-76.1	-31.4
127.800000	1534.084000	-43.7	-75.4	-30.7
118.800000	1543.934000	-44.2	-75.9	-31.2
136.975000	1643.464000	-43.9	-75.6	-30.9
127.800000	1661.704000	-44.3	-76	-31.3
118.800000	1663.428000	-44.6	-76.3	-31.6
136.975000	1780.200000	-43.8	-75.5	-30.8
118.800000	1782.337000	-44.3	-76	-31.3
127.800000	1788.785000	-42.6	-74.3	-29.6
127.800000	1917.060000	-43.7	-75.4	-30.7
136.975000	1917.253000	-43.1	-74.8	-30.1
136.975000	2054.696000	-44.1	-75.8	-31.1

PAGE NO. 13 of 27.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.

2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for ±2.5/±1.25 kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.

3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.

4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

5. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 14 of 27.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0060404: 2000-Jun-27 Tue 08:56:00
STATE: 2:High Power



POWER: HIGH
MODULATION: NONE

SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 15 of 27.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
g0060406: 2000-Jun-27 Tue 09:04:00
STATE: 2:High Power



POWER: HIGH
MODULATION: VOICE: 2500 Hz SINE WAVE
MASK: FCC, 87.139, AM,
25kHz BW

SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 16 of 27.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.

2. The audio output was connected at the output to the modulated stage.

3. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 17 of 27.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
TEST B. AUDIO FREQUENCY RESPONSE
TEST C. HUM AND NOISE LEVEL
TEST D. RESPONSE OF LOW PASS FILTER
TEST E. MODULATION LIMITING



Transmitter Test Set Up

Asset	Description (as applicable)	s/n
(1)	Audio Oscillator	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2)	COAXIAL ATTENUATOR	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	MODULATION ANALYZER	
i00020	HP 8901A	2105A01087
(4)	AUDIO ANALYZER	
i00017	HP 8903A	2216A01753

PAGE NO. 18 of 27.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g0060321: 2000-Jun-27 Tue 07:19:00
STATE: 0:General



SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 19 of 27.

NAME OF TEST: Audio Frequency Response

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.

2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.

3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.

4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.

5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.

6. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 20 of 27.

NAME OF TEST: Audio Frequency Response
g0060320: 2000-Jun-27 Tue 07:06:00
STATE: 0:General



Frequency of Maximum Audio Response, Hz = 562

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-3.40
20000	-27.91
30000	-28.22
50000	-28.02

SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 21 of 27.

NAME OF TEST: Modulation Limiting

SPECIFICATION: 47 CFR 2.1047(b)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."

2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.

3. The input level was varied from 30% modulation (±1.5 kHz deviation) to at least 20 dB higher than the saturation point.

4. Measurements were performed for both negative and positive modulation and the respective results were recorded.

5. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 22 of 27.

NAME OF TEST: Modulation Limiting
g0060326: 2000-Jun-27 Tue 08:26:00
STATE: 0:General

Positive Peaks:



Negative Peaks:



SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 23 of 27.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.

2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.

3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.

4. The temperature tests were performed for the worst case.

5. MEASUREMENT RESULTS: ATTACHED

PAGE NO. 24 of 27.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
TEST B. CARRIER FREQUENCY STABILITY
TEST C. OPERATIONAL PERFORMANCE STABILITY
TEST D. HUMIDITY
TEST E. VIBRATION
TEST F. ENVIRONMENTAL TEMPERATURE
TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION



Transmitter Test Set-Up

Asset	Description	s/n
(as applicable)		
(1)	TEMPERATURE, HUMIDITY, VIBRATION	
i00027	Tenny Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	COAXIAL ATTENUATOR	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	R.F. POWER	
i00014	HP 435A POWER METER	1733A05839
i00039	HP 436A POWER METER	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(4)	FREQUENCY COUNTER	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

PAGE NO. 25 of 27.

NAME OF TEST: Frequency Stability (Temperature Variation)
g0060391: 2000-Jun-27 Tue 10:14:00
STATE: 0:General



SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 26 of 27.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at 25±5°C and connected as for "Frequency Stability - Temperature Variation" test.

2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.

3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)
g0060403: 2000-Jun-27 Tue 08:48:08
STATE: 0:General

LIMIT, ppm = 20
LIMIT, Hz = 2556
BATTERY END POINT (Voltage) = 7.5

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	8.16	127.800010	10	0.08
100	9.6	127.800000	0	0.00
115	11.04	127.800000	0	0.00
78	7.5	127.799970	-30	-0.23

SUPERVISED BY: Morton Flom, P. Eng.

PAGE NO. 27 of 27.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 6K00A3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	=	0.56
MAXIMUM DEVIATION (D), kHz	=	2.4
CONSTANT FACTOR (K)	=	1
NECESSARY BANDWIDTH (B_N), kHz	=	(2xM)+(2xDxK)
	=	6

SUPERVISED BY: Morton Flom, P. Eng.

TESTIMONIAL AND STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.

2. THAT the technical data supplied with the application was taken under my direction and supervision.

3. THAT the data was obtained on representative units, randomly selected.

4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER: Morton Flom, P. Eng.