

RF EXPOSURE TEST

FCC ID: AJYSLX-1

Applied procedures / limit

These devices are not exempted from compliance does not exceed the Commission's RF exposure guidelines. Unless a device operates at substantially low power levels, with a low gain antenna(s), supporting information is generally needed to establish the various potential operating configurations and exposure conditions of a transmitter and its antenna(s) in order to determine compliance with the RF exposure guidelines.

In order to demonstrate compliance with MPE requirement (see Section 2.1091), the following information is typically needed:

Calculation that estimates the minimum separation distance (20 cm or more) between an antenna and persons required to satisfy power density limits defined for free space.

Antenna installation and device operating instructions for installers (professional/unskilled users), and the parties responsible for ensuring compliance with the RF exposure requirement. Any caution statements and/or warning labels that are necessary in order to comply with the exposure limits. Any other RF exposure related issues that may affect MPE compliance.

FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot^2} = \frac{EIRP}{4\pi \cdot^2}$$

P :power input to the antenna in Mw

EIRP :Equivalent(effective) isotropic radiated power.

S :power density mW/ cm²

G ;numeric gain of antenna relative to isotropic radiator

R :distance to centre of radiation in cm

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device

$$r = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{EIRP}{4\pi S}}$$

EIRP=10^(Antenna Gain+Peak Output Power/10)

Note:

1. s=1.0 mW /cm² for limits for General Population/Uncontrolled Exposures.
2. The time averaged power over 30 minutes will be equaled Output Power.
3. The Power Density at a distance of 20cm calculated from the formula is far below the limit of 1MW/ cm²

Tune-up power:

GSM 850: 33+-1dBm Max: 34dBm=2512mW

GPRS 850: 33+-1dBm Max: 34dBm=2512mW

GSM 1900: 29+-1dBm Max:30dBm=1000mW

GPRS 1900: 29+-1dBm Max:30dBm=1000mW

Band V: 23+-1 dBm Max: 24dBm=251.2mW

Band II: 23+-1 dBm Max: 24dBm=251.2mW

WIFI: 13+-1dBm Max : 14dBm=25.11mW

MPE calculate

Frequency bands	The maximum sourced based time-averaged transmit power(mW)	Antenna Gain	Distance (cm)	Power Density (mW/cm ²)	Power Density Limit (mW/cm ²)	PASS/Fail
GSM 850	2512mW	1.125 (0.51dBi)	30	0.25	0.55	PASS
GPRS 850	2512mW	1.125 (0.51dBi)	30	0.25	0.55	PASS
Band V	251.2mW	1.094 (0.39dBi)	30	0.02	0.55	PASS
GSM 1900	1000mW	1.081 (0.34dBi)	30	0.10	1	PASS
GPRS 1900	1000mW	1.081 (0.34dBi)	30	0.10	1	PASS
Band II	251.2mW	1.089 (0.37dBi)	30	0.02	1	PASS
WIFI	25,11mW	1.58 (2.0dBi)	30	0.004	1	PASS

Transmit simultaneously(Max):

Max (WIFI+GSM850): $0.25+0.004=0.254<0.55$.

Result: PASS