FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Sony Corporation

Bluetooth Module

Brand Name	Model No.
SONY	BM153

FCC ID: AK8BM153

Prepared for : Sony Corporation
1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.
No. 6, Ke Feng Rd., 52 Block,
Shenzhen Science & Industrial Park,
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F14070
Date of Test : Feb.08~10, 2014
Date of Report : Mar.03, 2014

TABLE OF CONTENTS

Description Page

1. SUMMARY OF STANDARDS AND RESULTS 1-1
1.1. Description of Standards and Results 1-1
2. GENERAL INFORMATION 2-1
2.1. Description of Device (EUT) 2-1
2.2. Tested Supporting System Details 2-2
2.3. EUT Configuration and operation conditions for test. 2-2
2.4. Test information 2-3
2.5. Test Facility 2-4
2.6. Measurement Uncertainty (95% confidence levels, k=2) 2-4
3. POWER LINE CONDUCTED EMISSION MEASUREMENT 3-1
3.1. Test Equipment 3-1
3.2. Block Diagram of Test Setup 3-1
3.3. Power Line Conducted Emission Test Limits 3-1
3.4. Configuration of EUT on Test 3-1
3.5. Operating Condition of EUT 3-2
3.6. Test Procedure 3-2
3.7. Conducted Emission at Mains Terminals Test Results 3-2
4. RADIATED EMISSION MEASUREMENT 4-1
4.1. Test Equipment 4-1
4.2. Block Diagram of Test Setup 4-2
4.3. Radiated Emission Limit Standard: FCC 15.209 4-3
4.4. EUT Configuration on Test 4-3
4.5. Operating Condition of EUT 4-3
4.6. Test Procedure 4-3
4.7. Radiated Emission Test Results 4-4
5. CONDUCTED SPURIOUS EMISSIONS 5-1
5.1. Test Equipment 5-1
5.2. Limit 5-1
5.3. Test Procedure 5-1
5.4. Test result 5-1
6. CARRIER FREQUENCY SEPARATION TEST 6-1
6.1. Test Equipment 6-1
6.2. Limit 6-1
6.3. Test Results. 6-1
7. 20 DB BANDWIDTH TEST 7-1
7.1. Test Equipment 7-1
7.2. Limit 7-1
7.3. Test Results 7-1
8. NUMBER OF HOPPING FREQUENCY TEST 8-1
8.1. Test Equipment 8-1
8.2. Limit 8-1
8.3. Test Results 8-1
9. DWELL TIME 9-1

9.1. Test Equipment 9-1
9.2. Limit 9-1
9.3. Test Results 9-1
10. MAXIMUM PEAK OUTPUT POWER TEST 10-1
10.1. Test Equipment 10-1
10.2. Limit 10-1
10.3. Test Procedure 10-1
10.4. Test Results 10-1
11. BAND EDGE COMPLIANCE TEST 11-1
11.1. Test Equipment 11-1
11.2. Limit 11-1
11.3. Test Produce 11-1
11.4. Test Results 11-1
12. DEVIATION TO TEST SPECIFICATIONS 12-1
13. PHOTOGRAPH OF TEST 13-1
13.1. Photos of Power Line Conducted Emission Test 13-1
13.2. Photos of Radiated Emission Test 13-2
14. PHOTOGRAPH OF EUT 14-1

TEST REPORT CERTIFICATION

Applicant : Sony Corporation

Manufacturer : Sony Corporation

EUT Description : Bluetooth Module

FCC ID : AK8BM153

(A) MODEL NO.& BRAND NAME :

Brand Name	Model No.
SONY	BM153

(B) SERIAL NO. : N/A

(C) POWER SUPPLY : DC 3.3V

(D) TEST VOLTAGE : DC 3.3V

Tested for comply with:
FCC Rules and Regulations Part 15 Subpart C: 2012
Test procedure used:
ANSI C63.10:2009

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Feb.08~ 10, 2014 Report of date: Mar.03, 2014

Prepared by : Julia Zhu
Julia Zhu / Assistant

Reviewed by :
Sunny Lu/ Assistant Manager

信華科技（深圳）有限公司
Audix Technology (Shenzhen) Co., Ltd.
EMC 部門報告專用章
Stamp only for EMC Dept. Report
Signature: David Jin 3.3

Approved & Authorized Signer :
David Jin / Manager

1. SUMMARY OF STANDARDS AND RESULTS

1.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	**Standard**	**Results**
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 :2009	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 :2009	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 :2009	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 :2009	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1)\ ANSI C63.10 :2009	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10 :2009	PASS
N/A is an abbreviation for Not Applicable.		

2. GENERAL INFORMATION

2.1. Description of Device (EUT)

Product Name : Bluetooth Module

Model Number& Brand Name :

Brand Name	Model No.
SONY	BM153

FCC ID : AK8BM153

Radio : Bluetooth V2.1 +EDR

Operation Frequency : 2402-2480MHz

Number of Channel : 79

Modulation Technology : GFSK, π/4DQPSK, 8DPSK

Power Supply : DC 3.3V

Antenna Assembly Gain : Integrated PCB Antenna, 2.12dBi PK Gain

Applicant : Sony Corporation
1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan

Date of Test : Feb.08~10, 2014

Date of Receipt : Feb.07, 2014

Sample Type : Prototype production

2.2.Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number	Approved type
2.	Personal Audio System	--	SONY	SRS-X3	N/A	☑FCC DoC
		Power Adaptor: Manufacture: SONY, M/N:AC-UUD11 Cable: Shielded, Detachable, 0.8m				

2.3.EUT Configuration and operation conditions for test.



a: USB Cable

(EUT: Bluetooth Module)

2.4. Test information

The test software "bluesuite.exe" was used to control EUT work in Continuous TX mode, and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH 0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
Tx Mode 8-DPSK modulation	3	Low: CH 0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480
Note: π/4DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.			

2.5. Test Facility

Site Description

Name of Firm	:	Audix Technology (Shenzhen) Co., Ltd. No. 6, Ke Feng Rd., 52 Block, Shenzhen Science & Industrial Park,Nantou, Shenzhen, Guangdong, China
3m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 90454 Valid Date: Feb.22, 2015
3m & 10m Anechoic Chamber	:	Certificated by FCC, USA Registration Number: 794232 Valid Date: Oct.31, 2015
EMC Lab.	:	Certificated by Industry Canada Registration Number: IC 5183A-1 Valid Date: Jun.13, 2014
	:	Certificated by DAkkS, Germany Registration No: D-PL-12151-01-00 Valid Date: Dec.15, 2016
	:	Accredited by NVLAP, USA NVLAP Code: 200372-0 Valid Date: Mar.31, 2014

2.6. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.08 dB(9KHz to 150KHz)
	3.1 dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	3.22 dB(30~200MHz, Polarize: H)
	3.23 dB(30~200MHz, Polarize: V)
	3.49 dB(200M~1GHz, Polarize: H)
	3.39 dB(200M~1GHz, Polarize: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	4.97 dB(1~6GHz, Distance: 3m)
	4.99 dB(6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.57 dB
Uncertainty for Conduction Spurious emission test	2.00 dB
Uncertainty for Output power test	0.73 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.038 %
Uncertainty for test site temperature and humidity	0.6℃
	3%

3. POWER LINE CONDUCTED EMISSION MEASUREMENT

3.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.18, 13	1 Year
2.	Test Receiver	Rohde & Schwarz	ESHS10	838693/001	Oct.31, 13	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	834066/011	Oct.31, 13	1 Year
4.	L.I.S.N.#3	Kyoritsu	KNW-242C	8-1920-1	May.08, 13	1 Year
5.	Terminator	Hubersuhner	50Ω	No. 1	May.08, 13	1 Year
6.	Terminator	Hubersuhner	50Ω	No. 2	May.08, 13	1 Year
7.	RF Cable	Fujikura	3D-2W	No.1	May.08, 13	1 Year
8.	Coaxial Switch	Anritsu	MP59B	M50564	May.08, 13	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100341	May.08, 13	1 Year
10.	MPEG2 Measurement Generator	ROHDE&SCHWARZ	DVG	100319	Dec.11, 13	1 Year
11.	TV Transmitter	ROHDE&SCHWARZ	SFQ	100521	May.08, 13	1 Year
12.	Signal Generator	HP	8648A	3625U00573	May.08, 13	1 Year
13.	Pattern Generator	Philiphs	PM5418	LO625020	May.08, 13	1 Year

3.2. Block Diagram of Test Setup



3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

3.4.1. Bluetooth Module (EUT)

Model Number : BM153
Serial Number : N/A

3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipment.

3.5.3. Let the EUT work in test mode (TX Mode) and measure it.

3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.4-2009 on conducted Emission test.

The bandwidth of test receiver (R&S TEST RECEIVER ESHS10) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked. The test result are reported on Section 3.7.

3.7. Conducted Emission at Mains Terminals Test Results

PASS. (All emissions not reported below are too low against the prescribed limits.)



Site no :1#conduction Data No :2
Dis./Ant. :2013 KNW-242C-VA
Limit :FCC PART 15 C
Env./Ins. :26.1*C/65% Engineer :Alan_Chen
EUT :Bluetooth Module
Power Rating :DC 3.3V
Test Mode :Tx Mode
M/N:BM153

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.20970	0.17	0.01	42.91	43.09	63.22	20.13	QP
2	0.38880	0.16	0.02	35.58	35.76	58.09	22.33	QP
3	0.47835	0.15	0.02	34.54	34.71	56.37	21.66	QP
4	0.59775	0.15	0.02	33.45	33.62	56.00	22.38	QP
5	0.80670	0.16	0.03	32.02	32.21	56.00	23.79	QP
6	1.195	0.18	0.03	32.14	32.35	56.00	23.65	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Site no :1#conduction
Dis./Ant. :2013 KNW-242C-VB
Limit :FCC PART 15 C
Env./Ins. :26.1*C/65%
EUT :Bluetooth Module
Power Rating :DC 3.3V
Test Mode :Tx Mode
M/N:BM153

Data No :1
Engineer :Alan_Chen

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.17985	0.27	0.01	43.68	43.96	64.49	20.53	QP
2	0.20970	0.26	0.01	44.05	44.32	63.22	18.90	QP
3	0.38880	0.27	0.02	36.18	36.47	58.09	21.62	QP
4	0.47835	0.27	0.02	36.71	37.00	56.37	19.37	QP
5	0.59775	0.27	0.02	35.55	35.84	56.00	20.16	QP
6	8.329	0.47	0.09	36.82	37.38	60.00	22.62	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.
2.If the average limit is met when useing a quasi-peak detector. the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

4. RADIATED EMISSION MEASUREMENT

4.1.Test Equipment

4.1.1. Frequency rang: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	3#Chamber	AUDIX	N/A	N/A	Nov.24, 13	1 Year
2	EMI Spectrum	Agilent	E4407B	MY41440292	May.08, 13	1 Year
3	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	May.08, 13	1 Year
4	Amplifier	HP	8447D	2648A04738	May.08, 13	1 Year
5	Bilog Antenna	TESEQ	CBL6112D	35375	May.30, 13	1 Year
6	RF Cable	MIYAZAKI	CFD400-NL	3# Chamber No.1	May.08, 13	1 Year
7	Coaxial Switch	Anritsu	MP59B	M74389	May.08, 13	1 Year
8	MPEG2 Measurement Generator	ROHDE&SCHWARZ	DVG	100319	Dec.11, 13	1 Year
9	TV Transmitter	ROHDE&SCHWARZ	SFQ	100521	May.08, 13	1 Year
10	Signal Generator	HP	8648A	3625U00573	May.08, 13	1 Year
11	Pattern Generator	Philiphs	PM5418	LO625020	May.08, 13	1 Year

4.1.2. Frequency rang: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	E4407B	MY41440292	May.08, 13	1 Year
2	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
3	Amplifier	Agilent	8449B	3008A00863	May.08, 13	1 Year
4	RF Cable	Hubersuhner	SUCOFLEX106	77980/6	May.08, 13	1 Year
5	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	May.08, 13	1 Year
6	Horn Antenna	EMCO	3116	00060089	Aug.28, 13	1 Year

4.2.Block Diagram of Test Setup

4.2.1. For frequency range 30MHz-1000MHz



4.2.2. For frequency range 1GHz-18GHz



4.3.Radiated Emission Limit Standard: FCC 15.209

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark： (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

(4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4.EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Bluetooth Module (EUT)

Model Number : BM153
Serial Number : N/A

4.5.Operating Condition of EUT

4.5.1. Setup the EUT and simulator as shown as Section 3.2.

4.5.2. Turned on the power of all equipment.

4.5.3. Let EUT work in Tx mode.

4.6.Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2009 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

4.7.Radiated Emission Test Results

PASS.

All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.
Note: The duty cycle factor for calculate average level is 9.10dB, and average limit is 20dB below peak limit, so if peak measured level comply with peak limit, the average level was deemed to comply with average limit.

Duty cycle: 0.443ms /1.263ms *100% = 35.08%
Duty cycle factor = 20log（1/duty cycle）= 9.10






Agilent Spectrum Analyzer - Swept SA
Marker 1 Δ 443.000 µs
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
ΔMkr1 443.0 µs
-0.33 dB
Center 2.402000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 1.000 ms (1001 pts)
Align Now, All required
Marker
Select Marker 1
Normal
Delta
Fixed
Off
Properties
More 1 of 2

Frequency: 30MHz~1GHz



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 CBL6112D 35375
Limit : FCC PART 15 C (3M)
Env. / Ins. : 26.7*C/49%
EUT : Bluetooth Module
Power rating : DC 3.3V
Test Mode : Tx Mode
M/N:BM153

Data no. : 2
Ant. pol. : HORIZONTAL
Engineer : Even_Deng

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	34.850	17.09	0.92	38.01	27.71	40.00	12.29	QP
2	167.740	10.41	1.67	38.29	22.60	43.50	20.90	QP
3	196.840	10.08	1.78	38.09	22.33	43.50	21.17	QP
4	422.850	17.34	2.53	36.66	28.52	46.00	17.48	QP
5	500.450	18.01	2.75	35.34	27.72	46.00	18.28	QP
6	565.440	18.81	2.94	34.04	27.28	46.00	18.72	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 CBL6112D 35375
Limit : FCC PART 15 C (3M)
Env. / Ins. : 26.7*C/49%
EUT : Bluetooth Module
Power rating : DC 3.3V
Test Mode : Tx Mode
M/N:BM153

Data no. : 1
Ant. pol. : VERTICAL
Engineer : Even_Deng

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	34.850	17.09	0.92	12.99	31.00	40.00	9.00	QP
2	88.200	9.04	1.36	16.25	26.65	43.50	16.85	QP
3	192.960	9.75	1.76	17.01	28.52	43.50	14.98	QP
4	427.700	17.19	2.54	9.89	29.62	46.00	16.38	QP
5	500.450	18.01	2.75	12.32	33.08	46.00	12.92	QP
6	565.440	18.81	2.94	8.57	30.32	46.00	15.68	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz




```
Site no.      : 3m Chamber                        Data no.  : 1
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2402MHz  Tx Mode
M/N           : BM153
```




```
Site no.      : 3m Chamber                        Data no.  : 2
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2402MHz  Tx Mode
M/N           : BM153
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	100.02	98.30	74.00	-24.30	Peak
2	4804.000	32.85	8.56	35.70	49.69	55.40	74.00	18.60	Peak
3	7206.000	35.95	10.97	35.46	48.25	59.71	74.00	14.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4804.000	55.40	9.10	46.3	54	Pass
7206.000	59.71	9.10	50.61	54	Pass




```
Site no.      : 3m Chamber                        Data no.   : 3
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2402MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 4
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	96.97	95.25	74.00	-21.25	Peak
2	4804.000	32.85	8.56	35.70	46.67	52.38	74.00	21.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 7
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2441MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 3115 (4580)
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56%
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2441MHz Tx Mode
M/N : BM153

Data no. : 8
Ant. pol. : HORIZONTAL
Engineer : Kevin

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	94.64	93.07	74.00	-19.07	Peak
2	4882.000	32.99	8.64	35.70	44.65	50.58	74.00	23.42	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 9
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2441MHz  Tx Mode
M/N           : BM153
```




```
Site no.      : 3m Chamber                        Data no.  : 10
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2441MHz  Tx Mode
M/N           : BM153
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	99.46	97.89	74.00	-23.89	Peak
2	4882.000	32.99	8.64	35.70	49.28	55.21	74.00	18.79	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4882.000	55.21	9.10	46.11	54	Pass




```
Site no.      : 3m Chamber                        Data no.   : 11
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2480MHz  Tx Mode
M/N           : BM153
```




```
Site no.      : 3m Chamber                        Data no.  : 12
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2480MHz  Tx Mode
M/N           : BM153
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	93.58	92.15	74.00	-18.15	Peak
2	4960.000	33.13	8.72	35.70	48.33	54.48	74.00	19.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4960.000	54.48	9.10	45.38	54	Pass




```
Site no.      : 3m Chamber                        Data no.  : 13
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : GFSK 2480MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 3115 (4580)
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56%
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2480MHz Tx Mode
M/N : BM153

Data no. : 14
Ant. pol. : VERTICAL
Engineer : Kevin

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	98.03	96.60	74.00	-22.60	Peak
2	4960.000	33.13	8.72	35.70	48.82	54.97	74.00	19.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
4960.000	54.97	9.10	45.87	54	Pass




```
Site no.      : 3m Chamber                        Data no.  : 19
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2480MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 20
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2480MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	96.59	95.16	74.00	-21.16	Peak
2	4960.000	33.13	8.72	35.70	46.79	52.94	74.00	21.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 21
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2480MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 22
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2480MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.36	5.91	35.70	92.63	91.20	74.00	-17.20	Peak
2	4960.000	33.13	8.72	35.70	46.34	52.49	74.00	21.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 23
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2441MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 24
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2441MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	93.21	91.64	74.00	-17.64	Peak
2	4882.000	32.99	8.64	35.70	47.31	53.24	74.00	20.76	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 25
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2441MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 26
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2441MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.27	5.86	35.70	98.06	96.49	74.00	-22.49	Peak
2	4882.000	32.99	8.64	35.70	46.96	52.89	74.00	21.11	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.   : 27
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : HORIZONTAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer   : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2402MHz  Tx Mode
M/N           : BM153
```



Site no. : 3m Chamber Data no. : 28
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	94.76	93.04	74.00	-19.04	Peak
2	4804.000	32.85	8.56	35.70	47.01	52.72	74.00	21.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.




```
Site no.      : 3m Chamber                        Data no.  : 29
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2402MHz  Tx Mode
M/N           : BM153
```




```
Site no.      : 3m Chamber                        Data no.  : 30
Dis. / Ant.   : 3m   2013 3115 (4580)        Ant. pol. : VERTICAL
Limit         : FCC PART 15C  PEAK
Env. / Ins.   : 24*C/56%                     Engineer  : Kevin
EUT           : Bluetooth Module
Power Rating  : DC 3.3V
Test Mode     : 8-DPSK 2402MHz  Tx Mode
M/N           : BM153
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.18	5.80	35.70	99.04	97.32	74.00	-23.32	Peak
2	4804.000	32.85	8.56	35.70	47.66	53.37	74.00	20.63	Peak
3	7206.000	35.95	10.97	35.46	44.25	55.71	74.00	18.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

Frequency（MHz）	Peak level（dBuv/m）	Duty cycle factor (dB)	AV level (dBuv/m)	Limit(dBuv/m)	Conclusion
7206.000	55.71	9.10	46.61	54	Pass

5. CONDUCTED SPURIOUS EMISSIONS

5.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Attenuator	Agilent	8491B	MY39262165	May.08,13	1 Year
3.	RF Cable	Hubersuhner	SUCOFLEX102	28618/2	May.08,13	1 Year

5.2.Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3.Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions detected.

5.4.Test result

PASS (The testing data was attached in the next pages.)

GFSK

Test Frequency: 2402MHz






Agilent Spectrum Analyzer - Swept SA
Marker 1 871.960000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 19/100
01:32:58 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 871.96 MHz
-66.700 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 92.7 ms (1001 pts)
1 N 1 f 871.96 MHz -66.700 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 22.360000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 1/100
01:33:07 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 22.360 GHz
-64.052 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 1.43 s (1001 pts)
1 N 1 f 22.360 GHz -64.052 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required

Test Frequency: 2441MHz







Test Frequency: 2480MHz




Agilent Spectrum Analyzer - Swept SA
Marker 1 935.980000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 30/100
01:29:45 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 935.98 MHz
-65.971 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 92.7 ms (1001 pts)
1 N 1 f 935.98 MHz -65.971 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 23.635000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 2/100
01:29:57 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 23.635 GHz
-62.698 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 1.43 s (1001 pts)
1 N 1 f 23.635 GHz -62.698 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required

8-DPSK

Test Frequency: 2402MHz




Agilent Spectrum Analyzer - Swept SA
Marker 1 938.890000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 23/100
01:23:30 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 938.89 MHz
-65.873 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 92.7 ms (1001 pts)
1 N 1 f 938.89 MHz -65.873 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 24.580000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 2/100
01:23:42 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 24.580 GHz
-62.354 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 1.43 s (1001 pts)
1 N 1 f 24.580 GHz -62.354 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required



Test Frequency: 2441MHz




Agilent Spectrum Analyzer - Swept SA
Marker 1 935.980000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 26/100
01:27:30 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 935.98 MHz
-66.005 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 92.7 ms (1001 pts)
1 N 1 f 935.98 MHz -66.005 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 23.620000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 2/100
01:27:42 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 23.620 GHz
-63.981 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 1.43 s (1001 pts)
1 N 1 f 23.620 GHz -63.981 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required

Test Frequency: 2480MHz




Agilent Spectrum Analyzer - Swept SA
Marker 1 54.250000000 MHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 23/100
01:26:34 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 54.25 MHz
-66.834 dBm
Start 30.0 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 1.0000 GHz
Sweep 92.7 ms (1001 pts)
1 N 1 f 54.25 MHz -66.834 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 20.920000000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold: 1/100
01:26:43 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 20.920 GHz
-63.513 dBm
Start 10.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 25.000 GHz
Sweep 1.43 s (1001 pts)
1 N 1 f 20.920 GHz -63.513 dBm
Peak Search
Next Peak
Next Pk Right
Next Pk Left
Marker Delta
Mkr→CF
Mkr→Ref Lvl
More
1 of 2
Align Now, All required

Hopping on GFSK





8 DPSK

Agilent Spectrum Analyzer - Swept SA
Start Freq 2.477000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
01:38:47 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.477 033 GHz
3.129 dBm
Start 2.47700 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.51000 GHz
Sweep 3.20 ms (1001 pts)
1 N 1 f 2.477 033 GHz 3.129 dBm
2 N 1 f 2.483 500 GHz -58.377 dBm
3 N 1 f 2.500 000 GHz -59.431 dBm
Frequency
Auto Tune
Center Freq
2.493500000 GHz
Start Freq
2.477000000 GHz
Stop Freq
2.510000000 GHz
CF Step
3.300000 MHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.310000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
01:39:44 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Mkr1 2.407 0 GHz
3.577 dBm
Start 2.31000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.41000 GHz
Sweep 9.60 ms (1001 pts)
1 N 1 f 2.407 0 GHz 3.577 dBm
2 N 1 f 2.390 0 GHz -59.800 dBm
3 N 1 f 2.400 0 GHz -44.169 dBm
Frequency
Auto Tune
Center Freq
2.360000000 GHz
Start Freq
2.310000000 GHz
Stop Freq
2.410000000 GHz
CF Step
10.000000 MHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required

6. CARRIER FREQUENCY SEPARATION TEST

6.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year

6.2.Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.3.Test Results.

EUT: Bluetooth Module		
M/N:BM153		
Test date: 2014-02-10	Pressure: 101.1±1.0 kpa	Humidity: 52.1±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 23.2±0.6℃

Test Mode	Channel separation	Conclusion
8-DPSK	1.0MHz	PASS
GFSK	1.0MHz	PASS

Agilent Spectrum Analyzer - Swept SA
Marker 3 Δ -1.000000000 MHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
01:41:00 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
ΔMkr3 -1.000 MHz
6.502 dB
3Δ4
1Δ2
Center 2.441000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Span 5.000 MHz
Sweep 2.53 ms (1001 pts)
1 Δ2 1 f (Δ) 1.000 MHz (Δ) 5.072 dB
2 F 1 f 2.441 000 GHz -5.460 dBm
3 Δ4 1 f (Δ) -1.000 MHz (Δ) 6.502 dB
4 F 1 f 2.441 000 GHz -3.904 dBm
Marker
Select Marker 3
Normal
Delta
Fixed
Off
Properties
More 1 of 2
Align Now, All required

7. 20 DB BANDWIDTH TEST

7.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year

7.2.Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

7.3.Test Results

EUT: Bluetooth Module		
M/N:BM153		
Test date: 2014-02-10	Pressure: 101.1±1.0 kpa	Humidity: 52.1±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 23.2±0.6℃

Cable loss: 1 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	20dB bandwidth (KHz)	Limit (KHz)
GFSK	2402	841.5	N/A
	2441	836.6	N/A
	2480	839.7	N/A
8-DPSK	2402	1.208	N/A
	2441	1.214	N/A
	2480	1.209	N/A
Conclusion：PASS			

GFSK

Test Frequency: 2402MHz

Test Frequency: 2441MHz

Test Frequency: 2480MHz

8-DPSK

Test Frequency: 2402MHz

Test Frequency: 2441MHz

Test Frequency: 2480MHz

8. NUMBER OF HOPPING FREQUENCY TEST

8.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year

8.2.Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

8.3.Test Results

EUT: Bluetooth Module		
M/N:BM153		
Test date: 2014-02-10	Pressure: 101.1±1.0 kpa	Humidity: 52.1±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 23.2±0.6℃

Test Mode	Number of channel	Limit	Conclusion
8-DPSK	79	>=15	PASS
GFSK	79	>=15	PASS


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.390000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
01:42:34 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr2 2.441 000 GHz
2.905 dBm
Start 2.39000 GHz
#Res BW 100 kHz
#VBW 100 kHz
Stop 2.44100 GHz
Sweep 6.20 ms (1001 pts)
1 N 1 f 2.402 000 GHz 3.676 dBm
2 N 1 f 2.441 000 GHz 2.905 dBm
Frequency
Auto Tune
Center Freq
2.415500000 GHz
Start Freq
2.390000000 GHz
Stop Freq
2.441000000 GHz
CF Step
5.100000 MHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Start Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
Atten: 20 dB
Avg Type: Log-Pwr
Avg|Hold:>100/100
01:43:02 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Mkr1 2.441 000 0 GHz
0.854 dBm
Start 2.44100 GHz
#Res BW 100 kHz
#VBW 100 kHz
Stop 2.48350 GHz
Sweep 5.13 ms (1001 pts)
1 N 1 f 2.441 000 0 GHz 0.854 dBm
2 N 1 f 2.480 000 0 GHz 3.141 dBm
Frequency
Auto Tune
Center Freq
2.462250000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.483500000 GHz
CF Step
4.250000 MHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required

9. DWELL TIME

9.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year

9.2.Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

9.3.Test Results

EUT: Bluetooth Module		
M/N:BM153		
Test date: 2014-02-10	Pressure: 101.1±1.0 kpa	Humidity: 52.1±3.0%
Tested by: Leo-Li	Test site: RF Site	Temperature: 23.2±0.6℃

Mode		dwell time	Limit	Conclusion
GFSK	DH1	51hops/5s*0.4*79chanels*0.443ms =142.79ms	<400ms	PASS
	DH3	25hops/5s*0.4*79chanels*1.698ms =268.28ms	<400ms	PASS
	DH5	17hops/5s*0.4*79chanels*2.980ms =320.17ms	<400ms	PASS
8-DPSK	DH1	51hops/5s*0.4*79chanels*0.465ms =149.88ms	<400ms	PASS
	DH3	25hops/5s*0.4*79chanels*1.710ms =270.18ms	<400ms	PASS
	DH5	17hops/5s*0.4*79chanels*2.970ms =319.10ms	<400ms	PASS

Note: All the lower levels were signal from receiver's, and should not considered in here.

Test Mode: GFSK

DH 1



DH 3


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:46:26 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 s (1001 pts)
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
100.000 kHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 Δ 1.69800 ms
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:47:03 PM Jan 27, 2014
ΔMkr1 1.698 ms
-1.31 dB
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 3.000 ms (1001 pts)
Marker
Select Marker
1
Normal
Delta
Fixed
Off
Properties
More
1 of 2
Align Now, All required

DH 5

Agilent Spectrum Analyzer - Swept SA
Marker 1 Δ 2.98000 ms
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:49:07 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
ΔMkr1 2.980 ms
-1.82 dB
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 ms (1001 pts)
Align Now, All required
Marker
Select Marker 1
Normal
Delta
Fixed
Off
Properties
More 1 of 2


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:49:19 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 s (1001 pts)
Align Now, All required
Frequency
Auto Tune
Center Freq 2.441000000 GHz
Start Freq 2.441000000 GHz
Stop Freq 2.441000000 GHz
CF Step 100.000 kHz
Auto
Man
Freq Offset 0 Hz

Test Mode: 8-DPSK

DH 1





DH 3


Agilent Spectrum Analyzer - Swept SA
Marker 1 Δ 1.71000 ms
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:47:33 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
ΔMkr1 1.710 ms
-0.77 dB
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 3.000 ms (1001 pts)
Align Now, All required
Marker
Select Marker
1
Normal
Delta
Fixed
Off
Properties
More
1 of 2


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:47:45 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 s (1001 pts)
Align Now, All required
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
100.000 kHz
Auto
Man
Freq Offset
0 Hz

DH 5


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:48:06 PM Jan 27, 2014
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 s (1001 pts)
Frequency
Auto Tune
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
100.000 kHz
Auto
Man
Freq Offset
0 Hz
Align Now, All required


Agilent Spectrum Analyzer - Swept SA
Marker 1 Δ 2.97000 ms
PNO: Wide
IFGain:Low
Trig: Line
Atten: 20 dB
Avg Type: Log-Pwr
01:48:32 PM Jan 27, 2014
ΔMkr1 2.970 ms
-1.58 dB
Ref Offset 1 dB
10 dB/div
Ref 11.00 dBm
Log
Center 2.441000000 GHz
Res BW 100 kHz
#VBW 100 kHz
Span 0 Hz
Sweep 5.000 ms (1001 pts)
Marker
Select Marker
1
Normal
Delta
Fixed
Off
Properties
More
1 of 2
Align Now, All required

10.MAXIMUM PEAK OUTPUT POWER TEST

10.1.Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year
5.	Power Meter	Anritsu	ML2487A	6K00002472	May.08, 13	1 Year
6.	Power Sensor	Anritsu	MA2491A	033005	May.08, 13	1 Year

10.2.Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

10.3.Test Procedure

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power Directly.

10.4.Test Results

EUT: Bluetooth Module			
M/N:BM153			
Test date: 2014-03-01	Pressure: 101.2±1.0 kpa	Humidity: 51.8±3.0%	
Tested by: Leo-Li	Test site: RF site	Temperature: 20.8±0.6 ℃	
Cable loss: 1.5 dB		Attenuator loss: 20 dB	
Test Mode	CH (MHz)	Peak output Power（dBm）	Limit (dBm)
GFSK	2402	4.123	30
	2441	4.099	30
	2480	3.662	30
8-DPSK	2402	3.622	30
	2441	3.215	30
	2480	2.925	30
Conclusion: PASS			

GFSK

Test Frequency: 2402MHz

Test Frequency: 2441MHz

Test Frequency: 2480MHz

8-DPSK

Test Frequency: 2402MHz

Test Frequency: 2441MHz

Test Frequency: 2480MHz

11. BAND EDGE COMPLIANCE TEST

11.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.31, 13	1 Year
2.	Amp	HP	8449B	3008A08495	May.08, 13	1 Year
3.	Horn Antenna	EMCO	3115	9510-4580	May.28, 13	1 Year
4.	HF Cable	Hubersuhne	Sucoflex104	-	May.08, 13	1 Year

11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz） from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205

For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
   (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
   (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

11.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



Site no. : 3m Chamber Data no. : 5
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	44.89	43.13	74.00	30.87	Peak
2	2400.000	28.18	5.80	35.70	63.08	61.36	74.00	12.64	Peak
3	2402.150	28.18	5.80	35.70	100.13	98.41	74.00	-24.41	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 6
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	45.38	43.62	74.00	30.38	Peak
2	2400.000	28.18	5.80	35.70	57.91	56.19	74.00	17.81	Peak
3	2401.865	28.18	5.80	35.70	96.07	94.35	74.00	-20.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2480MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	28.36	5.91	35.70	97.92	96.49	74.00	-22.49	Peak
2	2483.500	28.36	5.92	35.70	49.40	47.98	74.00	26.02	Peak
3	2485.184	28.37	5.92	35.70	50.16	48.75	74.00	25.25	Peak
4	2500.000	28.40	5.94	35.70	45.18	43.82	74.00	30.18	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 3115 (4580)
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56%
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : GFSK 2480MHz Tx Mode
M/N : BM153

Data no. : 16
Ant. pol. : HORIZONTAL
Engineer : Kevin

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.36	5.91	35.70	93.27	91.84	74.00	-17.84	Peak
2	2483.500	28.36	5.92	35.70	45.40	43.98	74.00	30.02	Peak
3	2500.000	28.40	5.94	35.70	44.28	42.92	74.00	31.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber
Dis. / Ant. : 3m 2013 3115 (4580)
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56%
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2480MHz Tx Mode
M/N : BM153

Data no. : 17
Ant. pol. : HORIZONTAL
Engineer : Kevin

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.970	28.36	5.91	35.70	92.12	90.69	74.00	-16.69	Peak
2	2483.500	28.36	5.92	35.70	45.42	44.00	74.00	30.00	Peak
3	2500.000	28.40	5.94	35.70	45.09	43.73	74.00	30.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 18
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2480MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.135	28.36	5.91	35.70	96.04	94.61	74.00	-20.61	Peak
2	2483.500	28.36	5.92	35.70	47.28	45.86	74.00	28.14	Peak
3	2500.000	28.40	5.94	35.70	45.69	44.33	74.00	29.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	44.98	43.22	74.00	30.78	Peak
2	2400.000	28.18	5.80	35.70	71.87	70.15	74.00	3.85	Peak
3	2402.150	28.18	5.80	35.70	98.72	97.00	74.00	-23.00	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32
Dis. / Ant. : 3m 2013 3115 (4580) Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 24*C/56% Engineer : Kevin
EUT : Bluetooth Module
Power Rating : DC 3.3V
Test Mode : 8-DPSK 2402MHz Tx Mode
M/N : BM153

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	28.16	5.78	35.70	44.99	43.23	74.00	30.77	Peak
2	2400.000	28.18	5.80	35.70	67.99	66.27	74.00	7.73	Peak
3	2401.960	28.18	5.80	35.70	94.25	92.53	74.00	-18.53	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor
2. The emission levels that are 20dB below the official limit are not reported.

12. DEVIATION TO TEST SPECIFICATIONS

[NONE]