RADIO TEST REPORT

Test Report No. : 11633501H-A

Applicant	:	**Sony Interactive Entertainment Inc.**
Type of Equipment	:	**Wireless Controller**
Model No.	:	**CUH-ZCT2U**
FCC ID	:	**AK8CUHZCT2A**
Test regulation	:	**FCC Part 15 Subpart C: 2016**
Test Result	:	**Complied**

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.
6. This test report covers Radio technical requirements. It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)

Date of test: March 9 and 10, 2017

Representative test engineer:
Tomoki Matsui
Engineer
Consumer Technology Division

Approved by:
Takayuki Shimada
Engineer
Consumer Technology Division

NVLAP TESTING
NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
http://japan.ul.com/resources/emc_accredited/

REVISION HISTORY

Original Test Report No.: 11633501H-A

Revision	Test report No.	Date	Page revised	Contents
- (Original)	11633501H-A	March 27, 2017	-	-

CONTENTS PAGE

SECTION 1: Customer information....4
SECTION 2: Equipment under test (E.U.T.)....4
SECTION 3: Test specification, procedures & results....5
SECTION 4: Operation of E.U.T. during testing....8
SECTION 5: Conducted Emission....10
SECTION 6: Radiated Spurious Emission....11
SECTION 7: Antenna Terminal Conducted Tests....12
APPENDIX 1: Test data....13
Conducted Emission....13
20dB Bandwidth and Carrier Frequency Separation....17
Number of Hopping Frequency....20
Dwell time....22
Maximum Peak Output Power....25
Average Output Power....26
Radiated Spurious Emission....28
Conducted Spurious Emission....39
Conducted Emission Band Edge compliance....45
99% Occupied Bandwidth....47
APPENDIX 2: Test instruments....49
APPENDIX 3: Photographs of test setup....50
Conducted Emission....50
Radiated Spurious Emission....51
Worst Case Position....52
Test Configuration and peripherals....53

SECTION 1: Customer information

Company Name	Sony Interactive Entertainment Inc.
Brand Name	SONY
Address	1-7-1 Konan, Minato-ku, Tokyo, 108-0075 Japan
Telephone Number	+81-50-3807-5639
Facsimile Number	+81-50-3807-9594
Contact Person	Kiyoto Sasaki

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment	Wireless Controller
Model No	CUH-ZCT2U
Serial No	See Clause 4.2
Country of Manufacture	China
Receipt Date of Sample	February 23, 2017
Condition of EUT	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT	No modification by the test lab

2.2 Product Description

Model: CUH-ZCT2U (referred to as the EUT in this report) is a Wireless Controller.

Product Specification

Maximum clock frequency in the system (except radio part)	80 MHz
Clock frequency in the system (radio part)	26 MHz
Operating Temperature	5-35 deg. C
Power Supply	DC 5 V (USB Bus Power)
Battery Supply	DC 3.65 V
Size	Approx. 161.2 x 64.5 x 100.3 mm (Width x Height x Depth)
Weight	Approx. 210 g

Radio Specification: Bluetooth (Ver. 2.1+EDR function)

Equipment Type	Transceiver
Frequency of Operation	2402 MHz - 2480 MHz
Type of Modulation	FHSS (GFSK, π/4DQPSK, 8DPSK)
Bandwidth & Channel spacing	79 MHz & 1 MHz
Method of frequency generation	Synthesizer
Power Supply (inner)	DC 3.2 V
Antenna Type	IFA
Antenna Gain	3.50 dBi max

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification	:	FCC Part 15 Subpart C FCC Part 15 final revised on November 14, 2016 and effective December 14, 2016
Title	:	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz

* Also the EUT complies with FCC Part 15 Subpart B.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	**FCC:** ANSI C63.10-2013 6. Standard test methods **IC:** RSS-Gen 8.8	**FCC:** Section 15.207 **IC:** RSS-Gen 8.8	**QP** 21.1 dB, 0.15000 MHz, L **AV** 20.4 dB, 0.56210 MHz, N / 0.56128 MHz, N	Complied	-
Carrier Frequency Separation	**FCC:** FCC Public Notice DA 00-705 **IC:** -	**FCC:** Section15.247(a)(1) **IC:** RSS-247 5.1 (2)	See data.	Complied	Conducted
20dB Bandwidth	**FCC:** FCC Public Notice DA 00-705 **IC:** -	**FCC:** Section15.247(a)(1) **IC:** RSS-247 5.1 (1)		Complied	Conducted
Number of Hopping Frequency	**FCC:** FCC Public Notice DA 00-705 **IC:** -	**FCC:** Section15.247(a)(1)(iii) **IC:** RSS-247 5.1 (4)		Complied	Conducted
Dwell time	**FCC:** FCC Public Notice DA 00-705 **IC:** -	**FCC:** Section15.247(a)(1)(iii) **IC:** RSS-247 5.1 (4)		Complied	Conducted
Maximum Peak Output Power	**FCC:** FCC Public Notice DA 00-705 **IC:** RSS-Gen 6.12	**FCC:** Section15.247(a)(b)(1) **IC:** RSS-247 5.4 (2)		Complied	Conducted
Spurious Emission & Band Edge Compliance	**FCC:** FCC Public Notice DA 00-705 **IC:** RSS-Gen 6.13	**FCC:** Section15.247(d) **IC:** RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	9.7 dB 319.487 MHz, Horizontal, QP 319.482 MHz, Horizontal, QP	Complied	Conducted/ Radiated (above 30 MHz) *1)
Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422. *1) Radiated test was selected over 30 MHz based on section 15.247(d).					

* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

FCC 15.31 (e)

The EUT is a battery-operated device and test was performed with the full-charged battery.
This EUT provides stable voltage (DC 3.2V) constantly to RF Part regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	**IC:** RSS-Gen 6.6	**IC:** -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI
The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor *k*=2.
Ise EMC Lab.

Antenna terminal test Uncertainty (+/-)							
Power meter		Conducted emission and Power density			Conducted emission		Channel power
Below 1 GHz	Above 1 GHz	Below 1 GHz	1 GHz - 3 GHz	3 GHz - 18 GHz	18 GHz - 26.5 GHz	26.5 GHz - 40 GHz	
0.9 dB	1.0 dB	1.4 dB	1.5 dB	2.8 dB	2.8 dB	2.9 dB	2.6 dB

Frequency range	Conducted emission using AMN(LISN) (+/-)
0.009 MHz - 0.15 MHz	3.5 dB
0.15 MHz - 30 MHz	3.0 dB

Polarity	Radiated emission (Below 1 GHz)			
	(3 m*) (+/-)		(10 m*) (+/-)	
	30 MHz - 200 MHz	200 MHz - 1000 MHz	30 MHz - 200 MHz	200 MHz - 1000 MHz
Horizontal	5.0 dB	5.3 dB	5.0 dB	5.0 dB
Vertical	4.7 dB	5.9 dB	5.0 dB	5.1 dB

Radiated emission (Above 1 GHz)				
(3 m*) (+/-)		(1 m*) (+/-)		(10 m*) (+/-)
1 GHz - 6 GHz	6 GHz - 18 GHz	10 GHz - 26.5 GHz	26.5 GHz - 40 GHz	1 GHz - 18 GHz
5.2 dB	5.4 dB	5.5 dB	5.5 dB	5.4 dB

*Measurement distance

Conducted Emission test
The data listed in this test report has enough margin, more than the site margin.

Radiated emission test
The data listed in this test report has enough margin, more than the site margin.

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124

Test site	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	-	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	-	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.6 shielded room	-	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	-	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	-	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	-	3.1 x 5.0 x 2.7	N/A	-	-
No.9 measurement room	-	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.11 measurement room	-	6.2 x 4.7 x 3.0	4.8 x 4.6	-	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 m x 2.0 m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Mode(s)

Bluetooth (BT): Transmitting (Tx), Payload: PRBS9

Details of Operating Mode(s)

Test Item	Mode	Tested frequency
Conducted Emission, Spurious Emission (Conducted/Radiated)	Tx (Hopping Off) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Carrier Frequency Separation	Tx (Hopping On) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
20dB Bandwidth	Tx (Hopping Off) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Number of Hopping Frequency	Tx (Hopping On) DH5, 3DH5	-
Dwell time	Tx (Hopping On), -DH1, DH3, DH5 -3DH1, 3DH3, 3DH5	-
Maximum Peak Output Power	Tx (Hopping Off) DH5, 2DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Band Edge Compliance (Conducted)	Tx DH5, 3DH5 -Hopping On -Hopping Off	2402 MHz 2480 MHz
99% Occupied Bandwidth	Tx DH5, 3DH5 -Hopping On -Hopping Off	2402 MHz 2441 MHz 2480 MHz

*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test)
*2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.
* It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all test items based on Bluetooth Core specification.

*EUT has the power settings by the software as follows;
- Power settings: 7
- Software: BT Tool, Version: W1620

*This setting of software is the worst case.
Any conditions under the normal use do not exceed the condition of setting.
In addition, end users cannot change the settings of the output power of the product.

4.2 Configuration and peripherals

This page has been submitted for a separate exhibit.

SECTION 5: Conducted Emission

Test Procedure and conditions

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The rear of tabletop was located 40 cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80 cm from any other grounded conducting surface. EUT was located 80 cm from a Line Impedance Stabilization Network (LISN) / Artificial mains Network (AMN) and excess AC cable was bundled in center.

1) For the tests on EUT with other peripherals (as a whole system)
I/O cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30 cm to 40 cm long and were hanged at a 40 cm height to the ground plane. All unused 50 ohm connectors of the LISN (AMN) were resistivity terminated in 50 ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber.
The EUT was connected to a LISN (AMN).
An overview sweep with peak detection has been performed.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Detector	**: QP and CISPR AV**
Measurement range	**: 0.15 MHz - 30 MHz**
Test data	**: APPENDIX**
Test result	**: Pass**

SECTION 6: Radiated Spurious Emission

Test Procedure

[For below 1 GHz]
EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]
EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane.
The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The height of the measuring antenna varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.
The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.
The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).
The test was made with the detector (RBW/VBW) in the following table.
When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (IC) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (IC).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 10 Hz *1)	RBW: 100 kHz VBW: 300 kHz
Test Distance	3 m	4.4 m*2) (1 GHz – 10 GHz), 1 m*3) (10 GHz – 26.5 GHz)		4.4 m*2) (1 GHz – 10 GHz), 1 m*3) (10 GHz – 26.5 GHz)

*1) Although DA 00-705 accepts VBW = 10 Hz for AV measurements, it was confirmed that superfluous smoothing was not performed.
*2) Distance Factor: 20 x log (4.4 m/3.0 m) = 3.33 dB
*3) Distance Factor: 20 x log (1.0 m/3.0 m) = -9.5 dB

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30 MHz - 26.5 GHz
Test data : APPENDIX
Test result : Pass

SECTION 7: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
20dB Bandwidth	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30 MHz	300 kHz	1 MHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100 kHz, 1 MHz	300 kHz, 3 MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	9.1 kHz	27 kHz				
	30 MHz to 25 GHz	100 kHz	300 kHz				
Conducted Spurious Emission Band Edge compliance	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

*1) Peak hold was applied as Worst-case measurement.
*2) Reference data
*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.
Then, wide-band noise near the limit was checked separately, however the noise was not detected as shown in the chart.
(9 kHz -150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 9.1 kHz)

The test results and limit are rounded off to two decimals place, so some differences might be observed.

Test data : **APPENDIX**
Test result : **Pass**

APPENDIX 1: Test data

Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber
Data : 2017/03/09

Report No. : 11633501H
Temp./Humi. : 20deg.C /35% RH
Engineer : Tomoki Matsui

Mode / Remarks : Tx DH5 2480MHz

Limit1 : FCC15.207 QP
Limit2 : FCC15.207 AV



No.	Freq.	Reading		C.Fac	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>		<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
	[MHz]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	0.15000	29.1	13.6	13.2	42.3	26.8	66.0	56.0	23.7	29.2	N	
2	0.17962	25.1	10.0	13.2	38.3	23.2	64.5	54.5	26.2	31.3	N	
3	0.56210	16.4	12.3	13.3	29.7	25.6	56.0	46.0	26.3	20.4	N	
4	2.58366	16.3	11.9	13.5	29.8	25.4	56.0	46.0	26.2	20.6	N	
5	7.38633	8.7	3.7	13.8	22.5	17.5	60.0	50.0	37.5	32.5	N	
6	18.75224	17.8	12.3	14.4	32.2	26.7	60.0	50.0	27.8	23.3	N	
7	0.15000	31.7	15.6	13.2	44.9	28.8	66.0	56.0	21.1	27.2	L	
8	0.17962	25.0	10.8	13.2	38.2	24.0	64.5	54.5	26.3	30.5	L	
9	0.55736	15.6	11.5	13.3	28.9	24.8	56.0	46.0	27.1	21.2	L	
10	2.58623	13.9	9.3	13.5	27.4	22.8	56.0	46.0	28.6	23.2	L	
11	7.38630	8.5	3.6	13.8	22.3	17.4	60.0	50.0	37.7	32.6	L	
12	18.75249	17.9	12.4	14.4	32.3	26.8	60.0	50.0	27.7	23.2	L	

CHART:WITH FACTOR Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTEN + CABLE)

Conducted Emission

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, DH5

2402 MHz



2441 MHz



2480 MHz



Y scale [dBuV] Chart — N — L

Conducted Emission

DATA OF CONDUCTED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.3 Semi Anechoic Chamber
Data : 2017/03/09

Report No. : 11633501H

Temp./Humi. : 20deg.C /35% RH
Engineer : Tomoki Matsui

Mode / Remarks : Tx 3DH5 2480MHz

Limit1 : FCC15.207 QP
Limit2 : FCC15.207 AV



No.	Freq.	Reading		C.Fac	Results		Limit		Margin		Phase	Comment
		<QP>	<AV>		<QP>	<AV>	<QP>	<AV>	<QP>	<AV>		
	[MHz]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dB]	[dB]		
1	0.15140	29.2	13.7	13.2	42.4	26.9	65.9	55.9	23.5	29.0	N	
2	0.18394	24.1	9.3	13.2	37.3	22.5	64.3	54.3	27.0	31.8	N	
3	0.56128	16.3	12.3	13.3	29.6	25.6	56.0	46.0	26.4	20.4	N	
4	2.62242	15.8	11.5	13.5	29.3	25.0	56.0	46.0	26.7	21.0	N	
5	7.11977	11.0	5.8	13.8	24.8	19.6	60.0	50.0	35.2	30.4	N	
6	18.84619	18.0	12.8	14.4	32.4	27.2	60.0	50.0	27.6	22.8	N	
7	0.15144	29.0	14.3	13.2	42.2	27.5	65.9	55.9	23.7	28.4	L	
8	0.17826	24.8	10.7	13.2	38.0	23.9	64.5	54.5	26.5	30.6	L	
9	0.55828	15.4	11.5	13.3	28.7	24.8	56.0	46.0	27.3	21.2	L	
10	2.62093	14.1	9.4	13.5	27.6	22.9	56.0	46.0	28.4	23.1	L	
11	7.11972	7.1	2.2	13.8	20.9	16.0	60.0	50.0	39.1	34.0	L	
12	18.84725	17.9	12.3	14.4	32.3	26.7	60.0	50.0	27.7	23.3	L	

CHART:WITH FACTOR Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTEN + CABLE)

Conducted Emission

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, DH5

2402 MHz



2441 MHz



2480 MHz



Y scale [dBuV] Chart N L

20dB Bandwidth and Carrier Frequency Separation

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off

Mode	Freq. [MHz]	20dB Bandwidth [MHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	1.030	1.000	>= 0.687
DH5	2441.0	1.029	1.000	>= 0.686
DH5	2480.0	1.019	1.000	>= 0.679
3DH5	2402.0	1.313	1.000	>= 0.875
3DH5	2441.0	1.307	1.000	>= 0.871
3DH5	2480.0	1.318	1.000	>= 0.879

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).
No limit applies to 20dB Bandwidth.

20dB Bandwidth and Carrier Frequency Separation

DH5

20 dB Bandwidth

2402 MHz



2441 MHz



2480 MHz



Carrier Frequency Separation

2402 MHz



2441 MHz



2480 MHz



20dB Bandwidth and Carrier Frequency Separation

3DH5

20 dB Bandwidth

2402 MHz



2441MHz



2480MHz



Carrier Frequency Separation

2402 MHz



2441 MHz



2480 MHz



Number of Hopping Frequency

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping On

Mode	Number of channel [channels]	Limit [channels]
DH5	79	>= 15
3DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

Number of Hopping Frequency

DH5	3DH5
Hopping On (1/3)	**Hopping On (1/3)**
	
Hopping On (2/3)	**Hopping On (2/3)**
	
Hopping On (3/3)	**Hopping On (3/3)**
	

Dwell time

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping On

Mode	Number of transmission in a 31.6(79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period	Length of transmission [msec]	Result [msec]	Limit [msec]
DH1	26.6 times / 5 sec. x 31.6 sec. = 169 times	0.385	65	400
DH3	25.8 times / 5 sec. x 31.6 sec. = 164 times	1.647	270	400
DH5	14.2 times / 5 sec. x 31.6 sec. = 90 times	2.915	262	400
3DH1	25.4 times / 5 sec. x 31.6 sec. = 161 times	0.391	63	400
3DH3	24.4 times / 5 sec. x 31.6 sec. = 155 times	1.657	257	400
3DH5	13.2 times / 5 sec. x 31.6 sec. = 84 times	2.957	248	400

Sample Calculation
Result = Number of transmission x Length of transmission

*Average data of 5 tests.(except Inquiry)

Mode	Sampling [times] 1	2	3	4	5	Average [times]
DH1	28	21	27	28	29	26.6
DH3	28	24	26	26	25	25.8
DH5	15	10	15	16	15	14.2
3DH1	27	25	25	25	25	25.4
3DH3	25	24	24	24	25	24.4
3DH5	12	9	19	12	14	13.2

Sample Calculation
Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in N x 0.4s, where N is the number of channels being used in the hopping sequence ($20 \leq N \leq 79$), is always less than 0.4s regardless of packet size. This is confirmed in the test report for N = 79.

Dwell time

DH1 (1/2)
(Representative chart)



DH1 (2/2)



DH3 (1/2)
(Representative chart)



DH3 (2/2)



DH5 (1/2)
(Representative chart)



DH5 (2/2)



Dwell time

3DH1 (1/2)
(Representative chart)



3DH1 (2/2)



3DH3 (1/2)
(Representative chart)



3DH3 (2/2)



3DH5 (1/2)
(Representative chart)



3DH5 (2/2)



Maximum Peak Output Power

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off

Mode	Freq.	Reading	Cable Loss	Atten. Loss	Result		Limit		Margin
	[MHz]	[dBm]	[dB]	[dB]	[dBm]	[mW]	[dBm]	[mW]	[dB]
DH5	2402.0	-11.25	1.75	10.03	0.53	1.13	20.96	125	20.43
DH5	2441.0	-11.15	1.75	10.03	0.63	1.16	20.96	125	20.33
DH5	2480.0	-11.14	1.76	10.03	0.65	1.16	20.96	125	20.31
2DH5	2402.0	-8.90	1.75	10.03	2.88	1.94	20.96	125	18.08
2DH5	2441.0	-8.88	1.75	10.03	2.90	1.95	20.96	125	18.06
2DH5	2480.0	-8.87	1.76	10.03	2.92	1.96	20.96	125	18.04
3DH5	2402.0	-8.63	1.75	10.03	3.15	2.07	20.96	125	17.81
3DH5	2441.0	-8.59	1.75	10.03	3.19	2.08	20.96	125	17.77
3DH5	2480.0	-8.59	1.76	10.03	3.20	2.09	20.96	125	17.76

Sample Calculation:
Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT.
As this device had AFH mode and frequency separation could not meet the requirement of over 20dB BW without 2/3 relaxation, 125mW power limit was applied to it.

Average Output Power
(Reference data for RF Exposure)

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off

Mode	Freq.	Reading	Cable Loss	Atten. Loss	Result (Time average)		Duty factor	Result (Burst power average)	
	[MHz]	[dBm]	[dB]	[dB]	[dBm]	[mW]	[dB]	[dBm]	[mW]
DH5	2402.0	-12.88	1.75	10.03	-1.10	0.78	1.13	0.03	1.01
DH5	2441.0	-12.86	1.75	10.03	-1.08	0.78	1.13	0.05	1.01
DH5	2480.0	-12.86	1.76	10.03	-1.07	0.78	1.13	0.06	1.01
2DH5	2402.0	-13.10	1.75	10.03	-1.32	0.74	1.13	-0.19	0.96
2DH5	2441.0	-13.00	1.75	10.03	-1.22	0.76	1.13	-0.09	0.98
2DH5	2480.0	-13.01	1.76	10.03	-1.22	0.76	1.13	-0.09	0.98
3DH5	2402.0	-13.08	1.75	10.03	-1.30	0.74	1.13	-0.17	0.96
3DH5	2441.0	-12.98	1.75	10.03	-1.20	0.76	1.13	-0.07	0.98
3DH5	2480.0	-12.99	1.76	10.03	-1.20	0.76	1.13	-0.07	0.98

Sample Calculation:
Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss
Result (Burst power average) = Time average + Duty factor

Burst Rate Confirmation

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off

DH5

Tx on / (Tx on + Tx off) =	**0.771**
Tx on / (Tx on + Tx off) * 100 =	**77.1 %**
Duty factor = 10 * log (3.75 / 2.892) =	**1.13 dB**



2DH5

Tx on / (Tx on + Tx off) =	**0.770**
Tx on / (Tx on + Tx off) * 100 =	**77.0 %**
Duty factor = 10 * log (3.75 / 2.889) =	**1.13 dB**



3DH5

Tx on / (Tx on + Tx off) =	**0.771**
Tx on / (Tx on + Tx off) * 100 =	**77.1 %**
Duty factor = 10 * log (3.75 / 2.892) =	**1.13 dB**



Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, DH5 2402 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.831	QP	33.8	9.1	7.5	32.2	-	18.2	40.0	21.8	
Hori	123.084	QP	23.0	13.2	8.4	32.2	-	12.4	43.5	31.1	
Hori	216.000	QP	36.4	11.8	9.3	32.0	-	25.5	43.5	18.0	
Hori	303.101	QP	39.6	13.5	10.0	31.9	-	31.2	46.0	14.8	
Hori	319.488	QP	44.1	13.8	10.1	31.9	-	36.1	46.0	9.9	
Hori	335.877	QP	37.5	14.2	10.2	31.9	-	30.0	46.0	16.0	
Hori	2390.000	PK	42.3	26.7	6.7	32.7	-	43.0	73.9	30.9	
Hori	4804.000	PK	39.9	31.0	8.9	31.8	-	48.0	73.9	25.9	Floor noise
Hori	7206.000	PK	40.6	35.7	10.2	32.6	-	53.9	73.9	20.0	Floor noise
Hori	9608.000	PK	41.0	37.2	10.8	33.2	-	55.8	73.9	18.1	Floor noise
Hori	2390.000	AV	30.4	26.7	6.7	32.7	-	31.1	53.9	22.8	
Hori	4804.000	AV	27.5	31.0	8.9	31.8	-	35.6	53.9	18.3	Floor noise
Hori	7206.000	AV	28.3	35.7	10.2	32.6	-	41.6	53.9	12.3	Floor noise
Hori	9608.000	AV	28.6	37.2	10.8	33.2	-	43.4	53.9	10.5	Floor noise
Vert	55.831	QP	41.6	9.1	7.5	32.2	-	26.0	40.0	14.0	
Vert	123.084	QP	33.2	13.2	8.4	32.2	-	22.6	43.5	20.9	
Vert	216.000	QP	37.3	11.8	9.3	32.0	-	26.4	43.5	17.1	
Vert	303.101	QP	34.8	13.5	10.0	31.9	-	26.4	46.0	19.6	
Vert	319.488	QP	38.1	13.8	10.1	31.9	-	30.1	46.0	15.9	
Vert	335.877	QP	32.0	14.2	10.2	31.9	-	24.5	46.0	21.5	
Vert	2390.000	PK	42.2	26.7	6.7	32.7	-	42.9	73.9	31.0	
Vert	4804.000	PK	39.9	31.0	8.9	31.8	-	48.0	73.9	25.9	Floor noise
Vert	7206.000	PK	40.6	35.7	10.2	32.6	-	53.9	73.9	20.0	Floor noise
Vert	9608.000	PK	41.0	37.2	10.8	33.2	-	55.8	73.9	18.1	Floor noise
Vert	2390.000	AV	30.3	26.7	6.7	32.7	-	31.0	53.9	22.9	
Vert	4804.000	AV	27.5	31.0	8.9	31.8	-	35.6	53.9	18.3	Floor noise
Vert	7206.000	AV	28.3	35.7	10.2	32.6	-	41.6	53.9	12.3	Floor noise
Vert	9608.000	AV	28.6	37.2	10.8	33.2	-	43.4	53.9	10.5	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2402.000	PK	98.5	26.7	6.7	32.7	99.2	-	-	Carrier
Hori	2400.000	PK	50.5	26.7	6.7	32.7	51.2	79.2	28.0	
Vert	2402.000	PK	98.0	26.7	6.7	32.7	98.7	-	-	Carrier
Vert	2400.000	PK	50.4	26.7	6.7	32.7	51.1	78.7	27.6	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amprifier)

***These results have sufficient margin without taking account Dwell time factor.**

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, DH5 2402 MHz

Horizontal

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Authorized-band band-edge Plot



20dBc Plot

Vertical

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Authorized-band band-edge Plot



20dBc Plot

* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, DH5 2441 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.833	QP	33.9	9.1	7.5	32.2	-	18.3	40.0	21.7	
Hori	123.082	QP	23.0	13.2	8.4	32.2	-	12.4	43.5	31.1	
Hori	216.000	QP	36.6	11.8	9.3	32.0	-	25.7	43.5	17.8	
Hori	303.101	QP	39.2	13.5	10.0	31.9	-	30.8	46.0	15.2	
Hori	319.487	QP	44.3	13.8	10.1	31.9	-	36.3	46.0	9.7	
Hori	335.872	QP	37.1	14.2	10.2	31.9	-	29.6	46.0	16.4	
Hori	4882.000	PK	40.3	31.3	8.9	31.7	-	48.8	73.9	25.1	Floor noise
Hori	7323.000	PK	40.3	35.6	10.2	32.6	-	53.5	73.9	20.4	Floor noise
Hori	9764.000	PK	40.9	37.2	10.8	33.3	-	55.6	73.9	18.3	Floor noise
Hori	4882.000	AV	27.8	31.3	8.9	31.7	-	36.3	53.9	17.6	Floor noise
Hori	7323.000	AV	28.3	35.6	10.2	32.6	-	41.5	53.9	12.4	Floor noise
Hori	9764.000	AV	28.7	37.2	10.8	33.3	-	43.4	53.9	10.5	Floor noise
Vert	55.833	QP	41.3	9.1	7.5	32.2	-	25.7	40.0	14.3	
Vert	123.082	QP	33.5	13.2	8.4	32.2	-	22.9	43.5	20.6	
Vert	216.000	QP	37.6	11.8	9.3	32.0	-	26.7	43.5	16.8	
Vert	303.101	QP	34.3	13.5	10.0	31.9	-	25.9	46.0	20.1	
Vert	319.487	QP	38.8	13.8	10.1	31.9	-	30.8	46.0	15.2	
Vert	335.872	QP	31.8	14.2	10.2	31.9	-	24.3	46.0	21.7	
Vert	4882.000	PK	40.3	31.3	8.9	31.7	-	48.8	73.9	25.1	Floor noise
Vert	7323.000	PK	40.3	35.6	10.2	32.6	-	53.5	73.9	20.4	Floor noise
Vert	9764.000	PK	40.9	37.2	10.8	33.3	-	55.6	73.9	18.3	Floor noise
Vert	4882.000	AV	27.8	31.3	8.9	31.7	-	36.3	53.9	17.6	Floor noise
Vert	7323.000	AV	28.3	35.6	10.2	32.6	-	41.5	53.9	12.4	Floor noise
Vert	9764.000	AV	28.7	37.2	10.8	33.3	-	43.4	53.9	10.5	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, DH5 2480 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.832	QP	33.9	9.1	7.5	32.2	-	18.3	40.0	21.7	
Hori	123.081	QP	23.1	13.2	8.4	32.2	-	12.5	43.5	31.0	
Hori	216.000	QP	36.7	11.8	9.3	32.0	-	25.8	43.5	17.7	
Hori	303.102	QP	39.4	13.5	10.0	31.9	-	31.0	46.0	15.0	
Hori	319.485	QP	44.0	13.8	10.1	31.9	-	36.0	46.0	10.0	
Hori	335.878	QP	37.6	14.2	10.2	31.9	-	30.1	46.0	15.9	
Hori	2483.500	PK	49.5	26.8	6.8	32.7	-	50.4	73.9	23.5	
Hori	4960.000	PK	40.0	31.5	8.9	31.7	-	48.7	73.9	25.2	Floor noise
Hori	7440.000	PK	41.2	35.5	10.2	32.7	-	54.2	73.9	19.7	Floor noise
Hori	9920.000	PK	40.8	37.2	10.9	33.4	-	55.5	73.9	18.4	Floor noise
Hori	2483.500	AV	36.3	26.8	6.8	32.7	-	37.2	53.9	16.7	
Hori	4960.000	AV	27.7	31.5	8.9	31.7	-	36.4	53.9	17.5	Floor noise
Hori	7440.000	AV	29.1	35.5	10.2	32.7	-	42.1	53.9	11.8	Floor noise
Hori	9920.000	AV	29.3	37.2	10.9	33.4	-	44.0	53.9	9.9	Floor noise
Vert	55.832	QP	41.8	9.1	7.5	32.2	-	26.2	40.0	13.8	
Vert	123.081	QP	33.1	13.2	8.4	32.2	-	22.5	43.5	21.0	
Vert	216.000	QP	37.5	11.8	9.3	32.0	-	26.6	43.5	16.9	
Vert	303.102	QP	34.7	13.5	10.0	31.9	-	26.3	46.0	19.7	
Vert	319.485	QP	38.2	13.8	10.1	31.9	-	30.2	46.0	15.8	
Vert	335.878	QP	32.0	14.2	10.2	31.9	-	24.5	46.0	21.5	
Vert	2483.500	PK	49.2	26.8	6.8	32.7	-	50.1	73.9	23.8	
Vert	4960.000	PK	40.0	31.5	8.9	31.7	-	48.7	73.9	25.2	Floor noise
Vert	7440.000	PK	41.2	35.5	10.2	32.7	-	54.2	73.9	19.7	Floor noise
Vert	9920.000	PK	40.8	37.2	10.9	33.4	-	55.5	73.9	18.4	Floor noise
Vert	2483.500	AV	35.8	26.8	6.8	32.7	-	36.7	53.9	17.2	
Vert	4960.000	AV	27.7	31.5	8.9	31.7	-	36.4	53.9	17.5	Floor noise
Vert	7440.000	AV	29.1	35.5	10.2	32.7	-	42.1	53.9	11.8	Floor noise
Vert	9920.000	AV	29.3	37.2	10.9	33.4	-	44.0	53.9	9.9	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, DH5 2480 MHz

Horizontal

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Vertical

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, 3DH5 2402 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.835	QP	33.6	9.1	7.5	32.2	-	18.0	40.0	22.0	
Hori	123.087	QP	23.2	13.2	8.4	32.2	-	12.6	43.5	30.9	
Hori	216.000	QP	36.3	11.8	9.3	32.0	-	25.4	43.5	18.1	
Hori	303.101	QP	39.7	13.5	10.0	31.9	-	31.3	46.0	14.7	
Hori	319.488	QP	44.1	13.8	10.1	31.9	-	36.1	46.0	9.9	
Hori	335.881	QP	37.5	14.2	10.2	31.9	-	30.0	46.0	16.0	
Hori	2390.000	PK	42.0	26.7	6.7	32.7	-	42.7	73.9	31.2	
Hori	4804.000	PK	39.9	31.0	8.9	31.8	-	48.0	73.9	25.9	Floor noise
Hori	7206.000	PK	40.6	35.7	10.2	32.6	-	53.9	73.9	20.0	Floor noise
Hori	9608.000	PK	41.0	37.2	10.8	33.2	-	55.8	73.9	18.1	Floor noise
Hori	2390.000	AV	30.2	26.7	6.7	32.7	-	30.9	53.9	23.0	
Hori	4804.000	AV	27.5	31.0	8.9	31.8	-	35.6	53.9	18.3	Floor noise
Hori	7206.000	AV	28.3	35.7	10.2	32.6	-	41.6	53.9	12.3	Floor noise
Hori	9608.000	AV	28.6	37.2	10.8	33.2	-	43.4	53.9	10.5	Floor noise
Vert	55.835	QP	42.0	9.1	7.5	32.2	-	26.4	40.0	13.6	
Vert	123.087	QP	33.3	13.2	8.4	32.2	-	22.7	43.5	20.8	
Vert	216.000	QP	37.3	11.8	9.3	32.0	-	26.4	43.5	17.1	
Vert	303.101	QP	34.2	13.5	10.0	31.9	-	25.8	46.0	20.2	
Vert	319.488	QP	38.1	13.8	10.1	31.9	-	30.1	46.0	15.9	
Vert	335.881	QP	32.0	14.2	10.2	31.9	-	24.5	46.0	21.5	
Vert	2390.000	PK	42.4	26.7	6.7	32.7	-	43.1	73.9	30.8	
Vert	4804.000	PK	39.9	31.0	8.9	31.8	-	48.0	73.9	25.9	Floor noise
Vert	7206.000	PK	40.6	35.7	10.2	32.6	-	53.9	73.9	20.0	Floor noise
Vert	9608.000	PK	41.0	37.2	10.8	33.2	-	55.8	73.9	18.1	Floor noise
Vert	2390.000	AV	30.2	26.7	6.7	32.7	-	30.9	53.9	23.0	
Vert	4804.000	AV	27.5	31.0	8.9	31.8	-	35.6	53.9	18.3	Floor noise
Vert	7206.000	AV	28.3	35.7	10.2	32.6	-	41.6	53.9	12.3	Floor noise
Vert	9608.000	AV	28.6	37.2	10.8	33.2	-	43.4	53.9	10.5	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2402.000	PK	98.2	26.7	6.7	32.7	98.9	-	-	Carrier
Hori	2400.000	PK	47.7	26.7	6.7	32.7	48.4	78.9	30.5	
Vert	2402.000	PK	97.7	26.7	6.7	32.7	98.4	-	-	Carrier
Vert	2400.000	PK	47.9	26.7	6.7	32.7	48.6	78.4	29.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amprifier)

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, 3DH5 2402 MHz

Horizontal

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Authorized-band band-edge Plot



20dBc Plot

Vertical

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Authorized-band band-edge Plot



20dBc Plot

* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, 3DH5 2441 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.838	QP	33.3	9.1	7.5	32.2	-	17.7	40.0	22.3	
Hori	123.083	QP	23.0	13.2	8.4	32.2	-	12.4	43.5	31.1	
Hori	216.000	QP	35.9	11.8	9.3	32.0	-	25.0	43.5	18.5	
Hori	303.101	QP	39.9	13.5	10.0	31.9	-	31.5	46.0	14.5	
Hori	319.482	QP	44.3	13.8	10.1	31.9	-	36.3	46.0	9.7	
Hori	335.879	QP	37.6	14.2	10.2	31.9	-	30.1	46.0	15.9	
Hori	4882.000	PK	40.3	31.3	8.9	31.7	-	48.8	73.9	25.1	Floor noise
Hori	7323.000	PK	40.3	35.6	10.2	32.6	-	53.5	73.9	20.4	Floor noise
Hori	9764.000	PK	40.9	37.2	10.8	33.3	-	55.6	73.9	18.3	Floor noise
Hori	4882.000	AV	27.8	31.3	8.9	31.7	-	36.3	53.9	17.6	Floor noise
Hori	7323.000	AV	28.3	35.6	10.2	32.6	-	41.5	53.9	12.4	Floor noise
Hori	9764.000	AV	28.7	37.2	10.8	33.3	-	43.4	53.9	10.5	Floor noise
Vert	55.838	QP	42.1	9.1	7.5	32.2	-	26.5	40.0	13.5	
Vert	123.083	QP	33.0	13.2	8.4	32.2	-	22.4	43.5	21.1	
Vert	216.000	QP	37.1	11.8	9.3	32.0	-	26.2	43.5	17.3	
Vert	303.101	QP	34.4	13.5	10.0	31.9	-	26.0	46.0	20.0	
Vert	319.482	QP	37.8	13.8	10.1	31.9	-	29.8	46.0	16.2	
Vert	335.879	QP	32.1	14.2	10.2	31.9	-	24.6	46.0	21.4	
Vert	4882.000	PK	40.3	31.3	8.9	31.7	-	48.8	73.9	25.1	Floor noise
Vert	7323.000	PK	40.3	35.6	10.2	32.6	-	53.5	73.9	20.4	Floor noise
Vert	9764.000	PK	40.9	37.2	10.8	33.3	-	55.6	73.9	18.3	Floor noise
Vert	4882.000	AV	27.8	31.3	8.9	31.7	-	36.3	53.9	17.6	Floor noise
Vert	7323.000	AV	28.3	35.6	10.2	32.6	-	41.5	53.9	12.4	Floor noise
Vert	9764.000	AV	28.7	37.2	10.8	33.3	-	43.4	53.9	10.5	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission

Test place Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No. 11633501H
Date March 9, 2017
Temperature / Humidity 20 deg. C / 35 % RH
Engineer Tomoki Matsui

Mode Tx, Hopping Off, 3DH5 2480 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	55.841	QP	33.0	9.1	7.5	32.2	-	17.4	40.0	22.6	
Hori	123.081	QP	23.1	13.2	8.4	32.2	-	12.5	43.5	31.0	
Hori	216.000	QP	36.2	11.8	9.3	32.0	-	25.3	43.5	18.2	
Hori	303.100	QP	40.1	13.5	10.0	31.9	-	31.7	46.0	14.3	
Hori	319.483	QP	44.1	13.8	10.1	31.9	-	36.1	46.0	9.9	
Hori	335.885	QP	37.6	14.2	10.2	31.9	-	30.1	46.0	15.9	
Hori	2483.500	PK	49.4	26.8	6.8	32.7	-	50.3	73.9	23.6	
Hori	4960.000	PK	40.0	31.5	8.9	31.7	-	48.7	73.9	25.2	Floor noise
Hori	7440.000	PK	41.2	35.5	10.2	32.7	-	54.2	73.9	19.7	Floor noise
Hori	9920.000	PK	40.8	37.2	10.9	33.4	-	55.5	73.9	18.4	Floor noise
Hori	2483.500	AV	36.4	26.8	6.8	32.7	-	37.3	53.9	16.6	
Hori	4960.000	AV	27.7	31.5	8.9	31.7	-	36.4	53.9	17.5	Floor noise
Hori	7440.000	AV	29.1	35.5	10.2	32.7	-	42.1	53.9	11.8	Floor noise
Hori	9920.000	AV	29.3	37.2	10.9	33.4	-	44.0	53.9	9.9	Floor noise
Vert	55.841	QP	42.3	9.1	7.5	32.2	-	26.7	40.0	13.3	
Vert	123.081	QP	33.2	13.2	8.4	32.2	-	22.6	43.5	20.9	
Vert	216.000	QP	37.4	11.8	9.3	32.0	-	26.5	43.5	17.0	
Vert	303.100	QP	34.5	13.5	10.0	31.9	-	26.1	46.0	19.9	
Vert	319.483	QP	38.0	13.8	10.1	31.9	-	30.0	46.0	16.0	
Vert	335.885	QP	32.3	14.2	10.2	31.9	-	24.8	46.0	21.2	
Vert	2483.500	PK	49.4	26.8	6.8	32.7	-	50.3	73.9	23.6	
Vert	4960.000	PK	40.0	31.5	8.9	31.7	-	48.7	73.9	25.2	Floor noise
Vert	7440.000	PK	41.2	35.5	10.2	32.7	-	54.2	73.9	19.7	Floor noise
Vert	9920.000	PK	40.8	37.2	10.9	33.4	-	55.5	73.9	18.4	Floor noise
Vert	2483.500	AV	36.2	26.8	6.8	32.7	-	37.1	53.9	16.8	
Vert	4960.000	AV	27.7	31.5	8.9	31.7	-	36.4	53.9	17.5	Floor noise
Vert	7440.000	AV	29.1	35.5	10.2	32.7	-	42.1	53.9	11.8	Floor noise
Vert	9920.000	AV	29.3	37.2	10.9	33.4	-	44.0	53.9	9.9	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)
*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (4.4 m / 3.0 m) = 3.33 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission
(Reference Plot for band-edge)

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, 3DH5 2480 MHz

Horizontal

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

Vertical

Restricted-band band-edge Plot



Trace Green : Peak Plot
Trace Purple : Average Plot

* Final result of restricted band edge was shown in tabular data.

Radiated Spurious Emission
(Plot data, Worst case)

Test place	Ise EMC Lab. No.3 Semi Anechoic Chamber
Report No.	11633501H
Date	March 9, 2017
Temperature / Humidity	20 deg. C / 35 % RH
Engineer	Tomoki Matsui
Mode	Tx, Hopping Off, 3DH5 2480 MHz





*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, DH5

2402 MHz

9 kHz - 150 kHz



150 kHz - 30 MHz



30 MHz - 25 GHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, DH5

2441 MHz

9 kHz – 150 kHz



150 kHz – 30 MHz



30 MHz – 25 GHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, DH5

2480 MHz

9 kHz – 150 kHz



150 kHz – 30 MHz



30 MHz – 25 GHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, 3DH5

2402 MHz

9 kHz – 150 kHz



150 kHz – 30 MHz



30 MHz – 25 GHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, 3DH5

2441 MHz

9 kHz - 150 kHz



150 kHz - 30 MHz



30 MHz - 25 GHz



Conducted Spurious Emission

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx, Hopping Off, 3DH5

2480 MHz

9 kHz - 150 kHz



150 kHz - 30 MHz



30 MHz - 25 GHz



Conducted Emission Band Edge compliance

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx DH5

Hopping On

Low



High



Hopping Off

Low



High



Conducted Emission Band Edge compliance

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx 3DH5

Hopping On

Low



High



Hopping Off

Low



High



99% Occupied Bandwidth

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx Hopping Off

Hopping Off, DH5

2402 MHz



2441 MHz



2480 MHz



Hopping Off, 3DH5

2402 MHz



2441 MHz



2480 MHz



99% Occupied Bandwidth

Test place	Ise EMC Lab. No.7 Shielded Room
Report No.	11633501H
Date	March 10, 2017
Temperature / Humidity	23 deg. C / 33 % RH
Engineer	Shinichi Miyazono
Mode	Tx Hopping On

Hopping On, DH5



Hopping On, 3DH5



APPENDIX 2: Test instruments

Test equipment

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-03	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	RE/CE	2016/10/20 * 12
MOS-13	Thermo-Hygrometer	Custom	CTH-180	1301	RE/CE	2017/01/20 * 12
MJM-16	Measure	KOMELON	KMC-36	-	RE/CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE/CE	-
MSA-10	Spectrum Analyzer	Agilent	E4448A	MY46180655	RE/CE	2016/08/17 * 12
MHA-20	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	258	RE	2016/05/29 * 12
MCC-167	Microwave Cable	Junkosha	MWX221	1404S374(1m) / 1405S074(5m)	RE	2016/05/20 * 12
MPA-11	MicroWave System Amplifier	Agilent	83017A	MY39500779	RE	2016/03/24 * 12
MHA-16	Horn Antenna 15-40GHz	Schwarzbeck	BBHA9170	BBHA9170306	RE	2016/05/29 * 12
MMM-08	DIGITAL HiTESTER	Hioki	3805	051201197	RE/CE	2017/01/19 * 12
MHF-25	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	RE	2016/09/21 * 12
MTR-08	Test Receiver	Rohde & Schwarz	ESCI	100767	RE	2016/09/15 * 12
MBA-03	Biconical Antenna	Schwarzbeck	BBA9106	1915	RE	2016/10/15 * 12
MLA-22	Logperiodic Antenna(200-1000MHz)	Schwarzbeck	VUSLP9111B	911B-191	RE	2017/01/26 * 12
MCC-51	Coaxial cable	UL Japan	-	-	RE	2016/07/26 * 12
MAT-98	Attenuator	KEYSIGHT	8491A	MY52462349	RE	2016/12/05 * 12
MPA-13	Pre Amplifier	SONOMA INSTRUMENT	310	260834	RE	2016/03/24 * 12
MLS-23	LISN(AMN)	Schwarzbeck	NSLK8127	8127-729	CE(EUT)	2016/07/07 * 12
MCC-112	Coaxial cable	Fujikura/Suhner/TSJ	5D-2W(10m)/SFM141(3m)/sucoform141-PE(1m)/421-010(1.5m)/RFM-E321(Switcher)	-/00640	CE	2016/07/26 * 12
MAT-66	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2016/12/24 * 12
MOS-34	Thermo-Hygrometer	Custom	CTH-201	3401	AT	2017/01/20 * 12
MSA-14	Spectrum Analyzer	Agilent	E4440A	MY48250080	AT	2016/10/14 * 12
MAT-25	Attenuator(10dB)(above 1GHz)	Agilent	8493C	71642	AT	2016/06/15 * 12
MCC-144	Microwave Cable	Junkosha	MWX221	1207S407	AT	2016/08/02 * 12
MAT-10	Attenuator(10dB)	Weinschel Corp	2	BL1173	AT	2016/11/28 * 12
MCC-64	Coaxial Cable	UL Japan	-	-	AT	2016/03/10 * 12
MPM-13	Power Meter	Anritsu	ML2495A	0824014	AT	2016/11/02 * 12
MPSE-18	Power sensor	Anritsu	MA2411B	0738174	AT	2016/11/02 * 12

The expiration date of the calibration is the end of the expired month.
All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item: CE: Conducted Emission test
RE: Radiated Emission test
AT: Antenna Terminal Conducted test