

RF EXPOSURE REPORT

Applicant	Sony Group Corporation
Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Manufacturer or Supplier	Sony Group Corporation
Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Product	Wireless Noise Canceling Stereo Headset
Brand Name	SONY
Model	YY2981
Additional Model & Model Difference	N/A
Date of tests	Jul. 21, 2023 ~ Aug. 10, 2023

☒ FCC Part 2 (Section 2.1093)

☒ KDB 447498 D04 Interim General RF Exposure Guidance v01

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	

Date: Oct. 10, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: FM2307WDG0150

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE DEFINE	5
3. MULTIPLE RF SOURCES ARE EXEMPT.....	6
4. SAR TEST EXCLUSION THRESHOLDS.....	7



Test Report No.: FM2307WDG0150

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2307WDG0150	Original release	Oct. 10, 2023

1. CERTIFICATION

FCC ID:	AK8YY2981
PRODUCT:	Wireless Noise Canceling Stereo Headset
BRAND NAME:	SONY
MODEL NO.:	YY2981
ADDITIONAL NO.:	N/A
TEST SAMPLE:	Engineering Sample
APPLICANT:	Sony Goup Corporation
STANDARDS:	FCC Part 2 (Section 2.1093)
	KDB 447498 D04 Interim General RF Exposure Guidance v01

2. RF EXPOSURE DEFINE

"Blanket" Exemption – §1.1307(b)(3)(i)(A)

- Regardless of the separation distance, the maximum time-averaged power is no more than 1mw.

"MPE" Exemption – §1.1307(b)(3)(i)(C)

- The minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.
- Table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits.

RF Source frequency (MHz)	Minimum Distance		Threshold ERP (watts)
	$\lambda_L/ 2\pi$	$\lambda_H/ 2\pi$	
0.3-1.34	159 m–35.6 m		1,920 R ² .
1.34-30	35.6 m–1.6 m		3,450 R ² /f ² .
30-300	1.6 m–159 mm		3.83 R ² .
300-1,500	159 mm–31.8 mm		0.0128 R ² f.
1,500-100,000	31.8 mm–0.5 mm		19.2 R ² .
R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters.			

- For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

"SAR" Exemption – §1.1307(b)(3)(i)(B)

- the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

And

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

3. MULTIPLE RF SOURCES ARE EXEMPT

Multiple RF sources are exempt– §1.1307(b)(3)(ii)

(a) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).

(b) Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluated_k term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for *P_{th}*, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source *i* at a distance between 0.5 cm and 40 cm (inclusive).

P_{th,i} = the exemption threshold power (*P_{th}*) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source *i*.

ERP_j = the ERP of fixed, mobile, or portable RF source *j*.

ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source *k* either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source *k*, as applicable from [§ 1.1310 of this chapter](#).

4. SAR TEST EXCLUSION THRESHOLDS

The antennas provided to the EUT, please refer to the following table:

Mode	Transmitter Circuit	Antenna Type	Antenna Gain (dBi)
GFSK	Chain 0	PCB antenna	2.48
8DPSK	Chain 0	PCB antenna	2.48
BT-LE (1Mbps)	Chain 0	PCB antenna	2.48
BT-LE (2Mbps)	Chain 0	PCB antenna	2.48

The measured EIRP

Mode	Frequency (MHz)	Conducted Averaged Power (dBm)	EIRP (dBm)
GFSK	2402	5.19	7.67
8DPSK	2402	3.54	6.02
BT-LE (1Mbps)	2402	5.15	7.63
BT-LE (2Mbps)	2440	5.67	8.15

The tuned EIRP (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	7	+/-1.5	5.5	8.5
8DPSK	2402-2480	6	+/-1.5	4.5	7.5
BT-LE (1Mbps)	2402-2480	7	+/-1.5	5.5	8.5
BT-LE (2Mbps)	2402-2480	8	+/-1.5	6.5	9.5



BUREAU
VERITAS

Test Report No.: FM2307WDG0150

The minimum distance from the transmitting antenna to the ear is greater than 24mm. Please refer to attachment A for minimum distance details.

SAR Exemption §1.1307(b)(3)(i)(B)				
Frequency (MHz)	Max. EIRP (dBm)	Max. EIRP (mW)	Limit Threshold (mW)	Test Result
2402-2480	9.5	8.912	54.325	Pass

CONCLUSION:

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.