

FCC ID: AL8-BT700  
Report No.: T200903W03-RP1

IC: 457A-BT700

Page: 1 / 70  
Rev.: 00

# RADIO TEST REPORT

## FCC 47 CFR PART 15 SUBPART C

### INDUSTRY CANADA RSS-247

|                          |                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Standard            | FCC Part 15.247<br>IC RSS-247 issue 2 and IC RSS-GEN issue 5                                                                                        |
| Product name             | Bluetooth USB adapter                                                                                                                               |
| Brand Name               |                                                                    |
| Model No.                | BT700                                                                                                                                               |
| Test Result              | Pass                                                                                                                                                |
| Statements of Conformity | Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty. |

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:



---

Kevin Tsai  
Deputy Manager

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

## **Revision History**

| Rev. | Issue Date       | Revisions     | Effect Page | Revised By |
|------|------------------|---------------|-------------|------------|
| 00   | October 30, 2020 | Initial Issue | ALL         | Mita Wu    |

## Table of contents

|                                                              |           |
|--------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                          | <b>4</b>  |
| <b>1.1 EUT INFORMATION .....</b>                             | <b>4</b>  |
| <b>1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS.....</b>   | <b>5</b>  |
| <b>1.3 EUT CHANNEL INFORMATION .....</b>                     | <b>6</b>  |
| <b>1.4 ANTENNA INFORMATION .....</b>                         | <b>6</b>  |
| <b>1.5 MEASUREMENT UNCERTAINTY .....</b>                     | <b>7</b>  |
| <b>1.6 FACILITIES AND TEST LOCATION.....</b>                 | <b>8</b>  |
| <b>1.7 INSTRUMENT CALIBRATION.....</b>                       | <b>8</b>  |
| <b>1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT.....</b>        | <b>9</b>  |
| <b>1.9 TEST METHODOLOGY AND APPLIED STANDARDS .....</b>      | <b>9</b>  |
| <b>2. TEST SUMMERY .....</b>                                 | <b>10</b> |
| <b>3. DESCRIPTION OF TEST MODES .....</b>                    | <b>11</b> |
| <b>3.1 THE WORST MODE OF OPERATING CONDITION.....</b>        | <b>11</b> |
| <b>3.2 THE WORST MODE OF MEASUREMENT .....</b>               | <b>12</b> |
| <b>3.3 EUT DUTY CYCLE .....</b>                              | <b>13</b> |
| <b>4. TEST RESULT .....</b>                                  | <b>14</b> |
| <b>4.1 AC POWER LINE CONDUCTED EMISSION .....</b>            | <b>14</b> |
| <b>4.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%) .....</b> | <b>17</b> |
| <b>4.3 OUTPUT POWER MEASUREMENT.....</b>                     | <b>23</b> |
| <b>4.4 FREQUENCY SEPARATION.....</b>                         | <b>25</b> |
| <b>4.5 NUMBER OF HOPPING .....</b>                           | <b>28</b> |
| <b>4.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION .....</b>    | <b>30</b> |
| <b>4.7 TIME OF OCCUPANCY (DWELL TIME).....</b>               | <b>35</b> |
| <b>4.8 RADIATION BANDEDGE AND SPURIOUS EMISSION .....</b>    | <b>37</b> |
| <b>APPENDIX 1 - PHOTOGRAPHS OF EUT</b>                       |           |

## 1. GENERAL INFORMATION

### 1.1 EUT INFORMATION

|                   |                                                                                                                    |
|-------------------|--------------------------------------------------------------------------------------------------------------------|
| FCC Applicant     | Plantronics Inc<br>345 Encinal Street Santa Cruz, CA 95060 USA                                                     |
| IC Applicant      | PLANTRONICS INC<br>345 Encinal Street, Santa Cruz CA 95060 United States Of America(Excluding The States Of Alaska |
| FCC Manufacturer  | Plantronics, Inc.<br>345 Encinal Street Santa Cruz, CA 95060 USA                                                   |
| IC Manufacturer   | PLANTRONICS INC<br>345 Encinal Street, Santa Cruz CA 95060 United States Of America(Excluding The States Of Alaska |
| Equipment         | Bluetooth USB adapter                                                                                              |
| Model No.         | BT700                                                                                                              |
| Model Discrepancy | N/A                                                                                                                |
| Trade Name        |                                 |
| Received Date     | September 3, 2020                                                                                                  |
| Date of Test      | September 9 ~ September 24, 2020                                                                                   |
| Power Operation   | EUT Power from Host System.                                                                                        |
| HW Version        | V01                                                                                                                |
| SW Version        | V76_308                                                                                                            |
| EUT Serial #      | BT700 RF# 1                                                                                                        |

## **1.2 INFORMATION ABOUT THE FHSS CHARACTERISTICS**

### **1.2.1 Pseudorandom Frequency Hopping Sequence**

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The nominal hop rate is 1 600 hops/s.

### **1.2.2 Equal Hopping Frequency Use**

The channels of this system will be used equally over the long-term distribution of the hopsets.

### **1.2.3 Example of a 79 hopping sequence in data mode:**

02, 05, 31, 24, 20, 10, 43, 36, 30, 23, 40, 06, 21, 50, 44, 09, 71, 78, 01, 13, 73, 07, 70, 72, 35, 62, 42, 11, 41, 08, 16, 29, 60, 15, 34, 61, 58, 04, 67, 12, 22, 53, 57, 18, 27, 76, 39, 32, 17, 77, 52, 33, 56, 46, 37, 47, 64, 49, 45, 38, 69, 14, 51, 26, 79, 19, 28, 65, 75, 54, 48, 03, 25, 66, 05, 16, 68, 74, 59, 63, 55

### **1.2.4 System Receiver Input Bandwidth**

Each channel bandwidth is 1MHz.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### **1.2.5 Equipment Description**

RSS-247, 5.1 (a): The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 1.3 EUT CHANNEL INFORMATION

|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Frequency Range   | 2402MHz-2480MHz                                                                    |
| Modulation Type   | 1. GFSK for BDR-1Mbps<br>2. $\pi/4$ -DQPSK for EDR-2Mbps<br>3. 8DPSK for EDR-3Mbps |
| Number of channel | 79 Channels                                                                        |

**Remark:**

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 and RSS-GEN Table 1 for test channels

| Number of frequencies to be tested                   |                       |                                              |
|------------------------------------------------------|-----------------------|----------------------------------------------|
| Frequency range in which device operates             | Number of frequencies | Location in frequency range of operation     |
| <input type="checkbox"/> 1 MHz or less               | 1                     | Middle                                       |
| <input type="checkbox"/> 1 MHz to 10 MHz             | 2                     | 1 near top and 1 near bottom                 |
| <input checked="" type="checkbox"/> More than 10 MHz | 3                     | 1 near top, 1 near middle, and 1 near bottom |

### 1.4 ANTENNA INFORMATION

|                   |                                                                                                                                      |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Antenna Type      | <input type="checkbox"/> PIFA <input checked="" type="checkbox"/> PCB <input type="checkbox"/> Dipole <input type="checkbox"/> Coils |
| Antenna Gain      | 2.54 dBi                                                                                                                             |
| Antenna Connector | N/A                                                                                                                                  |

## 1.5 MEASUREMENT UNCERTAINTY

| PARAMETER                             | UNCERTAINTY |
|---------------------------------------|-------------|
| AC Powerline Conducted Emission       | +/- 1.2575  |
| Emission bandwidth, 20dB bandwidth    | +/- 0.0014  |
| RF output power, conducted            | +/- 1.14    |
| Power density, conducted              | +/- 1.40    |
| 3M Semi Anechoic Chamber / 30M~200M   | +/- 4.12    |
| 3M Semi Anechoic Chamber / 200M~1000M | +/- 4.68    |
| 3M Semi Anechoic Chamber / 1G~8G      | +/- 5.18    |
| 3M Semi Anechoic Chamber / 8G~18G     | +/- 5.47    |
| 3M Semi Anechoic Chamber / 18G~26G    | +/- 3.81    |
| 3M Semi Anechoic Chamber / 26G~40G    | +/- 3.87    |

**Remark:**

- 1.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: T200903W03-RP1

## 1.6 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

| Test site          | Test Engineer | Remark |
|--------------------|---------------|--------|
| AC Conduction Room | Rick Lee      | -      |
| Radiation          | Jerry Chang   | -      |
| RF Conducted       | Rick Lee      | -      |

**Remark:** The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## 1.7 INSTRUMENT CALIBRATION

| 3M 966 Chamber Test Site         |                  |                 |              |            |            |
|----------------------------------|------------------|-----------------|--------------|------------|------------|
| Equipment                        | Manufacturer     | Model           | S/N          | Cal Date   | Cal Due    |
| Band Reject Filters              | MICRO TRONICS    | BRM 50702       | 120          | 02/25/2020 | 02/24/2021 |
| Bilog Antenna                    | Sunol Sciences   | JB3             | A030105      | 07/24/2020 | 07/23/2021 |
| Coaxial Cable                    | HUBER SUHNER     | SUCOFLEX 104PEA | 20995        | 02/25/2020 | 02/24/2021 |
| Coaxial Cable                    | EMCI             | EMC105          | 190914+25111 | 09/19/2020 | 09/18/2021 |
| Digital Thermo-Hygro Meter       | WISEWIND         | 1206            | D07          | 01/15/2020 | 01/14/2021 |
| double Ridged Guide Horn Antenna | ETC              | MCTD 1209       | DRH13M02003  | 10/04/2019 | 10/03/2020 |
| Loop Ant                         | COM-POWER        | AL-130          | 121051       | 03/27/2020 | 03/26/2021 |
| Pre-Amplifier                    | EMEC             | EM330           | 060609       | 02/25/2020 | 02/24/2021 |
| Pre-Amplifier                    | HP               | 8449B           | 3008A00965   | 02/25/2020 | 02/24/2021 |
| PSA Series Spectrum Analyzer     | Agilent          | E4446A          | MY46180323   | 07/24/2020 | 07/23/2021 |
| Antenna Tower                    | CCS              | CC-A-1F         | N/A          | N.C.R      | N.C.R      |
| Controller                       | CCS              | CC-C-1F         | N/A          | N.C.R      | N.C.R      |
| Turn Table                       | CCS              | CC-T-1F         | N/A          | N.C.R      | N.C.R      |
| Software                         | e3 6.11-20180413 |                 |              |            |            |

| Conducted Emission Room # B |                    |           |               |                  |                 |
|-----------------------------|--------------------|-----------|---------------|------------------|-----------------|
| Name of Equipment           | Manufacturer       | Model     | Serial Number | Calibration Date | Calibration Due |
| CABLE                       | EMCI               | CFD300-NL | CERF          | 06/29/2020       | 06/28/2021      |
| EMI Test Receiver           | R&S                | ESCI      | 100064        | 07/17/2020       | 07/16/2021      |
| LISN                        | SCHAFFNER          | NNB 41    | 03/10013      | 02/13/2020       | 02/12/2021      |
| Software                    | EZ-EMC(CCS-3A1-CE) |           |               |                  |                 |

**Remark:** Each piece of equipment is scheduled for calibration once a year.

| RF Conducted Test Site |              |         |               |                  |                 |
|------------------------|--------------|---------|---------------|------------------|-----------------|
| Name of Equipment      | Manufacturer | Model   | Serial Number | Calibration Date | Calibration Due |
| Coaxial Cable          | Woken        | WC12    | CC003         | 06/29/2020       | 06/28/2021      |
| EXA Signal Analyzer    | KEYSIGHT     | N9010B  | MY55460167    | 09/07/2020       | 09/06/2021      |
| Power Meter            | Anritsu      | ML2487A | 6K00003260    | 05/21/2020       | 05/20/2021      |
| Power Sensor           | Anritsu      | MA2490A | 032910        | 05/21/2020       | 05/20/2021      |
| Software               | N/A          |         |               |                  |                 |

**Remark:** Each piece of equipment is scheduled for calibration once a year.

## 1.8 SUPPORT AND EUT ACCESSORIES EQUIPMENT

| EUT Accessories Equipment |           |       |       |            |        |
|---------------------------|-----------|-------|-------|------------|--------|
| No.                       | Equipment | Brand | Model | Series No. | FCC ID |
|                           | N/A       |       |       |            |        |

| Support Equipment |           |       |       |            |        |
|-------------------|-----------|-------|-------|------------|--------|
| No.               | Equipment | Brand | Model | Series No. | FCC ID |
|                   | N/A       |       |       |            |        |

## 1.9 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247, RSS-247 Issue 2 and RSS-GEN Issue 5.

## 2. TEST SUMMERY

| FCC Standard Section | IC Standard Section  | Report Section | Test Item                   | Result |
|----------------------|----------------------|----------------|-----------------------------|--------|
| 15.203               | -                    | 1.3            | Antenna Requirement         | Pass   |
| 15.207(a)            | RSS-GEN 8.8          | 4.1            | AC Conducted Emission       | Pass   |
| 15.247(a)(1)         | RSS-247(5.1)(a)      | 4.2            | 20 dB Bandwidth             | Pass   |
| -                    | RSS-GEN 6.7          | 4.2            | Occupied Bandwidth (99%)    | Pass   |
| 15.247(b)(1)         | RSS-247(5.4)(b)      | 4.3            | Output Power Measurement    | Pass   |
| 15.247(a)(1)         | RSS-247(5.1)(b)      | 4.4            | Frequency Separation        | Pass   |
| 15.247(a)(1)(iii)    | RSS-247(5.1)(d)      | 4.5            | Number of Hopping           | Pass   |
| 15.247(d)            | RSS-247(5.5)         | 4.6            | Conducted Band Edge         | Pass   |
| 15.247(d)            | RSS-247(5.5)         | 4.6            | Conducted Spurious Emission | Pass   |
| 15.247(a)(1)(iii)    | RSS-247(5.1)(d)      | 4.7            | Time of Occupancy           | Pass   |
| 15.247(d)            | RSS-GEN 8.9,<br>8.10 | 4.8            | Radiation Band Edge         | Pass   |
| 15.247(d)            | RSS-GEN 8.9,<br>8.10 | 4.8            | Radiation Spurious Emission | Pass   |

### 3. DESCRIPTION OF TEST MODES

#### 3.1 THE WORST MODE OF OPERATING CONDITION

|                          |                                                                                                                                                                                                                                           |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operation mode           | GFSK for BDR-1Mbps (DH5)<br>8DPSK for EDR-3Mbps (3DH5)                                                                                                                                                                                    |
| Test Channel Frequencies | <b>GFSK for BDR-1Mbps:</b><br>1.Lowest Channel: 2402MHz<br>2.Middle Channel: 2441MHz<br>3.Highest Channel: 2480MHz<br><b>8DPSK for EDR-3Mbps:</b><br>1.Lowest Channel: 2402MHz<br>2.Middle Channel: 2441MHz<br>3.Highest Channel: 2480MHz |

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

### 3.2 THE WORST MODE OF MEASUREMENT

| AC Power Line Conducted Emission |                                                                                                                                            |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Test Condition                   | AC Power line conducted emission for line and neutral                                                                                      |
| Power supply Mode                | Mode 1: EUT power by Host System                                                                                                           |
| Worst Mode                       | <input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4 |

| Radiated Emission Measurement Below 1G |                                                                                                                                            |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Test Condition                         | Radiated Emission Below 1G                                                                                                                 |
| Power supply Mode                      | Mode 1: EUT power by Host System                                                                                                           |
| Worst Mode                             | <input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4 |

| Radiated Emission Measurement Above 1G |                                                                                                                                                                                                                                                                                               |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Condition                         | Radiated Emission Above 1G                                                                                                                                                                                                                                                                    |
| Power supply Mode                      | Mode 1: EUT power by Host System                                                                                                                                                                                                                                                              |
| Worst Mode                             | <input checked="" type="checkbox"/> Mode 1 <input type="checkbox"/> Mode 2 <input type="checkbox"/> Mode 3 <input type="checkbox"/> Mode 4                                                                                                                                                    |
| Worst Position                         | <input type="checkbox"/> Placed in fixed position.<br><input checked="" type="checkbox"/> Placed in fixed position at X-Plane (E2-Plane)<br><input type="checkbox"/> Placed in fixed position at Y-Plane (E1-Plane)<br><input type="checkbox"/> Placed in fixed position at Z-Plane (H-Plane) |

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.


## 3.3 EUT DUTY CYCLE

Temperature: 25°C

Humidity: 50% RH

Tested by: Rick Lee

| Duty Cycle    |                |                                            |           |                   |
|---------------|----------------|--------------------------------------------|-----------|-------------------|
| Configuration | Duty Cycle (%) | Duty Factor (dB)<br>=10*log (1/Duty Cycle) | 1/T (kHz) | VBW setting (kHz) |
| BDR-1Mbps     | 76.80%         | 1.15                                       | 0.35      | 1.00              |
| EDR-3Mbps     | 78.00%         | 1.08                                       | 0.34      | 1.00              |



## 4. TEST RESULT

### 4.1 AC POWER LINE CONDUCTED EMISSION

#### 4.1.1 Test Limit

According to §15.207(a) and RSS-GEN section 8.8,

| Frequency Range<br>(MHz) | Limits(dBμV) |           |
|--------------------------|--------------|-----------|
|                          | Quasi-peak   | Average   |
| 0.15 to 0.50             | 66 to 56*    | 56 to 46* |
| 0.50 to 5                | 56           | 46        |
| 5 to 30                  | 60           | 50        |


\* Decreases with the logarithm of the frequency.

#### 4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed on a non-conducted table, which is 0.8m above horizontal ground plane and 0.4m above vertical ground plane.
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

#### 4.1.3 Test Setup




#### 4.1.4 Test Result

**PASS**


## Test Data

|            |        |               |                    |
|------------|--------|---------------|--------------------|
| Test Mode: | Mode 1 | Temp/Hum      | 24(°C)/ 50%RH      |
| Phase:     | Line   | Test Date     | September 24, 2020 |
|            |        | Test Engineer | Rick Lee           |



| Frequency (MHz) | Quasi Peak reading (dBuV) | Average reading (dBuV) | Correction factor (dB) | Quasi Peak result (dBuV) | Average result (dBuV) | Quasi Peak limit (dBuV) | Average limit (dBuV) | Quasi Peak margin (dB) | Average margin (dB) | Remark |
|-----------------|---------------------------|------------------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|---------------------|--------|
| 0.1660          | 37.80                     | 22.75                  | 10.21                  | 48.01                    | 32.96                 | 65.16                   | 55.16                | -17.15                 | -22.20              | Pass   |
| 0.1940          | 30.27                     | 15.86                  | 10.21                  | 40.48                    | 26.07                 | 63.86                   | 53.86                | -23.38                 | -27.79              | Pass   |
| 0.2420          | 26.00                     | 13.83                  | 10.21                  | 36.21                    | 24.04                 | 62.03                   | 52.03                | -25.82                 | -27.99              | Pass   |
| 0.4700          | 21.12                     | 11.39                  | 10.22                  | 31.34                    | 21.61                 | 56.51                   | 46.51                | -25.17                 | -24.90              | Pass   |
| 0.5500          | 22.70                     | 14.86                  | 10.22                  | 32.92                    | 25.08                 | 56.00                   | 46.00                | -23.08                 | -20.92              | Pass   |
| 0.6660          | 15.10                     | 8.00                   | 10.22                  | 25.32                    | 18.22                 | 56.00                   | 46.00                | -30.68                 | -27.78              | Pass   |

|            |         |               |                    |
|------------|---------|---------------|--------------------|
| Test Mode: | Mode 1  | Temp/Hum      | 24(°C)/ 50%RH      |
| Phase:     | Neutral | Test Date     | September 24, 2020 |
|            |         | Test Engineer | Rick Lee           |



| Frequency (MHz) | Quasi Peak reading (dBuV) | Average reading (dBuV) | Correction factor (dB) | Quasi Peak result (dBuV) | Average result (dBuV) | Quasi Peak limit (dBuV) | Average limit (dBuV) | Quasi Peak margin (dB) | Average margin (dB) | Remark |
|-----------------|---------------------------|------------------------|------------------------|--------------------------|-----------------------|-------------------------|----------------------|------------------------|---------------------|--------|
| 0.1700          | 35.36                     | 20.90                  | 10.18                  | 45.54                    | 31.08                 | 64.96                   | 54.96                | -19.42                 | -23.88              | Pass   |
| 0.2140          | 20.38                     | 13.48                  | 10.19                  | 30.57                    | 23.67                 | 63.05                   | 53.05                | -32.48                 | -29.38              | Pass   |
| 0.2580          | 13.84                     | 7.11                   | 10.19                  | 24.03                    | 17.30                 | 61.50                   | 51.50                | -37.47                 | -34.20              | Pass   |
| 0.4620          | 20.14                     | 8.98                   | 10.19                  | 30.33                    | 19.17                 | 56.66                   | 46.66                | -26.33                 | -27.49              | Pass   |
| 0.7580          | 16.95                     | 8.35                   | 10.21                  | 27.16                    | 18.56                 | 56.00                   | 46.00                | -28.84                 | -27.44              | Pass   |
| 1.1700          | 15.05                     | 7.98                   | 10.21                  | 25.26                    | 18.19                 | 56.00                   | 46.00                | -30.74                 | -27.81              | Pass   |

## 4.2 20dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

### 4.2.1 Test Limit

According to §15.247(a) (1), RSS-247 section 5.1(a) and RSS-GEN 6.7,

**20 dB Bandwidth** : For reporting purposes only.


**Occupied Bandwidth(99%)** : For reporting purposes only.

### 4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 7.8.7,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 30kHz, VBW = 100kHz and Detector = Peak, to measurement 20 dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth
5. Measure and record the result of 20 dB Bandwidth and 99% Bandwidth. in the test report.

### 4.2.3 Test Setup



#### 4.2.4 Test Result

Temperature: 25°C

Humidity: 50% RH

Tested by: Rick Lee

| Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz |                 |                |               |
|------------------------------------------------|-----------------|----------------|---------------|
| Channel                                        | Frequency (MHz) | OBW(99%) (MHz) | 20dB BW (MHz) |
| Low                                            | 2402            | 0.8673         | 0.9280        |
| Mid                                            | 2441            | 0.8660         | 0.9288        |
| High                                           | 2480            | 0.8640         | 0.9273        |


| Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz |                 |                |               |
|-------------------------------------------------|-----------------|----------------|---------------|
| Channel                                         | Frequency (MHz) | OBW(99%) (MHz) | 20dB BW (MHz) |
| Low                                             | 2402            | 0.7882         | 0.5602        |
| Mid                                             | 2441            | 0.7833         | 0.5582        |
| High                                            | 2480            | 0.7932         | 0.5609        |

## Test Data


### 20dB BANDWIDTH

#### GFSK\_BDR-1Mbps mode

##### Low CH



##### Mid CH




##### High CH




## 8DPSK\_EDR-3Mbps mode

### Low CH



### Mid CH



### High CH




## Test Data


### BANDWIDTH 99%

#### GFSK\_BDR-1Mbps mode


##### Low CH



##### Mid CH




##### High CH



## 8DPSK\_EDR-3Mbps mode

### Low CH



### Mid CH



### High CH



## 4.3 OUTPUT POWER MEASUREMENT

### 4.3.1 Test Limit

According to §15.247(a)(1) and RSS-247 section 5.4(b)

**Peak output power** :

#### **FCC**

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### **IC**

According to RSS-247 section 5.4(b), For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).


|       |                                                                                                                                                                      |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Limit | <input checked="" type="checkbox"/> Antenna not exceed 6 dBi : 21dBm<br><input type="checkbox"/> Antenna with DG greater than 6 dBi : 21dBm [ Limit = 30 – (DG – 6)] |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Average output power** : For reporting purposes only.

### 4.3.2 Test Procedure

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

### 4.3.3 Test Setup



### 4.3.4 Test Result

#### Peak output power :

| BT                           |    |             |               |                |              |                     |                   |                    |                     |                    |
|------------------------------|----|-------------|---------------|----------------|--------------|---------------------|-------------------|--------------------|---------------------|--------------------|
| Config.                      | CH | Freq. (MHz) | Power Setting | PK Power (dBm) | PK Power (W) | EIRP PK Power (dBm) | EIRP PK Power (W) | FCC/IC Limit (dBm) | IC EIRP Limit (dBm) | Antenna Gain (dBi) |
| GFSK<br>BR-1Mbps<br>(DH5)    | 0  | 2402        | default       | <b>10.56</b>   | 0.0114       | 13.10               | 0.0204            | 21                 | 36                  | 2.54               |
|                              | 39 | 2441        | default       | 10.33          | 0.0108       | 12.87               | 0.0194            |                    |                     |                    |
|                              | 78 | 2480        | default       | 10.15          | 0.0104       | 12.69               | 0.0186            |                    |                     |                    |
| 8DPSK<br>EDR-3Mbps<br>(3DH5) | 0  | 2402        | default       | 10.21          | 0.0105       | 12.75               | 0.0188            |                    |                     |                    |
|                              | 39 | 2441        | default       | 10.20          | 0.0105       | 12.74               | 0.0188            |                    |                     |                    |
|                              | 78 | 2480        | default       | <b>10.28</b>   | 0.0107       | 12.82               | 0.0191            |                    |                     |                    |

#### Average output power :

| BT                           |    |             |                |
|------------------------------|----|-------------|----------------|
| Config.                      | CH | Freq. (MHz) | AV Power (dBm) |
| GFSK<br>BR-1Mbps<br>(DH5)    | 0  | 2402        | 10.34          |
|                              | 39 | 2441        | 10.16          |
|                              | 78 | 2480        | 10.34          |
| 8DPSK<br>EDR-3Mbps<br>(3DH5) | 0  | 2402        | 10.04          |
|                              | 39 | 2441        | 10.05          |
|                              | 78 | 2480        | 10.15          |

## 4.4 FREQUENCY SEPARATION

### 4.4.1 Test Limit

According to §15.247(a)(1) and RSS-247 section 5.1(b)


Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

|       |                                     |
|-------|-------------------------------------|
| Limit | > two-thirds of the 20 dB bandwidth |
|-------|-------------------------------------|

### 4.4.2 Test Procedure

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = 300kHz, Sweep = auto.  
Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency

### 4.4.3 Test Setup



#### 4.4.4 Test Result

Temperature: 25°C

Humidity: 50% RH


Tested by: Rick Lee

| Test mode: GFSK_BDR-1Mbps mode / 2402-2480 MHz |                 |                          |                                 |        |
|------------------------------------------------|-----------------|--------------------------|---------------------------------|--------|
| Channel                                        | Frequency (MHz) | Channel Separation (MHz) | Channel Separation Limits (MHz) | Result |
| Low                                            | 2402            | 0.9990                   | 0.619                           | PASS   |
| Mid                                            | 2441            | 0.9990                   | 0.619                           | PASS   |
| High                                           | 2480            | 0.9990                   | 0.618                           | PASS   |


| Test mode: 8DPSK_EDR-3Mbps mode / 2402-2480 MHz |                 |                          |                                 |        |
|-------------------------------------------------|-----------------|--------------------------|---------------------------------|--------|
| Channel                                         | Frequency (MHz) | Channel Separation (MHz) | Channel Separation Limits (MHz) | Result |
| Low                                             | 2402            | 1.0200                   | 0.373                           | PASS   |
| Mid                                             | 2441            | 1.0200                   | 0.372                           | PASS   |
| High                                            | 2480            | 1.0200                   | 0.374                           | PASS   |

## Test Data

### GFSK\_BDR-1Mbps mode



### 8DPSK\_EDR-3Mbps mode



Note: We selected worst case to performed test in middle channel, The results can be meet other channel.

## 4.5 NUMBER OF HOPPING

### 4.5.1 Test Limit

According to §15.247(a)(1)(iii) and RSS-247 section 5.1(d)


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 4.5.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 7.8.3

1. Place the EUT on the table and set it in transmitting mode.
2. EUT RF output port connected to the SA by RF cable.
3. Set spectrum analyzer Start Freq. = 2400 MHz, Stop Freq. = 2483.5 MHz, RBW = 100KHz, VBW = 300KHz.
4. Max hold, view and count how many channel in the band.


### 4.5.3 Test Setup



### 4.5.4 Test Result

| Number of Hopping |                 |                        |                               |        |
|-------------------|-----------------|------------------------|-------------------------------|--------|
| Mode              | Frequency (MHz) | Hopping Channel Number | Hopping Channel Number Limits | Result |
| BDR-1Mbps         | 2402-2480       | 79                     | 15                            | Pass   |
| EDR-3Mbps         | 2402-2480       | 79                     | 15                            |        |

## Test Data



## 4.6 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

### 4.6.1 Test Limit


According to §15.247(d) and RSS-247 section 5.5

|       |         |
|-------|---------|
| Limit | -20 dBc |
|-------|---------|

### 4.6.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. The Band Edge at 2.4GHz and 2.4835GHz are investigated with both hopping "ON" and "OFF" modes ".

### 4.6.3 Test Setup



Temperature: 25°C



Humidity: 50% RH

Tested by: Rick Lee

Report No.: T200903W03-RP1


## 4.6.4 Test Result

### Test Data




## GFSK\_BDR-1Mbps mode High CH

### Band Edge




### Spurious Emission 30MHz-25GHz




## GFSK\_BDR-1Mbps Hopping mode

### Low Band Edge




### High Band Edge




## 8DPSK\_EDR-3Mbps mode Low CH

### Band Edge




### Spurious Emission 30MHz-25GHz




## 8DPSK\_EDR-3Mbps mode Mid CH

### Spurious Emission 30MHz-25GHz




## 8DPSK\_EDR-3Mbps mode High CH

### Band Edge




### Spurious Emission 30MHz-25GHz




## 8DPSK\_EDR-3Mbps Hopping mode

### Low Band Edge



### High Band Edge



Report No.: T200903W03-RP1

#### 4.7 TIME OF OCCUPANCY (DWELL TIME)

#### 4.7.1 Test Limit


According to §15.247(a)(1)(iii) and RSS-247 section 5.1(d)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 4.7.2 Test Procedure

1. EUT RF output port connected to the SA by RF cable.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW, VBW=1MHz, Sweep = 1 ms

### 4.7.3 Test Setup




#### 4.7.4 Test Result

| Time of Occupancy (Dwell Time)                                                                                                                                                                              |                 |                             |                                 |                    |               |                       |        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------|---------------------------------|--------------------|---------------|-----------------------|--------|
| Mode                                                                                                                                                                                                        | Frequency (MHz) | Pulse Time Per Hopping (ms) | Minimum Number of Hopping Freq. | Number of pulse in | Dwell Time IN | Dwell Time Limits (s) | Result |
|                                                                                                                                                                                                             |                 |                             |                                 | (0.4 * N sec)      | (0.4 * N sec) |                       |        |
| BDR-1Mbps                                                                                                                                                                                                   | 2441            | 2.8800                      | 79                              | 106.67             | 0.3072        | 0.4                   | Pass   |
| EDR-3Mbps                                                                                                                                                                                                   | 2441            | 2.9250                      | 79                              | 106.67             | 0.3120        | 0.4                   |        |
| Non-AFH: DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 * 0.4 *79 = 106.6 |                 |                             |                                 |                    |               |                       |        |


## Test Data

### Time of Occupancy (Dwell Time)

#### GFSK\_BDR-1Mbps mode



#### 8DPSK\_EDR-3Mbps mode



## 4.8 RADIATION BANDEDGE AND SPURIOUS EMISSION

### 4.8.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

#### Below 30 MHz

| Frequency     | Field Strength<br>(microvolts/m) | Magnetic<br>H-Field<br>(microamperes/m) | Measurement<br>Distance<br>(meters) |
|---------------|----------------------------------|-----------------------------------------|-------------------------------------|
| 9-490 kHz     | 2,400/F (F in kHz)               | 2,400/F (F in kHz)                      | 300                                 |
| 490-1,705 kHz | 24,000/F (F in kHz)              | 24,000/F (F in kHz)                     | 30                                  |
| 1.705-30 MHz  | 30                               | N/A                                     | 30                                  |

#### Above 30 MHz

| Frequency<br>(MHz) | Field Strength<br>microvolts/m at 3 meters (watts, e.i.r.p.) |              |
|--------------------|--------------------------------------------------------------|--------------|
|                    | Transmitters                                                 | Receivers    |
| 30-88              | 100 (3 nW)                                                   | 100 (3 nW)   |
| 88-216             | 150 (6.8 nW)                                                 | 150 (6.8 nW) |
| 216-960            | 200 (12 nW)                                                  | 200 (12 nW)  |
| Above 960          | 500 (75 nW)                                                  | 500 (75 nW)  |

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

IC according to RSS-247 section 5.5, RSS-Gen, Section 8.9 and 8.10

**RSS-Gen Table 3 and Table 5 – General Field Strength Limits for Transmitters and Receivers at Frequencies Above 30 MHz** <sup>(Note)</sup>

| Frequency<br>(MHz) | Field Strength<br>microvolts/m at 3 meters (watts, e.i.r.p.) |              |
|--------------------|--------------------------------------------------------------|--------------|
|                    | Transmitters                                                 | Receivers    |
| 30-88              | 100 (3 nW)                                                   | 100 (3 nW)   |
| 88-216             | 150 (6.8 nW)                                                 | 150 (6.8 nW) |
| 216-960            | 200 (12 nW)                                                  | 200 (12 nW)  |
| Above 960          | 500 (75 nW)                                                  | 500 (75 nW)  |

**Note:** Measurements for compliance with the limits in table 3 may be performed at distances other than 3 meters, in accordance with Section 6.6.

**RSS-Gen Table 6: General Field Strength Limits for Transmitters at Frequencies Below 30 MHz (Transmit)**

| Frequency                 | Magnetic field strength<br>(H-Field) (μA/m) | Measurement Distance<br>(m) |
|---------------------------|---------------------------------------------|-----------------------------|
| 9-490 kHz <sup>Note</sup> | 6.37/F (F in kHz)                           | 300                         |
| 490-1,705 kHz             | 63.7/F (F in kHz)                           | 30                          |
| 1.705-30 MHz              | 0.08                                        | 30                          |

**Note:** The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

## 4.8.2 Test Procedure

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.

3. Span shall wide enough to full capture the emission measured. The SA from 9kHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Note: No emission found between lowest internal used/generated frequency to 30MHz(9KHz~30MHz)

4. For harmonic, the worst case of output power was BDR-1Mbps. Therefore only BDR-1Mbps record in the report.

5. The SA setting following :

(1) Below 1G : RBW = 100kHz, VBW  $\geq$  3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.

(2) Above 1G :

(2.1) For Peak measurement : RBW = 1MHz, VBW  $\geq$  3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.


(2.2) For Average measurement : RBW = 1MHz, VBW

·If Duty Cycle  $\geq$  98%, VBW=10Hz.


·If Duty Cycle < 98%, VBW $\geq$ 1/T.

## 4.8.3 Test Setup


### 9kHz ~ 30MHz



### 30MHz ~ 1GHz




## Above 1 GHz



## 4.8.4 Test Result


### Band Edge Test Data

|            |                          |               |                    |
|------------|--------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                | Test Date     | September 22, 2020 |
| Polarize   | Vertical                 | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average           |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 49.07                             | 1.25         | 50.32                  | 74.00                  | -23.68       |
| 2390.00      | Average                      | 36.81                             | 1.25         | 38.06                  | 54.00                  | -15.94       |

|            |                          |               |                    |
|------------|--------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                | Test Date     | September 22, 2020 |
| Polarize   | Horizontal               | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average           |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 49.00                             | 1.25         | 50.25                  | 74.00                  | -23.75       |
| 2390.00      | Average                      | 36.88                             | 1.25         | 38.13                  | 54.00                  | -15.87       |

|            |                           |               |                    |
|------------|---------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                 | Test Date     | September 22, 2020 |
| Polarize   | Vertical                  | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average            |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 49.78                             | 1.62         | 51.40                  | 74.00                  | -22.60       |
| 2483.50      | Average                      | 36.62                             | 1.62         | 38.24                  | 54.00                  | -15.76       |

|            |                           |               |                    |
|------------|---------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                 | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average            |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 49.91                             | 1.62         | 51.53                  | 74.00                  | -22.47       |
| 2483.50      | Average                      | 37.13                             | 1.62         | 38.75                  | 54.00                  | -15.25       |

|            |                                  |               |                    |
|------------|----------------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                        | Test Date     | September 22, 2020 |
| Polarize   | Vertical                         | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                   |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 50.88                             | -3.31        | 47.57                  | 74.00                  | -26.43       |
| 2390.00      | Average                      | 40.03                             | -3.31        | 36.72                  | 54.00                  | -17.28       |

|            |                                  |               |                    |
|------------|----------------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                        | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                       | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                   |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 51.06                             | -3.31        | 47.75                  | 74.00                  | -26.25       |
| 2390.00      | Average                      | 38.80                             | -3.31        | 35.49                  | 54.00                  | -18.51       |

|            |                                   |               |                    |
|------------|-----------------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                         | Test Date     | September 22, 2020 |
| Polarize   | Vertical                          | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                    |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 51.96                             | -2.85        | 49.11                  | 74.00                  | -24.89       |
| 2483.50      | Average                      | 39.18                             | -2.85        | 36.33                  | 54.00                  | -17.67       |
| 2484.93      | Peak                         | 56.95                             | -2.84        | 54.11                  | 74.00                  | -19.89       |
| 2484.93      | Average                      | 40.90                             | -2.84        | 38.06                  | 54.00                  | -15.94       |

|            |                                   |               |                    |
|------------|-----------------------------------|---------------|--------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                         | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                        | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                    |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 67.98                             | -2.85        | 65.13                  | 74.00                  | -8.87        |
| 2483.50      | Average                      | 54.53                             | -2.85        | 51.68                  | 54.00                  | -2.32        |
| 2484.60      | Peak                         | 68.23                             | -2.84        | 65.39                  | 74.00                  | -8.61        |
| 2484.60      | Average                      | 54.70                             | -2.84        | 51.86                  | 54.00                  | -2.14        |

|            |                           |               |                    |
|------------|---------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                 | Test Date     | September 22, 2020 |
| Polarize   | Vertical                  | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average            |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 49.15                             | -3.31        | 45.84                  | 74.00                  | -28.16       |
| 2390.00      | Average                      | 36.79                             | -3.31        | 33.48                  | 54.00                  | -20.52       |

|            |                           |               |                    |
|------------|---------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                 | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average            |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 49.67                             | -3.31        | 46.36                  | 74.00                  | -27.64       |
| 2390.00      | Average                      | 36.84                             | -3.31        | 33.53                  | 54.00                  | -20.47       |

|            |                            |               |                    |
|------------|----------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                  | Test Date     | September 22, 2020 |
| Polarize   | Vertical                   | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average             |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 48.68                             | 1.62         | 50.30                  | 74.00                  | -23.70       |
| 2483.50      | Average                      | 36.62                             | 1.62         | 38.24                  | 54.00                  | -15.76       |

|            |                            |               |                    |
|------------|----------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                  | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                 | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average             |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 50.19                             | 1.62         | 51.81                  | 74.00                  | -22.19       |
| 2483.50      | Average                      | 37.91                             | 1.62         | 39.53                  | 54.00                  | -14.47       |

|            |                                   |               |                    |
|------------|-----------------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>Low CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                         | Test Date     | September 22, 2020 |
| Polarize   | Vertical                          | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                    |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 49.37                             | 1.25         | 50.62                  | 74.00                  | -23.38       |
| 2390.00      | Average                      | 37.16                             | 1.25         | 38.41                  | 54.00                  | -15.59       |

|            |                                   |               |                    |
|------------|-----------------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>Low CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                         | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                        | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                    |               |                    |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2390.00      | Peak                         | 47.82                             | 1.25         | 49.07                  | 74.00                  | -24.93       |
| 2390.00      | Average                      | 37.21                             | 1.25         | 38.46                  | 54.00                  | -15.54       |

|            |                                    |               |                    |
|------------|------------------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>High CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                          | Test Date     | September 22, 2020 |
| Polarize   | Vertical                           | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                     |               |                    |



| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 48.27                             | 1.62         | 49.89                  | 74.00                  | -24.11       |
| 2483.50      | Average                      | 36.77                             | 1.62         | 38.39                  | 54.00                  | -15.61       |


|            |                                    |               |                    |
|------------|------------------------------------|---------------|--------------------|
| Test Mode: | 8DPSK_EDR-3Mbps<br>High CH Hopping | Temp/Hum      | 25.0(°C)/ 42%RH    |
| Test Item  | Band Edge                          | Test Date     | September 22, 2020 |
| Polarize   | Horizontal                         | Test Engineer | Jerry Chang        |
| Detector   | Peak / Average                     |               |                    |



| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 2483.50      | Peak                         | 48.22                             | 1.62         | 49.84                  | 74.00                  | -24.16       |
| 2483.50      | Average                      | 36.89                             | 1.62         | 38.51                  | 54.00                  | -15.49       |


## Below 1G Test Data

|            |            |               |                   |
|------------|------------|---------------|-------------------|
| Test Mode: | BT Mode    | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | 30MHz-1GHz | Test Date     | September 9, 2020 |
| Polarize   | Vertical   | Test Engineer | Jerry Chang       |
| Detector   | Peak       |               |                   |



| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 55.22        | Peak                         | 39.64                             | -16.20       | 23.44                  | 40.00                  | -16.56       |
| 99.84        | Peak                         | 38.98                             | -12.91       | 26.07                  | 43.50                  | -17.43       |
| 200.72       | Peak                         | 38.94                             | -9.82        | 29.12                  | 43.50                  | -14.38       |
| 468.44       | Peak                         | 25.10                             | -3.78        | 21.32                  | 46.00                  | -24.68       |
| 685.72       | Peak                         | 24.12                             | -0.35        | 23.77                  | 46.00                  | -22.23       |
| 871.96       | Peak                         | 23.45                             | 2.57         | 26.02                  | 46.00                  | -19.98       |


|            |            |               |                   |
|------------|------------|---------------|-------------------|
| Test Mode: | BT Mode    | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | 30MHz-1GHz | Test Date     | September 9, 2020 |
| Polarize   | Horizontal | Test Engineer | Jerry Chang       |
| Detector   | Peak       |               |                   |



| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 65.89        | Peak                         | 31.96                             | -15.54       | 16.42                  | 40.00                  | -23.58       |
| 177.44       | Peak                         | 40.17                             | -11.28       | 28.89                  | 43.50                  | -14.61       |
| 254.07       | Peak                         | 37.04                             | -10.72       | 26.32                  | 46.00                  | -19.68       |
| 550.89       | Peak                         | 24.79                             | -2.47        | 22.32                  | 46.00                  | -23.68       |
| 730.34       | Peak                         | 24.71                             | 0.42         | 25.13                  | 46.00                  | -20.87       |
| 890.39       | Peak                         | 25.45                             | 2.65         | 28.10                  | 46.00                  | -17.90       |

## Above 1G Test Data

|            |                          |               |                   |
|------------|--------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                 | Test Date     | September 9, 2020 |
| Polarize   | Vertical                 | Test Engineer | Jerry Chang       |
| Detector   | Peak                     |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4804.00      | Peak                         | 44.70                             | 3.36         | 48.06                  | 74.00                  | -25.94       |
| 7206.00      | Peak                         | 43.35                             | 10.77        | 54.12                  | 74.00                  | -19.88       |
| 7206.00      | Average                      | 39.98                             | 10.77        | 50.75                  | 54.00                  | -3.25        |
| N/A          |                              |                                   |              |                        |                        |              |

### Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|            |                          |               |                   |
|------------|--------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                 | Test Date     | September 9, 2020 |
| Polarize   | Horizontal               | Test Engineer | Jerry Chang       |
| Detector   | Peak                     |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4804.00      | Peak                         | 47.65                             | 3.36         | 51.01                  | 74.00                  | -22.99       |
| 7206.00      | Peak                         | 44.27                             | 10.77        | 55.04                  | 74.00                  | -18.96       |
| 7206.00      | Average                      | 40.36                             | 10.77        | 51.13                  | 54.00                  | -2.87        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

- Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
- For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|            |                          |               |                   |
|------------|--------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Mid CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                 | Test Date     | September 9, 2020 |
| Polarize   | Vertical                 | Test Engineer | Jerry Chang       |
| Detector   | Peak                     |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4882.00      | Peak                         | 43.21                             | 3.52         | 46.73                  | 74.00                  | -27.27       |
| 7323.00      | Peak                         | 42.96                             | 11.01        | 53.97                  | 74.00                  | -20.03       |
| 7323.00      | Average                      | 40.23                             | 11.01        | 51.24                  | 54.00                  | -2.76        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|            |                          |               |                   |
|------------|--------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>Mid CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                 | Test Date     | September 9, 2020 |
| Polarize   | Horizontal               | Test Engineer | Jerry Chang       |
| Detector   | Peak                     |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4882.00      | Peak                         | 45.93                             | 3.52         | 49.45                  | 74.00                  | -24.55       |
| 7323.00      | Peak                         | 42.72                             | 11.01        | 53.73                  | 74.00                  | -20.27       |
| 7323.00      | Average                      | 41.63                             | 11.01        | 52.64                  | 54.00                  | -1.36        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|            |                           |               |                   |
|------------|---------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize   | Vertical                  | Test Engineer | Jerry Chang       |
| Detector   | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dB $\mu$ V | Factor<br>dB | Actual<br>FS<br>dB $\mu$ V/m | Limit<br>@3m<br>dB $\mu$ V/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------------|--------------|------------------------------|------------------------------|--------------|
| 4960.00      | Peak                         | 37.24                                   | 4.46         | 41.70                        | 74.00                        | -32.30       |
| N/A          |                              |                                         |              |                              |                              |              |
|              |                              |                                         |              |                              |                              |              |
|              |                              |                                         |              |                              |                              |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz,the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|            |                           |               |                   |
|------------|---------------------------|---------------|-------------------|
| Test Mode: | GFSK_BDR-1Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item  | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize   | Horizontal                | Test Engineer | Jerry Chang       |
| Detector   | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dB $\mu$ V | Factor<br>dB | Actual<br>FS<br>dB $\mu$ V/m | Limit<br>@3m<br>dB $\mu$ V/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------------|--------------|------------------------------|------------------------------|--------------|
| 4960.00      | Peak                         | 42.81                                   | 4.46         | 47.27                        | 74.00                        | -26.73       |
| 7440.00      | Peak                         | 43.38                                   | 10.66        | 54.04                        | 74.00                        | -19.96       |
| 7440.00      | Average                      | 40.92                                   | 10.66        | 51.58                        | 54.00                        | -2.42        |
| N/A          |                              |                                         |              |                              |                              |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                           |               |                   |
|-----------|---------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize  | Vertical                  | Test Engineer | Jerry Chang       |
| Detector  | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4804.00      | Peak                         | 43.76                             | 3.36         | 47.12                  | 74.00                  | -26.88       |
| 7206.00      | Peak                         | 43.81                             | 10.77        | 54.58                  | 74.00                  | -19.42       |
| 7206.00      | Average                      | 40.10                             | 10.77        | 50.87                  | 54.00                  | -3.13        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                           |               |                   |
|-----------|---------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>Low CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize  | Horizontal                | Test Engineer | Jerry Chang       |
| Detector  | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4804.00      | Peak                         | 46.64                             | 3.36         | 50.00                  | 74.00                  | -24.00       |
| 7206.00      | Peak                         | 44.04                             | 10.77        | 54.81                  | 74.00                  | -19.19       |
| 7206.00      | Average                      | 40.25                             | 10.77        | 51.02                  | 54.00                  | -2.98        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                           |               |                   |
|-----------|---------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>Mid CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize  | Vertical                  | Test Engineer | Jerry Chang       |
| Detector  | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4882.00      | Peak                         | 44.15                             | 3.52         | 47.67                  | 74.00                  | -26.33       |
| 7323.00      | Peak                         | 43.32                             | 11.01        | 54.33                  | 74.00                  | -19.67       |
| 7323.00      | Average                      | 40.19                             | 11.01        | 51.20                  | 54.00                  | -2.80        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                           |               |                   |
|-----------|---------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>Mid CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                  | Test Date     | September 9, 2020 |
| Polarize  | Horizontal                | Test Engineer | Jerry Chang       |
| Detector  | Peak                      |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4882.00      | Peak                         | 44.72                             | 3.52         | 48.24                  | 74.00                  | -25.76       |
| 7323.00      | Peak                         | 43.27                             | 11.01        | 54.28                  | 74.00                  | -19.72       |
| 7323.00      | Average                      | 41.57                             | 11.01        | 52.58                  | 54.00                  | -1.42        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                            |               |                   |
|-----------|----------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                   | Test Date     | September 9, 2020 |
| Polarize  | Vertical                   | Test Engineer | Jerry Chang       |
| Detector  | Peak                       |               |                   |




| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dB $\mu$ V | Factor<br>dB | Actual<br>FS<br>dB $\mu$ V/m | Limit<br>@3m<br>dB $\mu$ V/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------------|--------------|------------------------------|------------------------------|--------------|
| 4960.00      | Peak                         | 36.65                                   | 4.46         | 41.11                        | 74.00                        | -32.89       |
| N/A          |                              |                                         |              |                              |                              |              |
|              |                              |                                         |              |                              |                              |              |
|              |                              |                                         |              |                              |                              |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

|           |                            |               |                   |
|-----------|----------------------------|---------------|-------------------|
| Test Mode | 8DPSK_EDR-3Mbps<br>High CH | Temp/Hum      | 25.0(°C)/ 42%RH   |
| Test Item | Harmonic                   | Test Date     | September 9, 2020 |
| Polarize  | Horizontal                 | Test Engineer | Jerry Chang       |
| Detector  | Peak                       |               |                   |



| Freq.<br>MHz | Detector<br>Mode<br>PK/QP/AV | Spectrum<br>Reading Level<br>dBμV | Factor<br>dB | Actual<br>FS<br>dBμV/m | Limit<br>@3m<br>dBμV/m | Margin<br>dB |
|--------------|------------------------------|-----------------------------------|--------------|------------------------|------------------------|--------------|
| 4960.00      | Peak                         | 42.10                             | 4.46         | 46.56                  | 74.00                  | -27.44       |
| 7440.00      | Peak                         | 42.76                             | 10.66        | 53.42                  | 74.00                  | -20.58       |
| 7440.00      | Average                      | 39.97                             | 10.66        | 50.63                  | 54.00                  | -3.37        |
| N/A          |                              |                                   |              |                        |                        |              |

**Remark:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. For above 1GHz, the EUT peak value was under average limit, therefore the Average value compliance with the average limit

- End of Test Report -