



SPORTON International Inc.


No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

Project No: CB10508219

RF Exposure Evaluation Report

Applicant's company	Plantronics, Inc.
Applicant Address	345 Encinal Street, Santa Cruz, CA 95060, USA.
FCC ID	AL8-RIG800
Manufacturer's company	Plantronics, Inc.
Manufacturer Address	345 Encinal Street, Santa Cruz, CA 95060, USA.

Product Name	Wireless Gaming headset
Brand Name	plantronics
Model Name	RIG 800
Ref. Standard(s)	47 CFR FCC Part 2 Subpart J, section 2.1093
Received Date	Jun. 30, 2016
Final Test Date	Aug. 14, 2016
Submission Type	Original Equipment



Sam Chen

SPORTON INTERNATIONAL INC.



Table of Contents

1. GENERAL DESCRIPTION.....	1
1.1. EUT General Information	1
1.2. Testing Location.....	1
2. RF EXPOSURE EVALUATION	2
2.1. Applicable Standard	2
2.2. SAR evaluation.....	2

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA662926	Rev. 01	Initial issue of report	Oct. 07, 2016

1. GENERAL DESCRIPTION

1.1. EUT General Information

RF General Information		
Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2400-2483.5	2403.35-2479.35	Pi/4 DQPSK

1.2. Testing Location

Testing Location		
☐	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
☒	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

2. RF EXPOSURE EVALUATION

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

- Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Tune-up Average Power		Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
(dBm)	(mW)			
-1.81	0.7	5	2.40335	0.20

- Per FCC KDB 447498 D01 v06 exclusion thresholds is $0.20 < 3$, RF exposure evaluation is not required.