

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

11.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


12. Radiated Emission


12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2026/10/10
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2026/10/10
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-5M	DDT-ZC03800	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2027/07/08
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2027/07/10
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2027/07/10
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2027/07/10
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04

PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/

12.2. Block diagram of test setup





12.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT	
MHz	Meters	uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m(Peak)	
		54.0 dBuV/m(Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz,

radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum

Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz, so the final test was performed with frequency range from 30 MHz to 25 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-04

Tested By:

Zhang Yibo

Test Mode:

TX BLE 1M Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:20.0°C;Humi:52.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26072123-2E\FCC BELOW 1G\3

Memo:

Sample Number: S26072123-013




Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	151.974	40.16	7.80	4.60	20.21	43.50	23.29	QP	Horizontal
2	196.023	38.42	10.80	4.86	21.68	43.50	21.82	QP	Horizontal
3	229.200	43.04	11.64	5.00	27.28	46.00	18.72	QP	Horizontal
4	271.205	36.14	12.62	5.16	21.52	46.00	24.48	QP	Horizontal
5	389.975	36.29	15.00	5.67	24.47	46.00	21.53	QP	Horizontal
6	584.852	30.1	18.50	6.35	22.14	46.00	23.86	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-04**Tested By:** Zhang Yibo**Test Mode:** TX BLE 1M Mode**Power Supply:** AC 120V/60Hz**Condition:** Temp:20.0°C;Humi:52.1%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2026 report data\Q26072123-2E\FCC BELOW 1G\4**Memo:** Sample Number: S26072123-013**Final Data List**

NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36.278	40.79	11.74	3.87	24.10	40.00	15.90	QP	Vertical
2	44.334	36.92	13.77	3.95	22.34	40.00	17.66	QP	Vertical
3	52.385	33.05	13.66	4.00	18.41	40.00	21.59	QP	Vertical
4	100.768	31.93	11.50	4.30	15.43	43.50	28.07	QP	Vertical
5	389.975	31.75	15.00	5.67	19.93	46.00	26.07	QP	Vertical
6	584.852	33.15	18.50	6.35	25.19	46.00	20.81	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-04

Tested By:

Zhang Yibo

Test Mode:

TX BLE 2M Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:20.0°C;Humi:52.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26072123-2E\FCC BELOW 1G\5

Memo:

Sample Number: S26072123-013



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	152.080	31.58	7.80	4.60	11.63	43.50	31.87	QP	Horizontal
2	229.682	38.1	11.67	5.00	22.37	46.00	23.63	QP	Horizontal
3	254.084	31.2	12.45	5.10	16.35	46.00	29.65	QP	Horizontal
4	389.975	36.8	15.00	5.67	24.98	46.00	21.02	QP	Horizontal
5	779.646	30.97	20.69	6.88	25.92	46.00	20.08	QP	Horizontal
6	974.390	29.66	22.20	7.30	27.71	54.00	26.29	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-04

Tested By:

Zhang Yibo

Test Mode:

TX BLE 2M Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:20.0°C;Humi:52.1%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26072123-2E\FCC BELOW 1G\6

Memo:

Sample Number: S26072123-013



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36.253	40.5	11.73	3.87	23.80	40.00	16.20	QP	Vertical
2	44.303	35.88	13.77	3.95	21.30	40.00	18.70	QP	Vertical
3	52.422	33.66	13.66	4.00	19.02	40.00	20.98	QP	Vertical
4	73.501	34.65	8.10	4.18	14.63	40.00	25.37	QP	Vertical
5	389.975	32.46	15.00	5.67	20.64	46.00	25.36	QP	Vertical
6	584.852	33.22	18.50	6.35	25.26	46.00	20.74	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-08

Tested By:

Liang Rijing

Test Mode:

TX BLE 1M 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\21

Memo:

Sample Number: S26072123-013



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4177.300	50.61	31.81	-41.11	41.31	74.00	32.69	PK	Horizontal
2	5054.500	50.21	34.00	-40.95	43.26	74.00	30.74	PK	Horizontal
3	7363.100	49.80	37.35	-39.70	47.45	74.00	26.55	PK	Horizontal
4	8223.300	48.78	37.90	-39.14	47.54	74.00	26.46	PK	Horizontal
5	11164.300	46.49	39.83	-35.14	51.18	74.00	22.82	PK	Horizontal
6	11975.200	45.06	39.75	-34.74	50.07	74.00	23.93	PK	Horizontal


Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11164.300	34.69	39.83	-35.14	39.38	54.00	14.62	AV	Horizontal
2	11975.200	33.29	39.75	-34.74	38.30	54.00	15.70	AV	Horizontal

Note:

- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijong
Test Mode: TX BLE 1M 2402MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\22
Memo: Sample Number: S26072123-013

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3901.900	50.20	31.60	-40.81	40.99	74.00	33.01	PK	Vertical
2	4933.800	50.38	33.64	-41.05	42.97	74.00	31.03	PK	Vertical
3	7290.000	48.75	37.72	-39.75	46.72	74.00	27.28	PK	Vertical
4	8301.500	49.09	38.00	-39.09	48.00	74.00	26.00	PK	Vertical
5	11171.100	45.78	39.84	-35.15	50.47	74.00	23.53	PK	Vertical
6	12002.400	45.43	39.80	-34.48	50.75	74.00	23.25	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11171.100	33.63	39.84	-35.15	38.32	54.00	15.68	AV	Vertical
2	12002.400	33.59	39.80	-34.48	38.91	54.00	15.09	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 1M 2440MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\23
Memo: Sample Number: S26072123-013



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3896.800	50.21	31.59	-40.81	40.99	74.00	33.01	PK	Horizontal
2	5001.800	50.15	33.90	-40.64	43.41	74.00	30.59	PK	Horizontal
3	7361.400	49.09	37.35	-39.70	46.74	74.00	27.26	PK	Horizontal
4	8123.000	48.91	37.90	-39.17	47.64	74.00	26.36	PK	Horizontal
5	11597.800	45.70	39.60	-34.82	50.48	74.00	23.52	PK	Horizontal
6	12296.500	45.89	39.80	-35.14	50.55	74.00	23.45	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11597.800	33.83	39.60	-34.82	38.61	54.00	15.39	AV	Horizontal
2	12296.500	33.20	39.80	-35.14	37.86	54.00	16.14	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 1M 2440MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\24
Memo: Sample Number: S26072123-013



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3896.800	50.63	31.59	-40.81	41.41	74.00	32.59	PK	Vertical
2	4784.200	50.75	33.14	-41.32	42.57	74.00	31.43	PK	Vertical
3	7383.500	48.76	37.27	-39.72	46.31	74.00	27.69	PK	Vertical
4	8335.500	49.23	38.00	-39.06	48.17	74.00	25.83	PK	Vertical
5	11135.400	45.67	39.77	-35.13	50.31	74.00	23.69	PK	Vertical
6	12097.600	44.66	39.90	-34.69	49.87	74.00	24.13	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8335.500	36.61	38.00	-39.06	35.55	54.00	18.45	AV	Vertical
2	11135.400	34.33	39.77	-35.13	38.97	54.00	15.03	AV	Vertical
3	12097.600	32.79	39.90	-34.69	38.00	54.00	16.00	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 1M 2480MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room

File Path:d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\25

Memo:Sample Number: S26072123-013



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3839.000	50.62	31.43	-40.93	41.12	74.00	32.88	PK	Horizontal
2	5061.300	49.83	34.00	-40.99	42.84	74.00	31.16	PK	Horizontal
3	7386.900	49.65	37.25	-39.72	47.18	74.00	26.82	PK	Horizontal
4	8420.500	48.80	38.18	-38.96	48.02	74.00	25.98	PK	Horizontal
5	11130.300	45.99	39.76	-35.13	50.62	74.00	23.38	PK	Horizontal
6	12379.800	44.88	39.72	-34.51	50.09	74.00	23.91	PK	Horizontal

Final Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8420.500	37.42	38.18	-38.96	36.64	54.00	17.36	AV	Horizontal
2	11130.300	34.81	39.76	-35.13	39.44	54.00	14.56	AV	Horizontal
3	12379.800	35.16	39.72	-34.51	40.37	54.00	13.63	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:2026-09-08

Tested By:Liang Rijing

Test Mode:TX BLE 1M 2480MHz Mode


Power Supply:AC 120V/60Hz

Condition:Temp:23.7°C;Humi:54.0%

Test Site:4# Fully Anechoic Room

File Path:d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\25

Memo:Sample Number: S26072123-013



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3849.200	51.14	31.50	-40.91	41.73	74.00	32.27	PK	Vertical
2	5061.300	50.27	34.00	-40.99	43.28	74.00	30.72	PK	Vertical
3	7713.300	49.68	37.33	-39.65	47.36	74.00	26.64	PK	Vertical
4	8372.900	47.92	38.05	-39.03	46.94	74.00	27.06	PK	Vertical
5	11101.400	46.92	39.70	-35.11	51.51	74.00	22.49	PK	Vertical
6	12114.600	45.15	39.90	-34.79	50.26	74.00	23.74	PK	Vertical

Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11101.400	34.94	39.70	-35.11	39.53	54.00	14.47	AV	Vertical
2	12114.600	34.79	39.90	-34.79	39.90	54.00	14.10	AV	Vertical

Note:
1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-08

Tested By:

Liang Rijing

Test Mode:

TX BLE 2M 2404MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\27

Memo:

Sample Number: S26072123-013



Suspected Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4190.900	50.85	31.86	-41.17	41.54	74.00	32.46	PK	Horizontal
2	4932.100	51.51	33.63	-41.06	44.08	74.00	29.92	PK	Horizontal
3	7378.400	48.96	37.29	-39.71	46.54	74.00	27.46	PK	Horizontal
4	8420.500	48.43	38.18	-38.96	47.65	74.00	26.35	PK	Horizontal
5	10866.800	46.19	39.93	-35.77	50.35	74.00	23.65	PK	Horizontal
6	12031.300	44.55	39.83	-34.54	49.84	74.00	24.16	PK	Horizontal


Final Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10866.800	33.23	39.93	-35.77	37.39	54.00	16.61	AV	Horizontal
2	12031.300	33.21	39.83	-34.54	38.50	54.00	15.50	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 2M 2404MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\28
Memo: Sample Number: S26072123-013

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4383.000	51.28	32.30	-40.97	42.61	74.00	31.39	PK	Vertical
2	4989.900	51.19	33.86	-40.69	44.36	74.00	29.64	PK	Vertical
3	7259.400	48.54	37.78	-40.02	46.30	74.00	27.70	PK	Vertical
4	8333.800	48.04	38.00	-39.06	46.98	74.00	27.02	PK	Vertical
5	11135.400	45.49	39.77	-35.13	50.13	74.00	23.87	PK	Vertical
6	12009.200	44.84	39.81	-34.49	50.16	74.00	23.84	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11135.400	34.63	39.77	-35.13	39.27	54.00	14.73	AV	Vertical
2	12009.200	33.68	39.81	-34.49	39.00	54.00	15.00	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-08

Tested By:

Liang Rijing

Test Mode:

TX BLE 2M 2440MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\29

Memo:

Sample Number: S26072123-013



Suspected Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3878.100	50.66	31.56	-40.85	41.37	74.00	32.63	PK	Horizontal
2	5119.100	49.95	33.96	-41.14	42.77	74.00	31.23	PK	Horizontal
3	7264.500	49.01	37.77	-39.98	46.80	74.00	27.20	PK	Horizontal
4	8330.400	48.15	38.00	-39.07	47.08	74.00	26.92	PK	Horizontal
5	10710.400	45.62	40.00	-35.70	49.92	74.00	24.08	PK	Horizontal
6	11978.600	45.93	39.76	-34.70	50.99	74.00	23.01	PK	Horizontal

Final Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10710.400	35.39	40.00	-35.70	39.69	54.00	14.31	AV	Horizontal
2	11978.600	34.14	39.76	-34.70	39.20	54.00	14.80	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-09-08

Tested By:

Liang Rijing

Test Mode:

TX BLE 2M 2440MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\30

Memo:

Sample Number: S26072123-013



Suspected Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2320.900	56.87	28.10	-40.08	44.89	74.00	29.11	PK	Vertical
2	4104.200	50.02	31.61	-40.77	40.86	74.00	33.14	PK	Vertical
3	4964.400	51.14	33.76	-40.85	44.05	74.00	29.95	PK	Vertical
4	7477.000	49.71	37.10	-39.95	46.86	74.00	27.14	PK	Vertical
5	11099.700	45.40	39.70	-35.11	49.99	74.00	24.01	PK	Vertical
6	12101.000	45.18	39.90	-34.71	50.37	74.00	23.63	PK	Vertical

Final Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11099.700	35.23	39.70	-35.11	39.82	54.00	14.18	AV	Vertical
2	12101.000	34.29	39.90	-34.71	39.48	54.00	14.52	AV	Vertical


Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 2M 2478MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\31
Memo: Sample Number: S26072123-013

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3878.100	50.34	31.56	-40.85	41.05	74.00	32.95	PK	Horizontal
2	4930.400	50.40	33.62	-41.07	42.95	74.00	31.05	PK	Horizontal
3	7378.400	49.16	37.29	-39.71	46.74	74.00	27.26	PK	Horizontal
4	8029.500	49.72	37.90	-39.57	48.05	74.00	25.95	PK	Horizontal
5	11179.600	45.57	39.86	-35.15	50.28	74.00	23.72	PK	Horizontal
6	12121.400	45.45	39.90	-34.83	50.52	74.00	23.48	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8029.500	37.36	37.90	-39.57	35.69	54.00	18.31	AV	Horizontal
2	11179.600	33.85	39.86	-35.15	38.56	54.00	15.44	AV	Horizontal
3	12121.400	34.40	39.90	-34.83	39.47	54.00	14.53	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-09-08 **Tested By:** Liang Rijing
Test Mode: TX BLE 2M 2478MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\32
Memo: Sample Number: S26072123-013

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3895.100	49.78	31.59	-40.81	40.56	74.00	33.44	PK	Vertical
2	4784.200	51.44	33.14	-41.32	43.26	74.00	30.74	PK	Vertical
3	7414.100	49.22	37.17	-39.77	46.62	74.00	27.38	PK	Vertical
4	8095.800	48.52	37.90	-39.20	47.22	74.00	26.78	PK	Vertical
5	11273.100	46.65	39.97	-35.81	50.81	74.00	23.19	PK	Vertical
6	12126.500	45.49	39.90	-34.87	50.52	74.00	23.48	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11273.100	34.28	39.97	-35.81	38.44	54.00	15.56	AV	Vertical
2	12126.500	32.96	39.90	-34.87	37.99	54.00	16.01	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-11 **Tested By:** Cao Jie
Test Mode: TX BLE 1M 2402MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072123\FCC ABOVE 1G BLE\21
Memo: Sample Number: S26072123-002

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	21287.511	48.93	38.43	3.80	40.42	74.00	33.58	PK	Horizontal
2	23586.619	51.13	39.18	4.66	44.29	74.00	29.71	PK	Horizontal
3	25125.626	51.02	39.56	4.78	45.49	74.00	28.51	PK	Horizontal
4	33054.328	47.58	41.62	5.38	46.54	74.00	27.46	PK	Horizontal
5	36661.458	48.56	42.87	6.32	48.48	74.00	25.52	PK	Horizontal
6	38922.964	47.58	45.75	6.47	49.93	74.00	24.07	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36661.458	43.26	42.87	6.32	43.18	54.00	10.82	AV	Horizontal
2	38922.964	42.17	45.75	6.47	44.52	54.00	9.48	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-11 **Tested By:** Cao Jie
Test Mode: TX BLE 1M 2402MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072123\FCC ABOVE 1G BLE\22
Memo: Sample Number: S26072123-002



Suspected Data List

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	21284.825	50.34	38.43	3.80	41.83	74.00	32.17	PK	Vertical
2	23495.300	50.49	39.20	4.70	43.59	74.00	30.41	PK	Vertical
3	24894.640	50.59	39.55	4.73	45.00	74.00	29.00	PK	Vertical
4	32944.207	47.23	41.58	5.34	46.22	74.00	27.78	PK	Vertical
5	36570.138	48.70	42.86	6.39	48.70	74.00	25.30	PK	Vertical
6	39108.290	46.91	45.99	6.60	49.40	74.00	24.60	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36570.138	42.65	42.86	6.39	42.65	54.00	11.35	AV	Vertical
2	39108.290	42.10	45.99	6.60	44.59	54.00	9.41	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-11 **Tested By:** Cao Jie
Test Mode: TX BLE 2M 2404MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072123\FCC ABOVE 1G BLE\23
Memo: Sample Number: S26072123-002

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	21421.804	48.96	38.44	3.86	40.42	74.00	33.58	PK	Horizontal
2	23479.184	50.28	39.20	4.69	43.35	74.00	30.65	PK	Horizontal
3	24875.839	50.22	39.54	4.72	44.60	74.00	29.40	PK	Horizontal
4	32839.458	47.18	41.54	5.29	46.09	74.00	27.91	PK	Horizontal
5	36443.902	49.53	42.84	6.37	49.51	74.00	24.49	PK	Horizontal
6	38968.624	48.91	45.84	6.54	51.38	74.00	22.62	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36443.902	42.51	42.84	6.37	42.49	54.00	11.51	AV	Horizontal
2	38968.624	41.34	45.84	6.54	43.81	54.00	10.19	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-11 **Tested By:** Cao Jie
Test Mode: TX BLE 2M 2404MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072123\FCC ABOVE 1G BLE\24
Memo: Sample Number: S26072123-002

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	21628.617	48.98	38.46	3.98	40.44	74.00	33.56	PK	Vertical
2	23487.242	49.52	39.20	4.70	42.61	74.00	31.39	PK	Vertical
3	24746.917	50.32	39.47	4.69	44.56	74.00	29.44	PK	Vertical
4	33099.988	47.05	41.64	5.39	45.96	74.00	28.04	PK	Vertical
5	36580.881	48.73	42.86	6.38	48.71	74.00	25.29	PK	Vertical
6	39027.713	47.08	45.92	6.59	49.61	74.00	24.39	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	36580.881	42.33	42.86	6.38	42.31	54.00	11.69	AV	Vertical
2	39027.713	41.21	45.92	6.59	43.74	54.00	10.26	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

13. Band Edge Compliance

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/

13.2. Block diagram of test setup



13.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 1M 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\19

Memo:

Sample Number: S26072123-002



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2384.930	54.50	28.17	-47.95	44.72	74.00	29.28	PK	Horizontal
2	2390.000	52.35	28.18	-47.94	42.59	74.00	31.41	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 1M 2402MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\20

Memo:

Sample Number: S26072123-002



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2382.710	54.79	28.17	-47.96	45.00	74.00	29.00	PK	Vertical
2	2390.000	54.24	28.18	-47.94	44.48	74.00	29.52	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 2M 2404MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\17

Memo:

Sample Number: S26072123-002



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2383.170	55.20	28.17	-47.96	45.41	74.00	28.59	PK	Horizontal
2	2390.000	51.92	28.18	-47.94	42.16	74.00	31.84	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 2M 2404MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\18

Memo:

Sample Number: S26072123-002



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2385.480	55.44	28.17	-47.95	45.66	74.00	28.34	PK	Vertical
2	2390.000	52.60	28.18	-47.94	42.84	74.00	31.16	PK	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 1M 2480MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\13

Memo:

Sample Number: S26072123-002




Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	54.40	28.60	-47.98	45.02	74.00	28.98	PK	Horizontal
2	2483.944	56.10	28.60	-47.98	46.72	74.00	27.28	PK	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-20**Tested By:** Cao Jie**Test Mode:** TX BLE 1M 2480MHz Mode**Power Supply:** AC 120V/60Hz**Condition:** Temp:23.7°C;Humi:54.0%**Test Site:** 4# Fully Anechoic Room**File Path:** d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\14**Memo:** Sample Number: S26072123-002

Suspected Data List

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	62.77	28.60	-47.98	53.39	74.00	20.61	PK	Vertical
2	2483.980	64.07	28.60	-47.98	54.69	74.00	19.31	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	57.55	28.60	-47.98	48.17	54.00	5.83	AV	Vertical
2	2483.980	57.23	28.60	-47.98	47.85	54.00	6.15	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-07-20

Tested By:

Cao Jie

Test Mode:

TX BLE 2M 2478MHz Mode

Power Supply:

AC 120V/60Hz

Condition:

Temp:23.7°C;Humi:54.0%

Test Site:


4# Fully Anechoic Room

File Path:

d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\15

Memo:

Sample Number: S26072123-002



Suspected Data List									
NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	57.38	28.60	-47.98	48.00	74.00	26.00	PK	Horizontal
2	2483.746	57.84	28.60	-47.98	48.46	74.00	25.54	PK	Horizontal

Final Data List									
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.746	53.51	28.60	-47.98	44.13	54.00	9.87	AV	Horizontal


Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-07-20 **Tested By:** Cao Jie
Test Mode: TX BLE 2M 2478MHz Mode **Power Supply:** AC 120V/60Hz
Condition: Temp:23.7°C;Humi:54.0% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q20260720 COVE A1\FCC ABOVE 1G BLE\16
Memo: Sample Number: S26072123-002



Suspected Data List

NO	Freq. [MHz]	Reading [dBV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	65.89	28.60	-47.98	56.51	74.00	17.49	PK	Vertical
2	2483.710	64.59	28.60	-47.98	55.21	74.00	18.79	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	57.82	28.60	-47.98	48.44	54.00	5.56	AV	Vertical
2	2483.708	57.51	28.60	-47.98	48.13	54.00	5.87	AV	Vertical

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Power Line Conducted Emissions

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
EMI Test Receiver	R&S	ESCI 3	DDT-ZC00235	2027/06/10
Two Line V-Network	R&S	ENV216	DDT-ZC00535	2027/06/14
Pulse Limiter	SCHWARZBECK	ESH3-Z2	DDT-ZC00539	2027/06/10
CE Cable 1	R&S	ESU8/RF2	DDT-ZC00566	2027/06/21
Conducted & Radiated Software	Audix	e3	DDT-ZC00562	/
Two-line V-shaped artificial network	ROHDE&SCHWARZ	ENV216	DDT-ZC05693	2026/11/04
Artificial mains	R&S	ESH2-Z5	DDT-ZC00538	2027/06/09

14.2. Block diagram of test setup



14.3. Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

14.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.


14.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room
 Test Date : 2026-09-04
 Power Supply : AC 120V/60Hz
 Condition : TEMP:21.2°C, RH:51.4%
 Memo : Sample Number: S26072123-013

D:\2026 CE Report Data\Q26072123-2E\0904 CE\0904
 CE.EM6
 Tested By : Zhang Yibo
 Test Mode : Tx mode
 LISN : 2026 1# ENV 216/LINE

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Margin (dB)	Detector	Phase
1	0.49	-6.87	9.57	0.00	9.87	12.57	56.23	43.66	QP	LINE
2	0.49	-11.63	9.57	0.00	9.87	7.81	46.23	38.42	Average	LINE
3	4.03	6.21	9.61	0.01	9.88	25.71	56.00	30.29	QP	LINE
4	4.03	-2.19	9.61	0.01	9.88	17.31	46.00	28.69	Average	LINE
5	6.95	2.55	9.63	0.03	9.88	22.09	60.00	37.91	QP	LINE
6	6.95	-9.23	9.63	0.03	9.88	10.31	50.00	39.69	Average	LINE
7	12.06	-8.86	9.78	0.07	9.91	10.90	60.00	49.10	QP	LINE
8	12.06	-13.83	9.78	0.07	9.91	5.93	50.00	44.07	Average	LINE
9	20.16	3.27	10.05	0.09	9.94	23.35	60.00	36.65	QP	LINE
10	20.16	-7.57	10.05	0.09	9.94	12.51	50.00	37.49	Average	LINE
11	28.15	-6.40	10.14	0.12	9.99	13.85	60.00	46.15	QP	LINE
12	28.15	-13.81	10.14	0.12	9.99	6.44	50.00	43.56	Average	LINE

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room

D:\2026 CE Report Data\Q26072123-2E\0904 CE\0904
CE.EM6

Test Date : 2026-09-04

Tested By : Zhang Yibo

Power Supply : AC 120V/60Hz


Test Mode : Tx mode

Condition : TEMP:21.2°C, RH:51.4%

LISN : 2026 1# ENV 216/NEUTRAL

Memo : Sample Number: S26072123-013

Data: 8



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Margin	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.48	-5.50	9.59	0.00	9.87	13.96	56.36	42.40	QP	NEUTRAL
2	0.48	-11.17	9.59	0.00	9.87	8.29	46.36	38.07	Average	NEUTRAL
3	4.03	7.97	9.65	0.01	9.88	27.51	56.00	28.49	QP	NEUTRAL
4	4.03	-2.44	9.65	0.01	9.88	17.10	46.00	28.90	Average	NEUTRAL
5	6.29	-3.17	9.67	0.03	9.88	16.41	60.00	43.59	QP	NEUTRAL
6	6.29	-10.50	9.67	0.03	9.88	9.08	50.00	40.92	Average	NEUTRAL
7	12.06	-5.20	9.84	0.07	9.91	14.62	60.00	45.38	QP	NEUTRAL
8	12.06	-14.08	9.84	0.07	9.91	5.74	50.00	44.26	Average	NEUTRAL
9	20.16	1.13	10.15	0.09	9.94	21.31	60.00	38.69	QP	NEUTRAL
10	20.16	-9.58	10.15	0.09	9.94	10.60	50.00	39.40	Average	NEUTRAL
11	28.15	-8.95	10.27	0.12	9.99	11.43	60.00	48.57	QP	NEUTRAL
12	28.15	-13.79	10.27	0.12	9.99	6.59	50.00	43.41	Average	NEUTRAL

Note:

1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto

16. Photos of the EUT

Please refer to DDT-Q26072123-1E appendix I

-----End Report-----