

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	CHARGE4J
Trade Mark	:	JBL
FCC ID	:	APIJBLCHARGE4J
IC	:	6132A-JBLCHARGE4J
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	6
2.	General test information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test.....	8
2.5.	Test environment conditions	8
2.6.	Deviations of test standard	8
2.7.	Test laboratory	8
2.8.	Measurement uncertainty	9
3.	Equipment used during test.....	10
4.	6dB Bandwidth and 99% Bandwidth	11
4.1.	Block diagram of test setup	11
4.2.	Limits	11
4.3.	Test Procedure.....	11
4.4.	Test Result	11
4.5.	Original test data	12
5.	Maximum Peak Output Power	13
5.1.	Block diagram of test setup	13
5.2.	Limits	13
5.3.	Test Procedure.....	13
5.4.	Test Result	13
5.5.	Original test data	14
6.	Power Spectral Density.....	15
6.1.	Block diagram of test setup	15
6.2.	Limits	15
6.3.	Test Procedure.....	15
6.4.	Test Result	15
6.5.	Original test data	16
7.	Band Edge Compliance (conducted method)	17
7.1.	Block diagram of test setup	17
7.2.	Limits	17
7.3.	Test Procedure.....	17
7.4.	Test Result	18

7.5.	Original test data	18
8.	Radiated emission	19
8.1.	Block diagram of test setup	19
8.2.	Limit.....	20
8.3.	Test Procedure.....	21
8.4.	Test result.....	23
9.	RF Conducted Spurious Emissions.....	29
9.1.	Block diagram of test setup	29
9.2.	Limits	29
9.3.	Test Procedure.....	29
9.4.	Test Result	30
9.5.	Original test data	30
10.	Emission in restricted frequency bands.....	34
10.1.	Block diagram of test setup	34
10.2.	Limit.....	34
10.3.	Test Procedure.....	34
10.4.	Test result.....	34
11.	Power Line Conducted Emission.....	40
11.1.	Block diagram of test setup	40
11.2.	Power Line Conducted Emission Limits	40
11.3.	Test Procedure.....	40
11.4.	Test Result	41
12.	Antenna Requirements	46
12.1.	Limit.....	46
12.2.	Result	46

TEST REPORT DECLARE

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Portable Bluetooth Speaker
Model No.	:	CHARGE4J
Trade mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used:

ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No:	DDT-R18091806-1E2		
Date of Receipt:	Jun. 26, 2018 and Sep. 19, 2018	Date of Test:	Jun. 26, 2018 ~ Jul. 17, 2018 and Sep. 19, 2018 ~ Sep. 26, 2018

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jul. 17, 2018	
V1.0	Add a new battery	Sep. 26, 2018	Ella Gong

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013 RSS-247 Issue 2	PASS
Band Edge Compliance (conducted method)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Radiation Emission	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
RF Conducted Spurious Emissions	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Emission in restricted frequency bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 RSS-Gen Issue 5	PASS
Antenna requirement	FCC Part 15: 15.203 RSS-Gen Issue 5	PASS
Note: This report added a new battery based on the original report: DDT-R18052803-1E3, this change doesn't influence the RF performance, so only radiated emission (below 1GHz) and Power Line Conducted Emissions were tested and recorded in this report, and the original test data was retained in this report.		

2. General test information

2.1. Description of EUT

EUT* Name	: Portable Bluetooth Speaker
Model Number	: CHARGE4J
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from external AC Adapter Lithium-ion polymer(3.6V/ 7500mAh) built-in battery
Radio Specification	: Bluetooth V4.2
Operation frequency	: 2402MHz -2480MHz
Modulation	: GFSK,
Data rate	: 1Mbps
Antenna Type	: Integrated antenna, maximum PK gain: 2.23dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

Channel information					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	15	2430MHz	29	2458MHz
2	2404MHz	16	2432MHz	30	2460MHz
3	2406MHz	17	2434MHz	31	2462MHz
4	2408MHz	18	2436MHz	32	2464MHz
5	2410MHz	19	2438MHz	33	2466MHz
6	2412MHz	20	2440MHz	34	2468MHz
7	2414MHz	21	2442MHz	35	2470MHz
8	2416MHz	22	2444MHz	36	2472MHz
9	2418MHz	23	2446MHz	37	2474MHz
10	2420MHz	24	2448MHz	38	2476MHz
11	2422MHz	25	2450MHz	39	2478MHz
12	2424MHz	26	2452MHz	40	2480MHz
13	2426MHz	27	2454MHz		
14	2428MHz	28	2456MHz		


2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
USB cable	Harman	N/A	N/A	Length: 1.2m, unshielded

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
AC Adapter	HUAWEI	HW-050450C00	N/A	Input: 100-240V~50/60Hz, Output: 5V/2A or 4.5V/5A or 5V/4.5A

2.4. Block diagram of EUT configuration for test



Test software: BlueSuite 2.6.4.EXE

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as blow table:

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK	CH0	2402
	CH19	2440
	CH39	2480
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.		

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. Deviations of test standard

No Deviation.

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB (10 MHz ≤ f < 3.6GHz);
	1.38dB (3.6GHz ≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Power Spectral Density	0.74dB (10 MHz ≤ f < 3.6GHz);
	1.38dB (3.6GHz ≤ f < 8GHz)
Frequencies Stability	6.7 x 10 ⁻⁸ (Antenna couple method)
	5.5 x 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86dB (10 MHz ≤ f < 3.6GHz);
	1.40dB (3.6GHz ≤ f < 8GHz)
	1.66dB (8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20kHz)	3×10 ⁻⁸
Temperature	0.4℃
Humidity	2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-40GHz)	4.10dB (1-6GHz)
	4.40dB (6GHz-18GHz)
	3.54dB (18GHz-26GHz)
	4.30dB (26GHz-40GHz)
Uncertainty for Power line conduction emission test	3.32dB (150kHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Oct. 23, 2017	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 29, 2018	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 23, 2017	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 29, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2017	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2017	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2017	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2017	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2017	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2017	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 29, 2018	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2017	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 17, 2017	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Oct. 17, 2017	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Nov. 09, 2017	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 21, 2017	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 21, 2017	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2017	1 Year
RF Cable	N/A	SMAJ-SMA J-1M+ 11M	17070133+17070131	Nov. 08, 2017	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2017	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2017	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2017	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2017	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2017	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the 6dB and 99% bandwidth of signal.

4.4. Test Result

Mode	Channel	6dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	6 dB width Limit (MHz)	Conclusion
GFSK	CH0	0.704	1.068	>0.5	PASS
	CH19	0.704	1.064	>0.5	PASS
	CH39	0.712	1.064	>0.5	PASS

4.5. Original test data



5. Maximum Peak Output Power

5.1. Block diagram of test setup

Same with 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:


RBW:	3MHz
VBW:	10MHz
Span	>1.5x 6dB bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges measure out the PK output power.

5.4. Test Result

Mode	Freq (MHz)	Peak Output Power (dBm)	Limit (dBm)	Conclusion
GFSK	2402	2.21	30	PASS
	2440	5.47	30	PASS
	2480	6.98	30	PASS

5.5. Original test data



6. Power Spectral Density

6.1. Block diagram of test setup

Same with 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test Result

EUT Set Mode	Channel	Result (dBm/30kHz)	Result (dBm/3kHz)
GFSK	CH0	0.27	-9.73
	CH19	3.56	-6.44
	CH39	5.10	-4.90
Note: Result (dBm/3kHz) = Result (dBm/30kHz)- 10dB			
Limit: <8dBm/3kHz		Conclusion: PASS	

6.5. Original test data



7. Band Edge Compliance (conducted method)

7.1. Block diagram of test setup

Same with 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
GFSK	CH0	2.375GHz-2.405GHz	PASS
	CH39	2.476GHz-2.506GHz	PASS


7.5. Original test data




8. Radiated emission

8.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.G
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(?)
13.36-13.41			

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$	$67.6-20\log(F)$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$	$87.6-20\log(F)$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\log(30\text{m}/3\text{m})$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical

axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of

Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHzso below final test was performed with frequency range from 30MHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 3MHz for Average measure (according ANSI C63.10:2013 clause

4.1.4.2.2 procedure for average measure).

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9kHz to 25GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in GFSK, Tx 2440MHz mode.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.


Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2018-06-29
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5'C,Humi:55.5%,
 Press:100.1kPa
Memo : (Li-ion Battery: ID998)

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6
Tested By : Talent
Model Number : CHARGE4J
Test Mode : TX mode
Antenna/Distance : 2017 VULB 9163 1#/3m/HORIZONTAL

Data: 26



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	41.42	2.99	12.79	3.89	19.67	40.00	-20.33	QP	HORIZONTAL
2	47.83	2.09	13.56	3.97	19.62	40.00	-20.38	QP	HORIZONTAL
3	108.65	2.35	10.45	4.48	17.28	43.50	-26.22	QP	HORIZONTAL
4	220.62	6.41	11.94	5.14	23.49	46.00	-22.51	QP	HORIZONTAL
5	298.27	5.54	13.27	5.51	24.32	46.00	-21.68	QP	HORIZONTAL
6	343.18	13.41	14.19	5.72	33.32	46.00	-12.68	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6

Test Date : 2018-06-29

Tested By : Talent

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4J

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5'C,Humi:55.5%,
Press:100.1kPa

Antenna/Distance : 2017 VULB 9163 1#/3m/VERTICAL

Memo : (Li-ion Battery: ID998-B)

Data: 27



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	40.56	1.36	12.67	3.88	17.91	40.00	-22.09	QP	VERTICAL
2	49.71	0.71	13.77	3.99	18.47	40.00	-21.53	QP	VERTICAL
3	74.92	1.90	8.39	4.21	14.50	40.00	-25.50	QP	VERTICAL
4	99.88	0.18	11.48	4.41	16.07	43.50	-27.43	QP	VERTICAL
5	252.06	8.00	12.53	5.31	25.84	46.00	-20.16	QP	VERTICAL
6	348.03	6.59	14.28	5.74	26.61	46.00	-19.39	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18091806-1E CHARGE4J\FCC
BELOW1G.EM6

Test Date : 2018-09-27

Tested By : JACKY

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4J

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5'C, Humi:55.5%,
Press:100.1kPa

Antenna/Distance : 2017 VULB 9163 1#/3m/VERTICAL

Memo : (Li-ion Battery: ID998-B)

Data: 3



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	48.67	2.72	13.66	3.98	20.36	40.00	-19.64	QP	VERTICAL
2	57.80	8.48	11.89	4.07	24.44	40.00	-15.56	QP	VERTICAL
3	70.83	6.90	9.06	4.18	20.14	40.00	-19.86	QP	VERTICAL
4	109.03	2.08	10.41	4.49	16.98	43.50	-26.52	QP	VERTICAL
5	247.68	3.40	12.45	5.28	21.13	46.00	-24.87	QP	VERTICAL
6	603.54	3.25	19.41	6.68	29.34	46.00	-16.66	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2018 RE1# Report Data\Q18091806-1E CHARGE4J\FCC
BELOW1G.EM6

Test Date : 2018-09-27

Tested By : JACKY

EUT : Portable Bluetooth Speaker

Model Number : CHARGE4J

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5'C, Humi:55.5%,
Press:100.1kPa

Antenna/Distance : 2017 VULB 9163 1#/3m/HORIZONTAL

Memo : BLE

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	48.84	1.68	13.67	3.98	19.33	40.00	-20.67	Peak	HORIZONTAL
2	54.84	6.99	12.58	4.04	23.61	40.00	-16.39	Peak	HORIZONTAL
3	100.93	1.66	11.38	4.42	17.46	43.50	-26.04	Peak	HORIZONTAL
4	222.95	4.68	11.98	5.15	21.81	46.00	-24.19	Peak	HORIZONTAL
5	252.06	5.09	12.53	5.31	22.93	46.00	-23.07	Peak	HORIZONTAL
6	706.70	3.98	19.81	7.03	30.82	46.00	-15.18	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq. (MHz)	Read level (dBμV)	Antenn a Factor (dB/m)	PRM Facto r(dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμ V/m)	Margin (dB)	Detecto r type	Polarization
GFSK Tx mode 2402MHz									
5981.00	48.94	35.69	43.21	8.20	49.62	74.00	-24.38	Peak	HORIZONTAL
7375.00	47.69	36.95	43.61	8.67	49.70	74.00	-24.30	Peak	HORIZONTAL
8633.00	46.95	37.35	43.99	9.95	50.26	74.00	-23.74	Peak	HORIZONTAL
9449.00	47.62	37.68	44.23	10.60	51.67	74.00	-22.33	Peak	HORIZONTAL
12118.00	46.15	38.88	44.13	11.01	51.91	74.00	-22.09	Peak	HORIZONTAL
13002.00	47.41	39.30	44.35	11.35	53.71	74.00	-20.29	Peak	HORIZONTAL
5998.00	49.48	35.70	43.20	8.21	50.19	74.00	-23.81	Peak	VERTICAL
7205.00	46.97	36.88	43.56	8.51	48.80	74.00	-25.20	Peak	VERTICAL
8395.00	47.15	37.28	43.92	9.68	50.19	74.00	-23.81	Peak	VERTICAL
9007.00	47.80	37.50	44.10	10.37	51.57	74.00	-22.43	Peak	VERTICAL
11387.00	47.07	38.65	44.19	11.03	52.56	74.00	-21.44	Peak	VERTICAL
13104.00	46.44	39.40	44.38	11.46	52.92	74.00	-21.08	Peak	VERTICAL
GFSK Tx mode 2440MHz									
5369.00	50.26	35.37	43.58	7.81	49.86	74.00	-24.14	Peak	HORIZONTAL
6831.00	48.00	36.43	43.45	8.31	49.29	74.00	-24.71	Peak	HORIZONTAL
8089.00	47.25	37.22	43.83	9.33	49.97	74.00	-24.03	Peak	HORIZONTAL
8531.00	48.13	37.31	43.96	9.84	51.32	74.00	-22.68	Peak	HORIZONTAL
12492.00	47.52	38.80	44.22	11.16	53.26	74.00	-20.74	Peak	HORIZONTAL
14056.00	46.97	40.17	44.58	12.39	54.95	74.00	-19.05	Peak	HORIZONTAL
4876.00	48.40	34.80	43.87	7.46	46.79	74.00	-27.21	Peak	VERTICAL
5692.00	48.88	35.58	43.38	8.02	49.10	74.00	-24.90	Peak	VERTICAL
7103.00	48.08	36.84	43.53	8.42	49.81	74.00	-24.19	Peak	VERTICAL
8225.00	47.75	37.24	43.87	9.49	50.61	74.00	-23.39	Peak	VERTICAL
9534.00	49.31	37.73	44.26	10.65	53.43	74.00	-20.57	Peak	VERTICAL
12713.00	47.08	39.01	44.28	11.24	53.05	74.00	-20.95	Peak	VERTICAL
GFSK Tx mode 2480MHz									
5726.00	48.71	35.59	43.36	8.04	48.98	74.00	-25.02	Peak	HORIZONTAL
6882.00	47.70	36.54	43.46	8.32	49.10	74.00	-24.90	Peak	HORIZONTAL
7443.00	47.21	36.98	43.63	8.73	49.29	74.00	-24.71	Peak	HORIZONTAL
8735.00	47.20	37.39	44.02	10.07	50.64	74.00	-23.36	Peak	HORIZONTAL
12050.00	46.89	38.89	44.11	10.99	52.66	74.00	-21.34	Peak	HORIZONTAL
13614.00	46.76	39.85	44.50	11.97	54.08	74.00	-19.92	Peak	HORIZONTAL
5998.00	49.66	35.70	43.20	8.21	50.37	74.00	-23.63	Peak	VERTICAL
6746.00	48.55	36.24	43.42	8.30	49.67	74.00	-24.33	Peak	VERTICAL
7936.00	47.94	37.17	43.78	9.17	50.50	74.00	-23.50	Peak	VERTICAL
9466.00	48.06	37.69	44.24	10.61	52.12	74.00	-21.88	Peak	VERTICAL
12509.00	47.00	38.81	44.23	11.16	52.74	74.00	-21.26	Peak	VERTICAL
13138.00	47.06	39.44	44.38	11.49	53.61	74.00	-20.39	Peak	VERTICAL
Result: Pass									

Note:1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup

Same as section 4.1

9.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test Result

Mode	Freq. (MHz)	Conclusion
GFSK	Hopping off 2402	PASS
	Hopping off 2441	PASS
	Hopping off 2480	PASS


9.5. Original test data






Date: 28.JUN.2018 14:19:11

BLE_ANT1_2440_Ref




Date: 28.JUN.2018 14:20:17

BLE_ANT1_2440_30~1000




Date: 28.JUN.2018 14:20:26

BLE_ANT1_2440_1000~26500




Date: 28.JUN.2018 14:20:37

BLE_ANT1_2480_Ref




Date: 28.JUN.2018 14:22:02

BLE_ANT1_2480_30~1000




Date: 28.JUN.2018 14:22:11

BLE_ANT1_2480_1000~26500



10. Emission in restricted frequency bands

10.1. Block diagram of test setup



10.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz and 5725MHz to 5850MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

10.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310MHz to 2415MHz and 2475MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

10.4. Test result


PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2018-06-29
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5°C,Humi:55.5%,
 Press:100.1kPa
Memo : BLE 2402

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6
Tested By : Talent
Model Number : CHARGE4J
Test Mode : TX mode
Antenna/Distance : 2017 HF907/3m/HORIZONTAL

Data: 16



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2376.00	54.82	26.95	44.32	5.09	42.54	74.00	-31.46	Peak	HORIZONTAL
2	2390.00	53.60	27.00	44.32	5.11	41.39	74.00	-32.61	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2018-06-29
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5°C,Humi:55.5%,
 Press:100.1kPa
Memo : BLE 2402

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6
Tested By : Talent
Model Number : CHARGE4J
Test Mode : TX mode
Antenna/Distance : 2017 HF907/3m/VERTICAL

Data: 17



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2374.90	56.01	26.95	44.32	5.09	43.73	74.00	-30.27	Peak	VERTICAL
2	2390.00	54.02	27.00	44.32	5.11	41.81	74.00	-32.19	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2018-06-29
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5°C,Humi:55.5%,
 Press:100.1kPa
Memo : BLE 2480

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6
Tested By : Talent
Model Number : CHARGE4J
Test Mode : TX mode
Antenna/Distance : 2017 HF907/3m/VERTICAL

Data: 18



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	53.88	27.34	44.32	5.21	42.11	74.00	-31.89	Peak	VERTICAL
2	2486.59	54.52	27.35	44.32	5.22	42.77	74.00	-31.23	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#
Test Date : 2018-06-29
EUT : Portable Bluetooth Speaker
Power Supply : Battery
Condition : Temp:24.5°C,Humi:55.5%,
 Press:100.1kPa
Memo : BLE 2480

D:\2018 RE1# Report Data\Q18052803-1E CHARGE 4\FCC ABOVE1G.EM6
Tested By : Talent
Model Number : CHARGE4J
Test Mode : TX mode
Antenna/Distance : 2017 HF907/3m/HORIZONTAL

Data: 19




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	60.08	27.34	44.32	5.21	48.31	74.00	-25.69	Peak	HORIZONTAL
2	2486.41	56.47	27.35	44.32	5.22	44.72	74.00	-29.28	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1# **D:\2018 RE1# Report Data\Y20180119-1\FCC above 1G.EM6**
Test Date : 2018-06-29 **Tested By** : Talent
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4J
Power Supply : Battery **Test Mode** : TX mode
Condition : Temp:24.5'C,Humi:55%,
Press:100.1kPa **Antenna/Distance** : 2016 HF907/3m/VERTICAL
Memo : BLE 2480

Data: 29




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	34.88	27.44	29.71	5.21	37.82	74.00	-36.18	Peak	VERTICAL
2	2490.16	37.10	27.46	29.71	5.22	40.07	74.00	-33.93	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

11. Power Line Conducted Emission

11.1. Block diagram of test setup



11.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

11.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

11.4. Test Result

PASS. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “-----” means Average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18052803-1E\CE.EM6**
Test Date : 2018-06-29 **Tested By** : Talent
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4J
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55.5%,
Press:100.1kPa **LISN** : 2017 ENV216/LINE
Memo : (Li-ion Battery: ID998)



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.18	35.11	9.52	0.04	9.86	54.53	64.37	-9.84	QP	LINE
2	0.18	20.45	9.52	0.04	9.86	39.87	54.37	-14.50	Average	LINE
3	0.25	31.04	9.52	0.04	9.86	50.46	61.91	-11.45	QP	LINE
4	0.25	15.96	9.52	0.04	9.86	35.38	51.91	-16.53	Average	LINE
5	0.30	26.83	9.53	0.04	9.86	46.26	60.24	-13.98	QP	LINE
6	0.30	13.37	9.53	0.04	9.86	32.80	50.24	-17.44	Average	LINE
7	0.36	23.59	9.52	0.04	9.84	42.99	58.65	-15.66	QP	LINE
8	0.36	10.50	9.52	0.04	9.84	29.90	48.65	-18.75	Average	LINE
9	0.43	18.74	9.53	0.04	9.82	38.13	57.29	-19.16	QP	LINE
10	0.43	3.41	9.53	0.04	9.82	22.80	47.29	-24.49	Average	LINE
11	0.49	16.99	9.54	0.04	9.80	36.37	56.19	-19.82	QP	LINE
12	0.49	4.34	9.54	0.04	9.80	23.72	46.19	-22.47	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.


2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18052803-1E\CE.EM6**
Test Date : 2018-06-29 **Tested By** : Talent
EUT : Portable Bluetooth Speaker **Model Number** : CHARGE4J
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,
Press:100.1kPa **LISN** : 2017 ENV216/NEUTRAL
Memo : (Li-ion Battery: ID998)



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.18	33.77	9.46	0.04	9.86	53.13	64.37	-11.24	QP	NEUTRAL
2	0.18	20.30	9.46	0.04	9.86	39.66	54.37	-14.71	Average	NEUTRAL
3	0.24	30.22	9.43	0.04	9.86	49.55	62.08	-12.53	QP	NEUTRAL
4	0.24	16.74	9.43	0.04	9.86	36.07	52.08	-16.01	Average	NEUTRAL
5	0.30	26.39	9.40	0.04	9.86	45.69	60.15	-14.46	QP	NEUTRAL
6	0.30	12.27	9.40	0.04	9.86	31.57	50.15	-18.58	Average	NEUTRAL
7	0.37	22.22	9.38	0.04	9.84	41.48	58.61	-17.13	QP	NEUTRAL
8	0.37	7.80	9.38	0.04	9.84	27.06	48.61	-21.55	Average	NEUTRAL
9	0.55	17.31	9.34	0.05	9.82	36.52	56.00	-19.48	QP	NEUTRAL
10	0.55	6.63	9.34	0.05	9.82	25.84	46.00	-20.16	Average	NEUTRAL
11	0.61	16.50	9.33	0.07	9.83	35.73	56.00	-20.27	QP	NEUTRAL
12	0.61	6.62	9.33	0.07	9.83	25.85	46.00	-20.15	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18091806-1E CHARGE4J\CE.EM6**
Test Date : 2018-09-25 **Tested By** : Sunny
EUT : Portable Bluetooth Spraker **Model Number** : CHARGE4J
Power Supply : AC 120V/60Hz **Test Mode** : Charging mode
Condition : Temp:24.5°C, Humi:55.5%,
 Press:100.1kPa **LISN** : 2017 ENV216/NEUTRAL
Memo : (Li-ion Battery: ID998-B)

Data: 5



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.20	29.34	9.45	0.04	9.86	48.69	63.80	-15.11	QP	NEUTRAL
2	0.20	16.84	9.45	0.04	9.86	36.19	53.80	-17.61	Average	NEUTRAL
3	0.26	27.08	9.42	0.04	9.86	46.40	61.42	-15.02	QP	NEUTRAL
4	0.26	16.80	9.42	0.04	9.86	36.12	51.42	-15.30	Average	NEUTRAL
5	0.33	26.66	9.39	0.04	9.85	45.94	59.57	-13.63	QP	NEUTRAL
6	0.33	16.56	9.39	0.04	9.85	35.84	49.57	-13.73	Average	NEUTRAL
7	0.46	24.13	9.36	0.04	9.81	43.34	56.76	-13.42	QP	NEUTRAL
8	0.46	15.43	9.36	0.04	9.81	34.64	46.76	-12.12	Average	NEUTRAL
9	0.84	22.08	9.31	0.12	9.86	41.37	56.00	-14.63	QP	NEUTRAL
10	0.84	13.28	9.31	0.12	9.86	32.57	46.00	-13.43	Average	NEUTRAL
11	3.22	25.53	9.27	0.11	9.87	44.78	56.00	-11.22	QP	NEUTRAL
12	3.22	11.90	9.27	0.11	9.87	31.15	46.00	-14.85	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room **D:\2018 CE report data\Q18091806-1E CHARGE4J\CE.EM6**
Test Date : 2018-09-25 **Tested By** : Sunny
EUT : Portable Bluetooth Spraker **Model Number** : CHARGE4J
Power Supply : AC 120V/60Hz **Test Mode** : Charging mode
Condition : Temp:24.5°C, Humi:55.5%,
 Press:100.1kPa **LISN** : 2017 ENV216/LINE
Memo : (Li-ion Battery: ID998-B)

Data: 7



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.20	28.65	9.51	0.04	9.86	48.06	63.80	-15.74	QP	LINE
2	0.20	19.60	9.51	0.04	9.86	39.01	53.80	-14.79	Average	LINE
3	0.26	25.40	9.52	0.04	9.86	44.82	61.42	-16.60	QP	LINE
4	0.26	18.84	9.52	0.04	9.86	38.26	51.42	-13.16	Average	LINE
5	0.33	26.09	9.52	0.04	9.85	45.50	59.57	-14.07	QP	LINE
6	0.33	21.08	9.52	0.04	9.85	40.49	49.57	-9.08	Average	LINE
7	0.46	26.80	9.54	0.04	9.81	46.19	56.76	-10.57	QP	LINE
8	0.46	20.09	9.54	0.04	9.81	39.48	46.76	-7.28	Average	LINE
9	0.52	23.44	9.54	0.05	9.81	42.84	56.00	-13.16	QP	LINE
10	0.52	18.48	9.54	0.05	9.81	37.88	46.00	-8.12	Average	LINE
11	0.85	25.80	9.56	0.12	9.86	45.34	56.00	-10.66	QP	LINE
12	0.85	18.38	9.56	0.12	9.86	37.92	46.00	-8.08	Average	LINE

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Result

The antennas used for this product is integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2.23dBi.

END OF REPORT