



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM170600623005
Page: 1 of 9

RF Exposure Evaluation Report

Application No.: SZEM1706006230CR
Applicant: Harman International Industries, Incorporated
Address of Applicant: 8500 Balboa Boulevard, Northridge, California 91329, United States.
Manufacturer: Harman International Industries, Incorporated
Address of Manufacturer: 8500 Balboa Boulevard, Northridge, California 91329, United States.
Factory: Shenzhen 3Nod Digital Technology Co., Ltd.
Address of Factory: Building D, NO.8 Langhui Road, Tangxiayong Community, Songgang Street, Baoan District, Shenzhen City, Guangdong Province, P.R. China
EUT Name: Portable Wireless Speaker
Model No.: LINK 20
Trade mark: JBL
FCC ID: APIJBLLINK20
Standards: 47 CFR Part 1.1307 (2016)
47 CFR Part 1.1310 (2016)
Date of Receipt: 2017-06-21
Date of Test: 2017-07-12 to 2017-07-19
Date of Issue: 2017-08-03

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600623005
Page: 2 of 9

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-08-03		Original

Authorized for issue by:				
		Benson Wang		
		Benson Wang /Project Engineer		
		Eric Fu		
		Eric Fu /Reviewer		



3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL DESCRIPTION OF EUT	4
4.1 TEST LOCATION	6
4.2 TEST FACILITY	6
4.3 DEVIATION FROM STANDARDS.....	6
4.4 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5 RF EXPOSURE EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1.1 Limits	7
5.1.2 Test Procedure.....	7
4.1.3 EUT RF EXPOSURE EVALUATION.....	8-9



4 General Description of EUT

Product Name:	Portable Wireless Speaker			
Model No.:	LINK 20			
Trade mark:	JBL			
For BLE:				
Operation Frequency:	2402MHz~2480MHz			
Bluetooth Version:	V 4.1 Dual mode			
Modulation Type:	GFSK			
Number of Channel:	40			
Antenna Type:	PIFA			
Antenna Gain:	Antenna 1: 2.26dBi; Antenna 2: 2.28dBi			
For BT:				
Operation Frequency:	2402MHz~2480MHz			
Bluetooth Version:	V 4.1 Dual mode			
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)			
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK			
Number of Channel:	79			
Hopping Channel Type:	Adaptive Frequency Hopping systems			
Antenna Type:	PIFA			
Antenna Gain:	Antenna 1: 2.26dBi; Antenna 2: 2.28dBi			
For 2.4G wifi:				
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz			
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels			
Channel Separation:	5MHz			
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)			
Antenna Type:	PIFA			
Antenna Gain:	Antenna 1: 2.26dBi; Antenna 2: 2.28dBi			
For 5G wifi:				
Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac 20MHz	5180-5240	4
		IEEE 802.11n/ac 40MHz	5190-5230	2
		IEEE 802.11ac 80MHz	5210	1
	UNII Band II-A	IEEE 802.11a	5260-5320	4
		IEEE 802.11n/ac 20MHz	5260-5320	4



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600623005
Page: 5 of 9

		IEEE 802.11n/ac 40MHz	5270-5310	2
		IEEE 802.11ac 80MHz	5290	1
	UNII Band II-C	IEEE 802.11a	5500-5700	11
		IEEE 802.11n/ac 20MHz	5500-5700	11
		IEEE 802.11n/ac 40MHz	5510-5670	5
		IEEE 802.11ac 80MHz	5530-5690	3
	UNII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n/ac 20MHz	5745-5825	5
		IEEE 802.11n/ac 40MHz	5755-5795	2
		IEEE 802.11ac 80MHz	5775	1
Type of Modulation:	IEEE 802.11a: OFDM(BPSK/QPSK/16QAM/64QAM) IEEE 802.11n: OFDM(BPSK/QPSK/16QAM/64QAM) IEEE 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)			
Antenna type:	PIFA			
Antenna gain	Antenna 1:3.52dBi; Antenna 2:3.55dBi			



4.1 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.3 Deviation from Standards

None.

4.4 Abnormalities from Standard Conditions

None.

4.5 Other Information Requested by the Customer

None.



5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600623005
Page: 8 of 9

4.1.3 EUT RF Exposure Evaluation

Remark: The Bluetooth and Wifi function can't synchronous transmission.

For BT

Antenna 1: 2.26dBi; Antenna 2: 2.28dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.68 / 1.69 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest	2	2402MHz	2.66	1.85	0.0006	1.0	PASS

Note: Refer to report No. SZEM170600623001 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

For BLE

Antenna 1: 2.26dBi; Antenna 2: 2.28dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.68 / 1.69 in linear scale

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest	2	2402MHz	2.19	1.66	0.0006	1.0	PASS

Note: Refer to report No. SZEM170600623002 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

For 2.4G WIFI

Antenna 1: 2.26dBi; Antenna 2: 2.28dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.68 / 1.69 in linear scale

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Middle	1	2462MHz	22.91	195.43	0.065	1.0	PASS

Note: Refer to report No. SZEM170600623003 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM170600623005
Page: 9 of 9

For 5GHz

Antenna 1:3.52dBi; Antenna 2:3.55dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.25/2.26 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency (MHz)	Antenna	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
5320 MHz	1	12.17	16.48	0.007	1.0	PASS

Note: Refer to report No. SZEM170600623004 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.