

SPECIFICATION



深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

通力 PB720 BT 天线组件

Tonly PB720 BT Antenna assembly

产 品 规 格 书

Product Specification

客 户 connection	通力 Tonly	频 段 frequency range	2400 ~ 2500MHz
项目名称 entry name	PB720	版 本 edition	V1.0
物料编号 Material No	1P-B720X-128	颜 色 Color	黑色 Black
客户料号 Customer Item Number	290000-019621		
环保要求 environmental requirement	☒ RoHS ☒ REACH ☒ HF		
R F 设计 R F Design	沈 川 Chuan.Shen	结构设计 Structural Design	周锐斌 Rui Bin.Zhou
品质经理 Quality Manager	胡子寅 ZiYi.Hu	技术总监 Technical Director	张 磊 Lei.Zhang
日 期 Date	2025-02-24		

客户确认:

Customer confirmation:

装配是否符合贵司要求: ☐OK ☐NG

Whether the assembly meets your company's requirements: ☐OK ☐NG

深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

深圳市龙岗区布吉镇吉华路 513 号上水径村(国防培训基地
对面) 达成工业园综合楼 7 楼

TEL:0755-28576002

FAX:0755-84276383

上海分部: 上海市张江高科技园区集成电路产业区龙东大道
3000 号 8 号楼 201 室

TEL:021-61630552

FAX:755-84276383

Buji Town, Longgang District, Shenzhen, China Jihua Road 513,
Shangshuijing Village (opposite the national defense
training base) Dacheng Industrial Park, Building 7.

TEL:0755-28576002

FAX:0755-84276383

Room201, Building8, LongDongRoad3000#, Semiconductor Industry
Park, ZhangJiang Hitech Zone, ShangHai

TEL:021-61630552

FAX:755-84276383

[illegible]

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

索引

Indexes

一、项目说明 Project Description.....	4
二、 BT 天线 antenna.....	4
1、 规格 specifications.....	4
1.1 电气规格标准 Electrical specifications and standards.....	5
1.1.1 电性能指标 Electrical performance index.....	5
1.1.2 天线位置图片 Antenna position picture.....	5
1.2 结构规格标准 Structural specifications and standards.....	5
1.2.1 天线组成 Antenna composition..	5
2、测试环境 testing environment.....	6
3、测试 test.	7
3.1 驻波(VSWR)的测试 Test of standing wave (VSWR).....	7
3.1.1 测试连接 Test connection.....	7
3.2 效率、功率（TRP）、灵敏度（TIS）的测试 Testing of efficiency, power (TRP), sensitivity (TIS).....	7
3.2.1 测试的场地 Test site.....	7
3.2.2 测试的仪表 Tested Instruments.....	7
3.2.3 测试数据 test data.....	7-9
4、VSWR 参数图 Parameter diagram.....	9
5、无源场型图 Passive field pattern diagram.....	10
6、场测数据（拉距测试） Field test data (Pull distance test)	11
7、暗室坐标系 Darkroom coordinate system.....	11
8、结论 conclusion.....	11
三、工程图 schedule drawing.....	12

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

一 项目说明 Project Description


客户名: Customer Name:	通力 Tonly
整机类型: Type of complete machine:	音箱 loudspeaker box
天线频段: Antenna band:	2400 ~ 2500MHz
天线形式: Antenna form:	FPC+同轴线+线材海绵+EVA 泡棉 FPC+coaxial line+wire sponge+EVA foam
馈电形式: Feed form:	焊接 weld
硬件版本: Hardware version:	/

二 BT 天线组件 Antenna assembly

1 规格 specifications

本报告主要提供 **PB720** 项目天线的各项电气和结构性能参数的测试状况。下图为大显设计的天线图片。

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the **PB720** project. The following image shows an antenna with a large display design.



天线外观图

antenna appearing diagram

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1.1 电气规格标准 Electrical specifications and standards

1.1.1 电性能指标 Electrical performance index

天线工作频段在 **2400 ~ 2500 MHz**。下表是大显设计和量产天线的电性能的指标。

The operating frequency band of the antenna is between **2400 and 2500 MHz**. The following table shows the electrical performance indicators of large display design and mass production antennas.

Frequency Range	Frequency (MHz)	VSWR
BT	2400 ~ 2500	≤ 2

1.1.2 天线位置图片 Antenna position picture



2 结构规格标准 Structural specifications and standards

1.2.1 天线组成 Antenna composition

天线主要是由 FPC+同轴线+线材海绵+EVA 泡棉 组成。

The antenna is mainly composed of FPC+coaxial line+wire sponge+EVA foam.

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

2、测试设备 The Equipment of Active Test

Satimo 3D Chamber $6 \times 4 \times 4$ (m)

Agilent 8960 E5515c

Network analyzer-R&S ZVL



图 2

Figure 2

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

3 测试 test

3.1 驻波(VSWR)的测试 Test of standing wave (VSWR)

3.1.1 测试连接: VSWR 测试装置依次连接为: R&S ZVL 网络分析仪 → 测试线 → 测试治

Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → test fixture

实测(附图)Actual measurement (attached drawing)

3.2 增益及效率、功率 (TRP)、灵敏度 (TIS) 的测试

Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 测试的场地 Test site:

大显微波暗室。测试频率范围为 400MHz—6GHz, 静区范围为 50cm 圆周, 反射率小于 -50 dB。

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than - 50dB.

3.2.2 测试的仪表 Tested Instruments:

R&S ZVL 网络分析仪、Agilent8960 E5515C、标准喇叭天线、法国 SATIMO-SG24SYSTEM 系统、打印机等。

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 测试数据 : 在微波暗室中, 测试的功率和灵敏度相关的数值如下表

Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table below

OTA 测试数据 OTA test data:

BAND	CH	TRP (dBm)	TIS (dBm)
BT	0	7.28	-90.46
	39	7.69	-90.73
	78	7.44	-90.52

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

无源效率&增益 Passive efficiency&gain:

Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	42.02	-3.77	1.14
2410	42.05	-3.76	1.22
2420	42.85	-3.68	1.32
2430	42.88	-3.68	1.26
2440	43.76	-3.59	1.41
2450	43.67	-3.60	1.42
2460	43.64	-3.60	1.37
2470	43.15	-3.65	1.33
2480	42.65	-3.70	1.29
2490	42.02	-3.77	1.25
2500	41.58	-3.81	1.15

4、VSWR 参数图 VSWR parameter diagram




www.Topant.com.cn

Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

5、无源场型图 Passive Field Pattern Diagram



www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

6、场测数据（拉距测试） Field test data (Pull distance test):

测试时间 Testing time: 2025/02/20

测试场地 test site: 深圳鹤洲铁岗水库附近 Near Tiegang Reservoir, Hesu, Shenzhen


测试手机 Test Cell Phones: Iphone 14 Pro

测试方向 Test direction	前 ahead	后 empress	左 left	右 right
	测试距离 Test Distance			
BT	100M	100M	100M	100M

www.Topant.com.cn**Confidentiality requirements**

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

7、暗室坐标系 Darkroom coordinate system



7、结论 conclusion


此天线是在客户提供样机基础上设计，电参数和结构性能已达到技术要求，请确认！

This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!

www.Topant.com.cn
Confidentiality requirements

Shenzhen Daxian Technology Co., Ltd. already possesses the information provided by the proprietary technology, which should be strictly confidential and not allowed to be disclosed to any person or company without the prior written consent of Shenzhen Daxian Technology Co., Ltd

1		2		3		4		5		6	
		0~10	10~30	30~50	50~	角度(angle)	O	⊙	⊥		
		0.05	0.10	0.15	0.20	1°	0.02	0.02	0.03	0.05	



1代端子口 (OM) 朝下
(Terminal port facing down)

技术要求:

(technical requirement:)

1. "※"为重点尺寸;

(1. "※" is the key dimension;)

2. 未标注尺寸请依图纸;

(2. Please refer to the drawing for unspecified dimensions;)

3. 不可有虚焊、漏焊、短线、断线等操作不良;

(3. There should be no poor operation such as faulty soldering, missing soldering, short wires, broken wires, etc;)

4. 符合 RoHS 要求;

(4. Meet RoHS requirements.)

D	EVA泡绵(EVA sponge)	EVA	黑色 (black)	
C	线材海绵(Cable sponge)	PUF	黑色 (black)	
B	端子引线(RF connector)	Cable	黑色 (black)	
A	FPC	Electroless copper Pl. base on one substrate	黑色 (black)	
序号(serial number)		零件名称(Part Name)	材质(material)	颜色(colour)
				备注(Note)



深圳大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

机型(Machine model)	PB720	产品颜色(Product Color)	黑色 (black)	日期(date)	2025/02/24
项目编码(Project Code)	CP-B720X-128	表面处理(Mold surface treatment)	NA	结构(MD)	周锐斌
零件名称(Part Name)	BT天线(BT antenna)	单位 (unit)	mm	比例 (scale)	1:1
零件编码(Part Number)	1P-B720X-128	第三视角 (Third perspective)	审核(check)	射频(RF)	沈川
材质(material)	FPC+sponge+RF connector+EVA		批准(ratify)		吴锡欢
保存路径(Save Path)			当前版本 (current version)		张磊
备注(Note)					B