

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type :Chip Antenna

Antenna Gain: 1 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	1.938	1.562	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	2.155	1.642	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.757	1.887	2±1	3	1.995	<5	0.62843	3.00	YES
π/4-DQPSK	2.402	2.112	1.626	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	2.336	1.712	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.944	1.970	2±1	3	1.995	<5	0.62843	3.00	YES
8DPSK	2.402	2.43	1.750	3±1	4	2.512	<5	0.77860	3.00	YES
	2.441	2.644	1.838	3±1	4	2.512	<5	0.78490	3.00	YES
	2.480	3.208	2.093	3±1	4	2.512	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.79114 \leq 3.0$ for 1-g SAR, No SAR is required.

Jason chen

Signature:

Date: 2017-09-29

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China