

W130 – Antenna Specification Document for Soft-pack Projects

Customer name: Shenzhen Dunshi Electronics Co., Ltd.

Customer Product Name: W130-Soft Pack

Product Name: R-FPC Antenna

Supplier Model: Right Earphone Antenna: 336080-IB

Supplier Address: Rooms 407-411, 4th Floor, Building 2, Nantai Cloud Innovation Valley Park, southeast side of the intersection of Guangming Avenue and Dongchang Road, Guangming District, Shenzhen

Change History:

order number	edition	state	Start and End Dates	person liable	page number	remarks
1	R:a	R:a	2026-5-18	Li Jieyi	10	

Supplier's acknowledgment signature:

Responsible Person/Date		IQC/ date -		Review/Date	Approved/Date
MD	Bi Yezhi	Su Guanfeng		Zeng Xianghao	
RF	Chen Kehong				

Buyer's acknowledgment signature (please return after signing):

Buyer's determination result: ☐ Qualified ☐ Unqualified			
Development Engineer/Date	SQE Engineer/Date	Procurement Manager/Date	Development Department Manager's Approval/Date

Catalogue

1. OVERVIEW	3
1.1 SCOPE OF APPLICATION	3
1.2 BASIC PROJECT INFORMATION	3
2. REQUIREMENTS FOR TECHNICAL SPECIFICATIONS	3
2.1 TEST ITEMS AND EQUIPMENT OVERVIEW	3
2.2 ACTIVE REPORTING	3
2.2.1 TESTING INSTRUCTIONS	3
2.2.2 CONDUCTION DATA	4
2.2.3 THE MATCHING CIRCUIT IS SHOWN IN FIGURE R BELOW	4
2.2.4 S11-FREE-R	5
2.2.5 S11 HEAD MOLD-R	5
2.2.6 DIRECTION DIAGRAM-R	6
2.2.7 PASSIVE DATA – R	7
2.2.8 ANTENNA OTA	9
3. STRUCTURAL DRAWINGS	10
4. BILL OF MATERIAL	11
5. PACKAGING SCHEMATIC DIAGRAM	12

1. Overview

1.1 Scope of Application

This specification defines the technical requirements for antennas and material specifications for W130 soft-pack products.

These requirements apply to the selection, testing, and acceptance of W130 soft-pack antennas.

1.2 Basic Project Information

Antenna Name:	W130 – Soft Pack
Antenna Frequency:	BT: 2400MHz-2500MHz
Antenna Material:	FPC

2. Requirements for Technical Specifications

2.1 Test Items and Equipment Overview

List	test item	equipment
Active Testing	TRP,TIS	Comprehensive tester, microwave anechoic chamber

2.2 Active Reporting

2.2.1 Testing Instructions

Testing equipment: Agilent 8960 comprehensive tester, R&SC MW500, fully electromagnetic far-field ETS anechoic chamber, high-precision positioning system with its controller, and a computer equipped with automatic testing software.

Test Environment: Temperature $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$, humidity $50\% \pm 15\%$

Test Method: The DUT is mounted on the H-plane at the center of the turntable, aligned horizontally with the center of the speaker antenna.


The positioning system enables the DUT to rotate across the entire spherical surface, achieving high-precision three-dimensional positioning. All RF instruments, turntable controllers, and PCs equipped with automatic testing software communicate via GPIB interfaces.

2.2.2 Conduction Data

	Channel	power	sensitivity
R	0	9.9	-94.0
	39	9.9	-94.0
	78	9.9	-94.0

2.2.3 The matching circuit is shown in Figure R below


2.2.4 S11-Free-R








2.2.5 S11 Head Mold-R



2.2.6 Direction Diagram-R





2.2.7 Passive Data – R

freedom : Freq	Effi	Gain
(MHz)	(%)	(dBi)
2400	17.7	-0.7
2410	17.8	-0.6
2420	18.9	-0.7
2430	22.6	-0.8
2440	23.6	-0.8
2450	25.7	-0.7
2460	26.4	-0.6
2470	25.3	-0.7
2480	23.1	-0.8
2490	19.8	-0.7
2500	18.6	-0.8

headform : Freq	Effi	Gain
(MHz)	(%)	(dBi)
2400	6.8	-4.4
2410	6.9	-4.5
2420	7.7	-4.3
2430	8.4	-4.4
2440	8.6	-4.2
2450	9.1	-4.1
2460	8.3	-4.3
2470	7.5	-4.2
2480	7.6	-4.3
2490	7.4	-4.4
2500	7.2	-4.5

2.2.8 Antenna OTA

free space	Channel	TRP (dBm)	TIS (dBm)
R	0	0.11	-85.02
	39	1.82	-85.85
	78	1.78	-85.95

Head Mold Data	Channel	TRP (dBm)	TIS (dBm)
R	0	-3.15	-81.35
	39	-2.85	-81.68
	78	-2.67	-81.74


3.Structural drawings

THOT

4. Bill Of Material

THOT

5. Packaging Schematic Diagram

Packaging Method Diagram		
product name	FPC antenna	
P / N	336080	
Project Model	W130 – Soft Pack	
Packaging Details	Carton Size 1: 270*260*200MM Paper Box Size 2: 260*200*200MM Carton Size 3: Based on order quantity/volume	
	Packaging Method	Pack by order quantity
	Total number of boxes packed	Pack by order quantity
labeling requirement	Label Size 1: General 100*100 mm Label Size 2: According to customer requirements	
matters need attention		
1. Due to order quantity limits, the packaging size for each material is determined based on either the total order quantity or actual volume.		
2. Storage temperature: Room temperature		
3. Storage conditions: Store in a cool, dry place		