

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-03

Tested By:

Li Xiongbin

Test Mode:

TX DH5 Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC Below 1G\6

Memo:

Sample Number: S26052027-001 Left side



| Final Data List |             |                  |                     |                 |                 |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|-----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable Loss [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 35.648      | 27.21            | 11.69               | 3.86            | 10.46           | 40.00          | 29.54       | QP       | Vertical |
| 2               | 46.991      | 27.05            | 13.40               | 3.96            | 12.11           | 40.00          | 27.89       | QP       | Vertical |
| 3               | 61.295      | 26.96            | 12.46               | 4.07            | 11.19           | 40.00          | 28.81       | QP       | Vertical |
| 4               | 72.579      | 28.75            | 9.33                | 4.18            | 9.96            | 40.00          | 30.04       | QP       | Vertical |
| 5               | 105.467     | 27.05            | 11.27               | 4.33            | 10.34           | 43.50          | 33.16       | QP       | Vertical |
| 6               | 143.986     | 30.49            | 8.61                | 4.56            | 11.32           | 43.50          | 32.18       | QP       | Vertical |


Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-03**Tested By:** Li Xiongbín**Test Mode:** TX DH5 Mode**Power Supply:** Battery**Condition:** Temp:22.5°C;Humi:55.6%**Test Site:** DDT 3# Chamber**File Path:** d:\ts\2026 report data\Q26052027-1E\FCC Below 1G\7**Memo:** Sample Number: S26052027-001 Right side**Final Data List**

| NO. | Freq.<br>[MHz] | Reading<br>[dBμV/m] | Antenna<br>Factor<br>[dB] | Cable<br>Loss<br>[dB] | Result<br>[dBμV/m] | Limit<br>[dBμV/m] | Margin<br>[dB] | Detector | Polarity   |
|-----|----------------|---------------------|---------------------------|-----------------------|--------------------|-------------------|----------------|----------|------------|
| 1   | 31.999         | 33.82               | 10.90                     | 3.81                  | 16.23              | 40.00             | 23.77          | QP       | Horizontal |
| 2   | 41.506         | 26.55               | 12.90                     | 3.93                  | 11.08              | 40.00             | 28.92          | QP       | Horizontal |
| 3   | 48.023         | 27.11               | 13.21                     | 3.97                  | 11.99              | 40.00             | 28.01          | QP       | Horizontal |
| 4   | 54.636         | 27.08               | 12.95                     | 4.02                  | 11.75              | 40.00             | 28.25          | QP       | Horizontal |
| 5   | 62.422         | 26.85               | 12.52                     | 4.09                  | 11.16              | 40.00             | 28.84          | QP       | Horizontal |
| 6   | 96.009         | 26.51               | 11.19                     | 4.28                  | 9.68               | 43.50             | 33.82          | QP       | Horizontal |

**Note:**

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-03

Tested By:

Li Xiongbin

Test Mode:

TX DH5 Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC Below 1G\8

Memo:

Sample Number: S26052027-001 Right side



| Final Data List |             |                  |                     |                 |                 |                |             |          |          |
|-----------------|-------------|------------------|---------------------|-----------------|-----------------|----------------|-------------|----------|----------|
| NO.             | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable Loss [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1               | 46.597      | 26.87            | 13.24               | 3.96            | 11.77           | 40.00          | 28.23       | QP       | Vertical |
| 2               | 49.667      | 27.48            | 13.47               | 3.98            | 12.63           | 40.00          | 27.37       | QP       | Vertical |
| 3               | 61.338      | 27.24            | 12.47               | 4.07            | 11.48           | 40.00          | 28.52       | QP       | Vertical |
| 4               | 72.579      | 30               | 9.33                | 4.18            | 11.21           | 40.00          | 28.79       | QP       | Vertical |
| 5               | 105.024     | 27.68            | 11.58               | 4.33            | 11.28           | 43.50          | 32.22       | QP       | Vertical |
| 6               | 143.986     | 30.66            | 8.61                | 4.56            | 11.49           | 43.50          | 32.01       | QP       | Vertical |

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\3

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 4546.200    | 46.98           | 32.04               | 4.94            | -39.75   | 44.21          | 74.00          | 29.79       | PK       | Horizontal |
| 2                   | 5032.400    | 45.94           | 33.06               | 5.26            | -39.79   | 44.47          | 74.00          | 29.53       | PK       | Horizontal |
| 3                   | 8403.500    | 42.71           | 37.67               | 6.30            | -39.32   | 47.36          | 74.00          | 26.64       | PK       | Horizontal |
| 4                   | 9109.000    | 43.15           | 38.18               | 6.79            | -38.72   | 49.40          | 74.00          | 24.60       | PK       | Horizontal |
| 5                   | 11206.800   | 41.82           | 38.79               | 7.49            | -39.60   | 48.50          | 74.00          | 25.50       | PK       | Horizontal |
| 6                   | 11888.500   | 42.95           | 38.51               | 7.77            | -39.60   | 49.63          | 74.00          | 24.37       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result


Test Date:2026-06-01Tested By:Cao Jie

Test Mode:TX DH5 2402MHz ModePower Supply:Battery

Condition:Temp:22.5°C;Humi:55.6%Test Site:DDT 3# Chamber

File Path:d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\4

Memo:Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 5035.800    | 45.55           | 33.07               | 5.26            | -39.79   | 44.09          | 74.00          | 29.91       | PK       | Vertical |
| 2                   | 7487.200    | 44.18           | 36.82               | 5.79            | -39.85   | 46.94          | 74.00          | 27.06       | PK       | Vertical |
| 3                   | 8418.800    | 43.24           | 37.51               | 6.32            | -39.30   | 47.77          | 74.00          | 26.23       | PK       | Vertical |
| 4                   | 9064.800    | 42.92           | 38.63               | 6.79            | -38.67   | 49.67          | 74.00          | 24.33       | PK       | Vertical |
| 5                   | 11410.800   | 42.36           | 39.69               | 7.57            | -39.60   | 50.02          | 74.00          | 23.98       | PK       | Vertical |
| 6                   | 12342.400   | 41.77           | 39.27               | 7.81            | -39.33   | 49.52          | 74.00          | 24.48       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-01 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2441MHz Mode **Power Supply:** Battery  
**Condition:** Temp:22.5°C;Humi:55.6% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\1  
**Memo:** Sample Number: S26052027-001 Left side

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 3796.500    | 46.69            | 30.82               | 4.54            | -39.62   | 42.43          | 74.00          | 31.57       | PK       | Horizontal |
| 2  | 4950.800    | 45.87            | 33.10               | 5.22            | -39.80   | 44.39          | 74.00          | 29.61       | PK       | Horizontal |
| 3  | 7324.000    | 49.19            | 37.00               | 5.73            | -39.87   | 52.05          | 74.00          | 21.95       | PK       | Horizontal |
| 4  | 9083.500    | 42.23            | 38.30               | 6.79            | -38.69   | 48.63          | 74.00          | 25.37       | PK       | Horizontal |
| 5  | 11393.800   | 41.43            | 39.73               | 7.57            | -39.60   | 49.13          | 74.00          | 24.87       | PK       | Horizontal |
| 6  | 14494.600   | 40.56            | 40.49               | 8.27            | -38.70   | 50.62          | 74.00          | 23.38       | PK       | Horizontal |

**Final Data List**

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| 1  | 7322.975    | 46.64            | 37.00               | 5.73            | 49.50          | 54.00          | 4.50        | AV       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\2

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3873.000    | 47.46           | 30.58               | 4.55            | -39.65   | 42.94          | 74.00          | 31.06       | PK       | Vertical |
| 2                   | 4277.600    | 46.85           | 31.64               | 4.76            | -39.73   | 43.52          | 74.00          | 30.48       | PK       | Vertical |
| 3                   | 7511.000    | 44.48           | 36.75               | 5.80            | -39.85   | 47.18          | 74.00          | 26.82       | PK       | Vertical |
| 4                   | 8456.200    | 42.76           | 37.29               | 6.35            | -39.25   | 47.15          | 74.00          | 26.85       | PK       | Vertical |
| 5                   | 10999.400   | 41.90           | 39.70               | 7.41            | -39.60   | 49.41          | 74.00          | 24.59       | PK       | Vertical |
| 6                   | 12075.500   | 41.89           | 39.38               | 7.81            | -39.54   | 49.54          | 74.00          | 24.46       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\5

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                  |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|------------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 4014.100    | 47.07            | 30.98               | 4.58            | -39.70   | 42.93          | 74.00          | 31.07       | PK       | Horizontal |
| 2                   | 4733.200    | 46.42            | 31.90               | 5.07            | -39.77   | 43.62          | 74.00          | 30.38       | PK       | Horizontal |
| 3                   | 7439.600    | 49.84            | 36.62               | 5.77            | -39.86   | 52.37          | 74.00          | 21.63       | PK       | Horizontal |
| 4                   | 9182.100    | 42.19            | 38.61               | 6.78            | -38.80   | 48.78          | 74.00          | 25.22       | PK       | Horizontal |
| 5                   | 11550.200   | 43.77            | 38.70               | 7.63            | -39.60   | 50.50          | 74.00          | 23.50       | PK       | Horizontal |
| 6                   | 12534.500   | 41.58            | 39.49               | 7.80            | -39.17   | 49.70          | 74.00          | 24.30       | PK       | Horizontal |

| Final Data List |             |                  |                     |                 |                |                |             |          |            |  |
|-----------------|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|--|
| NO              | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |  |
| 1               | 7440.030    | 46.10            | 36.62               | 5.77            | 48.63          | 54.00          | 5.37        | AV       | Horizontal |  |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\6

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3781.200    | 47.36           | 30.49               | 4.54            | -39.61   | 42.78          | 74.00          | 31.22       | PK       | Vertical |
| 2                   | 4746.800    | 45.74           | 32.14               | 5.08            | -39.77   | 43.19          | 74.00          | 30.81       | PK       | Vertical |
| 3                   | 7441.300    | 45.52           | 36.62               | 5.77            | -39.86   | 48.05          | 74.00          | 25.95       | PK       | Vertical |
| 4                   | 9054.600    | 42.21           | 38.82               | 6.79            | -38.66   | 49.16          | 74.00          | 24.84       | PK       | Vertical |
| 5                   | 11446.500   | 42.40           | 39.34               | 7.59            | -39.60   | 49.73          | 74.00          | 24.27       | PK       | Vertical |
| 6                   | 12648.400   | 41.51           | 39.20               | 7.80            | -39.08   | 49.43          | 74.00          | 24.57       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\19

Memo:

Sample Number: S26052027-001 Right side




| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 4087.200    | 46.90           | 31.13               | 4.63            | -39.71   | 42.95          | 74.00          | 31.05       | PK       | Horizontal |
| 2                   | 4886.200    | 46.43           | 33.04               | 5.17            | -39.79   | 44.85          | 74.00          | 29.15       | PK       | Horizontal |
| 3                   | 7494.000    | 43.90           | 36.86               | 5.79            | -39.85   | 46.70          | 74.00          | 27.30       | PK       | Horizontal |
| 4                   | 9059.700    | 42.59           | 38.73               | 6.79            | -38.67   | 49.44          | 74.00          | 24.56       | PK       | Horizontal |
| 5                   | 10678.100   | 41.74           | 39.43               | 7.17            | -39.63   | 48.71          | 74.00          | 25.29       | PK       | Horizontal |
| 6                   | 11405.700   | 41.29           | 39.74               | 7.57            | -39.60   | 49.00          | 74.00          | 25.00       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-01 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:22.5°C;Humi:55.6% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\20  
**Memo:** Sample Number: S26052027-001 Right side

**Suspected Data List**


| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 4094.000    | 47.45           | 31.11               | 4.63            | -39.71   | 43.48          | 74.00          | 30.52       | PK       | Vertical |
| 2  | 4564.900    | 46.12           | 31.89               | 4.95            | -39.76   | 43.20          | 74.00          | 30.80       | PK       | Vertical |
| 3  | 7511.000    | 43.99           | 36.75               | 5.80            | -39.85   | 46.69          | 74.00          | 27.31       | PK       | Vertical |
| 4  | 10885.500   | 42.36           | 39.51               | 7.33            | -39.61   | 49.59          | 74.00          | 24.41       | PK       | Vertical |
| 5  | 11759.300   | 43.36           | 38.56               | 7.71            | -39.60   | 50.03          | 74.00          | 23.97       | PK       | Vertical |
| 6  | 12405.300   | 41.83           | 39.13               | 7.81            | -39.28   | 49.49          | 74.00          | 24.51       | PK       | Vertical |

**Note:**

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-01 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2441MHz Mode **Power Supply:** Battery  
**Condition:** Temp:22.5°C;Humi:55.6% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\21  
**Memo:** Sample Number: S26052027-001 Right side



### Suspected Data List

| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| 1  | 4085.500    | 46.97           | 31.13               | 4.63            | -39.71   | 43.02          | 74.00          | 30.98       | PK       | Horizontal |
| 2  | 4872.600    | 46.04           | 32.99               | 5.16            | -39.79   | 44.40          | 74.00          | 29.60       | PK       | Horizontal |
| 3  | 7324.000    | 46.22           | 37.00               | 5.73            | -39.87   | 49.08          | 74.00          | 24.92       | PK       | Horizontal |
| 4  | 9156.600    | 42.45           | 38.92               | 6.78            | -38.77   | 49.38          | 74.00          | 24.62       | PK       | Horizontal |
| 5  | 11444.800   | 41.28           | 39.35               | 7.59            | -39.60   | 48.62          | 74.00          | 25.38       | PK       | Horizontal |
| 6  | 12084.000   | 41.60           | 39.42               | 7.81            | -39.53   | 49.30          | 74.00          | 24.70       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2441MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\22

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3910.400    | 46.64           | 30.78               | 4.56            | -39.66   | 42.32          | 74.00          | 31.68       | PK       | Vertical |
| 2                   | 4575.100    | 47.84           | 31.75               | 4.96            | -39.76   | 44.79          | 74.00          | 29.21       | PK       | Vertical |
| 3                   | 7324.000    | 45.19           | 37.00               | 5.73            | -39.87   | 48.05          | 74.00          | 25.95       | PK       | Vertical |
| 4                   | 8406.900    | 42.32           | 37.63               | 6.31            | -39.31   | 46.95          | 74.00          | 27.05       | PK       | Vertical |
| 5                   | 11455.000   | 41.74           | 39.25               | 7.59            | -39.60   | 48.98          | 74.00          | 25.02       | PK       | Vertical |
| 6                   | 12107.800   | 41.83           | 39.48               | 7.81            | -39.51   | 49.61          | 74.00          | 24.39       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\23

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 3798.200    | 46.66           | 30.86               | 4.54            | -39.62   | 42.44          | 74.00          | 31.56       | PK       | Horizontal |
| 2                   | 4886.200    | 45.33           | 33.04               | 5.17            | -39.79   | 43.75          | 74.00          | 30.25       | PK       | Horizontal |
| 3                   | 7439.600    | 47.14           | 36.62               | 5.77            | -39.86   | 49.67          | 74.00          | 24.33       | PK       | Horizontal |
| 4                   | 9000.200    | 42.37           | 38.50               | 6.80            | -38.60   | 49.07          | 74.00          | 24.93       | PK       | Horizontal |
| 5                   | 11434.600   | 41.69           | 39.45               | 7.58            | -39.60   | 49.12          | 74.00          | 24.88       | PK       | Horizontal |
| 6                   | 12031.300   | 42.07           | 39.16               | 7.81            | -39.57   | 49.47          | 74.00          | 24.53       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\24

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 3781.200    | 46.41           | 30.49               | 4.54            | -39.61   | 41.83          | 74.00          | 32.17       | PK       | Vertical |
| 2                   | 4864.100    | 45.40           | 32.96               | 5.16            | -39.79   | 43.73          | 74.00          | 30.27       | PK       | Vertical |
| 3                   | 7439.600    | 46.87           | 36.62               | 5.77            | -39.86   | 49.40          | 74.00          | 24.60       | PK       | Vertical |
| 4                   | 8102.600    | 43.32           | 37.30               | 6.06            | -39.68   | 47.00          | 74.00          | 27.00       | PK       | Vertical |
| 5                   | 8422.200    | 41.94           | 37.48               | 6.32            | -39.29   | 46.45          | 74.00          | 27.55       | PK       | Vertical |
| 6                   | 11982.000   | 42.50           | 38.91               | 7.80            | -39.60   | 49.61          | 74.00          | 24.39       | PK       | Vertical |

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-16 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:23.8°C;Humi:43.9% **Test Site:** 4# Fully Anechoic Room  
**File Path:** d:\ts\2026 report date\Q26052027-1E\FCC ABOVE1G BT 18-40G\1  
**Memo:** Sample Number: S26052027-001 Left side

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| 1  | 18249.786   | 46.68           | 37.97               | 3.83            | 40.22          | 74.00          | 33.78       | PK       | Horizontal |
| 2  | 20575.754   | 48.60           | 38.27               | 3.83            | 40.54          | 74.00          | 33.46       | PK       | Horizontal |
| 3  | 25681.602   | 49.81           | 39.40               | 4.88            | 44.11          | 74.00          | 29.89       | PK       | Horizontal |
| 4  | 33054.328   | 46.84           | 41.62               | 5.38            | 45.80          | 74.00          | 28.20       | PK       | Horizontal |
| 5  | 36712.489   | 49.16           | 42.87               | 6.28            | 49.03          | 74.00          | 24.97       | PK       | Horizontal |
| 6  | 39540.715   | 47.79           | 46.33               | 6.62            | 49.99          | 74.00          | 24.01       | PK       | Horizontal |

**Final Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| 1  | 36712.489   | 41.62            | 42.87               | 6.28            | 41.49          | 54.00          | 12.51       | AV       | Horizontal |
| 2  | 39540.715   | 41.34            | 46.33               | 6.62            | 43.54          | 54.00          | 10.46       | AV       | Horizontal |

**Note:**

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-16 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:23.8°C;Humi:43.9% **Test Site:** 4# Fully Anechoic Room  
**File Path:** d:\ts\2026 report date\Q26052027-1E\FCC ABOVE1G BT 18-40G\2  
**Memo:** Sample Number: S26052027-001 Left side

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1  | 21499.695   | 49.94           | 38.45               | 3.90            | 41.40          | 74.00          | 32.60       | PK       | Vertical |
| 2  | 24891.955   | 50.83           | 39.55               | 4.73            | 45.24          | 74.00          | 28.76       | PK       | Vertical |
| 3  | 26715.664   | 50.21           | 39.59               | 4.82            | 45.08          | 74.00          | 28.92       | PK       | Vertical |
| 4  | 33269.198   | 48.23           | 41.71               | 5.45            | 46.97          | 74.00          | 27.03       | PK       | Vertical |
| 5  | 36844.097   | 48.82           | 42.88               | 6.17            | 48.56          | 74.00          | 25.44       | PK       | Vertical |
| 6  | 38866.561   | 47.45           | 45.63               | 6.38            | 49.64          | 74.00          | 24.36       | PK       | Vertical |

**Final Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1  | 36844.097   | 43.05            | 42.88               | 6.17            | 42.79          | 54.00          | 11.21       | AV       | Vertical |
| 2  | 38866.561   | 42.16            | 45.63               | 6.38            | 44.35          | 54.00          | 9.65        | AV       | Vertical |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-16 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:23.8°C;Humi:43.9% **Test Site:** 4# Fully Anechoic Room  
**File Path:** d:\ts\2026 report date\Q26052027-1E\FCC ABOVE1G BT 18-40G\3  
**Memo:** Sample Number: S26052027-001 Right side

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|-----------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| 1  | 20089.611   | 48.18           | 38.13               | 3.72            | 40.31          | 74.00          | 33.69       | PK       | Horizontal |
| 2  | 23479.184   | 51.37           | 39.20               | 4.69            | 44.44          | 74.00          | 29.56       | PK       | Horizontal |
| 3  | 25251.862   | 49.79           | 39.52               | 4.81            | 44.23          | 74.00          | 29.77       | PK       | Horizontal |
| 4  | 32476.865   | 47.62           | 41.39               | 5.16            | 46.28          | 74.00          | 27.72       | PK       | Horizontal |
| 5  | 36151.141   | 49.74           | 42.82               | 5.95            | 49.34          | 74.00          | 24.66       | PK       | Horizontal |
| 6  | 39508.485   | 47.75           | 46.31               | 6.64            | 50.00          | 74.00          | 24.00       | PK       | Horizontal |

**Final Data List**


| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|------------|
| 1  | 36151.141   | 42.31            | 42.82               | 5.95            | 41.91          | 54.00          | 12.09       | AV       | Horizontal |
| 2  | 39508.485   | 41.25            | 46.31               | 6.64            | 43.50          | 54.00          | 10.50       | AV       | Horizontal |

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-16 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:23.8°C;Humi:43.9% **Test Site:** 4# Fully Anechoic Room  
**File Path:** d:\ts\2026 report date\Q26052027-1E\FCC ABOVE1G BT 18-40G\4  
**Memo:** Sample Number: S26052027-001 Right side



### Suspected Data List

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1  | 21494.323   | 49.82            | 38.45               | 3.90            | 41.28          | 74.00          | 32.72       | PK       | Vertical |
| 2  | 25082.652   | 50.51            | 39.58               | 4.77            | 45.00          | 74.00          | 29.00       | PK       | Vertical |
| 3  | 26637.773   | 49.47            | 39.56               | 4.81            | 44.25          | 74.00          | 29.75       | PK       | Vertical |
| 4  | 33022.097   | 48.09            | 41.61               | 5.37            | 47.09          | 74.00          | 26.91       | PK       | Vertical |
| 5  | 36712.489   | 49.25            | 42.87               | 6.28            | 49.12          | 74.00          | 24.88       | PK       | Vertical |
| 6  | 38931.022   | 48.05            | 45.76               | 6.48            | 50.41          | 74.00          | 23.59       | PK       | Vertical |

### Final Data List

| NO | Freq. [MHz] | Reading [dBμV/m] | Antenna Factor [dB] | Cable loss [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|------------------|---------------------|-----------------|----------------|----------------|-------------|----------|----------|
| 1  | 36712.489   | 42.43            | 42.87               | 6.28            | 42.30          | 54.00          | 11.70       | AV       | Vertical |
| 2  | 38931.022   | 41.38            | 45.76               | 6.48            | 43.74          | 54.00          | 10.26       | AV       | Vertical |

Note:


1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 15. Band Edge Compliance

### 15.1. Test equipment

| Equipment                                           | Manufacturer      | Model No.             | Serial No.  | Cal Due To |
|-----------------------------------------------------|-------------------|-----------------------|-------------|------------|
| High pass filter                                    | Micro-Tronics     | HPM50102              | DDT-ZC00561 | 2027/02/27 |
| RF cable                                            | Zhongke Junchuang | Z805UF-NJ-NJ-10M      | DDT-ZC05591 | 2026/10/10 |
| RF cable                                            | Zhongke Junchuang | Z805UF-NJ-NJ-3M       | DDT-ZC05590 | 2026/10/10 |
| RF cable                                            | Zhongke Junchuang | JCTB510-NJW-NJW-0.6M  | DDT-ZC04595 | 2026/10/10 |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-1M | DDT-ZC03802 | 2026/10/10 |
| RF cable                                            | Yuhu Technology   | ZT26S-SMAJ-SMAJ-1M    | DDT-ZC02037 | 2026/10/10 |
| RF cable                                            | Zhongke Junchuang | JCT40P-2.92J-2.92J-5M | DDT-ZC03800 | 2026/10/10 |
| Radiation disturbance fully automated test software | Tonscend          | JS32-RE (V5.0.0)      | DDT-ZC02739 | /          |
| Pre-amplifier                                       | SONOMA            | 310N                  | DDT-ZC01969 | 2026/07/06 |
| Pre-amplifier                                       | COM-POWER         | PAM-840A              | DDT-ZC01693 | 2027/03/05 |
| Pre-amplifier                                       | COM-POWER         | PAM-118A              | DDT-ZC01293 | 2026/08/10 |
| EMI TEST RECEIVER                                   | R&S               | ESU26                 | DDT-ZC01909 | 2027/02/27 |
| Micro-Tronics filters                               | REBES             | BRM50702              | DDT-ZC03242 | /          |
| High pass filter                                    | Micro-Tronics     | HPM50108              | DDT-ZC00560 | 2027/02/27 |
| High Pass filter                                    | Xi'an Xingbo      | XBLBQ-GTA67           | DDT-ZC02179 | 2027/02/27 |
| Micro-Tronics filters                               | REBES             | BRM50716              | DDT-ZC03240 | /          |
| Broad-Band Horn Antenna                             | Schwarzbeck       | BBHA 9170             | DDT-ZC00506 | 2027/03/04 |
| Trilog Broadband Antenna                            | Schwarzbeck       | VULB 9163             | DDT-ZC02050 | 2026/07/25 |
| Hochgewinn-Hornantenne                              | SCHWARZBEC K      | BBHA 9120 D           | DDT-ZC02129 | 2026/08/11 |
| Active Loop Antenna                                 | Schwarzbeck       | FMZB1519              | DDT-ZC00524 | 2026/08/18 |
| PSA Series Spectrum Analyzer                        | Agilent           | E4447A                | DDT-ZC00517 | 2027/02/27 |

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Description | other |
|---------------------|--------------|--------------|-------------|-------|
| /                   | /            | /            | /           | /     |

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.  
Remark: All restriction band have been tested, and only the worst case is shown in report.

15.6. Test result

PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\9

Memo:

Sample Number: S26052027-001 Left side




| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2374.300    | 13.31           | 27.55               | 3.76            | 0.00     | 44.62          | 74.00          | 29.38       | PK       | Horizontal |
| 2                   | 2390.000    | 12.14           | 27.46               | 3.78            | 0.00     | 43.38          | 74.00          | 30.62       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Date:** 2026-06-01 **Tested By:** Cao Jie  
**Test Mode:** TX DH5 2402MHz Mode **Power Supply:** Battery  
**Condition:** Temp:22.5°C;Humi:55.6% **Test Site:** DDT 3# Chamber  
**File Path:** d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\10  
**Memo:** Sample Number: S26052027-001 Left side

**Suspected Data List**

| NO | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
|----|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| 1  | 2381.940    | 13.66           | 27.51               | 3.77            | 0.00     | 44.94          | 74.00          | 29.06       | PK       | Vertical |
| 2  | 2390.000    | 11.05           | 27.46               | 3.78            | 0.00     | 42.29          | 74.00          | 31.71       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\7

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 12.68           | 27.54               | 3.88            | 0.00     | 44.10          | 74.00          | 29.90       | PK       | Horizontal |
| 2                   | 2484.070    | 15.25           | 27.54               | 3.88            | 0.00     | 46.67          | 74.00          | 27.33       | PK       | Horizontal |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\8

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 12.41           | 27.54               | 3.88            | 0.00     | 43.83          | 74.00          | 30.17       | PK       | Vertical |
| 2                   | 2484.325    | 14.46           | 27.54               | 3.88            | 0.00     | 45.88          | 74.00          | 28.12       | PK       | Vertical |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\11

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2369.920    | 15.25           | 27.58               | 3.75            | 0.00     | 46.58          | 74.00          | 27.42       | PK       | Horizontal |
| 2                   | 2390.000    | 10.36           | 27.46               | 3.78            | 0.00     | 41.60          | 74.00          | 32.40       | PK       | Horizontal |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\12

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2375.610    | 13.86           | 27.55               | 3.76            | 0.00     | 45.17          | 74.00          | 28.83       | PK       | Vertical |
| 2                   | 2390.000    | 10.56           | 27.46               | 3.78            | 0.00     | 41.80          | 74.00          | 32.20       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\13

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 13.84           | 27.54               | 3.88            | 0.00     | 45.26          | 74.00          | 28.74       | PK       | Horizontal |
| 2                   | 2483.662    | 17.41           | 27.54               | 3.88            | 0.00     | 48.83          | 74.00          | 25.17       | PK       | Horizontal |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\14

Memo:

Sample Number: S26052027-001 Left side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 12.01           | 27.54               | 3.88            | 0.00     | 43.43          | 74.00          | 30.57       | PK       | Vertical |
| 2                   | 2484.271    | 14.58           | 27.54               | 3.88            | 0.00     | 46.00          | 74.00          | 28.00       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\27

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2389.040    | 14.36           | 27.47               | 3.77            | 0.00     | 45.60          | 74.00          | 28.40       | PK       | Horizontal |
| 2                   | 2390.000    | 12.06           | 27.46               | 3.78            | 0.00     | 43.30          | 74.00          | 30.70       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\28

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2373.760    | 13.73           | 27.56               | 3.76            | 0.00     | 45.05          | 74.00          | 28.95       | PK       | Vertical |
| 2                   | 2390.000    | 11.36           | 27.46               | 3.78            | 0.00     | 42.60          | 74.00          | 31.40       | PK       | Vertical |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\25

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 14.17           | 27.54               | 3.88            | 0.00     | 45.59          | 74.00          | 28.41       | PK       | Horizontal |
| 2                   | 2483.668    | 17.02           | 27.54               | 3.88            | 0.00     | 48.44          | 74.00          | 25.56       | PK       | Horizontal |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\26

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 12.39           | 27.54               | 3.88            | 0.00     | 43.81          | 74.00          | 30.19       | PK       | Vertical |
| 2                   | 2484.031    | 15.27           | 27.54               | 3.88            | 0.00     | 46.69          | 74.00          | 27.31       | PK       | Vertical |

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\29

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2386.590    | 13.58           | 27.48               | 3.77            | 0.00     | 44.83          | 74.00          | 29.17       | PK       | Horizontal |
| 2                   | 2390.000    | 11.49           | 27.46               | 3.78            | 0.00     | 42.73          | 74.00          | 31.27       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\30

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2387.810    | 13.53           | 27.47               | 3.77            | 0.00     | 44.77          | 74.00          | 29.23       | PK       | Vertical |
| 2                   | 2390.000    | 10.60           | 27.46               | 3.78            | 0.00     | 41.84          | 74.00          | 32.16       | PK       | Vertical |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\31

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |            |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|------------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity   |
| 1                   | 2483.500    | 13.46           | 27.54               | 3.88            | 0.00     | 44.88          | 74.00          | 29.12       | PK       | Horizontal |
| 2                   | 2483.746    | 14.96           | 27.54               | 3.88            | 0.00     | 46.38          | 74.00          | 27.62       | PK       | Horizontal |

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-06-01

Tested By:

Cao Jie

Test Mode:

TX 2DH5 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:22.5°C;Humi:55.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26052027-1E\FCC ABOVE 1G BT\32

Memo:

Sample Number: S26052027-001 Right side



| Suspected Data List |             |                 |                     |                 |          |                |                |             |          |          |
|---------------------|-------------|-----------------|---------------------|-----------------|----------|----------------|----------------|-------------|----------|----------|
| NO                  | Freq. [MHz] | Reading [dBV/m] | Antenna Factor [dB] | Cable loss [dB] | AMP [dB] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Detector | Polarity |
| 1                   | 2483.500    | 10.90           | 27.54               | 3.88            | 0.00     | 42.32          | 74.00          | 31.68       | PK       | Vertical |
| 2                   | 2484.445    | 14.47           | 27.54               | 3.88            | 0.00     | 45.89          | 74.00          | 28.11       | PK       | Vertical |

Note:


- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 16. Power Line Conducted Emissions

### 16.1. Test equipment

| Equipment                   | Manufacturer | Model No. | Serial No.  | Cal Due To |
|-----------------------------|--------------|-----------|-------------|------------|
| EMI Test Receiver           | R&S          | ESCI 3    | DDT-ZC01972 | 2027/02/27 |
| Two Line V-Network          | R&S          | ENV216    | DDT-ZC00586 | 2026/07/06 |
| Pulse Limiter               | R&S          | KH43101   | DDT-ZC00747 | 2027/02/27 |
| Coaxial signal signal cable | H&S          | RG214-5   | DDT-ZC01817 | 2027/02/27 |
| Conducted Radiated Software | Audix        | e3        | DDT-ZC00562 | /          |
| Two Line V-Network          | R&S          | ENV216    | DDT-ZC02058 | 2026/07/06 |

### 16.2. Block diagram of test setup



### 16.3. Limits

| Frequency       | Quasi-Peak Level<br>dB(μV) | Average Level<br>dB(μV) |
|-----------------|----------------------------|-------------------------|
| 150 kHz~500 kHz | 66 ~ 56*                   | 56 ~ 46*                |
| 500 kHz~5 MHz   | 56                         | 46                      |
| 5 MHz~30 MHz    | 60                         | 50                      |

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 16.4. Assistant equipment used for test

| Assistant equipment | Manufacturer | Model number | Description                      | other                                                        |
|---------------------|--------------|--------------|----------------------------------|--------------------------------------------------------------|
| Adapter             | HUAWEI       | HW-050450C00 | Huawei fast charging-1#/2# venue | Input: 100-240V~50/60Hz, Output: 5V/2A or 4.5V/5A or 5V/4.5A |

### 16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

### 16.6. Test result

#### **PASS. (See below detailed test result)**

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means Peak detection; “----” means Average detection.


Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

## 16.7. Test data

## TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 5# Shield Room D:\2026 report data\Q26052027-1E\0609 CE.EM6  
Test Date : 2026-06-09 Tested By : Ling Yisheng  
Power Supply : AC 120V/60Hz Test Mode : Tx mode  
Condition : Temp:25.1°C,Humi:58.4% ISN : 2025 2# 216/LINE  
Memo : Sample Number: S26052027-001

Data: 2



| Item<br>(Mark) | Freq.<br>(MHz) | Read<br>Level<br>(dBμV) | ISN Factor<br>(dB) | Cable<br>Loss<br>(dB) | Pulse<br>Limiter<br>Factor<br>(dB) | Result<br>Level<br>(dBμV) | Limit<br>Line<br>(dBμV) | Margin<br>(dB) | Detector |
|----------------|----------------|-------------------------|--------------------|-----------------------|------------------------------------|---------------------------|-------------------------|----------------|----------|
| 1              | 0.15           | 15.67                   | 9.46               | 0.05                  | 10.21                              | 35.39                     | 66.00                   | 30.61          | QP       |
| 2              | 0.15           | 9.66                    | 9.46               | 0.05                  | 10.21                              | 29.38                     | 56.00                   | 26.62          | Average  |
| 3              | 0.52           | 15.76                   | 9.49               | 0.08                  | 10.33                              | 35.66                     | 56.00                   | 20.34          | QP       |
| 4              | 0.52           | 8.31                    | 9.49               | 0.08                  | 10.33                              | 28.21                     | 46.00                   | 17.79          | Average  |
| 5              | 0.85           | 15.49                   | 9.51               | 0.10                  | 10.38                              | 35.48                     | 56.00                   | 20.52          | QP       |
| 6              | 0.85           | 8.67                    | 9.51               | 0.10                  | 10.38                              | 28.66                     | 46.00                   | 17.34          | Average  |
| 7              | 1.62           | 11.20                   | 9.51               | 0.12                  | 10.39                              | 31.22                     | 56.00                   | 24.78          | QP       |
| 8              | 1.62           | 5.46                    | 9.51               | 0.12                  | 10.39                              | 25.48                     | 46.00                   | 20.52          | Average  |
| 9              | 4.72           | 5.48                    | 9.54               | 0.18                  | 10.27                              | 25.47                     | 56.00                   | 30.53          | QP       |
| 10             | 4.72           | -4.22                   | 9.54               | 0.18                  | 10.27                              | 15.77                     | 46.00                   | 30.23          | Average  |
| 11             | 22.18          | -6.74                   | 9.78               | 0.35                  | 10.31                              | 13.70                     | 60.00                   | 46.30          | QP       |
| 12             | 22.18          | -11.86                  | 9.78               | 0.35                  | 10.31                              | 8.58                      | 50.00                   | 41.42          | Average  |

Note: 1. Result Level = Read Level + ISN Factor + Pulse Limiter Factor + Cable loss.  
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site

: DDT 5# Shield Room

Test Date

: 2026-06-09

Power Supply

: AC 120V/60Hz

Condition

: Temp:25.1°C,Humi:58.4%

Memo

: Sample Number: S26052027-001

D:\2026 report data\Q26052027-1E\0609 CE.EM6

Tested By

: Ling Yisheng


Test Mode

: Tx mode

ISN

: 2025 2# 216/NEUTRAL

Data: 4



| Item   | Freq. | Read Level | ISN Factor | Cable Loss | Pulse Limiter Factor | Result Level | Limit Line | Margin | Detector |
|--------|-------|------------|------------|------------|----------------------|--------------|------------|--------|----------|
| (Mark) | (MHz) | (dBμV)     | (dB)       | (dB)       | (dB)                 | (dBμV)       | (dBμV)     | (dB)   |          |
| 1      | 0.22  | 15.76      | 9.49       | 0.06       | 10.21                | 35.52        | 62.96      | 27.44  | QP       |
| 2      | 0.22  | 10.18      | 9.49       | 0.06       | 10.21                | 29.94        | 52.96      | 23.02  | Average  |
| 3      | 0.78  | 16.30      | 9.48       | 0.09       | 10.37                | 36.24        | 56.00      | 19.76  | QP       |
| 4      | 0.78  | 11.71      | 9.48       | 0.09       | 10.37                | 31.65        | 46.00      | 14.35  | Average  |
| 5      | 1.59  | 9.91       | 9.50       | 0.12       | 10.39                | 29.92        | 56.00      | 26.08  | QP       |
| 6      | 1.59  | 4.97       | 9.50       | 0.12       | 10.39                | 24.98        | 46.00      | 21.02  | Average  |
| 7      | 4.67  | 5.13       | 9.53       | 0.18       | 10.27                | 25.11        | 56.00      | 30.89  | QP       |
| 8      | 4.67  | -3.25      | 9.53       | 0.18       | 10.27                | 16.73        | 46.00      | 29.27  | Average  |
| 9      | 9.71  | -6.14      | 9.62       | 0.25       | 10.15                | 13.88        | 60.00      | 46.12  | QP       |
| 10     | 9.71  | -11.34     | 9.62       | 0.25       | 10.15                | 8.68         | 50.00      | 41.32  | Average  |
| 11     | 21.37 | -6.19      | 9.94       | 0.35       | 10.31                | 14.41        | 60.00      | 45.59  | QP       |
| 12     | 21.37 | -11.89     | 9.94       | 0.35       | 10.31                | 8.71         | 50.00      | 41.29  | Average  |

Note: 1. Result Level = Read Level + ISN Factor + Pulse Limiter Factor + Cable loss.  
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

## 18. Photos of the EUT

Please refer to DDT-Q26052027-2E appendix I

-----End Report-----