



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM180300158705
Page: 1 of 9

RF Exposure Evaluation Report

Application No.: SZEM1803001587CR
Applicant: Harman International Industries, Inc.
Address of Applicant: 8500 Balboa Boulevard, Northridge, California, 91329, United States
Manufacturer: Harman International Industries, Inc.
Address of Manufacturer: 8500 Balboa Boulevard, Northridge, California, 91329, United States
Factory: TCL TECHNOLOGY ELECTRONICS (HUIZHOU) CO., LTD
Address of Factory: Section 19, Zhongkai High-tech development Zone, Huizhou City, Guangdong Province, China
Section 37, Zhongkai High-tech development Zone, Huizhou City, Guangdong Province, China
EUT Name: Voice-Activated speaker
Model No.: LINK VIEW
Trade mark: JBL
FCC ID: APILINKVIEW
Standards: 47 CFR Part 1.1307 (2016)
47 CFR Part 1.1310 (2016)
Date of Receipt: 2018-03-06
Date of Test: 2018-03-28 to 2018-05-16
Date of Issue: 2018-05-23

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180300158705
Page: 2 of 9

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-05-23		Original

Authorized for issue by:				
				
		Benson Wang /Project Engineer		
				
		Eric Fu /Reviewer		



3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL DESCRIPTION OF EUT	4
4.1 TEST LOCATION	6
4.2 TEST FACILITY	6
4.3 DEVIATION FROM STANDARDS	6
4.4 ABNORMALITIES FROM STANDARD CONDITIONS	6
4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5 RF EXPOSURE EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1.1 Limits	7
5.1.2 Test Procedure	7
5.1.3 EUT RF Exposure Evaluation	8-9



4 General Description of EUT

Product Name:	Voice-Activated speaker			
Model No.:	LINK VIEW			
Trade mark:	JBL			
For BT:				
Operation Frequency:	2402MHz~2480MHz			
Bluetooth Version:	BT V4.2			
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)			
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK			
Number of Channel:	79			
Antenna Type:	Integral Antenna			
Antenna Gain:	2.22dBi			
For BLE:				
Operation Frequency:	2402MHz~2480MHz			
Bluetooth Version:	BT V4.2			
Modulation Type:	GFSK			
Number of Channel:	40			
Antenna Type:	Integral Antenna			
Antenna Gain:	2.22dBi			
For 2.4G wifi:				
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz			
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n(HT40):7			
Channel Separation:	5MHz			
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK,BPSK)			
Antenna Type:	Integral Antenna			
Antenna Gain:	Antenna 1: 2.05dBi, Antenna 2: 2.06dBi Two antennas can simultaneous transmission.			
For 5G wifi:				
Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	IEEE 802.11a	5180-5240	4
		IEEE 802.11n/ac 20MHz	5180-5240	4
		IEEE 802.11n/ac 40MHz	5190-5230	2
		IEEE 802.11ac 80MHz	5210	1



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180300158705
Page: 5 of 9

	UNII Band II-A	IEEE 802.11a	5260-5320	4
		IEEE 802.11n/ac 20MHz	5260-5320	4
		IEEE 802.11n/ac 40MHz	5270-5310	2
		IEEE 802.11ac 80MHz	5290	1
	UNII Band II-C	IEEE 802.11a	5500-5700	11
		IEEE 802.11n/ac 20MHz	5500-5700	11
		IEEE 802.11n/ac 40MHz	5510-5670	5
		IEEE 802.11ac 80MHz	5530-5610	2
	UNII Band III	IEEE 802.11a	5745-5825	5
		IEEE 802.11n/ac 20MHz	5745-5825	5
		IEEE 802.11n/ac 40MHz	5755-5795	2
		IEEE 802.11ac 80MHz	5775	1
Type of Modulation:	IEEE 802.11a: OFDM(BPSK/QPSK/16QAM/64QAM) IEEE 802.11n: OFDM(BPSK/QPSK/16QAM/64QAM) IEEE 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)			
Antenna type:	Integral Antenna			
Antenna gain	Antenna 1: 4.32dBi, Antenna 2: 3.37dBi Two antennas can simultaneous transmission.			



4.1 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.3 Deviation from Standards

None.

4.4 Abnormalities from Standard Conditions

None.

4.5 Other Information Requested by the Customer

None.



5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



5.1.3 EUT RF Exposure Evaluation

For BT/BLE

Antenna : 2.22dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.67 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	MPE Ratios	Result
7.83	6.07	0.002	1.0	0.002	PASS

For 2.4G WIFI

Antenna 1: 2.05dBi, Antenna 2: 2.06dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.60 /1.61 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Sum of Power Density (mW/cm ²)	Limit	MPE Ratios	Result
20.87	122.18	0.039	0.074	1.0	0.074	PASS
20.35	108.39	0.035				

For 5GHz

Antenna 1:4.32dBi; Antenna 2:3.37dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.70/ 2.17in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Sum of Power Density (mW/cm ²)	Limit	MPE Ratios	Result
13.93	24.72	0.013	0.025	1.0	0.025	PASS
14.57	28.64	0.012				

The distancer (3RD column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.



1) . exposure conditions for simultaneous transmission operations

1. The Bluetooth only support one antenna to transmit.
2. The WIFI has two antenns to transmit and they can simultaneous transmission.
3. The antenna of Bluetooth and antennas of WIFI can simultaneous transmission.

So, Simultaneous transmission SAR test is not required, because the Max. sum of the MPE ratios is
 $0.002+0.074=0.076<1$.

- End of the Report -