



RADIO TEST REPORT

Applicant	:	Harman International Industries, Inc.
Address of Applicant	:	8500 Balboa Boulevard, Northridge, CA 91325, UNITED STATES
Manufacturer	:	Harman International Industries, Inc.
Address of Manufacturer	:	8500 Balboa Boulevard, Northridge, CA 91325, UNITED STATES
Trade mark	:	JBL
Equipment under Test	:	BLUETOOTH HEADSET
Model No.	:	LIVE BEAM 4
FCC ID	:	APILIVEBEAM4
IC	:	6132A-LIVEBEAM4
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63.10-2020+Cor.1-2023+C63.10a- 2024+Errata to C63.10a-2024
Report No.	:	DDT-RE26081111-1E02
Issue Date	:	2026/09/28
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	6 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits	13
4.3.	Test procedure	13
4.4.	Test result.....	14
4.5.	Test graphs	15
5.	99% Bandwidth	20
5.1.	Block diagram of test setup	20
5.2.	Limits	20
5.3.	Test procedure	20
5.4.	Test result.....	21
5.5.	Test graphs	22
6.	Maximum Peak Output Power.....	27
6.1.	Block diagram of test setup	27
6.2.	Limits	27
6.3.	Test procedure	27
6.4.	Test result.....	28
6.5.	Test graphs	29
7.	Power Spectral Density	34
7.1.	Block diagram of test setup	34
7.2.	Limits	34
7.3.	Test procedure	34
7.4.	Test result.....	35
7.5.	Test graphs	36
8.	Band Edge Compliance (Conducted Method).....	41

8.1.	Block diagram of test setup	41
8.2.	Limits	41
8.3.	Test procedure	41
8.4.	Test result.....	42
8.5.	Test graphs	43
9.	RF Conducted Spurious Emissions.....	46
9.1.	Block diagram of test setup	46
9.2.	Limits	46
9.3.	Test procedure	46
9.4.	Test result.....	47
9.5.	Test graphs	48
10.	Duty Cycle	61
10.1.	Block diagram of test setup	61
10.2.	Limit.....	61
10.3.	Test procedure	61
10.4.	Test result.....	62
10.5.	Test graphs	63
11.	Antenna Requirements.....	68
11.1.	Limit.....	68
11.2.	Result	68
12.	Radiated Emission	69
12.1.	Test equipment.....	69
12.2.	Block diagram of test setup	70
12.3.	Limits	71
12.4.	Assistant equipment used for test	73
12.5.	Test procedure	73
12.6.	Test data	75
13.	Band Edge Compliance.....	131
13.1.	Test equipment.....	131
13.2.	Block diagram of test setup	131
13.3.	Limits	132
13.4.	Assistant equipment used for test	132
13.5.	Test procedure	132
13.6.	Test result.....	132
13.7.	Test data	133
14.	Power Line Conducted Emissions.....	149
14.1.	Test equipment.....	149
14.2.	Block diagram of test setup	149

14.3. Limits149

14.4. Assistant equipment used for test150

14.5. Test procedure150

14.6. Test result.....150

14.7. Test data151

15. Test Setup Photograph155

16. Photos of the EUT159

Test Report Declare

Applicant	:	Harman International Industries, Inc.
Address of Applicant	:	8500 Balboa Boulevard, Northridge, CA 91325, UNITED STATES
Equipment under Test	:	BLUETOOTH HEADSET
Model No.	:	LIVE BEAM 4
Manufacturer	:	Harman International Industries, Inc.
Address of Manufacturer	:	8500 Balboa Boulevard, Northridge, CA 91325, UNITED STATES

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
RSS-247 Issue 4 July 24, 2025,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26081111-1E02		
Date of Receipt:	2026/08/11	Date of Test:	2026/08/11 - 2026/09/11

Created: Zoe Peng	Reviewed: Chen Ziqin	Approved: Damon Hu
		
2026/09/28	2026/09/28	2026/09/28

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/09/28	Damon Hu

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2), RSS-247 clause 6.3.1, RSS-Gen clause 6.7	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3), RSS-247 clause 6.3.2	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e), RSS-247 clause 6.3.1	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	Pass

Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. General Test Information

2.1. Description of EUT

EUT Name	: BLUETOOTH HEADSET
Model Number	: LIVE BEAM 4
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: CHARGING CASE: DC 5V from USB cable or Wireless charger EARBUDS: DC 5V from external charging case CHARGING CASE: DC 3.8V Lithium-ion built-in battery EARBUDS: DC 3.85V Lithium-ion built-in battery
Antenna Type	: LDS Antenna
Max Antenna Gain(dBi)	: Left: -0.65dBi, Right: -1.63dBi

Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Bluetooth LE 2Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464

4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	
13	2428	27	2456	/	
The channels denoted with the grey background are excluded, because they are primary advertising channel only for the Bluetooth LE 1Mbps according to the Bluetooth Core Specification.					

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
HEADSET CHARGING CASE	Harman	LIVE BEAM 4C	CHARGING CASE: DC 5V from USB cable or Wireless charger CHARGING CASE: DC 3.8V Lithium-ion built-in battery

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: BQB.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK 1M	7	CH0	2402
	7	CH19	2440
	7	CH39	2480
GFSK 2M	7	CH1	2404
	7	CH19	2440
	7	CH38	2478

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9\text{ kHz} \leq f < 7\text{ GHz}$);
	3.31 dB ($7\text{ GHz} \leq f < 40\text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
	4.14 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
	4.58 dB (18 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒ RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2027/07/10
Wideband Radio Communication Tester	R&S	CMW500	120259	2027/07/10
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2027/06/21
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2027/02/27
RF Control Unit	Tonscend	JS0806-2	20C8060230	2027/03/17
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/27
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.


4.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Left	2402	0.68	2401.65	2402.33	0.5	PASS
	Right	2402	0.68	2401.65	2402.33	0.5	PASS
	Left	2440	0.68	2439.65	2440.34	0.5	PASS
	Right	2440	0.69	2439.65	2440.34	0.5	PASS
	Left	2480	0.68	2479.65	2480.33	0.5	PASS
	Right	2480	0.68	2479.66	2480.34	0.5	PASS
BLE_2M	Left	2404	1.17	2403.41	2404.58	0.5	PASS
	Right	2404	1.17	2403.41	2404.58	0.5	PASS
	Left	2440	1.17	2439.41	2440.58	0.5	PASS
	Right	2440	1.17	2439.41	2440.58	0.5	PASS
	Left	2478	1.16	2477.42	2478.58	0.5	PASS
	Right	2478	1.16	2477.42	2478.58	0.5	PASS

4.5. Test graphs







BLE_1M_Right_2440




BLE_1M_Left_2480




BLE_1M_Right_2480




BLE 2M Left 2404




BLE 2M Right 2404




BLE 2M Left 2440




BLE 2M Right 2440



BLE 2M Left 2478




BLE 2M Right 2478



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Left	2402	1.0230	2401.4885	2402.5115	---	---
	Right	2402	1.0150	2401.4925	2402.5075	---	---
	Left	2440	1.0230	2439.4885	2440.5115	---	---
	Right	2440	1.0230	2439.4885	2440.5115	---	---
	Left	2480	1.0310	2479.4845	2480.5155	---	---
	Right	2480	1.0270	2479.4885	2480.5155	---	---
BLE_2M	Left	2404	2.0200	2402.9990	2405.0190	---	---
	Right	2404	2.0140	2403.0050	2405.0190	---	---
	Left	2440	2.0260	2438.9990	2441.0250	---	---
	Right	2440	2.0140	2439.0050	2441.0190	---	---
	Left	2478	2.0260	2476.9990	2479.0250	---	---
	Right	2478	2.0200	2477.0050	2479.0250	---	---

5.5. Test graphs







BLE 1M Right 2440




BLE 1M Left 2480




BLE 1M Right 2480




BLE 2M Left 2404




BLE 2M Right 2404




BLE 2M Left 2440




BLE 2M Right 2440



BLE 2M Left 2478




BLE 2M Right 2478



6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.


6.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Left	2402	5.32	≤30	4.67	≤36	PASS
	Right	2402	5.77	≤30	4.14	≤36	PASS
	Left	2440	5.51	≤30	4.86	≤36	PASS
	Right	2440	6.08	≤30	4.45	≤36	PASS
	Left	2480	5.36	≤30	4.71	≤36	PASS
	Right	2480	5.69	≤30	4.06	≤36	PASS
BLE_2M	Left	2404	5.32	≤30	4.67	≤36	PASS
	Right	2404	6.00	≤30	4.37	≤36	PASS
	Left	2440	5.53	≤30	4.88	≤36	PASS
	Right	2440	6.25	≤30	4.62	≤36	PASS
	Left	2478	5.48	≤30	4.83	≤36	PASS
	Right	2478	5.91	≤30	4.28	≤36	PASS

6.5. Test graphs







BLE_1M_Right_2440




BLE_1M_Left_2480




BLE_1M_Right_2480




BLE 2M Left 2404




BLE 2M Right 2404




BLE 2M Left 2440




BLE 2M Right 2440



BLE 2M Left 2478




BLE 2M Right 2478



7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.2.
 - (2) Connect EUT’s antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
 - (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
 - (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
 - (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Left	2402	-9.88	≤8.00	PASS
	Right	2402	-9.48	≤8.00	PASS
	Left	2440	-9.55	≤8.00	PASS
	Right	2440	-8.99	≤8.00	PASS
	Left	2480	-9.58	≤8.00	PASS
	Right	2480	-9.35	≤8.00	PASS
BLE_2M	Left	2404	-13.51	≤8.00	PASS
	Right	2404	-12.97	≤8.00	PASS
	Left	2440	-13.03	≤8.00	PASS
	Right	2440	-12.54	≤8.00	PASS
	Left	2478	-13.02	≤8.00	PASS
	Right	2478	-12.60	≤8.00	PASS

7.5. Test graphs







BLE_1M_Right_2440




BLE_1M_Left_2480




BLE_1M_Right_2480







BLE 2M Right 2440



BLE 2M Left 2478




BLE 2M Right 2478



8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Mode	Frequency [MHz]	Measured Range	Verdict
GFSK 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass
GFSK 2M	2404	2.310 GHz - 2.410 GHz	Pass
	2478	2.470 GHz - 2.500 GHz	Pass

8.5. Test graphs






BLE 1M Right High 2480



BLE 2M Left Low 2404




BLE 2M Right Low 2404



9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


9.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	24℃,46%RH	Test Date:	2026.8.18-2026.8.20
Test Power Supply:	Battery	Sample Number:	S26081111-004/005


Mode	Frequency [MHz]	Verdict
GFSK 1M	2402	Pass
	2440	Pass
	2480	Pass
GFSK 2M	2404	Pass
	2440	Pass
	2478	Pass

9.5. Test graphs







BLE 1M Right 2402 0~Reference




BLE 1M Right 2402 30~1000




BLE 1M Right 2402 1000~26500



BLE_1M_Left_2440_0~Reference



BLE_1M_Left_2440_30~1000



BLE_1M_Left_2440_1000~26500