


































10. Frequency Stability Measurement

10.1. Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user’s manual.


10.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

10.3. Test procedures

- (1) To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
- (2) The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10 dB lower than the measured peak value.
- (3) The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

10.4. Test setup



10.5. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.5℃,50.9%RH	Test Date:	2026.8.8-2026.8.19
Test Power Supply:	DC 5V	Sample Number:	S26072701-002

Voltage								
Test Mode	Antenna	Frequency[MHz]	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	NT	-20000.00	-3.861004	20	PASS
			LV	NT	-40000.00	-7.722008	20	PASS
			HV	NT	-40000.00	-7.722008	20	PASS
		5200	NV	NT	-20000.00	-3.846154	20	PASS
			LV	NT	-40000.00	-7.692308	20	PASS
			HV	NT	-40000.00	-7.692308	20	PASS
		5240	NV	NT	-40000.00	-7.633588	20	PASS
			LV	NT	-40000.00	-7.633588	20	PASS
			HV	NT	-40000.00	-7.633588	20	PASS
		5260	NV	NT	-20000.00	-3.802281	20	PASS
			LV	NT	-40000.00	-7.604563	20	PASS
			HV	NT	-40000.00	-7.604563	20	PASS
		5280	NV	NT	-60000.00	-11.363636	20	PASS
			LV	NT	-40000.00	-7.575758	20	PASS
			HV	NT	-40000.00	-7.575758	20	PASS
		5320	NV	NT	-40000.00	-7.518797	20	PASS
			LV	NT	-40000.00	-7.518797	20	PASS
			HV	NT	-60000.00	-11.278195	20	PASS
		5500	NV	NT	-60000.00	-10.909091	20	PASS
			LV	NT	-40000.00	-7.272727	20	PASS
			HV	NT	-40000.00	-7.272727	20	PASS
		5580	NV	NT	-40000.00	-7.168459	20	PASS
			LV	NT	-40000.00	-7.168459	20	PASS
			HV	NT	-40000.00	-7.168459	20	PASS
		5700	NV	NT	-40000.00	-7.017544	20	PASS
			LV	NT	-40000.00	-7.017544	20	PASS
			HV	NT	-40000.00	-7.017544	20	PASS
		5720	NV	NT	-40000.00	-6.993007	20	PASS
			LV	NT	-40000.00	-6.993007	20	PASS
			HV	NT	-20000.00	-3.496503	20	PASS
		5745	NV	NT	-60000.00	-10.443864	20	PASS
			LV	NT	-40000.00	-6.962576	20	PASS
			HV	NT	-60000.00	-10.443864	20	PASS
		5785	NV	NT	-40000.00	-6.914434	20	PASS
			LV	NT	-60000.00	-10.371651	20	PASS
			HV	NT	-40000.00	-6.914434	20	PASS
		5825	NV	NT	-60000.00	-10.300429	20	PASS
			LV	NT	-40000.00	-6.866953	20	PASS
			HV	NT	-40000.00	-6.866953	20	PASS
11N40MIMO	Ant1	5190	NV	NT	-80000.00	-15.414258	20	PASS
			LV	NT	-40000.00	-7.707129	20	PASS
			HV	NT	-80000.00	-15.414258	20	PASS
		5230	NV	NT	-40000.00	-7.648184	20	PASS
			LV	NT	-40000.00	-7.648184	20	PASS
			HV	NT	-80000.00	-15.296367	20	PASS
		5270	NV	NT	-40000.00	-7.590133	20	PASS
			LV	NT	-80000.00	-15.180266	20	PASS
			HV	NT	-40000.00	-7.590133	20	PASS
		5310	NV	NT	-40000.00	-7.532957	20	PASS
			LV	NT	-40000.00	-7.532957	20	PASS
			HV	NT	-40000.00	-7.532957	20	PASS
		5510	NV	NT	-40000.00	-7.259528	20	PASS
			LV	NT	-80000.00	-14.519056	20	PASS
			HV	NT	-40000.00	-7.259528	20	PASS

		5550	NV	NT	-40000.00	-7.207207	20	PASS
			LV	NT	-40000.00	-7.207207	20	PASS
			HV	NT	-40000.00	-7.207207	20	PASS
		5670	NV	NT	-40000.00	-7.054674	20	PASS
			LV	NT	-40000.00	-7.054674	20	PASS
			HV	NT	-40000.00	-7.054674	20	PASS
		5710	NV	NT	-80000.00	-14.010508	20	PASS
			LV	NT	-80000.00	-14.010508	20	PASS
			HV	NT	-40000.00	-7.005254	20	PASS
		5755	NV	NT	-40000.00	-6.950478	20	PASS
			LV	NT	-40000.00	-6.950478	20	PASS
			HV	NT	-40000.00	-6.950478	20	PASS
		5795	NV	NT	-40000.00	-6.902502	20	PASS
			LV	NT	-40000.00	-6.902502	20	PASS
			HV	NT	-40000.00	-6.902502	20	PASS
11AC80MIM O	Ant1	5210	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5290	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5530	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5610	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5690	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS
		5775	NV	NT	0.00	0.000000	20	PASS
			LV	NT	0.00	0.000000	20	PASS
			HV	NT	0.00	0.000000	20	PASS

Temperature								
Test Mode	Antenna	Frequency[MHz]	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	Limit (ppm)	Verdict
11A	Ant1	5180	NV	0	-40000.00	-7.722008	20	PASS
			NV	10	-20000.00	-3.861004	20	PASS
			NV	20	-20000.00	-3.861004	20	PASS
			NV	30	-40000.00	-7.722008	20	PASS
			NV	40	-20000.00	-3.861004	20	PASS
		5200	NV	0	-40000.00	-7.692308	20	PASS
			NV	10	-20000.00	-3.846154	20	PASS
			NV	20	-40000.00	-7.692308	20	PASS
			NV	30	-40000.00	-7.692308	20	PASS
			NV	40	-40000.00	-7.692308	20	PASS
		5240	NV	0	-40000.00	-7.633588	20	PASS
			NV	10	-40000.00	-7.633588	20	PASS
			NV	20	-40000.00	-7.633588	20	PASS
			NV	30	-20000.00	-3.816794	20	PASS
			NV	40	-40000.00	-7.633588	20	PASS
		5260	NV	0	-60000.00	-11.406844	20	PASS
			NV	10	-40000.00	-7.604563	20	PASS
			NV	20	-60000.00	-11.406844	20	PASS
			NV	30	-40000.00	-7.604563	20	PASS
			NV	40	-40000.00	-7.604563	20	PASS
		5280	NV	0	-40000.00	-7.575758	20	PASS
			NV	10	-20000.00	-3.787879	20	PASS
			NV	20	-40000.00	-7.575758	20	PASS
			NV	30	-40000.00	-7.575758	20	PASS
			NV	40	-40000.00	-7.575758	20	PASS
		5320	NV	0	-40000.00	-7.518797	20	PASS

11N40MIMO	Ant1		NV	10	-40000.00	-7.518797	20	PASS
			NV	20	-60000.00	-11.278195	20	PASS
			NV	30	-40000.00	-7.518797	20	PASS
			NV	40	-40000.00	-7.518797	20	PASS
		5500	NV	0	-60000.00	-10.909091	20	PASS
			NV	10	-20000.00	-3.636364	20	PASS
			NV	20	-60000.00	-10.909091	20	PASS
			NV	30	-60000.00	-10.909091	20	PASS
			NV	40	-40000.00	-7.272727	20	PASS
		5580	NV	0	-40000.00	-7.168459	20	PASS
			NV	10	-40000.00	-7.168459	20	PASS
			NV	20	-40000.00	-7.168459	20	PASS
			NV	30	-40000.00	-7.168459	20	PASS
			NV	40	-40000.00	-7.168459	20	PASS
		5700	NV	0	-40000.00	-7.017544	20	PASS
			NV	10	-40000.00	-7.017544	20	PASS
			NV	20	-40000.00	-7.017544	20	PASS
			NV	30	-60000.00	-10.526316	20	PASS
			NV	40	-40000.00	-7.017544	20	PASS
		5720	NV	0	-40000.00	-6.993007	20	PASS
			NV	10	-40000.00	-6.993007	20	PASS
			NV	20	-40000.00	-6.993007	20	PASS
			NV	30	-60000.00	-10.489510	20	PASS
			NV	40	-40000.00	-6.993007	20	PASS
		5745	NV	0	-40000.00	-6.962576	20	PASS
			NV	10	-40000.00	-6.962576	20	PASS
			NV	20	-40000.00	-6.962576	20	PASS
			NV	30	-40000.00	-6.962576	20	PASS
			NV	40	-40000.00	-6.962576	20	PASS
		5785	NV	0	-40000.00	-6.914434	20	PASS
			NV	10	-60000.00	-10.371651	20	PASS
			NV	20	-40000.00	-6.914434	20	PASS
			NV	30	-60000.00	-10.371651	20	PASS
			NV	40	-40000.00	-6.914434	20	PASS
		5825	NV	0	-40000.00	-6.866953	20	PASS
			NV	10	-40000.00	-6.866953	20	PASS
			NV	20	-40000.00	-6.866953	20	PASS
			NV	30	-60000.00	-10.300429	20	PASS
			NV	40	-40000.00	-6.866953	20	PASS
11N40MIMO	Ant1	5190	NV	0	-40000.00	-7.707129	20	PASS
			NV	10	-40000.00	-7.707129	20	PASS
			NV	20	-40000.00	-7.707129	20	PASS
			NV	30	-80000.00	-15.414258	20	PASS
			NV	40	-80000.00	-15.414258	20	PASS
		5230	NV	0	-40000.00	-7.648184	20	PASS
			NV	10	-40000.00	-7.648184	20	PASS
			NV	20	-40000.00	-7.648184	20	PASS
			NV	30	-40000.00	-7.648184	20	PASS
			NV	40	-40000.00	-7.648184	20	PASS
		5270	NV	0	-40000.00	-7.590133	20	PASS
			NV	10	-40000.00	-7.590133	20	PASS
			NV	20	-80000.00	-15.180266	20	PASS
			NV	30	-40000.00	-7.590133	20	PASS
			NV	40	-80000.00	-15.180266	20	PASS
		5310	NV	0	-40000.00	-7.532957	20	PASS
			NV	10	-40000.00	-7.532957	20	PASS
			NV	20	-40000.00	-7.532957	20	PASS
			NV	30	-40000.00	-7.532957	20	PASS
			NV	40	-40000.00	-7.532957	20	PASS
		5510	NV	0	-40000.00	-7.259528	20	PASS
			NV	10	-40000.00	-7.259528	20	PASS
			NV	20	-40000.00	-7.259528	20	PASS
			NV	30	-40000.00	-7.259528	20	PASS
			NV	40	-40000.00	-7.259528	20	PASS

		5550	NV	0	-40000.00	-7.207207	20	PASS
			NV	10	-40000.00	-7.207207	20	PASS
			NV	20	-40000.00	-7.207207	20	PASS
			NV	30	-40000.00	-7.207207	20	PASS
			NV	40	-40000.00	-7.207207	20	PASS
		5670	NV	0	-80000.00	-14.109347	20	PASS
			NV	10	-40000.00	-7.054674	20	PASS
			NV	20	-40000.00	-7.054674	20	PASS
			NV	30	-40000.00	-7.054674	20	PASS
			NV	40	-40000.00	-7.054674	20	PASS
		5710	NV	0	-80000.00	-14.010508	20	PASS
			NV	10	-40000.00	-7.005254	20	PASS
			NV	20	-40000.00	-7.005254	20	PASS
			NV	30	-40000.00	-7.005254	20	PASS
			NV	40	-40000.00	-7.005254	20	PASS
		5755	NV	0	-40000.00	-6.950478	20	PASS
			NV	10	-80000.00	-13.900956	20	PASS
			NV	20	-40000.00	-6.950478	20	PASS
			NV	30	-40000.00	-6.950478	20	PASS
			NV	40	-40000.00	-6.950478	20	PASS
		5795	NV	0	-40000.00	-6.902502	20	PASS
			NV	10	-40000.00	-6.902502	20	PASS
			NV	20	-40000.00	-6.902502	20	PASS
			NV	30	-80000.00	-13.805004	20	PASS
			NV	40	-40000.00	-6.902502	20	PASS
11AC80MIM O	Ant1	5210	NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	-80000.00	-15.355086	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	-80000.00	-15.355086	20	PASS
		5290	NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
		5530	NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
		5610	NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS
		5690	NV	0	0.00	0.000000	20	PASS
			NV	10	-80000.00	-14.059754	20	PASS
			NV	20	0.00	0.000000	20	PASS
			NV	30	-80000.00	-14.059754	20	PASS
			NV	40	0.00	0.000000	20	PASS
		5775	NV	0	0.00	0.000000	20	PASS
			NV	10	0.00	0.000000	20	PASS
			NV	20	-80000.00	-13.852814	20	PASS
			NV	30	0.00	0.000000	20	PASS
			NV	40	0.00	0.000000	20	PASS

11. Dynamic Frequency Selection

11.1. Applicability of DFS requirements

Table 1: Applicability of DFS Requirements Prior to Use of a Channel

Requirement	Operational Mode		
	☐ Master	☒ Client Without Radar Detection	☐ Client with Radar Detection
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode	
	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
DFS Detection Threshold	Yes	Not required
Channel Closing Transmission Time	Yes	Yes
Channel Move Time	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required

Additional requirements for devices with multiple bandwidth modes	☐ Master Device or Client with Radar Detection	☒ Client Without Radar Detection
U-NII Detection Bandwidth and Statistical Performance Check	All BW modes must be tested	Not required
Channel Move Time and Channel Closing Transmission Time	Test using widest BW mode available	Test using the widest BW mode available for the link
All other tests	Any single BW mode	Not required

Note: Frequencies selected for statistical performance check should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency.

11.2. Limit

(1) DFS Detection Thresholds

Table 3: DFS Detection Thresholds for Master Devices and Client Devices with Radar Detection

Maximum Transmit Power	Value (See Notes 1, 2, and 3)
EIRP $\geq$ 200 milliwatt	-64 dBm
EIRP $<$ 200 milliwatt and power spectral density $<$ 10 dBm/MHz	-62 dBm
EIRP $<$ 200 milliwatt that do not meet the power spectral density requirement	-64 dBm

Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna.

Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.

Note3: EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.

(2) DFS Response Requirements

Table 4: DFS Response Requirement Values

Parameter	Value
Non-occupancy period	Minimum 30 minutes
Channel Availability Check Time	60 seconds
Channel Move Time	10 seconds See Note 1.
Channel Closing Transmission Time	200 milliseconds + an aggregate of 60 milliseconds over remaining 10 second period. See Notes 1 and 2.
U-NII Detection Bandwidth	Minimum 100% of the U-NII 99% transmission power bandwidth. See Note 3.

Note 1: Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.

Note 2: The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required facilitating a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

Note 3: During the U-NII Detection Bandwidth detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.

11.3. Parameters of radar test waveforms

This section provides the parameters for required test waveforms, minimum percentage of successful detections, and the minimum number of trials that must be used for determining DFS conformance. Step intervals of 0.1 microsecond for Pulse Width, 1 microsecond for PRI, 1 MHz for chirp width and 1 for the number of pulses will be utilized for the random determination of specific test waveforms.

Table 5 Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (μsec)	PRI (μsec)	Number of Pulses	Minimum Percentage of Successful Detection	Minimum Number of Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A	Roundup $\left\{ \left(\frac{1}{360} \right) \cdot \left(\frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$	60%	30
		Test B			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A					


A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B. Test aggregate is average of the percentage of successful detections of short pulse radar types 1-4

11.4. Calibration of radar waveform

Radar Waveform Calibration Procedure:

- (1) A 50 ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to place of the master
- (2) The interference Radar Detection Threshold Level is $-62\text{dBm} + 2.17\text{dBi} = -59.83\text{dBm}$ that had been taken into account the output power range and antenna gain.
- (3) The following equipment setup was used to calibrate the conducted radar waveform. A vector signal generator was utilized to establish the test signal level for radar type 0. During this process there were no transmissions by either the master or client device. The spectrum analyzer was switched to the zero spans (time domain) at the frequency of the radar waveform generator. Peak detection was used. The spectrum analyzer resolution bandwidth (RBW) and video bandwidth (VBW) were set to 3 MHz.
- (4) The vector signal generator amplitude was set so that the power level measured at the spectrum analyzer was $-62\text{dBm} + 2.17\text{dBi} = -59.83\text{dBm}$. Capture the spectrum analyzer plots on short pulse radar waveform.


Conducted Calibration Setup:



Note: 1. Use the software "Web" to set the frequency channel.
2. EUT is not support TPC and not with Radar detection.

Radar Waveform Calibration Result:

TestMode	Frequency[MHz]	Radar Type	Result	Limit[dbm]	Verdict
11AX80MIMO	5290	Type0	-60.10	-59.83	PASS
	5530	Type0	-59.56	-59.43	PASS



11.5. Channel closing transmission time, channel move time and non-occupancy period


Block diagram of test setup Test Procedure:

- (1) The radar pulse generator is setup to provide a pulse at frequency that the master and client are operating. A type 0 radar pulse with a 1us pulse width and a 1428us PRI is used for the testing.
- (2) The vector signal generator is adjusted to provide the radar burst (18 pulses) at the level of approximately -61dBm at the antenna port of the master device.
- (3) A trigger is provided from the pulse generator to the DFS monitoring system in order to capture the traffic and the occurrence of the radar pulse.
- (4) EUT will associate with the master at channel. The file "iperf.exe" specified by the FCC is streamed from the PC 2 through the master and the client device to the PC 1 and played in full motion video using Test Software in order to properly load the network for the entire period of the test.
- (5) When radar burst with a level equal to the DFS Detection Threshold +1dB is generated on the operating channel of the U-NII device. At time T0 the radar waveform generator sends a burst of pulse of the radar waveform at Detection Threshold +1dB.
- (6) Observe the transmissions of the EUT at the end of the radar Burst on the Operating Channel. Measure and record the transmissions from the UUT during the observation time (Channel Move Time). One 15 seconds plot is reported for the Short Pulse Radar Type 0. The plot for the Short Pulse Radar Types start at the end of the radar burst. The Channel Move Time will be calculated based on the zoom in 600ms plot of the Short Pulse Radar Type.
- (7) Measurement of the aggregate duration of the Channel Closed Transmission Time method. With the
- (8) spectrum analyzer set to zero span tuned to the center frequency of the EUT operating channel at the radar simulated frequency, peak detection, and max hold, the dwell time per bin is given by: $Dwell (0.3ms) = S (12000ms) / B (4000)$; where Dwell is the dwell time per spectrum analyzer sampling bin, S is sweep time and B is the number of spectrum analyzer sampling bins. An upper bound of the aggregate duration of the intermittent control signals of Channel Closing Transmission Time is calculated by: $C (ms) = N \times Dwell (0.3ms)$; where C is the Closing Time, N is the number of spectrum analyzer sampling bins (intermittent control signals) showing a U-NII transmission and Dwell is the dwell time per bin.

Measurement the EUT for more than 30 minutes following the channel move time to verify that no transmission or beacons occur on this channel.

11.6. Test setup

Setup for Client with injection at the Master




11.7. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 3#
Ambient Condition:	27.5℃,50.9%RH	Test Date:	2026.8.8-2026.8.19
Test Power Supply:	DC 5V	Sample Number:	S26072701-002

TestMode	Frequency[MHz]	CCTT[ms]	Limit[ms]	CMT[ms]	Limit[ms]	Verdict
11AX80MIMO	5290	200+44.2	200+60	1333.8	10000	PASS
	5530	200+41.6	200+60	972.4	10000	PASS


Test plots as follows:



Non-Occupancy Period

TestMode	Frequency[MHz]	Result	Limit[s]	Verdict
11AX80MIMO	5290	see test graph	≥1800	PASS
	5530	see test graph	≥1800	PASS

Test plots as follows:



12. Antenna Requirements

12.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

12.2. Result

The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


13. Radiated Emission


13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2027/02/27
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-10M	DDT-ZC05591	2026/10/10
RF cable	Zhongke Junchuang	Z805UF-NJ-NJ-3M	DDT-ZC05590	2026/10/10
RF cable	Zhongke Junchuang	JCTB510-NJW-NJW-0.6M	DDT-ZC04595	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-5M	DDT-ZC03800	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS32-RE (V5.0.0)	DDT-ZC02739	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2027/06/25
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2027/07/08
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2027/02/27
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2027/02/27
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2027/02/27
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2027/07/10
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2027/07/10
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2027/07/10
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
Band Reject Filter Group	Tonscend	JS0806-F	DDT-ZC05733	/
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC05922	2027/01/06
Broadband Preamplifier	HPX	BP-01G-18G	DDT-ZC05923	2027/01/06
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2027/03/05
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04
Signal & Spectrum analyzer	R&S	FSV40-N	DDT-ZC04979	2027/07/10
SPECTRUM ANALYZER	R&S	FSU26	DDT-ZC00236	2027/06/25
RF Cable	Tonscend	7+1+1+0.5+0.5m	DDT-ZC05978	2027/01/29
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2027/03/04

PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2027/02/27
RF cable	Zhongke Junchuang	JCT40P-2.92J-2.92J-1M	DDT-ZC03802	2026/10/10
Radiation disturbance fully automated test software	Tonscend	JS-RE&RSE (V5.0.0)	DDT-ZC06466	/

13.2. Block diagram of test setup





13.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

13.6. Test result

PASS. (See below detailed test result)

13.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2026-08-04

Tested By:

Li Xiongbín

Test Mode:

MIMO N20 TX Mode

Power Supply:

DC 5V

Condition:

Temp:20.9°C;Humi:53.7%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2026 report data\Q26072701-2E\FCC Below 1G\9

Memo:

Sample Number: S26072701-001



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	31.531	41.63	10.61	3.80	23.74	40.00	16.26	QP	Horizontal
2	53.649	29.04	13.54	4.01	14.29	40.00	25.71	QP	Horizontal
3	119.906	35.54	9.73	4.42	17.37	43.50	26.13	QP	Horizontal
4	215.939	41.81	10.88	4.94	25.23	43.50	18.27	QP	Horizontal
5	241.237	44.4	12.20	5.04	29.24	46.00	16.76	QP	Horizontal
6	399.104	43.7	15.36	5.71	32.27	46.00	13.73	QP	Horizontal

Note:


1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Li Xiongbin
Test Mode: MIMO N20 TX Mode **Power Supply:** DC 5V
Condition: Temp:20.9°C;Humi:53.7% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2026 report data\Q26072701-2E\FCC Below 1G\10
Memo: Sample Number: S26072701-001

**Final Data List**


NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	34.492	38.52	11.00	3.84	21.06	40.00	18.94	QP	Vertical
2	53.649	37.45	13.54	4.01	22.70	40.00	17.30	QP	Vertical
3	96.346	36.79	10.97	4.28	19.74	43.50	23.76	QP	Vertical
4	138.054	39.26	7.89	4.52	19.33	43.50	24.17	QP	Vertical
5	278.919	35.13	12.78	5.20	20.71	46.00	25.29	QP	Vertical
6	399.664	38.86	15.39	5.71	27.46	46.00	18.54	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5180MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\18
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3859.400	51.34	31.52	-40.90	41.96	74.00	32.04	PK	Horizontal
2	4881.100	51.35	33.46	-39.58	45.23	74.00	28.77	PK	Horizontal
3	7274.700	49.71	37.75	-39.83	47.63	74.00	26.37	PK	Horizontal
4	8092.400	49.64	37.90	-38.66	48.88	74.00	25.12	PK	Horizontal
5	11033.400	46.88	39.70	-35.81	50.77	74.00	23.23	PK	Horizontal
6	11560.400	46.62	39.68	-35.51	50.79	74.00	23.21	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8092.400	39.38	37.90	-38.66	38.62	54.00	15.38	AV	Horizontal
2	11033.400	36.33	39.70	-35.81	40.22	54.00	13.78	AV	Horizontal
3	11560.400	36.78	39.68	-35.51	40.95	54.00	13.05	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5180MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\19
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3898.500	50.52	31.60	-40.76	41.36	74.00	32.64	PK	Vertical
2	4906.600	51.22	33.53	-39.55	45.20	74.00	28.80	PK	Vertical
3	7395.400	49.31	37.22	-39.05	47.48	74.00	26.52	PK	Vertical
4	8123.000	48.62	37.90	-38.46	48.06	74.00	25.94	PK	Vertical
5	11133.700	46.36	39.77	-35.63	50.50	74.00	23.50	PK	Vertical
6	11511.100	46.48	39.78	-35.71	50.55	74.00	23.45	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8123.000	38.64	37.90	-38.46	38.08	54.00	15.92	AV	Vertical
2	11133.700	36.17	39.77	-35.63	40.31	54.00	13.69	AV	Vertical
3	11511.100	37.11	39.78	-35.71	41.18	54.00	12.82	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5200MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\20
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3752.300	52.55	30.91	-41.35	42.11	74.00	31.89	PK	Horizontal
2	4898.100	51.85	33.50	-39.56	45.79	74.00	28.21	PK	Horizontal
3	7301.900	49.22	37.69	-39.57	47.34	74.00	26.66	PK	Horizontal
4	8259.000	49.04	37.92	-38.72	48.24	74.00	25.76	PK	Horizontal
5	11183.000	46.16	39.87	-35.65	50.38	74.00	23.62	PK	Horizontal
6	11412.500	46.64	39.98	-35.92	50.70	74.00	23.30	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8259.000	37.97	37.92	-38.72	37.17	54.00	16.83	AV	Horizontal
2	11183.000	36.90	39.87	-35.65	41.12	54.00	12.88	AV	Horizontal
3	11412.500	35.20	39.98	-35.92	39.26	54.00	14.74	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5200MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\21
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3879.800	50.51	31.56	-40.82	41.25	74.00	32.75	PK	Vertical
2	4894.700	51.15	33.49	-39.56	45.08	74.00	28.92	PK	Vertical
3	7291.700	49.47	37.72	-39.66	47.53	74.00	26.47	PK	Vertical
4	8106.000	49.21	37.90	-38.53	48.58	74.00	25.42	PK	Vertical
5	10936.500	46.58	39.83	-35.75	50.66	74.00	23.34	PK	Vertical
6	11495.800	46.73	39.81	-35.76	50.78	74.00	23.22	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8106.000	40.02	37.90	-38.53	39.39	54.00	14.61	AV	Vertical
2	10936.500	34.48	39.83	-35.75	38.56	54.00	15.44	AV	Vertical
3	11495.800	37.19	39.81	-35.76	41.24	54.00	12.76	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5240MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\22
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4121.200	50.36	31.64	-40.90	41.10	74.00	32.90	PK	Horizontal
2	4884.500	52.64	33.47	-39.57	46.54	74.00	27.46	PK	Horizontal
3	7692.900	49.75	37.30	-38.79	48.26	74.00	25.74	PK	Horizontal
4	8231.800	48.55	37.90	-38.44	48.01	74.00	25.99	PK	Horizontal
5	10860.000	46.32	39.94	-35.60	50.66	74.00	23.34	PK	Horizontal
6	12044.900	46.31	39.84	-35.29	50.86	74.00	23.14	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7692.900	39.52	37.30	-38.79	38.03	54.00	15.97	AV	Horizontal
2	8231.800	39.81	37.90	-38.44	39.27	54.00	14.73	AV	Horizontal
3	10860.000	36.70	39.94	-35.60	41.04	54.00	12.96	AV	Horizontal
4	12044.900	36.98	39.84	-35.29	41.53	54.00	12.47	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5240MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\23
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3857.700	50.23	31.52	-40.91	40.84	74.00	33.16	PK	Vertical
2	4876.000	51.32	33.45	-39.58	45.19	74.00	28.81	PK	Vertical
3	7288.300	48.92	37.72	-39.70	46.94	74.00	27.06	PK	Vertical
4	8260.700	49.66	37.92	-38.74	48.84	74.00	25.16	PK	Vertical
5	11109.900	46.05	39.72	-35.61	50.16	74.00	23.84	PK	Vertical
6	11528.100	45.93	39.74	-35.64	50.03	74.00	23.97	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8260.700	39.18	37.92	-38.74	38.36	54.00	15.64	AV	Vertical
2	11109.900	35.47	39.72	-35.61	39.58	54.00	14.42	AV	Vertical
3	11528.100	36.65	39.74	-35.64	40.75	54.00	13.25	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5260MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\24
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3900.200	50.64	31.60	-40.75	41.49	74.00	32.51	PK	Horizontal
2	5006.900	50.74	33.91	-39.44	45.21	74.00	28.79	PK	Horizontal
3	7686.100	49.51	37.30	-38.83	47.98	74.00	26.02	PK	Horizontal
4	8121.300	48.70	37.90	-38.47	48.13	74.00	25.87	PK	Horizontal
5	11466.900	46.54	39.87	-35.81	50.60	74.00	23.40	PK	Horizontal
6	12364.500	45.58	39.74	-35.58	49.74	74.00	24.26	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8121.300	38.31	37.90	-38.47	37.74	54.00	16.26	AV	Horizontal
2	11466.900	36.18	39.87	-35.81	40.24	54.00	13.76	AV	Horizontal
3	12364.500	35.10	39.74	-35.58	39.26	54.00	14.74	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5260MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\25
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3842.400	51.46	31.45	-40.96	41.95	74.00	32.05	PK	Vertical
2	5023.900	50.74	33.95	-39.42	45.27	74.00	28.73	PK	Vertical
3	7701.400	48.68	37.30	-38.74	47.24	74.00	26.76	PK	Vertical
4	8231.800	49.38	37.90	-38.44	48.84	74.00	25.16	PK	Vertical
5	11133.700	45.78	39.77	-35.63	49.92	74.00	24.08	PK	Vertical
6	11626.700	46.15	39.57	-35.58	50.14	74.00	23.86	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8231.800	39.28	37.90	-38.44	38.74	54.00	15.26	AV	Vertical
2	11133.700	35.61	39.77	-35.63	39.75	54.00	14.25	AV	Vertical
3	11626.700	35.21	39.57	-35.58	39.20	54.00	14.80	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5260MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\26
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3903.600	50.39	31.61	-40.77	41.23	74.00	32.77	PK	Horizontal
2	4906.600	50.85	33.53	-39.55	44.83	74.00	29.17	PK	Horizontal
3	7444.700	48.87	37.11	-39.16	46.82	74.00	27.18	PK	Horizontal
4	8218.200	49.25	37.90	-38.31	48.84	74.00	25.16	PK	Horizontal
5	11026.600	46.25	39.70	-35.83	50.12	74.00	23.88	PK	Horizontal
6	12112.900	45.82	39.90	-35.42	50.30	74.00	23.70	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8218.200	37.38	37.90	-38.31	36.97	54.00	17.03	AV	Horizontal
2	11026.600	36.87	39.70	-35.83	40.74	54.00	13.26	AV	Horizontal
3	12112.900	35.80	39.90	-35.42	40.28	54.00	13.72	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5280MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\27
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3857.700	50.77	31.52	-40.91	41.38	74.00	32.62	PK	Vertical
2	4998.400	51.15	33.89	-39.45	45.59	74.00	28.41	PK	Vertical
3	7293.400	50.22	37.71	-39.65	48.28	74.00	25.72	PK	Vertical
4	8083.900	50.53	37.90	-38.77	49.66	74.00	24.34	PK	Vertical
5	11021.500	46.17	39.70	-35.85	50.02	74.00	23.98	PK	Vertical
6	11997.300	45.55	39.79	-35.25	50.09	74.00	23.91	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7293.400	39.83	37.71	-39.65	37.89	54.00	16.11	AV	Vertical
2	8083.900	38.30	37.90	-38.77	37.43	54.00	16.57	AV	Vertical
3	11021.500	37.14	39.70	-35.85	40.99	54.00	13.01	AV	Vertical
4	11997.300	34.22	39.79	-35.25	38.76	54.00	15.24	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5320MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\28
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4003.900	50.97	31.60	-41.28	41.29	74.00	32.71	PK	Horizontal
2	4879.400	52.21	33.46	-39.58	46.09	74.00	27.91	PK	Horizontal
3	7415.800	49.04	37.17	-39.07	47.14	74.00	26.86	PK	Horizontal
4	8174.000	49.40	37.90	-38.23	49.07	74.00	24.93	PK	Horizontal
5	10645.800	50.01	39.89	-36.26	53.64	74.00	20.36	PK	Horizontal
6	11988.800	45.67	39.78	-35.31	50.14	74.00	23.86	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8174.000	38.63	37.90	-38.23	38.30	54.00	15.70	AV	Horizontal
2	10645.800	39.94	39.89	-36.26	43.57	54.00	10.43	AV	Horizontal
3	11988.800	35.24	39.78	-35.31	39.71	54.00	14.29	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5320MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\29
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4347.300	49.27	32.29	-40.84	40.72	74.00	33.28	PK	Vertical
2	4872.600	51.36	33.45	-39.59	45.22	74.00	28.78	PK	Vertical
3	7308.700	49.29	37.65	-39.53	47.41	74.00	26.59	PK	Vertical
4	8145.100	48.09	37.90	-38.36	47.63	74.00	26.37	PK	Vertical
5	10645.800	59.64	39.89	-36.26	63.27	74.00	10.73	PK	Vertical
6	11990.500	45.92	39.78	-35.30	50.40	74.00	23.60	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10645.800	45.90	39.89	-36.26	49.53	54.00	4.47	AV	Vertical
2	10645.810	44.89	39.89	-36.26	48.52	54.00	5.48	AV	Vertical
3	11990.500	35.59	39.78	-35.30	40.07	54.00	13.93	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5500MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\30
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4083.800	50.56	31.60	-40.86	41.30	74.00	32.70	PK	Horizontal
2	5025.600	51.23	33.95	-39.41	45.77	74.00	28.23	PK	Horizontal
3	7432.800	49.56	37.13	-39.12	47.57	74.00	26.43	PK	Horizontal
4	8379.700	49.60	38.06	-39.28	48.38	74.00	25.62	PK	Horizontal
5	10746.100	47.21	40.00	-35.81	51.40	74.00	22.60	PK	Horizontal
6	12107.800	45.07	39.90	-35.40	49.57	74.00	24.43	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8379.700	38.12	38.06	-39.28	36.90	54.00	17.10	AV	Horizontal
2	10746.100	34.91	40.00	-35.81	39.10	54.00	14.90	AV	Horizontal
3	12107.800	34.75	39.90	-35.40	39.25	54.00	14.75	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5500MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\31
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4102.500	50.43	31.61	-40.79	41.25	74.00	32.75	PK	Vertical
2	4899.800	52.25	33.50	-39.56	46.19	74.00	27.81	PK	Vertical
3	7448.100	49.72	37.10	-39.17	47.65	74.00	26.35	PK	Vertical
4	8111.100	48.01	37.90	-38.51	47.40	74.00	26.60	PK	Vertical
5	11001.100	48.40	39.70	-35.91	52.19	74.00	21.81	PK	Vertical
6	11993.900	45.83	39.79	-35.28	50.34	74.00	23.66	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11001.010	42.89	39.70	-35.91	46.68	54.00	7.32	AV	Vertical
2	11993.900	34.04	39.79	-35.28	38.55	54.00	15.45	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5580MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\32
Memo: Sample Number: S26072701-001

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3896.800	50.59	31.59	-40.76	41.42	74.00	32.58	PK	Horizontal
2	5003.500	51.21	33.91	-39.44	45.68	74.00	28.32	PK	Horizontal
3	7417.500	49.18	37.17	-39.07	47.28	74.00	26.72	PK	Horizontal
4	8172.300	48.19	37.90	-38.24	47.85	74.00	26.15	PK	Horizontal
5	10807.300	45.97	39.99	-35.53	50.43	74.00	23.57	PK	Horizontal
6	11591.000	45.50	39.62	-35.39	49.73	74.00	24.27	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10807.300	36.53	39.99	-35.53	40.99	54.00	13.01	AV	Horizontal
2	11591.000	34.87	39.62	-35.39	39.10	54.00	14.90	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5580MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\33
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4100.800	50.07	31.60	-40.78	40.89	74.00	33.11	PK	Vertical
2	4899.800	51.79	33.50	-39.56	45.73	74.00	28.27	PK	Vertical
3	7310.400	49.27	37.64	-39.52	47.39	74.00	26.61	PK	Vertical
4	8126.400	48.54	37.90	-38.44	48.00	74.00	26.00	PK	Vertical
5	11162.600	48.84	39.83	-35.64	53.03	74.00	20.97	PK	Vertical
6	12114.600	44.63	39.90	-35.43	49.10	74.00	24.90	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	11162.600	38.93	39.83	-35.64	43.12	54.00	10.88	AV	Vertical
2	12114.600	34.23	39.90	-35.43	38.70	54.00	15.30	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5700MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\34
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3978.400	50.37	31.64	-41.18	40.83	74.00	33.17	PK	Horizontal
2	5010.300	51.32	33.92	-39.43	45.81	74.00	28.19	PK	Horizontal
3	7414.100	49.76	37.17	-39.06	47.87	74.00	26.13	PK	Horizontal
4	8238.600	48.15	37.90	-38.51	47.54	74.00	26.46	PK	Horizontal
5	10943.300	46.83	39.81	-35.77	50.87	74.00	23.13	PK	Horizontal
6	12248.900	45.78	39.85	-35.74	49.89	74.00	24.11	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	10943.300	36.09	39.81	-35.77	40.13	54.00	13.87	AV	Horizontal
2	12248.900	36.11	39.85	-35.74	40.22	54.00	13.78	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5700MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\35
Memo: Sample Number: S26072701-001

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3871.300	51.27	31.54	-40.86	41.95	74.00	32.05	PK	Vertical
2	5013.700	52.16	33.93	-39.43	46.66	74.00	27.34	PK	Vertical
3	7284.900	49.04	37.73	-39.73	47.04	74.00	26.96	PK	Vertical
4	8121.300	48.92	37.90	-38.47	48.35	74.00	25.65	PK	Vertical
5	10980.700	46.45	39.74	-35.86	50.33	74.00	23.67	PK	Vertical
6	11630.100	46.04	39.57	-35.61	50.00	74.00	24.00	PK	Vertical

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8121.300	37.71	37.90	-38.47	37.14	54.00	16.86	AV	Vertical
2	10980.700	34.65	39.74	-35.86	38.53	54.00	15.47	AV	Vertical
3	11630.100	36.16	39.57	-35.61	40.12	54.00	13.88	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5720MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\36
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3861.100	51.17	31.52	-40.89	41.80	74.00	32.20	PK	Horizontal
2	5017.100	51.37	33.93	-39.42	45.88	74.00	28.12	PK	Horizontal
3	7291.700	48.97	37.72	-39.66	47.03	74.00	26.97	PK	Horizontal
4	8106.000	49.07	37.90	-38.53	48.44	74.00	25.56	PK	Horizontal
5	10839.600	46.01	39.96	-35.58	50.39	74.00	23.61	PK	Horizontal
6	11159.200	46.38	39.82	-35.64	50.56	74.00	23.44	PK	Horizontal

Final Data List


NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	8106.000	38.70	37.90	-38.53	38.07	54.00	15.93	AV	Horizontal
2	10839.600	35.45	39.96	-35.58	39.83	54.00	14.17	AV	Horizontal
3	11159.200	35.92	39.82	-35.64	40.10	54.00	13.90	AV	Horizontal

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2026-08-04 **Tested By:** Liang Rijing
Test Mode: TX MIMO N20 5720MHz Mode **Power Supply:** DC 5V
Condition: Temp:23.4°C;Humi:48.3% **Test Site:** 4# Fully Anechoic Room
File Path: d:\ts\2026 fcc report date\Q26072701-2E\FCC ABOVE 1G 5G\37
Memo: Sample Number: S26072701-001



Suspected Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4058.300	50.26	31.60	-41.00	40.86	74.00	33.14	PK	Vertical
2	4884.500	51.47	33.47	-39.57	45.37	74.00	28.63	PK	Vertical
3	7310.400	49.96	37.64	-39.52	48.08	74.00	25.92	PK	Vertical
4	8104.300	49.37	37.90	-38.54	48.73	74.00	25.27	PK	Vertical
5	11116.700	46.31	39.73	-35.62	50.42	74.00	23.58	PK	Vertical
6	12378.100	45.57	39.72	-35.57	49.72	74.00	24.28	PK	Vertical

Final Data List

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	7310.400	41.40	37.64	-39.52	39.52	54.00	14.48	AV	Vertical
2	8104.300	38.56	37.90	-38.54	37.92	54.00	16.08	AV	Vertical
3	11116.700	36.58	39.73	-35.62	40.69	54.00	13.31	AV	Vertical
4	12378.100	35.10	39.72	-35.57	39.25	54.00	14.75	AV	Vertical

Note:

1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.